

---

|                  |                                                           |
|------------------|-----------------------------------------------------------|
| Workgroup:       | Network Working Group                                     |
| Internet-Draft:  | draft-wullink-rpp-jscontact-profile-00                    |
| Published:       | 30 April 2026                                             |
| Intended Status: | Standards Track                                           |
| Expires:         | 1 November 2026                                           |
| Authors:         | M. Wullink      P. Kowalik<br><i>SIDN Labs      DENIC</i> |

# JSContact Profile for RESTful Provisioning Protocol (RPP)

---

## Abstract

This document defines the JSContact Profile as defined in [[I-D.ietf-calext-jscontact-profiles](#)] for the [RESTful Provisioning Protocol](#) (RPP). The JSContact Profile for RPP specifies how the JSContact format defined in [[RFC9553](#)] can be used as a standardized representation of contact information within RPP operations, enabling interoperability and consistency across RPP implementations that manage contact data.

## Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on 1 November 2026.

## Copyright Notice

Copyright (c) 2026 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Revised BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Revised BSD License.

# Table of Contents

|                                        |   |
|----------------------------------------|---|
| 1. Introduction                        | 3 |
| 2. Terminology                         | 3 |
| 3. Conventions Used in This Document   | 3 |
| 4. Using JSContact in RPP              | 3 |
| 4.1. JSContact Profile for RPP         | 3 |
| 4.1.1. Kind                            | 3 |
| 4.1.2. Language                        | 3 |
| 4.1.3. Name                            | 3 |
| 4.1.4. Organizations                   | 4 |
| 4.1.5. Addresses                       | 4 |
| 4.1.6. Emails                          | 4 |
| 4.1.7. Phones                          | 4 |
| 4.1.8. Links                           | 4 |
| 4.1.9. Map Keys                        | 4 |
| 4.1.10. Localizations                  | 4 |
| 4.1.11. Profile Properties             | 5 |
| 5. IANA Considerations                 | 7 |
| 5.1. JSContact Profile Registry        | 7 |
| 6. Internationalization Considerations | 7 |
| 7. Security Considerations             | 7 |
| 8. Change History                      | 7 |
| 8.1. Version 00                        | 7 |
| 9. Normative References                | 7 |
| Acknowledgements                       | 7 |
| Authors' Addresses                     | 8 |

## 1. Introduction

TODO: write introduction, motivation, scope, etc.

## 2. Terminology

In this document the following terminology is used.

RESTful Provisioning Protocol or RPP - The protocol described in this document.

URL - A Uniform Resource Locator as defined in [\[RFC3986\]](#).

RPP client - An HTTP user agent performing an RPP request

RPP server - An HTTP server responsible for processing requests and returning results in any supported media type.

## 3. Conventions Used in This Document

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [\[RFC2119\]](#).

## 4. Using JSContact in RPP

### 4.1. JSContact Profile for RPP

Since JSContact is a generalized representation of contact data, many of its capabilities are not optimized for interoperable use in RPP payloads. This document therefore defines a usage profile for JSContact that simplifies implementation for both RPP clients and RPP servers.

The JSContact profile for RPP is compliant with the rules described in [\[I-D.ietf-calex-jscontact-profiles\]](#). The profile properties are formally listed in [Section 4.1.1.1](#). All types mentioned in this section refer to the JSContact specification [\[RFC9553\]](#).

#### 4.1.1.1. Kind

The Card "kind" member value MUST be "individual" (default) or "org" to represent an individual or an organization, respectively.

#### 4.1.1.2. Language

The Card "language" member SHOULD be set when localizations are specified (i.e., when the "localizations" member is present and non-null).

#### 4.1.1.3. Name

The Card "name" member MUST include the "full" member and MAY include the "components" member.

When present, each NameComponent MUST include only the "kind" and "value" members. The "kind" member value MUST be "title", "given" or "surname".

#### 4.1.4. Organizations

The Organization type MUST include only the "org" member.

#### 4.1.5. Addresses

The Address type MUST include at least one of the "full", "components", or "countryCode" members.

When present, each AddressComponent MUST include only the "kind" and "value" members. The "kind" member value MUST be "name", "locality", "region", "postcode", or "country".

#### 4.1.6. Emails

The EmailAddress type MUST include only the "address" member.

#### 4.1.7. Phones

The Phone type MUST include the "number" member and MAY include the "features" member. When the "features" member is present, its values MUST be "voice" or "fax". When the "features" member is absent, the phone number is assumed to be a voice number.

#### 4.1.8. Links

The Link type MUST include the "uri" member and MAY include the "kind" member. When the "kind" member is present, its value MUST be "contact".

#### 4.1.9. Map Keys

Since most JSContact collections are represented as maps, map keys must be defined. A JSContact map key MUST comply with the Id type definition in [\[RFC9553\]](#). To aid interoperability, RPP implementations SHOULD use the following predefined keys:

- "org" in the "organizations" map for a single preferred organization.
- "addr" in the "addresses" map for a single preferred postal address.
- "email" in the "emails" map for the preferred email address.
- "voice" in the "phones" map for the preferred voice number.
- "fax" in the "phones" map for the preferred fax number.
- "url" in the "links" map for a preferred contact URL; the "kind" member of the Link object MUST NOT be set.
- "contact-uri" in the "links" map for a contact URI; the "kind" member of the Link object MUST be set to "contact".

When internationalized and localized versions of an organization, postal address, or email exist, the internationalized version MUST be included under the predefined map key, while the localized version MUST be placed in the "localizations" map as described in [Section 4.1.10](#).

#### 4.1.10. Localizations

A RPP request MUST NOT include a "localizations" member, as RPP clients are not expected to provide localized contact information. However, A RPP response MAY include a "localizations" member to provide localized versions of the contact information.

If present, localized variants of name, organization, postal address, and email MUST be added to the "localizations" map. RPP implementations MUST expand all localizations, meaning a nested PatchObject key of the form "{key1}/{key2}/.../{keyN}" MUST NOT be used.

The following is an elided example of a Card including a localized version of the postal address:

```
{
  "@type": "Card",
  "version": "1.0",
  "language": "en",
  "name": {
    "full": "Joe User"
  },
  "organizations": {
    "org": { "name": "Example Org" }
  },
  "addresses": {
    "addr": {
      "components": [
        { "kind": "name", "value": "Main Street 1" },
        { "kind": "locality", "value": "Ludwigshafen am Rhein" },
        { "kind": "region", "value": "Rhineland-Palatinate" },
        { "kind": "postcode", "value": "67067" },
        { "kind": "country", "value": "Germany" }
      ],
      "countryCode": "DE"
    }
  },
  "localizations": {
    "de": {
      "addresses": {
        "addr": {
          "components": [
            { "kind": "name", "value": "Hauptstraße 1" },
            { "kind": "locality", "value": "Ludwigshafen am Rhein" },
            { "kind": "region", "value": "Rheinland-Pfalz" },
            { "kind": "postcode", "value": "67067" },
            { "kind": "country", "value": "Deutschland" }
          ],
          "countryCode": "DE"
        }
      }
    }
  }
}
```

Figure 1: Example of handling localizations in JSContact

4.1.11. Profile Properties

The properties of the JSContact profile for RPP registered in the JSContact Profile registry as described in [Section 5.1](#) are:

| Property | Context | Restricted | Restricted Enum |

| Attributes |      | Values |  |
|------------|------|--------|--|
| language   | Card |        |  |

| Attributes    |                  | Values                                    |
|---------------|------------------|-------------------------------------------|
| kind          | Card             | individual, org                           |
| name          | Card             |                                           |
| full          | Name             | mandatory                                 |
| components    | Name             |                                           |
| kind          | NameComponent    | title, given, surname                     |
| value         | NameComponent    |                                           |
| organizations | Card             |                                           |
| name          | Organization     |                                           |
| addresses     | Card             |                                           |
| full          | Address          |                                           |
| countryCode   | Address          |                                           |
| components    | Address          |                                           |
| kind          | AddressComponent | name, locality, region, postcode, country |
| value         | AddressComponent |                                           |
| emails        | Card             |                                           |
| address       | EmailAddress     |                                           |
| phones        | Card             |                                           |
| features      | Phone            | voice, fax                                |
| number        | Phone            |                                           |
| links         | Card             |                                           |
| kind          | Link             | contact                                   |
| uri           | Link             |                                           |
| localizations | Card             | yes                                       |

Table 1

Client validation **MUST** return an error if any JSContact properties other than those listed above are present.

## 5. IANA Considerations

### 5.1. JSContact Profile Registry

IANA is requested to register the following entry in the "JSContact Profile" registry [I-D.ietf-calext-jscontact-profiles]:

Name: rpp Profile Version: 1.0 Reference: TODO

TODO

## 6. Internationalization Considerations

TODO

## 7. Security Considerations

TODO

## 8. Change History

### 8.1. Version 00

- Created initial document and added boilerplate sections.

## 9. Normative References

- [I-D.ietf-calext-jscontact-profiles] Stepanek, R. and M. Loffredo, "Protocol-Specific Profiles for JSContact", Work in Progress, Internet-Draft, draft-ietf-calext-jscontact-profiles-14, 17 February 2026, <<https://datatracker.ietf.org/doc/html/draft-ietf-calext-jscontact-profiles-14>>.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC3986] Berners-Lee, T., Fielding, R., and L. Masinter, "Uniform Resource Identifier (URI): Generic Syntax", STD 66, RFC 3986, DOI 10.17487/RFC3986, January 2005, <<https://www.rfc-editor.org/info/rfc3986>>.
- [RFC9553] Stepanek, R. and M. Loffredo, "JSContact: A JSON Representation of Contact Data", RFC 9553, DOI 10.17487/RFC9553, May 2024, <<https://www.rfc-editor.org/info/rfc9553>>.

## Acknowledgements

TODO

## Authors' Addresses

**Maarten Wullink**

SIDN Labs

Email: [maarten.wullink@sidn.nl](mailto:maarten.wullink@sidn.nl)URI: <https://sidn.nl/>**Pawel Kowalik**

DENIC

Email: [pawel.kowalik@denic.de](mailto:pawel.kowalik@denic.de)URI: <https://denic.de/>