


PHP 설치 <pre> root@localhost ~# dnf install -y vsftpd Last metadata expiration check: 1:04:31 ago on Mon Oct 27 12:58:31 2025. Dependencies resolved. ===== Package Architecture Version Repository ===== Installing: vsftpd x86_64 3.0.5-6.el9 appstream Transaction Summary ===== Install 1 Package Total download size: 157 k Installed size: 347 k Downloading Packages: vsftpd-3.0.5-6.el9.x86_64.rpm 830 kB/s 157 kB 00:0 ----- Total 199 kB/s 157 kB 00:0 Running transaction check Transaction check succeeded. Running transaction test Transaction test succeeded. Running transaction Preparing : Installing : vsftpd-3.0.5-6.el9.x86_64 Running scriptlet: vsftpd-3.0.5-6.el9.x86_64 Verifying : vsftpd-3.0.5-6.el9.x86_64 Installed: vsftpd-3.0.5-6.el9.x86_64 Complete! </pre>	<pre> root@localhost ~# systemctl enable --now vsftpd systemctl status vsftpd Created symlink /etc/systemd/system/multi-user.target.wants/vsftpd.service - /usr/lib/s /system/vsftpd.service. Loaded: loaded (/usr/lib/systemd/system/vsftpd.service; enabled; preset: disabled) Active: active (running) since Mon 2025-10-27 14:04:05 KST; 11ms ago Process: 5813 ExecStart=/usr/sbin/vsftpd /etc/vsftpd/vsftpd.conf (code=exited, stat Main PID: 5814 (vsftpd) Tasks: 1 (limit: 22915) Memory: 740.0K CPU: 3ms CGroup: /system.slice/vsftpd.service └─5814 /usr/sbin/vsftpd /etc/vsftpd/vsftpd.conf Oct 27 14:04:05 localhost.localdomain systemd[1]: Starting Vsftpd ftp daemon... Oct 27 14:04:05 localhost.localdomain systemd[1]: Started Vsftpd ftp daemon. </pre>
dnf install -y vsftpd 설치	systemctl enable --now vsftpd systemctl status vsftpd 정상상태 =active(running)
Example config file /etc/vsftpd/vsftpd.conf <pre> # The default compiled in settings are fairly paranoid. This sample file # loosens things up a bit, to make the ftp daemon more usable. # Please see vsftpd.conf.5 for all compiled in defaults. # # READ THIS: This example file is NOT an exhaustive list of vsftpd options. # Please read the vsftpd.conf.5 manual page to get a full idea of vsftpd's # capabilities. # # Allow anonymous FTP? (Beware - allowed by default if you comment this out). anonymous_enable=NO # # Uncomment this to allow local users to log in. local_enable=YES # # Uncomment this to enable any form of FTP write command. write_enable=YES # # Default umask for local users is 077. You may wish to change this to 022, # if your users expect that (022 is used by most other ftp'd's) local_umask=022 # # Uncomment this to allow the anonymous FTP user to upload files. This only # has an effect if the above global write enable is activated. Also, you will # obviously need to create a directory writable by the FTP user. # When SELinux is enforcing check for SE bool allow_ftp_anon_write, allow_ftp anon_upload_enable=YES # # Uncomment this if you want the anonymous FTP user to be able to create # new directories anon_mkdir_write_enable=YES # # Activate directory messages - messages given to remote users when they # go into a certain directory. dirmessage_enable=YES # # Activate logging of uploads/downloads. xferlog_enable=YES # # Make sure PORT transfer connections originate from port 20 (ftp-data). connect_from_port_20=YES # # If you want, you can arrange for uploaded anonymous files to be owned by # a different user. Note! Using "root" for uploaded files is not # recommended! #chown_uploads=YES #chown_username=noever # # You may override where the log file goes if you like. The default is shown </pre>	- anonymous_enable=NO → 익명 접속 금지 - local_enable=YES → 로컬 사용자 로그인 허용 - write_enable=YES → 파일 업로드/수정 가능 - chroot_local_user=YES → 사용자 홈 디렉터리 제한 - allow_writeable_chroot=YES → chroot 시 쓰기 가능
vim /etc/vsftpd/vsftpd.conf 여기까지 php 설치	systemctl restart vsftpd 서비스 재시작 여기까지 php 설치
<pre> root@localhost ~# uname -a Linux localhost.localdomain 5.14.0-503.14.1.el9_5.x86_64 #1 SMP PREEMPT_DYNAMIC Fri Nov 15 12:04:32 UTC 2024 x86_64 x86_64 GNU/Linux root@localhost ~# cat /etc/os-release NAME="Rocky Linux" VERSION="9.6 (Blue Onyx)" ID="rocky" ID_LIKE="rhel centos fedora" VERSION_ID="9.6" PLATFORM_ID="platform:el9" PRETTY_NAME="Rocky Linux 9.6 (Blue Onyx)" ANSI_COLOR="0;32" LOGO="fedora-logo-icon" CPE_NAME="cpe:/o:rocky:rocky:9::baseos" HOME_URL="https://rockylinux.org/" VENDOR_NAME="RESF" VENDOR_URL="https://resf.org/" BUG_REPORT_URL="https://bugs.rockylinux.org/" SUPPORT_END="2032-05-31" ROCKY_SUPPORT_PRODUCT="Rocky Linux 9" ROCKY_SUPPORT_PRODUCT_VERSION="9.6" REDHAT_SUPPORT_PRODUCT="Rocky Linux" REDHAT_SUPPORT_PRODUCT_VERSION="9.6" </pre>	<pre> Running transaction check Transaction check succeeded. Running transaction test Transaction test succeeded. Running transaction Preparing : apr-1.7.0-12.el9_3.x86_64 1/11 Installing : apr-util-openssl-1.0.1-23.el9.x86_64 2/11 Installing : apr-util-1.0.1-23.el9.x86_64 3/11 Installing : apr-util-bdb-1.0.1-23.el9.x86_64 4/11 Installing : httpd-tools-2.4.62-4.el9_6.4.x86_64 5/11 Installing : rocky-logos-httpd-90.16.1.el9.noarch 6/11 Installing : mailcap-2.1.49-5.el9.noarch 7/11 Installing : httpd-core-2.4.62-4.el9_6.4.x86_64 8/11 Installing : mod_lua-2.4.62-4.el9_6.4.x86_64 9/11 Installing : httpd-2.4.62-4.el9_6.4.x86_64 10/11 Running scriptlet: httpd-2.4.62-4.el9_6.4.x86_64 11/11 Running scriptlet: mod_http2-2.0.26-4.el9_6.1.x86_64 12/11 Verifying : mailcap-2.1.49-5.el9.noarch 1/11 Verifying : apr-util-bdb-1.0.1-23.el9.x86_64 2/11 Verifying : httpd-tools-2.4.62-4.el9_6.4.x86_64 3/11 Verifying : httpd-2.4.62-4.el9_6.4.x86_64 4/11 Verifying : apr-util-1.0.1-23.el9.x86_64 5/11 Verifying : rocky-logos-httpd-90.16.1.el9.noarch 6/11 Verifying : httpd-core-2.4.62-4.el9_6.4.x86_64 7/11 Verifying : mod_lua-2.4.62-4.el9_6.4.x86_64 8/11 Verifying : mod_http2-2.0.26-4.el9_6.1.x86_64 9/11 Verifying : apr-util-openssl-1.0.1-23.el9.x86_64 10/11 Verifying : apr-1.7.0-12.el9_3.x86_64 11/11 Installed: apr-1.7.0-12.el9_3.x86_64 apr-util-1.0.1-23.el9.x86_64 apr-util-bdb-1.0.1-23.el9.x86_64 apr-util-openssl-1.0.1-23.el9.x86_64 httpd-2.4.62-4.el9_6.4.x86_64 httpd-core-2.4.62-4.el9_6.4.x86_64 httpd-tools-2.4.62-4.el9_6.4.x86_64 mailcap-2.1.49-5.el9.noarch mod_http2-2.0.26-4.el9_6.1.x86_64 mod_lua-2.4.62-4.el9_6.4.x86_64 rocky-logos-httpd-90.16.1.el9.noarch Complete! </pre>
uname -a 커널이름, 호스트이름, 운영체제 확인 명령어 cat /etc/os-release 배포판 정보 확인	dnf -y install httpd
<pre> root@localhost ~# systemctl restart httpd root@localhost ~# systemctl status httpd ● httpd.service - The Apache HTTP Server Loaded: loaded (/usr/lib/systemd/system/httpd.service; disabled; preset: disabled) Drop-In: /etc/systemd/system/httpd.service.d -php-fpm.conf Active: active (running) since Thu 2025-10-23 15:53:14 KST; 11s ago Docs: man:httpd.service(8) Main PID: 65238 (httpd) Status: "Total requests: 0; Idle/Busy workers 100/0;Requests/sec: 0; Bytes served/sec: 0" Tasks: 177 (limit: 22932) Memory: 22.0M CPU: 111ms CGroup: /system.slice/httpd.service └─65235 /usr/sbin/httpd -DFOREGROUND └─65237 /usr/sbin/httpd -DFOREGROUND └─65238 /usr/sbin/httpd -DFOREGROUND └─65239 /usr/sbin/httpd -DFOREGROUND └─65240 /usr/sbin/httpd -DFOREGROUND </pre>	← → ↻ 🌐 📄 172.16.77 ☆ 🔍 ⋮ HTTP Server Test Page This page is used to test the proper operation of an HTTP server after it has been installed on a Rocky Linux system. If you can read this page, it means that the software is working correctly.

systemctl restart httpd systemctl status httpd	인터넷창에 http://172.16.77:80 실행결과
<pre>[root@localhost ~]# cd /var/www/html [root@localhost html]# echo "ㅇㅇㅇ" > index.html [root@localhost html]# ls index.html</pre>	
cd /var/www/html 디렉터리 이동 index.html 파일생 -> ls 파일생성 확인	설정후 바뀐 모습
<pre># Note that from this point forward you must specifically allow # particular features to be enabled - so if something's not working as # you might expect, make sure that you have specifically enabled it # here. # # DocumentRoot: The directory out of which you will serve your # documents. By default, all requests are taken from this directory, but # symbolic links and aliases may be used to point to other locations. # # DocumentRoot "/home/ktt" # # Relax access to content within /var/www. # # <Directory "/var/www"> # AllowOverride None # # Require all granted # </Directory> # # Further relax access to the default document root: # # <Directory "/home/ktt"> # # Possible values for the Options directive are "None", "All", # or any combination of: # Indexes FollowSymLinks SymLinksIfOwnerMatch ExecCGI MultiViews # Indexes includes FollowSymLinks SymLinksIfOwnerMatch ExecCGI MultiViews # Note that "MultiViews" must be named "explicitly" --- "Options All" # Doesn't give it to you. # The Options directive is both complicated and important. Please see # http://httpd.apache.org/docs/2.2/mod/core.html#options # for more information. # Options Indexes FollowSymLinks # # AllowOverride controls what directives may be placed in .htaccess files. # It can be "All", "None", or any combination of the keywords: # # Options FileInfo AuthConfig Limit # AllowOverride None # # </Directory></pre>	
vim /etc/httpd/conf/httpd.conf gogo esc :set nu 입력하면 줄 넘버 표기됨	Listen 81 추가 해주기
<pre>124 DocumentRoot "/home/ktt" 125 126 # 127 # Relax access to content within /var/www. 128 # 129 <Directory "/var/www"> 130 AllowOverride None 131 # Allow open access: 132 Require all granted 133 </Directory> 134 135 # Further relax access to the default document root: 136 <Directory "/home/ktt"></pre>	
124번째 136번째줄 <Directory "/home/본인 계정명"	