

Virtual Host 매뉴얼

<pre>Last login: Wed Oct 22 14:55:24 2025 [root@localhost ~]# cd /home/ [root@localhost home]# ls yw [root@localhost home]# useradd -m test [root@localhost home]# ls test yw [root@localhost home]# passwd test Changing password for user test. New password:</pre> <pre>New password: BAD PASSWORD: The password fails the dictionary check - it is based on a dictionary word Retype new password: passwd: all authentication tokens updated successfully.</pre>	1. 새로운 계정을 만든다. <pre>[root@localhost ~]# cd /home/ [root@localhost home]# ls yw [root@localhost home]# useradd -m test (m = make) [root@localhost home]# ls test yw [root@localhost home]# [root@localhost home]# passwd test Changing password for user test. New password:</pre> **설정된 PW : asd123!@ "BAD PASSWORD: The password fails the dictionary check - it is based on a dictionary word" 설정된 비밀번호가 단순할 때 나타난다. 단순한 경고 문구이므로 똑같이 재입력하면 완료된다.
<pre>[root@localhost home]# chmod 777 test [root@localhost home]# ls -l total 0 drwxrwxrwx. 2 test test 62 Oct 22 14:55 test drwxrwxrwx. 2 yw yw 99 Sep 11 17:34 yw [root@localhost home]#</pre>	2. test 계정의 권한 설정 <pre>[root@localhost home]# chmod 777 test [root@localhost home]# ls -l total 0 drwxrwxrwx. 2 test test 62 Sep 17 14:13 test drwxrwxrwx. 2 yw yw 110 Sep 12 15:03 yw (drwx/rwx/rwx 유저/그룹/아더) [root@localhost home]#</pre>

<pre>[root@localhost home]# cd /etc/httpd/conf.d [root@localhost conf.d]# vim /etc/httpd/conf/httpd.conf</pre> <pre>41 # Change this to Listen on a specific IP address, but not 42 # httpd.service is enabled to run at boot time, the addre 43 # available when the service starts. See the httpd.servi 44 # page for more information. 45 # 46 #Listen 12.34.56.78:80 47 Listen 80 48 Listen 81 49 50 # 51 # Dynamic Shared Object (DSO) Support 52 #</pre>	4. 포트 생성하기 <pre>[root@localhostconf.d]# vim /etc/httpd/conf/httpd.conf</pre> > Listen 81 추가
선생님이 주신 소스로 포트별로 사용할 계정을 바꿔 입력해 둔다.	<pre><VirtualHost *:80> DocumentRoot "/home/yw" <Directory "/home/yw/"> AllowOverride None Options Indexes FollowSymLinks Require all granted </Directory> </VirtualHost> <VirtualHost *:81> DocumentRoot "/home/test" <Directory "/home/test/"> AllowOverride None Options Indexes FollowSymLinks Require all granted </Directory> </VirtualHost></pre>
<pre>[root@localhost conf.d]# ls README autoindex.conf userdir.conf welcome.conf [root@localhost conf.d]# vim vhost.conf [root@localhost conf.d]#</pre> <pre><VirtualHost *:80> DocumentRoot "/home/yw" <Directory "/home/yw/"> AllowOverride None Options Indexes FollowSymLinks Require all granted </Directory> </VirtualHost> <VirtualHost *:81> DocumentRoot "/home/test" <Directory "/home/test/"> AllowOverride None Options Indexes FollowSymLinks Require all granted </Directory> </VirtualHost></pre>	5. 파일을 만들고 소스 넣기 <pre>[root@localhost conf.d]# ls README autoindex.conf userdir.conf welcome.conf</pre> <pre>[root@localhost conf.d]# vim vhost.conf (파일명은 자유)</pre> ls -> 생성된 vhost.conf 확인

```

[root@localhost conf.d]# systemctl restart httpd
[root@localhost conf.d]# systemctl status httpd
● httpd.service - The Apache HTTP Server
   Loaded: loaded (/usr/lib/systemd/system/httpd.service; disabled; preset: disabled)
   Active: active (running) since Wed 2025-10-22 15:26:24 KST; 7s ago
     Docs: man:httpd.service(8)
   Main PID: 12100 (httpd)
   Status: "Started, listening on: port 81, port 80"
   Tasks: 177 (limit: 22916)
  Memory: 30.6M
    CPU: 73ms
   CGroup: /system.slice/httpd.service
           └─12100 /usr/sbin/httpd -DFOREGROUND
              └─12101 /usr/sbin/httpd -DFOREGROUND
                 └─12102 /usr/sbin/httpd -DFOREGROUND
                    └─12103 /usr/sbin/httpd -DFOREGROUND
                       └─12104 /usr/sbin/httpd -DFOREGROUND

Oct 22 15:26:24 localhost.localdomain systemd[1]: Starting The Apache HTTP Server...
Oct 22 15:26:24 localhost.localdomain httpd[12100]: AH00558: httpd: Could not reliably determine
Oct 22 15:26:24 localhost.localdomain httpd[12100]: Server configured, listening on: port 81, p
Oct 22 15:26:24 localhost.localdomain systemd[1]: Started The Apache HTTP Server.
lines 1-20/20 (END)

```

6. httpd 서비스 실행하여 포트별 홈페이지 생성

```

[root@localhost conf.d]# systemctl restart httpd
[root@localhost conf.d]# systemctl status httpd

```

브라우저 > IP:80 / IP:81 로 접속 가능

