

Ubuntu에서 monitoriX 설치 및 설정 메뉴얼

과정

설명

```
root@root:~# apt update
Hit:1 http://kr.archive.ubuntu.com/ubuntu plucky InRelease
Get:2 http://kr.archive.ubuntu.com/ubuntu plucky-updates InRelease [126 kB]
Get:3 http://kr.archive.ubuntu.com/ubuntu plucky-backports InRelease [126 kB]
Get:4 http://kr.archive.ubuntu.com/ubuntu plucky-updates/main amd64 Packages [382 kB]
Get:5 http://kr.archive.ubuntu.com/ubuntu plucky-updates/main amd64 Components [58.5 k
B]
root@root:~# apt install apache2 -y
apache2 is already the newest version (2.4.63-1ubuntu1.1).
The following packages were automatically installed and are no longer required:
  libmecab2 libprotobuf-lite32t64 mecab-ipadic mecab-ipadic-utf8 mecab-utils
Use 'apt autoremove' to remove them.

Summary:
  Upgrading: 0, Installing: 0, Removing: 0, Not Upgrading: 15
root@root:~# apt install monitorix -y
The following packages were automatically installed and are no longer required:
  libmecab2 libprotobuf-lite32t64 mecab-ipadic mecab-ipadic-utf8 mecab-utils
Use 'apt autoremove' to remove them.

Installing:
  monitorix

Installing dependencies:
  libconfig-general-perl  libmime-lite-perl  libxml-simple-perl
  libdbi1t64              libmime-types-perl  net-tools
  libemail-date-format-perl  librrd8t64         rrdtool
  libhttp-server-simple-perl  librrds-perl
```

1. 필수 패키지 설치

명령어 : apt update

apt install apache2 -y

Apache 웹 서버 설치

apt install monitorix -y

monitoriX와 필수 Perl 모듈 설치

```
<httpd_builtin>
  enabled = y
  host =
  port = 8080
  user = nobody
  group = nobody
  log_file = /var/log/monitorix-httpd
  hosts_deny =
  hosts_allow =
  autocheck_responsiveness = y
</auth>
  enabled = n
  hosts_deny = all
  msg = Monitorix: Restricted access
  htpasswd = /var/lib/monitorix/htpasswd
</auth>
</httpd_builtin>
```

2. monitoriX 설정 파일 수정 (선택 사항)

포트 변경과 모니터링할 항목 수정하려면...

명령어 : vim /etc/monitorix/monitorix.conf

기본 포트(8080) 말고 다른 포트 사용할시 httpd_user 섹션 아래의 port 값을 수정

```
root@root:~# systemctl start monitorix
root@root:~# systemctl enable monitorix
Synchronizing state of monitorix.service with SysV service script with /usr/lib/system
d/systemd-sysv-install.
Executing: /usr/lib/systemd/systemd-sysv-install enable monitorix
root@root:~# systemctl status monitorix
● monitorix.service - Monitorix
   Loaded: loaded (/usr/lib/systemd/system/monitorix.service; enabled; preset: enab
   Active: active (running) since Thu 2025-10-23 02:27:25 UTC; 5min ago
   Invocation: b29a769fa93a476ab832b62d277bb110
     Docs: man:monitorix(8)
    Main PID: 263973 (/usr/bin/monitorix)
       Tasks: 2 (limit: 3913)
      Memory: 78.2M (peak: 94.1M)
         CPU: 1.221s
        CGroup: /system.slice/monitorix.service
                └─263973 /usr/bin/monitorix -c /etc/monitorix/monitorix.conf -p /run/monit
                  264051 "monitorix-httpd listening on 8080"

Oct 23 02:27:25 root systemd[1]: Starting monitorix.service - Monitorix...
Oct 23 02:27:25 root systemd[1]: Started monitorix.service - Monitorix.
lines 1-15/15 (END)
```

3. 서비스 시작 및 활성화

명령어 : systemctl start monitorix

systemctl enable monitorix

systemctl status monitorix

```
root@root:~# ufw allow 8080/tcp
Rules updated
Rules updated (v6)
root@root:~# ufw reload
Firewall not enabled (skipping reload)
root@root:~#
```

4. 방화벽 설정 (UFW)

명령어 : ufw allow 8080/tcp

ufw reload



5. 웹 접속

웹 브라우저에서 다음 주소로 접속합니다:
http://[Ubuntu 서버 IP 주소]:8080/monitorix