

Ubuntu web-server 매뉴얼(html+php)

1. 아파치 서버 설치

1) 방화벽 해제

: 우분투는 selinux, firewalld 안쓰고 ufw이므로 ufw를 해제

- sudo systemctl status ufw : 현재 방화벽 확인
- sudo systemctl stop ufw : 방화벽 끄기

```
root@ubuntu21:~# sudo systemctl stop ufw
root@ubuntu21:~# sudo systemctl status ufw
○ ufw.service - Uncomplicated firewall
   Loaded: loaded (/usr/lib/systemd/system/ufw.service; disabled; preset: enabled)
   Active: inactive (dead)
     Docs: man:ufw(8)

Sep 23 08:40:10 ubuntu21 systemd[1]: Starting ufw.service - Uncomplicated firewall...
Sep 23 08:40:10 ubuntu21 systemd[1]: Finished ufw.service - Uncomplicated firewall.
Sep 24 07:06:23 ubuntu21 systemd[1]: Stopping ufw.service - Uncomplicated firewall...
Sep 24 07:06:23 ubuntu21 ufw-init[5257]: Skip stopping firewall: ufw (not enabled)
Sep 24 07:06:23 ubuntu21 systemd[1]: ufw.service: Deactivated successfully.
Sep 24 07:06:23 ubuntu21 systemd[1]: Stopped ufw.service - Uncomplicated firewall.
root@ubuntu21:~#
```

2) 서버 설치를 위해 리포지터리(생략) 및 apache2 설치

리눅스는 epel-release / remi-release 리포지터리를 깔고, 서비스 httpd를 설치했지만,
데비안은 기본 Apache 설치시에는 추가 리포지터리 필요가 없고, 서비스명이 apache2

- sudo apt update
- sudo apt install apache2
- systemctl status apache2 로 상태 확인

```
root@ubuntu21:~# sudo apt update
Hit:1 http://kr.archive.ubuntu.com/ubuntu plucky InRelease
Hit:2 http://kr.archive.ubuntu.com/ubuntu plucky-updates InRelease
Hit:3 http://kr.archive.ubuntu.com/ubuntu plucky-backports InRelease
Hit:4 http://security.ubuntu.com/ubuntu plucky-security InRelease
38 packages can be upgraded. Run 'apt list --upgradable' to see them.
root@ubuntu21:~# sudo apt install apache2
apache2 is already the newest version (2.4.63-1ubuntu1.1).
Summary:
  Upgrading: 0, Installing: 0, Removing: 0, Not Upgrading: 38
root@ubuntu21:~#
```

3) 설정파일 경로

- 아파치 서비스 설정파일(apache2.conf 있는 곳) : /etc/apache2
- 홈페이지 홈디렉터리(index.html 있는 곳) 변경:
Directory "/var/www/" => "/home/hj" 로 변경

```
<Directory /var/www/>
    Options Indexes FollowSymLinks
    AllowOverride None
    Require all granted
</Directory>
```

- conf파일 설정

/etc/apache2/sites-available/000-default.conf 이게 적용되는 설정파일임(수정)

```
root@ubuntu21:/etc/apache2/sites-available# ls
000-default.conf  default-ssl.conf
root@ubuntu21:/etc/apache2/sites-available# vim 000-default.conf
root@ubuntu21:/etc/apache2/sites-available# systemctl reload apache2
```

```
<VirtualHost *:80>
    # The ServerName directive sets the request scheme, hostname and port that
    # the server uses to identify itself. This is used when creating
    # redirection URLs. In the context of virtual hosts, the ServerName
    # specifies what hostname must appear in the request's Host: header to
    # match this virtual host. For the default virtual host (this file) this
    # value is not decisive as it is used as a last resort host regardless.
    # However, you must set it for any further virtual host explicitly.
    #ServerName www.example.com

    ServerAdmin webmaster@localhost

    DocumentRoot /home/hj

    <Directory /home/hj>
        Options Indexes FollowSymLinks
        AllowOverride None
        Require all granted
    </Directory>

    # Available loglevels: trace8, ..., trace1, debug, info, notice, warn,
    # error, crit, alert, emerg.
    # It is also possible to configure the loglevel for particular
    # modules, e.g.
    #LogLevel info ssl:warn

    ErrorLog ${APACHE_LOG_DIR}/error.log
    CustomLog ${APACHE_LOG_DIR}/access.log combined

    # For most configuration files from conf-available/, which are
    # enabled or disabled at a global level, it is possible to
    # include a line for only one particular virtual host. For example the
    # following line enables the CGI configuration for this host only
    # after it has been globally disabled with "a2disconf".
    #Include conf-available/serve-cgi-bin.conf
</VirtualHost>
~
~
~
```

=> 여기 원래 DocumentRoot랑 Directory부분 빠져있는데 넣어줘야함!!!

```
DocumentRoot /home/hj
<Directory /home/hj>
    Options Indexes FollowSymLinks
    AllowOverride None
    Require all granted
</Directory>
```

이제 vhost를 위해서 저거 000.default.conf파일을 복사해서 vhost.conf 따로 생성

※원래는 vhost하나로 하지 않고 각각 vhost마다 conf파일을 만드는 것이 관리에 용이

```
root@ubuntu21:/etc/apache2/sites-available# cp -ap 000-default.conf vhost.conf
```

그리고 위의 sites-available에 있던 conf파일의 링크가 /etc/apache2/sites-enabled에 생겨있어. 그러면 이제 두 디렉토리에 있는건 동기화 되는 것!

2. PHP 설치

1) 리포지터리 설치

```
sudo apt install software-properties-common
```

```
sudo apt install dpkg
```

2) php설치

```
sudo add-apt-repository ppa:ondrej/php
```

```
sudo apt update
```

```
sudo apt install php
```

3) 확인하기

– PHP 모듈 설치 확인

```
sudo apt install libapache2-mod-php8.4
```

```
root@ubuntu21:/home# sudo apt install libapache2-mod-php8.4
libapache2-mod-php8.4 is already the newest version (8.4.5-1ubuntu1.1).
libapache2-mod-php8.4 set to manually installed.
Summary:
  Upgrading: 0, Installing: 0, Removing: 0, Not Upgrading: 2
root@ubuntu21:/home#
```

– Apache PHP 모듈 활성화

```
– sudo a2enmod php8.4
```

```
– sudo systemctl restart apache2
```

```
root@ubuntu21:/home# sudo a2enmod php8.4
sudo systemctl restart apache2
Considering dependency mpm_prefork for php8.4:
Considering conflict mpm_event for mpm_prefork:
Considering conflict mpm_worker for mpm_prefork:
Module mpm_prefork already enabled
Considering conflict php5 for php8.4:
Module php8.4 already enabled
root@ubuntu21:/home#
```

----- Ip설정팁 -----

```
sudo ifconfig enp3s0f0 172.16.0.2 netmask 255.255.0.0 up
```

```
sudo route add default gw 172.16.0.1 enp3s0f0
```

```
echo "nameserver 8.8.8.8" | sudo tee /etc/resolv.conf
```

```
sudo nmcli con mod enp3s0f0 ipv4.addresses 172.16.0.2/16
```

```
sudo nmcli con mod enp3s0f0 ipv4.method manual
```

```
sudo nmcli con up enp3s0f0
```

```
sudo nmcli con mod enp3s0f0 ipv4.gateway 172.16.0.1
```

```
sudo nmcli con up enp3s0f0
```