

Ubuntu에서 MariaDB 설치 메뉴얼

우분투 환경

설명

```

root@root:~# apt update -y
Hit:1 http://kr.archive.ubuntu.com/ubuntu plucky InRelease
Hit:2 http://kr.archive.ubuntu.com/ubuntu plucky-updates InRelease
Hit:3 http://kr.archive.ubuntu.com/ubuntu plucky-backports InRelease
Get:4 http://security.ubuntu.com/ubuntu plucky-security InRelease [126 kB]
Get:5 http://security.ubuntu.com/ubuntu plucky-security/main amd64 Components [16.5 kB]
Get:6 http://security.ubuntu.com/ubuntu plucky-security/restricted amd64 Components [12 B]
Get:7 http://security.ubuntu.com/ubuntu plucky-security/universe amd64 Components [3,680 B]
Get:8 http://security.ubuntu.com/ubuntu plucky-security/multiverse amd64 Components [12 B]
Fetched 147 kB in 2s (96.7 kB/s)
10 packages can be upgraded. Run 'apt list --upgradable' to see them.
root@root:~# apt install mariadb-server -y
The following packages were automatically installed and are no longer required:
  libmecab2 libprotobuf-lite32t64 mecab-ipadic mecab-ipadic-utf8 mecab-utils
Use 'apt autoremove' to remove them.

Installing:
  mariadb-server

Installing dependencies:
  galera-4 mariadb-plugin-provider-bzip2
  libconfig-inifiles-perl mariadb-plugin-provider-lz4
  libdbd-mariadb-perl mariadb-plugin-provider-lzma
  libdbi-perl mariadb-plugin-provider-lzo
  libmariadb3 mariadb-plugin-provider-snappy
  mariadb-client mariadb-server-core
  mariadb-client-core pv
  mariadb-common socat

Suggested packages:
  libnet-daemon-perl libsql-statement-perl mailx mariadb-test

REMOVING:
  mysql-client mysql-client-core mysql-server mysql-server-core

Summary:
  Upgrading: 0, Installing: 17, Removing: 4, Not Upgrading: 10
  Download size: 17.0 MB
  Freed space: 58.1 MB

```

```
Package: Configuration

```

```

The old data directory will be saved at new location
A file named /var/lib/mysql/debian-5.7.33-1 flag exists on this system. The number
indicates a database binary format version that cannot automatically be
updated (or downgraded).
Therefore the previous data directory will be renamed to /var/lib/mysql- and
a new data directory will be initialized at /var/lib/mysql.
Please manually export/import your data (e.g. with mysqldump) if needed.

```

```


```

```
root@root:~# systemctl start mariadb
root@root:~# systemctl status mariadb
● mariadb.service - MariaDB 11.4.7 database server
   Loaded: loaded (/usr/lib/systemd/system/mariadb.service; enabled; preset: enabled)
   Active: active (running) since Wed 2025-10-22 14:38:27 UTC; 1min 39s ago
   Invocation: d9045dd8a2914e2808589ba4ff6221
   Docs: man:mariadb(8)
        https://mariadb.com/kb/en/library/systemd/
   Main PID: 5488 (mariabdd)
   Status: "Taking your SQL requests now..."
   Tasks: 10 (limit: 25827)
   Memory: 84.9M (peak: 89.6M)
   CPU: 1.276s
   CGroup: /system.slice/mariadb.service
           └─5488 /usr/sbin/mariabdd

Oct 22 14:38:26 root mariabdd[5488]: 2025-10-22 14:38:26 0 [Note] Plugin 'wsrep-provi
Oct 22 14:38:26 root mariabdd[5488]: 2025-10-22 14:38:26 0 [Note] InnoDB: Loading buf
Oct 22 14:38:26 root mariabdd[5488]: 2025-10-22 14:38:26 0 [Note] InnoDB: Buffer pool
Oct 22 14:38:27 root mariabdd[5488]: 2025-10-22 14:38:27 0 [Note] Server socket creat
Oct 22 14:38:27 root mariabdd[5488]: 2025-10-22 14:38:27 0 [Note] mariabdd: Event sch
Oct 22 14:38:27 root mariabdd[5488]: 2025-10-22 14:38:27 0 [Note] /usr/sbin/mariabdd:
Oct 22 14:38:27 root mariabdd[5488]: Version: '11.4.7-MariaDB-0ubuntu.25.04.1' socke
Oct 22 14:38:27 root systemd[1]: Started mariadb.service - MariaDB 11.4.7 database se
Oct 22 14:38:27 root /etc/mysql/debian-start[5524]: Checking for insecure root accou
Oct 22 14:38:27 root /etc/mysql/debian-start[5528]: Triggering myisam-recover for all
[lines 1-24/24 (END)]
```

```
root@root:~# systemctl enable mariadb
Synchronizing state of mariadb.service with SysV service script with /usr/lib/systemd/
systemd-sysv-install.
Executing: /usr/lib/systemd/systemd-sysv-install enable mariadb
```

```
root@root:~# mariadb-secure-installation
```

NOTE: RUNNING ALL PARTS OF THIS SCRIPT IS RECOMMENDED FOR ALL MariaDB SERVERS IN PRODUCTION USE! PLEASE READ EACH STEP CAREFULLY!

In order to log into MariaDB to secure it, we'll need the current password for the root user. If you've just installed MariaDB, and haven't set the root password yet, you should just press enter here.

Enter current password for root (enter for none):

1. 시스템 업데이트 및 MariaDB 서버 설치

명령어 : apt update -y

```
apt install mariadb-server -y
```

중간에 하늘색 화면 뜨면 엔터 ㄱㄱ

2. MariaDB 서비스 시작 및 상태 확인

```
명령어 : systemctl start mariadb
```

```
systemctl status mariadb
```

부팅 시 자동 시작 활성화

명령어 : systemctl enable mariadb

3. 초기화 작업

명령어 : mariadb-secure-installation

1) DBMS 계정의 root 비밀번호를 입력해라.

-> enter (설정하지 않으면 엔터키 눌러라)

2) 외부에 있는 특정대상이 DBMS에 접속할때 root계정

<pre>OK, successfully used password, moving on... Setting the root password or using the unix socket ensures that nobody can log into the MariaDB root user without the proper authorisation. You already have your root account protected, so you can safely answer 'n'. Switch to unix_socket authentication [Y/n] █</pre>	으로 접속할수있게(socket) 허용할건가? -> y
<pre>Enabled successfully! Reloading privilege tables.. ... Success! You already have your root account protected, so you can safely answer 'n'. Change the root password? [Y/n] █</pre>	3) root의 비번을 지정할래? -> y (n 으로는 : root 사용 자체를 못해버림)
<pre>Change the root password? [Y/n] y New password: Re-enter new password: Password updated successfully! Reloading privilege tables.. ... Success!</pre>	4) 비밀번호 설정 (2번 입력) -> asd123!@
<pre>By default, a MariaDB installation has an anonymous user, allowing anyone to log into MariaDB without having to have a user account created for them. This is intended only for testing, and to make the installation go a bit smoother. You should remove them before moving into a production environment. Remove anonymous users? [Y/n] █</pre>	5) 익명의 사용자 지울꺼냐? -> y
<pre>... Success! Normally, root should only be allowed to connect from 'localhost'. This ensures that someone cannot guess at the root password from the network. Disallow root login remotely? [Y/n] █</pre>	6) 외부에서 원격접속을 허용할꺼냐? -> n
<pre>... skipping. By default, MariaDB comes with a database named 'test' that anyone can access. This is also intended only for testing, and should be removed before moving into a production environment. Remove test database and access to it? [Y/n] █</pre>	7) 테스트 데이터베이스 접속 제거할꺼냐? -> y
<pre>- Dropping test database... ... Success! - Removing privileges on test database... ... Success! Reloading the privilege tables will ensure that all changes made so far will take effect immediately. Reload privilege tables now? [Y/n] █</pre>	8) 권한 table이 재설정됐으니 바로 설정할래?(reload) -> y
<pre>... Success! Cleaning up... All done! If you've completed all of the above steps, your MariaDB installation should now be secure. Thanks for using MariaDB! root@root:~# █</pre>	- 초기화 작업 END -
<pre>root@root:~# mysql -u root -p Enter password: Welcome to the MariaDB monitor. Commands end with ; or \g. Your MariaDB connection id is 40 Server version: 11.4.7-MariaDB-0ubuntu0.25.04.1 Ubuntu 25.04 Copyright (c) 2000, 2018, Oracle, MariaDB Corporation Ab and others. Support MariaDB developers by giving a star at https://github.com/MariaDB/server Type 'help;' or '\h' for help. Type '\c' to clear the current input statement. MariaDB [(none)]> █</pre>	4. 설치한 DB(mysql) 실행 명령어 : <code>mysql -u root -p</code> (비밀번호 asd123!@)
<pre>MariaDB [(none)]> create user 'wj'@'%' identified by 'asd123!@'; Query OK, 0 rows affected (0.001 sec)</pre>	5. 사용자 계정 생성 명령어 : <code>create user '사용자 계정 이름' identified by '비밀번호';</code> # % : wj라는 아이디와 비밀번호로 모든 호스트(모든 ip)에서 접속하는 것을 허용한다는 뜻 # @ : 사용자 이름과 접속 호스트 정보를 나누는 분리 기호 의미 : MariaDB 서버에 접속하고 작업을 수행할 수 있는 신원과 인증 정보 생성
<pre>MariaDB [(none)]> create database wj; Query OK, 1 row affected (0.001 sec)</pre>	6. 데이터 베이스를 생성하기(DB생성) 명령어 : <code>create database 데이터 베이스 이름;</code> -> 데이터를 실제로 저장할 수 있는 논리적인 저장소 생성

<pre>MariaDB [(none)]> grant all privileges on wj.* to 'wj'@'%'; Query OK, 0 rows affected (0.001 sec)</pre>	8. 권한 위임주기(* wj 데이터베이스가 갖고있는 모든 권한) -> 'wj' DB에 대한 사용 권한을 'wj'@'%'에게 위임하겠다. 명령어 : <code>grant all privileges on 데이터 베이스 이름.* to '사용자 계정'@'%'</code>; 의미 : 모든 호스트에서 접속하는 'wj' 사용자에게, 'wj' 데이터베이스 내의 모든 테이블에 대한 모든 권한을 부여하라
<pre>MariaDB [(none)]> flush privileges; Query OK, 0 rows affected (0.001 sec)</pre>	9. 설정권한 변경으로 reload 해준다. 명령어 : <code>flush privileges</code>; -> 권한 변경(부여)했으니 변경된 내용 적용해라!
<pre>MariaDB [(none)]> quit; Bye root@root:~# █</pre>	10. DB 종료하기 명령어 : <code>quit</code>;
번외 - MariaDB 실행하여 할 수 있는 기능	
<pre>MariaDB [(none)]> show databases; +-----+ Database +-----+ information_schema mysql performance_schema sys wj +-----+ 5 rows in set (0.001 sec)</pre>	1. 자신이 권한을 갖고 있는 DB의 목록 확인 할 수 있다. (mysql 진입후) 명령어 : <code>show databases</code>;
<pre>MariaDB [(none)]> use wj; Database changed MariaDB [wj]> █</pre>	2. '사용자 계정' DB 안에 어떤 내용이 있는지 궁금하다. 명령어 : <code>use 사용자 계정</code>;
<pre>MariaDB [wj]> show tables; Empty set (0.000 sec) MariaDB [wj]> █</pre>	3. 어떤 Table이 있는지 궁금하다. 명령어 : <code>show tables</code>; # 아무것도 아직없다. -> Empty set