

Subsetting Data in R

Data Wrangling in R

Dealing with Missing Data

Missing data types

One of the most important aspects of data cleaning is missing values.

Types of “missing” data:

- NA - general missing data
- NaN - stands for “**N**ot **a** **N**umber”, happens when you do $0/0$.
- Inf and -Inf - Infinity, happens when you take a positive number (or negative number) by 0.

Finding Missing data

Each missing data type has a function that returns `TRUE` if the data is missing:

- `NA` - `is.na()`
- `NaN` - `is.nan()`
- `Inf` and `-Inf` - `is.infinite()`
- `is.finite()` returns `FALSE` for all missing data and `TRUE` for non-missing

Missing Data with Logicals

One important aspect (esp with subsetting) is that logical operations return NA for NA values. Think about it, the data could be > 2 or not. We don't know, so R says there is no TRUE or FALSE, and instead that is missing:

```
x = c(0, NA, 2, 3, 4)
x > 2
```

```
[1] FALSE    NA FALSE   TRUE   TRUE
```

Missing Data with Logicals

What to do? What if we want if $x > 2$ and x isn't NA?

```
x
```

```
[1]  0 NA  2  3  4
```

```
!is.na(x)
```

```
[1]  TRUE FALSE  TRUE  TRUE  TRUE
```

```
x > 2 & !is.na(x)
```

```
[1] FALSE FALSE FALSE  TRUE  TRUE
```

Missing Data with Operations

Similarly with logicals, operations/arithmetic with NA will result in NAs:

```
x + 2
```

```
[1]  2 NA  4  5  6
```

```
x * 2
```

```
[1]  0 NA  4  6  8
```

UFO data again

```
ufo = read_csv("../data/ufo/ufo_data_complete.csv", col_types =  
               cols(  
                 .default = col_character(),  
                 `duration (seconds)` = col_double(),  
                 longitude = col_double()  
               ))  
  
head(ufo)
```

```
# A tibble: 6 x 11  
  datetime    city state country shape `duration (seco...` `duration (hour...` commen  
  <chr>      <chr> <chr> <chr>   <chr>      <dbl> <chr>              <chr>  
1 10/10/19... san ... tx    us    cyli...    2700 45 minutes      This e  
2 10/10/19... lack... tx    <NA>    light    7200 1-2 hrs        1949 I  
3 10/10/19... ches... <NA>    gb     circ...     20 20 seconds      Green/  
4 10/10/19... edna  tx     us     circ...     20 1/2 hour        My olo  
5 10/10/19... kane... hi     us     light     900 15 minutes      AS a M  
6 10/10/19... bris... tn     us     sphe...     300 5 minutes       My fat  
# ... with 3 more variables: date posted <chr>, latitude <chr>, longitude <dbl>
```


Filtering and tibbles

Missing value and filter can be powerful

```
ufo %>%  
  filter(is.na(state) | is.na(country)) %>%  
  head()
```

```
# A tibble: 6 x 11  
  datetime    city    state country shape `duration (seco...` `duration (hour...` comment  
  <chr>      <chr> <chr> <chr>    <chr>      <dbl> <chr>              <chr>  
1 10/10/19... lack... tx      <NA>    light      7200 1-2 hrs            1949 I  
2 10/10/19... ches... <NA>    gb      circ...      20 20 seconds        Green/  
3 10/10/19... pena... <NA>    gb      circ...     180 about 3 mins      penart  
4 10/10/19... berm... <NA>    <NA>    light      20 20 sec.           saw fa  
5 10/10/19... will... az      <NA>    light     120 2 min             The ob  
6 10/10/19... card... <NA>    gb      disk     1200 20 minutes        back i  
# ... with 3 more variables: date posted <chr>, latitude <chr>, longitude <dbl>
```

Filtering and tibbles

Group logical statements with parentheses

```
ufo %>%  
  filter(  
    (!is.na(state) & is.na(country)) | city == "seattle") %>%  
  head()
```

```
# A tibble: 6 x 11  
  datetime    city  state country shape `duration (seco...`duration (hour... commen  
  <chr>      <chr> <chr> <chr>    <chr>    <dbl> <chr>      <chr>  
1 10/10/19... lack... tx      <NA>    light    7200 1-2 hrs    1949 I  
2 10/10/19... will... az      <NA>    light    120 2 min     The ok  
3 10/10/19... sadd... ab      <NA>    tria...  270 4.5 or more min. Lights  
4 10/10/19... holm... ny      <NA>    chev...  180 3 minutes  Footba  
5 10/10/19... mani... on      <NA>    disk    600 10/mins   We cou  
6 10/10/19... kran... ky      <NA>    tria...  180 3min      Triang  
# ... with 3 more variables: date posted <chr>, latitude <chr>, longitude <dbl>
```

Renaming Columns

Renaming Columns of a `data.frame`

To rename columns in `dplyr`, you use the `rename` command (NEW=old)

```
ufo = ufo %>% rename(City = city, duration_s = `duration (seconds)`)
head(ufo)
```

```
# A tibble: 6 x 11
  datetime City      state country shape duration_s `duration (hour... comments
  <chr>      <chr>    <chr> <chr>   <chr>    <dbl> <chr>             <chr>
1 10/10/19... san ma... tx      us      cyli...    2700 45 minutes      This event
2 10/10/19... lackla... tx      <NA>    light    7200 1-2 hrs         1949 Lackl
3 10/10/19... cheste... <NA>    gb      circ...     20 20 seconds      Green/Oran
4 10/10/19... edna      tx      us      circ...     20 1/2 hour        My older b
5 10/10/19... kaneohe   hi      us      light     900 15 minutes      AS a Marin
6 10/10/19... bristol   tn      us      sphe...     300 5 minutes       My father
# ... with 3 more variables: date posted <chr>, latitude <chr>, longitude <dbl>
```

Renaming All Columns of a `data.frame`: `dplyr`

To rename all columns you use the `rename_all` command (with a function)

```
ufo_upper = ufo %>% rename_all(toupper)
head(ufo_upper)
```

```
# A tibble: 6 x 11
  DATETIME CITY STATE COUNTRY SHAPE DURATION S `DURATION (HOUR... COMMENTS
  <chr> <chr> <chr> <chr> <chr> <dbl> <chr> <chr>
1 10/10/19... san ma... tx us cyli... 2700 45 minutes This event
2 10/10/19... lackla... tx <NA> light 7200 1-2 hrs 1949 Lackl
3 10/10/19... cheste... <NA> gb circ... 20 20 seconds Green/Oran
4 10/10/19... edna tx us circ... 20 1/2 hour My older b
5 10/10/19... kaneohe hi us light 900 15 minutes AS a Marin
6 10/10/19... bristol tn us sphe... 300 5 minutes My father
# ... with 3 more variables: DATE POSTED <chr>, LATITUDE <chr>, LONGITUDE <dbl>
```

Adding columns to a `data.frame`

`mutate` - allows you to add or replace columns (need to reassign for it to stick)

```
ufo %>% select(state) %>% head(3)
```

```
# A tibble: 3 x 1
  state
  <chr>
1 tx
2 tx
3 <NA>
```

```
ufo2 = ufo %>% mutate(State = toupper(state)) # we renamed city
ufo2 %>% select(State) %>% head(3)
```

```
# A tibble: 3 x 1
  State
  <chr>
1 TX
2 TX
3 <NA>
```

Creating conditional variables

One frequently-used tool is creating variables with conditions.

A general function for creating new variables based on existing variables is the `ifelse()` function, which “returns a value with the same shape as test which is filled with elements selected from either yes or no depending on whether the element of test is TRUE or FALSE.”

```
ifelse(test, yes, no)
```

```
# test: an object which can be coerced  
#       to logical mode.  
# yes:  return values for true elements of test.  
# no:   return values for false elements of test.
```

Recoding to missing

Sometimes people code missing data in weird or inconsistent ways.

```
ages = data.frame(age = c(23, -999, 21, 44, 32, 57, 65, 54))  
range(ages$age)
```

```
[1] -999    65
```


Recoding to create new column

Say we want to make a new column about if the age was over 30?

```
pull(ages, age)
```

```
[1] 23 -999 21 44 32 57 65 54
```

```
ages = ages %>% mutate(over_20 = ifelse(age > 30, "Yes", "No"))
ages
```

	age	over_20
1	23	No
2	-999	No
3	21	No
4	44	Yes
5	32	Yes
6	57	Yes
7	65	Yes
8	54	Yes

Recoding value to missing

How do we change the -999 to be treated as missing for the age column?

```
pull(ages, age)
```

```
[1] 23 -999 21 44 32 57 65 54
```

```
ages = ages %>% mutate(age = ifelse(age == -999, NA, age))  
range(ages$age)
```

```
[1] NA NA
```

```
range(ages$age, na.rm=TRUE)
```

```
[1] 21 65
```

```
pull(ages, age)
```

```
[1] 23 NA 21 44 32 57 65 54
```

Adding columns to a `data.frame`: dplyr

```
ufo = ufo %>% mutate(  
  region = ifelse(  
    country %in% c("us", "ca"),  
    "North America",  
    "Not North America")  
)  
ufo %>% select(country, region) %>% head()
```

```
# A tibble: 6 x 2  
  country region  
  <chr>    <chr>  
1 us      North America  
2 <NA>    Not North America  
3 gb      Not North America  
4 us      North America  
5 us      North America  
6 us      North America
```

Adding columns to a `data.frame`: `dplyr`

Alternatively, `case_when` provides a more general way (multiple tests easily):

```
casewhen(test ~ value if test is true,  
          test2 ~ vluue if test2 is true,  
          TRUE ~ value if all above tests are not true) # defaults to NA
```

```
ufo = ufo %>% mutate(  
  region = case_when(  
    country %in% c("us", "ca") ~ "North America",  
    country %in% c("de") ~ "Europe",  
    country %in% "gb" ~ "Great Britain"  
  ))
```

```
ufo %>% select(country, region) %>% head()
```

```
# A tibble: 6 x 2  
  country region  
  <chr>    <chr>  
1 us      North America  
2 <NA>    <NA>  
3 gb      Great Britain  
4 us      North America  
5 us      North America  
6 us      North America
```

`case_when()` with value if all tests fail

```
ufo = ufo %>% mutate(  
  region = case_when(  
    country %in% c("us", "ca") ~ "North America",  
    country %in% c("de") ~ "Europe",  
    country %in% "gb" ~ "Great Britain",  
    TRUE ~ "Other"  
  )  
)  
ufo %>% select(country, region) %>% head()
```

```
# A tibble: 6 x 2  
  country region  
  <chr>    <chr>  
1 us      North America  
2 <NA>    Other  
3 gb      Great Britain  
4 us      North America  
5 us      North America  
6 us      North America
```

Ordering the rows of a `data.frame`: `dplyr`

The `arrange` function can reorder rows By default, `arrange` orders in ascending order:

```
ufo %>% arrange(duration_s)
```

```
# A tibble: 88,875 x 12
  datetime    City      state country shape duration_s `duration (hour... comments
  <chr>      <chr>    <chr> <chr>    <chr>    <dbl> <chr>          <chr>
1 10/10/19... puerto... pr      <NA>    <NA>      0 <NA>          Woman cal
2 10/10/19... ashlan... mo      us      light     0 two seperate ti... We saw or
3 10/10/20... bahamas <NA>    <NA>    egg       0 <NA>          we are si
4 10/10/20... burnie... <NA>    au      cross     0 12           the craft
5 10/10/20... edgewa... fl      us      <NA>      0 300          orange ba
6 10/10/20... frankl... in      us      disk      0 ?           two yello
7 10/10/20... knik     ak      us      tria...   0 5           Slow movi
8 10/10/20... bakers... ca      us      circ...   0 had a call of a... UFO sight
9 10/10/20... amaril... tx      us      flash    0 <NA>         we saw fl
10 10/10/20... greenl... <NA>    <NA>    rect...   0 <NA>         Found thi
# ... with 88,865 more rows, and 4 more variables: date posted <chr>,
#   latitude <chr>, longitude <dbl>, region <chr>
```

Ordering the rows of a `data.frame`: `dplyr`

Use the `desc` to arrange the rows in descending order:

```
ufo %>% arrange(desc(duration_s))
```

```
# A tibble: 88,875 x 12
```

	datetime	City	state	country	shape	duration_s	`duration` (hour...	comments
	<chr>	<chr>	<chr>	<chr>	<chr>	<dbl>	<chr>	<chr>
1	10/1/198...	birmi...	<NA>	gb	sphe...	97836000	31 years	Firstly
2	6/3/2010...	ottaw...	on	ca	other	82800000	23000hrs	((HOAX??))
3	9/15/199...	green...	ar	us	light	66276000	21 years	Orange or
4	4/2/1983...	dont ...	<NA>	<NA>	<NA>	52623200	2 months	Hi, I&
5	8/10/201...	finley	wa	us	light	52623200	2 months	There have
6	8/24/200...	engle...	fl	us	light	52623200	2 months	bright sta
7	6/30/196...	somer...	<NA>	gb	cone	25248000	8 years	First time
8	10/7/201...	oklah...	ok	<NA>	circ...	10526400	4 months	Bright fly
9	3/1/1994...	menif...	ca	us	unkn...	10526400	4 months	Sun City /
10	8/3/2008...	virgi...	va	us	fire...	10526400	4 months	this objec

```
# ... with 88,865 more rows, and 4 more variables: date posted <chr>,  
#   latitude <chr>, longitude <dbl>, region <chr>
```

Ordering the rows of a `data.frame`: `dplyr`

It is a bit more straightforward to mix increasing and decreasing orderings:

```
ufo %>% arrange(country, desc(duration_s))
```

```
# A tibble: 88,875 x 12
```

	datetime	City	state	country	shape	duration_s	`duration` (hour...	comments
	<chr>	<chr>	<chr>	<chr>	<chr>	<dbl>	<chr>	<chr>
1	11/12/20...	mount ...	<NA>	au	sphe...	1209600	2 weeks	Orange or
2	5/12/200...	sydney...	<NA>	au	light	345600	4 days+	Infra rec
3	4/18/200...	sydney...	<NA>	au	light	86400	day	It was a
4	4/15/198...	brisba...	<NA>	au	chan...	37800	1 1/2 hours	A brillia
5	4/18/199...	brisba...	<NA>	au	<NA>	18000	5 hours plus	Five hour
6	6/9/2005...	melbou...	<NA>	au	circ...	18000	5 hours +	UFO sight
7	11/6/200...	perth ...	<NA>	au	light	14400	4hrs	Unusual l
8	3/15/200...	adelai...	<NA>	au	form...	10800	1-3 hrs	ive got t
9	3/2/2014...	perth ...	<NA>	au	light	10800	2-3 hours	Constant
10	6/20/200...	canber...	<NA>	au	tear...	10800	3 hrs	8 tear dr

```
# ... with 88,865 more rows, and 4 more variables: date posted <chr>,  
#   latitude <chr>, longitude <dbl>, region <chr>
```


Lab

[Link to Lab](#)