

Playwright XPATH

How? When?

Playwright

XPATH

How? When?

The Golden Rule

What

What is Xpath?

XML path –address of the element in DOM

When

When to use?

Basic locators are not available / changing dynamically.

How

How to write xpath?

Based on the element path and syntax

The Golden Rule

Absolute Xpath

Absolute Xpath

- long path

- Starts from root tag(<html>) and ends at the target element tag.

- Starts with "/" and traverse through each and every tag in hierarchy to reach the required WebElement.

The syntax for the absolute xpath is

```
/html/body/div[2]/div/div/form/p/input
```

- Rarely used because of unreliable

Relative XPath

Relative XPath

*works in relation with the WebElement location in the DOM.

It goes directly to the address of the target WebElement.

*Relative XPath starts with the “//” which locates the inner or middle part of the DOM.

General syntax of the Relative xpath is:

```
//tagname[@attribute='attributeValue']
```

Current node

tagname of the targeted element

Attribute of the element

value of the selected attribute

Types of Relative Locators

Relative Locators

► Basic XPath

► Advanced XPath

Attribute

Attribute Value

Text

Basic Xpath – Attribute Based

Contd..

Attribute Based XPath:

->uses the attribute and attribute value of the WebElement in the DOM.

Syntax:

```
//tagName[@attribute='attributeValue']
```

Example

```
//input[@id='username']
```

Basic Xpath – Text Based

Contd..

Text Based Xpath:

->based on the text displayed for the WebElement in dom.

Syntax:

```
//tagName[text()='text value in DOM']
```

Example:

```
//a[text()='Create New Account']
```

Basic Xpath – Partial Match

Contd..

Partial attribute Based Xpath:

=>uses the partial attribute value of the WebElement

*Contains ->check for the given attribute value with the value in DOM

Syntax:

```
//tagName[contains(@attribute, 'Partial value of the attribute')]
```

Example:

```
//input[contains(@id, 'user')]
```

Basic Xpath – Partial Match

Contd..

Partial Text Based Xpath:

->uses the partial text value of the WebElement

Syntax:

```
//tagname[contains(text(),' Partial text in my DOM' ')]
```

Example:

```
//a[contains(text(),'Create')]
```

Basic Xpath - Collection

Collection Based Xpath:

-> when there is multiple matches of found for a xpath

->uses index to match the exact element

->Index starts with 1

Syntax:

```
(//tagName[@attribute='attributeValue'])[index]
```

Example

```
(//input[@class='inputLogin'])[2]
```

Summary

Basic Xpath-What , when, How?

2 types- Absolute and Relative xpath

Most recommended –Relative xpath