

Alerts in Playwright

Target Locators

PLAYWRIGHT ALERT HANDLING

Playwright handles browser dialogs through the page dialog event.

WHAT

An alert is an information or message presented by the application.

WHY

A modal browser dialog interrupts normal page interaction until it is handled.

HOW

Listen for the dialog event and respond using the Dialog object.

Types of Alert

Modal and Non-Modal

Modal Alert

Non-Modal Alert

Simple Alert

Accept the information

One action

Accept the information displayed by the alert.

Playwright

Use `dialog.accept()` to accept the alert.

Example TypeScript

```
page.once('dialog', async dialog => {  
  await dialog.accept();  
});  
  
await page.getByRole('button', { name: 'Show' }).click();
```

Confirmation Alert

Accept or reject

Accept

Use `dialog.accept()` when the confirmation should be accepted.

Reject

Use `dialog.dismiss()` when the confirmation should be cancelled.

Accept TypeScript

```
page.once('dialog', async dialog => {  
  await dialog.accept();  
});  
await page.getByRole('button', { name: 'Show' }).click();
```

Dismiss TypeScript

```
page.once('dialog', async dialog => {  
  await dialog.dismiss();  
});  
await page.getByRole('button', { name: 'Show' }).click();
```

Prompt Alert

Accept, reject and provide input

Accept with input

A prompt can receive user input when it is accepted.

Reject

Use `dialog.dismiss()` to cancel the prompt.

Read message

Use `dialog.message()` to get the text displayed in the dialog.

Example TypeScript

```
page.once('dialog', async dialog => {  
  console.log(dialog.message());  
  await dialog.accept('Testleaf');  
});  
await page.getByRole('button', { name: 'Show' }).click();
```

How to Handle It?

Playwright approach

Register a dialog listener before the action that opens the dialog.

Perform the action that triggers the alert.

Use the Dialog object to accept, dismiss or read the dialog.

Core syntax TypeScript

```
page.on('dialog', async dialog => {  
  await dialog.accept();  
});
```

Important

Unlike Selenium's `driver.switchTo().alert()`, Playwright uses the page dialog event.

Dialog Methods

Actions available in Playwright

Accept the dialog. For a prompt, an optional input string can be supplied.

Dismiss or cancel the dialog.

Return the message displayed in the dialog.

Return the default value of a prompt dialog.

Return the dialog type.

Selenium → Playwright

Concept mapping

Switch to alert

Accept

Dismiss

Get text

Prompt input

Sweet Alert

DOM-based alert

Inspectable

When implemented inside the page DOM, a sweet alert can be inspected.

Locator based

Use Playwright locators to interact with its buttons and text.

Example TypeScript

```
await page.getByRole('button', { name: 'Delete' }).click();  
await page.getByRole('button', { name: 'Confirm' }).click();
```

Key distinction

Browser JavaScript dialogs use the dialog event. DOM-based sweet alerts use normal locators.

Practical Patterns

Common Playwright examples

Simple TypeScript

```
page.once('dialog', async dialog => await dialog.accept());  
await page.getByRole('button', { name: 'Show' }).click();
```

Confirmation TypeScript

```
page.once('dialog', async dialog => await dialog.dismiss());  
await page.getByRole('button', { name: 'Show' }).click();
```

Prompt TypeScript

```
page.once('dialog', async dialog => await dialog.accept('Testleaf'));  
await page.getByRole('button', { name: 'Show' }).click();
```

One-time handling

Use `page.once('dialog', ...)` when one dialog is expected for the triggering action.

Summary

Alert handling in Playwright

Browser JavaScript dialogs are exposed through the page dialog event.

Simple Alert → `dialog.accept()`

Confirmation Alert → `dialog.accept()` / `dialog.dismiss()`

Prompt Alert → `dialog.accept('input')` / `dialog.dismiss()`

Read text → `dialog.message()`

DOM Sweet Alert → normal Playwright locators.

Mind Map

Playwright Alert Handling

Alert

Browser JavaScript Dialog

Types

Simple • Confirmation • Prompt

Event

`page.on('dialog')` / `page.once('dialog')`

Actions

`accept()` • `dismiss()`

Read

`message()` • `defaultValue()` • `type()`

Prompt

`accept('text')`

Sweet Alert

DOM element → locator-based handling