10 Linux Commands

1. Basename – command to know the file name alone

```
acer@Z14-55M:~/linux_practice_15$ pwd
/home/acer/linux_practice_15
acer@Z14-55M:~/linux_practice_15$ basename /home/acer/linux_practice_15
linux_practice_15
acer@Z14-55M:~/linux_practice_15$ basename /home/acer/linux_practice_15/
file1.txt
file1.txt
acer@Z14-55M:~/linux_practice_15$ basename /home/acer/linux_practice_15/
file1.txt .txt
file1
```

2. Cksum file.txt - shows the checksum value, file size in bytes, filename

```
acer@Z14-55M:~/linux_practice_15$ cksum file1.txt
1347938048 57 file1.txt
```

3. Csplit file.txt 2 – splits the file.txt at specific line number

```
acer@Z14-55M:~/linux_practice_15$ cat file1.txt
hi
this is sample text
sample file
line 1
line number 2

acer@Z14-55M:~/linux_practice_15$ csplit file1.txt 2
3
54
acer@Z14-55M:~/linux_practice_15$ ls
file1.txt  file2.txt  xx00  xx01
acer@Z14-55M:~/linux_practice_15$ cat xx00
hi
acer@Z14-55M:~/linux_practice_15$ cat xx01
this is sample text
sample file
line 1
line number 2
```

4. Cpio - command to copy in command

```
n auto mode
Processing triggers for man-db (2.13.1-1build1) ...
acer@Z14-55M:~/linux_practice_15$ find . -name "*.txt" | cpio -ov > arch
ive.cpio
./file2.txt
./file1.txt
1 block
acer@Z14-55M:~/linux_practice_15$ ls
archive.cpio  file1.txt  file2.txt  xx00  xx01
acer@Z14-55M:~/linux_practice_15$
```

5. Cpio – copy in command

```
acer@Z14-55M:~/linux_practice_15/extracted$ sudo cpio -iv < ../archive.c
pio
file2.txt
file1.txt
1 block
acer@Z14-55M:~/linux_practice_15/extracted$ ls
file1.txt  file2.txt
```

6. Login a user – su <user>

```
siva@Z14-55M: /home/acer/li
acer@Z14-55M:~/linux_practice_15$ su siva
Password:
siva@Z14-55M:/home/acer/linux_practice_15$ pinky
Login    Name                TTY       Idle   When             Where
siva@Z14-55M:/home/acer/linux_practice_15$
```

7. Arp –a - adding a host ip

```
Setting up net-tools (2.10-2ubuntu1) ...
Processing triggers for man-db (2.13.1-1build1) ...
acer@Z14-55M:~/linux_practice_15$ arp -a
Z14-55M.mshome.net (172.22.240.1) at 00:15:5d:b6:d2:ae [ether] on eth0
acer@Z14-55M:~/linux_practice_15$ ping 172.22.240.1
PING 172.22.240.1 (172.22.240.1) 56(84) bytes of data.
64 bytes from 172.22.240.1: icmp_seq=1 ttl=128 time=1.52 ms
64 bytes from 172.22.240.1: icmp_seq=2 ttl=128 time=1.09 ms
64 bytes from 172.22.240.1: icmp_seq=3 ttl=128 time=0.827 ms
64 bytes from 172.22.240.1: icmp_seq=4 ttl=128 time=0.969 ms
64 bytes from 172.22.240.1: icmp_seq=5 ttl=128 time=0.904 ms
64 bytes from 172.22.240.1: icmp_seq=6 ttl=128 time=0.879 ms
64 bytes from 172.22.240.1: icmp_seq=7 ttl=128 time=1.06 ms
64 bytes from 172.22.240.1: icmp_seq=8 ttl=128 time=6.56 ms
^C
--- 172.22.240.1 ping statistics ---
8 packets transmitted, 8 received, 0% packet loss, time 7011ms
rtt min/avg/max/mdev = 0.827/1.726/6.559/1.837 ms
acer@Z14-55M:~/linux_practice_15$
```

8. More /etc/hosts - checking machines

10 Linux Commands

```
acer@Z14-55M:~/linux_practice_15$ more /etc/hosts
# This file was automatically generated by WSL. To stop automatic genera
tion of this file, add the following entry to /etc/wsl.conf:
# [network]
# generateHosts = false
127.0.0.1       localhost
127.0.1.1       Z14-55M.localdomain     Z14-55M

# The following lines are desirable for IPv6 capable hosts
::1     ip6-localhost ip6-loopback
fe00::0 ip6-localnet
ff00::0 ip6-mcastprefix
ff02::1 ip6-allnodes
ff02::2 ip6-allrouters
acer@Z14-55M:~/linux_practice_15$
```

9. Df

```
acer@Z14-55M:~/linux_practice_15$ df
Filesystem      1K-blocks      Used  Available Use% Mounted on
none              1824576         0    1824576   0% /usr/lib/modules/6.1
8.33.2-microsoft-standard-WSL2
none              1824576         4    1824572   1% /mnt/wsl
drivers         143609852 129283836   14326016  91% /usr/lib/wsl/drivers
/dev/sdd       1055762868   1357392 1000702004   1% /
none              1824576        36    1824540   1% /mnt/wslg
none              1824576         0    1824576   0% /usr/lib/wsl/lib
rootfs            1818820      2772    1816048   1% /init
none              1824576       512    1824064   1% /run
none              1824576         0    1824576   0% /run/lock
none              1824576         0    1824576   0% /run/shm
none              1824576       100    1824476   1% /mnt/wslg/versions.t
xt
none              1824576       100    1824476   1% /mnt/wslg/doc
C:\             143609852 129283836   14326016  91% /mnt/c
D:\              52428796     96380   52332416   1% /mnt/d
tmpfs             1824580         0    1824580   0% /tmp
none                 1024         0       1024   0% /run/credentials/sys
temd-journald.service
none                 1024         0       1024   0% /run/credentials/sys
temd-resolved.service
none                 1024         0       1024   0% /run/credentials/get
ty@tty1.service
tmpfs              364912        12     364900   1% /run/user/1000
acer@Z14-55M:~/linux_practice_15$
```

10. Iostat

10 Linux Commands

