Ex.No:01	SIMPLE WEB DESIGN USING HTML

Objective:

Build a web page that conforms to HTML5 standards and has the following elements: doctype, html, meta (in the revised html5 format), title, head, body, header, footer, nav, section, div, p, span, headings, image, anchor, table, list, html comment, etc..

Description:

Hypertext Markup Language (HTML) is the standard markup language for documents designed to be displayed in a web browser.

Working with Tables

The HTML tables are created using the <table> tag in which the <tr> tag is used to create table rows and <td> tag is used to create data cells. The elements under <td> are regular and left aligned by default. colspan attribute used to merge two or more columns into a single column. Similar way rowspan is used to merge two or more rows. The caption tag will serve as a title or explanation for the table and it shows up at the top of the table. You can use one table inside another table. Not only tables you can use almost all the tags inside table data tag <td>.

```
<table border = "1">
       <tr>
         <td>Row 1, Column 1</td>
         <td>Row 1, Column 2</td>
       </tr>
       <tr>
         <td>Row 2, Column 1</td>
         <td>Row 2, Column 2</td>
       </tr>
</table>
```

This will produce the following result −

Row 1, Column 1	Row 1, Column 2
Row 2, Column 1	Row 2, Column 2

Working with list

HTML offers web authors three ways for specifying lists of information. Lists may contain −

- − An unordered list. This will list items using plain bullets.

- − An ordered list. This will use different schemes of numbers to list your items.
- <dl> − A definition list. This arranges your items in the same way as they are arranged in a dictionary.

Type attribute for <ul> tag to specify the type of bullet you like. By default, it is a disc.

```
<ul>
  <li>Beetroot</li>
  <li>Ginger</li>
  <li>Potato</li>
  <li>Radish</li>
</ul>
```

This will produce the following result −

- Beetroot
- Ginger
- Potato
- Radish

Working with Text

<abbr> tag defines an abbreviation or an acronym.

<blockquote> tag specifies a section that is quoted from another source.

<cite> tag defines the title of a work (e.g. a book, a song, etc.).

<code> tag is a phrase tag. It defines a piece of computer code.

 tag is a phrase tag. It renders as emphasized text.

<h1> to <h6> tags are used to define HTML headings.

<mark> tag defines marked text.

<pre> tag defines preformatted text.

 tag is used to group inline-elements in a document.

<sub> tag defines subscript text.

<sup> tag to define superscripted text

<p> element defines a paragraph

HTML Entities

Some characters are reserved in HTML. Character entities are used to display reserved characters in HTML. To display a less than sign (<) we must write: <

Working with links

HTML links are hyperlinks. It links another document. The target attribute specifies where to open the linked document.

The target attribute can have one of the following values:

- _blank - Opens the linked document in a new window or tab
- _self - Opens the linked document in the same window/tab as it was clicked (this is default)
- _parent - Opens the linked document in the parent frame
- _top - Opens the linked document in the full body of the window

```
<body>
    <p>Click any of the following links</p>
    <a href = "/html/index.htm" target = "_blank">Opens in New</a> |
    <a href = "/html/index.htm" target = "_self">Opens in Self</a> |
    <a href = "/html/index.htm" target = "_parent">Opens in Parent</a>
|
    <a href = "/html/index.htm" target = "_top">Opens in Body</a>
</body>
```

This will produce the following result –

Click any of the following links

Opens in New | Opens in Self | Opens in Parent | Opens in Body

Bookmark

HTML bookmarks are used to allow readers to jump to specific parts of a Web page. Bookmarks can be useful if your webpage is very long. To make a bookmark, you must first create the bookmark, and then add a link to it.

Image

Images are very important to beautify as well as to depict many complex concepts in simple way on your web page. Insert any image in your web page by using <img> tag. src attribute specify the location of the image file. Image name is always case sensitive. The alt attribute is a mandatory attribute which specifies an alternate text for an image, if the image cannot be displayed. You can set image width and height based on your requirement using width and height attributes.

```
<body>
  <p>Simple Image Insert</p>
  <img src = "/html/images/test.png" alt = "Test Image" />
</body>
```

Sample web page design:

