

Cloud Security & Compliance Posture



Report Details

Description	This report summarizes the Security and Availability controls implemented by Aptible on behalf of Aids Healthcare Foundation.
Generated for	Aids Healthcare Foundation
Generated At	June 24, 2026 6:40PM UTC
Scope	Showing control implementation for ahf1417

Multi-factor Authentication

Network Segmentation Standards define the design of networks to isolate business critical assets, sensitive user data, and sessions that mandate stronger internal controls. Aptible's underlying servers on AWS employs boundary devices (firewalls) that employ rule sets, access control lists (ACLs) and configurations to enforce the flow of information to specific information system services. Role-based access control is implemented on and by Aptible, and capable of mapping each user to one or more roles, and each role to one or more system functions. The access control system for the system components storing, processing or transmitting covered information is set with a default "deny-all" setting on Aptible. As documented in the Aptible Reference Architecture, the Bastion layer utilizes SSH with role-based API and two factor authentication for customers to grant access following the principle of least privilege. Cryptography is used to protect the confidentiality and integrity of remote access sessions to the internal network and to external systems. Aptible utilizes strong password following NIST SP800-63b guidance, with authentication methods that prohibit the display of a password when being entered.

Multi-factor authentication methods are used in accordance with the organizational security policy for access into Aptible systems.

Control Category	Access Management
Implementation status	0 of 1 User (0%)

SSO Integration

Single Sign On (SSO) reduces security risks surrounding sensitive user data across multiple products and streamline IT management and login processes. Aptible provides functionality to login using an SSO provider. Aptible supports the industry-standard SAML 2.0 protocol for using an external provider. Most SSO Providers support SAML, including Okta and Google's GSuite. SAML provides a secure method to transfer identity and authentication information between the SSO provider and Aptible.

Control Category Access Management

Implementation status 0 of 1 Environment (0%)

Centralized Container Logging

Application, Database, and Endpoint logs are automatically centralized in the Environment's Log Drain(s). Centralizing logs with a logging provider will increase the security and reliability of your services by allowing you to inspect, analyze, and alert on your services' activity.

Control Category Auditing

Implementation status 0 of 1 Environment (0%)

SSH Session Logging

Aptible provides access to ephemeral containers via the `aptible ssh` command. These sessions create an ephemeral container configured identically to the customer's app containers to access a management console, run ad-hoc jobs, and other related operations. As documented in the Aptible Reference Architecture, the Bastion layer utilizes SSH with role-based API and two factor authentication for customers to grant access following the principle of least privilege. Every output from an ephemeral SSH session can be captured and routed to log drains for auditing, aggregation, and record keeping.

Control Category Auditing

Implementation status 0 of 1 Environment (0%)

Host Intrusion Detection

Aptible Managed Host-based Intrusion Detection (HIDS) is installed on each host that runs containers by default and will detect potential intrusions and other anomalous activities. Intrusion detection/information protection system (IDS/IPS) alerts are utilized for reporting information security events. Aptible monitors the underlying EC2 instances in a Dedicated Stacks for potential intrusions, such as unauthorized SSH access, rootkits, file integrity issues, and privilege escalation. The Aptible Security Team monitors and investigates each event to determine the legitimacy of all activity. Crucially, the Aptible Security Team immediately responds to and resolves any issues that are discovered through investigation of anomalous activity and will notify customers of any remediation steps taken.

Aptible adheres to the HITECH Act requirements for responding to a data breach (of covered information) and reporting the breach to affected individuals, media, and federal agencies. Incidents (or a sample of incidents) are reviewed to identify necessary improvement to the security controls.

Aptible is hosted on AWS data-centers. AWS data centers are housed in nondescript facilities. Physical access is strictly controlled both at the perimeter and at building ingress points by professional security staff utilizing video surveillance, intrusion detection systems, and other electronic means.

All vulnerabilities are classified by severity according to the level of risk they present to the confidentiality, integrity, and availability of Aptible services and customer data. Vulnerabilities are remediated on a timeline commensurate with the severity:

- Critical - within 24 hours
- High - within 7 days
- Medium - within 30 days
- Low - within 90 days

Control Category Auditing

Implementation status 0 of 1 Stack (0%)

Network Intrusion Detection

Internal and external vulnerability assessments of covered information systems, virtualized environments, and networked environments, including both network- and application-layer tests, on Aptible are performed by a qualified individual, on a quarterly basis or after significant changes. Aptible employs automated mechanisms to (i) centrally manage, apply, and verify configuration settings; (ii) respond to unauthorized changes to network and system security-related configuration settings; and, (iii) enforce access restrictions and auditing of the enforcement actions. Aptible scans for vulnerabilities in the information system and hosted applications to determine the state of flaw remediation monthly (automatically), and again (manually or automatically) when new vulnerabilities potentially affecting the underlying systems and networked environments are identified and reported. The ability of users to connect to the internal Aptible network is restricted using a deny-by-default and allow-by-exception policy at managed interfaces according to the access control policy and the requirements of its business applications. Crucially, the Aptible Security Team immediately responds to and resolves any issues that are discovered through investigation of anomalous activity and will notify customers of any remediation steps taken.

All vulnerabilities are classified by severity according to the level of risk they present to the confidentiality, integrity, and availability of Aptible services and customer data. Vulnerabilities are remediated on a timeline commensurate with the severity:

- Critical - within 24 hours
- High - within 7 days
- Medium - within 30 days
- Low - within 90 days

Control Category Auditing

Implementation status 0 of 1 Stack (0%)

Drift Detection and Protection

Aptible has put in place drift detection procedures and policies to ensure no infrastructure changes occur that deviate from the expected configuration. Annual compliance reviews are conducted by security or audit individuals using manual or automated tools by Aptible; if non-compliance is found, appropriate action is taken. The results and recommendations of the reviews are documented and approved by management. Automated compliance tools are used when possible. Aptible has developed a continuous monitoring strategy and implemented a continuous monitoring program. Aptible employs assessors or assessment teams with a level of independence appropriate to its continuous monitoring strategy to monitor the security controls in the information system on an ongoing basis. The internal Aptible security organization reviews and maintains records of compliance results (e.g., organization-defined metrics) in order to better track security trends, respond to the results of correlation and analysis, and address longer term areas of concern as part of its formal risk assessment process.

Aptible tests and approves all network connections and firewall, router, and switch configuration changes prior to implementation. Any deviations from the standard configuration or updates to the standard configuration are documented and approved in a change control system. All new configuration rules beyond a baseline-hardened configuration that allow traffic to flow through network security devices, such as firewalls and network-based IPS, are also documented and recorded, with a

specific business reason for each change. Aptible identifies unauthorized (blacklisted) software on the information system, prevents program execution in accordance with a list of unauthorized (blacklisted) software programs, employs an allow-all, deny-by exception policy to prohibit execution of known unauthorized (blacklisted) software, and reviews and updates the list of unauthorized (blacklisted) software programs annually.

Control Category Auditing

Implementation status 0 of 1 Environment (0%)

24/7 Site Reliability and Incident Response

Aptible Managed Host-based Intrusion Detection (HIDS) is installed on each host that runs containers by default and will detect potential intrusions and other anomalous activities. Intrusion detection/information protection system (IDS/IPS) alerts are utilized for reporting information security events. Aptible monitors the underlying EC2 instances in Dedicated Stacks for potential intrusions, such as unauthorized SSH access, rootkits, file integrity issues, and privilege escalation. The Aptible Security Team monitors and investigates each event to determine the legitimacy of all activity.

Internal and external vulnerability assessments of covered information systems, virtualized environments, and networked environments, including both network- and application-layer tests, on Aptible are performed by a qualified individual, on a quarterly basis or after significant changes. Aptible employs automated mechanisms to (i) centrally manage, apply, and verify configuration settings; (ii) respond to unauthorized changes to network and system security-related configuration settings; and, (iii) enforce access restrictions and auditing of the enforcement actions. Aptible scans for vulnerabilities in the information system and hosted applications to determine the state of flaw remediation monthly (automatically), and again (manually or automatically) when new vulnerabilities potentially affecting the underlying systems and networked environments are identified and reported.

All vulnerabilities are classified by severity according to the level of risk they present to the confidentiality, integrity, and availability of Aptible services and customer data. Vulnerabilities are remediated on a timeline commensurate with the severity:

• Critical - within 24 hours • High - within 7 days • Medium - within 30 days • Low - within 90 days

Control Category Business Continuity

Implementation status 0 of 1 Environment (0%)

Network Segregation

Aptible's Business Associates Agreement, required for HIPAA and HITRUST, only applies to Dedicated Stacks. This BAA governs Aptible's Use and Disclosure of any PHI that the platform creates, receives, maintains, or transmits on the customer's behalf. Dedicated Aptible environments are deployed on AWS VPC-based Dedicated Stacks, isolated at the customer level. The VPC, network, underlying instances, and AWS virtual infrastructure for a Dedicated Stack are not shared with any other tenant. Most services run in a private subnet. Only SSL/TLS endpoints and a bastion host are exposed to the Internet. Backend users connect to the stack through the bastion host, which restricts access to stack components and logs activity for review.

Control Category Network Protection

Implementation status 0 of 1 Stack (0%)

Secure, Isolated Network Connections through VPNs and VPCs

Aptible enables customers to connect with third-party networks with a secure, isolated connection that's specific to the customer's isolated network of their Dedicated Stack on Aptible, using IPsec managed VPNs. Customers can also connect with AWS networks with secure VPC peers

Control Category	Network Protection
Implementation status	0 of 1 Stack (0%)

Secure Network Architecture

Aptible's security gateways (e.g., firewalls) (i) enforce security policies; (ii) are configured to filter traffic between domains; (iii) block unauthorized access; (iv) are used to maintain segregation between internal wired, internal wireless, and external network segments (e.g., the Internet), including DMZs; and, (vi) enforce access control policies for each of the domains. Aptible's network is logically and physically segmented with a defined security perimeter and a graduated set of controls, including subnetworks for publicly accessible system components that are logically separated from the internal network, based on organizational requirements; traffic is controlled based on functionality required and classification of the data/systems based on a risk assessment and their respective security requirements. Networks are segregated from production-level networks when migrating physical servers, applications, or data to virtualized servers. The ability of users to connect to the internal network is restricted using a deny-by-default and allow-by-exception policy at managed interfaces according to the access control policy and the requirements of its business applications. Network traffic is controlled in accordance with Aptible's access control policy through firewall and other network-related restrictions for each network access point or external telecommunication services managed interface. Transmitted information is secured and, at a minimum, encrypted over open, public networks.

Control Category	Network Protection
Implementation status	0 of 1 Environment (0%)

Centralized IAM

Network Segmentation Standards define the design of networks to isolate business critical assets, sensitive user data, and sessions that mandate stronger internal controls. Aptible's underlying servers on AWS employs boundary devices (firewalls) that employ rule sets, access control lists (ACLs) and configurations to enforce the flow of information to specific information system services. Role-based access control is implemented on and by Aptible, and capable of mapping each user to one or more roles, and each role to one or more system functions. The access control system for the system components storing, processing or transmitting covered information is set with a default "deny-all" setting on Aptible. As documented in the Aptible Reference Architecture, the Bastion layer utilizes SSH with role-based API and two factor authentication for customers to grant access following the principle of least privilege. Cryptography is used to protect the confidentiality and integrity of remote access sessions to the internal network and to external systems. Aptible utilizes strong password following NIST SP800-63b guidance, with authentication methods that prohibit the display of a password when being entered.

Control Category	Access Management
Implementation status	1 of 1 Environment (100%)

Platform Activity Logging

Backend users on Aptible connect to a Dedicated Stack through the bastion host, which restricts access to stack components and logs activity for review. Aptible logs AWS and Aptible API activity, and host activity within the customer environments. Aptible provides Activity Reports for each environment. These Activity Reports list all operations that took place in the environment over a reporting period, including operations that executed on resources that have later been deleted.

Control Category Auditing

Implementation status 1 of 1 Environment (100%)

Automatic Container Recovery

Aptible containers that exit unexpectedly are restarted in pristine condition, ensuring uptime even if a customer app crashes. Any changes to the filesystem will be undone (e.g. PID files will be deleted, etc.). Appropriate information is sent as output in log drains for notification. If a container is continuously restarting, Aptible will throttle recovery to a rate of one attempt every 2 minutes.

Control Category Business Continuity

Implementation status 1 of 1 Environment (100%)

DDoS Protection

A distributed denial-of-service (DDoS) attack is a malicious attempt to disrupt the normal traffic of a targeted server, service or network by overwhelming the target or its surrounding infrastructure with a flood of Internet traffic. Aptible's VPC-based approach means that most stack components are not accessible from the Internet, and cannot be targeted directly by a DDoS attack.

Aptible Deploy SSL/TLS endpoints include an AWS Application Load Balancer, which only supports valid TCP requests, meaning DDoS attacks such as UDP and SYN floods will not reach a customer's app layer.

Control Category Business Continuity

Implementation status 1 of 1 Environment (100%)

Automated DNS Security and Load Balancing

Aptible provides a highly available and scalable Domain Name System (DNS) services that answers DNS Queries. This allows the translation of domain names to IP addresses and enables the connection of users to hosted applications and databases. Traffic is managed globally through a variety of routing types including Latency Based Routing (LBR), Geo DNS, and Weighted Round-Robin (WRR)

Control Category Business Continuity

Implementation status 1 of 1 Environment (100%)

Automated Backup Testing

Aptible maintains the integrity and security of the backup copies to ensure future availability, and any potential accessibility problems with the backup copies are identified and mitigated in the event of an area-wide disaster. Covered information is backed-up in an encrypted format to ensure confidentiality. Aptible performs incremental or differential backups daily and full backups weekly to separate media. Aptible ensures a current, retrievable copy of covered information is available before movement of servers. Aptible tests backup information following each backup to verify media reliability and information integrity, and at least annually thereafter.

The backups are stored in a physically secure remote location, at a sufficient distance to make them reasonably immune from damage to data at the primary site, and reasonable physical and environmental controls are in place to ensure their protection at the remote location.

Control Category	Business Continuity
Implementation status	1 of 1 Environment (100%)

Memory Management

Application and database containers exceeding their allocated memory could contribute to a series of unintended consequences for end users of a customer's business, eventually leading to downtime. Aptible enables memory management for all containers hosted on the platform, so containers exceeding their allocated memory can cleanly exit and restart gracefully in the event of a crash, with the appropriate logs generated to diagnose the issue and scale to the appropriate amount of memory.

When memory management is enabled and a container exceeds its memory allocation, the following happens:

- Aptible sends a log message to log drains (this includes aptible logs) indicating that the container in question exceeded its memory allocation, and dumps a list of the processes running in the container for troubleshooting purposes.
- If there is free memory on the instance, Aptible increases container memory allowance by 10%. This gives the container a better shot at exiting cleanly.
- Aptible delivers a SIGTERM signal to all the processes in the container, and gives containers 10 seconds to exit. If the container does not exit within 10 seconds, Aptible delivers a SIGKILL signal, effectively terminating all the processes in the Container immediately.
- Aptible triggers Container Recovery to restart the container.

Control Category	Business Continuity
Implementation status	1 of 1 Stack (100%)

End-to-end Encryption in Transit

Aptible uses FIPS-validated cryptographic mechanisms during transmission to prevent unauthorized disclosure of information and detect changes to information unless otherwise protected by organization-defined alternative physical measures. Protocols used to communicate between all involved parties are secured using cryptographic techniques (e.g., SSL). Aptible formally addresses multiple safeguards before allowing the use of information systems for information exchange. Aptible establishes terms and conditions, consistent with any trust relationship established with other organizations owning, operating, and/or maintaining external information systems, allowing authorized individuals to (i) access the information system from external information systems; and (ii) process, store or transmit organization-controlled information using external information systems. Cryptography is used to protect the confidentiality and integrity of remote access sessions to the internal network and to external

systems. Strong cryptography protocols are used to safeguard covered information during transmission over less trusted/open public networks. Aptible ensures that communication protection requirements, including the security of exchanges of information, are the subject of policy development and compliance audits.

Aptible ensures the storage of the transaction details are located outside of any publicly accessible environments (e.g., on a storage platform existing on the organization's intranet) and not retained and exposed on a storage medium directly accessible from the Internet. Where a trusted authority is used (e.g., for the purposes of issuing and maintaining digital signatures and/or digital certificates), security is integrated and embedded throughout the entire end- to-end certificate/signature management process. The protocols used for communications are enhanced to address any new vulnerability, and the updated versions of the protocols are adopted as soon as possible. Encryption is used to protect covered information on mobile/removable media and across communication lines based on predetermined criteria. Key management is implemented based on specific roles and responsibilities, and in consideration of national and international regulations, restrictions, and issues.

Control Category Encryption

Implementation status 1 of 1 Environment (100%)

Host Hardening

Aptible host operating systems are hardened based on the Center for Internet Security's Security Configuration Benchmark for the OS and version in use. For all operating systems:

- Operating systems are installed on hosts only from bare images, and only via automated configuration management. Services installed can be enumerated upon request.
- Host password logins are disabled. SSH root keys are not permitted.
- No user SSH keys are permitted on hosts by default. Aptible internal workforce user access is configured only on a per-user basis, and only when necessary to provide customer support.
- Swap is disabled to avoid writing in-memory secrets to unencrypted volumes.
- Command history for shell sessions is disabled.
- Non-default SSH ports are used.
- No password-based services are installed automatically. Password-based services (such as PostgreSQL) are provisioned only with unique, per-resource, Aptible-generated passphrases. No default passwords are permitted.
- Host security updates are automated.
- All host ports are opened only via whitelist.

Control Category Vulnerability Management

Implementation status 1 of 1 Environment (100%)

Kernel Vulnerability Management

The operating system kernel needs to be consistently checked for critical vulnerabilities that could hamper the overall security of mission critical data and IP. Aptible constantly monitors for any system software libraries that have patches available and applies them automatically on a daily basis via Ubuntu's unattended upgrades feature. For kernel patches or other security updates that cannot be applied via Ubuntu's unattended upgrades, patches are applied within a timeframe dictated by severity.

Control Category Vulnerability Management

Implementation status 1 of 1 Environment (100%)

Secure Infrastructure Access, Development and Testing Practices

Aptible services provide system configurations as code. Any updates on critical systems are tested before being pushed out into the code. Aptible source code for sensitive/confidential software is stored in private repositories. These are restricted based on business need. Aptible development, test, and operation systems are separated into their own environments to reduce risks of unauthorized access or changes.

Software is utilized by Aptible to assist with compliance check such as CloudWatch and CloudTrail. All Aptible system configuration requirements are stored in code so systems spin-up from the images built, no manual interaction is required. Deployment of these images is performed through OpsWork and Cloud Formation. Compliance checks are built into system and run nightly. Integration tests are performed in order to deploy current version of all systems. Interoperability requirements are tested for the APIs in this process. Aptible services provide system configurations as code. Systems are established with a secure and current baseline configuration based on secure coding guidelines. The code is tested on a frequent basis and Aptible relies heavily on automated tools to check for common vulnerabilities.

Aptible identifies unauthorized (blacklisted) software on the information system, prevents program execution in accordance with a list of unauthorized (blacklisted) software programs, employs an allow-all, deny-by exception policy to prohibit execution of known unauthorized (blacklisted) software, and reviews and updates the list of unauthorized (blacklisted) software programs annually.

All remote access by Aptible employees is be configured with specific software to enhance the security of the connection and use. Aptible employees use laptops and workstations enrolled in mobile device management (MDM) that inventories the devices, verifies MDM is operating, and verifies MDM policies can't be altered/disabled without detection.

Control Category	Organization and platform security
Implementation status	1 of 1 Environment (100%)

Infrastructure Penetration Tested

The organization undergoes regular penetration testing by an independent agent or team, at least every 365 days, on defined information systems or system components; conducts such testing from outside as well as inside the network perimeter; and such testing includes tests for the protection of unprotected system information that would be useful to attackers.

Control Category	Organization and platform security
Implementation status	1 of 1 Environment (100%)

Industry Certified and Approved

Aptible's infrastructure has gone through multiple independent audits to obtain and maintain SOC 2 certification. Aptible is also HITRUST CSF-certified.

Control Category	Organization and platform security
Implementation status	1 of 1 Environment (100%)

High-availability (HA) App Deployment

Aptible automatically deploys horizontally-scaled app and database containers across separate AWS availability zones, to ensure high availability. Availability Zones are multiple, isolated locations within each region. When distributed across multiple Availability Zones, when one instance fails, applications can be designed so that an instance in another Availability Zone can handle requests

Control Category	Business Continuity
Implementation status	0 of 0 Resources (0%)

Database Replication and Clustering

In order to avoid any loss of sensitive data and ensure business continuity, database replication and clustering across multiple availability zones is recommended. Aptible supports replication or clustering for a number of databases, and when configured, will automatically deploy customer database containers across different availability zones

Control Category	Business Continuity
Implementation status	0 of 0 Resources (0%)

Automated Backups

Aptible maintains the integrity and security of the backup copies to ensure future availability, and any potential accessibility problems with the backup copies are identified and mitigated in the event of an area-wide disaster. Covered information is backed-up in an encrypted format to ensure confidentiality. Aptible performs incremental or differential backups daily and full backups weekly to separate media. Aptible ensures a current, retrievable copy of covered information is available before movement of servers. Aptible tests backup information following each backup to verify media reliability and information integrity, and at least annually thereafter.

The backups are stored in a physically secure remote location, at a sufficient distance to make them reasonably immune from damage to data at the primary site, and reasonable physical and environmental controls are in place to ensure their protection at the remote location.

Control Category	Business Continuity
Implementation status	0 of 0 Resources (0%)

Cross-region Backups

Aptible maintains the integrity and security of the backup copies to ensure future availability, and any potential accessibility problems with the backup copies are identified and mitigated in the event of an area-wide disaster. Covered information is backed up in an encrypted format to ensure confidentiality. Aptible performs incremental or differential backups daily and full backups weekly to separate media. Aptible ensures that a current, retrievable copy of covered information is available before the movement of servers. Aptible tests backup information following each backup to verify media reliability and data integrity, and at least annually after that.

The backups are stored in a physically secure remote location, at a sufficient distance to make them reasonably immune from damage to data at the primary site, and reasonable physical and environmental controls are in place to ensure their protection at the remote location.

Backups are performed as volume snapshots of the already encrypted data volume, so the encryption key and algorithm used for Database Encryption apply to all Backups of a given Database.

Control Category Business Continuity

Implementation status 0 of 0 Resources (0%)

Zero-downtime Deployments

Zero downtime deployment is a method where a website or application is never down or in an unstable state during the deployment process. For containers exposed via HTTP(S) endpoints, Aptible automatically provides zero-downtime deployments by ensuring that new containers are accepting traffic before terminating old containers.

Specifically, the process is:

- Launch new containers.
- Wait for the new containers to pass Health Checks to ensure they respond to requests with valid HTTP responses
- Register the new containers with the endpoint's load balancer. Wait for registration to complete.
- Deregister the old containers from the endpoint's load balancer. Wait for deregistration to complete (in-flight requests are given 15 seconds to complete).
- Shutdown the old containers.

Control Category Business Continuity

Implementation status 0 of 0 Resources (0%)

Database Encryption at Rest

Databases run in the database layer of the Aptible stack, on a private subnet accessible only from app or bastion layer. SSL/TLS is required if the database protocol supports it. Disk volumes backing databases are encrypted at the filesystem level using Aptible-managed AES-256, or AES-128 for legacy databases. Aptible manages the creation, access security, and destruction of encryption keys. Customers of Aptible can rekey the database by dumping/restoring it at any time. Customers of Aptible may implement additional controls, such as database security policies or row-/column-level encryption with keys they manage.

Control Category Encryption

Implementation status 0 of 0 Resources (0%)

Forced TLS/HTTPS

HTTPS is HTTP with encryption. The main difference between the two protocols is that HTTPS uses TLS (SSL) to encrypt normal HTTP requests and responses. As a result, HTTPS is far more secure than HTTP. By default, Aptible HTTP(S) endpoints accept traffic over both HTTP and HTTPS.

To disallow HTTP and redirect traffic to HTTPS at the endpoint level, customers can set the `FORCE_SSL` configuration variable to true for heightened security.

Control Category Encryption

Implementation status 0 of 0 Resources (0%)

Standards-compliant TLS Configuration

Aptible uses FIPS-validated cryptographic mechanisms during transmission to prevent unauthorized disclosure of information and detect changes to information unless otherwise protected by organization-defined alternative physical measures. Aptible formally addresses multiple safeguards before allowing the use of information systems for information exchange. Aptible establishes terms and conditions, consistent with any trust relationship established with other organizations owning, operating, and/or maintaining external information systems, allowing authorized individuals to (i) access the information system from external information systems; and (ii) process, store or transmit organization-controlled information using external information systems. Cryptography is used to protect the confidentiality and integrity of remote access sessions to the internal network and to external systems. Strong cryptography protocols are used to safeguard covered information during transmission over less trusted/open public networks. Aptible ensures that communication protection requirements, including the security of exchanges of information, are the subject of policy development and compliance audits. Remote (external) access to the organization's information assets and access to external information assets (for which the organization has no control) is based on clearly defined terms and conditions.

Endpoints let customers expose their application containers on Aptible to clients over the public internet or their stack's internal network. All new endpoints provisioned by Aptible come with an Application Load Balancer where weak TLS ciphers are disabled by default.

Control Category Encryption

Implementation status 0 of 0 Resources (0%)

Database Endpoint Filtering

Database Endpoints let customers expose a database to the public internet. Malicious traffic feeding malware variants to databases housing sensitive data can be a security issue if the customer's business is targeted by attackers. Database Endpoints support IP Filtering to restrict connections to database to a set of pre-approved IP addresses.

Control Category Network Protection

Implementation status 0 of 0 Resources (0%)

Automated SSL/TLS Certificate Renewal

Aptible fully automates the configuration and renewal of SSL/TLS certificates for endpoints with a "Managed HTTPS" domain configured. Enable this control by switching your endpoints to use "Managed HTTPS."

Control Category Encryption

Implementation status 0 of 0 Resources (0%)