

The following tables show incorrect NL to SQL translation cases in Spider and BIRD datasets.

- "Modified SQL" is the column of checked and fixed SQL by our manual effort with the help of SQLDRILLER.
- "Tag" represents the incorrect pattern of the original SQL.
- "Follow Consistency" represents whether the execution result of the original SQL is consistent with SQLDRILLER.
- "Correctly Fixed" represents whether the automatic fix of SQLDRILLER is correct or not.

Table 1: Incorrect case list of Spider train set.

Case Id	NL	Original SQL	Modified SQL	Tag	Follow Consistency	Correctly Fixed
0	How many heads of the departments are older than 56 ?	SELECT count(*) FROM head WHERE age > 56	SELECT COUNT(*) FROM head WHERE age > 56 AND head_id IN (SELECT head_id FROM management)	semantic error	0	1
8	In which year were most departments established?	SELECT creation FROM department GROUP BY creation ORDER BY count(*) DESC LIMIT 1	SELECT creation FROM department GROUP BY creation HAVING count(*) = (SELECT count(*) FROM department GROUP BY creation ORDER BY count(*) DESC LIMIT 1)	limit 1	0	0
9	Show the name and number of employees for the departments managed by heads whose temporary acting value is 'Yes'?	SELECT T1.name , T1.num_employees FROM department AS T1 JOIN management AS T2 ON T1.department_id = T2.department_id WHERE T2.temporary_acting = 'Yes'	SELECT department.name, department.num_employees FROM department WHERE department.department_id IN (SELECT management.department_id FROM management JOIN head ON management.head_id = head.head_id WHERE management.temporary_acting = 'Yes')	join -> in-sub	0	1
32	List the official name and status of the city with the largest population.	SELECT Official_Name , Status FROM city ORDER BY Population DESC LIMIT 1	SELECT official_name, status FROM city WHERE population = (SELECT MAX(population) FROM city)	limit 1	0	1
33	What is the official name and status of the city with the most residents?	SELECT Official_Name , Status FROM city ORDER BY Population DESC LIMIT 1	SELECT official_name, status FROM city WHERE population = (SELECT MAX(population) FROM city)	limit 1	0	1
38	Show the status of the city that has hosted the greatest number of competitions.	SELECT T1.Status FROM city AS T1 JOIN farm_competition AS T2 ON T1.City_ID = T2.Host_city_ID GROUP BY T2.Host_city_ID ORDER BY COUNT(*) DESC LIMIT 1	SELECT c.status FROM city c JOIN farm_competition fc ON c.city_id = fc.host_city_id GROUP BY c.city_id HAVING COUNT(DISTINCT fc.competition_id) = (SELECT COUNT(DISTINCT competition_id) FROM farm_competition GROUP BY host_city_id ORDER BY COUNT(DISTINCT competition_id) DESC LIMIT 1)	limit 1	0	1
39	What is the status of the city that has hosted the most competitions?	SELECT T1.Status FROM city AS T1 JOIN farm_competition AS T2 ON T1.City_ID = T2.Host_city_ID GROUP BY T2.Host_city_ID ORDER BY COUNT(*) DESC LIMIT 1	SELECT Status FROM (SELECT T1.Status, rank() over (ORDER BY COUNT(*) DESC) AS rk FROM city AS T1 LEFT JOIN farm_competition AS T2 ON T1.City_ID = T2.Host_city_ID GROUP BY T2.Host_city_ID) WHERE rk = 1	limit 1; join -> left join	1	0
43	What are the statuses and average populations of each city?	SELECT Status , avg(Population) FROM city GROUP BY Status	SELECT status, population FROM city	semantic error; nlq vague: group by what	0	0
44	Please show the different statuses, ordered by the number of cities that have each.	SELECT Status FROM city GROUP BY Status ORDER BY COUNT(*) ASC	SELECT DISTINCT status FROM city ORDER BY COUNT(city_id) OVER (PARTITION BY status) DESC	order matters	0	1
46	List the most common type of Status across cities.	SELECT Status FROM city GROUP BY Status ORDER BY COUNT(*) DESC LIMIT 1	SELECT Status FROM (SELECT Status, rank() over (ORDER BY COUNT(*) DESC) as rk FROM city GROUP BY Status) WHERE rk = 1	limit 1	1	0
47	What is the most common status across all cities?	SELECT Status FROM city GROUP BY Status ORDER BY COUNT(*) DESC LIMIT 1	SELECT status FROM city GROUP BY status HAVING COUNT(city_id) = (SELECT MAX(num_cities) FROM (SELECT COUNT(city_id) as num_cities FROM city GROUP BY status))	limit 1	0	1

56	which course has most number of registered students?	SELECT T1.course_name FROM courses AS T1 JOIN student_course_registrations AS T2 ON T1.course_id = T2.course_id GROUP BY T1.course_id ORDER BY count(*) DESC LIMIT 1	SELECT course_name FROM (SELECT T1.course_name, rank() over (ORDER BY count(*) DESC) as rk FROM courses AS T1 LEFT JOIN student_course_registrations AS T2 ON T1.course_id = T2.course_id GROUP BY T1.course_id) WHERE rk = 1	limit 1; join -> left join	0	0
57	What is the name of the course with the most registered students?	SELECT T1.course_name FROM courses AS T1 JOIN student_course_registrations AS T2 ON T1.course_id = T2.course_id GROUP BY T1.course_id ORDER BY count(*) DESC LIMIT 1	SELECT course_name FROM (SELECT T1.course_name, rank() over (ORDER BY count(*) DESC) as rk FROM courses AS T1 LEFT JOIN student_course_registrations AS T2 ON T1.course_id = T2.course_id GROUP BY T1.course_id) WHERE rk = 1	limit 1; join -> left join	0	0
58	what is id of students who registered some courses but the least number of courses in these students?	SELECT student_id FROM student_course_registrations GROUP BY student_id ORDER BY count(*) LIMIT 1	SELECT student_id FROM student_course_registrations GROUP BY student_id HAVING COUNT(course_id) = (SELECT MIN(CourseCount) FROM (SELECT COUNT(course_id) AS CourseCount FROM student_course_registrations GROUP BY student_id))	limit 1	0	1
59	What are the ids of the students who registered for some courses but had the least number of courses for all students?	SELECT student_id FROM student_course_registrations GROUP BY student_id ORDER BY count(*) LIMIT 1	SELECT student_id FROM student_course_registrations GROUP BY student_id HAVING COUNT(course_id) = (SELECT MIN(course_count) FROM (SELECT COUNT(course_id) AS course_count FROM student_course_registrations GROUP BY student_id))	limit 1	0	1
64	List the id of students who attended some courses?	SELECT student_id FROM student_course_attendance	SELECT DISTINCT student_id FROM student_course_attendance	lack distinct	0	1
65	What are the ids of all students who have attended at least one course?	SELECT student_id FROM student_course_attendance	SELECT DISTINCT student_id FROM student_course_attendance	lack distinct	0	1
67	What is detail of the student who most recently registered course?	SELECT T2.student_details FROM student_course_registrations AS T1 JOIN students AS T2 ON T1.student_id = T2.student_id ORDER BY T1.registration_date DESC LIMIT 1	SELECT student_details FROM (SELECT T2.student_details, rank() over (ORDER BY T1.registration_date DESC) as rk FROM student_course_registrations AS T1 JOIN students AS T2 ON T1.student_id = T2.student_id) WHERE rk = 1	limit 1	1	0
68	What details do we have on the students who registered for courses most recently?	SELECT T2.student_details FROM student_course_registrations AS T1 JOIN students AS T2 ON T1.student_id = T2.student_id ORDER BY T1.registration_date DESC LIMIT 1	SELECT student_details FROM (SELECT T2.student_details, rank() over (ORDER BY T1.registration_date DESC) as rk FROM student_course_registrations AS T1 JOIN students AS T2 ON T1.student_id = T2.student_id) WHERE rk = 1	limit 1	0	0
69	How many students attend course English?	SELECT count(*) FROM courses AS T1 JOIN student_course_attendance AS T2 ON T1.course_id = T2.course_id WHERE T1.course_name = 'English'	SELECT count(DISTINCT student_id) FROM courses AS T1 JOIN student_course_attendance AS T2 ON T1.course_id = T2.course_id WHERE T1.course_name = 'English'	lack distinct	0	0
70	How many students are attending English courses?	SELECT count(*) FROM courses AS T1 JOIN student_course_attendance AS T2 ON T1.course_id = T2.course_id WHERE T1.course_name = 'English'	SELECT COUNT(DISTINCT student_id) FROM student_course_attendance WHERE course_id IN (SELECT course_id FROM courses WHERE course_name = 'English')	lack distinct	0	1
75	Find id of the candidate who most recently accessed the course?	SELECT candidate_id FROM candidate_assessments ORDER BY assessment_date DESC LIMIT 1	SELECT candidate_id FROM candidate_assessments WHERE assessment_date = (SELECT max(assessment_date) FROM candidate_assessments)	limit 1	0	1
76	What is the id of the candidate who most recently accessed the course?	SELECT candidate_id FROM candidate_assessments ORDER BY assessment_date DESC LIMIT 1	SELECT candidate_id FROM candidate_assessments WHERE assessment_date = (SELECT max(assessment_date) FROM candidate_assessments)	limit 1	1	0
77	What is detail of the student who registered the most number of courses?	SELECT T1.student_details FROM students AS T1 JOIN student_course_registrations AS T2 ON T1.student_id = T2.student_id GROUP BY T1.student_id ORDER BY count(*) DESC LIMIT 1	SELECT student_details FROM (SELECT T1.student_details, rank() over (ORDER BY count(*) DESC) as rk FROM students AS T1 LEFT JOIN student_course_registrations AS T2 ON T1.student_id = T2.student_id GROUP BY T1.student_id) WHERE rk = 1	limit 1; join -> left join	1	0

78	What are the details of the student who registered for the most number of courses?	SELECT T1.student_details FROM students AS T1 JOIN student_course_registrations AS T2 ON T1.student_id = T2.student_id GROUP BY T1.student_id ORDER BY count(*) DESC LIMIT 1	SELECT student_details FROM (SELECT T1.student_details, rank() over (ORDER BY count(*) DESC) as rk FROM students AS T1 LEFT JOIN student_course_registrations AS T2 ON T1.student_id = T2.student_id GROUP BY T1.student_id) WHERE rk = 1	limit 1; join -> left join	1	0
81	How many registered students do each course have? List course name and the number of their registered students?	SELECT T3.course_name, count(*) FROM students AS T1 JOIN student_course_registrations AS T2 ON T1.student_id = T2.student_id JOIN courses AS T3 ON T2.course_id = T3.course_id GROUP BY T2.course_id	SELECT T3.course_name, count(*) FROM students AS T1 LEFT JOIN student_course_registrations AS T2 ON T1.student_id = T2.student_id JOIN courses AS T3 ON T2.course_id = T3.course_id GROUP BY T2.course_id	join -> left join	0	0
82	For each course id, how many students are registered and what are the course names?	SELECT T3.course_name, count(*) FROM students AS T1 JOIN student_course_registrations AS T2 ON T1.student_id = T2.student_id JOIN courses AS T3 ON T2.course_id = T3.course_id GROUP BY T2.course_id	SELECT sc.course_id, COUNT(sc.student_id) AS num_registered_students, c.course_name FROM student_course_registrations sc JOIN courses c ON sc.course_id = c.course_id GROUP BY sc.course_id, c.course_name	join -> left join	0	1
83	Find id of candidates whose assessment code is 'Pass'?	SELECT candidate_id FROM candidate_assessments WHERE assessment_outcome_code = 'Pass'	SELECT candidate_id FROM candidates WHERE candidate_id IN (SELECT candidate_id FROM candidate_assessments WHERE assessment_outcome_code = 'Pass')	lack distinct	0	1
85	Find the cell mobile number of the candidates whose assessment code is 'Fail'?	SELECT T3.cell_mobile_number FROM candidates AS T1 JOIN candidate_assessments AS T2 ON T1.candidate_id = T2.candidate_id JOIN people AS T3 ON T1.candidate_id = T3.person_id WHERE T2.assessment_outcome_code = 'Fail'	SELECT cell_mobile_number FROM people WHERE person_id IN (SELECT candidate_id FROM candidates WHERE candidate_id IN (SELECT candidate_id FROM candidate_assessments WHERE assessment_outcome_code = 'Fail'))	join -> in-sub	0	1
86	What are the cell phone numbers of the candidates that received an assessment code of 'Fail'?	SELECT T3.cell_mobile_number FROM candidates AS T1 JOIN candidate_assessments AS T2 ON T1.candidate_id = T2.candidate_id JOIN people AS T3 ON T1.candidate_id = T3.person_id WHERE T2.assessment_outcome_code = 'Fail'	SELECT cell_mobile_number FROM people WHERE person_id IN (SELECT candidate_id FROM candidate_assessments WHERE assessment_outcome_code = 'Fail')	join -> in-sub	0	1
87	What are the id of students who registered course 301?	SELECT student_id FROM student_course_attendance WHERE course_id = 301	SELECT student_id FROM student_course_registrations WHERE course_id = 301	semantic error	0	1
88	What are the ids of the students who registered for course 301?	SELECT student_id FROM student_course_attendance WHERE course_id = 301	SELECT student_id FROM student_course_registrations WHERE course_id = 301	semantic error	0	1
89	What is the id of the student who most recently registered course 301?	SELECT student_id FROM student_course_attendance WHERE course_id = 301 ORDER BY date_of_attendance DESC LIMIT 1	SELECT student_id FROM student_course_attendance WHERE course_id = 301 AND date_of_attendance = (SELECT max(date_of_attendance) FROM student_course_attendance WHERE course_id = 301)	limit 1	0	0
90	What are the ids of the students who registered for course 301 most recently?	SELECT student_id FROM student_course_attendance WHERE course_id = 301 ORDER BY date_of_attendance DESC LIMIT 1	SELECT student_id FROM student_course_attendance WHERE course_id = 301 AND date_of_attendance = (SELECT max(date_of_attendance) FROM student_course_attendance WHERE course_id = 301)	limit 1	0	0
103	What are all info of students who registered courses but not attended courses?	SELECT * FROM student_course_registrations WHERE student_id NOT IN (SELECT student_id FROM student_course_attendance)	SELECT * FROM students WHERE student_id IN (SELECT student_id FROM student_course_registrations EXCEPT SELECT student_id FROM student_course_attendance)	semantic error; nlq vague: what do all info mean? student info or people info?	0	1
104	What are all details of the students who registered but did not attend any course?	SELECT * FROM student_course_registrations WHERE student_id NOT IN (SELECT student_id FROM student_course_attendance)	SELECT student_details FROM Students WHERE student_id IN (SELECT student_id FROM student_course_registrations) AND student_id NOT IN (SELECT student_id FROM student_course_attendance)	semantic error	0	0

119	What is the id of the trip that has the shortest duration?	SELECT id FROM trip ORDER BY duration LIMIT 1	SELECT id FROM trip WHERE duration = (SELECT MIN(duration) FROM trip)	limit 1	0	1
120	What is the id of the shortest trip?	SELECT id FROM trip ORDER BY duration LIMIT 1	SELECT id FROM trip AS t1 WHERE NOT EXISTS (SELECT 1 FROM trip AS t2 WHERE t2.duration < t1.duration)	limit 1	0	1
124	For each zip code, what is the average mean temperature for all dates that start with '8'?	SELECT zip_code , avg(mean_temperature_f) FROM weather WHERE date LIKE '8/%' GROUP BY zip_code	SELECT zip_code, AVG(mean_temperature_f) FROM weather WHERE date LIKE '8/%' GROUP BY zip_code	str	0	1
133	Which start station had the most trips starting from August? Give me the name and id of the station.	SELECT start_station_name , start_station_id FROM trip WHERE start_date LIKE '8/%' GROUP BY start_station_name ORDER BY COUNT(*) DESC LIMIT 1	SELECT start_station_name, start_station_id FROM (SELECT start_station_name, start_station_id, rank() over (ORDER BY COUNT(*) DESC) as rk FROM trip WHERE start_date LIKE '8/%' GROUP BY start_station_id) WHERE rk = 1	limit 1; group by non-key	1	0
134	What are the start station's name and id for the one that had the most start trips in August?	SELECT start_station_name , start_station_id FROM trip WHERE start_date LIKE '8/%' GROUP BY start_station_name ORDER BY COUNT(*) DESC LIMIT 1	SELECT start_station_name, start_station_id FROM (SELECT start_station_name, start_station_id, rank() over (ORDER BY COUNT(*) DESC) as rk FROM trip WHERE start_date LIKE '8/%' GROUP BY start_station_id) WHERE rk = 1	limit 1; group by non-key	1	0
135	Which bike traveled the most often in zip code 94002?	SELECT bike_id FROM trip WHERE zip_code = 94002 GROUP BY bike_id ORDER BY COUNT(*) DESC LIMIT 1	SELECT bike_id FROM trip WHERE zip_code = 94002 GROUP BY bike_id HAVING COUNT(*) = (SELECT COUNT(*) FROM trip WHERE zip_code = 94002 GROUP BY bike_id ORDER BY COUNT(*) DESC LIMIT 1)	limit 1	0	0
136	What is the id of the bike that traveled the most in 94002?	SELECT bike_id FROM trip WHERE zip_code = 94002 GROUP BY bike_id ORDER BY COUNT(*) DESC LIMIT 1	SELECT bike_id FROM trip WHERE zip_code = 94002 GROUP BY bike_id HAVING COUNT(*) = (SELECT COUNT(*) FROM trip WHERE zip_code = 94002 GROUP BY bike_id ORDER BY COUNT(*) DESC LIMIT 1)	limit 1	1	0
137	How many days had both mean humidity above 50 and mean visibility above 8?	SELECT COUNT(*) FROM weather WHERE mean_humidity > 50 AND mean_visibility_miles > 8	SELECT COUNT(DISTINCT date) FROM weather WHERE mean_humidity > 50 AND mean_visibility_miles > 8	lack distinct	0	1
138	What is the number of days that had an average humidity above 50 and an average visibility above 8?	SELECT COUNT(*) FROM weather WHERE mean_humidity > 50 AND mean_visibility_miles > 8	SELECT COUNT(DISTINCT date) FROM weather WHERE mean_humidity > 50 AND mean_visibility_miles > 8	lack distinct	0	1
139	What is the latitude, longitude, city of the station from which the shortest trip started?	SELECT T1.lat , T1.long , T1.city FROM station AS T1 JOIN trip AS T2 ON T1.id = T2.start_station_id ORDER BY T2.duration LIMIT 1	SELECT lat, long, city FROM station WHERE id IN (SELECT start_station_id FROM trip WHERE duration = (SELECT min(duration) FROM trip))	limit 1; join -> in-sub	1	0
140	What is the latitude, longitude, and city of the station from which the trip with smallest duration started?	SELECT T1.lat , T1.long , T1.city FROM station AS T1 JOIN trip AS T2 ON T1.id = T2.start_station_id ORDER BY T2.duration LIMIT 1	SELECT lat, long, city FROM station WHERE id IN (SELECT start_station_id FROM trip WHERE duration = (SELECT min(duration) FROM trip))	limit 1; join -> in-sub	0	0
145	What is the 3 most common cloud cover rates in the region of zip code 94107?	SELECT cloud_cover FROM weather WHERE zip_code = 94107 GROUP BY cloud_cover ORDER BY COUNT (*) DESC LIMIT 3	SELECT cloud_cover FROM (SELECT cloud_cover, rank() over (ORDER BY COUNT(*) DESC) as rk FROM weather WHERE zip_code = 94107 GROUP BY cloud_cover) WHERE rk <= 3	limit n	1	0
147	What is the zip code in which the average mean sea level pressure is the lowest?	SELECT zip_code FROM weather GROUP BY zip_code ORDER BY avg(mean_sea_level_pressure_inches) LIMIT 1	SELECT zip_code FROM weather GROUP BY zip_code HAVING AVG(mean_sea_level_pressure_inches) = (SELECT MIN(avg_pres) FROM (SELECT AVG(mean_sea_level_pressure_inches) AS avg_pres FROM weather GROUP BY zip_code))	limit 1	0	1

148	What is the zip code that has the lowest average mean sea level pressure?	SELECT zip_code FROM weather GROUP BY zip_code ORDER BY avg(mean_sea_level_pressure_inches) LIMIT 1	SELECT zip_code FROM (SELECT zip_code, AVG(mean_sea_level_pressure_inches) AS average_pressure FROM weather GROUP BY zip_code) WHERE average_pressure = (SELECT MIN(avg_mean_pressure) FROM (SELECT AVG(mean_sea_level_pressure_inches) AS avg_mean_pressure FROM weather GROUP BY zip_code))	limit 1	0	1
155	Give me ids for all the trip that took place in a zip code area with average mean temperature above 60.	SELECT T1.id FROM trip AS T1 JOIN weather AS T2 ON T1.zip_code = T2.zip_code GROUP BY T2.zip_code HAVING avg(T2.mean_temperature_f) > 60	SELECT id FROM trip WHERE zip_code IN (SELECT zip_code FROM weather GROUP BY zip_code HAVING AVG(mean_temperature_f) > 60)	join -> in-sub	0	1
156	For each zip code, find the ids of all trips that have a higher average mean temperature above 60?	SELECT T1.id FROM trip AS T1 JOIN weather AS T2 ON T1.zip_code = T2.zip_code GROUP BY T2.zip_code HAVING avg(T2.mean_temperature_f) > 60	SELECT DISTINCT T1.id FROM trip AS T1 JOIN weather AS T2 ON T1.zip_code = T2.zip_code GROUP BY T2.zip_code HAVING avg(T2.mean_temperature_f) > 60	join -> in-sub; nlq vague: col to select	0	0
163	Which trip started from the station with the largest dock count? Give me the trip id.	SELECT T1.id FROM trip AS T1 JOIN station AS T2 ON T1.start_station_id = T2.id ORDER BY T2.dock_count DESC LIMIT 1	SELECT t.id FROM trip t INNER JOIN station s on t.start_station_id = s.id WHERE s.dock_count = (SELECT MAX(dock_count) FROM station)	limit 1	0	1
164	What is the id of the trip that started from the station with the highest dock count?	SELECT T1.id FROM trip AS T1 JOIN station AS T2 ON T1.start_station_id = T2.id ORDER BY T2.dock_count DESC LIMIT 1	SELECT id FROM trip WHERE start_station_id IN (SELECT id FROM station WHERE dock_count = (SELECT max(dock_count) FROM station))	limit1	0	0
167	In zip code 94107, on which day neither Fog nor Rain was not observed?	SELECT date FROM weather WHERE zip_code = 94107 AND EVENTS != 'Fog' AND EVENTS != 'Rain'	SELECT date FROM weather WHERE zip_code = 94107 AND (EVENTS = 'Fog' OR EVENTS = 'Rain')	semantic error	1	0
171	What are names of stations that have average bike availability above 10 and are not located in San Jose city?	SELECT T1.name FROM station AS T1 JOIN status AS T2 ON T1.id = T2.station_id GROUP BY T2.station_id HAVING avg(bikes_available) > 10 EXCEPT SELECT name FROM station WHERE city = 'San Jose'	SELECT T1.name FROM station AS T1 JOIN status AS T2 ON T1.id = T2.station_id WHERE city = 'San Jose' GROUP BY T2.station_id HAVING avg(bikes_available) > 10	except non-key	1	0
172	What are the names of all stations that have more than 10 bikes available and are not located in San Jose?	SELECT T1.name FROM station AS T1 JOIN status AS T2 ON T1.id = T2.station_id GROUP BY T2.station_id HAVING avg(bikes_available) > 10 EXCEPT SELECT name FROM station WHERE city = 'San Jose'	SELECT station.name FROM station JOIN (SELECT station_id FROM status WHERE bikes_available > 10 EXCEPT SELECT id FROM station WHERE city = 'San Jose') ON station.id = station_id	except non-key	0	1
173	What are the name, latitude, and city of the station with the lowest latitude?	SELECT name, lat, city FROM station ORDER BY lat LIMIT 1	SELECT name, lat, city FROM station WHERE lat = (SELECT MIN(lat) FROM station)	limit 1	0	1
174	What is the name, latitude, and city of the station that is located the furthest South?	SELECT name, lat, city FROM station ORDER BY lat LIMIT 1	SELECT name, lat, city FROM station WHERE lat = (SELECT MIN(lat) FROM station)	limit 1	0	1
175	What are the date, mean temperature and mean humidity for the top 3 days with the largest max gust speeds?	SELECT date, mean_temperature_f, mean_humidity FROM weather ORDER BY max_gust_speed_mph DESC LIMIT 3	SELECT date, mean_temperature_f, mean_humidity FROM (SELECT date, mean_temperature_f, mean_humidity, rank() over (ORDER BY max_gust_speed_mph DESC) as rk FROM weather) WHERE rk <= 3	limit n	1	0

176	What is the date, average temperature and mean humidity for the days with the 3 largest maximum gust speeds?	SELECT date , mean_temperature_f , mean_humidity FROM weather ORDER BY max_gust_speed_mph DESC LIMIT 3	SELECT date, mean_temperature_f, mean_humidity FROM (SELECT date, mean_temperature_f, mean_humidity, rank() over (ORDER BY max_gust_speed_mph DESC) as rk FROM weather) WHERE rk <= 3	limit n	1	0
179	Find the ids and names of stations from which at least 200 trips started.	SELECT start_station_id, start_station_name FROM trip GROUP BY start_station_name HAVING COUNT(*) >= 200	SELECT start_station_id, start_station_name FROM trip GROUP BY start_station_id HAVING COUNT(*) >= 200	group by non-key	1	0
180	What are the ids and names of all start stations that were the beginning of at least 200 trips?	SELECT start_station_id, start_station_name FROM trip GROUP BY start_station_name HAVING COUNT(*) >= 200	SELECT start_station_id, start_station_name FROM trip GROUP BY start_station_id HAVING COUNT(*) >= 200	group by non-key	1	0
185	What are the dates that had the top 5 cloud cover rates? Also tell me the cloud cover rate.	SELECT date , cloud_cover FROM weather ORDER BY cloud_cover DESC LIMIT 5	SELECT date, cloud_cover FROM (SELECT date, cloud_cover, rank() over (ORDER BY cloud_cover DESC) as rk FROM weather ORDER BY cloud_cover DESC) WHERE rk <= 5	limit n	1	0
186	What are the dates that have the 5 highest cloud cover rates and what are the rates?	SELECT date , cloud_cover FROM weather ORDER BY cloud_cover DESC LIMIT 5	SELECT date, cloud_cover FROM weather WHERE cloud_cover in (SELECT cloud_cover FROM weather ORDER BY cloud_cover DESC LIMIT 5) ORDER BY cloud_cover DESC	limit n	0	1
187	What are the ids and durations of the trips with the top 3 durations?	SELECT id , duration FROM trip ORDER BY duration DESC LIMIT 3	SELECT id, duration FROM (SELECT id, duration, rank() over (ORDER BY duration DESC) as rk FROM trip) WHERE rk <= 3	limit n	1	0
188	What are the ids of the trips that lasted the longest and how long did they last?	SELECT id , duration FROM trip ORDER BY duration DESC LIMIT 3	SELECT id, duration FROM trip WHERE duration = (SELECT MAX(duration) FROM trip)	limit n	0	1
189	For each station, return its longitude and the average duration of trips that started from the station.	SELECT T1.name , T1.long , avg(T2.duration) FROM station AS T1 JOIN trip AS T2 ON T1.id = T2.start_station_id GROUP BY T2.start_station_id	SELECT station.long, AVG(trip.duration) AS avg_duration FROM station LEFT JOIN trip ON station.id = trip.start_station_id GROUP BY station.id	join -> left join	0	1
190	For each start station id, what is its name, longitude and average duration of trips started there?	SELECT T1.name , T1.long , avg(T2.duration) FROM station AS T1 JOIN trip AS T2 ON T1.id = T2.start_station_id GROUP BY T2.start_station_id	SELECT T1.id, T1.name, T1.long, avg(T2.duration) FROM station AS T1 LEFT JOIN trip AS T2 ON T1.id = T2.start_station_id GROUP BY T2.start_station_id	join -> left join; semantic error: output col	0	0
191	For each station, find its latitude and the minimum duration of trips that ended at the station.	SELECT T1.name , T1.lat , min(T2.duration) FROM station AS T1 JOIN trip AS T2 ON T1.id = T2.end_station_id GROUP BY T2.end_station_id	SELECT station.lat, MIN(trip.duration) FROM station LEFT JOIN trip ON trip.end_station_id = station.id GROUP BY station.id	join -> left join	0	1
192	For each end station id, what is its name, latitude, and minimum duration for trips ended there?	SELECT T1.name , T1.lat , min(T2.duration) FROM station AS T1 JOIN trip AS T2 ON T1.id = T2.end_station_id GROUP BY T2.end_station_id	SELECT T1.id, T1.name, T1.long, min(T2.duration) FROM station AS T1 LEFT JOIN trip AS T2 ON T1.id = T2.start_station_id GROUP BY T2.start_station_id	join -> left join; semantic error: output col	0	0
198	What are the ids of all trips that had a duration as long as the average trip duration in the zip code 94103?	SELECT id FROM trip WHERE duration >= (SELECT avg(duration) FROM trip WHERE zip_code = 94103)	SELECT t.id FROM trip t WHERE t.duration = (SELECT AVG(duration) FROM trip WHERE zip_code = '94103')	semantic error	0	1

200	What are the dates that have an average sea level pressure between 30.3 and 31?	SELECT date FROM weather WHERE mean_sea_level_pressure_inches BETWEEN 30.3 AND 31	SELECT date FROM weather WHERE mean_sea_level_pressure_inches BETWEEN 30.3 AND 31 GROUP BY date	semantic error	0	1
201	Find the day in which the difference between the max temperature and min temperature was the smallest. Also report the difference.	SELECT date , max_temperature_f - min_temperature_f FROM weather ORDER BY max_temperature_f - min_temperature_f LIMIT 1	SELECT date, max_temperature_f - min_temperature_f FROM weather WHERE (max_temperature_f - min_temperature_f) = (SELECT max_temperature_f - min_temperature_f FROM weather ORDER BY max_temperature_f - min_temperature_f limit 1)	limit 1	0	0
202	What are the days that had the smallest temperature range, and what was that range?	SELECT date , max_temperature_f - min_temperature_f FROM weather ORDER BY max_temperature_f - min_temperature_f LIMIT 1	SELECT date, (max_temperature_f - min_temperature_f) AS temperature_range FROM weather WHERE (max_temperature_f - min_temperature_f) = (SELECT MIN(max_temperature_f - min_temperature_f) FROM weather)	limit 1	0	1
207	What are the names of stations that are located in Palo Alto city but have never been the ending point of trips more than 100 times?	SELECT name FROM station WHERE city = 'Palo Alto' EXCEPT SELECT end_station_name FROM trip GROUP BY end_station_name HAVING count(*) > 100	SELECT s.name FROM station s WHERE s.city = 'Palo Alto' AND s.id NOT IN (SELECT t.end_station_id FROM trip t GROUP BY t.end_station_id HAVING COUNT(t.end_station_id) > 100)	except non-key	0	1
208	What are the names of the stations that are located in Palo Alto but have never been the ending point of the trips	SELECT name FROM station WHERE city = 'Palo Alto' EXCEPT SELECT end_station_name FROM trip GROUP BY end_station_name HAVING count(*) > 100	SELECT name FROM station WHERE city = 'Palo Alto' AND id NOT IN (SELECT end_station_id FROM trip)	except non-key	0	1
211	What is the average latitude and longitude of the starting points of all trips?	SELECT avg(T1.lat) , avg(T1.long) FROM station AS T1 JOIN trip AS T2 ON T1.id = T2.start_station_id	SELECT avg(lat), avg(long) FROM station WHERE id IN (SELECT start_station_id FROM trip)	join -> in-sub	1	0
212	What is the average latitude and longitude of all starting stations for the trips?	SELECT avg(T1.lat) , avg(T1.long) FROM station AS T1 JOIN trip AS T2 ON T1.id = T2.start_station_id	SELECT AVG(s.lat) AS average_latitude, AVG(s.long) AS average_longitude FROM station s WHERE s.id IN (SELECT start_station_id FROM trip)	join -> in-sub	0	1
214	List the writers of the books in ascending alphabetical order.	SELECT Writer FROM book ORDER BY Writer ASC	SELECT DISTINCT Writer FROM book ORDER BY Writer ASC	lack distinct	1	0
220	List the publisher of the publication with the highest price.	SELECT Publisher FROM publication ORDER BY Price DESC LIMIT 1	SELECT DISTINCT publisher FROM publication WHERE price = (SELECT MAX(price) FROM publication)	lack distinct, limit 1	0	1
221	List the publication dates of publications with 3 lowest prices.	SELECT Publication_Date FROM publication ORDER BY Price ASC LIMIT 3	SELECT publication_date FROM publication WHERE price IN (SELECT price FROM publication ORDER BY price LIMIT 3)	limit n	0	0
223	Show writers who have published a book with price more than 4000000.	SELECT T1.Writer FROM book AS T1 JOIN publication AS T2 ON T1.Book_ID = T2.Book_ID WHERE T2.Price > 4000000	SELECT DISTINCT b.writer FROM publication p INNER JOIN book b ON p.book_id = b.book_id WHERE p.price > 4000000	lack distinct	1	0
227	Please show the most common publication date.	SELECT Publication_Date FROM publication GROUP BY Publication_Date ORDER BY COUNT(*) DESC LIMIT 1	SELECT MAX(publication_date) FROM publication GROUP BY publication_date HAVING COUNT(*) = (SELECT MAX(pub_count) FROM (SELECT COUNT(*) AS pub_count FROM publication GROUP BY publication_date))	limit 1	0	1

244	What is the duration of the oldest actor?	SELECT Duration FROM actor ORDER BY Age DESC LIMIT 1	SELECT duration FROM actor WHERE age = (SELECT MAX(age) FROM actor)	limit 1	0	1
245	Return the duration of the actor with the greatest age.	SELECT Duration FROM actor ORDER BY Age DESC LIMIT 1	SELECT a.duration FROM actor a INNER JOIN (SELECT MAX(age) AS max_age FROM actor) b ON a.age = b.max_age	limit 1	0	1
256	Show names of musicals and the number of actors who have appeared in the musicals.	SELECT T2.Name , COUNT(*) FROM actor AS T1 JOIN musical AS T2 ON T1.Musical_ID = T2.Musical_ID GROUP BY T1.Musical_ID	SELECT name, (SELECT COUNT(actor_id) FROM actor WHERE musical_id = musical.musical_id) AS actor_count FROM musical	join -> left join	0	1
257	How many actors have appeared in each musical?	SELECT T2.Name , COUNT(*) FROM actor AS T1 JOIN musical AS T2 ON T1.Musical_ID = T2.Musical_ID GROUP BY T1.Musical_ID	SELECT T2.Name, COUNT(T1.Actor_ID) FROM musical AS T2 LEFT JOIN actor AS T1 ON T1.Musical_ID = T2.Musical_ID GROUP BY T1.Musical_ID	join -> left join	0	0
262	Please show the nominee who has been nominated the greatest number of times.	SELECT Nominee FROM musical GROUP BY Nominee ORDER BY COUNT(*) DESC LIMIT 1	WITH cnt AS (SELECT Nominee, COUNT(*) AS cnt FROM musical GROUP BY Nominee) SELECT Nominee FROM cnt WHERE cnt = (SELECT MAX(cnt) FROM cnt)	limit 1	1	0
263	Who is the nominee who has been nominated for the most musicals?	SELECT Nominee FROM musical GROUP BY Nominee ORDER BY COUNT(*) DESC LIMIT 1	SELECT nominee FROM musical GROUP BY nominee HAVING COUNT(DISTINCT musical_id) = (SELECT COUNT(musical_id) FROM musical GROUP BY nominee ORDER BY COUNT(musical_id) DESC LIMIT 1)	limit 1	0	1
264	List the most common result of the musicals.	SELECT RESULT FROM musical GROUP BY RESULT ORDER BY COUNT(*) DESC LIMIT 1	SELECT result FROM musical GROUP BY result HAVING COUNT(*) = (SELECT MAX(cnt) FROM (SELECT COUNT(*) AS cnt FROM musical GROUP BY result))	limit 1	0	1
265	Return the most frequent result across all musicals.	SELECT RESULT FROM musical GROUP BY RESULT ORDER BY COUNT(*) DESC LIMIT 1	SELECT result FROM musical GROUP BY result HAVING COUNT(result) = (SELECT MAX(ResultCount) FROM (SELECT COUNT(result) AS ResultCount FROM musical GROUP BY result))	limit 1	0	1
272	Show the musical nominee with award 'Bob Fosse' or 'Cleavant Derricks'.	SELECT Nominee FROM musical WHERE Award = 'Tony Award' OR Award = 'Cleavant Derricks'	SELECT nominee FROM musical WHERE award = 'Bob Fosse' OR award = 'Cleavant Derricks'	semantic error	0	1
273	Who are the nominees who were nominated for either of the Bob Fosse or Cleavant Derricks awards?	SELECT Nominee FROM musical WHERE Award = 'Tony Award' OR Award = 'Cleavant Derricks'	SELECT DISTINCT nominee FROM musical WHERE award = 'Bob Fosse' UNION SELECT DISTINCT nominee FROM musical WHERE award = 'Cleavant Derricks'	lack distinct	0	1
277	How many followers does each user have?	SELECT count(*) FROM follows	SELECT followers FROM user_profiles	semantic error	0	0
278	Find the number of followers for each user.	SELECT count(*) FROM follows GROUP BY f1	SELECT followers FROM user_profiles	join -> left join	0	0
285	Find the names of the users whose number of followers is greater than that of the user named 'Tyler Swift'.	SELECT T1.name FROM user_profiles AS T1 JOIN follows AS T2 ON T1.uid = T2.f1 GROUP BY T2.f1 HAVING count(*) > (SELECT count(*) FROM user_profiles AS T1 JOIN follows AS T2 ON T1.uid = T2.f1 WHERE T1.name = 'Tyler Swift')	SELECT name FROM user_profiles u1 WHERE EXISTS (SELECT 1 FROM user_profiles u2 WHERE u2.name = 'Tyler Swift' AND u1.followers > u2.followers)	semantic error	0	0
289	Find the id of users who are followed by Mary or Susan.	SELECT T2.f1 FROM user_profiles AS T1 JOIN follows AS T2 ON T1.uid = T2.f2 WHERE T1.name = 'Mary' OR T1.name = 'Susan'	SELECT DISTINCT T2.f1 FROM user_profiles AS T1 JOIN follows AS T2 ON T1.uid = T2.f2 WHERE T1.name = 'Mary' OR T1.name = 'Susan'	lack distinct	0	0
290	Find the name of the user who has the largest number of followers.	SELECT name FROM user_profiles ORDER BY followers DESC LIMIT 1	SELECT name FROM user_profiles WHERE followers = (SELECT MAX(followers) FROM user_profiles)	limit 1	0	1

291	Find the name and email of the user followed by the least number of people.	SELECT name , email FROM user_profiles ORDER BY followers LIMIT 1	SELECT name , email FROM user_profiles WHERE followers = (SELECT MIN(followers) FROM user_profiles)	limit 1	1	0
293	List the names of 5 users followed by the largest number of other users.	SELECT name FROM user_profiles ORDER BY followers DESC LIMIT 5	SELECT name FROM user_profiles WHERE followers IN (SELECT followers FROM user_profiles ORDER BY followers DESC LIMIT 5)	limit n; nlq vague: orderby second key	0	0
295	Find the name of each user and number of tweets tweeted by each of them.	SELECT T1.name , count(*) FROM user_profiles AS T1 JOIN tweets AS T2 ON T1.uid = T2.uid GROUP BY T2.uid	SELECT name, (SELECT COUNT(*) FROM tweets WHERE uid = user_profiles.uid) AS total_tweets FROM user_profiles	join -> left join	0	1
301	Find the names of all the catalog entries.	SELECT distinct(catalog_entry_name) FROM catalog_contents	SELECT catalog_entry_name FROM catalog_contents	distinct	0	1
302	What are all the catalog entry names?	SELECT distinct(catalog_entry_name) FROM catalog_contents	SELECT catalog_entry_name FROM catalog_contents	distinct	0	1
309	Find all the catalog publishers whose name contains 'Murray'	SELECT distinct(catalog_publisher) FROM catalogs WHERE catalog_publisher LIKE '%Murray%'	SELECT catalog_publisher FROM catalogs WHERE catalog_publisher LIKE '%Murray%'	distinct	0	1
310	Which catalog publishers have substring 'Murray' in their names?	SELECT distinct(catalog_publisher) FROM catalogs WHERE catalog_publisher LIKE '%Murray%'	SELECT catalog_publisher FROM catalogs WHERE catalog_publisher LIKE '%Murray%'	distinct	0	1
311	Which catalog publisher has published the most catalogs?	SELECT catalog_publisher FROM catalogs GROUP BY catalog_publisher ORDER BY count(*) DESC LIMIT 1	SELECT catalog_publisher FROM catalogs GROUP BY catalog_publisher HAVING COUNT(*) = (SELECT MAX(cnt) FROM (SELECT COUNT(*) AS cnt FROM catalogs GROUP BY catalog_publisher) T)	limit 1	0	0
312	Find the catalog publisher that has the most catalogs.	SELECT catalog_publisher FROM catalogs GROUP BY catalog_publisher ORDER BY count(*) DESC LIMIT 1	SELECT c.catalog_publisher FROM (SELECT catalog_publisher, COUNT(*) as cnt FROM catalogs GROUP BY catalog_publisher) c JOIN (SELECT MAX(c_count) as max_count FROM (SELECT catalog_publisher, COUNT(*) as c_count FROM catalogs GROUP BY catalog_publisher)) m ON c.cnt = m.max_count	limit 1	0	1
313	Find the names and publication dates of all catalogs that have catalog level number greater than 5.	SELECT t1.catalog_name , t1.date_of_publication FROM catalogs AS t1 JOIN catalog_structure AS t2 ON t1.catalog_id = t2.catalog_id WHERE catalog_level_number > 5	SELECT catalog_name, date_of_publication FROM catalogs WHERE catalog_id IN (SELECT catalog_id FROM catalog_structure WHERE catalog_level_number > 5)	join -> in-sub	0	1
314	What are the name and publication date of the catalogs with catalog level number above 5?	SELECT t1.catalog_name , t1.date_of_publication FROM catalogs AS t1 JOIN catalog_structure AS t2 ON t1.catalog_id = t2.catalog_id WHERE catalog_level_number > 5	SELECT catalog_name, date_of_publication FROM catalogs WHERE catalog_id IN (SELECT catalog_id FROM catalog_structure WHERE catalog_level_number > 5)	join -> in-sub	0	1
315	What are the entry names of catalog with the attribute possessed by most entries.	SELECT t1.catalog_entry_name FROM Catalog_Contents AS t1 JOIN Catalog_Contents_Additional_Attributes AS t2 ON t1.catalog_entry_id = t2.catalog_entry_id WHERE t2.attribute_value = (SELECT attribute_value FROM Catalog_Contents_Additional_Attributes GROUP BY attribute_value ORDER BY count(*) DESC LIMIT 1)	SELECT catalog_entry_name FROM catalog_contents WHERE catalog_entry_id IN (SELECT catalog_entry_id FROM catalog_contents_additional_attributes WHERE attribute_id IN (SELECT attribute_id FROM catalog_contents_additional_attributes GROUP BY attribute_id HAVING COUNT(DISTINCT catalog_entry_id) = (SELECT MAX(cnt) FROM (SELECT COUNT(DISTINCT catalog_entry_id) AS cnt FROM catalog_contents_additional_attributes GROUP BY attribute_id) T))	limit 1; schema flaw: no PK IC	0	0

316	Find the entry names of the catalog with the attribute that have the most entries.	SELECT t1.catalog_entry_name FROM Catalog_Contents AS t1 JOIN Catalog_Contents_Additional_Attributes AS t2 ON t1.catalog_entry_id = t2.catalog_entry_id WHERE t2.attribute_value = (SELECT attribute_value FROM Catalog_Contents_Additional_Attributes GROUP BY attribute_value ORDER BY count(*) DESC LIMIT 1)	SELECT catalog_entry_name FROM catalog_contents WHERE catalog_entry_id IN (SELECT catalog_entry_id FROM catalog_contents_additional_attributes WHERE attribute_id IN (SELECT attribute_id FROM catalog_contents_additional_attributes GROUP BY attribute_id HAVING COUNT(DISTINCT catalog_entry_id) = (SELECT MAX(cnt) FROM (SELECT COUNT(DISTINCT catalog_entry_id) AS cnt FROM catalog_contents_additional_attributes GROUP BY attribute_id) T)))	limit 1	0	0
317	What is the entry name of the most expensive catalog (in USD)?	SELECT catalog_entry_name FROM catalog_contents ORDER BY price_in_dollars DESC LIMIT 1	SELECT catalog_entry_name FROM catalog_contents WHERE price_in_dollars = (SELECT MAX(price_in_dollars) FROM catalog_contents)	limit 1	0	1
318	Find the entry name of the catalog with the highest price (in USD).	SELECT catalog_entry_name FROM catalog_contents ORDER BY price_in_dollars DESC LIMIT 1	SELECT C1.catalog_entry_name FROM catalog_contents C1 WHERE price_in_dollars = (SELECT MAX(price_in_dollars) FROM catalog_contents)	limit 1	1	0
319	What is the level name of the cheapest catalog (in USD)?	SELECT t2.catalog_level_name FROM catalog_contents AS t1 JOIN catalog_structure AS t2 ON t1.catalog_level_number = t2.catalog_level_number ORDER BY t1.price_in_dollars LIMIT 1	SELECT catalog_level_name FROM catalog_structure WHERE catalog_level_number IN (SELECT catalog_level_number FROM catalog_contents WHERE price_in_dollars = (SELECT MIN(price_in_dollars) FROM catalog_contents))	limit 1	1	0
320	Find the level name of the catalog with the lowest price (in USD).	SELECT t2.catalog_level_name FROM catalog_contents AS t1 JOIN catalog_structure AS t2 ON t1.catalog_level_number = t2.catalog_level_number ORDER BY t1.price_in_dollars LIMIT 1	SELECT catalog_level_name FROM catalog_structure WHERE catalog_level_number IN (SELECT catalog_level_number FROM catalog_contents WHERE price_in_dollars = (SELECT MIN(price_in_dollars) FROM catalog_contents))	limit 1	0	0
323	What is the product with the highest height? Give me the catalog entry name.	SELECT catalog_entry_name FROM catalog_contents ORDER BY height DESC LIMIT 1	SELECT catalog_entry_name FROM catalog_contents WHERE height = (SELECT MAX(height) FROM catalog_contents)	limit 1	0	1
324	Which catalog content has the highest height? Give me the catalog entry name.	SELECT catalog_entry_name FROM catalog_contents ORDER BY height DESC LIMIT 1	SELECT catalog_entry_name FROM catalog_contents WHERE height = (SELECT MAX(height) FROM catalog_contents)	limit 1	0	1
325	Find the name of the product that has the smallest capacity.	SELECT catalog_entry_name FROM catalog_contents ORDER BY capacity ASC LIMIT 1	SELECT catalog_entry_name FROM catalog_contents WHERE capacity = (SELECT MIN(capacity) FROM catalog_contents)	limit 1	0	0
326	Which catalog content has the smallest capacity? Return the catalog entry name.	SELECT catalog_entry_name FROM catalog_contents ORDER BY capacity ASC LIMIT 1	SELECT catalog_entry_name FROM catalog_contents WHERE capacity = (SELECT MIN(capacity) FROM catalog_contents)	limit 1	0	1
329	Find the names of catalog entries with level number 8.	SELECT t1.catalog_entry_name FROM Catalog_Contents AS t1 JOIN Catalog_Contents_Additional_Attributes AS t2 ON t1.catalog_entry_id = t2.catalog_entry_id WHERE t2.catalog_level_number = '8'	SELECT catalog_entry_name FROM catalog_contents WHERE catalog_level_number = 8	semantic error	0	1
330	What are the names of catalog entries with level number 8?	SELECT t1.catalog_entry_name FROM Catalog_Contents AS t1 JOIN Catalog_Contents_Additional_Attributes AS t2 ON t1.catalog_entry_id = t2.catalog_entry_id WHERE t2.catalog_level_number = '8'	SELECT catalog_entry_name FROM catalog_contents WHERE catalog_level_number = 8	semantic error	0	1
331	Find the names of the products with length smaller than 3 or height greater than 5.	SELECT catalog_entry_name FROM catalog_contents WHERE LENGTH < 3 OR width > 5	SELECT catalog_entry_name FROM catalog_contents WHERE length < 3 OR height > 5	semantic error	0	0

332	Which catalog contents have length below 3 or above 5? Find the catalog entry names.	SELECT catalog_entry_name FROM catalog_contents WHERE LENGTH < 3 OR width > 5	SELECT catalog_entry_name FROM catalog_contents WHERE length < 3 OR length > 5	semantic error	1	0
333	Find the name and attribute ID of the attribute definitions with attribute value 0.	SELECT t1.attribute_name , t1.attribute_id FROM Attribute_Definitions AS t1 JOIN Catalog_Contents_Additional_Attributes AS t2 ON t1.attribute_id = t2.attribute_id WHERE t2.attribute_value = 0	SELECT attribute_name, attribute_id FROM attribute_definitions WHERE attribute_id IN (SELECT attribute_id FROM catalog_contents_additional_attributes WHERE attribute_value = 0)	join -> in-sub	1	0
334	Which attribute definitions have attribute value 0? Give me the attribute name and attribute ID.	SELECT t1.attribute_name , t1.attribute_id FROM Attribute_Definitions AS t1 JOIN Catalog_Contents_Additional_Attributes AS t2 ON t1.attribute_id = t2.attribute_id WHERE t2.attribute_value = 0	SELECT attribute_name, attribute_id FROM attribute_definitions WHERE attribute_id IN (SELECT attribute_id FROM catalog_contents_additional_attributes WHERE attribute_value = 0)	join -> in-sub	0	1
355	Show the id and name of the aircraft with the maximum distance.	SELECT aid , name FROM Aircraft ORDER BY distance DESC LIMIT 1	SELECT aid, name FROM aircraft WHERE distance = (SELECT MAX(distance) FROM aircraft)	limit 1	0	1
356	What is the id and name of the aircraft that can cover the maximum distance?	SELECT aid , name FROM Aircraft ORDER BY distance DESC LIMIT 1	SELECT aid, name FROM aircraft WHERE distance = (SELECT MAX(distance) FROM aircraft)	limit 1	0	1
357	Show the name of aircrafts with top three lowest distances.	SELECT name FROM Aircraft ORDER BY distance LIMIT 3	SELECT name FROM aircraft WHERE distance IN (SELECT distance FROM aircraft ORDER BY distance ASC LIMIT 3)	limit n	1	0
358	What are the aircrafts with top 3 shortest lengths? List their names.	SELECT name FROM Aircraft ORDER BY distance LIMIT 3	SELECT name FROM aircraft WHERE distance IN (SELECT distance FROM aircraft ORDER BY distance ASC LIMIT 3)	limit n	1	0
365	Show ids for all employees with at least 100000 salary.	SELECT eid FROM Employee WHERE salary > 100000	SELECT eid FROM employee WHERE salary >= 100000	semantic error	0	1
366	What is the id of every employee who has at least a salary of 100000?	SELECT eid FROM Employee WHERE salary > 100000	SELECT eid FROM employee WHERE salary >= 100000	semantic error	0	1
373	Show the id and name of the employee with maximum salary.	SELECT eid , name FROM Employee ORDER BY salary DESC LIMIT 1	SELECT eid, name FROM employee WHERE salary = (SELECT MAX(salary) FROM employee)	limit 1	0	1
374	What is the id and name of the employee with the highest salary?	SELECT eid , name FROM Employee ORDER BY salary DESC LIMIT 1	SELECT eid, name FROM employee WHERE salary = (SELECT MAX(salary) FROM employee)	limit 1	0	1
375	Show the name of employees with three lowest salaries.	SELECT name FROM Employee ORDER BY salary ASC LIMIT 3	WITH cte AS (SELECT name, RANK() OVER (ORDER BY salary) as rn FROM employee) SELECT name AS name FROM cte WHERE rn <= 3	limit n	1	0
376	What is the name of the 3 employees who get paid the least?	SELECT name FROM Employee ORDER BY salary ASC LIMIT 3	WITH cte AS (SELECT name, RANK() OVER (ORDER BY salary) as rn FROM employee) SELECT name AS name FROM cte WHERE rn <= 3	limit n	1	0
397	Show the flight number and distance of the flight with maximum price.	SELECT fno , distance FROM Flight ORDER BY price DESC LIMIT 1	SELECT fno, distance FROM flight WHERE price = (SELECT MAX(price) FROM flight)	limit 1	0	1
398	What is the flight number and its distance for the one with the maximum price?	SELECT fno , distance FROM Flight ORDER BY price DESC LIMIT 1	SELECT fno, distance FROM flight WHERE price = (SELECT MAX(price) FROM flight)	limit 1	0	1

399	Show the flight number of flights with three lowest distances.	SELECT fno FROM Flight ORDER BY distance ASC LIMIT 3	SELECT fno FROM (SELECT fno, RANK() OVER (ORDER BY distance) as rn FROM flight) WHERE rn <= 3	limit n	1	0
400	What are the numbers of the shortest flights?	SELECT fno FROM Flight ORDER BY distance ASC LIMIT 3	SELECT fno FROM flight WHERE distance = (SELECT MIN(distance) FROM flight)	limit 1	0	1
402	What is the average distance and price for all flights from LA?	SELECT avg(distance) , avg(price) FROM Flight WHERE origin = 'Los Angeles'	SELECT AVG(distance) AS avg_distance, AVG(price) AS avg_price FROM flight WHERE origin = 'LA'	str	0	1
407	Which origin has most number of flights?	SELECT origin FROM Flight GROUP BY origin ORDER BY count(*) DESC LIMIT 1	SELECT origin FROM flight GROUP BY origin HAVING COUNT(*) = (SELECT MAX(flights) FROM (SELECT origin, COUNT(*) AS flights FROM flight GROUP BY origin))	limit 1	0	1
408	What place has the most flights coming from there?	SELECT origin FROM Flight GROUP BY origin ORDER BY count(*) DESC LIMIT 1	SELECT origin FROM flight GROUP BY origin HAVING COUNT(*) = (SELECT MAX(counts) FROM (SELECT COUNT(*) AS counts FROM flight GROUP BY origin))	limit 1	0	1
409	Which destination has least number of flights?	SELECT destination FROM Flight GROUP BY destination ORDER BY count(*) LIMIT 1	SELECT destination FROM flight GROUP BY destination HAVING COUNT(*) = (SELECT MIN(cnt) FROM (SELECT COUNT(*) as cnt FROM flight GROUP BY destination))	limit 1	0	1
410	What destination has the fewest number of flights?	SELECT destination FROM Flight GROUP BY destination ORDER BY count(*) LIMIT 1	SELECT destination FROM flight GROUP BY destination HAVING COUNT(*) = (SELECT MIN(cnt) FROM (SELECT COUNT(*) as cnt FROM flight GROUP BY destination))	limit 1	0	1
415	Show aircraft names and number of flights for each aircraft.	SELECT T2.name , count(*) FROM Flight AS T1 JOIN Aircraft AS T2 ON T1.aid = T2.aid GROUP BY T1.aid	SELECT a.name, (SELECT COUNT(*) FROM flight WHERE aid = a.aid) AS num_flights FROM aircraft a	join -> left join	0	1
416	What is the name of each aircraft and how many flights does each one complete?	SELECT T2.name , count(*) FROM Flight AS T1 JOIN Aircraft AS T2 ON T1.aid = T2.aid GROUP BY T1.aid	SELECT name, (SELECT COUNT(*) FROM flight WHERE flight.aid = aircraft.aid) FROM aircraft	join -> left join	0	1
423	Show names for all aircrafts of which John Williams has certificates.	SELECT T3.name FROM Employee AS T1 JOIN Certificate AS T2 ON T1.eid = T2.eid JOIN Aircraft AS T3 ON T3.aid = T2.aid WHERE T1.name = 'John Williams'	SELECT A.name FROM aircraft A WHERE EXISTS (SELECT * FROM certificate C JOIN employee E ON C.eid = E.eid WHERE A.aid = C.aid AND E.name = 'John Williams')	join -> in-sub	0	1
424	What are the names of all aircrafts that John Williams have certificates to be able to fly?	SELECT T3.name FROM Employee AS T1 JOIN Certificate AS T2 ON T1.eid = T2.eid JOIN Aircraft AS T3 ON T3.aid = T2.aid WHERE T1.name = 'John Williams'	SELECT name FROM aircraft WHERE aid IN (SELECT aid FROM certificate WHERE eid IN (SELECT eid FROM employee WHERE name = 'John Williams'))	join -> in-sub	0	0
425	Show names for all employees who have certificate of Boeing 737-800.	SELECT T1.name FROM Employee AS T1 JOIN Certificate AS T2 ON T1.eid = T2.eid JOIN Aircraft AS T3 ON T3.aid = T2.aid WHERE T3.name = 'Boeing 737-800'	SELECT name FROM employee WHERE eid IN (SELECT eid FROM certificate JOIN aircraft ON certificate.aid = aircraft.aid WHERE aircraft.name = 'Boeing 737-800')	join -> in-sub	0	1
426	What are the names of all employees who have a certificate to fly Boeing 737-800?	SELECT T1.name FROM Employee AS T1 JOIN Certificate AS T2 ON T1.eid = T2.eid JOIN Aircraft AS T3 ON T3.aid = T2.aid WHERE T3.name = 'Boeing 737-800'	SELECT name FROM employee WHERE eid IN (SELECT e.eid FROM employee e JOIN certificate c ON e.eid = c.eid JOIN aircraft a ON c.aid = a.aid WHERE a.name = 'Boeing 737-800')	join -> in-sub	1	0
427	Show names for all employees who have certificates on both Boeing 737-800 and Airbus A340-300.	SELECT T1.name FROM Employee AS T1 JOIN Certificate AS T2 ON T1.eid = T2.eid JOIN Aircraft AS T3 ON T3.aid = T2.aid WHERE T3.name = 'Boeing 737-800' INTERSECT SELECT T1.name FROM Employee AS T1 JOIN Certificate AS T2 ON T1.eid = T2.eid JOIN Aircraft AS T3 ON T3.aid = T2.aid WHERE T3.name = 'Airbus A340-300'	SELECT name FROM employee WHERE eid IN (SELECT e.eid FROM employee e JOIN certificate c ON e.eid = c.eid JOIN aircraft a ON c.aid = a.aid WHERE a.name = 'Boeing 737-800' INTERSECT SELECT e.eid FROM employee e JOIN certificate c ON e.eid = c.eid JOIN aircraft a ON c.aid = a.aid WHERE a.name = 'Airbus A340-300')	intersect non-key	0	0

428	What are the names of all employees who can fly both the Boeing 737-800 and the Airbus A340-300?	SELECT T1.name FROM Employee AS T1 JOIN Certificate AS T2 ON T1.eid = T2.eid JOIN Aircraft AS T3 ON T3.aid = T2.aid WHERE T3.name = 'Boeing 737-800' INTERSECT SELECT T1.name FROM Employee AS T1 JOIN Certificate AS T2 ON T1.eid = T2.eid JOIN Aircraft AS T3 ON T3.aid = T2.aid WHERE T3.name = 'Airbus A340-300'	SELECT name FROM employee e WHERE (SELECT COUNT(DISTINCT a.name) FROM certificate c JOIN aircraft a ON c.aid = a.aid WHERE e.eid = c.eid AND a.name IN ('Boeing 737-800', 'Airbus A340-300')) = 2	intersect non-key	0	1
429	Show names for all employees who do not have certificate of Boeing 737-800.	SELECT name FROM Employee EXCEPT SELECT T1.name FROM Employee AS T1 JOIN Certificate AS T2 ON T1.eid = T2.eid JOIN Aircraft AS T3 ON T3.aid = T2.aid WHERE T3.name = 'Boeing 737-800'	SELECT name FROM employee WHERE eid NOT IN (SELECT eid FROM certificate WHERE aid IN (SELECT aid FROM aircraft WHERE name = 'Boeing 737-800'))	intersect non-key	0	1
430	What are the names of all employees who are not certified to fly Boeing 737-800s?	SELECT name FROM Employee EXCEPT SELECT T1.name FROM Employee AS T1 JOIN Certificate AS T2 ON T1.eid = T2.eid JOIN Aircraft AS T3 ON T3.aid = T2.aid WHERE T3.name = 'Boeing 737-800'	SELECT employee.name FROM employee WHERE employee.eid NOT IN (SELECT c.eid FROM certificate c JOIN aircraft a ON c.aid = a.aid WHERE a.name = 'Boeing 737-800')	intersect non-key	0	1
431	Show the name of aircraft which fewest people have its certificate.	SELECT T2.name FROM Certificate AS T1 JOIN Aircraft AS T2 ON T2.aid = T1.aid GROUP BY T1.aid ORDER BY count(*) DESC LIMIT 1	WITH cnt AS (SELECT COUNT(c.aid) AS cnt, a.name FROM Aircraft a LEFT JOIN Certificate c ON a.aid = c.aid GROUP BY a.aid) SELECT name FROM cnt WHERE cnt = (SELECT MIN(cnt) FROM cnt)	limit 1	0	0
432	What are the names of the aircraft that the least people are certified to fly?	SELECT T2.name FROM Certificate AS T1 JOIN Aircraft AS T2 ON T2.aid = T1.aid GROUP BY T1.aid ORDER BY count(*) DESC LIMIT 1	WITH cnt AS (SELECT COUNT(c.aid) AS cnt, a.name FROM Aircraft a LEFT JOIN Certificate c ON a.aid = c.aid GROUP BY a.aid) SELECT name FROM cnt WHERE cnt = (SELECT MIN(cnt) FROM cnt)	limit 1	0	0
433	Show the name and distance of the aircrafts with more than 5000 distance and which at least 5 people have its certificate.	SELECT T2.name FROM Certificate AS T1 JOIN Aircraft AS T2 ON T2.aid = T1.aid WHERE T2.distance > 5000 GROUP BY T1.aid ORDER BY count(*) >= 5	SELECT name, distance FROM aircraft WHERE distance > 5000 AND aid IN (SELECT aid FROM certificate GROUP BY aid HAVING COUNT(*) >= 5)	semantic error	0	1
434	What is the name and distance of every aircraft that can cover a distance of more than 5000 and which at least 5 people can fly?	SELECT T2.name FROM Certificate AS T1 JOIN Aircraft AS T2 ON T2.aid = T1.aid WHERE T2.distance > 5000 GROUP BY T1.aid ORDER BY count(*) >= 5	SELECT name, distance FROM aircraft WHERE aid IN (SELECT aid FROM certificate GROUP BY aid HAVING COUNT(eid) >= 5) AND distance > 5000	semantic error	0	0
435	what is the salary and name of the employee who has the most number of aircraft certificates?	SELECT T1.name, T1.salary FROM Employee AS T1 JOIN Certificate AS T2 ON T1.eid = T2.eid GROUP BY T1.eid ORDER BY count(*) DESC LIMIT 1	SELECT e.name, e.salary FROM employee e JOIN certificate c ON e.eid = c.eid GROUP BY e.eid HAVING COUNT(c.aid) = (SELECT MAX(cnt) FROM (SELECT COUNT(aid) AS cnt FROM certificate GROUP BY eid))	limit 1	0	1
436	What is the salary and name of the employee that is certified to fly the most planes?	SELECT T1.name, T1.salary FROM Employee AS T1 JOIN Certificate AS T2 ON T1.eid = T2.eid GROUP BY T1.eid ORDER BY count(*) DESC LIMIT 1	SELECT name, salary FROM employee WHERE eid IN (SELECT eid FROM certificate GROUP BY eid HAVING COUNT(aid) = (SELECT COUNT(aid) FROM certificate GROUP BY eid ORDER BY COUNT(aid) DESC LIMIT 1))	limit 1	0	1
437	What is the salary and name of the employee who has the most number of certificates on aircrafts with distance more than 5000?	SELECT T1.name FROM Employee AS T1 JOIN Certificate AS T2 ON T1.eid = T2.eid JOIN Aircraft AS T3 ON T3.aid = T2.aid WHERE T3.distance > 5000 GROUP BY T1.eid ORDER BY count(*) DESC LIMIT 1	SELECT e.salary, e.name FROM employee AS e JOIN certificate AS c ON e.eid = c.eid JOIN aircraft AS a ON c.aid = a.aid WHERE a.distance > 5000 GROUP BY e.eid HAVING COUNT(c.aid) = (SELECT COUNT(c2.aid) FROM certificate AS c2 JOIN aircraft AS a2 ON c2.aid = a2.aid WHERE a2.distance > 5000 GROUP BY c2.eid ORDER BY COUNT(c2.aid) DESC LIMIT 1)	limit 1; semantic error	0	1

438	What is the salary and name of the employee with the most certificates to fly planes more than 5000?	SELECT T1.name FROM Employee AS T1 JOIN Certificate AS T2 ON T1.eid = T2.eid JOIN Aircraft AS T3 ON T3.aid = T2.aid WHERE T3.distance > 5000 GROUP BY T1.eid ORDER BY count(*) DESC LIMIT 1	SELECT name, salary FROM employee WHERE eid IN (SELECT eid FROM certificate WHERE aid IN (SELECT aid FROM aircraft WHERE distance > 5000) GROUP BY aid HAVING COUNT(aid) = (SELECT COUNT(aid) FROM certificate WHERE aid IN (SELECT aid FROM aircraft WHERE distance > 5000) GROUP BY aid ORDER BY COUNT(aid) DESC LIMIT 1))	limit 1; semantic error	0	1
442	How many distinct allergies are there?	SELECT count(DISTINCT allergytype) FROM Allergy_type	SELECT COUNT(DISTINCT allergy) FROM allergy_type	semantic error	0	1
455	Which allergy type has most number of allergies?	SELECT allergytype FROM Allergy_type GROUP BY allergytype ORDER BY count(*) DESC LIMIT 1	SELECT allergytype FROM Allergy_type GROUP BY allergytype HAVING COUNT(*) = (SELECT MAX(cnt) FROM (SELECT COUNT(*) AS cnt FROM Allergy_type GROUP BY allergytype) T)	limit 1	0	0
456	Which allergy type is most common?	SELECT allergytype FROM Allergy_type GROUP BY allergytype ORDER BY count(*) DESC LIMIT 1	SELECT allergytype FROM Allergy_type GROUP BY allergytype HAVING COUNT(*) = (SELECT MAX(cnt) FROM (SELECT COUNT(*) AS cnt FROM Allergy_type GROUP BY allergytype) T)	limit 1	0	0
457	Which allergy type has least number of allergies?	SELECT allergytype FROM Allergy_type GROUP BY allergytype ORDER BY count(*) ASC LIMIT 1	SELECT allergytype FROM Allergy_type GROUP BY allergytype HAVING COUNT(*) = (SELECT MIN(cnt) FROM (SELECT COUNT(*) AS cnt FROM Allergy_type GROUP BY allergytype) T)	limit 1	0	0
458	Which allergy type is the least common?	SELECT allergytype FROM Allergy_type GROUP BY allergytype ORDER BY count(*) ASC LIMIT 1	SELECT allergytype FROM allergy_type GROUP BY allergytype HAVING COUNT(*) = (SELECT MIN(cnt) FROM (SELECT COUNT(*) AS cnt FROM allergy_type GROUP BY allergytype))	limit 1; nlq vague: what is common?; misunderstand	0	1
465	Show all majors.	SELECT DISTINCT Major FROM Student	SELECT major FROM student	distinct	0	1
491	Which major has most number of students?	SELECT major FROM Student GROUP BY major ORDER BY count(*) DESC LIMIT 1	SELECT major FROM student GROUP BY major HAVING COUNT(stuid) = (SELECT MAX(student_count) FROM (SELECT COUNT(stuid) AS student_count FROM student GROUP BY major))	limit 1	0	1
492	What is the largest major?	SELECT major FROM Student GROUP BY major ORDER BY count(*) DESC LIMIT 1	SELECT major FROM student GROUP BY major HAVING COUNT(*) = (SELECT MAX(cnt) FROM (SELECT COUNT(*) AS cnt FROM student GROUP BY major))	limit 1; nlq vague: largest major	0	0

Table 2: Incorrect case list of Spider Test set.

Case Id	NL	Original SQL	Modified SQL	Tag	Follow Consistency	Correctly Fixed
10	What is the name of the player with the highest earnings?	SELECT Name FROM player ORDER BY Earnings DESC LIMIT 1	SELECT p.name FROM player p WHERE p.earnings = (SELECT MAX(earnings) FROM player);	limit 1	0	1
11	Return the name of the player who earns the most money.	SELECT Name FROM player ORDER BY Earnings DESC LIMIT 1	SELECT P.name FROM player P WHERE P.earnings = (SELECT MAX(earnings) FROM player)	limit 1	0	1
14	What is the country of the player with the highest earnings among players that have more than 2 win counts?	SELECT Country FROM player WHERE Wins_count > 2 ORDER BY Earnings DESC LIMIT 1	SELECT Country FROM player WHERE Wins_count > 2 ORDER BY Earnings DESC LIMIT 1	limit 1	0	1
15	Of players who have more than 2 wins, what is the country of the player who makes the most?	SELECT Country FROM player WHERE Wins_count > 2 ORDER BY Earnings DESC LIMIT 1	SELECT p.country FROM player p WHERE p.wins_count > 2 and p.earnings = (SELECT MAX(earnings) FROM player WHERE wins_count>2)	limit 1	0	1
18	Show names of clubs that have players with more than 2 win counts.	SELECT T1.Name FROM club AS T1 JOIN player AS T2 ON T1.Club_ID = T2.Club_ID WHERE T2.Wins_count > 2	SELECT name FROM club WHERE club_id IN (SELECT club_id FROM player WHERE wins_count > 2)	join -> in-sub	0	0
19	What are the names of clubs that have players who have won more than twice?	SELECT T1.Name FROM club AS T1 JOIN player AS T2 ON T1.Club_ID = T2.Club_ID WHERE T2.Wins_count > 2	SELECT name FROM club WHERE club_id IN (SELECT club_id FROM player WHERE wins_count > 2)	join -> in-sub	0	0
26	Please show the most common manufacturer of clubs.	SELECT Manufacturer FROM club GROUP BY Manufacturer ORDER BY COUNT(*) DESC LIMIT 1	SELECT manufacturer FROM club GROUP BY manufacturer HAVING COUNT(*) = (SELECT MAX(cnt) FROM (SELECT COUNT(*) as cnt FROM club GROUP BY manufacturer))	limit 1	0	1
27	Which manufacturer is most common among clubs?	SELECT Manufacturer FROM club GROUP BY Manufacturer ORDER BY COUNT(*) DESC LIMIT 1	SELECT manufacturer FROM club GROUP BY manufacturer HAVING COUNT(*) = (SELECT MAX(cnt) FROM (SELECT COUNT(*) as cnt FROM club GROUP BY manufacturer))	limit 1	0	0
34	Show the country of players with earnings more than 1400000 and players with earnings less than 1100000.	SELECT Country FROM player WHERE Earnings > 1400000 INTERSECT SELECT Country FROM player WHERE Earnings < 1100000	SELECT DISTINCT country FROM player WHERE earnings > 1400000 UNION ALL SELECT DISTINCT country FROM player WHERE earnings < 1100000	semantic error: filter condition	0	1
43	For every order, how many products does it contain, and what are the orders' statuses and ids?	SELECT T1.order_id, T1.order_status_code, count(*) FROM Orders AS T1 JOIN Order_items AS T2 ON T1.order_id = T2.order_id GROUP BY T1.order_id	SELECT order_id, order_status_code, (SELECT COUNT(*) FROM order_items WHERE order_items.order_id = orders.order_id) AS product_count FROM orders	join -> left join	0	1
46	Which customers did not make any orders? List the first name, middle initial and last name.	SELECT customer_first_name, customer_middle_initial, customer_last_name FROM Customers EXCEPT SELECT T1.customer_first_name, T1.customer_middle_initial, T1.customer_last_name FROM Customers AS T1 JOIN Orders AS T2 ON T1.customer_id = T2.customer_id	SELECT customer_first_name, customer_middle_initial, customer_last_name FROM customers WHERE customer_id NOT IN (SELECT customer_id FROM orders)	except non-key	0	1

47	What are the first and last names, and middle initials of all customers who did not make any orders?	SELECT customer_first_name , customer_middle_initial , customer_last_name FROM Customers EXCEPT SELECT T1.customer_first_name , T1.customer_middle_initial , T1.customer_last_name FROM Customers AS T1 JOIN Orders AS T2 ON T1.customer_id = T2.customer_id	SELECT c.customer_first_name, c.customer_last_name, c.customer_middle_initial FROM customers c WHERE NOT EXISTS (SELECT 1 FROM orders o WHERE o.customer_id = c.customer_id)	except non-key	0	1
49	What are the ids , names , prices , and colors of all products that have been listed in less than two orders ?	select t1.product_id , t1.product_name , t1.product_price , t1.product_color from products as t1 join order_items as t2 on t1.product_id = t2.product_id join orders as t3 on t2.order_id = t3.order_id group by t1.product_id having count(*) < 2	SELECT p.product_id, p.product_name, p.product_price, p.product_color FROM products p WHERE (SELECT COUNT(DISTINCT oi.order_id) FROM order_items oi WHERE oi.product_id = p.product_id) < 2	semantic error	0	1
52	Which product are listed in orders most frequently? List the id, product name and price.	SELECT T1.product_id , T1.product_name , T1.product_price FROM Products AS T1 JOIN Order_items AS T2 ON T1.product_id = T2.product_id GROUP BY T1.product_id ORDER BY count(*) DESC LIMIT 1	WITH RankedProducts AS (SELECT P.product_id, P.product_name, P.product_price, RANK() OVER (ORDER BY COUNT(OI.product_id) DESC) as Rank FROM products P JOIN order_items OI ON P.product_id = OI.product_id GROUP BY P.product_id) SELECT product_id, product_name, product_price FROM Ranked-Products WHERE Rank = 1;	limit 1	0	1
53	What are the ids, names, and prices of all products that are ordered most frequently?	SELECT T1.product_id , T1.product_name , T1.product_price FROM Products AS T1 JOIN Order_items AS T2 ON T1.product_id = T2.product_id GROUP BY T1.product_id ORDER BY count(*) DESC LIMIT 1	SELECT product_id, product_name, product_price FROM (SELECT T1.product_id, T1.product_name, T1.product_price, rank() over (ORDER BY count(*) DESC) as rk FROM Products AS T1 JOIN Order_items AS T2 ON T1.product_id = T2.product_id GROUP BY T1.product_id) WHERE rk = 1;	limit 1	1	0
54	Which order have the least sum of the product prices. List the order id and sum.	SELECT T1.order_id , sum(T2.product_price) FROM Order_items AS T1 JOIN Products AS T2 ON T1.product_id = T2.product_id GROUP BY T1.order_id ORDER BY sum(T2.product_price) ASC LIMIT 1	SELECT order_id, sum_price FROM (SELECT T1.order_id, sum(T2.product_price) as sum_price, rank() over (ORDER BY sum(T2.product_price)) as rk FROM Order_items AS T1 JOIN Products AS T2 ON T1.product_id = T2.product_id GROUP BY T1.order_id) WHERE rk = 1;	limit 1	0	0
55	What is the order that total cost the least , and how much is the total cost ?	select t1.order_id , sum(t2.product_price) from order_items as t1 join products as t2 on t1.product_id = t2.product_id group by t1.order_id order by sum(t2.product_price) asc limit 1	SELECT order_id, sum_price FROM (SELECT T1.order_id, sum(T2.product_price) as sum_price, rank() over (ORDER BY sum(T2.product_price)) as rk FROM Order_items AS T1 JOIN Products AS T2 ON T1.product_id = T2.product_id GROUP BY T1.order_id) WHERE rk = 1;	limit 1	0	0
56	What is the most popular payment method?	SELECT Payment_method_code FROM Customer_Payment_Methods GROUP BY Payment_method_code ORDER BY count(*) DESC LIMIT 1	SELECT payment_method_code FROM (SELECT payment_method_code, RANK() OVER (ORDER BY COUNT(*) DESC) as rank FROM customer_payment_methods GROUP BY payment_method_code) WHERE rank = 1	limit 1	0	1
57	What is the payment method that most customers use?	SELECT Payment_method_code FROM Customer_Payment_Methods GROUP BY Payment_method_code ORDER BY count(*) DESC LIMIT 1	SELECT payment_method_code FROM customer_payment_methods GROUP BY payment_method_code HAVING COUNT(*) = (SELECT max(count_global.use_count) FROM (SELECT payment_method_code, COUNT(*) AS use_count FROM customer_payment_methods GROUP BY payment_method_code) count_global)	limit 1	0	1
58	How many number of products does each gender of customers buy? List the gender and the number	SELECT T1.gender_code , count(*) FROM Customers AS T1 JOIN Orders AS T2 ON T1.customer_id = T2.customer_id JOIN Order_items AS T3 ON T2.order_id = T3.order_id GROUP BY T1.gender_code	SELECT g.gender_code, COUNT(*) AS total_products FROM customers g LEFT JOIN orders o ON g.customer_id = o.customer_id LEFT JOIN order_items oi ON o.order_id = oi.order_id GROUP BY g.gender_code;	join -> left join	0	0

59	How many products does each gender buy?	SELECT T1.gender_code , count(*) FROM Customers AS T1 JOIN Orders AS T2 ON T1.customer_id = T2.customer_id JOIN Order_items AS T3 ON T2.order_id = T3.order_id GROUP BY T1.gender_code	SELECT g.gender_code, COUNT(*) AS total_products FROM customers g LEFT JOIN orders o ON g.customer_id = o.customer_id LEFT JOIN order_items oi ON o.order_id = oi.order_id GROUP BY g.gender_code;	join -> left join	0	0
60	How many orders has each gender of customers placed?	SELECT T1.gender_code , count(*) FROM Customers AS T1 JOIN Orders AS T2 ON T1.customer_id = T2.customer_id GROUP BY T1.gender_code	SELECT c.gender_code, COUNT(o.order_id) FROM customers c LEFT JOIN orders o ON c.customer_id = o.customer_id GROUP BY c.gender_code	join -> left join	0	1
61	How many orders has each gender placed?	SELECT T1.gender_code , count(*) FROM Customers AS T1 JOIN Orders AS T2 ON T1.customer_id = T2.customer_id GROUP BY T1.gender_code	SELECT g.gender_code, COUNT(*) AS total_products FROM customers g LEFT JOIN orders o ON g.customer_id = o.customer_id LEFT JOIN order_items oi ON o.order_id = oi.order_id GROUP BY g.gender_code;	join -> left join	1	0
62	List the customers' first name, middle initial, last name and payment methods.	SELECT T1.customer_first_name , T1.customer_middle_initial , T1.customer_last_name , T2.Payment_method_code FROM Customers AS T1 JOIN Customer_Payment_Methods AS T2 ON T1.customer_id = T2.customer_id	SELECT first_name, middle_initial, last_name, method_code FROM (SELECT customer_first_name AS first_name, customer_middle_initial AS middle_initial, customer_last_name AS last_name, customer_id FROM customers) AS cust LEFT JOIN (SELECT payment_method_code AS method_code, customer_id FROM customer_payment_methods) AS paym ON cust.customer_id = paym.customer_id	join -> left join	0	1
63	What are the first names, middle initials, last names, and payment methods of all customers?	SELECT T1.customer_first_name , T1.customer_middle_initial , T1.customer_last_name , T2.Payment_method_code FROM Customers AS T1 JOIN Customer_Payment_Methods AS T2 ON T1.customer_id = T2.customer_id	SELECT c1.customer_first_name, c1.customer_middle_initial, c1.customer_last_name, cp.payment_method_code FROM customers c1 LEFT JOIN customer_payment_methods cp ON c1.customer_id = cp.customer_id	join -> left join	0	1
64	List the invoices' status, date and the date of shipment.	SELECT T1.invoice_status_code , T1.invoice_date , T2.shipment_date FROM Invoices AS T1 JOIN Shipments AS T2 ON T1.invoice_number = T2.invoice_number	SELECT T2.invoice_status_code, T2.invoice_date, T1.shipment_date FROM Shipments AS T1 LEFT JOIN Invoices AS T2 ON T1.invoice_number = T2.invoice_number	join -> left join	1	0
65	What are the statuses, dates, and shipment dates for all invoices?	SELECT T1.invoice_status_code , T1.invoice_date , T2.shipment_date FROM Invoices AS T1 JOIN Shipments AS T2 ON T1.invoice_number = T2.invoice_number	SELECT A.invoice_status_code, A.invoice_date, B.shipment_date FROM (SELECT invoice_number, invoice_status_code, invoice_date FROM invoices) A LEFT JOIN shipments B ON A.invoice_number = B.invoice_number	join -> left join	0	1
70	What is the product name and the color of the ordered items which have been shipped?	SELECT T1.product_name , T1.product_color FROM Products AS T1 JOIN Order_items AS T2 ON T1.product_id = T2.product_id JOIN Shipment_Items AS T3 ON T2.order_item_id = T3.order_item_id JOIN Shipments AS T4 ON T3.shipment_id = T4.shipment_id	SELECT product_name, product_color FROM products WHERE product_id IN (SELECT product_id FROM order_items WHERE order_item_id IN (SELECT order_item_id FROM shipment_items))	join -> in-sub	0	1
71	What are the names and colors of all products that have been shipped?	SELECT T1.product_name , T1.product_color FROM Products AS T1 JOIN Order_items AS T2 ON T1.product_id = T2.product_id JOIN Shipment_Items AS T3 ON T2.order_item_id = T3.order_item_id JOIN Shipments AS T4 ON T3.shipment_id = T4.shipment_id	SELECT product_name, product_color FROM products WHERE product_id IN (SELECT product_id FROM order_items WHERE order_item_id IN (SELECT order_item_id FROM shipment_items))	join -> in-sub	0	1
98	List all the pairs of buyer first names and product names.	SELECT T1.customer_first_name , T4.product_name FROM Customers AS T1 JOIN Orders AS T2 ON T1.customer_id = T2.customer_id JOIN Order_items AS T3 ON T2.order_id = T3.order_id JOIN Products AS T4 ON T3.product_id = T4.product_id	SELECT c.customer_first_name AS buyer, p.product_name AS product FROM customers c CROSS JOIN products p WHERE EXISTS (SELECT 1 FROM orders o JOIN order_items oi ON o.order_id = oi.order_id WHERE o.customer_id = c.customer_id AND oi.product_id = p.product_id)	join -> in-sub	0	1
99	What are the first names of all buyers and what products did they buy? List them in pairs.	SELECT T1.customer_first_name , T4.product_name FROM Customers AS T1 JOIN Orders AS T2 ON T1.customer_id = T2.customer_id JOIN Order_items AS T3 ON T2.order_id = T3.order_id JOIN Products AS T4 ON T3.product_id = T4.product_id	SELECT c.customer_first_name AS buyer, p.product_name AS product FROM customers c CROSS JOIN products p WHERE EXISTS (SELECT 1 FROM orders o JOIN order_items oi ON o.order_id = oi.order_id WHERE o.customer_id = c.customer_id AND oi.product_id = p.product_id)	join -> in-sub	1	0

101	How many products have been shipped?	SELECT count(*) FROM Shipment_Items	SELECT COUNT(DISTINCT products.product_id) FROM products JOIN order_items ON products.product_id = order_items.product_id JOIN shipment_items ON order_items.order_item_id = shipment_items.order_item_id	semantic error	0	1
104	What is the average price of the products being ordered?	SELECT avg(T1.product_price) FROM Products AS T1 JOIN Order_items AS T2 ON T1.product_id = T2.product_id	SELECT AVG(product_price) FROM products p JOIN (SELECT DISTINCT product_id FROM order_items) pi ON p.product_id = pi.product_id	semantic error	0	1
105	What is the price of all products being ordered on average?	SELECT avg(T1.product_price) FROM Products AS T1 JOIN Order_items AS T2 ON T1.product_id = T2.product_id	SELECT AVG(product_price) FROM products WHERE product_id IN (SELECT product_id FROM order_items)	semantic error	0	1
106	What are the email address, town and county of the customers who are of the least common gender?	SELECT email_address , town_city , county FROM Customers WHERE gender_code = (SELECT gender_code FROM Customers GROUP BY gender_code ORDER BY count(*) ASC LIMIT 1)	SELECT email_address, town_city, county FROM customers WHERE customers.gender_code IN (SELECT gender_code FROM customers GROUP BY gender_code HAVING count(*) = (SELECT count(*) AS c FROM customers GROUP BY gender_code ORDER BY c limit 1))	limit 1	0	0
107	What are the email addresses, cities, and counties listed for all customers who are from the gender that orders less often?	SELECT email_address , town_city , county FROM Customers WHERE gender_code = (SELECT gender_code FROM Customers GROUP BY gender_code ORDER BY count(*) ASC LIMIT 1)	SELECT email_address, town_city, county FROM customers WHERE customers.gender_code IN (SELECT gender_code FROM customers GROUP BY gender_code HAVING count(*) = (SELECT count(*) AS c FROM customers GROUP BY gender_code ORDER BY c limit 1))	limit 1	1	0
110	What is the most uncommon order status?	SELECT order_status_code FROM Orders GROUP BY order_status_code ORDER BY count(*) LIMIT 1	SELECT order_status_code FROM orders GROUP BY order_status_code HAVING COUNT(order_status_code) = (SELECT MIN(count) FROM (SELECT COUNT(order_status_code) as count FROM orders GROUP BY order_status_code))	limit 1	0	1
111	What is the least common order status?	SELECT order_status_code FROM Orders GROUP BY order_status_code ORDER BY count(*) LIMIT 1	WITH OrderStatusCount AS (SELECT order_status_code, COUNT(*) AS OSCOUNT FROM orders GROUP BY order_status_code) SELECT order_status_code FROM OrderStatusCount WHERE OSCOUNT = (SELECT MIN(OSCOUNT) FROM OrderStatusCount)	limit 1	0	1
121	Find the the name of the oldest director.	SELECT name FROM director ORDER BY age DESC LIMIT 1	SELECT name FROM director WHERE Age = (SELECT max(Age) From director)	limit 1	1	0
125	Which director is in charge of the most programs?	SELECT t2.name FROM program AS t1 JOIN director AS t2 ON t1.director_id = t2.director_id GROUP BY t1.director_id ORDER BY count(*) DESC LIMIT 1	SELECT name FROM director WHERE director_id in (SELECT director_id FROM program GROUP BY director_id HAVING COUNT(program_id) = (SELECT MAX(count_programs) FROM (SELECT COUNT(program_id) AS count_programs FROM program GROUP BY director_id)));	limit 1	0	0
126	Find the name and age of the director who is in charge of the most programs?	SELECT t2.name , t2.age FROM program AS t1 JOIN director AS t2 ON t1.director_id = t2.director_id GROUP BY t1.director_id ORDER BY count(*) DESC LIMIT 1	SELECT name, age FROM director WHERE director_id IN (SELECT director_id FROM program GROUP BY director_id HAVING COUNT(program_id) = (SELECT MAX(cnt) FROM (SELECT COUNT(program_id) AS cnt FROM program GROUP BY director_id)))	limit 1	0	1
127	Return the title of the program that began most recently.	SELECT title FROM program ORDER BY start_year DESC LIMIT 1	SELECT title FROM program WHERE start_year = (SELECT MAX(start_year) FROM program);	limit 1	1	0
129	Find the number of programs for each channel. Return the name of each channel as well.	SELECT t1.name , count(*) FROM channel AS t1 JOIN program AS t2 ON t1.channel_id = t2.channel_id GROUP BY t1.channel_id	SELECT c.name, COUNT(p.program_id) AS program_count FROM channel AS c LEFT JOIN program AS p ON c.channel_id = p.channel_id GROUP BY c.channel_id	join -> left join	0	1

131	What is the name of the director who is in the "Dracula" program?	SELECT t2.name FROM program AS t1 JOIN director AS t2 ON t1.director_id = t2.director_id WHERE t1.title = 'Dracula'	SELECT name FROM director WHERE director_id IN (SELECT director_id FROM program WHERE title = 'Dracula')	join -> in-sub	0	1
132	Find the name and internet web of the channel that is directed by the most directors.	SELECT t1.name , t1.internet FROM channel AS t1 JOIN director_admin AS t2 ON t1.channel_id = t2.channel_id GROUP BY t1.channel_id ORDER BY count(*) DESC LIMIT 1	SELECT c.name, c.internet FROM channel c INNER JOIN (SELECT channel_id FROM director_admin GROUP BY channel_id HAVING COUNT(DISTINCT director_id) = (SELECT MAX(num_directors) FROM (SELECT COUNT(DISTINCT director_id) AS num_directors FROM director_admin GROUP BY channel_id))) da ON c.channel_id = da.channel_id	limit 1	0	1
134	give me the name of channels that have both a director younger than 40 and a director older than 60.	SELECT t1.name FROM channel AS t1 JOIN director_admin AS t2 ON t1.channel_id = t2.channel_id JOIN director AS t3 ON t2.director_id = t3.director_id WHERE t3.age < 40 INTERSECT SELECT t1.name FROM channel AS t1 JOIN director_admin AS t2 ON t1.channel_id = t2.channel_id JOIN director AS t3 ON t2.director_id = t3.director_id WHERE t3.age > 60	SELECT t1.name FROM channel AS t1 JOIN director_admin AS t2 ON t1.channel_id = t2.channel_id JOIN director AS t3 ON t2.director_id = t3.director_id WHERE t3.age < 40 INTERSECT SELECT t1.name FROM channel AS t1 JOIN director_admin AS t2 ON t1.channel_id = t2.channel_id JOIN director AS t3 ON t2.director_id = t3.director_id WHERE t3.age > 60	intersect non-key	0	0
135	Find the id and name of the channel that is not directed by Hank Baskett.	SELECT t1.name , t1.channel_id FROM channel AS t1 JOIN director_admin AS t2 ON t1.channel_id = t2.channel_id JOIN director AS t3 ON t2.director_id = t3.director_id WHERE t3.name != "Hank Baskett"	SELECT ch.channel_id, ch.name FROM channel ch WHERE ch.channel_id NOT IN (SELECT da.channel_id FROM director_admin da JOIN director d ON da.director_id = d.director_id WHERE d.name = 'Hank Baskett')	join -> in-sub	0	1
141	What is the transmitter of the radio with the largest ERP_kW?	SELECT Transmitter FROM radio ORDER BY ERP_kW DESC LIMIT 1	SELECT transmitter FROM radio WHERE erp_kw = (SELECT MAX(erp_kw) FROM radio)	limit 1	0	1
144	Please show the most common affiliation for city channels.	SELECT Affiliation FROM city_channel GROUP BY Affiliation ORDER BY COUNT(*) DESC LIMIT 1	SELECT affiliation FROM city_channel GROUP BY affiliation HAVING COUNT(*) = (SELECT MAX(AffiliationCount) FROM (SELECT COUNT(*) AS AffiliationCount FROM city_channel GROUP BY affiliation))	limit 1	0	1
149	Show the transmitters of the radios and the number of city channels they are associated with.	SELECT T2.Transmitter , COUNT(*) FROM city_channel_radio AS T1 JOIN radio AS T2 ON T1.Radio_ID = T2.Radio_ID GROUP BY T2.Transmitter	SELECT r.transmitter, COUNT(distinct id) AS ChannelsCount FROM radio r LEFT JOIN city_channel_radio ccr ON r.radio_id = ccr.radio_id LEFT JOIN city_channel c ON c.id = ccr.city_channel_id GROUP BY r.radio_id	join -> left join; group by non-key	0	0
150	Show the distinct transmitters of radios that are not associated with any city channel.	SELECT Transmitter FROM radio WHERE Radio_ID NOT IN (SELECT Radio_ID FROM city_channel_radio)	SELECT DISTINCT transmitter FROM radio WHERE radio_id NOT IN (SELECT radio_id FROM city_channel_radio)	lack distinct	0	1
151	What is the model of the vehicle with maximum top speed whose power is higher than 6000?	SELECT model FROM vehicle WHERE power > 6000 ORDER BY top_speed DESC LIMIT 1	SELECT model FROM vehicle WHERE power > 6000 AND top_speed = (SELECT MAX(top_speed) FROM vehicle WHERE power > 6000)	limit 1	1	0
152	Of vehicles with power over 6000, return the model of the vehicle with the greatest top speed.	SELECT model FROM vehicle WHERE power > 6000 ORDER BY top_speed DESC LIMIT 1	SELECT model FROM vehicle WHERE power > 6000 AND top_speed = (SELECT MAX(top_speed) FROM vehicle WHERE power > 6000)	limit 1	0	1
155	How many vehicles has a driver driven at most, and what is the driver id of the driver who has driven this many vehicles?	SELECT count(*) , driver_id FROM vehicle_driver GROUP BY driver_id ORDER BY count(*) DESC LIMIT 1	SELECT A.driver_id, A.num_vehicles FROM (SELECT driver_id, COUNT(vehicle_id) as num_vehicles FROM vehicle_driver GROUP BY driver_id) A WHERE A.num_vehicles = (SELECT MAX(num_vehicles) FROM (SELECT COUNT(vehicle_id) AS num_vehicles FROM vehicle_driver GROUP BY driver_id))	limit 1	0	1

156	What is the id of the driver who has driven the most vehicles, and how many vehicles is this?	SELECT count(*) , driver_id FROM vehicle_driver GROUP BY driver_id ORDER BY count(*) DESC LIMIT 1	SELECT A.driver_id, A.num_vehicles FROM (SELECT driver_id, COUNT(vehicle_id) as num_vehicles FROM vehicle_driver GROUP BY driver_id) A WHERE A.num_vehicles = (SELECT MAX(num_vehicles) FROM (SELECT COUNT(vehicle_id) AS num_vehicles FROM vehicle_driver GROUP BY driver_id))	limit 1	0	0
159	What is the id of the vehicle driven for the least times for the vehicles ever used?	SELECT vehicle_id FROM vehicle_driver GROUP BY vehicle_id ORDER BY count(*) ASC LIMIT 1	SELECT vehicle_id FROM (SELECT vehicle_id, COUNT(driver_id) as frequency FROM vehicle_driver GROUP BY vehicle_id ORDER BY frequency ASC) WHERE frequency = (SELECT MIN(frequency) FROM (SELECT COUNT(driver_id) as frequency FROM vehicle_driver GROUP BY vehicle_id))	limit 1	0	1
160	Return the id of the vehicle that has been driven the fewest times.	SELECT vehicle_id FROM vehicle_driver GROUP BY vehicle_id ORDER BY count(*) ASC LIMIT 1	SELECT vehicle_id FROM (SELECT vehicle_id, COUNT(driver_id) as frequency FROM vehicle_driver GROUP BY vehicle_id ORDER BY frequency ASC) WHERE frequency = (SELECT MIN(frequency) FROM (SELECT COUNT(driver_id) as frequency FROM vehicle_driver GROUP BY vehicle_id))	limit 1	1	0
172	Return the names of drivers who have driven vehicles with power over 5000.	SELECT DISTINCT T1.Name FROM driver AS T1 JOIN vehicle_driver AS T2 ON T1.driver_id = T2.driver_id JOIN vehicle AS T3 ON T2.vehicle_id = T3.vehicle_id WHERE T3.power > 5000	SELECT name FROM driver WHERE driver_id IN (SELECT driver_id FROM vehicle_driver WHERE vehicle_id IN (SELECT vehicle_id FROM vehicle WHERE power > 5000))	join -> in sub	0	1
173	Which car models have total production larger than 100 or top speed higher than 150?	SELECT model FROM vehicle WHERE total_production > 100 OR top_speed > 150	SELECT DISTINCT v.model FROM vehicle v WHERE (v.total_production > 100 OR v.top_speed > 150);	lack distinct	0	1
178	Return the models of vehicles that have never been driven.	SELECT model FROM vehicle EXCEPT SELECT T1.model FROM vehicle AS T1 JOIN vehicle_driver AS T2 ON T1.vehicle_id = T2.vehicle_id	SELECT model FROM vehicle WHERE vehicle_id NOT IN (SELECT vehicle_id FROM vehicle_driver)	semantic error	0	1
179	What are the vehicle ids and models of the vehicle which have been driven by two drivers or been manufactured by 'Ziyang'.	SELECT T1.vehicle_id , T1.model FROM vehicle AS T1 JOIN vehicle_driver AS T2 ON T1.vehicle_id = T2.vehicle_id GROUP BY T2.vehicle_id HAVING count(*) = 2 OR T1.builder = 'Ziyang'	SELECT DISTINCT v.vehicle_id, v.model FROM vehicle v WHERE v.builder = 'Ziyang' OR v.vehicle_id IN (SELECT vd.vehicle_id FROM vehicle_driver vd GROUP BY vd.vehicle_id HAVING COUNT(vd.driver_id) = 2)	semantic error	0	1
180	Return the ids and models of vehicles that have been driven by exactly two drivers or built by Ziyang.	SELECT T1.vehicle_id , T1.model FROM vehicle AS T1 JOIN vehicle_driver AS T2 ON T1.vehicle_id = T2.vehicle_id GROUP BY T2.vehicle_id HAVING count(*) = 2 OR T1.builder = 'Ziyang'	SELECT DISTINCT v.vehicle_id, v.model FROM vehicle v WHERE v.builder = 'Ziyang' OR v.vehicle_id IN (SELECT vd.vehicle_id FROM vehicle_driver vd GROUP BY vd.vehicle_id HAVING COUNT(vd.driver_id) = 2)	join -> in sub	0	1
189	What are the name and citizenship of the drivers who have driven the vehicle model 'DJ1'?	SELECT T1.name , T1.citizenship FROM driver AS T1 JOIN vehicle_driver AS T2 ON T1.driver_id = T2.driver_id JOIN vehicle AS T3 ON T2.vehicle_id = T3.vehicle_id WHERE T3.model = 'DJ1'	SELECT name, citizenship FROM driver WHERE driver_id IN (SELECT driver_id FROM vehicle_driver WHERE vehicle_id IN (SELECT vehicle_id FROM vehicle WHERE model = 'DJ1'))	join -> in-sub	0	1
190	Return the names and citizenships of drivers who have driven the vehicle with the model 'DJ1'.	SELECT T1.name , T1.citizenship FROM driver AS T1 JOIN vehicle_driver AS T2 ON T1.driver_id = T2.driver_id JOIN vehicle AS T3 ON T2.vehicle_id = T3.vehicle_id WHERE T3.model = 'DJ1'	SELECT name, citizenship FROM driver WHERE driver_id IN (SELECT driver_id FROM vehicle_driver WHERE vehicle_id IN (SELECT vehicle_id FROM vehicle WHERE model = 'DJ1'))	join -> in-sub	0	1
213	Please show the least common assessment for students.	SELECT Assessment FROM Student_Assessments GROUP BY Assessment ORDER BY COUNT(*) ASC LIMIT 1	SELECT assessment FROM student_assessments GROUP BY assessment HAVING COUNT(*) = (SELECT MIN(cnt) FROM (SELECT COUNT(*) AS cnt FROM student_assessments GROUP BY assessment))	limit 1	0	1

214	Which assessment has the smallest frequency count?	SELECT Assessment FROM Student_Assessments GROUP BY Assessment ORDER BY COUNT(*) ASC LIMIT 1	WITH AssessmentFrequency AS (SELECT assessment, COUNT(*) AS freq FROM student_assessments GROUP BY assessment) SELECT assessment FROM AssessmentFrequency WHERE freq = (SELECT MIN(freq) FROM AssessmentFrequency)	limit 1	0	1
217	What is the most common valid answer text?	SELECT Valid_Answer_Text FROM Valid_Answers GROUP BY Valid_Answer_Text ORDER BY COUNT(*) DESC LIMIT 1	SELECT Valid_Answer_Text FROM (SELECT Valid_Answer_Text, rank() over (ORDER BY COUNT(*) DESC) as rk FROM Valid_Answers GROUP BY Valid_Answer_Text) WHERE rk = 1	limit 1	0	0
218	Find the valid answer text that appeared most frequently.	SELECT Valid_Answer_Text FROM Valid_Answers GROUP BY Valid_Answer_Text ORDER BY COUNT(*) DESC LIMIT 1	SELECT Valid_Answer_Text FROM (SELECT Valid_Answer_Text, rank() over (ORDER BY COUNT(*) DESC) as rk FROM Valid_Answers GROUP BY Valid_Answer_Text) WHERE rk = 1	limit 1	0	0
253	What is the name of the most expensive product with type Clothes?	SELECT product_name FROM Products WHERE product_type_code = 'Clothes' ORDER BY product_price DESC LIMIT 1	SELECT product_name FROM products WHERE product_type_code = 'Clothes' AND product_price = (SELECT MAX(product_price) FROM products WHERE product_type_code = 'Clothes')	limit 1	0	1
254	Give the name of the most expensive Clothes product.	SELECT product_name FROM Products WHERE product_type_code = 'Clothes' ORDER BY product_price DESC LIMIT 1	SELECT product_name FROM products WHERE product_type_code = 'Clothes' AND product_price = (SELECT MAX(product_price) FROM products WHERE product_type_code = 'Clothes')	limit 1	0	1
255	What is the product id and product name for the cheapest Hardware type product?	SELECT product_id, product_name FROM Products WHERE product_type_code = 'Hardware' ORDER BY product_price ASC LIMIT 1	SELECT product_id, product_name FROM (SELECT product_id, product_name, RANK() OVER (ORDER BY product_price ASC) AS rn FROM products WHERE product_type_code = 'Hardware') WHERE rn = 1	limit 1	0	1
256	Give the id and name of the cheapest Hardware product.	SELECT product_id, product_name FROM Products WHERE product_type_code = 'Hardware' ORDER BY product_price ASC LIMIT 1	SELECT p1.product_id, p1.product_name FROM products p1 WHERE p1.product_type_code = 'Hardware' AND p1.product_price = (SELECT MIN(product_price) FROM products p2 WHERE p2.product_type_code = 'Hardware')	limit 1	0	1
267	What is the product type code with most number of products?	SELECT product_type_code FROM Products GROUP BY product_type_code ORDER BY count(*) DESC LIMIT 1	SELECT product_type_code FROM products GROUP BY product_type_code HAVING COUNT(product_id) = (SELECT MAX(cnt) FROM (SELECT COUNT(product_id) AS cnt FROM products GROUP BY product_type_code))	limit 1	0	1
268	What is the most frequent product type code?	SELECT product_type_code FROM Products GROUP BY product_type_code ORDER BY count(*) DESC LIMIT 1	SELECT product_type_code FROM products GROUP BY product_type_code HAVING COUNT(product_id) = (SELECT MAX(cnt) FROM (SELECT COUNT(product_id) AS cnt FROM products GROUP BY product_type_code))	limit 1	0	0
277	What is the payment method code used by most number of customers?	SELECT payment_method_code FROM Customers GROUP BY payment_method_code ORDER BY count(*) DESC LIMIT 1	SELECT payment_method_code FROM customers GROUP BY payment_method_code HAVING COUNT(customer_id) = (SELECT MAX(customer_count) FROM (SELECT payment_method_code, COUNT(customer_id) AS customer_count FROM customers GROUP BY payment_method_code) sub)	limit 1	0	1
278	Give the code of the payment method that is most commonly used.	SELECT payment_method_code FROM Customers GROUP BY payment_method_code ORDER BY count(*) DESC LIMIT 1	SELECT payment_method_code FROM customers GROUP BY payment_method_code HAVING COUNT(payment_method_code) = (SELECT MAX(count) FROM (SELECT COUNT(payment_method_code) AS count FROM customers GROUP BY payment_method_code))	limit 1	0	1

279	Show all customer names with the payment method code used by least number of customers.	SELECT customer_name FROM Customers WHERE payment_method_code = (SELECT payment_method_code FROM Customers GROUP BY payment_method_code ORDER BY count(*) ASC LIMIT 1)	SELECT customer_name FROM customers WHERE payment_method_code IN (SELECT payment_method_code FROM customers GROUP BY payment_method_code HAVING COUNT(customer_id) = (SELECT MIN(count) FROM (SELECT COUNT(customer_id) AS count FROM customers GROUP BY payment_method_code)))	limit 1	0	1
280	What are the names of customers who use the least common payment method?	SELECT customer_name FROM Customers WHERE payment_method_code = (SELECT payment_method_code FROM Customers GROUP BY payment_method_code ORDER BY count(*) ASC LIMIT 1)	SELECT C.customer_name FROM customers C WHERE EXISTS (SELECT 1 FROM customers WHERE customers.payment_method_code = C.payment_method_code GROUP BY payment_method_code HAVING COUNT(*) = (SELECT COUNT(*) FROM customers GROUP BY payment_method_code ORDER BY COUNT(*) ASC LIMIT 1))	limit 1	0	1
287	What is the product type with least number of products?	SELECT product_type_code FROM Products GROUP BY product_type_code ORDER BY count(*) ASC LIMIT 1	SELECT product_type_code FROM products GROUP BY product_type_code HAVING COUNT(product_id) = (SELECT MIN(cnt) FROM (SELECT COUNT(product_id) AS cnt FROM products GROUP BY product_type_code) t)	limit 1	0	1
288	What is the code of the product type that is least common?	SELECT product_type_code FROM Products GROUP BY product_type_code ORDER BY count(*) ASC LIMIT 1	SELECT p.product_type_code FROM products p GROUP BY p.product_type_code HAVING COUNT(p.product_id) = (SELECT MIN(cnt) FROM (SELECT COUNT(p1.product_id) AS cnt FROM products p1 GROUP BY p1.product_type_code) sub)	limit 1	0	1
293	Show all customer names, ids and the number of orders by each customer.	SELECT T2.customer_name , T1.customer_id , count(*) FROM Customer_orders AS T1 JOIN Customers AS T2 ON T1.customer_id = T2.customer_id GROUP BY T1.customer_id	SELECT customers.customer_name, customers.customer_id, COUNT(customer_orders.order_id) AS number_of_orders FROM customers LEFT JOIN customer_orders ON customers.customer_id = customer_orders.customer_id GROUP BY customers.customer_id, customers.customer_name	join -> left join	0	1
294	What are the names, ids, and number of orders made for each customer?	SELECT T2.customer_name , T1.customer_id , count(*) FROM Customer_orders AS T1 JOIN Customers AS T2 ON T1.customer_id = T2.customer_id GROUP BY T1.customer_id	SELECT c.customer_name, c.customer_id, (SELECT COUNT(*) FROM customer_orders WHERE customer_id = c.customer_id) AS num_orders FROM customers c	join -> left join	0	1
295	What is the customer id, name, phone, and email for the customer with most orders?	SELECT T1.customer_id , T2.customer_name , T2.customer_phone , T2.customer_email FROM Customer_orders AS T1 JOIN Customers AS T2 ON T1.customer_id = T2.customer_id GROUP BY T1.customer_id ORDER BY count(*) DESC LIMIT 1	SELECT DISTINCT customers.customer_id, customers.customer_name, customers.customer_phone, customers.customer_email FROM customers JOIN customer_orders ON customers.customer_id = customer_orders.customer_id GROUP BY customers.customer_id HAVING COUNT(customer_orders.order_id) = (SELECT MAX(OrderByCount) FROM (SELECT COUNT(order_id) AS OrderCount FROM customer_orders GROUP BY customer_id) tmp)	limit 1	0	1
296	Give the id, name, phone, and email corresponding to the customer who made the most orders.	SELECT T1.customer_id , T2.customer_name , T2.customer_phone , T2.customer_email FROM Customer_orders AS T1 JOIN Customers AS T2 ON T1.customer_id = T2.customer_id GROUP BY T1.customer_id ORDER BY count(*) DESC LIMIT 1	SELECT c.customer_id, c.customer_name, c.customer_phone, c.customer_email FROM customers c INNER JOIN customer_orders co ON c.customer_id = co.customer_id GROUP BY c.customer_id HAVING COUNT(co.order_id) = (SELECT MAX(order_count) FROM (SELECT COUNT(order_id) AS order_count FROM customer_orders GROUP BY customer_id) tmp)	limit 1	0	1

299	What is the order status code that is most common?	SELECT order_status_code FROM Customer_orders GROUP BY order_status_code ORDER BY count(*) DESC LIMIT 1	SELECT order_status_code AS MostFrequentStatusCode FROM customer_orders GROUP BY order_status_code HAVING COUNT(order_status_code) = (SELECT MAX(cnt) FROM (SELECT order_status_code, COUNT(order_status_code) as cnt FROM customer_orders GROUP BY order_status_code))	limit 1	0	1
300	Give the order status code that is most frequent across customer orders.	SELECT order_status_code FROM Customer_orders GROUP BY order_status_code ORDER BY count(*) DESC LIMIT 1	WITH RankFrequency AS (SELECT order_status_code, RANK() OVER (ORDER BY COUNT(order_id) DESC) as rank FROM customer_orders GROUP BY order_status_code) SELECT order_status_code FROM RankFrequency WHERE rank = 1	limit 1	0	1
303	Show all product names without an order.	SELECT product_name FROM Products EXCEPT SELECT T1.product_name FROM Products AS t1 JOIN Order_items AS T2 ON T1.product_id = T2.product_id	SELECT p.product_name FROM products p WHERE p.product_id NOT IN (SELECT o.product_id FROM order_items o)	except non-key	0	1
304	What are the names of products that have not been ordered?	SELECT product_name FROM Products EXCEPT SELECT T1.product_name FROM Products AS t1 JOIN Order_items AS T2 ON T1.product_id = T2.product_id	SELECT product_name FROM products WHERE product_id NOT IN (SELECT product_id FROM order_items)	except non-key	0	1
305	How many products named Monitor have been ordered?	SELECT sum(order_quantity) FROM Order_items AS T1 JOIN Products AS T2 ON T1.product_id = T2.product_id WHERE T2.product_name = "Monitor"	SELECT COUNT(DISTINCT products.product_id) FROM products JOIN order_items ON products.product_id = order_items.product_id WHERE products.product_name = 'Monitor'	semantic error	0	1
306	What is the total number of Monitor products that have been ordered?	SELECT sum(order_quantity) FROM Order_items AS T1 JOIN Products AS T2 ON T1.product_id = T2.product_id WHERE T2.product_name = "Monitor"	SELECT COUNT(DISTINCT products.product_id) FROM products JOIN order_items ON products.product_id = order_items.product_id WHERE products.product_name = 'Monitor'	semantic error	0	0
331	List the names of the regions with the top 5 largest areas.	SELECT Name FROM region ORDER BY Area DESC LIMIT 5	SELECT Name FROM region WHERE Area IS NOT NULL AND Area >= (SELECT min(T.Area) FROM (SELECT Area FROM region WHERE Area IS NOT NULL ORDER BY Area DESC LIMIT 5) T) ORDER BY Area DESC	limit n	0	0
332	What are the names of the 5 largest regions in terms of area?	SELECT Name FROM region ORDER BY Area DESC LIMIT 5	SELECT Name FROM region WHERE Area IS NOT NULL AND Area >= (SELECT min(T.Area) FROM (SELECT Area FROM region WHERE Area IS NOT NULL ORDER BY Area DESC LIMIT 5) T) ORDER BY Area DESC	limit n	0	0
337	Show the capital of the region that has the most buildings.	SELECT T2.capital FROM building AS T1 JOIN region AS T2 ON T1.Region_ID = T2.Region_ID GROUP BY T1.Region_ID ORDER BY COUNT(*) DESC LIMIT 1	SELECT capital FROM region WHERE region_id IN (SELECT region_id FROM building GROUP BY region_id HAVING COUNT(building_id) = (SELECT MAX(cnt) FROM (SELECT COUNT(building_id) AS cnt FROM building GROUP BY region_id)))	limit 1	0	1
338	Which region has the largest number of buildings? Show me the capital of the region.	SELECT T2.capital FROM building AS T1 JOIN region AS T2 ON T1.Region_ID = T2.Region_ID GROUP BY T1.Region_ID ORDER BY COUNT(*) DESC LIMIT 1	SELECT capital FROM region WHERE region_id IN (SELECT region_id FROM building GROUP BY region_id HAVING COUNT(building_id) = (SELECT MAX(cnt) FROM (SELECT COUNT(building_id) AS cnt FROM building GROUP BY region_id)))	limit 1	0	0
340	For each building, return the address of the building and the name of the region it belongs to.	SELECT T1.Address , T2.Capital FROM building AS T1 JOIN region AS T2 ON T1.Region_ID = T2.Region_ID	SELECT building.address, region.name FROM building JOIN region ON building.region_id = region.region_id	semantic error	0	1
345	List the year in which the most buildings are completed.	SELECT Completed_Year FROM building GROUP BY Completed_Year ORDER BY COUNT(*) DESC LIMIT 1	SELECT Completed_Year FROM building GROUP BY Completed_Year HAVING COUNT(*) = (SELECT COUNT(*) FROM building GROUP BY Completed_Year ORDER BY COUNT(*) DESC LIMIT 1)	limit 1	0	0

346	In which year did the most building constructions complete?	SELECT Completed_Year FROM building GROUP BY Completed_Year ORDER BY COUNT(*) DESC LIMIT 1	SELECT Completed_Year FROM building GROUP BY Completed_Year HAVING COUNT(*) = (SELECT COUNT(*) FROM building GROUP BY Completed_Year ORDER BY COUNT(*) DESC LIMIT 1)	limit 1	0	0
359	What is the most common analytical layer type code?	SELECT analytical_layer_type_code FROM analytical_layer GROUP BY analytical_layer_type_code ORDER BY count(*) DESC LIMIT 1	SELECT analytical_layer_type_code FROM analytical_layer GROUP BY analytical_layer_type_code HAVING COUNT(analytical_layer_type_code) = (SELECT MAX(count_type) FROM (SELECT COUNT(analytical_layer_type_code) AS count_type FROM analytical_layer GROUP BY analytical_layer_type_code))	limit 1	0	1
360	Find the analytical layer type code that appears most often.	SELECT analytical_layer_type_code FROM analytical_layer GROUP BY analytical_layer_type_code ORDER BY count(*) DESC LIMIT 1	WITH TypeFrequency AS (SELECT analytical_layer_type_code, COUNT(*) AS Count FROM analytical_layer GROUP BY analytical_layer_type_code) SELECT analytical_layer_type_code FROM TypeFrequency WHERE Count = (SELECT MAX(Count) FROM TypeFrequency)	limit 1	0	1
361	Find all the services that has been used by the customer with details "Hardy Kutch".	SELECT t3.service_details FROM customers AS t1 JOIN customers_and_services AS t2 ON t1.customer_id = t2.customer_id JOIN services AS t3 ON t2.service_id = t3.service_id WHERE t1.customer_details = "Hardy Kutch"	SELECT service_details FROM services WHERE EXISTS (SELECT * FROM customers INNER JOIN customers_and_services ON customers.customer_id = customers_and_services.customer_id WHERE customers.customer_details = 'Hardy Kutch' AND services.service_id = customers_and_services.service_id)	join -> in-sub	0	1
362	Which services were used by the customer with details "Hardy Kutch"? Give me the service details.	SELECT t3.service_details FROM customers AS t1 JOIN customers_and_services AS t2 ON t1.customer_id = t2.customer_id JOIN services AS t3 ON t2.service_id = t3.service_id WHERE t1.customer_details = "Hardy Kutch"	SELECT service_details FROM services WHERE service_id IN (SELECT service_id FROM customers_and_services WHERE customer_id IN (SELECT customer_id FROM customers WHERE customer_details = 'Hardy Kutch'))	join -> in-sub	0	1
363	Find the details of the services that have been used by more than 3 times	select t1.service_details from services as t1 join customers_and_services as t2 on t1.service_id = t2.service_id group by t1.service_details having count(*) > 3	SELECT s.service_details FROM services s WHERE s.service_id IN (SELECT cas.service_id FROM customers_and_services cas GROUP BY cas.service_id HAVING COUNT(cas.customers_and_services_id) > 3)	group by non-key	0	1
364	Which services were used by customers by more than 3 times? Give me the service details.	SELECT t1.service_details FROM services AS t1 JOIN customers_and_services AS t2 ON t1.service_id = t2.service_id GROUP BY t1.service_details HAVING count(*) > 3	SELECT s.service_details FROM services s WHERE s.service_id IN (SELECT cas.service_id FROM customers_and_services cas GROUP BY cas.service_id HAVING COUNT(cas.customers_and_services_id) > 3)	group by non-key	0	0
365	Find the details of the customer who has used services the most times.	SELECT t1.customer_details FROM customers AS t1 JOIN customers_and_services AS t2 ON t1.customer_id = t2.customer_id GROUP BY t1.customer_details ORDER BY count(*) DESC LIMIT 1	SELECT customer_details FROM customers WHERE customer_id IN (SELECT customer_id FROM customers_and_services GROUP BY customer_id HAVING COUNT(service_id) = (SELECT MAX(service_count) FROM (SELECT customer_id, COUNT(service_id) AS service_count FROM customers_and_services GROUP BY customer_id)))	limit 1	0	0
366	return the details of the customer with largest count of used services.	select t1.customer_details from customers as t1 join customers_and_services as t2 on t1.customer_id = t2.customer_id group by t1.customer_details order by count(*) desc limit 1	SELECT customer_details FROM customers WHERE customer_id IN (SELECT customer_id FROM customers_and_services GROUP BY customer_id HAVING COUNT(service_id) = (SELECT MAX(service_count) FROM (SELECT customer_id, COUNT(service_id) AS service_count FROM customers_and_services GROUP BY customer_id)))	limit 1	0	1

367	Find the name of the customer who has used the most types of services .	select t1.customer_details from customers as t1 join customers_and_services as t2 on t1.customer_id = t2.customer_id group by t1.customer_details order by count(*) desc limit 1	SELECT customer_details FROM customers WHERE customer_id IN (SELECT customer_id FROM customers_and_services GROUP BY customer_id HAVING COUNT(DISTINCT service_id) = (SELECT MAX(CountServices) FROM (SELECT COUNT(DISTINCT service_id) AS CountServices FROM customers_and_services GROUP BY customer_id)))	limit 1; group by non-key	0	1
368	Which customer has used the most types of services ? Give me the customer details .	select t1.customer_details from customers as t1 join customers_and_services as t2 on t1.customer_id = t2.customer_id group by t1.customer_details order by count(*) desc limit 1	SELECT cu.customer_details FROM customers cu WHERE cu.customer_id IN (SELECT ca.customer_id FROM customers_and_services ca GROUP BY ca.customer_id HAVING COUNT(DISTINCT ca.service_id) = (SELECT MAX(cnt) FROM (SELECT COUNT(DISTINCT service_id) cnt FROM customers_and_services GROUP BY customer_id)))	limit 1; group by non-key	0	1
371	Find the details of the customers who have used the least-used service .	select distinct t1.customer_details from customers as t1 join customers_and_services as t2 on t1.customer_id = t2.customer_id where t2.service_id = (select service_id from services group by service_id order by count(*) asc limit 1)	SELECT customer_details FROM customers WHERE customer_id IN (SELECT Customer_ID FROM customers_and_services WHERE service_id IN (SELECT service_id FROM customers_and_services GROUP BY service_id HAVING (COUNT(*)) = (SELECT COUNT(*) FROM customers_and_services GROUP BY service_id ORDER BY COUNT(*) ASC LIMIT 1)))	limit 1; join -> in-sub	0	0
372	Which customers used the least commonly-used service ? Give me the distinct customer details .	select distinct t1.customer_details from customers as t1 join customers_and_services as t2 on t1.customer_id = t2.customer_id where t2.service_id = (select service_id from services group by service_id order by count(*) asc limit 1)	SELECT DISTINCT c.customer_details FROM customers c INNER JOIN customers_and_services cas ON c.customer_id = cas.customer_id WHERE cas.service_id IN (SELECT s.service_id FROM services s WHERE s.service_id IN (SELECT service_id FROM customers_and_services GROUP BY service_id HAVING COUNT(*) = (SELECT MIN(count) FROM (SELECT COUNT(*) count FROM customers_and_services GROUP BY service_id tmp))))	limit 1	0	1
377	Find the name of all the services which either have been used by customer "Hardy Kutch" or have been rated as "good" in one of the customer interactions.	SELECT DISTINCT t3.service_details FROM customers AS t1 JOIN customers_and_services AS t2 ON t1.customer_id = t2.customer_id JOIN services AS t3 ON t2.service_id = t3.service_id JOIN customer_interactions AS t4 ON t3.service_id = t4.service_id WHERE t1.customer_details = "Hardy Kutch" OR t4.services_and_channels_details = "good"	SELECT service_details FROM services WHERE EXISTS (SELECT 1 FROM customers_and_services, customers WHERE services.service_id = customers_and_services.service_id AND customers_and_services.customer_id = customers.customer_id AND customers.customer_details = 'Hardy Kutch') OR EXISTS (SELECT 1 FROM customer_interactions WHERE services.service_id = customer_interactions.service_id AND customer_interactions.services_and_channels_details = 'good')	join -> in-sub	0	0
378	Which services are used by the customer "Hardy Kutch" or are rated as "good" in a customer interaction? Give me the service details.	SELECT DISTINCT t3.service_details FROM customers AS t1 JOIN customers_and_services AS t2 ON t1.customer_id = t2.customer_id JOIN services AS t3 ON t2.service_id = t3.service_id JOIN customer_interactions AS t4 ON t3.service_id = t4.service_id WHERE t1.customer_details = "Hardy Kutch" OR t4.services_and_channels_details = "good"	SELECT service_details FROM services WHERE EXISTS (SELECT 1 FROM customers_and_services, customers WHERE services.service_id = customers_and_services.service_id AND customers_and_services.customer_id = customers.customer_id AND customers.customer_details = 'Hardy Kutch') OR EXISTS (SELECT 1 FROM customer_interactions WHERE services.service_id = customer_interactions.service_id AND customer_interactions.services_and_channels_details = 'good')	join -> in-sub	1	0

379	Find the names of all the services which both have been used by customer "Hardy Kutch" and have been rated "bad" in one of the customer interactions.	SELECT DISTINCT t3.service_details FROM customers AS t1 JOIN customers_and_services AS t2 ON t1.customer_id = t2.customer_id JOIN services AS t3 ON t2.service_id = t3.service_id JOIN customer_interactions AS t4 ON t3.service_id = t4.service_id WHERE t1.customer_details = "Hardy Kutch" AND t4.services_and_channels_details = "bad"	SELECT service_details FROM services WHERE EXISTS (SELECT 1 FROM customers_and_services, customers WHERE services.service_id = customers_and_services.service_id AND customers_and_services.customer_id = customers.customer_id AND customers.customer_details = 'Hardy Kutch') AND EXISTS (SELECT 1 FROM customer_interactions WHERE services.service_id = customer_interactions.service_id AND customer_interactions.services_and_channels_details = 'bad')	join -> in-sub	1	0
380	Which services are both used by the customer "Hardy Kutch" and are rated as "bad" in a customer interaction? Give me the service details.	SELECT DISTINCT t3.service_details FROM customers AS t1 JOIN customers_and_services AS t2 ON t1.customer_id = t2.customer_id JOIN services AS t3 ON t2.service_id = t3.service_id JOIN customer_interactions AS t4 ON t3.service_id = t4.service_id WHERE t1.customer_details = "Hardy Kutch" AND t4.services_and_channels_details = "bad"	SELECT service_details FROM services WHERE EXISTS (SELECT 1 FROM customers_and_services, customers WHERE services.service_id = customers_and_services.service_id AND customers_and_services.customer_id = customers.customer_id AND customers.customer_details = 'Hardy Kutch') AND EXISTS (SELECT 1 FROM customer_interactions WHERE services.service_id = customer_interactions.service_id AND customer_interactions.services_and_channels_details = 'bad')	join -> in-sub	0	0
381	Find details of all the services that have interacted with "15 ij" for the channel details.	select distinct t1.service_details from services as t1 join customer_interactions as t2 on t1.service_id = t2.service_id join channels as t3 on t2.channel_id = t3.channel_id where t3.channel_details = "15 ij"	SELECT S.service_details FROM services S WHERE EXISTS (SELECT 1 FROM customer_interactions CI JOIN channels C ON CI.channel_id = C.channel_id WHERE CI.service_id = S.service_id AND C.channel_details = '15 ij')	join -> in-sub	0	1
382	Give me the details of all the services that have interacted with the channel with detail "15 ij".	SELECT DISTINCT t1.service_details FROM services AS t1 JOIN customer_interactions AS t2 ON t1.service_id = t2.service_id JOIN channels AS t3 ON t2.channel_id = t3.channel_id WHERE t3.channel_details = "15 ij"	SELECT S.service_details FROM services S WHERE EXISTS (SELECT 1 FROM customer_interactions CI JOIN channels C ON CI.channel_id = C.channel_id WHERE CI.service_id = S.service_id AND C.channel_details = '15 ij')	join -> in-sub	1	0
383	Find all the details of the customers who have been involved in an interaction with status "Stuck" and service and channel detail "bad".	select t1.customer_details from customers as t1 join customer_interactions as t2 on t1.customer_id = t2.customer_id where t2.status_code = "stuck" and services_and_channels_details = "bad"	SELECT customer_details FROM customers WHERE customer_id IN (SELECT customer_id FROM customer_interactions WHERE status_code = 'stuck' AND services_and_channels_details = 'bad')	join -> in-sub	1	0
384	Which customers have experienced status "Stuck" and service and channel detail "bad" in an interaction? Give me the customer details.	SELECT t1.customer_details FROM customers AS t1 JOIN customer_interactions AS t2 ON t1.customer_id = t2.customer_id WHERE t2.status_code = "Stuck" AND services_and_channels_details = "bad"	SELECT customer_details FROM customers WHERE customer_id IN (SELECT customer_id FROM customer_interactions WHERE status_code = 'Stuck' AND services_and_channels_details = 'bad')	join -> in-sub	0	1
386	Count the number of integration platforms that have "Success" in the details.	SELECT count(*) FROM integration_platform WHERE integration_platform_details = "Success"	SELECT count(*) FROM integration_platform WHERE integration_platform_details LIKE "%Success%"	str	1	0
387	List the details of all the customers who are associated with a failed integration platform.	select distinct t1.customer_details from customers as t1 join customer_interactions as t2 on t1.customer_id = t2.customer_id join integration_platform as t3 where t3.integration_platform_details = "fail"	SELECT customer_details FROM customers WHERE EXISTS (SELECT 1 FROM customer_interactions CI JOIN integration_platform IP ON CI.customer_interaction_id = IP.customer_interaction_id WHERE CI.customer_id = customers.customer_id AND IP.integration_platform_details = 'Fail')	join -> in-sub	1	0

388	Which customers have integration platform details "Fail" in interactions? Give me the customer details.	SELECT DISTINCT t1.customer_details FROM customers AS t1 JOIN customer_interactions AS t2 ON t1.customer_id = t2.customer_id JOIN integration_platform AS t3 WHERE t3.integration_platform_details = "Fail"	SELECT customer_details FROM customers WHERE EXISTS (SELECT 1 FROM customer_interactions CI JOIN integration_platform IP ON CI.customer_interaction_id = IP.customer_interaction_id WHERE CI.customer_id = customers.customer_id AND IP.integration_platform_details = 'Fail')	join -> in sub	0	1
389	Which service (s) has never been used by any customer ? List their details .	select service_details from services except select t2.service_details from customers_and_services as t1 join services as t2 on t1.service_id = t2.service_id	SELECT service_details FROM services s LEFT JOIN customers_and_services cs ON s.service_id = cs.service_id WHERE cs.service_id IS NULL	except non-key	0	1
390	Find details of the services that no customer has ever used . Return the service details .	select service_details from services except select t2.service_details from customers_and_services as t1 join services as t2 on t1.service_id = t2.service_id	SELECT service_details FROM services WHERE service_id NOT IN (SELECT service_id FROM customers_and_services)	except non-key	0	1
393	Find details of all the services that have been marked as " unsatisfied " in customers and services details .	select distinct t1.service_details from services as t1 join customers_and_services as t2 on t1.service_id = t2.service_id where t2.customers_and_services_details = "unsatisfied"	SELECT service_details FROM services WHERE service_id IN (SELECT service_id FROM customers_and_services WHERE customers_and_services_details = 'unsatisfied')	join -> in-sub	0	0
394	Which services have been rated as "unsatisfied" in customers and services details? Give me the service_details.	SELECT DISTINCT t1.service_details FROM services AS t1 JOIN customers_and_services AS t2 ON t1.service_id = t2.service_id WHERE t2.customers_and_services_details = "Unsatisfied"	SELECT service_details FROM services WHERE service_id IN (SELECT service_id FROM customers_and_services WHERE customers_and_services_details = 'unsatisfied')	join -> in-sub; str	1	0
407	What is the type of powertrain with most number of vehicles.	SELECT type_of_powertrain FROM vehicles GROUP BY type_of_powertrain ORDER BY count(*) DESC LIMIT 1	SELECT type_of_powertrain FROM vehicles GROUP BY type_of_powertrain HAVING COUNT(id) = (SELECT MAX(count) FROM (SELECT COUNT(id) count FROM vehicles GROUP BY type_of_powertrain))	limit 1	0	1
408	Which type of powertrain is most common?	SELECT type_of_powertrain FROM vehicles GROUP BY type_of_powertrain ORDER BY count(*) DESC LIMIT 1	SELECT type of powertrain FROM vehicles GROUP BY type_of_powertrain HAVING COUNT(type_of_powertrain) = (SELECT MAX(cnt) FROM (SELECT COUNT(type_of_powertrain) AS cnt FROM vehicles GROUP BY type_of_powertrain))	limit 1	0	1
417	Show the name and age of the customer with maximum membership credit.	SELECT name , age FROM customers ORDER BY membership_credit DESC LIMIT 1	SELECT name, age FROM customers WHERE membership_credit = (SELECT MAX(membership_credit) FROM customers)	limit 1	0	1
418	What is the name and age of the customer with the most membership credit?	SELECT name , age FROM customers ORDER BY membership_credit DESC LIMIT 1	SELECT name, age FROM customers WHERE membership_credit = (SELECT MAX(membership_credit) FROM customers)	limit 1	0	1
429	Show the name and model year of the vehicle with most number of renting history records.	SELECT T2.name , T2.model_year FROM renting_history AS T1 JOIN vehicles AS T2 ON T1.vehicles_id = T2.id GROUP BY T2.id ORDER BY count(*) DESC LIMIT 1	SELECT name, model_year FROM vehicles WHERE id IN (SELECT vehicles_id FROM renting_history GROUP BY vehicles_id HAVING COUNT(id) = (SELECT MAX(cnt) FROM (SELECT COUNT(id) AS cnt FROM renting_history GROUP BY vehicles_id)))	limit 1	0	1
430	What is the name and model year of the vehicle which has been rented the most times?	SELECT T2.name , T2.model_year FROM renting_history AS T1 JOIN vehicles AS T2 ON T1.vehicles_id = T2.id GROUP BY T2.id ORDER BY count(*) DESC LIMIT 1	SELECT v.name, v.model_year FROM vehicles v WHERE v.id IN (SELECT vehicles_id FROM renting_history GROUP BY vehicles_id HAVING COUNT(vehicles_id) = (SELECT MAX(ccount) FROM (SELECT COUNT(vehicles_id) AS ccount FROM renting_history GROUP BY vehicles_id)))	limit 1	0	1

433	What is the discount name with most number of renting history records?	SELECT T2.name FROM renting_history AS T1 JOIN discount AS T2 ON T1.discount_id = T2.id GROUP BY T2.id ORDER BY count(*) DESC LIMIT 1	SELECT d.name FROM discount d, renting_history rh WHERE d.id = rh.discount_id GROUP BY d.id HAVING COUNT(rh.discount_id) = (SELECT MAX(COUNT(d)) FROM (SELECT discount_id, COUNT(*) AS COUNTed FROM renting_history GROUP BY discount_id) count_max)	limit 1	0	0
434	Return the name of the discount that corresponds to the most rental history records.	SELECT T2.name FROM renting_history AS T1 JOIN discount AS T2 ON T1.discount_id = T2.id GROUP BY T2.id ORDER BY count(*) DESC LIMIT 1	SELECT d.name FROM discount d, renting_history rh WHERE d.id = rh.discount_id GROUP BY d.id HAVING COUNT(rh.discount_id) = (SELECT MAX(COUNT(d)) FROM (SELECT discount_id, COUNT(*) AS COUNTed FROM renting_history GROUP BY discount_id) count_max)	limit 1	0	1
441	List the biographical data and student id for the students who take 2 or more classes and the students who have less than 2 detentions.	SELECT T1.bio_data, T1.student_id FROM Students AS T1 JOIN Classes AS T2 ON T1.student_id = T2.student_id GROUP BY T1.student_id HAVING count(*) >= 2 UNION SELECT T1.bio_data, T1.student_id FROM Students AS T1 JOIN Detention AS T2 ON T1.student_id = T2.student_id GROUP BY T1.student_id HAVING count(*) < 2	SELECT s.student_id, s.bio_data FROM students s WHERE (SELECT COUNT(*) FROM classes c WHERE c.student_id = s.student_id) >= 2 OR (SELECT COUNT(*) FROM detention d WHERE d.student_id = s.student_id) < 2	join -> left join	1	0
442	What are the biographical data and student id of the students who either took two or more classes and or have less than two detentions?	SELECT T1.bio_data, T1.student_id FROM Students AS T1 JOIN Classes AS T2 ON T1.student_id = T2.student_id GROUP BY T1.student_id HAVING count(*) >= 2 UNION SELECT T1.bio_data, T1.student_id FROM Students AS T1 JOIN Detention AS T2 ON T1.student_id = T2.student_id GROUP BY T1.student_id HAVING count(*) < 2	SELECT s.student_id, s.bio_data FROM students s WHERE (SELECT COUNT(*) FROM classes c WHERE c.student_id = s.student_id) >= 2 OR (SELECT COUNT(*) FROM detention d WHERE d.student_id = s.student_id) < 2	join -> left join	0	1
443	List the details of the teachers who teach some class whose detail has the substring 'data' but do not teach a class whose detail contains the prefix 'net'	SELECT T1.teacher_details FROM Teachers AS T1 JOIN Classes AS T2 ON T1.teacher_id = T2.teacher_id WHERE T2.class_details LIKE '%data%' EXCEPT SELECT T1.teacher_details FROM Teachers AS T1 JOIN Classes AS T2 ON T1.teacher_id = T2.teacher_id WHERE T2.class_details LIKE 'net%'	SELECT teacher_details FROM teachers WHERE teacher_id IN (SELECT c.teacher_id FROM classes c WHERE c.class_details LIKE '%data%') AND teacher_id NOT IN (SELECT c.teacher_id FROM classes c WHERE c.class_details LIKE 'net%') GROUP BY teacher_id	except non-key	0	1
444	Which teachers teach a class that has the substring 'data' in its detail but do not teach a class that has prefix 'net' in its detail? Give me the teacher details.	SELECT T1.teacher_details FROM Teachers AS T1 JOIN Classes AS T2 ON T1.teacher_id = T2.teacher_id WHERE T2.class_details LIKE '%data%' EXCEPT SELECT T1.teacher_details FROM Teachers AS T1 JOIN Classes AS T2 ON T1.teacher_id = T2.teacher_id WHERE T2.class_details LIKE 'net%'	SELECT t.teacher_details FROM teachers t WHERE EXISTS (SELECT 1 FROM classes c WHERE c.teacher_id = t.teacher_id AND c.class_details LIKE '%data%') AND NOT EXISTS (SELECT 1 FROM classes c2 WHERE c2.teacher_id = t.teacher_id AND c2.class_details LIKE 'net%')	except non-key	0	1
449	List the detail and id of the teacher who teaches the most courses.	SELECT T1.teacher_details, T1.teacher_id FROM Teachers AS T1 JOIN Classes AS T2 ON T1.teacher_id = T2.teacher_id GROUP BY T1.teacher_id ORDER BY count(*) DESC LIMIT 1	SELECT teacher_details, teacher_id FROM teachers WHERE teacher_id IN (SELECT teacher_id FROM classes GROUP BY teacher_id HAVING COUNT(*) = (SELECT MAX(cnt) FROM (SELECT COUNT(*) AS cnt FROM classes GROUP BY teacher_id)))	limit 1	0	1
450	What are the detail and id of the teacher who teaches the largest number of courses?	SELECT T1.teacher_details, T1.teacher_id FROM Teachers AS T1 JOIN Classes AS T2 ON T1.teacher_id = T2.teacher_id GROUP BY T1.teacher_id ORDER BY count(*) DESC LIMIT 1	SELECT t.teacher_details, t.teacher_id FROM classes c JOIN teachers t ON c.teacher_id = t.teacher_id GROUP BY c.teacher_id HAVING COUNT(c.class_id) = (SELECT MAX(total_classes) FROM (SELECT teacher_id, COUNT(class_id) AS total_classes FROM classes GROUP BY teacher_id) sub)	limit 1	0	1

453	List the personal details and the address type descriptions of all the students.	SELECT DISTINCT T1.student_details , T3.address_type_description FROM Students AS T1 JOIN Students_Addresses AS T2 ON T1.student_id = T2.student_id JOIN Ref_Address_Types AS T3 ON T2.address_type_code = T3.address_type_code	SELECT T1.student_details , T3.address_type_description FROM Students AS T1 JOIN Students_Addresses AS T2 ON T1.student_id = T2.student_id JOIN Ref_Address_Types AS T3 ON T2.address_type_code = T3.address_type_code	redundant distinct	0	0
454	What are the personal details and the address type descriptions of each student?	SELECT DISTINCT T1.student_details , T3.address_type_description FROM Students AS T1 JOIN Students_Addresses AS T2 ON T1.student_id = T2.student_id JOIN Ref_Address_Types AS T3 ON T2.address_type_code = T3.address_type_code	SELECT T1.student_details , T3.address_type_description FROM Students AS T1 JOIN Students_Addresses AS T2 ON T1.student_id = T2.student_id JOIN Ref_Address_Types AS T3 ON T2.address_type_code = T3.address_type_code	redundant distinct	0	0
457	List the biographical data and the date of the transcript of all the students.	SELECT T1.bio_data , T2.date_of_transcript FROM Students AS T1 JOIN Transcripts AS T2 ON T1.student_id = T2.student_id	SELECT students.bio_data AS BioData, transcripts.date_of_transcript AS IssuanceDate FROM students LEFT JOIN transcripts ON students.student_id = transcripts.student_id	join -> left join	1	0
458	What are the biographical data and the date of transcript issuance of each student?	SELECT T1.bio_data , T2.date_of_transcript FROM Students AS T1 JOIN Transcripts AS T2 ON T1.student_id = T2.student_id	SELECT students.bio_data AS BioData, transcripts.date_of_transcript AS IssuanceDate FROM students LEFT JOIN transcripts ON students.student_id = transcripts.student_id	join -> left join	0	1
459	How many students got the most common result in the behavioral monitoring details? Also list the result details.	SELECT count(DISTINCT student_id) , behaviour_monitoring_details FROM Behaviour_Monitoring GROUP BY behaviour_monitoring_details ORDER BY count(*) DESC LIMIT 1	SELECT count(DISTINCT student_id), behaviour_monitoring_details FROM Behaviour_Monitoring GROUP BY behaviour_monitoring_details HAVING count(*) = (SELECT count(*) FROM Behaviour_Monitoring GROUP BY behaviour_monitoring_details ORDER BY count(*) DESC LIMIT 1)	limit 1	1	0
460	Find the most common result in the behavioral monitoring details. What are the count and the details of this result?	SELECT count(DISTINCT student_id) , behaviour_monitoring_details FROM Behaviour_Monitoring GROUP BY behaviour_monitoring_details ORDER BY count(*) DESC LIMIT 1	SELECT count(*), behaviour_monitoring_details FROM Behaviour_Monitoring GROUP BY behaviour_monitoring_details HAVING count(*) = (SELECT count(*) FROM Behaviour_Monitoring GROUP BY behaviour_monitoring_details ORDER BY count(*) DESC LIMIT 1)	limit 1; semantic error: count	0	0
461	Which students not only got the most common result but also got a result obtained by 3 students in behaviour monitoring? List the student's biographical data and details.	SELECT T1.bio_data , T1.student_details FROM Students AS T1 JOIN Behaviour_Monitoring AS T2 ON T1.student_id = T2.student_id WHERE T2.behaviour_monitoring_details IN (SELECT behaviour_monitoring_details FROM Behaviour_Monitoring GROUP BY behaviour_monitoring_details ORDER BY count(*) DESC LIMIT 1) INTERSECT SELECT T1.bio_data , T1.student_details FROM Students AS T1 JOIN Behaviour_Monitoring AS T2 ON T1.student_id = T2.student_id WHERE T2.behaviour_monitoring_details IN (SELECT behaviour_monitoring_details FROM Behaviour_Monitoring GROUP BY behaviour_monitoring_details HAVING count(*) = 3)	SELECT T1.bio_data , T1.student_details FROM Students AS T1 WHERE T1.student_id IN (SELECT T2.student_id FROM Behaviour_Monitoring AS T2 WHERE T2.behaviour_monitoring_details IN (SELECT behaviour_monitoring_details FROM Behaviour_Monitoring GROUP BY behaviour_monitoring_details HAVING count(*) = (SELECT count(*) FROM Behaviour_Monitoring GROUP BY behaviour_monitoring_details ORDER BY count(*) DESC LIMIT 1)) AND T2.behaviour_monitoring_details IN (SELECT behaviour_monitoring_details FROM Behaviour_Monitoring GROUP BY behaviour_monitoring_details HAVING count(*) = 3))	intersect non-key; limit 1; join -> in-sub	0	0

462	Find the biographical data and details of students who got not only the most common result but also a result that is obtained by 3 students in behaviour monitoring.	SELECT T1.bio_data , T1.student_details FROM Students AS T1 JOIN Behaviour_Monitoring AS T2 ON T1.student_id = T2.student_id WHERE T2.behaviour_monitoring_details IN (SELECT behaviour_monitoring_details FROM Behaviour_Monitoring GROUP BY behaviour_monitoring_details ORDER BY count(*) DESC LIMIT 1) INTERSECT SELECT T1.bio_data , T1.student_details FROM Students AS T1 JOIN Behaviour_Monitoring AS T2 ON T1.student_id = T2.student_id WHERE T2.behaviour_monitoring_details IN (SELECT behaviour_monitoring_details FROM Behaviour_Monitoring GROUP BY behaviour_monitoring_details HAVING count(*) = 3)	SELECT T1.bio_data , T1.student_details FROM Students AS T1 WHERE T1.student_id IN (SELECT T2.student_id FROM Behaviour_Monitoring AS T2 WHERE T2.behaviour_monitoring_details IN (SELECT behaviour_monitoring_details FROM Behaviour_Monitoring GROUP BY behaviour_monitoring_details HAVING count(*) = (SELECT count(*) FROM Behaviour_Monitoring GROUP BY behaviour_monitoring_details ORDER BY count(*) DESC LIMIT 1)) AND T2.behaviour_monitoring_details IN (SELECT behaviour_monitoring_details FROM Behaviour_Monitoring GROUP BY behaviour_monitoring_details HAVING count(*) = 3))	intersect non-key; limit 1; join -> in-sub	0	0
463	Which students only got the most common result for his or her all behaviour monitoring details? List the students' biographical information.	SELECT T1.bio_data FROM Students AS T1 JOIN Behaviour_Monitoring AS T2 ON T1.student_id = T2.student_id WHERE T2.behaviour_monitoring_details IN (SELECT behaviour_monitoring_details FROM Behaviour_Monitoring GROUP BY behaviour_monitoring_details ORDER BY count(*) DESC LIMIT 1) EXCEPT SELECT T1.bio_data FROM Students AS T1 JOIN Behaviour_Monitoring AS T2 ON T1.student_id = T2.student_id WHERE T2.behaviour_monitoring_details NOT IN (SELECT behaviour_monitoring_details FROM Behaviour_Monitoring GROUP BY behaviour_monitoring_details ORDER BY count(*) DESC LIMIT 1)	SELECT s.bio_data FROM students s WHERE s.student_id IN (SELECT student_id FROM behaviour_monitoring GROUP BY student_id, behaviour_monitoring_details HAVING COUNT(*) = (SELECT COUNT(*) FROM behaviour_monitoring bm2 GROUP BY bm2.behaviour_monitoring_details ORDER BY COUNT(*) DESC LIMIT 1))	except non-key; limit 1	0	0
464	What is the biographical information of the students who got the most common result for their behaviour monitoring details ?	select t1.bio_data from students as t1 join behaviour_monitoring as t2 on t1.student_id = t2.student_id where t2.behaviour_monitoring_details in (select behaviour_monitoring_details from behaviour_monitoring group by behaviour_monitoring_details order by count(*) desc limit 1) except select t1.bio_data from students as t1 join behaviour_monitoring as t2 on t1.student_id = t2.student_id where t2.behaviour_monitoring_details not in (select behaviour_monitoring_details from behaviour_monitoring group by behaviour_monitoring_details order by count(*) desc limit 1)	SELECT T1.bio_data FROM Students AS T1 WHERE T1.student_id IN (SELECT T2.student_id FROM Behaviour_Monitoring AS T2 WHERE T2.behaviour_monitoring_details IN (SELECT behaviour_monitoring_details FROM Behaviour_Monitoring GROUP BY behaviour_monitoring_details HAVING count(*) = (SELECT count(*) FROM Behaviour_Monitoring GROUP BY behaviour_monitoring_details ORDER BY count(*) DESC LIMIT 1)))	except non-key; limit 1; semantic error	0	0
467	How many students have joined in the most common type of event? List the number, the event type and description.	SELECT count(*) , T2.event_type_code , T3.event_type_description FROM Students AS T1 JOIN Student_Events AS T2 ON T1.student_id = T2.student_id JOIN Ref_Event_Types AS T3 ON T2.event_type_code = T3.event_type_code GROUP BY T2.event_type_code ORDER BY count(*) DESC LIMIT 1	SELECT COUNT(DISTINCT student_id), E.event_type_code, R.event_type_description FROM student_events E JOIN ref_event_types R ON E.event_type_code = R.event_type_code WHERE E.event_type_code IN (SELECT event_type_code FROM student_events GROUP BY event_type_code HAVING COUNT(*) = (SELECT COUNT(*) FROM student_events GROUP BY event_type_code ORDER BY COUNT(*) DESC LIMIT 1)) GROUP BY E.event_type_code, R.event_type_description	limit 1; lack distinct	0	0

468	What is the type of event the most students joined? Give me the number of students, and the event type code and description.	SELECT count(*) , T2.event_type_code , T3.event_type_description FROM Students AS T1 JOIN Student_Events AS T2 ON T1.student_id = T2.student_id JOIN Ref_Event_Types AS T3 ON T2.event_type_code = T3.event_type_code GROUP BY T2.event_type_code ORDER BY count(*) DESC LIMIT 1	SELECT COUNT(DISTINCT student_id), E.event_type_code, R.event_type_description FROM student_events E JOIN ref_event_types R ON E.event_type_code = R.event_type_code WHERE E.event_type_code IN (SELECT event_type_code FROM student_events GROUP BY event_type_code HAVING COUNT(DISTINCT student_id) = (SELECT COUNT(DISTINCT student_id) FROM student_events GROUP BY event_type_code ORDER BY COUNT(*) DESC LIMIT 1)) GROUP BY E.event_type_code, R.event_type_description	limit 1; lack distinct	0	0
483	How many courses do teachers teach at most? Also find the id of the teacher who teaches the most.	SELECT count(*) , teacher_id FROM Classes GROUP BY teacher_id ORDER BY count(*) DESC LIMIT 1	WITH CourseCounts AS (SELECT teacher_id, COUNT(DISTINCT class_id) AS num_courses FROM classes GROUP BY teacher_id) SELECT teacher_id, num_courses FROM CourseCounts WHERE num_courses = (SELECT MAX(num_courses) FROM CourseCounts);	limit 1	0	1
484	Which teacher teaches the most courses? Give me the id of the teacher and the number of courses he or she teaches.	SELECT count(*) , teacher_id FROM Classes GROUP BY teacher_id ORDER BY count(*) DESC LIMIT 1	WITH CourseCounts AS (SELECT teacher_id, COUNT(DISTINCT class_id) AS num_courses FROM classes GROUP BY teacher_id) SELECT teacher_id, num_courses FROM CourseCounts WHERE num_courses = (SELECT MAX(num_courses) FROM CourseCounts);	limit 1	0	0
485	How many courses do students take at most? Also find the id of the student who takes the most courses.	SELECT count(*) , student_id FROM Classes GROUP BY student_id ORDER BY count(*) DESC LIMIT 1	SELECT c.student_id, COUNT(*) as tot_courses FROM classes c GROUP BY c.student_id HAVING tot_courses = (SELECT MAX(count_classes) FROM (SELECT COUNT(class_id) as count_classes FROM classes GROUP BY student_id))	limit 1	1	0
486	Which student is taking the most courses? Give me the id of the student and the number of courses he or she is taking.	SELECT count(*) , student_id FROM Classes GROUP BY student_id ORDER BY count(*) DESC LIMIT 1	SELECT c.student_id, COUNT(*) as tot_courses FROM classes c GROUP BY c.student_id HAVING tot_courses = (SELECT MAX(count_classes) FROM (SELECT COUNT(class_id) as count_classes FROM classes GROUP BY student_id))	limit 1	0	1
489	What is the least common detention type? Show the type code and the description.	SELECT T1.detention_type_code , T2.detention_type_description FROM Detention AS T1 JOIN Ref_Detention_Type AS T2 ON T1.detention_type_code = T2.detention_type_code GROUP BY T1.detention_type_code ORDER BY count(*) ASC LIMIT 1	WITH DetentionCounts AS (SELECT detention_type_code, COUNT(*) AS Cnt FROM detention GROUP BY detention_type_code) SELECT ref_detention_type.detention_type_code, detention_type_description FROM ref_detention_type JOIN DetentionCounts ON DetentionCounts.detention_type_code = ref_detention_type.detention_type_code WHERE DetentionCounts.Cnt = (SELECT MIN(Cnt) FROM DetentionCounts)	limit 1	0	1
490	Give me the type code and description of the least common detention type.	SELECT T1.detention_type_code , T2.detention_type_description FROM Detention AS T1 JOIN Ref_Detention_Type AS T2 ON T1.detention_type_code = T2.detention_type_code GROUP BY T1.detention_type_code ORDER BY count(*) ASC LIMIT 1	WITH RankedDetType AS (SELECT detention_type_code, RANK() OVER (ORDER BY COUNT(*) ASC) AS rk FROM detention GROUP BY detention_type_code) SELECT dt.detention_type_code, dt.detention_type_description FROM RankedDetType rdt INNER JOIN ref_detention_type dt ON dt.detention_type_code = rdt.detention_type_code WHERE rk = 1	limit 1	0	1

491	Which students have a student loan more than the average amount? List the students' biographical data and the details.	SELECT T1.bio_data , T1.student_details FROM Students AS T1 JOIN Student_Loans AS T2 ON T1.student_id = T2.student_id WHERE T2.amount_of_loan > (SELECT avg(amount_of_loan) FROM Student_Loans)	SELECT s.bio_data, s.student_details FROM students s WHERE s.student_id IN (SELECT sl.student_id FROM student_loans sl WHERE sl.amount_of_loan > (SELECT AVG(amount_of_loan) FROM student_loans))	join -> in-sub	0	0
492	Find the biographical data and details for students whose student loan is above the average amount.	SELECT T1.bio_data , T1.student_details FROM Students AS T1 JOIN Student_Loans AS T2 ON T1.student_id = T2.student_id WHERE T2.amount_of_loan > (SELECT avg(amount_of_loan) FROM Student_Loans)	SELECT s.bio_data, s.student_details FROM students s WHERE s.student_id IN (SELECT sl.student_id FROM student_loans sl WHERE sl.amount_of_loan > (SELECT AVG(amount_of_loan) FROM student_loans))	join -> in-sub	0	1
495	Which student has the loan with the minimum value? List the student's biographical information.	SELECT T1.bio_data FROM Students AS T1 JOIN Student_Loans AS T2 ON T1.student_id = T2.student_id ORDER BY T2.amount_of_loan ASC LIMIT 1	SELECT T1.bio_data FROM Students AS T1 WHERE T1.student_id IN (SELECT T2.student_id FROM Student_Loans AS T2 WHERE T2.amount_of_loan = (SELECT min(amount_of_loan) FROM Student_Loans))	limit 1; join -> in-sub	1	0
496	Find the biographical information of the student with the smallest student loan.	SELECT T1.bio_data FROM Students AS T1 JOIN Student_Loans AS T2 ON T1.student_id = T2.student_id ORDER BY T2.amount_of_loan ASC LIMIT 1	SELECT T1.bio_data FROM Students AS T1 WHERE T1.student_id IN (SELECT T2.student_id FROM Student_Loans AS T2 WHERE T2.amount_of_loan = (SELECT min(amount_of_loan) FROM Student_Loans))	limit 1; join -> in-sub	1	0
497	When was the transcript issued for the student with loan of maximum value?	SELECT T1.date_of_transcript FROM Transcripts AS T1 JOIN Student_Loans AS T2 ON T1.student_id = T2.student_id ORDER BY T2.amount_of_loan DESC LIMIT 1	SELECT date_of_transcript FROM transcripts WHERE student_id IN (SELECT student_id FROM student_loans WHERE amount_of_loan = (SELECT MAX(amount_of_loan) FROM student_loans));	limit 1	1	0
498	What is the transcript issuance date for the student with the largest amount of loan?	SELECT T1.date_of_transcript FROM Transcripts AS T1 JOIN Student_Loans AS T2 ON T1.student_id = T2.student_id ORDER BY T2.amount_of_loan DESC LIMIT 1	SELECT date_of_transcript FROM transcripts WHERE student_id IN (SELECT student_id FROM student_loans WHERE amount_of_loan = (SELECT MAX(amount_of_loan) FROM student_loans));	limit 1	1	0
499	Which teachers have taught the student with the earliest transcript issuance? List the teacher details.	SELECT T1.teacher_details FROM Teachers AS T1 JOIN Classes AS T2 ON T1.teacher_id = T2.teacher_id JOIN Transcripts AS T3 ON T2.student_id = T3.student_id ORDER BY T3.date_of_transcript ASC LIMIT 1	SELECT T.teacher_details FROM teachers T WHERE EXISTS (SELECT 1 FROM classes C WHERE C.teacher_id = T.teacher_id AND C.student_id IN (SELECT student_id FROM transcripts WHERE date_of_transcript = (SELECT MIN(date_of_transcript) FROM transcripts)))	limit 1; join -> in-sub	1	0
500	Find the details of the teachers who have taught the student with the earliest transcript issuance.	SELECT T1.teacher_details FROM Teachers AS T1 JOIN Classes AS T2 ON T1.teacher_id = T2.teacher_id JOIN Transcripts AS T3 ON T2.student_id = T3.student_id ORDER BY T3.date_of_transcript ASC LIMIT 1	SELECT T.teacher_details FROM teachers T WHERE EXISTS (SELECT 1 FROM classes C WHERE C.teacher_id = T.teacher_id AND C.student_id IN (SELECT student_id FROM transcripts WHERE date_of_transcript = (SELECT MIN(date_of_transcript) FROM transcripts)))	limit 1; join -> in-sub	0	1
501	How much total loan does each student have ? List the student ids and the amounts .	select student_id , sum(amount_of_loan) from student_loans group by student_id	SELECT students.student_id, (SELECT SUM(sl.amount_of_loan) FROM student_loans sl WHERE sl.student_id = students.student_id) FROM students GROUP BY students.student_id	join -> left join	1	0
502	For each student, find the student id and the total amount of loan he or she has.	SELECT student_id , sum(amount_of_loan) FROM Student_Loans GROUP BY student_id	SELECT students.student_id, (SELECT SUM(sl.amount_of_loan) FROM student_loans sl WHERE sl.student_id = students.student_id) FROM students GROUP BY students.student_id	join -> left join	0	1

503	How many courses does each student take? List the student id, the student biographical data and the course count.	SELECT T1.student_id, T1.bio_data, count(*) FROM Students AS T1 JOIN Classes AS T2 ON T1.student_id = T2.student_id GROUP BY T1.student_id	SELECT student_id, bio_data, (SELECT COUNT(*) FROM classes WHERE student_id = students.student_id) AS course_count FROM students	join -> left join	0	1
504	For each student, find the student id, student biographical data, and the number of courses he or she takes.	SELECT T1.student_id, T1.bio_data, count(*) FROM Students AS T1 JOIN Classes AS T2 ON T1.student_id = T2.student_id GROUP BY T1.student_id	SELECT s.student_id, s.bio_data, (SELECT COUNT(*) FROM classes WHERE classes.student_id = s.student_id) AS num_courses FROM students s	join -> left join	0	1
507	What is the code and description of the most common student address type?	SELECT T1.address_type_code, T2.address_type_description FROM Students_Addresses AS T1 JOIN Ref_Address_Types AS T2 WHERE T1.address_type_code = T2.address_type_code GROUP BY T1.address_type_code ORDER BY count(*) DESC LIMIT 1	SELECT r.address_type_code, r.address_type_description FROM ref_address_types r WHERE address_type_code IN (SELECT address_type_code FROM students_addresses GROUP BY address_type_code HAVING COUNT(*) = (SELECT MAX(counts) FROM (SELECT COUNT(*) as counts FROM students_addresses GROUP BY address_type_code)))	limit 1	0	0
508	What is the most common student address type? Give me the code and description of the address type.	SELECT T1.address_type_code, T2.address_type_description FROM Students_Addresses AS T1 JOIN Ref_Address_Types AS T2 WHERE T1.address_type_code = T2.address_type_code GROUP BY T1.address_type_code ORDER BY count(*) DESC LIMIT 1	SELECT r.address_type_code, r.address_type_description FROM ref_address_types r WHERE address_type_code IN (SELECT address_type_code FROM students_addresses GROUP BY address_type_code HAVING COUNT(*) = (SELECT MAX(counts) FROM (SELECT COUNT(*) as counts FROM students_addresses GROUP BY address_type_code)))	limit 1; join -> in sub	0	1
509	For those students who have gone through an event, who do not have a student loan? List the students' biographical data	SELECT T1.bio_data FROM Students AS T1 JOIN Student_Events AS T2 WHERE T1.student_id = T2.student_id EXCEPT SELECT T1.bio_data FROM Students AS T1 JOIN Student_Loans AS T2 WHERE T1.student_id = T2.student_id	SELECT s.bio_data FROM students s WHERE s.student_id IN (SELECT student_id FROM student_events) AND s.student_id NOT IN (SELECT student_id FROM student_loans)	except non-key	0	1
510	Among the students who have an event record, who do not have a student loan? Return the students' biographical data.	SELECT T1.bio_data FROM Students AS T1 JOIN Student_Events AS T2 WHERE T1.student_id = T2.student_id EXCEPT SELECT T1.bio_data FROM Students AS T1 JOIN Student_Loans AS T2 WHERE T1.student_id = T2.student_id	SELECT s.bio_data FROM students s WHERE s.student_id IN (SELECT student_id FROM student_events) AND s.student_id NOT IN (SELECT student_id FROM student_loans)	except non-key	0	1
533	Show all author names and the numbers of books each has written.	SELECT T1.name, count(*) FROM Author AS T1 JOIN Author_Book AS T2 ON T1.idAuthor = T2.Author GROUP BY T1.idAuthor	SELECT author.name, COUNT(author_book.author) FROM author LEFT JOIN author_book ON author.idauthor = author_book.author GROUP BY author.idauthor	join -> left join	0	0
534	What are the names of all the authors, and how many books has each written?	SELECT T1.name, count(*) FROM Author AS T1 JOIN Author_Book AS T2 ON T1.idAuthor = T2.Author GROUP BY T1.idAuthor	SELECT author.name, COUNT(author_book.author) FROM author LEFT JOIN author_book ON author.idauthor = author_book.author GROUP BY author.idauthor	join -> left join	0	1
535	Show all book isbns and the numbers of orders for each.	SELECT isbn, count(*) FROM Books_Order GROUP BY isbn	SELECT book.isbn, COUNT(books_order.isbn) AS order_count FROM book LEFT JOIN books_order ON book.isbn = books_order.isbn GROUP BY book.isbn;	join -> left join	1	0
536	What are all isbns for each book, and how many times has each been ordered?	SELECT isbn, count(*) FROM Books_Order GROUP BY isbn	SELECT book.isbn, COUNT(books_order.isbn) AS order_count FROM book LEFT JOIN books_order ON book.isbn = books_order.isbn GROUP BY book.isbn	join -> left join	0	1

537	Show all book isbns and the total amount ordered for each.	SELECT isbn , sum(amount) FROM Books_Order GROUP BY isbn	SELECT T1.isbn, sum(T2.amount) FROM Book AS T1 LEFT JOIN Books_Order AS T2 ON T1.ISBN = T2.ISBN GROUP BY T1.isbn	join -> left join	1	0
538	What are the isbns for all books, and what is the total amount ordered for each?	SELECT isbn , sum(amount) FROM Books_Order GROUP BY isbn	SELECT book.isbn, IFNULL(TOTAL(books_order.amount), 0) AS totalOrders FROM book LEFT JOIN books_order ON books_order.isbn = book.isbn GROUP BY book.isbn	join -> left join	0	0
539	Show the book title corresponding to the book with the most number of orders.	SELECT T2.title FROM Books_Order AS T1 JOIN Book AS T2 ON T1.isbn = T2.isbn GROUP BY T1.isbn ORDER BY count(*) DESC LIMIT 1	SELECT b1.title FROM book b1 WHERE b1.isbn = (SELECT bo1.isbn FROM books_order bo1 GROUP BY bo1.isbn HAVING COUNT(bo1.isbn) = (SELECT MAX(cnt) FROM (SELECT COUNT(isbn) AS cnt FROM books_order GROUP BY isbn)));	limit 1	0	0
540	What is the title of the book that has been ordered the greatest number of times?	SELECT T2.title FROM Books_Order AS T1 JOIN Book AS T2 ON T1.isbn = T2.isbn GROUP BY T1.isbn ORDER BY count(*) DESC LIMIT 1	SELECT title FROM (SELECT T2.title, rank() over (ORDER BY count(*) DESC) FROM Books_Order AS T1 JOIN Book AS T2 ON T1.isbn = T2.isbn GROUP BY T1.isbn)	limit 1	0	0
541	Show the book title and purchase price of the book that has had the greatest amount in orders.	SELECT T2.title , T2.PurchasePrice FROM Books_Order AS T1 JOIN BOOK AS T2 ON T1.isbn = T2.isbn GROUP BY T1.isbn ORDER BY sum(amount) DESC LIMIT 1	SELECT t.title, t.purchaseprice FROM book t JOIN (SELECT isbn FROM books_order GROUP BY isbn HAVING SUM(amount) = (SELECT MAX(total_amount) FROM (SELECT SUM(amount) AS total_amount FROM books_order GROUP BY isbn))) t2 ON t.isbn = t2.isbn	limit 1	0	0
542	What is the title and purchase price of the book that has the highest total order amount?	SELECT T2.title , T2.PurchasePrice FROM Books_Order AS T1 JOIN BOOK AS T2 ON T1.isbn = T2.isbn GROUP BY T1.isbn ORDER BY sum(amount) DESC LIMIT 1	SELECT t.title, t.purchaseprice FROM book t JOIN (SELECT isbn FROM books_order GROUP BY isbn HAVING SUM(amount) = (SELECT MAX(total_amount) FROM (SELECT SUM(amount) AS total_amount FROM books_order GROUP BY isbn))) t2 ON t.isbn = t2.isbn	limit 1	0	1
543	Show the titles of books that have been ordered.	SELECT DISTINCT T1.title FROM book AS T1 JOIN books_order AS T2 ON T1.isbn = T2.isbn	SELECT book.title FROM book WHERE EXISTS (SELECT 1 FROM books_order WHERE books_order.isbn = book.isbn);	join -> in-sub	0	1
546	What are the names of the different clients who have made an order?	SELECT DISTINCT T1.name FROM Client AS T1 JOIN Orders AS T2 ON T1.idClient = T2.idClient	SELECT name FROM client WHERE idclient IN (SELECT idclient FROM orders)	join -> in-sub	0	1
547	Show all client names and the number of orders each has made.	SELECT T2.name , count(*) FROM Orders AS T1 JOIN Client AS T2 ON T1.idClient = T2.idClient GROUP BY T1.idClient	SELECT cl.name, (SELECT COUNT(*) FROM orders ords WHERE ords.idclient = cl.idclient) FROM client cl	join -> left join	0	1
548	What are the names of all the clients, and how many times has each of them ordered?	SELECT T2.name , count(*) FROM Orders AS T1 JOIN Client AS T2 ON T1.idClient = T2.idClient GROUP BY T1.idClient	SELECT c1.name, COALESCE(order_count.count, 0) AS order_number FROM client c1 LEFT JOIN (SELECT idclient, COUNT(idorder) AS count FROM orders GROUP BY idclient) order_count ON c1.idclient = order_count.idclient	join -> left join	0	1
549	What is the name of the client with the most number of orders?	SELECT T2.name FROM Orders AS T1 JOIN Client AS T2 ON T1.idClient = T2.idClient GROUP BY T1.idClient ORDER BY count(*) DESC LIMIT 1	SELECT c.name FROM client AS c INNER JOIN (SELECT idclient FROM orders GROUP BY idclient HAVING COUNT(idorder) = (SELECT MAX(total_orders) FROM (SELECT idclient, COUNT(*) AS total_orders FROM orders GROUP BY idclient) tmp)) AS max_orders ON c.idclient = max_orders.idclient	limit 1	0	1
550	Give the name of the client who has made the most orders.	SELECT T2.name FROM Orders AS T1 JOIN Client AS T2 ON T1.idClient = T2.idClient GROUP BY T1.idClient ORDER BY count(*) DESC LIMIT 1	SELECT name FROM client WHERE idclient IN (SELECT idclient FROM orders GROUP BY idclient HAVING COUNT(idorder) = (SELECT MAX(order_count) FROM (SELECT idclient, COUNT(idorder) AS order_count FROM orders GROUP BY idclient) temp))	limit 1	0	1

551	Show the client names and their total amounts of books ordered.	SELECT T2.name , sum(T3.amount) FROM Orders AS T1 JOIN Client AS T2 ON T1.idClient = T2.idClient JOIN Books_Order AS T3 ON T3.idOrder = T1.idOrder GROUP BY T1.idClient	SELECT T1.name, sum(T3.amount) FROM Client AS T1 LEFT JOIN Orders AS T2 ON T1.idClient = T2.idClient LEFT JOIN Books_Order AS T3 ON T2.idOrder = T3.idOrder GROUP BY T1.idClient;	join -> left join	1	0
552	What are the names of all the clients, and the total amount of books ordered by each?	SELECT T2.name , sum(T3.amount) FROM Orders AS T1 JOIN Client AS T2 ON T1.idClient = T2.idClient JOIN Books_Order AS T3 ON T3.idOrder = T1.idOrder GROUP BY T1.idClient	SELECT T1.name, sum(T3.amount) FROM Client AS T1 LEFT JOIN Orders AS T2 ON T1.idClient = T2.idClient LEFT JOIN Books_Order AS T3 ON T2.idOrder = T3.idOrder GROUP BY T1.idClient;	join -> left join	1	0
553	Show the client name who has the most total amount of books ordered.	SELECT T2.name FROM Orders AS T1 JOIN Client AS T2 ON T1.idClient = T2.idClient JOIN Books_Order AS T3 ON T3.idOrder = T1.idOrder GROUP BY T1.idClient ORDER BY sum(T3.amount) DESC LIMIT 1	SELECT c.name FROM client c, orders o, books_order bo WHERE c.idclient = o.idclient AND o.idorder = bo.idorder GROUP BY c.idclient HAVING SUM(bo.amount) = (SELECT MAX(Total) FROM (SELECT SUM(amount) AS Total FROM orders JOIN books_order ON orders.idorder = books_order.idorder GROUP BY idclient) totals)	limit 1	0	1
554	What is the name of the client who has ordered the greatest total amount of books?	SELECT T2.name FROM Orders AS T1 JOIN Client AS T2 ON T1.idClient = T2.idClient JOIN Books_Order AS T3 ON T3.idOrder = T1.idOrder GROUP BY T1.idClient ORDER BY sum(T3.amount) DESC LIMIT 1	SELECT c.name FROM client c, orders o, books_order bo WHERE c.idclient = o.idclient AND o.idorder = bo.idorder GROUP BY c.idclient HAVING SUM(bo.amount) = (SELECT MAX(Total) FROM (SELECT SUM(amount) AS Total FROM orders JOIN books_order ON orders.idorder = books_order.idorder GROUP BY idclient) totals)	limit 1	1	0
555	Show all book titles for books that have no orders.	SELECT title FROM book EXCEPT SELECT T1.title FROM book AS T1 JOIN books_order AS T2 ON T1.isbn = T2.isbn	SELECT title FROM book WHERE isbn NOT IN (SELECT isbn FROM books_order)	except non-key	0	1
556	What are the titles of books that have never been ordered?	SELECT title FROM book EXCEPT SELECT T1.title FROM book AS T1 JOIN books_order AS T2 ON T1.isbn = T2.isbn	SELECT title FROM book WHERE isbn NOT IN (SELECT isbn FROM books_order)	except non-key	0	1
557	Show all client names for clients who have not made orders.	SELECT name FROM Client EXCEPT SELECT T1.name FROM Client AS T1 JOIN Orders AS T2 ON T1.idClient = T2.idClient	SELECT name FROM client WHERE idclient NOT IN (SELECT idclient FROM orders)	except non-key	0	1
558	What are the names of clients who have never made an order?	SELECT name FROM Client EXCEPT SELECT T1.name FROM Client AS T1 JOIN Orders AS T2 ON T1.idClient = T2.idClient	SELECT name FROM client WHERE idclient NOT IN (SELECT idclient FROM orders)	except non-key	0	1
571	What is the average sale price of books written by George Orwell?	SELECT avg(saleprice) FROM Book AS T1 JOIN Author_book AS T2 ON T1.isbn = T2.isbn JOIN Author AS T3 ON T2.Author = T3.idAuthor WHERE T3.name = "George Orwell"	SELECT AVG(saleprice) FROM book WHERE isbn IN (SELECT isbn FROM author_book WHERE author IN (SELECT idauthor FROM author WHERE name = 'George Orwell'))	join -> in-sub	0	1
572	Give the average sale price of books authored by George Orwell.	SELECT avg(saleprice) FROM Book AS T1 JOIN Author_book AS T2 ON T1.isbn = T2.isbn JOIN Author AS T3 ON T2.Author = T3.idAuthor WHERE T3.name = "George Orwell"	SELECT AVG(saleprice) FROM book WHERE isbn IN (SELECT isbn FROM author_book JOIN author ON author_book.author = author.idauthor WHERE author.name = 'George Orwell')	join -> in-sub	0	1
573	What are sale prices of books written by Plato?	SELECT saleprice FROM Book AS T1 JOIN Author_book AS T2 ON T1.isbn = T2.isbn JOIN Author AS T3 ON T2.Author = T3.idAuthor WHERE T3.name = "Plato"	SELECT saleprice FROM book WHERE isbn IN (SELECT isbn FROM author_book WHERE author IN (SELECT idauthor FROM author WHERE name = 'Plato'))	join -> in-sub	0	1
574	Return the sale prices of books authored by Plato.	SELECT saleprice FROM Book AS T1 JOIN Author_book AS T2 ON T1.isbn = T2.isbn JOIN Author AS T3 ON T2.Author = T3.idAuthor WHERE T3.name = "Plato"	SELECT b.saleprice FROM book AS b WHERE EXISTS (SELECT 1 FROM author_book AS ab JOIN author AS a ON ab.author = a.idauthor WHERE ab.isbn = b.isbn AND a.name = 'Plato')	join -> in-sub	0	1
575	What is the title of the book written by George Orwell that has the lowest sale price?	SELECT T1.title FROM Book AS T1 JOIN Author_book AS T2 ON T1.isbn = T2.isbn JOIN Author AS T3 ON T2.Author = T3.idAuthor WHERE T3.name = "George Orwell" ORDER BY T1.saleprice LIMIT 1	WITH LowestPrice AS (SELECT book.isbn FROM book JOIN author_book ON book.isbn = author_book.isbn JOIN author ON author_book.author = author.idauthor WHERE author.name = 'George Orwell' and book.SalePrice = (SELECT MIN(saleprice) FROM book JOIN author_book ON book.isbn = author_book.isbn JOIN author ON author_book.author = author.idauthor WHERE author.name = 'George Orwell')) SELECT title FROM book WHERE isbn IN (SELECT isbn FROM LowestPrice);	limit 1	0	0

576	Give the title of book by George Orwell that has the lowest saleprice.	SELECT T1.title FROM Book AS T1 JOIN Author_book AS T2 ON T1.isbn = T2.isbn JOIN Author AS T3 ON T2.Author = T3.idAuthor WHERE T3.name = "George Orwell" ORDER BY T1.saleprice LIMIT 1	WITH LowestPrice AS (SELECT book.isbn FROM book JOIN author_book ON book.isbn = author_book.isbn JOIN author ON author_book.author = author.idauthor WHERE author.name = 'George Orwell' and book.SalePrice = (SELECT MIN(saleprice) FROM book JOIN author_book ON book.isbn = author_book.isbn JOIN author ON author_book.author = author.idauthor WHERE author.name = 'George Orwell')) SELECT title FROM book WHERE isbn IN (SELECT isbn FROM LowestPrice);	limit 1	0	0
577	What is the title of the book written by Plato that has price lower than the average sale price of all books?	SELECT T1.title FROM Book AS T1 JOIN Author_book AS T2 ON T1.isbn = T2.isbn JOIN Author AS T3 ON T2.Author = T3.idAuthor WHERE T3.name = "Plato" AND T1.saleprice < (SELECT avg(saleprice) FROM Book)	SELECT title FROM book WHERE isbn IN (SELECT isbn FROM author_book WHERE author IN (SELECT idauthor FROM author WHERE name = 'Plato')) AND saleprice < (SELECT AVG(saleprice) FROM book);	join -> in-sub	0	0
578	Give the titles of books authored by Plato that have a sale price lower than the average sale price across all books.	SELECT T1.title FROM Book AS T1 JOIN Author_book AS T2 ON T1.isbn = T2.isbn JOIN Author AS T3 ON T2.Author = T3.idAuthor WHERE T3.name = "Plato" AND T1.saleprice < (SELECT avg(saleprice) FROM Book)	SELECT title FROM book WHERE isbn IN (SELECT isbn FROM author_book WHERE author IN (SELECT idauthor FROM author WHERE name = 'Plato')) AND saleprice < (SELECT AVG(saleprice) FROM book)	join -> in-sub	0	1
579	Who is the author of the book "Pride and Prejudice"?	SELECT T3.name FROM Book AS T1 JOIN Author_book AS T2 ON T1.isbn = T2.isbn JOIN Author AS T3 ON T2.Author = T3.idAuthor WHERE T1.title = "Pride and Prejudice"	SELECT name FROM author WHERE idauthor IN (SELECT author FROM author_book WHERE isbn IN (SELECT isbn FROM book WHERE title = 'Pride and Prejudice'))	join -> in-sub	0	1
580	Give the name of the author who wrote the book titled Pride and Prejudice.	SELECT T3.name FROM Book AS T1 JOIN Author_book AS T2 ON T1.isbn = T2.isbn JOIN Author AS T3 ON T2.Author = T3.idAuthor WHERE T1.title = "Pride and Prejudice"	SELECT name FROM author WHERE idauthor IN (SELECT author FROM author_book WHERE isbn IN (SELECT isbn FROM book WHERE title = 'Pride and Prejudice'))	join -> in-sub	1	0
581	List titles of all books published by an author whose name contains the string 'Plato'?	SELECT T1.title FROM Book AS T1 JOIN Author_book AS T2 ON T1.isbn = T2.isbn JOIN Author AS T3 ON T2.Author = T3.idAuthor WHERE T3.name LIKE "%Plato%"	SELECT title FROM book WHERE isbn IN (SELECT isbn FROM author_book WHERE author IN (SELECT idauthor FROM author WHERE name LIKE '%Plato%'))	join -> in-sub	1	0
582	What are the titles of all books written by an author with a name that contains Plato?	SELECT T1.title FROM Book AS T1 JOIN Author_book AS T2 ON T1.isbn = T2.isbn JOIN Author AS T3 ON T2.Author = T3.idAuthor WHERE T3.name LIKE "%Plato%"	SELECT title FROM book WHERE isbn IN (SELECT isbn FROM author_book WHERE author IN (SELECT idauthor FROM author WHERE name LIKE '%Plato%'))	join -> in-sub	0	1
583	How many orders do we have for "Pride and Prejudice"?	SELECT count(*) FROM Book AS T1 JOIN Books_Order AS T2 ON T1.isbn = T2.isbn WHERE T1.title = "Pride and Prejudice"	SELECT COUNT(DISTINCT orders.idorder) FROM book JOIN books_order ON book.isbn = books_order.isbn JOIN orders ON books_order.idorder = orders.idorder WHERE book.title = 'Pride and Prejudice'	semantic error: one order for two books with the same name	0	1
584	Return the number of orders received for Pride and Prejudice.	SELECT count(*) FROM Book AS T1 JOIN Books_Order AS T2 ON T1.isbn = T2.isbn WHERE T1.title = "Pride and Prejudice"	SELECT COUNT(*) FROM orders WHERE idorder IN (SELECT idorder FROM books_order WHERE isbn IN (SELECT isbn FROM book WHERE title = 'Pride and Prejudice'))	semantic error: one order for two books with the same name	0	1
589	Find the title of books which are ordered by client Peter Doe but not client James Smith.	SELECT T4.title FROM Orders AS T1 JOIN Books_Order AS T2 ON T1.idOrder = T2.idOrder JOIN Client AS T3 ON T1.idClient = T3.idClient JOIN book AS T4 ON T2.ISBN = T4.isbn WHERE T3.name = "Peter Doe" EXCEPT SELECT T4.title FROM Orders AS T1 JOIN Books_Order AS T2 ON T1.idOrder = T2.idOrder JOIN Client AS T3 ON T1.idClient = T3.idClient JOIN book AS T4 ON T2.ISBN = T4.isbn WHERE T3.name = "James Smith"	SELECT title FROM Book WHERE ISBN IN (SELECT T2.ISBN FROM Orders AS T1 JOIN Books_Order AS T2 ON T1.IdOrder = T2.IdOrder JOIN Client AS T3 ON T1.IdClient = T3.IdClient WHERE T3.name = "Peter Doe" EXCEPT SELECT T2.ISBN FROM Orders AS T1 JOIN Books_Order AS T2 ON T1.IdOrder = T2.IdOrder JOIN Client AS T3 ON T1.IdClient = T3.IdClient WHERE T3.name = "James Smith")	except non-key	1	0

590	What are the titles of books that the client Peter Doe ordered, but the client James Smith did not?	SELECT T4.title FROM Orders AS T1 JOIN Books_Order AS T2 ON T1.idOrder = T2.idOrder JOIN Client AS T3 ON T1.idClient = T3.idClient JOIN book AS T4 ON T2.ISBN = T4.isbn WHERE T3.name = "Peter Doe" EXCEPT SELECT T4.title FROM Orders AS T1 JOIN Books_Order AS T2 ON T1.idOrder = T2.idOrder JOIN Client AS T3 ON T1.idClient = T3.idClient JOIN book AS T4 ON T2.ISBN = T4.isbn WHERE T3.name = "James Smith"	SELECT title FROM Book WHERE ISBN IN (SELECT T2.ISBN FROM Orders AS T1 JOIN Books_Order AS T2 ON T1.IdOrder = T2.IdOrder JOIN Client AS T3 ON T1.IdClient = T3.IdClient WHERE T3.name = "Peter Doe" EXCEPT SELECT T2.ISBN FROM Orders AS T1 JOIN Books_Order AS T2 ON T1.IdOrder = T2.IdOrder JOIN Client AS T3 ON T1.IdClient = T3.IdClient WHERE T3.name = "James Smith")	except non-key	1	0
591	Show all client names who have orders for "Pride and Prejudice".	SELECT T3.name FROM Orders AS T1 JOIN Books_Order AS T2 ON T1.idOrder = T2.idOrder JOIN Client AS T3 ON T1.idClient = T3.idClient JOIN Book AS T4 ON T4.isbn = T2.isbn WHERE T4.title = "Pride and Prejudice"	SELECT name FROM client WHERE idclient IN (SELECT idclient FROM orders WHERE idorder IN (SELECT idorder FROM book WHERE title = 'Pride and Prejudice'))	join -> in-sub	0	0
592	What are the names of clients who have ordered Pride and Prejudice?	SELECT T3.name FROM Orders AS T1 JOIN Books_Order AS T2 ON T1.idOrder = T2.idOrder JOIN Client AS T3 ON T1.idClient = T3.idClient JOIN Book AS T4 ON T4.isbn = T2.isbn WHERE T4.title = "Pride and Prejudice"	SELECT name FROM client WHERE idclient IN (SELECT idclient FROM orders WHERE idorder IN (SELECT idorder FROM book WHERE title = 'Pride and Prejudice'))	join -> in sub	0	1
601	What is the rating of the book with the largest number of chapters?	SELECT T2.Rating FROM book AS T1 JOIN review AS T2 ON T1.Book_ID = T2.Book_ID ORDER BY T1.Chapters DESC LIMIT 1	SELECT r.rating FROM review r JOIN book b ON r.book_id = b.book_id WHERE b.chapters = (SELECT MAX(chapters) FROM book);	limit 1	0	0
602	What is the rank of the book with the smallest number of pages?	SELECT T2.Rank FROM book AS T1 JOIN review AS T2 ON T1.Book_ID = T2.Book_ID ORDER BY T1.Pages ASC LIMIT 1	SELECT r.rank FROM review r JOIN book b ON r.book_id = b.book_id WHERE b.pages = (SELECT MIN(pages) FROM book);	limit 1	1	0
603	What is the title of the book with the highest rank in the review?	SELECT T1.Title FROM book AS T1 JOIN review AS T2 ON T1.Book_ID = T2.Book_ID ORDER BY T2.Rank LIMIT 1	SELECT Title FROM (SELECT Title, rank() over (ORDER BY (SELECT max(rank) FROM review WHERE review.Book_ID = book.Book_ID)) as rk FROM book) WHERE rk = 1	semantic error; limit 1	0	0
606	What is the most common type of books?	SELECT TYPE FROM book GROUP BY TYPE ORDER BY COUNT(*) DESC LIMIT 1	SELECT type FROM book GROUP BY type HAVING COUNT(type) = (SELECT MAX(count) FROM (SELECT type, COUNT(*) AS count FROM book GROUP BY type))	limit 1	0	1
609	List the title and audio length for all the books in descending order of the number of readers.	SELECT T1.Title, T1.audio FROM book AS T1 JOIN review AS T2 ON T1.Book_ID = T2.Book_ID ORDER BY T2.Readers_in_Million DESC	SELECT T1.Title, T1.audio FROM book AS T1 LEFT JOIN review AS T2 ON T1.Book_ID = T2.Book_ID GROUP BY T1.Book_ID ORDER BY sum(T2.Readers_in_Million) DESC	semantic error; join -> left join	0	0
613	What are the type and title of the books that are not rated?	SELECT TYPE, title FROM book EXCEPT SELECT T1.type, T1.title FROM book AS T1 JOIN review AS T2 ON T1.Book_ID = T2.Book_ID;	SELECT DISTINCT book.type, book.title FROM book LEFT JOIN review ON book.book_id = review.book_id WHERE review.rating IS NULL	semantic error: rating	0	1
624	What is the card credit of the customer with the highest membership level?	SELECT Card_Credit FROM customer ORDER BY Level_of_Membership DESC LIMIT 1	SELECT card_credit FROM (SELECT card_credit, RANK() OVER (ORDER BY level_of_membership DESC) as rk FROM customer) WHERE rk = 1;	limit 1	1	0
625	Find the customer with the highest membership level and return his or her card credit.	SELECT Card_Credit FROM customer ORDER BY Level_of_Membership DESC LIMIT 1	SELECT card_credit FROM (SELECT card_credit, RANK() OVER (ORDER BY level_of_membership DESC) as rk FROM customer) WHERE rk = 1;	limit 1	0	1
628	Show the most common nationality of customers.	SELECT Nationality FROM customer GROUP BY Nationality ORDER BY COUNT(*) DESC LIMIT 1	SELECT nationality FROM customer GROUP BY nationality HAVING COUNT(nationality) = (SELECT MAX(cnt) FROM (SELECT nationality, COUNT(*) as cnt FROM customer GROUP BY nationality) subquery)	limit 1	0	1
629	Which nationality does the most customers have?	SELECT Nationality FROM customer GROUP BY Nationality ORDER BY COUNT(*) DESC LIMIT 1	WITH RankedNationalities AS (SELECT nationality, RANK() OVER (ORDER BY COUNT(customer_id) DESC) as rank FROM customer GROUP BY nationality) SELECT nationality FROM RankedNationalities WHERE rank = 1	limit 1	0	1

631	Which nations have both customers with card credit above 50 and customers with card credit below 75.	SELECT Nationality FROM customer WHERE Card_Credit < 50 INTERSECT SELECT Nationality FROM customer WHERE Card_Credit > 75	SELECT DISTINCT c1.nationality FROM customer c1 JOIN customer c2 ON c1.nationality = c2.nationality WHERE c1.card_credit > 50 AND c2.card_credit < 75	semantic error	0	1
636	Show each customer name and the total quantities of dishes ordered by that customer.	SELECT T1.Name , sum(T2.Quantity) FROM customer AS T1 JOIN customer_order AS T2 ON T1.Customer_ID = T2.Customer_ID GROUP BY T1.Name	SELECT c.name, SUM(quantity) AS total_orders FROM customer c LEFT JOIN customer_order co ON c.customer_id = co.customer_id GROUP BY c.customer_id	join -> left join; group by non-key	0	0
637	What is the total quantities of dishes ordered by each customer ? List the customer name and the total quantity .	select t1.name , sum(t2.quantity) from customer as t1 join customer_order as t2 on t1.customer_id = t2.customer_id group by t1.name	SELECT c.name, SUM(quantity) AS total_orders FROM customer c LEFT JOIN customer_order co ON c.customer_id = co.customer_id GROUP BY c.customer_id	join -> left join; group by non-key	0	0
638	Show the customers with total quantity of order bigger than 1.	SELECT T1.Name FROM customer AS T1 JOIN customer_order AS T2 ON T1.Customer_ID = T2.Customer_ID GROUP BY T1.Name HAVING sum(T2.Quantity) > 1	SELECT c.name FROM customer c JOIN customer_order co ON c.customer_id = co.customer_id GROUP BY c.customer_id HAVING SUM(co.quantity) > 1	group by non-key	1	0
639	Which customers have total order quantity greater than 1? Give me the customer names.	SELECT T1.Name FROM customer AS T1 JOIN customer_order AS T2 ON T1.Customer_ID = T2.Customer_ID GROUP BY T1.Name HAVING sum(T2.Quantity) > 1	SELECT c.name FROM customer c WHERE c.customer_id IN (SELECT co.customer_id FROM customer_order co GROUP BY co.customer_id HAVING SUM(co.quantity) > 1)	group by non-key	0	1
647	List the names of members whose nationality is not "England" .	select name from member where nationality != "england"	SELECT name FROM member WHERE nationality != 'England'	str	0	1
649	What is the name of the oldest member?	SELECT Name FROM member ORDER BY Age DESC LIMIT 1	SELECT name FROM member WHERE age = (SELECT MAX(age) FROM member)	limit 1	0	1
651	Please show the most common nationality of members.	SELECT Nationality , COUNT(*) FROM member GROUP BY Nationality ORDER BY COUNT(*) DESC LIMIT 1	SELECT M.nationality FROM member M GROUP BY M.nationality HAVING COUNT(M.nationality) = (SELECT MAX(count) FROM (SELECT COUNT(M2.nationality) as count FROM member M2 GROUP BY M2.nationality))	limit 1	0	1
654	Show the names of club leaders of clubs with overall ranking higher than 100.	SELECT T3.Name , T2.Club_Name FROM club_leader AS T1 JOIN club AS T2 ON T1.Club_ID = T2.Club_ID JOIN member AS T3 ON T1.Member_ID = T3.Member_ID WHERE T2.Overall_Ranking < 100	SELECT name FROM member WHERE member_id IN (SELECT member_id FROM club_leader WHERE club_id IN (SELECT club_id FROM club WHERE overall_ranking > 100))	join -> in-sub; semantic error	0	1
655	Show the names of club leaders that joined their club before 2018.	SELECT T3.Name , T2.Club_Name FROM club_leader AS T1 JOIN club AS T2 ON T1.Club_ID = T2.Club_ID JOIN member AS T3 ON T1.Member_ID = T3.Member_ID WHERE T1.Year_Join < 2018	SELECT name FROM member WHERE member_id IN (SELECT member_id FROM club_leader WHERE year_join < 2018)	join -> in-sub; semantic error	0	1
656	Show the name of the leader of the club named "Houston".	SELECT T3.Name FROM club_leader AS T1 JOIN club AS T2 ON T1.Club_ID = T2.Club_ID JOIN member AS T3 ON T1.Member_ID = T3.Member_ID WHERE T2.Club_Name = "Houston"	SELECT Name FROM member WHERE Member_ID IN (SELECT Member_ID FROM club_leader WHERE Club_ID IN (SELECT Club_ID FROM club WHERE Club_Name = 'Houston'))	join -> in-sub	1	0
659	What is the average age of all the club leaders?	SELECT avg(T2.age) FROM club_leader AS T1 JOIN member AS T2 ON T1.member_id = T2.member_id	SELECT AVG(age) FROM member WHERE member_id IN (SELECT member_id FROM club_leader)	join -> in-sub	0	1
671	What is the parent document of document owned by Marlin? List the document id.	SELECT Parent_Document_Object_ID FROM Document_Objects WHERE OWNER = 'Marlin'	SELECT document_object_id FROM document_objects WHERE document_object_id IN (SELECT parent_document_object_id FROM document_objects WHERE owner = 'Marlin')	semantic error	0	1

672	What are the document object ids of the objects owned by Marlin?	SELECT Parent_Document_Object_ID FROM Document_Objects WHERE OWNER = 'Marlin'	SELECT document_object_id FROM document_objects WHERE owner = 'Marlin'	semantic error	0	1
675	What is the owner of the parent document of document owned by 'Marlin'?	SELECT T2.Owner FROM Document_Objects AS T1 JOIN Document_Objects AS T2 ON T1.Parent_Document_Object_ID = T2.Document_Object_ID WHERE T1.Owner = 'Marlin'	SELECT parent.owner FROM document_objects AS parent WHERE parent.document_object_id IN (SELECT child.parent_document_object_id FROM document_objects AS child WHERE child.owner = 'Marlin')	join -> in-sub	0	1
676	Who is the owner of the parent document of every documents where 'Marlin' is the owner?	SELECT T2.Owner FROM Document_Objects AS T1 JOIN Document_Objects AS T2 ON T1.Parent_Document_Object_ID = T2.Document_Object_ID WHERE T1.Owner = 'Marlin'	SELECT parent.owner FROM document_objects AS parent WHERE parent.document_object_id IN (SELECT child.parent_document_object_id FROM document_objects AS child WHERE child.owner = 'Marlin')	join -> in-sub	1	0
689	What is the name of the parent collection of the collection named Nice?	SELECT T2.Collection_Name FROM Collections AS T1 JOIN Collections AS T2 ON T1.Parent_Collection_ID = T2.Collection_ID WHERE T1.Collection_Name = "Nice";	SELECT c1.Collection_Name FROM Collections AS c1 WHERE c1.Collection_ID IN (SELECT c2.Parent_Collection_ID FROM Collections AS c2 WHERE c2.Collection_Name = "Nice");	join -> in-sub	1	0
690	What are the names of all parent collections of the collection named Nice?	SELECT T2.Collection_Name FROM Collections AS T1 JOIN Collections AS T2 ON T1.Parent_Collection_ID = T2.Collection_ID WHERE T1.Collection_Name = "Nice";	SELECT c1.Collection_Name FROM Collections AS c1 WHERE c1.Collection_ID IN (SELECT c2.Parent_Collection_ID FROM Collections AS c2 WHERE c2.Collection_Name = "Nice");	join -> in-sub	1	0
691	Which collection is not the parent of other collection? List the collection's name.	SELECT Collection_Name FROM Collections EXCEPT SELECT T2.Collection_Name FROM Collections AS T1 JOIN Collections AS T2 ON T1.Parent_Collection_ID = T2.Collection_ID;	SELECT collection_name FROM collections WHERE collection_id NOT IN (SELECT parent_collection_id FROM collections WHERE parent_collection_id IS NOT NULL)	join -> in-sub	0	1
692	What are the names of the collections that are not the parent of the other collections?	SELECT Collection_Name FROM Collections EXCEPT SELECT T2.Collection_Name FROM Collections AS T1 JOIN Collections AS T2 ON T1.Parent_Collection_ID = T2.Collection_ID;	SELECT collection_name FROM collections WHERE collection_id NOT IN (SELECT parent_collection_id FROM collections WHERE parent_collection_id IS NOT NULL)	join -> in-sub	0	1
697	List all document which is related to document owned by Ransom . List the document id .	select t1.document_object_id from document_subset_members as t1 join document_objects as t2 on t1.document_object_id = t2.document_object_id where t2.owner = 'ransom'	SELECT DISTINCT d.document_object_id FROM document_objects d JOIN document_subset_members dsm ON d.document_object_id = dsm.Document_Object_ID JOIN document_objects do ON do.document_object_id = dsm.Related_Document_Object_ID WHERE do.owner = 'Ransom';	str; semantic error	0	0
698	What are the document object ids of the related to the document owned by Ransom ?	select t1.document_object_id from document_subset_members as t1 join document_objects as t2 on t1.document_object_id = t2.document_object_id where t2.owner = 'ransom'	SELECT DISTINCT d.document_object_id FROM document_objects d JOIN document_subset_members dsm ON d.document_object_id = dsm.Document_Object_ID JOIN document_objects do ON do.document_object_id = dsm.Related_Document_Object_ID WHERE do.owner = 'Ransom';	str; semantic error	0	0
699	List collection subset id, name and number of collections in each subset.	SELECT T2.Collection_Subset_ID , T1.Collection_Subset_Name , count(*) FROM Collection_Subsets AS T1 JOIN Collection_Subset_Members AS T2 ON T1.Collection_Subset_ID = T2.Collection_Subset_ID GROUP BY T2.Collection_Subset_ID;	SELECT cs.collection_subset_id, cs.collection_subset_name, COUNT(csm.collection_id) AS number_of_collections FROM collection_subsets cs LEFT JOIN collection_subset_members csm ON cs.collection_subset_id = csm.collection_subset_id GROUP BY cs.collection_subset_id, cs.collection_subset_name	join -> left join	0	1

700	What are the collection subset ids, names, and number of collections for each subset?	SELECT T2.Collection_Subset_ID , T1.Collection_Subset_Name , count(*) FROM Collection_Subsets AS T1 JOIN Collection_Subset_Members AS T2 ON T1.Collection_Subset_ID = T2.Collection_Subset_ID GROUP BY T2.Collection_Subset_ID;	SELECT cs.collection_subset_id, cs.collection_subset_name, COUNT(csm.collection_id) AS num_collections FROM collection_subsets cs LEFT JOIN collection_subset_members csm ON cs.collection_subset_id = csm.collection_subset_id GROUP BY cs.collection_subset_id, cs.collection_subset_name	join -> left join	0	1
701	Which document has most of child? List the document id and the number of child.	SELECT T2.Document_Object_ID , count(*) FROM Document_Objects AS T1 JOIN Document_Objects AS T2 ON T1.Parent_Document_Object_ID = T2.Document_Object_ID GROUP BY T2.Document_Object_ID ORDER BY count(*) DESC LIMIT 1;	SELECT Document_Object_ID, cnt FROM (SELECT T2.Document_Object_ID, COUNT(*) as cnt, RANK() OVER (ORDER BY COUNT(*) DESC) as rk FROM Document_Objects AS T1 JOIN Document_Objects AS T2 ON T1.Parent_Document_Object_ID = T2.Document_Object_ID GROUP BY T2.Document_Object_ID) AS subquery WHERE rk = 1	limit 1	1	0
702	For each document object id, how many children do they have?	SELECT T2.Document_Object_ID , count(*) FROM Document_Objects AS T1 JOIN Document_Objects AS T2 ON T1.Parent_Document_Object_ID = T2.Document_Object_ID GROUP BY T2.Document_Object_ID ORDER BY count(*) DESC LIMIT 1;	SELECT parent.document_object_id, COUNT(child.document_object_id) AS child_count FROM document_objects AS parent LEFT JOIN document_objects AS child ON parent.document_object_id = child.parent_document_object_id GROUP BY parent.document_object_id	semantic error	0	1
703	Which document has least number of related documents? List the document id and the number of related documents.	SELECT Document_Object_ID , count(*) FROM Document_Subset_Members GROUP BY Document_Object_ID ORDER BY count(*) ASC LIMIT 1;	SELECT d.document_object_id, COUNT(r.related_document_object_id) AS CountRelated FROM document_objects d LEFT JOIN document_subset_members r ON d.document_object_id = r.document_object_id GROUP BY d.document_object_id ORDER BY CountRelated ASC LIMIT 1	limit 1	0	1
704	What is the document object id with the least number of documents ?	select document_object_id , count(*) from document_subset_members group by document_object_id order by count(*) asc limit 1;	SELECT d.document_object_id, COUNT(r.related_document_object_id) AS CountRelated FROM document_objects d LEFT JOIN document_subset_members r ON d.document_object_id = r.document_object_id GROUP BY d.document_object_id ORDER BY CountRelated ASC LIMIT 1	limit 1; semantic error	0	0
711	List subset id, name and number of different documents in each subset.	SELECT T1.Document_Subset_ID , T2.Document_Subset_Name , count(DISTINCT T1.Document_Object_ID) FROM Document_Subset_Members AS T1 JOIN Document_Subsets AS T2 ON T1.Document_Subset_ID = T2.Document_Subset_ID GROUP BY T1.Document_Subset_ID;	SELECT doc_sub.document_subset_id, doc_sub.document_subset_name, (SELECT COUNT(DISTINCT doc_mem.document_object_id) FROM document_subset_members doc_mem WHERE doc_mem.document_subset_id = doc_sub.document_subset_id) AS doc_count FROM document_subsets doc_sub	join -> left join	0	1
712	What is the subset id, name, and number of different documents for each subset?	SELECT T1.Document_Subset_ID , T2.Document_Subset_Name , count(DISTINCT T1.Document_Object_ID) FROM Document_Subset_Members AS T1 JOIN Document_Subsets AS T2 ON T1.Document_Subset_ID = T2.Document_Subset_ID GROUP BY T1.Document_Subset_ID;	SELECT document_subsets.document_subset_id, document_subset_name, (SELECT COUNT(DISTINCT document_object_id) FROM document_subset_members WHERE document_subset_members.document_subset_id = document_subsets.document_subset_id) FROM document_subsets	join -> left join	0	1
713	Which document subset has most of number of distinct documents ? List subset id , name and number of documents .	select t1.document_subset_id , t2.document_subset_name , count(distinct t1.document_object_id) from document_subset_members as t1 join document_subsets as t2 on t1.document_subset_id = t2.document_subset_id group by t1.document_subset_id order by count(*) desc limit 1;	SELECT document_subset_id, document_subset_name, num_docs FROM (SELECT ds.document_subset_id, ds.document_subset_name, COUNT(DISTINCT dsm.document_object_id) as num_docs, rank() over (ORDER BY COUNT(DISTINCT dsm.document_object_id) DESC) as rk FROM document_subsets ds JOIN document_subset_members dsm ON ds.document_subset_id = dsm.document_subset_id GROUP BY ds.document_subset_id, ds.document_subset_name) WHERE rk = 1;	limit 1	0	0

714	For the document subset with the most number of different documents, what are the ids and names of the subset, as well as the number of documents?	select t1.document_subset_id, t2.document_subset_name, count(distinct t1.document_object_id) from document_subset_members as t1 join document_subsets as t2 on t1.document_subset_id = t2.document_subset_id group by t1.document_subset_id order by count(*) desc limit 1;	SELECT a.document_subset_id, a.document_subset_name, COUNT(DISTINCT b.document_object_id) AS document_count FROM document_subsets a INNER JOIN document_subset_members b ON a.document_subset_id = b.document_subset_id GROUP BY a.document_subset_id HAVING document_count = (SELECT MAX(c.countdoc) FROM (SELECT COUNT(DISTINCT document_object_id) AS countdoc FROM document_subset_members GROUP BY document_subset_id) c)	limit 1	0	1
719	List the Collection Name that document owned by 'Ransom' belong to.	select t1.collection_name from collections as t1 join documents_in_collections as t2 on t1.collection_id = t2.collection_id join document_objects as t3 on t2.document_object_id = t3.document_object_id where t3.owner = 'ransom'	SELECT c.collection_name FROM collections c WHERE c.collection_id IN (SELECT dc.collection_id FROM documents_in_collections dc JOIN document_objects d ON dc.document_object_id = d.document_object_id WHERE d.owner = 'Ransom')	str; join -> in-sub	0	0
720	What is the collection name of a document owned by 'Ransom'?	SELECT T1.Collection_Name FROM Collections AS T1 JOIN Documents_in_Collections AS T2 ON T1.Collection_ID = T2.Collection_ID JOIN Document_Objects AS T3 ON T2.Document_Object_ID = T3.Document_Object_ID WHERE T3.owner = 'Ransom'	SELECT c.collection_name FROM collections c WHERE c.collection_id IN (SELECT dc.collection_id FROM documents_in_collections dc JOIN document_objects d ON dc.document_object_id = d.document_object_id WHERE d.owner = 'Ransom')	join -> in-sub	1	0
721	How many collections does each document belong to? List the count and the document id.	SELECT count(*), T2.Document_Object_ID FROM Collections AS T1 JOIN Documents_in_Collections AS T2 ON T1.Collection_ID = T2.Collection_ID GROUP BY T2.Document_Object_ID	SELECT d.document_object_id, COUNT(c.collection_id) AS total_collections FROM document_objects d LEFT JOIN documents_in_collections dc ON d.document_object_id = dc.document_object_id LEFT JOIN collections c ON dc.collection_id = c.collection_id GROUP BY d.document_object_id	join -> left join	1	0
722	For each document object id, how many collections does it belong to?	SELECT count(*), T2.Document_Object_ID FROM Collections AS T1 JOIN Documents_in_Collections AS T2 ON T1.Collection_ID = T2.Collection_ID GROUP BY T2.Document_Object_ID	SELECT d.document_object_id, COUNT(c.collection_id) AS total_collections FROM document_objects d LEFT JOIN documents_in_collections dc ON d.document_object_id = dc.document_object_id LEFT JOIN collections c ON dc.collection_id = c.collection_id GROUP BY d.document_object_id	join -> left join	0	1
723	How many documents does collection named 'Best' has?	SELECT count(*) FROM Collections AS T1 JOIN Documents_in_Collections AS T2 ON T1.Collection_ID = T2.Collection_ID WHERE T1.Collection_Name = "Best";	SELECT COUNT(DISTINCT doc.document_object_id) FROM collections col INNER JOIN documents_in_collections doc_col ON col.collection_id = doc_col.collection_id INNER JOIN document_objects doc ON doc_col.document_object_id = doc.document_object_id WHERE col.collection_name = 'Best'	lack distinct	0	1
724	What is the number of documents in the collection named 'Best'?	SELECT count(*) FROM Collections AS T1 JOIN Documents_in_Collections AS T2 ON T1.Collection_ID = T2.Collection_ID WHERE T1.Collection_Name = "Best";	SELECT COUNT(DISTINCT doc.document_object_id) FROM documents_in_collections dic JOIN collections c ON dic.collection_id = c.collection_id JOIN document_objects doc ON dic.document_object_id = doc.document_object_id WHERE c.collection_name = 'Best'	lack distinct	0	1
725	List the document id of all documents in collection named Best.	SELECT T2.Document_Object_ID FROM Collections AS T1 JOIN Documents_in_Collections AS T2 ON T1.Collection_ID = T2.Collection_ID WHERE T1.Collection_Name = "Best";	SELECT DISTINCT document_objects.document_object_id FROM document_objects, documents_in_collections, collections WHERE document_objects.document_object_id = documents_in_collections.document_object_id AND documents_in_collections.collection_id = collections.collection_id AND collections.collection_name = 'Best'	lack distinct	0	1

726	What is the number of document object ids in the collection named Best?	SELECT T2.Document_Object_ID FROM Collections AS T1 JOIN Documents_in_Collections AS T2 ON T1.Collection_ID = T2.Collection_ID WHERE T1.Collection_Name = "Best";	SELECT COUNT(DISTINCT doc.document_object_id) FROM documents_in_collections AS doc JOIN collections AS col ON doc.collection_id = col.collection_id WHERE col.collection_name = 'Best'	semantic error	0	1
727	Which collection have most number of documents? List collection name, id and number of documents.	SELECT T1.Collection_Name , T1.Collection_ID , count(*) FROM Collections AS T1 JOIN Documents_in_Collections AS T2 ON T1.Collection_ID = T2.Collection_ID WHERE T1.Collection_Name = "Best" GROUP BY T1.Collection_ID ORDER BY count(*) DESC LIMIT 1;	SELECT c.collection_name, c.collection_id, COUNT(d.document_object_id) AS total_docs FROM collections c JOIN documents_in_collections d ON c.collection_id = d.collection_id WHERE c.collection_name = 'Best' GROUP BY c.collection_id HAVING total_docs = (SELECT MAX(doc_counts) FROM (SELECT COUNT(document_object_id) AS doc_counts FROM documents_in_collections GROUP BY collection_id))	semantic error; limit 1	0	0
728	For ever collection named 'Best', what is the name and id of the one with the most documents, and how many documents does it have?	SELECT T1.Collection_Name , T1.Collection_ID , count(*) FROM Collections AS T1 JOIN Documents_in_Collections AS T2 ON T1.Collection_ID = T2.Collection_ID WHERE T1.Collection_Name = "Best" GROUP BY T1.Collection_ID ORDER BY count(*) DESC LIMIT 1;	SELECT c.collection_name, c.collection_id, COUNT(d.document_object_id) AS total_docs FROM collections c JOIN documents_in_collections d ON c.collection_id = d.collection_id WHERE c.collection_name = 'Best' GROUP BY c.collection_id HAVING total_docs = (SELECT MAX(doc_counts) FROM (SELECT COUNT(document_object_id) AS doc_counts FROM documents_in_collections GROUP BY collection_id))	limit 1	0	1
735	List all name of collections that are related to collection named Best.	SELECT DISTINCT T4.Collection_Name FROM Collection_Subset_Members AS T1 JOIN Collection_Subset_Members AS T2 ON T1.Related_Collection_ID = T2.Collection_ID JOIN Collections AS T3 ON T1.Collection_ID = T3.Collection_ID JOIN Collections AS T4 ON T2.Collection_ID = T4.Collection_ID WHERE T3.Collection_Name = "Best";	SELECT T1.collection_name FROM collections AS T1 WHERE T1.collection_id IN (SELECT T2.collection_id FROM collection_subset_members AS T2 JOIN collections AS T3 ON T2.Related_Collection_ID = T3.collection_id WHERE T3.collection_name = 'Best')	join -> in-sub	0	0
736	What are the names of the collections that are related to the collection named Best?	SELECT DISTINCT T4.Collection_Name FROM Collection_Subset_Members AS T1 JOIN Collection_Subset_Members AS T2 ON T1.Related_Collection_ID = T2.Collection_ID JOIN Collections AS T3 ON T1.Collection_ID = T3.Collection_ID JOIN Collections AS T4 ON T2.Collection_ID = T4.Collection_ID WHERE T3.Collection_Name = "Best";	SELECT T1.collection_name FROM collections AS T1 WHERE T1.collection_id IN (SELECT T2.collection_id FROM collection_subset_members AS T2 JOIN collections AS T3 ON T2.Related_Collection_ID = T3.collection_id WHERE T3.collection_name = 'Best')	join -> in-sub	0	0
739	Which collection subset does collection name Best in? List collection subset name.	SELECT DISTINCT T1.Collection_Subset_Name FROM Collection_Subsets AS T1 JOIN Collection_Subset_Members AS T2 ON T1.Collection_Subset_ID = T2.Collection_Subset_ID JOIN Collections AS T3 ON T2.Collection_ID = T3.Collection_ID WHERE T3.Collection_Name = "Best";	SELECT cs.collection_subset_name FROM collection_subsets AS cs WHERE cs.collection_subset_id IN (SELECT csm.collection_subset_id FROM collection_subset_members AS csm WHERE csm.collection_id IN (SELECT c.collection_id FROM collections AS c WHERE c.collection_name = 'Best'))	join -> in sub	1	0
740	What are the collection subsets that the collection named 'Best' in?	SELECT DISTINCT T1.Collection_Subset_Name FROM Collection_Subsets AS T1 JOIN Collection_Subset_Members AS T2 ON T1.Collection_Subset_ID = T2.Collection_Subset_ID JOIN Collections AS T3 ON T2.Collection_ID = T3.Collection_ID WHERE T3.Collection_Name = "Best";	SELECT cs.collection_subset_name FROM collection_subsets AS cs WHERE cs.collection_subset_id IN (SELECT csm.collection_subset_id FROM collection_subset_members AS csm WHERE csm.collection_id IN (SELECT c.collection_id FROM collections AS c WHERE c.collection_name = 'Best'))	join -> in sub	0	0
751	What are the id and name of the participants who received score 5 for their sound quality or rhythm tempo?	SELECT T1.id , T1.name FROM participants AS T1 JOIN performance_score AS T2 ON T2.participant_id = T1.id WHERE T2.voice_sound_quality = 5 OR T2.rhythm_tempo = 5	SELECT DISTINCT p.id, p.name FROM participants p, performance_score ps WHERE p.id = ps.participant_id AND (ps.voice_sound_quality = 5 OR ps.rhythm_tempo = 5)	join -> in-sub	0	1

753	What are the id and name of the song sung by the most participants?	SELECT T1.id , T1.name FROM songs AS T1 JOIN performance_score AS T2 ON T1.id = T2.songs_id GROUP BY T1.id ORDER BY count(*) DESC LIMIT 1	SELECT s.id, s.name FROM songs s INNER JOIN performance_score ps ON s.id = ps.songs_id GROUP BY s.id, s.name HAVING COUNT(DISTINCT ps.participant_id) = (SELECT MAX(participant_count) FROM (SELECT COUNT(DISTINCT ps.participant_id) AS participant_count FROM performance_score ps GROUP BY ps.songs_id) t)	limit 1	0	1
758	What are the name and popularity of participants who have sung a song both in 'Croatian' language and in 'English' language?	SELECT T1.name , T1.popularity FROM participants AS T1 JOIN performance_score AS T2 ON T2.participant_id = T1.id JOIN songs AS T3 ON T3.id = T2.songs_id WHERE T3.language = 'Croatian' INTERSECT SELECT T1.name , T1.popularity FROM participants AS T1 JOIN performance_score AS T2 ON T2.participant_id = T1.id JOIN songs AS T3 ON T3.id = T2.songs_id WHERE T3.language = 'English'	SELECT p.name, p.popularity FROM participants p WHERE EXISTS (SELECT 1 FROM songs s JOIN performance_score ps ON s.id = ps.songs_id WHERE s.language = 'Croatian' AND ps.participant_id = p.id) AND EXISTS (SELECT 1 FROM songs s JOIN performance_score ps ON s.id = ps.songs_id WHERE s.language = 'English' AND ps.participant_id = p.id)	intersect non-key	0	1
760	Find the original artists who sing songs with rhythm tempo above 5 , and list results in descending order of voice sound quality .	select t2.original_artist from performance_score as t1 join songs as t2 on t2.id = t1.songs_id where t1.rhythm_tempo > 5 order by t1.voice_sound_quality desc	select original_artist from songs AS T1 join (select songs_id, max(voice_sound_quality) as voice_sound_quality from performance_score where rhythm_tempo > 5 group by songs_id) AS T2 where T1.id = T2.songs_id ORDER BY T2.voice_sound_quality	semantic error	0	0
783	Which state has most number of cities?	SELECT state FROM City GROUP BY state ORDER BY count(*) DESC LIMIT 1	SELECT state FROM city GROUP BY state HAVING COUNT(city_name) = (SELECT MAX(Cnt) FROM (SELECT COUNT(*) as Cnt FROM city GROUP BY state))	limit 1	0	1
784	Give the state that has the most cities.	SELECT state FROM City GROUP BY state ORDER BY count(*) DESC LIMIT 1	SELECT state FROM city GROUP BY state HAVING COUNT(city_name) = (SELECT MAX(city_count) FROM (SELECT COUNT(city_name) AS city_count FROM city GROUP BY state))	limit 1	0	1
785	Which country has fewest number of cities?	SELECT country FROM City GROUP BY country ORDER BY count(*) ASC LIMIT 1	SELECT country FROM city GROUP BY country HAVING COUNT(city_code) = (SELECT MIN(total) FROM (SELECT COUNT(city_code) AS total FROM city GROUP BY country))	limit 1	0	1
786	Give the country with the fewest number of cities.	SELECT country FROM City GROUP BY country ORDER BY count(*) ASC LIMIT 1	WITH CityCount AS (SELECT country, COUNT(*) AS count FROM city GROUP BY country) SELECT country FROM CityCount WHERE count = (SELECT MIN(count) FROM CityCount)	limit 1	0	1
793	Show the number of students living in each country.	SELECT T1.country , count(*) FROM City AS T1 JOIN Student AS T2 ON T1.city_code = T2.city_code GROUP BY T1.country	SELECT T1.country , count(*) FROM City AS T1 LEFT JOIN Student AS T2 ON T1.city_code = T2.city_code GROUP BY T1.country	join -> left join	1	0
794	How many students live in each country?	SELECT T1.country , count(*) FROM City AS T1 JOIN Student AS T2 ON T1.city_code = T2.city_code GROUP BY T1.country	SELECT T1.country , count(*) FROM City AS T1 LEFT JOIN Student AS T2 ON T1.city_code = T2.city_code GROUP BY T1.country	join -> left join	1	0
795	Find the number of students living in each city.	SELECT T1.city_name , count(*) FROM City AS T1 JOIN Student AS T2 ON T1.city_code = T2.city_code GROUP BY T1.city_code	SELECT CITY.CITY_NAME, (SELECT COUNT(STUID) FROM STUDENT WHERE CITY_CODE = CITY.CITY_CODE) AS STUDENT_COUNT FROM CITY	join -> left join; nlq vague	0	0
796	How many students live in each city?	SELECT T1.city_name , count(*) FROM City AS T1 JOIN Student AS T2 ON T1.city_code = T2.city_code GROUP BY T1.city_code	SELECT CITY.CITY_NAME, (SELECT COUNT(STUID) FROM STUDENT WHERE CITY_CODE = CITY.CITY_CODE) AS STUDENT_COUNT FROM CITY	join -> left join	0	1
797	Which state has most number of students?	SELECT T1.state FROM City AS T1 JOIN Student AS T2 ON T1.city_code = T2.city_code GROUP BY T1.state ORDER BY count(*) DESC LIMIT 1	SELECT state FROM city INNER JOIN student ON city.city_code = student.city_code GROUP BY state HAVING COUNT(student.city_code) = (SELECT MAX(c) FROM (SELECT COUNT(student.city_code) AS c FROM city JOIN student ON city.city_code = student.city_code GROUP BY state))	limit 1	0	1

798	Give the state that has the most students.	SELECT T1.state FROM City AS T1 JOIN Student AS T2 ON T1.city_code = T2.city_code GROUP BY T1.state ORDER BY count(*) DESC LIMIT 1	SELECT state FROM city INNER JOIN student ON city.city_code = student.city_code GROUP BY state HAVING COUNT(student.city_code) = (SELECT MAX(c) FROM (SELECT COUNT(student.city_code) AS c FROM city JOIN student ON city.city_code = student.city_code GROUP BY state))	limit 1	0	0
799	Which country has least number of students?	SELECT T1.country FROM City AS T1 JOIN Student AS T2 ON T1.city_code = T2.city_code GROUP BY T1.country ORDER BY count(*) LIMIT 1	WITH StudentCount AS (SELECT country, COUNT(student.stuid) AS s_count FROM city LEFT JOIN student ON city.city_code = student.city_code GROUP BY country) SELECT country FROM StudentCount WHERE s_count = (SELECT min(s_count) FROM StudentCount)	limit 1; join -> left join	0	0
800	Give the country with the fewest students.	SELECT T1.country FROM City AS T1 JOIN Student AS T2 ON T1.city_code = T2.city_code GROUP BY T1.country ORDER BY count(*) LIMIT 1	WITH StudentCount AS (SELECT country, COUNT(student.stuid) AS s_count FROM city LEFT JOIN student ON city.city_code = student.city_code GROUP BY country) SELECT country FROM StudentCount WHERE s_count = (SELECT min(s_count) FROM StudentCount)	limit 1; join -> left join	0	0
817	Show me the city code of two cities with maximum distance.	SELECT city1_code , city2_code FROM Direct_distance ORDER BY distance DESC LIMIT 1	SELECT city1_code, city2_code FROM direct_distance WHERE distance = (SELECT MAX(distance) FROM direct_distance)	limit 1	0	0
818	What are the city codes of the cities with the maximum distance?	SELECT city1_code , city2_code FROM Direct_distance ORDER BY distance DESC LIMIT 1	SELECT city1_code, city2_code FROM direct_distance WHERE distance = (SELECT MAX(distance) FROM direct_distance)	limit 1	0	0
827	What is the name of the city closest to Chicago?	SELECT T3.city_name FROM Direct_distance AS T1 JOIN City AS T2 ON T1.city1_code = T2.city_code JOIN City AS T3 ON T1.city2_code = T3.city_code WHERE T2.city_name = "Chicago" ORDER BY distance LIMIT 1	SELECT city_name FROM (SELECT T3.city_name, rank() OVER (ORDER BY T1.distance) as rk FROM Direct_distance AS T1 JOIN City AS T2 ON T1.city1_code = T2.city_code JOIN City AS T3 ON T1.city2_code = T3.city_code WHERE T2.city_name = 'Chicago') AS subquery WHERE rk = 1	limit 1	0	0
828	Give the name of the nearest city to Chicago.	SELECT T3.city_name FROM Direct_distance AS T1 JOIN City AS T2 ON T1.city1_code = T2.city_code JOIN City AS T3 ON T1.city2_code = T3.city_code WHERE T2.city_name = "Chicago" ORDER BY distance LIMIT 1	SELECT city_name FROM (SELECT T3.city_name, rank() OVER (ORDER BY T1.distance) as rk FROM Direct_distance AS T1 JOIN City AS T2 ON T1.city1_code = T2.city_code JOIN City AS T3 ON T1.city2_code = T3.city_code WHERE T2.city_name = 'Chicago') AS subquery WHERE rk = 1	limit 1	1	0
829	What is the name of the city furthest to Boston?	SELECT T3.city_name FROM Direct_distance AS T1 JOIN City AS T2 ON T1.city1_code = T2.city_code JOIN City AS T3 ON T1.city2_code = T3.city_code WHERE T2.city_name = "Boston" ORDER BY distance DESC LIMIT 1	SELECT city_name FROM (SELECT T3.city_name, rank() OVER (ORDER BY T1.distance DESC) as rk FROM Direct_distance AS T1 JOIN City AS T2 ON T1.city1_code = T2.city_code JOIN City AS T3 ON T1.city2_code = T3.city_code WHERE T2.city_name = 'Boston') AS subquery WHERE rk = 1	limit 1	0	0
830	Give the city name of the city with greatest distance from Boston.	SELECT T3.city_name FROM Direct_distance AS T1 JOIN City AS T2 ON T1.city1_code = T2.city_code JOIN City AS T3 ON T1.city2_code = T3.city_code WHERE T2.city_name = "Boston" ORDER BY distance DESC LIMIT 1	SELECT city_name FROM (SELECT T3.city_name, rank() OVER (ORDER BY T1.distance DESC) as rk FROM Direct_distance AS T1 JOIN City AS T2 ON T1.city1_code = T2.city_code JOIN City AS T3 ON T1.city2_code = T3.city_code WHERE T2.city_name = 'Boston') AS subquery WHERE rk = 1	limit 1	1	0

833	Show all city names and the average distance to all other cities.	SELECT T2.city_name , avg(distance) FROM Direct_distance AS T1 JOIN City AS T2 ON T1.city1_code = T2.city_code GROUP BY T1.city1_code	SELECT city_name, (SELECT AVG(distance) FROM direct_distance WHERE city_code = city1_code) AS average_distance FROM city	join -> left join	1	0
834	What are the city name and average distances from each city?	SELECT T2.city_name , avg(distance) FROM Direct_distance AS T1 JOIN City AS T2 ON T1.city1_code = T2.city_code GROUP BY T1.city1_code	SELECT city_name, (SELECT AVG(distance) FROM direct_distance WHERE city_code = city1_code) AS average_distance FROM city	join -> left join	0	1
837	What is the first name and last name of the student living furthest to Linda Smith?	SELECT T3.Fname , T3.Lname FROM Direct_distance AS T1 JOIN Student AS T2 ON T1.city1_code = T2.city_code JOIN Student AS T3 ON T1.city2_code = T3.city_code WHERE T2.Fname = "Linda" AND T2.Lname = "Smith" ORDER BY distance DESC LIMIT 1	SELECT fn.fname, fn.lname FROM student fn, direct_distance dd, (SELECT st.city_code FROM student st WHERE st.fname = 'Linda' AND st.lname = 'Smith') linda WHERE fn.city_code = dd.city2_code AND dd.distance = (SELECT MAX(distance) FROM direct_distance WHERE city1_code = linda.city_code)	limit 1	0	1
838	What is the full name of the student who lives furthest from Linda Smith?	SELECT T3.Fname , T3.Lname FROM Direct_distance AS T1 JOIN Student AS T2 ON T1.city1_code = T2.city_code JOIN Student AS T3 ON T1.city2_code = T3.city_code WHERE T2.Fname = "Linda" AND T2.Lname = "Smith" ORDER BY distance DESC LIMIT 1	SELECT fn.fname, fn.lname FROM student fn, direct_distance dd, (SELECT st.city_code FROM student st WHERE st.fname = 'Linda' AND st.lname = 'Smith') linda WHERE fn.city_code = dd.city2_code AND dd.distance = (SELECT MAX(distance) FROM direct_distance WHERE city1_code = linda.city_code)	limit 1	0	0
839	Which state does the student whose first name is Linda live in?	SELECT state FROM Student AS T1 JOIN City AS T2 ON T1.city_code = T2.city_code WHERE T1.Fname = "Linda"	SELECT state FROM city WHERE city_code IN (SELECT city_code FROM student WHERE fname = 'Linda')	join -> in-sub	0	1
840	Give the state that the student with first name Linda lives in.	SELECT state FROM Student AS T1 JOIN City AS T2 ON T1.city_code = T2.city_code WHERE T1.Fname = "Linda"	SELECT state FROM city WHERE city_code IN (SELECT city_code FROM student WHERE fname = 'Linda')	join -> in-sub	0	1
847	Who reserved boat 102?	SELECT T1.name FROM Sailors AS T1 JOIN Reserves AS T2 ON T1.sid = T2.sid WHERE T2.bid = 102	SELECT name FROM sailors WHERE sid IN (SELECT sid FROM reserves WHERE bid = 102)	join -> in-sub	0	1
848	What is the name of the sailor who reserved boat 102?	SELECT T1.name FROM Sailors AS T1 JOIN Reserves AS T2 ON T1.sid = T2.sid WHERE T2.bid = 102	SELECT name FROM sailors WHERE sid IN (SELECT sid FROM reserves WHERE bid = 102)	join -> in-sub	0	1
853	return the unique ids of sailors who are older than any sailors.	SELECT DISTINCT sid FROM Sailors WHERE age > (SELECT min(age) FROM Sailors);	SELECT S.sid FROM sailors S WHERE S.age > (SELECT MAX(S2.age) FROM sailors S2 WHERE S2.sid != S.sid)	semantic error	0	1
855	Return the unique names of sailors who are older than any sailors whose rating is larger than 7.	SELECT DISTINCT name FROM Sailors WHERE age > (SELECT min(age) FROM Sailors WHERE rating > 7);	SELECT DISTINCT s1.name FROM Sailors s1 WHERE s1.age > (SELECT max(s2.age) FROM Sailors s2 WHERE s2.sid != s1.sid AND s2.rating > 7);	semantic error	1	0
859	Find the id and name of the sailors who reserved more than one boat.	SELECT DISTINCT T1.name , T1.sid FROM Sailors AS T1 JOIN Reserves AS T2 ON T1.sid = T2.sid GROUP BY T2.sid HAVING COUNT(*) > 1	SELECT S.sid, S.name FROM sailors S INNER JOIN reserves R ON S.sid = R.sid GROUP BY S.sid, S.name HAVING COUNT(DISTINCT R.bid) > 1	semantic error	0	1
860	What are the different names of sailors who reserved two or more boats ?	select distinct t1.name , t1.sid from sailors as t1 join reserves as t2 on t1.sid = t2.sid group by t2.sid having count(*) >= 2	SELECT DISTINCT sailors.name FROM sailors JOIN reserves ON sailors.sid = reserves.sid GROUP BY sailors.sid HAVING COUNT(DISTINCT reserves.bid) >= 2	semantic error	0	1
875	What is the name of the sailors who reserved boat with id 103?	SELECT DISTINCT T1.name FROM Sailors AS T1 JOIN Reserves AS T2 ON T1.sid = T2.sid WHERE T2.bid = 103	SELECT name FROM sailors WHERE sid IN (SELECT sid FROM reserves WHERE bid = 103)	redundant distinct	0	1
876	Find the name of the sailors who reserved boat with id 103.	SELECT DISTINCT T1.name FROM Sailors AS T1 JOIN Reserves AS T2 ON T1.sid = T2.sid WHERE T2.bid = 103	SELECT name FROM sailors WHERE sid IN (SELECT sid FROM reserves WHERE bid = 103)	redundant distinct	0	1

877	What is the name of all sailors whose rating is higher than any sailor named Luis?	SELECT name FROM Sailors WHERE rating > (SELECT min(rating) FROM Sailors WHERE name = 'Luis')	SELECT S.name FROM sailors S WHERE NOT EXISTS (SELECT 1 FROM sailors S2 WHERE S2.name = 'Luis' AND S2.rating >= S.rating)	emptyset in agg return none	0	0
878	What are the sailors' names, the ones whose rating is higher than any sailor named Luis?	SELECT name FROM Sailors WHERE rating > (SELECT min(rating) FROM Sailors WHERE name = 'Luis')	SELECT S.name FROM sailors S WHERE NOT EXISTS (SELECT 1 FROM sailors S2 WHERE S2.name = 'Luis' AND S2.rating >= S.rating)	emptyset in agg return none	0	0
879	What is the name of all sailors whose rating is higher than all sailors named Luis?	SELECT name FROM Sailors WHERE rating > (SELECT max(rating) FROM Sailors WHERE name = 'Luis')	SELECT s.name FROM sailors s WHERE NOT EXISTS (SELECT 1 FROM sailors l WHERE l.name = 'Luis' AND l.rating >= s.rating)	emptyset in agg return none	0	1
880	What are the names of all sailors with a higher rating than every sailor named Luis?	SELECT name FROM Sailors WHERE rating > (SELECT max(rating) FROM Sailors WHERE name = 'Luis')	SELECT name FROM sailors s1 WHERE NOT EXISTS (SELECT s2.sid FROM sailors s2 WHERE s2.name = 'Luis' AND s1.rating <= s2.rating)	emptyset in agg return none	0	1
893	Find the number of reservations for each boat.	SELECT bid , count(*) FROM Reserves GROUP BY bid	SELECT boats.bid, COUNT(reserves.bid) AS reservation_count FROM boats LEFT JOIN reserves ON boats.bid = reserves.bid GROUP BY boats.bid	join -> left join	0	1
894	How many reservations exist for each boat?	SELECT bid , count(*) FROM Reserves GROUP BY bid	SELECT boats.bid, COUNT(reserves.bid) AS reservation_count FROM boats LEFT JOIN reserves ON boats.bid = reserves.bid GROUP BY boats.bid	join -> left join	1	0
895	Find the number of reservations for each boat with id greater than 50.	SELECT bid , count(*) FROM Reserves GROUP BY bid HAVING bid > 50	SELECT boats.bid, COUNT(reserves.bid) AS reservation_count FROM boats LEFT JOIN reserves ON boats.bid = reserves.bid WHERE boats.bid > 50 GROUP BY boats.bid	join -> left join	1	0
896	How many reservations exist for each boat with an id greater than 50?	SELECT bid , count(*) FROM Reserves GROUP BY bid HAVING bid > 50	SELECT boats.bid, COUNT(reserves.bid) AS reservation_count FROM boats LEFT JOIN reserves ON boats.bid = reserves.bid WHERE boats.bid > 50 GROUP BY boats.bid	join -> left join	1	0
899	Find the number of reservations by sailors with id greater than 1 for each boat.	SELECT bid , count(*) FROM Reserves WHERE sid > 1 GROUP BY bid	SELECT boats.bid, COUNT(reserves.bid) AS reservation_count FROM boats LEFT JOIN reserves ON boats.bid = reserves.bid WHERE reserves.sid > 1 GROUP BY boats.bid	join -> left join	1	0
900	How many reservations for each boat did the sailors with an id greater than 1 make?	SELECT bid , count(*) FROM Reserves WHERE sid > 1 GROUP BY bid	SELECT boats.bid, COUNT(reserves.bid) AS reservation_count FROM boats LEFT JOIN reserves ON boats.bid = reserves.bid WHERE reserves.sid > 1 GROUP BY boats.bid	join -> left join	1	0
901	What is the rating and average age for sailors who have reserved red boat grouped by rating?	SELECT T1.rating , avg(T1.age) FROM Sailors AS T1 JOIN Reserves AS T2 ON T1.sid = T2.sid JOIN Boats AS T3 ON T3.bid = T2.bid WHERE T3.color = 'red' GROUP BY T1.rating	SELECT rating, AVG(age) FROM sailors WHERE sid IN (SELECT sid FROM reserves WHERE bid IN (SELECT bid FROM boats WHERE color = 'red')) GROUP BY rating	join -> in-sub	0	1
902	What are the rating and average age for sailors who reserved red boats for each rating?	SELECT T1.rating , avg(T1.age) FROM Sailors AS T1 JOIN Reserves AS T2 ON T1.sid = T2.sid JOIN Boats AS T3 ON T3.bid = T2.bid WHERE T3.color = 'red' GROUP BY T1.rating	SELECT RATING, AVG(AGE) FROM sailors WHERE sid IN (SELECT sid FROM reserves WHERE bid IN (SELECT bid FROM boats WHERE color = 'red')) GROUP BY RATING	join -> in-sub	0	1

909	Find the names of boats booked by sailors whose age is between 20 and 30.	SELECT T3.name FROM Sailors AS T1 JOIN Reserves AS T2 ON T1.sid = T2.sid JOIN Boats AS T3 ON T3.bid = T2.bid WHERE T1.age BETWEEN 20 AND 30	SELECT b.name FROM boats b WHERE b.bid IN (SELECT r.bid FROM reserves r INNER JOIN sailors s ON r.sid = s.sid WHERE s.age >= 20 AND s.age <= 30)	join -> in-sub	0	1
910	What are the names of the boats booked by people between age 20 and 30?	SELECT T3.name FROM Sailors AS T1 JOIN Reserves AS T2 ON T1.sid = T2.sid JOIN Boats AS T3 ON T3.bid = T2.bid WHERE T1.age BETWEEN 20 AND 30	SELECT b.name FROM boats b WHERE b.bid IN (SELECT r.bid FROM reserves r INNER JOIN sailors s ON r.sid = s.sid WHERE s.age >= 20 AND s.age <= 30)	join -> in-sub	0	0
911	Find the names of sailors whose rating is larger than the rating of all sailors who booked a red boat.	SELECT name FROM Sailors WHERE rating > (SELECT max(T1.rating) FROM Sailors AS T1 JOIN Reserves AS T2 ON T1.sid = T2.sid JOIN Boats AS T3 ON T3.bid = T2.bid WHERE T3.color = 'red')	SELECT S.name FROM sailors S WHERE NOT EXISTS (SELECT 1 FROM sailors S2 JOIN reserves R ON S2.sid = R.sid JOIN boats B ON B.bid = R.bid WHERE B.color = 'red' AND S2.rating >= S.rating)	emptyset in agg return none	0	1
912	What are the names of the sailors whose rating is larger than the rating of all sailors who booked a red boat?	SELECT name FROM Sailors WHERE rating > (SELECT max(T1.rating) FROM Sailors AS T1 JOIN Reserves AS T2 ON T1.sid = T2.sid JOIN Boats AS T3 ON T3.bid = T2.bid WHERE T3.color = 'red')	SELECT s.name FROM sailors s WHERE NOT EXISTS (SELECT 1 FROM sailors s2 JOIN reserves r ON s2.sid = r.sid JOIN boats b ON r.bid = b.bid WHERE b.color = 'red' AND s2.rating >= s.rating)	emptyset in agg return none	0	1
915	Find the names of sailors who reserved boat with the name Melon.	SELECT T1.name FROM Sailors AS T1 JOIN Reserves AS T2 ON T1.sid = T2.sid JOIN Boats AS T3 ON T3.bid = T2.bid WHERE T3.name = 'Melon'	SELECT name FROM sailors WHERE sid IN (SELECT sid FROM reserves WHERE bid IN (SELECT bid FROM boats WHERE name = 'Melon'))	join -> in-sub	0	1
916	What are the names of sailors who reserved a boat with the name Melon?	SELECT T1.name FROM Sailors AS T1 JOIN Reserves AS T2 ON T1.sid = T2.sid JOIN Boats AS T3 ON T3.bid = T2.bid WHERE T3.name = 'Melon'	SELECT name FROM sailors WHERE sid IN (SELECT sid FROM reserves, boats WHERE reserves.bid = boats.bid AND boats.name = 'Melon')	join -> in-sub	0	1
919	Find the model of the most expensive headphone.	SELECT model FROM headphone ORDER BY price DESC LIMIT 1	SELECT model FROM headphone WHERE price = (SELECT MAX(price) FROM headphone)	limit 1	0	1
920	Which headphone model has the highest price?	SELECT model FROM headphone ORDER BY price DESC LIMIT 1	SELECT h1.model FROM headphone AS h1 WHERE NOT EXISTS (SELECT 1 FROM headphone AS h2 WHERE h2.price > h1.price)	limit 1	0	1
923	Which headphone class is the most common one?	SELECT CLASS FROM headphone GROUP BY CLASS ORDER BY count(*) DESC LIMIT 1	SELECT h.class FROM headphone h GROUP BY h.class HAVING COUNT(h.class) = (SELECT MAX(freq) FROM (SELECT COUNT(*) freq FROM headphone GROUP BY class) sub)	limit 1	0	1
924	Which headphone class contains the most headphones?	SELECT CLASS FROM headphone GROUP BY CLASS ORDER BY count(*) DESC LIMIT 1	SELECT class FROM headphone GROUP BY class HAVING COUNT(headphone_id) = (SELECT MAX(count) FROM (SELECT class, COUNT(headphone_id) AS count FROM headphone GROUP BY class))	limit 1	0	1
926	Find the headphone class that does not contain more than two headphones.	SELECT CLASS FROM headphone GROUP BY CLASS HAVING count(*) > 2	SELECT h.class FROM headphone h GROUP BY h.class HAVING COUNT(DISTINCT h.headphone_id) <= 2	semantic error	0	1
931	Find the top 2 earpads that are mostly used.	SELECT earpads FROM headphone GROUP BY earpads ORDER BY count(*) DESC LIMIT 2	SELECT earpads FROM (SELECT earpads, RANK() OVER (ORDER BY COUNT(*) DESC) as rk FROM headphone GROUP BY earpads) AS subquery WHERE rk <= 2	limit n	0	0
932	What are the top 2 earpads in terms of the number of headphones using them?	SELECT earpads FROM headphone GROUP BY earpads ORDER BY count(*) DESC LIMIT 2	SELECT earpads FROM (SELECT earpads, RANK() OVER (ORDER BY COUNT(*) DESC) as rk FROM headphone GROUP BY earpads) AS subquery WHERE rk <= 2	limit n	1	0
933	What are the model, class, and construction of the cheapest headphone?	SELECT model, CLASS, construction FROM headphone ORDER BY price LIMIT 1	SELECT model, class, construction FROM headphone WHERE price = (SELECT MIN(price) FROM headphone)	limit 1	1	0

934	Find the model, class, and construction of the headphone with the lowest price.	SELECT model , CLASS , construction FROM headphone ORDER BY price LIMIT 1	SELECT model, class, construction FROM headphone WHERE price = (SELECT MIN(price) FROM headphone)	limit 1	0	1
951	Find the name of the store which has the most headphones in stock. List the number of headphones as well.	SELECT t1.name , sum(t2.quantity) FROM store AS t1 JOIN stock AS t2 ON t1.store_id = t2.store_id GROUP BY t2.store_id ORDER BY sum(t2.quantity) DESC LIMIT 1	SELECT name, sum FROM (SELECT t1.name, SUM(t2.quantity) as sum, RANK() OVER (ORDER BY SUM(t2.quantity) DESC) as rk FROM store AS t1 JOIN stock AS t2 ON t1.store_id = t2.store_id GROUP BY t2.store_id) AS sub-query WHERE rk = 1	limit 1	1	0
952	Which store has the headphones in stock? Give me the store name and the total quantity.	SELECT t1.name , sum(t2.quantity) FROM store AS t1 JOIN stock AS t2 ON t1.store_id = t2.store_id GROUP BY t2.store_id ORDER BY sum(t2.quantity) DESC LIMIT 1	SELECT s.name, (SELECT SUM(st.quantity) FROM stock st WHERE st.store_id = s.store_id GROUP BY st.store_id) AS Quantity FROM store s	semantic error	0	1
953	Find the name of stores which have no headphone in stock.	SELECT name FROM store WHERE store_id NOT IN (SELECT store_id FROM stock)	SELECT name FROM store WHERE store_id NOT IN (SELECT store_id FROM stock WHERE quantity > 0)	semantic error	0	1
954	Which stores do not have any headphones in stock? Give me the store names.	SELECT name FROM store WHERE store_id NOT IN (SELECT store_id FROM stock)	SELECT name FROM store WHERE store_id NOT IN (SELECT DISTINCT store_id FROM stock WHERE quantity > 0)	semantic error	0	1
955	Which headphone models do not have any stock in any store?	SELECT model FROM headphone WHERE headphone_id NOT IN (SELECT headphone_id FROM stock)	SELECT DISTINCT h.model FROM headphone h WHERE NOT EXISTS (SELECT 1 FROM stock s WHERE s.headphone_id = h.headphone_id AND quantity > 0)	semantic error; lack distinct	1	0
956	Find the headphone models that are not in stock in any store.	SELECT model FROM headphone WHERE headphone_id NOT IN (SELECT headphone_id FROM stock)	SELECT DISTINCT h.model FROM headphone h WHERE NOT EXISTS (SELECT 1 FROM stock s WHERE s.headphone_id = h.headphone_id AND quantity > 0)	semantic error; lack distinct	0	0
957	Which headphone model has the largest quantity of stock across all the stores?	SELECT t1.model FROM headphone AS t1 JOIN stock AS t2 ON t1.headphone_id = t2.headphone_id GROUP BY t1.model ORDER BY sum(t2.quantity) DESC LIMIT 1	SELECT model FROM (SELECT t1.model, rank() over (ORDER BY sum(t2.quantity) DESC) as rk FROM headphone AS t1 JOIN stock AS t2 ON t1.headphone_id = t2.headphone_id GROUP BY t1.model) WHERE rk = 1;	limit 1	0	0
958	Find the headphone model whose total quantity in stock is the largest.	SELECT t1.model FROM headphone AS t1 JOIN stock AS t2 ON t1.headphone_id = t2.headphone_id GROUP BY t1.model ORDER BY sum(t2.quantity) DESC LIMIT 1	SELECT model FROM headphone WHERE headphone_id IN (SELECT headphone_id FROM stock GROUP BY headphone_id HAVING SUM(quantity) = (SELECT MAX(total_quantity) FROM (SELECT SUM(quantity) AS total_quantity FROM stock GROUP BY headphone_id)))	limit 1	0	1
961	Which neighborhood does not have any headphone in stock?	SELECT Neighborhood FROM store EXCEPT SELECT t1.Neighborhood FROM store AS t1 JOIN stock AS t2 ON t1.store_id = t2.store_id	SELECT neighborhood FROM store EXCEPT SELECT neighborhood FROM store WHERE store_id IN (SELECT store_id FROM stock WHERE quantity > 0)	semantic error	0	1
962	Find the neighborhood where no headphones are in stock.	SELECT Neighborhood FROM store EXCEPT SELECT t1.Neighborhood FROM store AS t1 JOIN stock AS t2 ON t1.store_id = t2.store_id	SELECT s.neighborhood FROM store s LEFT JOIN stock st ON s.store_id = st.store_id GROUP BY s.neighborhood HAVING SUM(st.quantity) IS NULL OR SUM(st.quantity) = 0	semantic error	0	1
973	List names and addresses for all affiliations.	SELECT DISTINCT name , address FROM Affiliation	SELECT name, address FROM affiliation	redundant distinct	0	1
974	What are the names and addresses for all affiliations?	SELECT DISTINCT name , address FROM Affiliation	SELECT name, address FROM affiliation;	redundant distinct	0	1
975	List all venues and years for papers ordered by year.	SELECT DISTINCT venue , YEAR FROM paper ORDER BY YEAR	SELECT venue, year FROM paper ORDER BY year	redundant distinct	0	1

979	Find all papers with titles and paper IDs written by Mckeown.	SELECT T1.title , T1.paper_id FROM Paper AS T1 JOIN Author_list AS T2 ON T1.paper_id = T2.paper_id JOIN Author AS T3 ON T3.author_id = T2.author_id WHERE T3.name LIKE "%Mckeown%"	SELECT title, paper_id FROM paper WHERE paper_id IN (SELECT paper_id FROM author_list WHERE author_id IN (SELECT author_id FROM author WHERE name = '%Mckeown%'))	join -> in-sub	1	0
980	What are the titles and paper ids for papers written by Mckeown?	SELECT T1.title , T1.paper_id FROM Paper AS T1 JOIN Author_list AS T2 ON T1.paper_id = T2.paper_id JOIN Author AS T3 ON T3.author_id = T2.author_id WHERE T3.name LIKE "%Mckeown%"	SELECT title, paper_id FROM paper WHERE paper_id IN (SELECT paper_id FROM author_list WHERE author_id IN (SELECT author_id FROM author WHERE name = '%Mckeown%'))	join -> in-sub	1	0
987	Find the titles and paper IDs for papers which have Mckeown, Kathleen or Rambow, Owen in author list.	SELECT DISTINCT T1.title , T1.paper_id FROM Paper AS T1 JOIN Author_list AS T2 ON T1.paper_id = T2.paper_id JOIN Author AS T3 ON T2.author_id = T3.author_id WHERE T3.name LIKE "%Mckeown , Kathleen%" OR T3.name LIKE "%Rambow , Owen%"	SELECT DISTINCT T1.title , T1.paper_id FROM Paper AS T1 JOIN Author_list AS T2 ON T1.paper_id = T2.paper_id JOIN Author AS T3 ON T2.author_id = T3.author_id WHERE T3.name LIKE "%Mckeown, Kathleen%" OR T3.name LIKE "%Rambow, Owen%"	str	0	0
988	What are the titles and paper ids for papers that have Mckeown, Kathleen or Rambow, Owen in their author list?	SELECT DISTINCT T1.title , T1.paper_id FROM Paper AS T1 JOIN Author_list AS T2 ON T1.paper_id = T2.paper_id JOIN Author AS T3 ON T2.author_id = T3.author_id WHERE T3.name LIKE "%Mckeown , Kathleen%" OR T3.name LIKE "%Rambow , Owen%"	SELECT DISTINCT T1.title , T1.paper_id FROM Paper AS T1 JOIN Author_list AS T2 ON T1.paper_id = T2.paper_id JOIN Author AS T3 ON T2.author_id = T3.author_id WHERE T3.name LIKE "%Mckeown, Kathleen%" OR T3.name LIKE "%Rambow, Owen%"	str	0	0
989	List the names of all authors and their number of papers in descending order by number of papers.	SELECT T1.name , count(*) FROM Author AS T1 JOIN Author_list AS T2 ON T1.author_id = T2.author_id GROUP BY T1.author_id ORDER BY count(*) DESC	SELECT aut.name, (SELECT COUNT(*) FROM paper WHERE paper.paper_id IN (SELECT author_list.paper_id FROM author_list WHERE author_list.author_id = aut.author_id)) AS paper_num FROM author aut GROUP BY aut.author_id ORDER BY paper_num DESC	join -> left join	0	1
990	How many papers did each author publish, ordered by number of papers?	SELECT T1.name , count(*) FROM Author AS T1 JOIN Author_list AS T2 ON T1.author_id = T2.author_id GROUP BY T1.author_id ORDER BY count(*) DESC	SELECT aut.name, (SELECT COUNT(*) FROM paper WHERE paper.paper_id IN (SELECT author_list.paper_id FROM author_list WHERE author_list.author_id = aut.author_id)) AS paper_num FROM author aut GROUP BY aut.author_id ORDER BY paper_num DESC	join -> left join	0	0
997	What is the venue and year with the most number of publications?	SELECT venue , YEAR FROM paper GROUP BY venue , YEAR ORDER BY count(*) DESC LIMIT 1	SELECT venue, year FROM paper GROUP BY venue, year HAVING COUNT(paper_id) = (SELECT MAX(count) FROM (SELECT COUNT(paper_id) as count FROM paper GROUP BY venue, year))	limit 1	0	1
998	What was the venue and year with the most publications?	SELECT venue , YEAR FROM paper GROUP BY venue , YEAR ORDER BY count(*) DESC LIMIT 1	SELECT p.venue, p.year FROM paper p GROUP BY p.venue, p.year HAVING COUNT(p.paper_id) = (SELECT MAX(c) FROM (SELECT COUNT(paper_id) AS c FROM paper GROUP BY venue, year) t)	limit 1	0	1
999	What is the venue with the least number of publications?	SELECT venue FROM paper GROUP BY venue ORDER BY count(*) LIMIT 1	SELECT p.venue FROM paper p GROUP BY p.venue HAVING COUNT(p.paper_id) = (SELECT MIN(c.count) FROM (SELECT COUNT(paper_id) AS count FROM paper GROUP BY venue) c)	limit 1	0	1
1000	Which venue has the fewest publications?	SELECT venue FROM paper GROUP BY venue ORDER BY count(*) LIMIT 1	WITH VenueCount AS (SELECT venue, COUNT(paper_id) as cnt FROM paper GROUP BY venue) SELECT venue FROM VenueCount WHERE cnt = (SELECT MIN(cnt) FROM VenueCount)	limit 1	0	1
1005	What is the id and the number of citations of the most cited paper?	SELECT paper_id , count(*) FROM Citation GROUP BY cited_paper_id ORDER BY count(*) DESC LIMIT 1	SELECT cited_paper_id, COUNT(cited_paper_id) as total_citations FROM citation GROUP BY cited_paper_id HAVING total_citations = (SELECT MAX(citation_count) FROM (SELECT COUNT(*) as citation_count FROM citation GROUP BY cited_paper_id))	limit 1; semantic error	0	0

1006	Give the id and the number of citations of the most cited paper.	SELECT paper_id , count(*) FROM Citation GROUP BY cited_paper_id ORDER BY count(*) DESC LIMIT 1	SELECT cited_paper_id, COUNT(cited_paper_id) as total_citations FROM citation GROUP BY cited_paper_id HAVING total_citations = (SELECT MAX(citation_count) FROM (SELECT COUNT(*) as citation_count FROM citation GROUP BY cited_paper_id))	limit 1; semantic error	0	1
1007	Give the title of the paper which cites most number of papers?	SELECT T2.title FROM Citation AS T1 JOIN Paper AS T2 ON T2.paper_id = T1.paper_id GROUP BY T1.paper_id ORDER BY count(*) DESC LIMIT 1	SELECT title FROM (SELECT T2.title, rank() over (ORDER BY count(*) DESC) as rk FROM Citation AS T1 JOIN Paper AS T2 ON T2.paper_id = T1.paper_id GROUP BY T1.paper_id) WHERE rk = 1	limit 1	0	0
1008	What is the title of the paper which cites the most other papers?	SELECT T2.title FROM Citation AS T1 JOIN Paper AS T2 ON T2.paper_id = T1.paper_id GROUP BY T1.paper_id ORDER BY count(*) DESC LIMIT 1	SELECT title FROM (SELECT T2.title, rank() over (ORDER BY count(*) DESC) as rk FROM Citation AS T1 JOIN Paper AS T2 ON T2.paper_id = T1.paper_id GROUP BY T1.paper_id) WHERE rk = 1	limit 1	1	0
1009	List top 10 most cited papers and their numbers of citations.	SELECT paper_id , count(*) FROM Citation GROUP BY cited_paper_id ORDER BY count(*) DESC LIMIT 10	SELECT cited_paper_id, cnt FROM (SELECT cited_paper_id , count(*) as cnt, RANK() OVER (ORDER BY count(*) DESC) as rk FROM Citation GROUP BY cited_paper_id) WHERE rk <= 10	limit n; semantic error	1	0
1010	What are the 10 most cited papers, and how many citations did each have?	SELECT paper_id , count(*) FROM Citation GROUP BY cited_paper_id ORDER BY count(*) DESC LIMIT 10	SELECT cited_paper_id, cnt FROM (SELECT cited_paper_id , count(*) as cnt, RANK() OVER (ORDER BY count(*) DESC) as rk FROM Citation GROUP BY cited_paper_id) WHERE rk <= 10	limit n; semantic error	1	0
1015	Find the name and number of citations of the author who has most citations among all authors?	SELECT T3.name , count(*) FROM Citation AS T1 JOIN Author_list AS T2 ON T1.cited_paper_id = T2.paper_id JOIN Author AS T3 ON T2.author_id = T3.author_id GROUP BY T2.author_id ORDER BY count(*) DESC LIMIT 1	SELECT name, cnt FROM (SELECT T3.name, count(*) as cnt, RANK() OVER (ORDER BY count(*) DESC) as rk FROM Citation AS T1 JOIN Author_list AS T2 ON T1.cited_paper_id = T2.paper_id JOIN Author AS T3 ON T2.author_id = T3.author_id GROUP BY T2.author_id) WHERE rk <= 1	limit 1	0	0
1016	What is the name and number of citations of the author with the greatest number of citations among authors?	SELECT T3.name , count(*) FROM Citation AS T1 JOIN Author_list AS T2 ON T1.cited_paper_id = T2.paper_id JOIN Author AS T3 ON T2.author_id = T3.author_id GROUP BY T2.author_id ORDER BY count(*) DESC LIMIT 1	SELECT name, cnt FROM (SELECT T3.name, count(*) as cnt, RANK() OVER (ORDER BY count(*) DESC) as rk FROM Citation AS T1 JOIN Author_list AS T2 ON T1.cited_paper_id = T2.paper_id JOIN Author AS T3 ON T2.author_id = T3.author_id GROUP BY T2.author_id) WHERE rk <= 1	limit 1	0	0
1019	What are the venues and years where Columbia University had papers ?	select distinct t1.venue , t1.year from paper as t1 join author_list as t2 on t1.paper_id = t2.paper_id join affiliation as t3 on t2.affiliation_id = t3.affiliation_id where t3.name = "columbia university"	SELECT DISTINCT p.venue, p.year FROM paper p JOIN author_list al ON p.paper_id = al.paper_id JOIN affiliation a ON al.affiliation_id = a.affiliation_id WHERE a.name = 'Columbia University'	str	0	1
1020	Which venues and years did Columbia University have papers ?	select distinct t1.venue , t1.year from paper as t1 join author_list as t2 on t1.paper_id = t2.paper_id join affiliation as t3 on t2.affiliation_id = t3.affiliation_id where t3.name = "columbia university"	SELECT DISTINCT P.venue, P.year FROM paper P JOIN author_list AL ON P.paper_id = AL.paper_id JOIN affiliation A ON AL.affiliation_id = A.affiliation_id WHERE A.name = 'Columbia University'	str	0	1
1021	Which author had the most papers in the year 2009?	SELECT T3.name FROM Paper AS T1 JOIN Author_list AS T2 ON T1.paper_id = T2.paper_id JOIN Author AS T3 ON T3.author_id = T2.author_id WHERE T1.year = 2009 GROUP BY T2.author_id ORDER BY count(*) DESC LIMIT 1	SELECT name FROM (SELECT T3.name, RANK() OVER (ORDER BY COUNT(*) DESC) as rk FROM Paper AS T1 JOIN Author_list AS T2 ON T1.paper_id = T2.paper_id JOIN Author AS T3 ON T3.author_id = T2.author_id WHERE T1.year = 2009 GROUP BY T2.author_id) AS subquery WHERE rk = 1	limit 1	1	0
1022	What is the name of the author with the most papers in 2009?	SELECT T3.name FROM Paper AS T1 JOIN Author_list AS T2 ON T1.paper_id = T2.paper_id JOIN Author AS T3 ON T3.author_id = T2.author_id WHERE T1.year = 2009 GROUP BY T2.author_id ORDER BY count(*) DESC LIMIT 1	SELECT name FROM (SELECT T3.name, RANK() OVER (ORDER BY COUNT(*) DESC) as rk FROM Paper AS T1 JOIN Author_list AS T2 ON T1.paper_id = T2.paper_id JOIN Author AS T3 ON T3.author_id = T2.author_id WHERE T1.year = 2009 GROUP BY T2.author_id) AS subquery WHERE rk = 1	limit 1	1	0

1023	What are the names of the top 3 affiliations that have the most papers in year 2009?	SELECT T3.name FROM Paper AS T1 JOIN Author_list AS T2 ON T1.paper_id = T2.paper_id JOIN Affiliation AS T3 ON T2.affiliation_id = T3.affiliation_id WHERE T1.year = 2009 GROUP BY T2.affiliation_id ORDER BY count(*) DESC LIMIT 3	SELECT name FROM (SELECT T3.name, RANK() OVER (ORDER BY COUNT(*) DESC) as rk FROM Paper AS T1 JOIN Author_list AS T2 ON T1.paper_id = T2.paper_id JOIN Affiliation AS T3 ON T2.affiliation_id = T3.affiliation_id WHERE T1.year = 2009 GROUP BY T2.affiliation_id) AS subquery WHERE rk <= 3	limit n	1	0
1024	Which 3 affiliations had the most papers in 2009?	SELECT T3.name FROM Paper AS T1 JOIN Author_list AS T2 ON T1.paper_id = T2.paper_id JOIN Affiliation AS T3 ON T2.affiliation_id = T3.affiliation_id WHERE T1.year = 2009 GROUP BY T2.affiliation_id ORDER BY count(*) DESC LIMIT 3	SELECT name FROM (SELECT T3.name, RANK() OVER (ORDER BY COUNT(*) DESC) as rk FROM Paper AS T1 JOIN Author_list AS T2 ON T1.paper_id = T2.paper_id JOIN Affiliation AS T3 ON T2.affiliation_id = T3.affiliation_id WHERE T1.year = 2009 GROUP BY T2.affiliation_id) AS subquery WHERE rk <= 3	limit n	0	0
1025	How many papers does Columbia University have in or before 2009 ?	select count(distinct t1.paper_id) from paper as t1 join author_list as t2 on t1.paper_id = t2.paper_id join affiliation as t3 on t2.affiliation_id = t3.affiliation_id where t1.year <= 2009 and t3.name = "columbia university"	SELECT COUNT(DISTINCT paper.paper_id) FROM paper JOIN author_list ON paper.paper_id = author_list.paper_id JOIN affiliation ON affiliation.affiliation_id = author_list.affiliation_id WHERE affiliation.name = 'Columbia University' AND paper.year <= 2009	str	0	1
1026	Count the number of papers Columbia University had during or prior to 2009 .	select count(distinct t1.paper_id) from paper as t1 join author_list as t2 on t1.paper_id = t2.paper_id join affiliation as t3 on t2.affiliation_id = t3.affiliation_id where t1.year <= 2009 and t3.name = "columbia university"	SELECT COUNT(DISTINCT paper.paper_id) FROM paper JOIN author_list ON paper.paper_id = author_list.paper_id JOIN affiliation ON author_list.affiliation_id = affiliation.affiliation_id WHERE affiliation.name = 'Columbia University' AND paper.year <= 2009	str	0	1
1029	What is the title of the paper that has most number of authors?	SELECT T2.title FROM Author_list AS T1 JOIN Paper AS T2 ON T1.paper_id = T2.paper_id GROUP BY T2.paper_id ORDER BY count(*) DESC LIMIT 1	SELECT P.title FROM paper P WHERE P.paper_id IN (SELECT A.paper_id FROM author_list A GROUP BY A.paper_id HAVING COUNT(A.author_id) = (SELECT MAX(T.auth_count) FROM (SELECT COUNT(author_id) AS auth_count FROM author_list GROUP BY paper_id) T))	limit 1	1	0
1030	Give the title of the paper with the most authors.	SELECT T2.title FROM Author_list AS T1 JOIN Paper AS T2 ON T1.paper_id = T2.paper_id GROUP BY T2.paper_id ORDER BY count(*) DESC LIMIT 1	SELECT P.title FROM paper P WHERE P.paper_id IN (SELECT A.paper_id FROM author_list A GROUP BY A.paper_id HAVING COUNT(A.author_id) = (SELECT MAX(T.auth_count) FROM (SELECT COUNT(author_id) AS auth_count FROM author_list GROUP BY paper_id) T))	limit 1	0	1
1033	Who has the most papers co-authored with Mckeown , Kathleen ?	select t4.name from author_list as t1 join author_list as t2 on t1.paper_id = t2.paper_id and t1.author_id != t2.author_id join author as t3 on t1.author_id = t3.author_id join author as t4 on t2.author_id = t4.author_id where t3.name = "mckeown , kathleen" group by t2.author_id order by count(*) desc limit 1	SELECT name FROM (SELECT t4.name, RANK() OVER (ORDER BY COUNT(*) DESC) as rk FROM author_list as t1 JOIN author_list as t2 ON t1.paper_id = t2.paper_id AND t1.author_id != t2.author_id JOIN author as t3 ON t1.author_id = t3.author_id JOIN author as t4 ON t2.author_id = t4.author_id WHERE t3.name = 'mckeown , kathleen' GROUP BY t2.author_id) AS subquery WHERE rk = 1	limit 1	1	0
1034	What is the name of the author who has co-authored the most papers with Mckeown , Kathleen ?	select t4.name from author_list as t1 join author_list as t2 on t1.paper_id = t2.paper_id and t1.author_id != t2.author_id join author as t3 on t1.author_id = t3.author_id join author as t4 on t2.author_id = t4.author_id where t3.name = "mckeown , kathleen" group by t2.author_id order by count(*) desc limit 1	SELECT name FROM (SELECT t4.name, RANK() OVER (ORDER BY COUNT(*) DESC) as rk FROM author_list as t1 JOIN author_list as t2 ON t1.paper_id = t2.paper_id AND t1.author_id != t2.author_id JOIN author as t3 ON t1.author_id = t3.author_id JOIN author as t4 ON t2.author_id = t4.author_id WHERE t3.name = 'mckeown , kathleen' GROUP BY t2.author_id) AS subquery WHERE rk = 1	limit 1	1	0

1039	Find the name of the affiliation whose address contains 'China' and publishes the greatest number of papers.	SELECT T1.name FROM Affiliation AS T1 JOIN Author_list AS T2 ON T1.affiliation_id = T2.affiliation_id WHERE T1.address LIKE "%China%" GROUP BY T1.affiliation_id ORDER BY count(*) DESC LIMIT 1	SELECT a.name FROM affiliation a WHERE a.address LIKE '%China%' AND a.affiliation_id IN (SELECT al.affiliation_id FROM author_list al GROUP BY al.affiliation_id HAVING COUNT(DISTINCT al.paper_id) = (SELECT MAX(c) FROM (SELECT COUNT(paper_id) AS c FROM author_list WHERE affiliation_id IN (SELECT affiliation_id FROM affiliation WHERE address LIKE '%China%') GROUP BY affiliation_id)))	limit 1	0	0
1040	What is the name of the affiliation which publishes the greatest number of papers among those whose address contains 'China'.	SELECT T1.name FROM Affiliation AS T1 JOIN Author_list AS T2 ON T1.affiliation_id = T2.affiliation_id WHERE T1.address LIKE "%China%" GROUP BY T1.affiliation_id ORDER BY count(*) DESC LIMIT 1	SELECT a.name FROM affiliation a WHERE a.address LIKE '%China%' AND a.affiliation_id IN (SELECT al.affiliation_id FROM author_list al GROUP BY al.affiliation_id HAVING COUNT(DISTINCT al.paper_id) = (SELECT MAX(c) FROM (SELECT COUNT(paper_id) AS c FROM author_list WHERE affiliation_id IN (SELECT affiliation_id FROM affiliation WHERE address LIKE '%China%') GROUP BY affiliation_id)))	limit 1	0	1
1063	which year has least number of conferences?	SELECT YEAR FROM conference GROUP BY YEAR ORDER BY count(*) LIMIT 1	SELECT year FROM conference GROUP BY year HAVING COUNT(*) = (SELECT MIN(c) FROM (SELECT COUNT(*) AS c FROM conference GROUP BY year))	limit 1	0	1
1064	What year had the fewest conferences?	SELECT YEAR FROM conference GROUP BY YEAR ORDER BY count(*) LIMIT 1	SELECT a.year FROM (SELECT year, COUNT(conference_id) transmission_count FROM conference GROUP BY year) a WHERE a.transmission_count = (SELECT MIN(transmission_count) FROM (SELECT COUNT(conference_id) transmission_count FROM conference GROUP BY year))	limit 1	0	1
1071	Show the institution name and location of institution that is most recently founded.	SELECT institution_name , LOCATION FROM institution ORDER BY founded DESC LIMIT 1	SELECT i.institution_name, i.location FROM institution i WHERE i.founded = (SELECT MAX(founded) FROM institution)	limit 1	0	1
1072	What are the names and locations of the most recently-founded institution?	SELECT institution_name , LOCATION FROM institution ORDER BY founded DESC LIMIT 1	SELECT i.institution_name, i.location FROM institution i WHERE i.founded = (SELECT MAX(founded) FROM institution)	limit 1	1	0
1073	Show the institution name and the number of staff for each institution founded after 1800.	SELECT T1.institution_name , count(*) FROM institution AS T1 JOIN staff AS T2 ON T1.institution_id = T2.institution_id WHERE T1.founded > 1800 GROUP BY T2.institution_id	SELECT institution_name, (SELECT COUNT(*) FROM staff WHERE staff.institution_id = institution.institution_id) AS staff_count FROM institution WHERE founded > 1800	join -> left join	0	1
1074	For each institution id , how many staff members does each institution have that was founded after 1800 ? return their names .	select t1.institution_name , count(*) from institution as t1 join staff as t2 on t1.institution_id = t2.institution_id where t1.founded > 1800 group by t2.institution_id	SELECT institution_name, (SELECT COUNT(*) FROM staff WHERE staff.institution_id = institution.institution_id) AS staff_count FROM institution WHERE founded > 1800	join -> left join	0	0
1079	What is the maximum and minimum age of all staff from the United States?	SELECT max(age) , min(age) FROM staff	SELECT MAX(age) AS maximum_age, MIN(age) AS minimum_age FROM staff WHERE nationality = 'United States';	semantic error	1	0
1081	Show all conference names which the staff from Canada attends.	SELECT T1.conference_name FROM conference AS T1 JOIN conference_participation AS T2 ON T1.conference_id = T2.conference_id JOIN staff AS T3 ON T2.staff_id = T3.staff_id WHERE T3.nationality = "Canada"	SELECT conference_name FROM conference WHERE conference_id IN (SELECT conference_id FROM conference_participation WHERE staff_id IN (SELECT staff_id FROM staff WHERE nationality = 'Canada'))	join -> in-sub	0	1

1082	What are the names of all the conferences that has staff from Canada attending?	SELECT T1.conference_name FROM conference AS T1 JOIN conference_participation AS T2 ON T1.conference_id = T2.conference_id JOIN staff AS T3 ON T2.staff_id = T3.staff_id WHERE T3.nationality = "Canada"	SELECT conference_name FROM conference WHERE conference_id IN (SELECT conference_id FROM conference_participation WHERE staff_id IN (SELECT staff_id FROM staff WHERE nationality = 'Canada'))	join -> in-sub	0	0
1083	Show all staff names who have been both speaker and sponsor in some conference.	SELECT T1.name FROM staff AS T1 JOIN conference_participation AS T2 ON T1.staff_id = T2.staff_id WHERE T2.role = 'Speaker' INTERSECT SELECT T1.name FROM staff AS T1 JOIN conference_participation AS T2 ON T1.staff_id = T2.staff_id WHERE T2.role = 'Sponsor'	SELECT name FROM staff WHERE staff_id IN (SELECT staff_id FROM conference_participation WHERE role = 'Speaker' INTERSECT SELECT staff_id FROM conference_participation WHERE role = 'Sponsor')	except non-key	0	1
1084	What are the names of the staff members who have been both a speaker and a sponsor at some conference?	SELECT T1.name FROM staff AS T1 JOIN conference_participation AS T2 ON T1.staff_id = T2.staff_id WHERE T2.role = 'Speaker' INTERSECT SELECT T1.name FROM staff AS T1 JOIN conference_participation AS T2 ON T1.staff_id = T2.staff_id WHERE T2.role = 'Sponsor'	SELECT name FROM staff WHERE staff_id IN (SELECT staff_id FROM conference_participation WHERE role = 'Speaker') AND staff_id IN (SELECT staff_id FROM conference_participation WHERE role = 'Sponsor')	except non-key	0	1
1085	Show all names who have been in both ACL and Naccl.	SELECT T1.name FROM staff AS T1 JOIN conference_participation AS T2 JOIN Conference AS T3 ON T1.staff_id = T2.staff_id AND T2.conference_id = T3.conference_id WHERE T3.Conference_name = 'ACL' INTERSECT SELECT T1.name FROM staff AS T1 JOIN conference_participation AS T2 JOIN conference AS T3 ON T1.staff_id = T2.staff_id AND T2.conference_id = T3.conference_id WHERE T3.Conference_name = 'Naccl'	SELECT s.name FROM staff s WHERE EXISTS (SELECT 1 FROM conference_participation cp JOIN conference c ON cp.conference_id = c.conference_id WHERE s.staff_id = cp.staff_id AND c.conference_name = 'ACL') AND EXISTS (SELECT 1 FROM conference_participation cp JOIN conference c ON cp.conference_id = c.conference_id WHERE s.staff_id = cp.staff_id AND c.conference_name = 'Naccl')	except non-key	0	1
1086	What are the names of everybody who has participated in both the ACL and NACCL conferences?	SELECT T1.name FROM staff AS T1 JOIN conference_participation AS T2 JOIN Conference AS T3 ON T1.staff_id = T2.staff_id AND T2.conference_id = T3.conference_id WHERE T3.Conference_name = 'ACL' INTERSECT SELECT T1.name FROM staff AS T1 JOIN conference_participation AS T2 JOIN conference AS T3 ON T1.staff_id = T2.staff_id AND T2.conference_id = T3.conference_id WHERE T3.Conference_name = 'Naccl'	SELECT s.name FROM staff s WHERE EXISTS (SELECT 1 FROM conference_participation cp JOIN conference c ON cp.conference_id = c.conference_id WHERE s.staff_id = cp.staff_id AND c.conference_name = 'ACL') AND EXISTS (SELECT 1 FROM conference_participation cp JOIN conference c ON cp.conference_id = c.conference_id WHERE s.staff_id = cp.staff_id AND c.conference_name = 'NACCL')	except non-key; str	1	0
1087	Show all staff names who attend a conference in 2003 or 2004.	SELECT DISTINCT T1.name FROM staff AS T1 JOIN conference_participation AS T2 JOIN Conference AS T3 ON T1.staff_id = T2.staff_id AND T2.conference_id = T3.conference_id WHERE T3.year = 2003 OR T3.year = 2004	SELECT s.name FROM staff s WHERE EXISTS (SELECT 1 FROM conference_participation cp JOIN conference c ON cp.conference_id = c.conference_id WHERE cp.staff_id = s.staff_id AND c.year IN (2003, 2004))	join -> in-sub	0	1
1088	What are the staff names who participated in conferences between 2003 or 2004?	SELECT DISTINCT T1.name FROM staff AS T1 JOIN conference_participation AS T2 JOIN Conference AS T3 ON T1.staff_id = T2.staff_id AND T2.conference_id = T3.conference_id WHERE T3.year = 2003 OR T3.year = 2004	SELECT name FROM staff WHERE EXISTS (SELECT 1 FROM conference_participation cp JOIN conference c ON cp.conference_id = c.conference_id WHERE cp.staff_id = staff.staff_id AND (c.year BETWEEN 2003 AND 2004))	join -> in-sub	0	1
1089	Show the conference name and year and the number of participants for each conference.	SELECT T1.conference_name, T1.year, count(*) FROM Conference AS T1 JOIN Conference_participation AS T2 ON T1.conference_id = T2.conference_id GROUP BY T2.conference_id	SELECT c.conference_name, c.year, (SELECT COUNT(*) FROM conference_participation WHERE conference_id = c.conference_id) AS participants FROM conference c	join -> left join	0	1
1090	For each conference id, what are their names, year, and number of participants?	SELECT T1.conference_name, T1.year, count(*) FROM Conference AS T1 JOIN Conference_participation AS T2 ON T1.conference_id = T2.conference_id GROUP BY T2.conference_id	SELECT c.conference_id, c.conference_name, c.year, (SELECT COUNT(*) FROM conference_participation WHERE conference_id = c.conference_id) AS num_participants FROM conference AS c	join -> left join; semantic error: lack column	0	1
1091	Find the name of the conferences that have the top 2 most number of attendants.	SELECT T1.conference_name FROM Conference AS T1 JOIN Conference_participation AS T2 ON T1.conference_id = T2.conference_id GROUP BY T2.conference_id ORDER BY count(*) DESC LIMIT 2	SELECT conference_name FROM (SELECT T1.conference_name, rank() over (ORDER BY count(*) DESC) as rk FROM Conference AS T1 JOIN Conference_participation AS T2 ON T1.conference_id = T2.conference_id GROUP BY T2.conference_id) WHERE rk <= 2	limit n	1	0

1092	What are the names of the conferences that have the top 2 most people attending?	SELECT T1.conference_name FROM Conference AS T1 JOIN Conference_participation AS T2 ON T1.conference_id = T2.conference_id GROUP BY T2.conference_id ORDER BY count(*) DESC LIMIT 2	SELECT conference_name FROM (SELECT T1.conference_name, rank() over (ORDER BY count(*) DESC) as rk FROM Conference AS T1 JOIN Conference_participation AS T2 ON T1.conference_id = T2.conference_id GROUP BY T2.conference_id) WHERE rk <= 2	limit n	0	0
1095	Find the name and location of the universities that did not have any staff participated in any conference in 2004.	SELECT T1.Institution_Name , T1.location FROM institution AS T1 JOIN staff AS T2 ON T1.institution_id = T2.institution_id WHERE T2.staff_id NOT IN (SELECT T4.staff_id FROM Conference AS T3 JOIN Conference_participation AS T4 ON T3.conference_id = T4.conference_id WHERE T3.year = 2004)	SELECT i.institution_name, i.location FROM institution i WHERE NOT EXISTS (SELECT 1 FROM staff s JOIN conference_participation cp ON s.staff_id = cp.staff_id JOIN conference c ON c.conference_id = cp.conference_id WHERE c.year = 2004 AND s.institution_id = i.institution_id)	join -> in-sub	0	1
1096	What are the names and locations of the universities that did not have any staff participating in any conferences in 2004?	SELECT T1.Institution_Name , T1.location FROM institution AS T1 JOIN staff AS T2 ON T1.institution_id = T2.institution_id WHERE T2.staff_id NOT IN (SELECT T4.staff_id FROM Conference AS T3 JOIN Conference_participation AS T4 ON T3.conference_id = T4.conference_id WHERE T3.year = 2004)	SELECT i.institution_name, i.location FROM institution i WHERE NOT EXISTS (SELECT 1 FROM staff s JOIN conference_participation cp ON s.staff_id = cp.staff_id JOIN conference c ON cp.conference_id = c.conference_id WHERE s.institution_id = i.institution_id AND c.year = 2004)	join -> in-sub	0	1
1097	What is the name of the oldest pilot?	SELECT pilot_name FROM PilotSkills ORDER BY age DESC LIMIT 1	SELECT pilot_name FROM pilotskills WHERE age = (SELECT MAX(age) FROM pilotskills)	limit 1	0	1
1098	Return the name of the oldest pilot.	SELECT pilot_name FROM PilotSkills ORDER BY age DESC LIMIT 1	SELECT pilot_name FROM pilotskills WHERE age = (SELECT MAX(age) FROM pilotskills)	limit 1	0	1
1115	Who is the youngest pilot to fly the plane Piper Cub?	SELECT pilot_name FROM pilotskills WHERE plane_name = 'Piper Cub' ORDER BY age LIMIT 1	SELECT pilot_name FROM pilotskills WHERE plane_name = 'Piper Cub' AND age = (SELECT MIN(age) FROM pilotskills WHERE plane_name = 'Piper Cub')	limit 1	0	1
1116	Return the name of the youngest pilot to fly Piper Cub.	SELECT pilot_name FROM pilotskills WHERE plane_name = 'Piper Cub' ORDER BY age LIMIT 1	SELECT pilot_name FROM pilotskills WHERE plane_name = 'Piper Cub' AND age = (SELECT MIN(age) FROM pilotskills WHERE plane_name = 'Piper Cub')	limit 1	0	1
1117	What is the name of the most popular plane?	SELECT plane_name FROM pilotskills GROUP BY plane_name ORDER BY count(*) DESC LIMIT 1	WITH RankedPlanes AS (SELECT plane_name, RANK() OVER (ORDER BY COUNT(*) DESC) as rank FROM pilotskills GROUP BY plane_name) SELECT plane_name FROM RankedPlanes WHERE rank = 1	limit 1	0	1
1118	What is the name of the plane that is flown the most often?	SELECT plane_name FROM pilotskills GROUP BY plane_name ORDER BY count(*) DESC LIMIT 1	SELECT plane_name FROM pilotskills GROUP BY plane_name HAVING COUNT(*) = (SELECT MAX(cnt) FROM (SELECT COUNT(*) AS cnt FROM pilotskills GROUP BY plane_name) t)	limit 1	0	1
1119	What is the name of the least popular plane?	SELECT plane_name FROM pilotskills GROUP BY plane_name ORDER BY count(*) LIMIT 1	SELECT plane_name FROM (SELECT h.plane_name, rank() over (ORDER BY COUNT(p.plane_name)) as rk FROM hangar h LEFT JOIN pilotskills p ON h.plane_name = p.plane_name GROUP BY h.plane_name) WHERE rk = 1	limit 1; join -> left join	0	0
1120	What is the name of the plane that is flown the least often?	SELECT plane_name FROM pilotskills GROUP BY plane_name ORDER BY count(*) LIMIT 1	SELECT plane_name FROM (SELECT h.plane_name, rank() over (ORDER BY COUNT(p.plane_name)) as rk FROM hangar h LEFT JOIN pilotskills p ON h.plane_name = p.plane_name GROUP BY h.plane_name) WHERE rk = 1	limit 1; join -> left join	0	0
1138	What are the different plane names, ordered alphabetically?	SELECT DISTINCT plane_name FROM pilotskills ORDER BY plane_name	SELECT DISTINCT plane_name FROM hangar ORDER BY plane_name ASC	semantic error: wrong table	0	1
1155	Find the number of planes for each type.	SELECT count(*) , plane_name FROM pilotskills GROUP BY plane_name	SELECT h.plane_name, count(p.plane_name) FROM Hangar AS h LEFT JOIN PilotSkills as p on h.plane_name = p.plane_name group by h.plane_name	join -> left join	1	0

1156	Count the number of entries for each plane name.	SELECT count(*) , plane_name FROM pilotskills GROUP BY plane_name	SELECT h.plane_name, count(p.plane_name) FROM Hangar AS h LEFT JOIN PilotSkills as p on h.plane_name = p.plane_name group by h.plane_name	join -> left join	0	0
1157	Find the name of the oldest pilot for each type of plane, and order the results by plane name.	SELECT pilot_name , plane_name , max(age) FROM pilotskills GROUP BY plane_name ORDER BY plane_name	SELECT ps.plane_name, ps.pilot_name FROM pilotskills ps WHERE ps.age = (SELECT MAX(age) FROM pilotskills WHERE plane_name = ps.plane_name) ORDER BY ps.plane_name	limit 1; semantic error: redundant column	0	0
1158	What are the different plane names, and what are the names of the oldest pilot who has each, ordered by plane name?	SELECT pilot_name , plane_name , max(age) FROM pilotskills GROUP BY plane_name ORDER BY plane_name	SELECT h.plane_name, ps.pilot_name FROM hangar h JOIN pilotskills ps ON h.plane_name = ps.plane_name WHERE ps.age = (SELECT MAX(age) FROM pilotskills WHERE plane_name = h.plane_name) ORDER BY h.plane_name	limit 1; semantic error: redundant column	0	1
1159	What are the names of oldest pilots for each type of plane?	SELECT pilot_name , plane_name , max(age) FROM pilotskills GROUP BY plane_name	SELECT ps.pilot_name, ps.plane_name FROM pilotskills ps INNER JOIN (SELECT plane_name, MAX(age) AS max_age FROM pilotskills GROUP BY plane_name) max_ps ON ps.plane_name = max_ps.plane_name AND ps.age = max_ps.max_age	limit 1; semantic error: redundant column	0	0
1160	Return the names of the different planes, as well as the names of the oldest pilots who flew each.	SELECT pilot_name , plane_name , max(age) FROM pilotskills GROUP BY plane_name	SELECT DISTINCT hangar.plane_name, pilotskills.pilot_name FROM hangar JOIN pilotskills ON hangar.plane_name = pilotskills.plane_name WHERE pilotskills.age = (SELECT MAX(age) FROM pilotskills WHERE pilotskills.plane_name = hangar.plane_name)	limit 1; semantic error: redundant column	0	1
1163	For each city, find the number and average age of pilots who have a plane.	SELECT count(T1.pilot_name) , avg(T1.age) , T2.location FROM pilotskills AS T1 JOIN hangar AS T2 ON T1.plane_name = T2.plane_name GROUP BY T2.location	SELECT h.location, COUNT(pilot_name) as num_pilots, AVG(ps.age) as av_age FROM hangar h LEFT JOIN pilotskills ps ON h.plane_name = ps.plane_name GROUP BY h.location	join -> left join	1	0
1164	What are the different hangar locations and how many pilots correspond to each. Also, what are their average ages?	SELECT count(T1.pilot_name) , avg(T1.age) , T2.location FROM pilotskills AS T1 JOIN hangar AS T2 ON T1.plane_name = T2.plane_name GROUP BY T2.location	SELECT h.location, COUNT(pilot_name) as num_pilots, AVG(ps.age) as av_age FROM hangar h LEFT JOIN pilotskills ps ON h.plane_name = ps.plane_name GROUP BY h.location	join -> left join	0	0
1167	Find the location of the plane that is owned by the youngest pilot.	SELECT T2.location FROM pilotskills AS T1 JOIN hangar AS T2 ON T1.plane_name = T2.plane_name WHERE T1.age = (SELECT min(age) FROM pilotskills)	SELECT location FROM hangar WHERE plane_name in (SELECT plane_name FROM pilotskills WHERE age = (select min(age) from PilotSkills))	join -> in sub	0	0
1168	What is the location of the plane that was flown by the pilot with the lowest age?	SELECT T2.location FROM pilotskills AS T1 JOIN hangar AS T2 ON T1.plane_name = T2.plane_name WHERE T1.age = (SELECT min(age) FROM pilotskills)	SELECT location FROM hangar WHERE plane_name in (SELECT plane_name FROM pilotskills WHERE age = (select min(age) from PilotSkills))	join -> in sub	0	0
1171	List in alphabetic order the names of pilots whose age is greater than some pilots having plane Piper Cub.	SELECT pilot_name FROM pilotskills WHERE age > (SELECT min(age) FROM pilotskills WHERE plane_name = 'Piper Cub') ORDER BY pilot_name	SELECT DISTINCT p1.pilot_name FROM pilotskills p1, pilotskills p2 WHERE p1.age > p2.age AND p2.plane_name = 'Piper Cub' ORDER BY p1.pilot_name	lack distinct; schema flaw	0	1
1172	Return the names of pilots who are older than any pilot who has flown Piper Cub, ordered alphabetically.	SELECT pilot_name FROM pilotskills WHERE age > (SELECT min(age) FROM pilotskills WHERE plane_name = 'Piper Cub') ORDER BY pilot_name	SELECT ps1.pilot_name FROM pilotskills ps1 WHERE ps1.age > (SELECT MAX(ps2.age) FROM pilotskills ps2 WHERE ps2.plane_name = 'Piper Cub') ORDER BY ps1.pilot_name	semantic error; lack distinct; schema flaw	0	1

1175	Find all different planes whose names contain substring 'Bomber'.	SELECT DISTINCT plane_name FROM pilot-skills WHERE plane_name LIKE '%Bomber%'	SELECT DISTINCT plane_name FROM hangar WHERE plane_name LIKE '%Bomber%'	semantic error: wrong table	0	1
1176	What are the different plane names that contain the word Bomber?	SELECT DISTINCT plane_name FROM pilot-skills WHERE plane_name LIKE '%Bomber%'	SELECT DISTINCT plane_name FROM hangar WHERE plane_name LIKE '%Bomber%'	semantic error: wrong table	0	1
1179	Find the name of the district which has the largest area.	SELECT name FROM district ORDER BY Area_km DESC LIMIT 1	SELECT d.name FROM district d WHERE d.area_km = (SELECT MAX(area_km) FROM district)	limit 1	0	1
1180	Select the area and government website of the district with the smallest population.	SELECT area_km , Government_website FROM district ORDER BY Population LIMIT 1	SELECT area_km , Government_website FROM district WHERE Population = (SELECT min(Population) FROM district);	limit 1	0	0
1183	What is the total population of the districts whose areas are in the top 3?	SELECT sum(population) FROM district ORDER BY area_km DESC LIMIT 3	SELECT SUM(Population) FROM (SELECT Population, rank() over (ORDER BY Area_km DESC) AS rk FROM district) WHERE rk <= 3	limit n	0	0
1190	Who is the oldest spokesman?	SELECT name FROM spokesman ORDER BY age DESC LIMIT 1	SELECT name FROM spokesman WHERE Age = (SELECT max(Age) FROM spokesman)	limit 1	1	0
1192	Find the name of the district which has greatest number of spokesmen.	SELECT t1.name FROM district AS t1 JOIN spokesman_district AS t2 ON t1.District_ID = t2.District_ID GROUP BY t2.District_ID ORDER BY count(*) DESC LIMIT 1	SELECT d.name FROM district AS d INNER JOIN (SELECT district_id FROM spokesman_district GROUP BY district_id HAVING COUNT(spokesman_id) = (SELECT MAX(c) FROM (SELECT COUNT(spokesman_id) as c FROM spokesman_district GROUP BY district_id))) y ON d.district_id = y.district_id	limit 1	0	1
1193	Find the names of spokesmen who have served some district before 2004.	SELECT t1.name FROM spokesman AS t1 JOIN spokesman_district AS t2 ON t1.Spokesman_ID = t2.Spokesman_ID WHERE t2.start_year < 2004	SELECT name FROM spokesman WHERE spokesman_id IN (SELECT spokesman_id FROM spokesman_district WHERE start_year < 2004)	join -> in sub	0	0
1194	Find the number of spokesmen for each district, and the show district names as well.	SELECT t1.name , count(*) FROM district AS t1 JOIN spokesman_district AS t2 ON t1.District_ID = t2.District_ID GROUP BY t2.District_ID	SELECT name, (SELECT COUNT(spokesman_id) FROM spokesman_district WHERE district_id = d.district_id) AS num_spokesmen FROM district AS d	join -> left join	0	1
1195	Find the names of the districts which have had both spokesman with rank position 1 and 2.	SELECT t3.name FROM spokesman AS t1 JOIN spokesman_district AS t2 ON t1.Spokesman_ID = t2.Spokesman_ID JOIN district AS t3 ON t3.district_id = t2.district_id WHERE t1.rank_position = 1 INTERSECT SELECT t3.name FROM spokesman AS t1 JOIN spokesman_district AS t2 ON t1.Spokesman_ID = t2.Spokesman_ID JOIN district AS t3 ON t3.district_id = t2.district_id WHERE t1.rank_position = 2	SELECT d.name FROM district d WHERE EXISTS (SELECT 1 FROM spokesman_district sd JOIN spokesman s ON sd.spokesman_id = s.spokesman_id WHERE sd.district_id = d.district_id AND s.rank_position = 1) AND EXISTS (SELECT 1 FROM spokesman_district sd JOIN spokesman s ON sd.spokesman_id = s.spokesman_id WHERE sd.district_id = d.district_id AND s.rank_position = 2);	intersect non-key	1	0
1200	What is the title of the sculpture that was created in the most recent year ?	select title from sculptures order by year desc limit 1	SELECT title FROM sculptures WHERE year = (SELECT MAX(year) FROM sculptures)	limit 1	0	1
1201	What is the name of the sculpture that was created most recently ?	select title from sculptures order by year desc limit 1	SELECT title FROM sculptures WHERE year = (SELECT MAX(year) FROM sculptures)	limit 1	0	0
1202	What is the title and location of the oldest painting ?	select title , location from paintings order by year limit 1	SELECT paintings.title, paintings.location FROM paintings WHERE paintings.year = (SELECT MIN(year) FROM paintings);	limit 1	1	0

1203	What is the name of the oldest painting and where is it located?	SELECT title , LOCATION , YEAR FROM paintings ORDER BY YEAR LIMIT 1	SELECT paintings.title, paintings.location FROM paintings WHERE paintings.year = (SELECT MIN(year) FROM paintings);	limit 1	0	1
1216	What are the first and last names of all distinct artists who made sculptures before 1900?	SELECT DISTINCT T1.lname , T1.fname FROM artists AS T1 JOIN sculptures AS T2 ON T1.artistID = T2.sculptorID WHERE T2.year < 1900	SELECT fname, lname FROM (SELECT DISTINCT artistid, fname, lname FROM artists) AS unique_artists WHERE unique_artists.artistid IN (SELECT sculptorid FROM sculptures WHERE year < 1900)	join -> in sub	0	1
1217	What is the first and last name of each distinct artists who made a sculpture before 1900?	SELECT DISTINCT T1.lname , T1.fname FROM artists AS T1 JOIN sculptures AS T2 ON T1.artistID = T2.sculptorID WHERE T2.year < 1900	SELECT fname, lname FROM artists WHERE EXISTS (SELECT 1 FROM sculptures WHERE sculptorid = artistid AND year < 1900)	join -> in sub	0	1
1218	Find the birth years of all distinct artists who made sculptures after 1920?	SELECT DISTINCT T1.birthYear FROM artists AS T1 JOIN sculptures AS T2 ON T1.artistID = T2.sculptorID WHERE T2.year > 1920	SELECT birthyear FROM artists WHERE EXISTS (SELECT 1 FROM sculptures WHERE sculptures.sculptorid = artists.artistid AND year > 1920)	join -> in sub	1	0
1219	What is the birth year of each distinct artists who created sculptures after 1920?	SELECT DISTINCT T1.birthYear FROM artists AS T1 JOIN sculptures AS T2 ON T1.artistID = T2.sculptorID WHERE T2.year > 1920	SELECT birthyear FROM artists WHERE EXISTS (SELECT 1 FROM sculptures WHERE sculptures.sculptorid = artists.artistid AND year > 1920)	join -> in sub	1	0
1220	What are the first and last names of the artist who lived the longest?	SELECT lname , fname FROM artists ORDER BY deathYear - birthYear DESC LIMIT 1	SELECT a.fname, a.lname FROM artists a WHERE (a.deathyear - a.birthyear) = (SELECT MAX(b.deathyear - b.birthyear) FROM artists b)	limit 1	1	0
1221	Give the full name of the artist who lived the longest.	SELECT lname , fname FROM artists ORDER BY deathYear - birthYear DESC LIMIT 1	SELECT a.fname, a.lname FROM artists a WHERE (a.deathyear - a.birthyear) = (SELECT MAX(b.deathyear - b.birthyear) FROM artists b)	limit 1	0	0
1222	What is the age of the artist who had the shortest life?	SELECT deathYear - birthYear FROM artists ORDER BY deathYear - birthYear LIMIT 1	SELECT lifespan FROM (SELECT (deathyear - birthyear) AS lifespan FROM artists) WHERE lifespan = (SELECT MIN(deathyear - birthyear) FROM artists)	limit 1	0	1
1223	How old is the artist who lived the shortest life?	SELECT deathYear - birthYear FROM artists ORDER BY deathYear - birthYear LIMIT 1	SELECT lifespan FROM (SELECT (deathyear - birthyear) AS lifespan FROM artists) WHERE lifespan = (SELECT MIN(deathyear - birthyear) FROM artists)	limit 1	0	0
1224	What are the first name and age of the artist who had the longest life?	SELECT fname , deathYear - birthYear FROM artists ORDER BY deathYear - birthYear DESC LIMIT 1	SELECT fname, deathyear - birthyear AS age FROM artists WHERE (deathyear - birthyear) = (SELECT MAX(deathyear - birthyear) FROM artists)	limit 1	0	0
1225	What is the first name and age of the artist who lived the longest?	SELECT fname , deathYear - birthYear FROM artists ORDER BY deathYear - birthYear DESC LIMIT 1	SELECT fname, deathyear - birthyear AS age FROM artists WHERE (deathyear - birthyear) = (SELECT MAX(deathyear - birthyear) FROM artists)	limit 1	1	0
1228	How many paintings did the artist with the longest life make ?	select count(*) from artists as t1 join paintings as t2 on t1.artistid = t2.painterid group by t2.painterid order by t1.deathyear - t1.birthyear desc limit 1	SELECT artistid, COUNT(*) FROM artists a LEFT JOIN paintings p ON p.painterid = a.artistid WHERE (a.deathyear - a.birthyear) = (SELECT MAX(deathyear - birthyear) FROM artists) GROUP BY a.artistid;	limit 1; join -> left join	0	0
1229	What is the painting count of the artist with the longest life ?	select count(*) from artists as t1 join paintings as t2 on t1.artistid = t2.painterid group by t2.painterid order by t1.deathyear - t1.birthyear desc limit 1	SELECT artistid, COUNT(*) FROM artists a LEFT JOIN paintings p ON p.painterid = a.artistid WHERE (a.deathyear - a.birthyear) = (SELECT MAX(deathyear - birthyear) FROM artists) GROUP BY a.artistid;	limit 1; join -> left join	1	0
1236	Find the first and last names of the artists who have both works of paintings and sculptures?	SELECT T1.lname , T1.fname FROM artists AS T1 JOIN sculptures AS T2 ON T1.artistID = T2.sculptorID INTERSECT SELECT T3.lname , T3.fname FROM artists AS T3 JOIN paintings AS T4 ON T3.artistID = T4.painterID	SELECT a.fname, a.lname FROM artists a WHERE EXISTS (SELECT 1 FROM paintings p WHERE p.painterid = a.artistid) AND EXISTS (SELECT 1 FROM sculptures s WHERE s.sculptorid = a.artistid)	intersect non-key	0	1

1237	Give the full names of artists who have created paintings and sculptures.	SELECT T1.lname , T1.fname FROM artists AS T1 JOIN sculptures AS T2 ON T1.artistID = T2.sculptorID INTERSECT SELECT T3.lname , T3.fname FROM artists AS T3 JOIN paintings AS T4 ON T3.artistID = T4.painterID	SELECT a.fname, a.lname FROM artists a WHERE EXISTS (SELECT 1 FROM paintings p WHERE p.painterid = a.artistid) AND EXISTS (SELECT 1 FROM sculptures s WHERE s.sculptorid = a.artistid)	intersect non-key	0	0
1238	What are the first and last names of the artists who have not only medium oil paintings but also paintings with the lithographic medium?	SELECT T1.lname , T1.fname FROM artists AS T1 JOIN paintings AS T2 ON T1.artistID = T2.painterID WHERE T2.medium = "oil" INTERSECT SELECT T3.lname , T3.fname FROM artists AS T3 JOIN paintings AS T4 ON T3.artistID = T4.painterID WHERE T4.medium = "lithograph"	SELECT a.fname, a.lname FROM artists a WHERE artistid IN (SELECT painterid FROM paintings WHERE medium = 'oil') AND artistid IN (SELECT painterid FROM paintings WHERE medium = 'lithograph')	intersect non-key	0	1
1239	What are the first and last names of artists who have painted using both oil and lithographic mediums?	SELECT T1.lname , T1.fname FROM artists AS T1 JOIN paintings AS T2 ON T1.artistID = T2.painterID WHERE T2.medium = "oil" INTERSECT SELECT T3.lname , T3.fname FROM artists AS T3 JOIN paintings AS T4 ON T3.artistID = T4.painterID WHERE T4.medium = "lithograph"	SELECT fname, lname FROM artists WHERE artistid IN (SELECT painterid FROM paintings WHERE medium = 'oil') AND artistid IN (SELECT painterid FROM paintings WHERE medium = 'lithograph')	intersect non-key	0	1
1240	What is the birth year of the artist who created a painting in 1884 that is on canvas?	SELECT T1.birthYear FROM artists AS T1 JOIN paintings AS T2 ON T1.artistID = T2.painterID WHERE T2.year = 1884 AND mediumOn = "canvas"	SELECT birthyear FROM artists WHERE artistid IN (SELECT painterid FROM paintings WHERE year = 1884 AND mediumon = 'canvas')	join -> in sub	0	1
1241	In what year was the artist who created a painting in 1884 born?	SELECT T1.birthYear FROM artists AS T1 JOIN paintings AS T2 ON T1.artistID = T2.painterID WHERE T2.year = 1884 AND mediumOn = "canvas"	SELECT birthyear FROM artists WHERE artistid IN (SELECT painterid FROM paintings WHERE year = 1884)	join -> in sub	0	1
1243	What are first names of the artists with oil paintings in gallery 241?	SELECT DISTINCT T1.fname FROM artists AS T1 JOIN paintings AS T2 ON T1.artistID = T2.painterID WHERE T2.medium = "oil" AND LOCATION = "Gallery 241"	SELECT fname FROM artists WHERE artistid IN (SELECT painterid FROM paintings WHERE medium = 'oil' AND location = 'Gallery 241')	join -> in sub	0	1
1244	What are the numbers of works for different medium type?	SELECT count(*) , medium FROM paintings GROUP BY medium	SELECT medium, COUNT(*) AS NumWorks FROM (SELECT medium FROM paintings UNION ALL SELECT medium FROM sculptures) GROUP BY medium;	semantic error	1	0
1245	How many works are there in each medium?	SELECT count(*) , medium FROM paintings GROUP BY medium	SELECT medium, COUNT(*) AS total_works FROM (SELECT medium FROM paintings UNION ALL SELECT medium FROM sculptures) GROUP BY medium	semantic error	1	0
1258	Find the id of the oldest painting.	SELECT paintingID FROM paintings ORDER BY YEAR LIMIT 1	SELECT paintingid FROM paintings WHERE year = (SELECT MIN(year) FROM paintings)	limit 1	1	0
1259	What is the id of the oldest painting?	SELECT paintingID FROM paintings ORDER BY YEAR LIMIT 1	SELECT paintingid FROM paintings WHERE year = (SELECT MIN(year) FROM paintings)	limit 1	1	0
1260	What are the first and last name of the artist who had a sculpture work whose title has the word "female" in it?	SELECT T1.lname , T1.fname FROM artists AS T1 JOIN sculptures AS T2 ON T1.artistID = T2.sculptorID WHERE T2.title LIKE "%female%"	SELECT fname, lname FROM artists WHERE artistid IN (SELECT sculptorid FROM sculptures WHERE title LIKE '%female%')	join -> in sub	0	1
1261	What is the full name of the artist with a sculpture whose title includes the word "female"?	SELECT T1.lname , T1.fname FROM artists AS T1 JOIN sculptures AS T2 ON T1.artistID = T2.sculptorID WHERE T2.title LIKE "%female%"	SELECT fname, lname FROM artists WHERE artistid IN (SELECT sculptorid FROM sculptures WHERE title LIKE '%female%')	join -> in sub	0	0
1262	List the names of all distinct paintings in alphabetical order.	SELECT DISTINCT title FROM paintings ORDER BY title	SELECT title FROM paintings ORDER BY title	redundant distinct	1	0
1263	What is the name of every distinct painting in alphabetical order?	SELECT DISTINCT title FROM paintings ORDER BY title	SELECT title FROM paintings ORDER BY title	redundant distinct	1	0

1264	List the names of all distinct paintings ordered by length.	SELECT DISTINCT title FROM paintings ORDER BY height_mm	SELECT title FROM paintings ORDER BY height_mm	redundant distinct	0	0
1265	List the names of all distinct paintings from shortest to longest in height.	SELECT DISTINCT title FROM paintings ORDER BY height_mm	SELECT title FROM paintings ORDER BY height_mm	redundant distinct	0	0
1266	What are the names of both paintings and sculptures created between 1900 and 1950?	SELECT title FROM paintings WHERE YEAR BETWEEN 1900 AND 1950 UNION SELECT title FROM sculptures WHERE YEAR BETWEEN 1900 AND 1950	SELECT title FROM paintings WHERE year BETWEEN 1900 AND 1950 UNION ALL SELECT title FROM sculptures WHERE year BETWEEN 1900 AND 1950	union non-key	0	1
1267	What are the names of paintings and sculptures created between 1900 and 1950?	SELECT title FROM paintings WHERE YEAR BETWEEN 1900 AND 1950 UNION SELECT title FROM sculptures WHERE YEAR BETWEEN 1900 AND 1950	SELECT title FROM (SELECT title, year FROM paintings UNION ALL SELECT title, year FROM sculptures) WHERE year BETWEEN 1900 AND 1950	union non-key	0	1
1268	Find the titles of paintings and sculpture works made by the artist whose id is 222?	SELECT T2.title FROM artists AS T1 JOIN paintings AS T2 ON T1.artistID = T2.painterID WHERE T1.artistID = 222 UNION SELECT T4.title FROM artists AS T3 JOIN sculptures AS T4 ON T3.artistID = T4.sculptorID WHERE T3.artistID = 222	SELECT p.title FROM paintings AS p WHERE p.painterid = 222 UNION ALL SELECT s.title FROM sculptures AS s WHERE s.sculptorid = 222	union non-key	0	1
1269	What are the titles of all paintings and sculpture works made by the artist whose id is 222?	SELECT T2.title FROM artists AS T1 JOIN paintings AS T2 ON T1.artistID = T2.painterID WHERE T1.artistID = 222 UNION SELECT T4.title FROM artists AS T3 JOIN sculptures AS T4 ON T3.artistID = T4.sculptorID WHERE T3.artistID = 222	SELECT title FROM paintings WHERE painterid = 222 UNION ALL SELECT title FROM sculptures WHERE sculptorid = 222	union non-key	0	1
1270	What is the id of the artist who has the highest number of painting works before 1900?	SELECT T1.artistID FROM artists AS T1 JOIN paintings AS T2 ON T1.artistID = T2.painterID WHERE T2.year < 1900 GROUP BY T1.artistID ORDER BY count(*) DESC LIMIT 1	SELECT a.artistid FROM artists a WHERE (SELECT COUNT(*) FROM paintings p WHERE p.painterid = a.artistid AND p.year < 1900) = (SELECT MAX(c.cnt) FROM (SELECT COUNT(*) AS cnt FROM paintings WHERE year < 1900 GROUP BY painterid) c);	limit 1	0	0
1271	What is the id of the artist with the most paintings before 1900?	SELECT T1.artistID FROM artists AS T1 JOIN paintings AS T2 ON T1.artistID = T2.painterID WHERE T2.year < 1900 GROUP BY T1.artistID ORDER BY count(*) DESC LIMIT 1	SELECT a.artistid FROM artists a WHERE (SELECT COUNT(*) FROM paintings p WHERE p.painterid = a.artistid AND p.year < 1900) = (SELECT MAX(c.cnt) FROM (SELECT COUNT(*) AS cnt FROM paintings WHERE year < 1900 GROUP BY painterid) c);	limit 1	0	0
1272	What is the first name of the artist who has the highest number of sculptures?	SELECT T1.fname FROM artists AS T1 JOIN sculptures AS T2 ON T1.artistID = T2.sculptorID GROUP BY T2.sculptorID ORDER BY count(*) DESC LIMIT 1	SELECT fname FROM artists WHERE artistid IN (SELECT sculptorid FROM sculptures GROUP BY sculptorid HAVING COUNT(*) = (SELECT MAX(cnt) FROM (SELECT sculptorid, COUNT(*) AS cnt FROM sculptures GROUP BY sculptorid)))	limit 1	0	1
1273	What is the first name of the sculptor with the greatest number of works?	SELECT T1.fname FROM artists AS T1 JOIN sculptures AS T2 ON T1.artistID = T2.sculptorID GROUP BY T2.sculptorID ORDER BY count(*) DESC LIMIT 1	SELECT fname FROM artists WHERE artistid IN (SELECT sculptorid FROM sculptures GROUP BY sculptorid HAVING COUNT(sculptorid) = (SELECT MAX(work_count) FROM (SELECT COUNT(*) AS work_count FROM sculptures GROUP BY sculptorid)))	limit 1	0	1
1286	What are the maximum height and id of paintings painted before 1900?	SELECT max(height_mm), paintingID FROM paintings WHERE YEAR < 1900	SELECT height_mm, paintingID FROM paintings WHERE YEAR < 1900 AND height_mm = (SELECT MAX(height_mm) FROM paintings WHERE YEAR < 1900)	limit 1	0	0
1287	What is the height and id of the tallest painting created before 1900?	SELECT max(height_mm), paintingID FROM paintings WHERE YEAR < 1900	SELECT height_mm, paintingID FROM paintings WHERE YEAR < 1900 AND height_mm = (SELECT MAX(height_mm) FROM paintings WHERE YEAR < 1900)	limit 1	0	0

1288	What are the maximum height and width of paintings for each year?	SELECT max(height_mm) , max(width_mm) , YEAR FROM paintings GROUP BY YEAR ORDER BY YEAR	SELECT max(height_mm) , max(width_mm) , YEAR FROM paintings GROUP BY YEAR	redundant order by	1	0
1289	What are largest height and width dimensions for paintings in each year?	SELECT max(height_mm) , max(width_mm) , YEAR FROM paintings GROUP BY YEAR ORDER BY YEAR	SELECT max(height_mm) , max(width_mm) , YEAR FROM paintings GROUP BY YEAR	redundant order by	1	0
1290	What are the average height and width of paintings grouped by painters and ordered by name?	SELECT avg(height_mm) , avg(width_mm) , painterID FROM paintings GROUP BY painterID ORDER BY title	SELECT artists.artistID, AVG(paintings.height_mm) AS AverageHeight, AVG(paintings.width_mm) AS AverageWidth FROM paintings INNER JOIN artists ON paintings.painterid = artists.artistid GROUP BY artists.artistid ORDER BY artists.lname, artists.fname	nlq vague; semantic error: order by col	0	0
1291	Find the average height and width of paintings grouped by painters and ordered by name	SELECT avg(height_mm) , avg(width_mm) , painterID FROM paintings GROUP BY painterID ORDER BY title	SELECT artists.artistID, AVG(paintings.height_mm) AS AverageHeight, AVG(paintings.width_mm) AS AverageWidth FROM paintings INNER JOIN artists ON paintings.painterid = artists.artistid GROUP BY artists.artistid ORDER BY artists.lname, artists.fname	nlq vague; semantic error: order by col	0	0
1294	Find the death year of all artists who have at most 3 paintings?	SELECT T1.deathYear FROM artists AS T1 JOIN paintings AS T2 ON T1.artistID = T2.painterID GROUP BY T2.painterID HAVING count(*) <= 3	SELECT A.deathyear FROM artists A WHERE 3 >= (SELECT COUNT(*) FROM paintings WHERE painterid = A.artistid)	join -> left join	0	1
1295	When did each artist who created less than 4 paintings die ?	select t1.deathyear from artists as t1 join paintings as t2 on t1.artistid = t2.painterid group by t2.painterid having count(*) < 4	SELECT deathyear FROM artists WHERE (SELECT COUNT(*) FROM paintings WHERE painterid = artistid) < 4	join -> left join	0	1
1296	Find the death year of the artist who made the least number of sculptures?	SELECT T1.deathYear FROM artists AS T1 JOIN sculptures AS T2 ON T1.artistID = T2.sculptorID GROUP BY T2.sculptorID ORDER BY count(*) LIMIT 1	WITH tmp as (SELECT A.deathYear, count(S.sculptureID) as cnt FROM Artists A LEFT JOIN Sculptures S on A.artistID = S.sculptorID GROUP BY A.artistID) SELECT tmp.deathYear FROM tmp WHERE cnt = (SELECT min(cnt) FROM tmp)	join -> left join; limit 1	0	0
1297	When did the artist who made the fewest sculptures die?	SELECT T1.deathYear FROM artists AS T1 JOIN sculptures AS T2 ON T1.artistID = T2.sculptorID GROUP BY T2.sculptorID ORDER BY count(*) LIMIT 1	WITH tmp as (SELECT A.deathYear, count(S.sculptureID) as cnt FROM Artists A LEFT JOIN Sculptures S on A.artistID = S.sculptorID GROUP BY A.artistID) SELECT tmp.deathYear FROM tmp WHERE cnt = (SELECT min(cnt) FROM tmp)	join -> left join; limit 1	0	0
1298	What are the id and height of the painting with the longest width in gallery 240?	SELECT paintingID , height_mm FROM paintings WHERE LOCATION = 'Gallery 240' ORDER BY width_mm DESC LIMIT 1	SELECT paintingid, height_mm FROM paintings WHERE location = 'Gallery 240' AND width_mm = (SELECT MAX(width_mm) FROM paintings WHERE location = 'Gallery 240')	limit 1	0	1
1299	Tell me the height and id number of the widest painting in gallery 240.	SELECT paintingID , height_mm FROM paintings WHERE LOCATION = 'Gallery 240' ORDER BY width_mm DESC LIMIT 1	SELECT paintingid, height_mm FROM paintings WHERE width_mm = (SELECT MAX(width_mm) FROM paintings WHERE location = 'Gallery 240') AND location = 'Gallery 240'	limit 1	0	1
1304	Find the top 3 artists who have the biggest number of painting works whose medium is oil?	SELECT T1.lname , T1.fname FROM artists AS T1 JOIN paintings AS T2 ON T1.artistID = T2.painterID WHERE T2.medium = "oil" GROUP BY T2.painterID ORDER BY count(*) DESC LIMIT 3	SELECT fname, lname FROM (SELECT a.fname, a.lname, rank() over (ORDER BY COUNT(p.paintingid) DESC) as rk FROM artists a JOIN paintings p ON a.artistid = p.painterid WHERE p.medium = 'oil' GROUP BY a.artistid) WHERE rk <= 3	limit n	0	0
1305	Which artists have the most paintings in oil?	SELECT T1.lname , T1.fname FROM artists AS T1 JOIN paintings AS T2 ON T1.artistID = T2.painterID WHERE T2.medium = "oil" GROUP BY T2.painterID ORDER BY count(*) DESC LIMIT 3	SELECT fname, lname FROM (SELECT a.fname, a.lname, rank() over (ORDER BY COUNT(p.paintingid) DESC) as rk FROM artists a JOIN paintings p ON a.artistid = p.painterid WHERE p.medium = 'oil' GROUP BY a.artistid) WHERE rk = 1	limit 1; semantic error	0	0

1310	Find the first and last name of artists who have painting but no sculpture work.	SELECT T1.lname , T1.fname FROM artists AS T1 JOIN paintings AS T2 ON T1.artistID = T2.painterID EXCEPT SELECT T3.lname , T3.fname FROM artists AS T3 JOIN sculptures AS T4 ON T3.artistID = T4.sculptorID	SELECT a.fname, a.lname FROM artists a WHERE a.artistid IN (SELECT p.painterid FROM paintings p) AND a.artistid NOT IN (SELECT s.sculptorid FROM sculptures s)	except non-key	0	0
1311	What are the first and last names of the artists who did not sculpt but could paint.	SELECT T1.lname , T1.fname FROM artists AS T1 JOIN paintings AS T2 ON T1.artistID = T2.painterID EXCEPT SELECT T3.lname , T3.fname FROM artists AS T3 JOIN sculptures AS T4 ON T3.artistID = T4.sculptorID	SELECT a.fname, a.lname FROM artists a WHERE a.artistid IN (SELECT p.painterid FROM paintings p) AND a.artistid NOT IN (SELECT s.sculptorid FROM sculptures s)	except non-key	0	1
1312	Find the locations that have paintings before 1885 and no work with medium on canvas?	SELECT DISTINCT LOCATION FROM paintings WHERE YEAR < 1885 AND mediumOn != "canvas"	SELECT p.location FROM paintings p WHERE p.year < 1885 EXCEPT SELECT p.location FROM paintings p WHERE p.mediumon = 'canvas'	semantic error: filter condition	0	1
1320	Who are the constructors of drivers sorted by drivers' age in ascending order?	SELECT DISTINCT CONSTRUCTOR FROM driver ORDER BY Age ASC	SELECT CONSTRUCTOR FROM driver ORDER BY Age ASC	redundant distinct	0	0
1332	Please show the names of drivers and the number of races they participate in.	SELECT T1.Driver_Name , COUNT(*) FROM driver AS T1 JOIN race AS T2 ON T1.Driver_ID = T2.Driver_ID GROUP BY T1.Driver_ID	SELECT D.driver_name, (SELECT COUNT(*) FROM race R WHERE R.driver_id = D.driver_id) AS races_participated FROM driver D	join -> left join	0	1
1333	How many races did each driver participate in?	SELECT T1.Driver_Name , COUNT(*) FROM driver AS T1 JOIN race AS T2 ON T1.Driver_ID = T2.Driver_ID GROUP BY T1.Driver_ID	SELECT D.driver_name, (SELECT COUNT(*) FROM race R WHERE R.driver_id = D.driver_id) AS races_participated FROM driver D	join -> left join	0	0
1334	Please show the age of the driver who participated in the most number of races.	SELECT T1.Age FROM driver AS T1 JOIN race AS T2 ON T1.Driver_ID = T2.Driver_ID GROUP BY T1.Driver_ID ORDER BY COUNT(*) DESC LIMIT 1	SELECT age FROM driver d WHERE driver_id IN (SELECT driver_id FROM race GROUP BY driver_id HAVING COUNT(*) = (SELECT MAX(x.total) FROM (SELECT driver_id, COUNT(*) as total FROM race GROUP BY driver_id) x))	limit 1	0	0
1335	What is the age of the driver who raced in the most races?	SELECT T1.Age FROM driver AS T1 JOIN race AS T2 ON T1.Driver_ID = T2.Driver_ID GROUP BY T1.Driver_ID ORDER BY COUNT(*) DESC LIMIT 1	SELECT age FROM driver d WHERE driver_id IN (SELECT driver_id FROM race GROUP BY driver_id HAVING COUNT(*) = (SELECT MAX(x.total) FROM (SELECT driver_id, COUNT(*) as total FROM race GROUP BY driver_id) x))	limit 1	0	0
1344	List the most common type of engine used by drivers.	SELECT Engine FROM driver GROUP BY Engine ORDER BY COUNT(*) DESC LIMIT 1	SELECT engine FROM driver GROUP BY engine HAVING COUNT(engine) = (SELECT MAX(counts) FROM (SELECT COUNT(engine) AS counts FROM driver GROUP BY engine))	limit 1	0	1
1345	What is the most common type of engine?	SELECT Engine FROM driver GROUP BY Engine ORDER BY COUNT(*) DESC LIMIT 1	SELECT engine FROM driver GROUP BY engine HAVING COUNT(engine) = (SELECT MAX(count) FROM (SELECT engine, COUNT(*) as count FROM driver GROUP BY engine))	limit 1	0	1
1354	Find the names of drivers who were in both "James Hinchcliffe" and "Carl Skerlong" pole positions before.	SELECT T1.Driver_Name FROM driver AS T1 JOIN race AS T2 ON T1.Driver_ID = T2.Driver_ID WHERE Pole_Position = "Carl Skerlong" INTERSECT SELECT T1.Driver_Name FROM driver AS T1 JOIN race AS T2 ON T1.Driver_ID = T2.Driver_ID WHERE Pole_Position = "James Hinchcliffe"	SELECT driver_name FROM driver WHERE driver_id IN (SELECT driver_id FROM race WHERE pole_position = 'Carl Skerlong' INTERSECT SELECT driver_id FROM race WHERE pole_position = 'James Hinchcliffe');	intersect non-key	1	0
1355	What are the names of drivers who had both the pole position James Hinchcliffe and the pole position Carl Skerlong?	SELECT T1.Driver_Name FROM driver AS T1 JOIN race AS T2 ON T1.Driver_ID = T2.Driver_ID WHERE Pole_Position = "Carl Skerlong" INTERSECT SELECT T1.Driver_Name FROM driver AS T1 JOIN race AS T2 ON T1.Driver_ID = T2.Driver_ID WHERE Pole_Position = "James Hinchcliffe"	SELECT driver_name FROM driver WHERE driver_id IN (SELECT driver_id FROM race WHERE pole_position IN ('James Hinchcliffe', 'Carl Skerlong')) GROUP BY driver_id HAVING COUNT(DISTINCT pole_position) = 2;	intersect non-key	0	0

1356	find the name of drivers who were never in "James Hinchcliffe" pole position before.	SELECT Driver_Name FROM driver EXCEPT SELECT T1.Driver_Name FROM driver AS T1 JOIN race AS T2 ON T1.Driver_ID = T2.Driver_ID WHERE Pole_Position = "James Hinchcliffe"	SELECT driver_name FROM driver WHERE driver_id NOT IN (SELECT driver_id FROM race WHERE pole_position = 'James Hinch- cliffe')	except non-key	0	1
1357	What are the names of drivers except for those who had the pole position James Hinchcliffe?	SELECT Driver_Name FROM driver EXCEPT SELECT T1.Driver_Name FROM driver AS T1 JOIN race AS T2 ON T1.Driver_ID = T2.Driver_ID WHERE Pole_Position = "James Hinchcliffe"	SELECT driver_name FROM driver WHERE driver_id NOT IN (SELECT driver_id FROM race WHERE pole_position = 'James Hinch- cliffe')	except non-key	0	1
1374	List the name of the country with the biggest score in politics.	SELECT name FROM countries ORDER BY politics_score DESC LIMIT 1	SELECT countries.name FROM coun- tries WHERE politics_score = (SELECT MAX(politics_score) FROM countries)	limit 1	0	1
1375	What is the name of the country with the highest politics score?	SELECT name FROM countries ORDER BY politics_score DESC LIMIT 1	SELECT name FROM countries WHERE polit- ics_score = (SELECT MAX(politics_score) FROM countries)	limit 1	0	1
1378	Show the official languages and the number of countries speaking each language.	SELECT T2.name , COUNT(*) FROM offi- cial_languages AS T1 JOIN languages AS T2 ON T1.language_id = T2.id GROUP BY T2.name	SELECT language.name, (SELECT COUNT(*) FROM official_languages WHERE lan- guage_id = language.id) AS CountriesCount FROM languages AS language	group by non-key; join -> left join	0	1
1379	What are the names of the different official languages, as well as the number of countries that speak each?	SELECT T2.name , COUNT(*) FROM offi- cial_languages AS T1 JOIN languages AS T2 ON T1.language_id = T2.id GROUP BY T2.name	SELECT L.name, (SELECT COUNT(distinct O.country_id) FROM official_languages O WHERE L.id = O.language_id) AS num_countries FROM languages L	group by non-key; join -> left join	0	1
1380	Show the official language spoken by the most number of countries.	SELECT T2.name FROM official_languages AS T1 JOIN languages AS T2 ON T1.language_id = T2.id GROUP BY T2.id ORDER BY COUNT(*) DESC LIMIT 1	SELECT name FROM languages WHERE id IN (SELECT language_id FROM offi- cial_languages GROUP BY language_id HAVING COUNT(language_id) = (SELECT MAX(cnt) FROM (SELECT COUNT(language_id) AS cnt FROM offi- cial_languages GROUP BY language_id)))	limit 1	1	0
1381	What is the official language that is most common?	SELECT T2.name FROM official_languages AS T1 JOIN languages AS T2 ON T1.language_id = T2.id GROUP BY T2.id ORDER BY COUNT(*) DESC LIMIT 1	SELECT name FROM languages WHERE id IN (SELECT language_id FROM offi- cial_languages GROUP BY language_id HAVING COUNT(language_id) = (SELECT MAX(cnt) FROM (SELECT COUNT(language_id) AS cnt FROM offi- cial_languages GROUP BY language_id)))	limit 1	0	1
1384	Show the average overall scores of countries whose official language is "English".	SELECT avg(T1.overall_score) FROM coun- tries AS T1 JOIN official_languages AS T2 ON T1.id = T2.country_id JOIN languages AS T3 ON T2.language_id = T3.id WHERE T3.name = "English"	SELECT AVG(ov_score) FROM (SELECT overall_score AS ov_score FROM countries WHERE id IN (SELECT country_id FROM of- ficial_languages WHERE language_id IN (SE- LECT id FROM languages WHERE name = 'English')))	join -> in sub	0	1
1385	What is the average overall score across countries with English as their official language?	SELECT avg(T1.overall_score) FROM coun- tries AS T1 JOIN official_languages AS T2 ON T1.id = T2.country_id JOIN languages AS T3 ON T2.language_id = T3.id WHERE T3.name = "English"	SELECT AVG(ovsc) FROM (SELECT over- all_score AS ovsc FROM countries WHERE id IN (SELECT country_id FROM offi- cial_languages JOIN languages ON offi- cial_languages.language_id = languages.id WHERE languages.name = 'English'))	join -> in sub	0	1
1386	Show the three official languages that are most commonly spoken.	SELECT T2.name FROM official_languages AS T1 JOIN languages AS T2 ON T1.language_id = T2.id GROUP BY T2.id ORDER BY COUNT(*) DESC LIMIT 3	WITH RankedLanguages AS (SELECT language_id, RANK() OVER (ORDER BY COUNT(DISTINCT country_id) DESC) as rank FROM official_languages GROUP BY language_id) SELECT name FROM languages WHERE id IN (SELECT language_id FROM RankedLanguages WHERE rank <= 3)	limit n	1	0

1387	What are the names of the three official languages spoken in the most countries?	SELECT T2.name FROM official_languages AS T1 JOIN languages AS T2 ON T1.language_id = T2.id GROUP BY T2.id ORDER BY COUNT(*) DESC LIMIT 3	WITH RankedLanguages AS (SELECT language_id, RANK() OVER (ORDER BY COUNT(DISTINCT country_id) DESC) as rank FROM official_languages GROUP BY language_id) SELECT name FROM languages WHERE id IN (SELECT language_id FROM RankedLanguages WHERE rank <= 3)	limit n	1	0
1390	Show the name of the country that has the greatest number of official languages.	SELECT T1.Name FROM countries AS T1 JOIN official_languages AS T2 ON T1.id = T2.country_id GROUP BY T1.id ORDER BY COUNT(*) DESC LIMIT 1	SELECT name FROM countries WHERE id IN (SELECT ol.country_id FROM official_languages ol GROUP BY ol.country_id HAVING COUNT(ol.language_id) = (SELECT MAX(lang_count) FROM (SELECT COUNT(language_id) AS lang_count FROM official_languages GROUP BY country_id)))	limit 1	0	0
1391	Which country has the greatest number of official languages?	SELECT T1.Name FROM countries AS T1 JOIN official_languages AS T2 ON T1.id = T2.country_id GROUP BY T1.id ORDER BY COUNT(*) DESC LIMIT 1	SELECT name FROM countries WHERE id IN (SELECT ol.country_id FROM official_languages ol GROUP BY ol.country_id HAVING COUNT(ol.language_id) = (SELECT MAX(lang_count) FROM (SELECT COUNT(language_id) AS lang_count FROM official_languages GROUP BY country_id)))	limit 1	0	0
1396	Show the names of languages that are the official language for both countries with overall score greater than 95 and countries with overall score less than 90.	SELECT T3.name FROM countries AS T1 JOIN official_languages AS T2 ON T1.id = T2.country_id JOIN languages AS T3 ON T2.language_id = T3.id WHERE T1.overall_score > 95 INTERSECT SELECT T3.name FROM countries AS T1 JOIN official_languages AS T2 ON T1.id = T2.country_id JOIN languages AS T3 ON T2.language_id = T3.id WHERE T1.overall_score < 90	SELECT name FROM languages WHERE id IN (SELECT ol.language_id FROM official_languages ol JOIN countries c ON ol.country_id = c.id WHERE c.overall_score > 95) AND id IN (SELECT ol.language_id FROM official_languages ol JOIN countries c ON ol.country_id = c.id WHERE c.overall_score < 90);	intersect non-key	0	1
1397	What are the names of languages that are the official language not only for countries that have an overall score of above 95, but also for countries that have an overall score below 90?	SELECT T3.name FROM countries AS T1 JOIN official_languages AS T2 ON T1.id = T2.country_id JOIN languages AS T3 ON T2.language_id = T3.id WHERE T1.overall_score > 95 INTERSECT SELECT T3.name FROM countries AS T1 JOIN official_languages AS T2 ON T1.id = T2.country_id JOIN languages AS T3 ON T2.language_id = T3.id WHERE T1.overall_score < 90	SELECT languages.name FROM languages WHERE languages.id IN (SELECT ol.language_id FROM official_languages ol JOIN countries c ON ol.country_id = c.id GROUP BY ol.language_id HAVING MAX(c.overall_score) > 95 AND MIN(c.overall_score) < 90)	intersect non-key	0	0
1398	Which countries and cities are included in addresses?	SELECT country, town_city FROM Addresses;	SELECT DISTINCT country, town_city FROM addresses	lack distinct	0	1
1400	In which states are each of the the properties located?	SELECT DISTINCT T1.county_state_province FROM Addresses AS T1 JOIN Properties AS T2 ON T1.address_id = T2.property_address_id;	SELECT T1.county_state_province FROM Addresses AS T1 JOIN Properties AS T2 ON T1.address_id = T2.property_address_id;	redundant distinct	1	0
1401	Give the states or provinces corresponding to each property.	SELECT DISTINCT T1.county_state_province FROM Addresses AS T1 JOIN Properties AS T2 ON T1.address_id = T2.property_address_id;	SELECT T1.county_state_province FROM Addresses AS T1 JOIN Properties AS T2 ON T1.address_id = T2.property_address_id;	redundant distinct	0	0
1404	What are the feature name and description of the most commonly seen feature across properties?	SELECT T1.feature_name, T1.feature_description FROM Features AS T1 JOIN Property_Features AS T2 ON T1.feature_id = T2.feature_id GROUP BY T1.feature_name ORDER BY count(*) DESC LIMIT 1;	SELECT f.feature_name, f.feature_description FROM features f JOIN property_features pf ON f.feature_id = pf.feature_id GROUP BY f.feature_id HAVING COUNT(pf.property_id) = (SELECT MAX(Cnt) FROM (SELECT COUNT(property_id) AS Cnt FROM property_features GROUP BY feature_id))	limit 1	0	0

1405	Give the feature name and description for the most common feature across all properties.	SELECT T1.feature_name, T1.feature_description FROM Features AS T1 JOIN Property_Features AS T2 ON T1.feature_id = T2.feature_id GROUP BY T1.feature_name ORDER BY count(*) DESC LIMIT 1;	SELECT f.feature_name, f.feature_description FROM features f JOIN property_features pf ON f.feature_id = pf.feature_id GROUP BY f.feature_id HAVING COUNT(pf.property_id) = (SELECT MAX(Cnt) FROM (SELECT COUNT(property_id) AS Cnt FROM property_features GROUP BY feature_id))	limit 1	0	1
1412	What is the first name of the user who owns the greatest number of properties?	SELECT T1.first_name FROM Users AS T1 JOIN Properties AS T2 ON T2.owner_user_id = T1.User_id GROUP BY T1.User_id ORDER BY count(*) DESC LIMIT 1;	SELECT U.first_name FROM users U WHERE EXISTS (SELECT 1 FROM properties P WHERE P.owner_user_id = U.user_id GROUP BY P.owner_user_id HAVING COUNT(P.property_id) = (SELECT MAX(Cnt) FROM (SELECT COUNT(property_id) AS Cnt FROM properties GROUP BY owner_user_id)))	limit 1	0	1
1413	Return the first name of the user who owns the most properties.	SELECT T1.first_name FROM Users AS T1 JOIN Properties AS T2 ON T2.owner_user_id = T1.User_id GROUP BY T1.User_id ORDER BY count(*) DESC LIMIT 1;	SELECT U.first_name FROM users U WHERE EXISTS (SELECT 1 FROM properties P WHERE P.owner_user_id = U.user_id GROUP BY P.owner_user_id HAVING COUNT(P.property_id) = (SELECT MAX(Cnt) FROM (SELECT COUNT(property_id) AS Cnt FROM properties GROUP BY owner_user_id)))	limit 1	0	0
1414	List the average room count of the properties with gardens.	SELECT avg(T3.room_count) FROM Property_Features AS T1 JOIN Features AS T2 ON T1.feature_id = T2.feature_id JOIN Properties AS T3 ON T1.property_id = T3.property_id WHERE T2.feature_name = 'garden';	SELECT AVG(room_count) FROM properties WHERE EXISTS (SELECT 1 FROM property_features JOIN features ON property_features.feature_id = features.feature_id WHERE features.feature_name = 'garden' AND properties.property_id = property_features.property_id)	join -> in sub	0	1
1415	On average, how many rooms do properties with garden features have?	SELECT avg(T3.room_count) FROM Property_Features AS T1 JOIN Features AS T2 ON T1.feature_id = T2.feature_id JOIN Properties AS T3 ON T1.property_id = T3.property_id WHERE T2.feature_name = 'garden';	SELECT AVG(room_count) AS avg_rooms FROM properties WHERE property_id IN (SELECT properties.property_id FROM properties JOIN property_features ON properties.property_id = property_features.property_id JOIN features ON property_features.feature_id = features.feature_id WHERE features.feature_name = 'garden')	join -> in sub	0	1
1416	In which cities are there any properties equipped with a swimming pool?	SELECT T2.town_city FROM Properties AS T1 JOIN Addresses AS T2 ON T1.property_address_id = T2.address_id JOIN Property_Features AS T3 ON T1.property_id = T3.property_id JOIN Features AS T4 ON T4.feature_id = T3.feature_id WHERE T4.feature_name = 'swimming pool';	SELECT DISTINCT t.town_city FROM addresses t JOIN properties p ON t.address_id = p.property_address_id JOIN property_features pf ON p.property_id = pf.property_id JOIN features f ON pf.feature_id = f.feature_id WHERE f.feature_name = 'swimming pool'	lack distinct	0	1
1417	Return the cities in which there exist properties that have swimming pools.	SELECT T2.town_city FROM Properties AS T1 JOIN Addresses AS T2 ON T1.property_address_id = T2.address_id JOIN Property_Features AS T3 ON T1.property_id = T3.property_id JOIN Features AS T4 ON T4.feature_id = T3.feature_id WHERE T4.feature_name = 'swimming pool';	SELECT DISTINCT t.town_city FROM addresses t JOIN properties p ON t.address_id = p.property_address_id JOIN property_features pf ON p.property_id = pf.property_id JOIN features f ON pf.feature_id = f.feature_id WHERE f.feature_name = 'swimming pool'	lack distinct	0	0
1418	Which property had the lowest price requested by the vendor? List the id and the price.	SELECT property_id, vendor_requested_price FROM Properties ORDER BY vendor_requested_price LIMIT 1;	SELECT property_id, vendor_requested_price FROM properties WHERE vendor_requested_price = (SELECT MIN(vendor_requested_price) FROM properties)	limit 1	0	1
1419	What is the id of the property that had the lowest requested price from the vendor, and what was that price?	SELECT property_id, vendor_requested_price FROM Properties ORDER BY vendor_requested_price LIMIT 1;	SELECT property_id, vendor_requested_price FROM properties WHERE vendor_requested_price = (SELECT MIN(vendor_requested_price) FROM properties)	limit 1	0	1

1424	What are the ids of users who have searched at least twice, and what did they search?	SELECT search_seq , user_id FROM User_Searches GROUP BY user_id HAVING count(*) >= 2;	SELECT u.user_id, us.search_string FROM user_searches us INNER JOIN users u ON us.user_id = u.user_id WHERE u.user_id IN (SELECT user_id FROM user_searches GROUP BY user_id HAVING COUNT(search_seq) >= 2)	semantic error	0	1
1425	Return the ids of users who have performed two or more searches, as well as their search sequence.	SELECT search_seq , user_id FROM User_Searches GROUP BY user_id HAVING count(*) >= 2;	SELECT DISTINCT us.user_id, us.search_seq FROM user_searches us INNER JOIN (SELECT user_id FROM user_searches GROUP BY user_id HAVING COUNT(search_seq) >= 2) t ON us.user_id = t.user_id	semantic error	0	1
1434	What is the age range category of the user who made the first search?	SELECT T1.age_category_code FROM Users AS T1 JOIN User_Searches AS T2 ON T1.user_id = T2.user_id ORDER BY T2.search_datetime LIMIT 1;	SELECT age_category_code FROM Users WHERE user_id IN (SELECT user_id FROM User_Searches WHERE search_datetime = (SELECT min(search_datetime) FROM User_Searches))	limit 1	0	0
1435	Return the age category for the user who made the earliest search.	SELECT T1.age_category_code FROM Users AS T1 JOIN User_Searches AS T2 ON T1.user_id = T2.user_id ORDER BY T2.search_datetime LIMIT 1;	SELECT age_category_code FROM Users WHERE user_id IN (SELECT user_id FROM User_Searches WHERE search_datetime = (SELECT min(search_datetime) FROM User_Searches))	limit 1	0	0
1446	How many properties are there with at least 2 features?	SELECT count(*) FROM Properties GROUP BY property_id HAVING count(*) >= 2;	SELECT COUNT(DISTINCT properties.property_id) FROM properties JOIN property_features ON properties.property_id = property_features.property_id GROUP BY properties.property_id HAVING COUNT(property_features.feature_id) >= 2	semantic error: wrong table	0	1
1447	Count the number of properties with at least two features.	SELECT count(*) FROM Properties GROUP BY property_id HAVING count(*) >= 2;	SELECT COUNT(DISTINCT pf.property_id) FROM property_features pf GROUP BY pf.property_id HAVING COUNT(pf.feature_id) >= 2	semantic error: wrong table	0	1
1448	How many photos does each property have?	SELECT count(*) , property_id FROM Property_Photos GROUP BY property_id;	SELECT p.property_id, IFNULL(COUNT(pp.photo_seq), 0) FROM properties p LEFT JOIN property_photos pp ON p.property_id = pp.property_id GROUP BY p.property_id	join -> left join	0	1
1449	Count the number of property photos each property has by id.	SELECT count(*) , property_id FROM Property_Photos GROUP BY property_id;	SELECT properties.property_id, COUNT(property_photos.photo_seq) AS photo_count FROM properties LEFT JOIN property_photos ON properties.property_id = property_photos.property_id GROUP BY properties.property_id	join -> left join	0	1
1450	How many photos does each owner has of his or her properties? List user id and number of photos.	SELECT T1.owner_user_id , count(*) FROM Properties AS T1 JOIN Property_Photos AS T2 ON T1.property_id = T2.property_id GROUP BY T1.owner_user_id;	SELECT owner_user_id AS user_id, COUNT(photo_seq) AS photo_count FROM properties LEFT JOIN property_photos ON properties.property_id = property_photos.property_id GROUP BY owner_user_id	join -> left join	0	1
1456	What is the description of the most common property type? List the description and code.	SELECT T1.property_type_description , T1.property_type_code FROM Ref_Property_Types AS T1 JOIN Properties AS T2 ON T1.property_type_code = T2.property_type_code GROUP BY T1.property_type_code ORDER BY count(*) DESC LIMIT 1;	SELECT property_type_description, property_type_code FROM (SELECT T1.property_type_description, T1.property_type_code, rank() over (ORDER BY count(*) DESC) as rk FROM Ref_Property_Types AS T1 JOIN Properties AS T2 ON T1.property_type_code = T2.property_type_code GROUP BY T1.property_type_code) WHERE rk = 1	limit 1	0	0
1457	What is the most common property type, and what is its description.	SELECT T1.property_type_description , T1.property_type_code FROM Ref_Property_Types AS T1 JOIN Properties AS T2 ON T1.property_type_code = T2.property_type_code GROUP BY T1.property_type_code ORDER BY count(*) DESC LIMIT 1;	SELECT property_type_description, property_type_code FROM (SELECT T1.property_type_description, T1.property_type_code, rank() over (ORDER BY count(*) DESC) as rk FROM Ref_Property_Types AS T1 JOIN Properties AS T2 ON T1.property_type_code = T2.property_type_code GROUP BY T1.property_type_code) WHERE rk = 1	limit 1	1	0

1464	What are the first, middle and last names of users who own the property they live in?	SELECT first_name , middle_name , last_name FROM Properties AS T1 JOIN Users AS T2 ON T1.owner_user_id = T2.user_id WHERE T1.property_address_id = T2.user_address_id;	SELECT first_name,middle_name,last_name FROM users WHERE user_id IN (SELECT owner_user_id FROM properties WHERE property_address_id IN (SELECT address_id FROM addresses WHERE address_id = user_address_id))	join -> in sub	0	1
1465	Return the full names of users who live in properties that they own.	SELECT first_name , middle_name , last_name FROM Properties AS T1 JOIN Users AS T2 ON T1.owner_user_id = T2.user_id WHERE T1.property_address_id = T2.user_address_id;	SELECT first_name,middle_name,last_name FROM users WHERE EXISTS (SELECT 1 FROM properties WHERE property_address_id = user_address_id)	join -> in sub	0	0
1466	List the search content of the users who do not own a single property.	SELECT search_string FROM User_Searches EXCEPT SELECT T1.search_string FROM User_Searches AS T1 JOIN Properties AS T2 ON T1.user_id = T2.owner_user_id;	SELECT us.search_string FROM user_searches us WHERE us.user_id NOT IN (SELECT properties.owner_user_id FROM properties)	except non-key	1	0
1467	What search strings were entered by users who do not own any properties?	SELECT search_string FROM User_Searches EXCEPT SELECT T1.search_string FROM User_Searches AS T1 JOIN Properties AS T2 ON T1.user_id = T2.owner_user_id;	SELECT us.search_string FROM user_searches us WHERE us.user_id NOT IN (SELECT properties.owner_user_id FROM properties)	except non-key	0	0
1468	List the last names and ids of users who have at least 2 properties and searched at most twice.	SELECT T1.last_name , T1.user_id FROM Users AS T1 JOIN User_Searches AS T2 ON T1.user_id = T2.user_id GROUP BY T1.user_id HAVING count(*) <= 2 INTERSECT SELECT T3.last_name , T3.user_id FROM Users AS T3 JOIN Properties AS T4 ON T3.user_id = T4.owner_user_id GROUP BY T3.user_id HAVING count(*) >= 2;	SELECT u.user_id, u.last_name FROM users u WHERE (SELECT COUNT(*) FROM properties p WHERE p.owner_user_id = u.user_id) >= 2 AND (SELECT COUNT(*) FROM user_searches s WHERE s.user_id = u.user_id) <= 2	join -> left join	0	1
1469	What are the last names and ids of users who have searched two or fewer times, and own two or more properties?	SELECT T1.last_name , T1.user_id FROM Users AS T1 JOIN User_Searches AS T2 ON T1.user_id = T2.user_id GROUP BY T1.user_id HAVING count(*) <= 2 INTERSECT SELECT T3.last_name , T3.user_id FROM Users AS T3 JOIN Properties AS T4 ON T3.user_id = T4.owner_user_id GROUP BY T3.user_id HAVING count(*) >= 2;	SELECT u.user_id, u.last_name FROM users u WHERE (SELECT COUNT(*) FROM properties p WHERE p.owner_user_id = u.user_id) >= 2 AND (SELECT COUNT(*) FROM user_searches s WHERE s.user_id = u.user_id) <= 2	join -> left join	1	0
1478	What are the id and name of the cyclist who owns the most bikes?	SELECT T1.id , T1.name FROM cyclist AS T1 JOIN cyclists_own_bikes AS T2 ON T1.id = T2.cyclist_id GROUP BY T1.id ORDER BY count(*) DESC LIMIT 1	SELECT c.id, c.name FROM cyclist c JOIN cyclists_own_bikes cb ON c.id = cb.cyclist_id GROUP BY c.id HAVING COUNT(cb.bike_id) = (SELECT MAX(bike_count) FROM (SELECT COUNT(bike_id) AS bike_count FROM cyclists_own_bikes GROUP BY cyclist_id));	limit 1	0	1
1482	What are the names of distinct racing bikes that are purchased by the cyclists with better results than '4:21.558' ?	SELECT DISTINCT T3.product_name FROM cyclist AS T1 JOIN cyclists_own_bikes AS T2 ON T1.id = T2.cyclist_id JOIN bike AS T3 ON T2.bike_id = T3.id WHERE T1.result < '4:21.558'	SELECT T1.product_name FROM bike AS T1 WHERE T1.id IN (SELECT T3.bike_id FROM cyclist AS T2 JOIN cyclists_own_bikes AS T3 ON T2.id = T3.cyclist_id WHERE T2.result < '4:21.558')	join -> in sub	1	0
1483	List the name and price of the bike that is owned by both the cyclists named 'Bradley Wiggins' and the cyclist named 'Antonio Tauler'.	SELECT T3.product_name , T3.price FROM cyclist AS T1 JOIN cyclists_own_bikes AS T2 ON T1.id = T2.cyclist_id JOIN bike AS T3 ON T2.bike_id = T3.id WHERE T1.name = 'Bradley Wiggins' INTERSECT SELECT T3.product_name , T3.price FROM cyclist AS T1 JOIN cyclists_own_bikes AS T2 ON T1.id = T2.cyclist_id JOIN bike AS T3 ON T2.bike_id = T3.id WHERE T1.name = 'Antonio Tauler'	SELECT bike.product_name, bike.price FROM bike JOIN cyclists_own_bikes ON bike.id = cyclists_own_bikes.bike_id JOIN cyclist ON cyclists_own_bikes.cyclist_id = cyclist.id WHERE cyclist.name IN ('Bradley Wiggins', 'Antonio Tauler') GROUP BY bike.id HAVING COUNT(DISTINCT cyclist.name) = 2	intersect non-key	0	0
1484	Show the name, nation and result for the cyclists who did not purchase any racing bike.	SELECT name , nation , RESULT FROM cyclist EXCEPT SELECT T1.name , T1.nation , T1.result FROM cyclist AS T1 JOIN cyclists_own_bikes AS T2 ON T1.id = T2.cyclist_id	SELECT name,nation, RESULT FROM cyclist WHERE id NOT IN (SELECT cyclist_id FROM cyclists_own_bikes)	intersect non-key	1	0

1486	How many bikes does each cyclist own? Order by cyclist id.	SELECT cyclist_id , count(*) FROM cyclists_own_bikes GROUP BY cyclist_id ORDER BY cyclist_id	SELECT cy.id, COUNT(distinct cb.bike_id) FROM cyclist cy LEFT JOIN cyclists_own_bikes cb ON cy.id = cb.cyclist_id GROUP BY cy.id ORDER BY cy.id	join -> left join	0	1
1487	What is the most expensive cake and its flavor?	SELECT id , flavor FROM goods WHERE food = "Cake" ORDER BY price DESC LIMIT 1	SELECT goods.id, goods.flavor FROM goods WHERE goods.food = 'cake' AND goods.price = (SELECT MAX(price) FROM goods WHERE food = 'cake')	limit 1; str	0	0
1488	Give the id and flavor of the most expensive cake.	SELECT id , flavor FROM goods WHERE food = "Cake" ORDER BY price DESC LIMIT 1	SELECT goods.id, goods.flavor FROM goods WHERE goods.food = 'cake' AND goods.price = (SELECT MAX(price) FROM goods WHERE food = 'cake')	limit 1; str	1	0
1489	What is the cheapest cookie and its flavor?	SELECT id , flavor FROM goods WHERE food = "Cookie" ORDER BY price LIMIT 1	SELECT goods.id, goods.flavor FROM goods WHERE goods.food = 'cookie' AND price = (SELECT MIN(price) FROM goods WHERE food = 'cookie')	limit 1; str	0	0
1490	What is the id and flavor of the cheapest cookie?	SELECT id , flavor FROM goods WHERE food = "Cookie" ORDER BY price LIMIT 1	SELECT goods.id, goods.flavor FROM goods WHERE goods.food = 'cookie' AND price = (SELECT MIN(price) FROM goods WHERE food = 'cookie')	limit 1; str	1	0
1491	Find the ids of goods that have apple flavor.	SELECT id FROM goods WHERE flavor = "Apple"	SELECT id FROM goods WHERE flavor = 'apple'	str	1	0
1492	What are the ids with apple flavor?	SELECT id FROM goods WHERE flavor = "Apple"	SELECT id FROM goods WHERE flavor = 'apple'	str	1	0
1495	List the distinct ids of all customers who bought a cake with lemon flavor?	SELECT DISTINCT T3.CustomerId FROM goods AS T1 JOIN items AS T2 ON T1.Id = T2.Item JOIN receipts AS T3 ON T2.Receipt = T3.ReceiptNumber WHERE T1.Flavor = "Lemon" AND T1.Food = "Cake"	SELECT DISTINCT customers.id FROM customers JOIN receipts ON customers.id = receipts.customerid JOIN items ON receipts.receiptnumber = items.receipt JOIN goods ON items.item = goods.id WHERE goods.food = 'cake' AND goods.flavor = 'lemon'	str	1	0
1496	What are the distinct ids of customers who bought lemon flavored cake?	SELECT DISTINCT T3.CustomerId FROM goods AS T1 JOIN items AS T2 ON T1.Id = T2.Item JOIN receipts AS T3 ON T2.Receipt = T3.ReceiptNumber WHERE T1.Flavor = "Lemon" AND T1.Food = "Cake"	SELECT DISTINCT customers.id FROM customers JOIN receipts ON customers.id = receipts.customerid JOIN items ON receipts.receiptnumber = items.receipt JOIN goods ON items.item = goods.id WHERE goods.food = 'cake' AND goods.flavor = 'lemon'	str	1	0
1497	For each type of food, tell me how many customers have ever bought it.	SELECT T1.food , count(DISTINCT T3.CustomerId) FROM goods AS T1 JOIN items AS T2 ON T1.Id = T2.Item JOIN receipts AS T3 ON T2.Receipt = T3.ReceiptNumber GROUP BY T1.food	SELECT g.Food, COUNT(DISTINCT r.CustomerId) FROM goods g LEFT JOIN items i ON g.Id = i.Item JOIN receipts r ON i.Receipt = r.ReceiptNumber GROUP BY g.Food	join -> left join	1	0
1498	How many customers have bought each food?	SELECT T1.food , count(DISTINCT T3.CustomerId) FROM goods AS T1 JOIN items AS T2 ON T1.Id = T2.Item JOIN receipts AS T3 ON T2.Receipt = T3.ReceiptNumber GROUP BY T1.food	SELECT g.Food, COUNT(DISTINCT r.CustomerId) FROM goods g LEFT JOIN items i ON g.Id = i.Item JOIN receipts r ON i.Receipt = r.ReceiptNumber GROUP BY g.Food	join -> left join	1	0
1504	Count the number of types of cake this bakery sells.	SELECT count(*) FROM goods WHERE food = "Cake"	SELECT COUNT(DISTINCT id) FROM goods WHERE food = 'cake'	str	1	0
1506	What are all the flavors of croissant?	SELECT flavor FROM goods WHERE food = "Croissant"	SELECT flavor FROM goods WHERE food = "croissant"	str	0	0
1512	What are the receipt numbers for instances where both cakes and cookies were purchased?	SELECT T1.receipt FROM items AS T1 JOIN goods AS T2 ON T1.item = T2.id WHERE T2.food = "Cake" INTERSECT SELECT T1.receipt FROM items AS T1 JOIN goods AS T2 ON T1.item = T2.id WHERE T2.food = "Cookie"	SELECT DISTINCT r.receiptnumber FROM receipts r WHERE EXISTS (SELECT 1 FROM items i JOIN goods g ON i.item = g.id WHERE g.food = 'cake' AND i.receipt = r.receiptnumber) AND EXISTS (SELECT 1 FROM items i2 JOIN goods g2 ON i2.item = g2.id WHERE g2.food = 'cookie' AND i2.receipt = r.receiptnumber)	str	1	0

1513	Find all the receipt numbers in which customer with last name LOGAN purchased Croissant.	SELECT T1.ReceiptNumber FROM receipts AS T1 JOIN items AS T2 ON T1.ReceiptNumber = T2.receipt JOIN goods AS T3 ON T2.item = T3.id JOIN customers AS T4 ON T4.Id = T1.CustomerId WHERE T3.food = "Croissant" AND T4.LastName = 'LOGAN'	SELECT DISTINCT receipts.receiptnumber FROM receipts, customers, items, goods WHERE receipts.customerid = customers.id AND items.receipt = receipts.receiptnumber AND items.item = goods.id AND customers.lastname = 'LOGAN' AND goods.food = 'Croissant'	join -> in-sub	0	1
1514	What are the receipt numbers for a customer with the last name Logan who purchased a croissant?	SELECT T1.ReceiptNumber FROM receipts AS T1 JOIN items AS T2 ON T1.ReceiptNumber = T2.receipt JOIN goods AS T3 ON T2.item = T3.id JOIN customers AS T4 ON T4.Id = T1.CustomerId WHERE T3.food = "Croissant" AND T4.LastName = 'LOGAN'	SELECT DISTINCT r.receiptnumber FROM receipts r JOIN customers c ON r.customerid = c.id JOIN items i ON r.receiptnumber = i.receipt JOIN goods g ON i.item = g.id WHERE c.lastname = 'Logan' AND g.food = 'croissant'	join -> in-sub; str	1	0
1515	What is the receipt number and date of the receipt in which the most expensive item was bought?	SELECT T1.ReceiptNumber , T1.Date FROM receipts AS T1 JOIN items AS T2 ON T1.ReceiptNumber = T2.receipt JOIN goods AS T3 ON T2.item = T3.id ORDER BY T3.price DESC LIMIT 1	SELECT receiptnumber, date FROM receipts WHERE receiptnumber IN (SELECT receipt FROM items WHERE item IN (SELECT id FROM goods WHERE price = (SELECT MAX(price) FROM goods)))	limit 1	0	0
1516	What is the receipt number and date corresponding to the receipt for which the most expensive item was purchased?	SELECT T1.ReceiptNumber , T1.Date FROM receipts AS T1 JOIN items AS T2 ON T1.ReceiptNumber = T2.receipt JOIN goods AS T3 ON T2.item = T3.id ORDER BY T3.price DESC LIMIT 1	SELECT receiptnumber, date FROM receipts WHERE receiptnumber IN (SELECT receipt FROM items WHERE item IN (SELECT id FROM goods WHERE price = (SELECT MAX(price) FROM goods)))	limit 1	1	0
1517	What is the item that was bought the least number of times?	SELECT item FROM items GROUP BY item ORDER BY count(*) LIMIT 1	SELECT I.item FROM items I GROUP BY I.item HAVING COUNT(I.item) = (SELECT MIN(Count) FROM (SELECT COUNT(item) Count FROM items GROUP BY item))	limit 1	0	1
1518	Which item was bought the fewest times?	SELECT item FROM items GROUP BY item ORDER BY count(*) LIMIT 1	SELECT I.item FROM items I GROUP BY I.item HAVING COUNT(I.item) = (SELECT MIN(Count) FROM (SELECT COUNT(item) Count FROM items GROUP BY item))	limit 1	0	0
1525	Find flavor of cakes that cost more than 10 dollars.	SELECT flavor FROM goods WHERE food = "Cake" AND price > 10	SELECT flavor FROM goods WHERE food = "cake" AND price > 10	str	1	0
1526	What are the flavors of cakes that cost more than 10 dollars?	SELECT flavor FROM goods WHERE food = "Cake" AND price > 10	SELECT flavor FROM goods WHERE food = "cake" AND price > 10	str	0	0
1530	Give the distinct ids for goods that cost less than any Tart.	SELECT DISTINCT id FROM goods WHERE price < (SELECT max(price) FROM goods WHERE food = "Tart")	SELECT DISTINCT id FROM goods WHERE price < (SELECT min(price) FROM goods WHERE food = "Tart")	semantic error: "any"	1	0
1539	List the last names of all customers in an alphabetical order.	SELECT DISTINCT LastName FROM customers ORDER BY LastName	SELECT LastName FROM customers ORDER BY LastName	redundant distinct	1	0
1540	What are the last names of the customers in alphabetical order?	SELECT DISTINCT LastName FROM customers ORDER BY LastName	SELECT LastName FROM customers ORDER BY LastName	redundant distinct	1	0
1543	Find all receipts in which either apple flavor pie was bought or customer id 12 shopped.	SELECT T1.receipt FROM items AS T1 JOIN goods AS T2 ON T1.item = T2.id WHERE T2.flavor = "Apple" AND T2.food = "Pie" UNION SELECT ReceiptNumber FROM receipts WHERE CustomerId = 12	SELECT DISTINCT r.receiptnumber FROM receipts r WHERE r.customerid = 12 OR r.receiptnumber IN (SELECT i.receipt FROM items i JOIN goods g ON i.item = g.id WHERE g.flavor = 'apple' AND g.food = 'pie')	str	1	0
1544	What are the receipt numbers for which either an apple flavor pie was purchased or the customer with id 12 shopped?	SELECT T1.receipt FROM items AS T1 JOIN goods AS T2 ON T1.item = T2.id WHERE T2.flavor = "Apple" AND T2.food = "Pie" UNION SELECT ReceiptNumber FROM receipts WHERE CustomerId = 12	SELECT receipts.receiptnumber FROM receipts WHERE EXISTS (SELECT 1 FROM items JOIN goods ON items.item = goods.id WHERE items.receipt = receipts.receiptnumber AND goods.flavor = 'apple' AND goods.food = 'pie') OR receipts.customerid = 12	str	1	0

1549	What are the ids of Cookie and Cake that cost between 3 and 7 dollars.	SELECT id FROM goods WHERE food = "Cookie" OR food = "Cake" AND price BETWEEN 3 AND 7	SELECT id FROM goods WHERE food IN ('Cookie', 'Cake') AND price BETWEEN 3 AND 7	operator precedence	0	1
1550	Give the ids of Cookies or Cakes that cost between 3 and 7 dollars.	SELECT id FROM goods WHERE food = "Cookie" OR food = "Cake" AND price BETWEEN 3 AND 7	SELECT id FROM goods WHERE food IN ('Cookie', 'Cake') AND price BETWEEN 3 AND 7	operator precedence	1	0
1551	Find the first name and last name of a customer who visited on the earliest date.	SELECT T1.FirstName, T1.LastName FROM customers AS T1 JOIN receipts AS T2 ON T1.id = T2.CustomerId ORDER BY T2.date LIMIT 1	SELECT firstname, lastname FROM customers WHERE id IN (SELECT customerid FROM receipts WHERE date = (SELECT MIN(date) FROM receipts))	limit 1	0	1
1552	What is the full name of the customer who visited on the earliest date?	SELECT T1.FirstName, T1.LastName FROM customers AS T1 JOIN receipts AS T2 ON T1.id = T2.CustomerId ORDER BY T2.date LIMIT 1	SELECT firstname, lastname FROM customers WHERE id IN (SELECT customerid FROM receipts WHERE date = (SELECT MIN(date) FROM receipts))	limit 1	0	0
1553	What is average price of goods whose flavor is blackberry or blueberry?	SELECT avg(price) FROM goods WHERE flavor = "Blackberry" OR flavor = "Blueberry"	SELECT AVG(price) FROM goods WHERE flavor IN ('blackberry', 'blueberry')	str	1	0
1554	What are the average prices of goods with blackberry or blueberry flavor?	SELECT avg(price) FROM goods WHERE flavor = "Blackberry" OR flavor = "Blueberry"	SELECT AVG(price) FROM goods WHERE flavor IN ('blackberry', 'blueberry')	str	1	0
1555	Return the cheapest price for goods with cheese flavor.	SELECT min(price) FROM goods WHERE flavor = "Cheese"	SELECT MIN(price) FROM goods WHERE flavor = 'cheese'	str	1	0
1556	What is the cheapest good with cheese flavor?	SELECT min(price) FROM goods WHERE flavor = "Cheese"	SELECT id FROM goods WHERE flavor = 'cheese' AND price = (SELECT MIN(price) FROM goods WHERE flavor = 'cheese')	semantic error; str	0	0
1561	Find the top three dates with the most receipts.	SELECT date FROM receipts GROUP BY date ORDER BY count(*) DESC LIMIT 3	WITH RankedDates AS (SELECT date, RANK() OVER (ORDER BY COUNT(*) DESC) AS rnk FROM receipts GROUP BY date) SELECT date FROM RankedDates WHERE rnk <= 3	limit n	1	0
1562	What are the three dates for which the most receipts were given?	SELECT date FROM receipts GROUP BY date ORDER BY count(*) DESC LIMIT 3	WITH RankedDates AS (SELECT date, RANK() OVER (ORDER BY COUNT(*) DESC) AS rnk FROM receipts GROUP BY date) SELECT date FROM RankedDates WHERE rnk <= 3	limit n	0	0
1563	Which customer shopped most often? How many times?	SELECT CustomerId, count(*) FROM receipts GROUP BY CustomerId ORDER BY count(*) DESC LIMIT 1	WITH cnt AS (SELECT CustomerId, count(*) AS cnt FROM receipts GROUP BY CustomerId) SELECT CustomerId, cnt FROM cnt WHERE cnt = (SELECT MAX(cnt) FROM cnt)	limit 1	1	0
1564	Give the customer id of the customer that made the most purchases, as well as the number of purchases made.	SELECT CustomerId, count(*) FROM receipts GROUP BY CustomerId ORDER BY count(*) DESC LIMIT 1	WITH cnt AS (SELECT CustomerId, count(*) AS cnt FROM receipts GROUP BY CustomerId) SELECT CustomerId, cnt FROM cnt WHERE cnt = (SELECT MAX(cnt) FROM cnt)	limit 1	0	0
1567	Give me the first name and last name of customers who have bought apple flavor Tart.	SELECT DISTINCT T4.FirstName, T4.LastName FROM goods AS T1 JOIN items AS T2 ON T1.id = T2.item JOIN receipts AS T3 ON T2.receipt = T3.ReceiptNumber JOIN customers AS T4 ON T3.CustomerId = T4.id WHERE T1.flavor = "Apple" AND T1.food = "Tart"	SELECT firstname, lastname FROM customers WHERE id IN (SELECT customerid FROM receipts WHERE receiptnumber IN (SELECT receipt FROM items WHERE item IN (SELECT id FROM goods WHERE flavor = 'apple' AND food = 'Tart')))	join -> in-sub; redundant distinct	1	0

1568	What are the full names of customers who bought apple flavored Tarts?	SELECT DISTINCT T4.FirstName , T4.LastName FROM goods AS T1 JOIN items AS T2 ON T1.id = T2.item JOIN receipts AS T3 ON T2.receipt = T3.ReceiptNumber JOIN customers AS T4 ON T3.CustomerId = T4.id WHERE T1.flavor = "Apple" AND T1.food = "Tart"	SELECT firstname, lastname FROM customers WHERE id IN (SELECT customerid FROM receipts WHERE receiptnumber IN (SELECT receipt FROM items WHERE item IN (SELECT id FROM goods WHERE flavor = 'apple' AND food = 'Tart')))	join -> in-sub; redundant distinct	0	0
1573	What are the ids of goods whose price is above twice the average price of all goods?	SELECT id FROM goods WHERE price > (SELECT avg(price) FROM goods)	SELECT id FROM goods WHERE price > 2 * (SELECT AVG(price) FROM goods)	semantic error	0	1
1574	Give the ids of goods that are more than twice as expensive as the average good.	SELECT id FROM goods WHERE price > (SELECT avg(price) FROM goods)	SELECT id FROM goods WHERE price > 2 * (SELECT AVG(price) FROM goods)	semantic error	1	0
1579	Find all the items that have chocolate flavor but were not bought more than 10 times.	SELECT DISTINCT T1.item FROM items AS T1 JOIN goods AS T2 ON T1.item = T2.id WHERE T2.flavor = "Chocolate" GROUP BY item HAVING count(*) <= 10	SELECT g.id FROM goods g WHERE g.flavor = 'chocolate' AND (SELECT COUNT(*) FROM items i WHERE i.item = g.id) <= 10	join -> left join; str	1	0
1580	What are the items with chocolate flavor that were purchased at most 10 times.	SELECT DISTINCT T1.item FROM items AS T1 JOIN goods AS T2 ON T1.item = T2.id WHERE T2.flavor = "Chocolate" GROUP BY item HAVING count(*) <= 10	SELECT g.id FROM goods g WHERE g.flavor = 'chocolate' AND (SELECT COUNT(*) FROM items i WHERE i.item = g.id) <= 10	join -> left join; str	1	0
1583	What is the three most popular goods in this bakery?	SELECT item FROM items GROUP BY item ORDER BY COUNT (*) DESC LIMIT 3	WITH cnt AS (SELECT item, COUNT(*) AS cnt FROM items GROUP BY item) SELECT item FROM cnt WHERE EXISTS (SELECT 1 FROM (SELECT cnt FROM cnt ORDER BY cnt DESC LIMIT 3) t WHERE cnt.cnt = t.cnt)	limit n	0	0
1584	Give the three most purchased items at this bakery.	SELECT item FROM items GROUP BY item ORDER BY COUNT (*) DESC LIMIT 3	WITH cnt AS (SELECT item, COUNT(*) AS cnt FROM items GROUP BY item) SELECT item FROM cnt WHERE EXISTS (SELECT 1 FROM (SELECT cnt FROM cnt ORDER BY cnt DESC LIMIT 3) t WHERE cnt.cnt = t.cnt)	limit n	0	0
1601	Find the make that has more than one team.	SELECT make FROM team GROUP BY team HAVING count(*) > 1	SELECT make FROM team GROUP BY make HAVING COUNT(team_id) > 1	semantic error: group by key	0	1
1602	Which make has more than one team?	SELECT make FROM team GROUP BY team HAVING count(*) > 1	SELECT make FROM team GROUP BY make HAVING COUNT(team_id) > 1	semantic error: group by key	0	1
1613	Please show the names of drivers, and countries they are from.	SELECT T2.Driver , T1.Country FROM country AS T1 JOIN driver AS T2 ON T1.Country_ID = T2.Country	SELECT T2.Driver, T1.Country FROM country AS T1 RIGHT JOIN driver AS T2 ON T1.Country_ID = T2.Country	join -> left join	1	0
1614	For each driver, return his or her name and country.	SELECT T2.Driver , T1.Country FROM country AS T1 JOIN driver AS T2 ON T1.Country_ID = T2.Country	SELECT T2.Driver, T1.Country FROM country AS T1 RIGHT JOIN driver AS T2 ON T1.Country_ID = T2.Country	join -> left join	1	0
1619	What are the countries that have drivers with points larger than 150?	SELECT T1.Country FROM country AS T1 JOIN driver AS T2 ON T1.Country_ID = T2.Country WHERE T2.Points > 150	SELECT country.country FROM country WHERE country_id IN (SELECT country_id FROM country JOIN driver ON country.country_id = driver.country WHERE driver.points > 150)	join -> in-sub	1	0
1620	Find all the countries where some drivers have points above 150.	SELECT T1.Country FROM country AS T1 JOIN driver AS T2 ON T1.Country_ID = T2.Country WHERE T2.Points > 150	SELECT country.country FROM country WHERE country_id IN (SELECT country_id FROM country JOIN driver ON country.country_id = driver.country WHERE driver.points > 150)	join -> in-sub	1	0
1621	What is the capital of the country where the driver with the most points is from?	SELECT T1.Capital FROM country AS T1 JOIN driver AS T2 ON T1.Country_ID = T2.Country ORDER BY T2.Points DESC LIMIT 1	SELECT (SELECT capital FROM country WHERE country = d.country) AS capital FROM driver d WHERE d.points = (SELECT MAX(points) FROM driver)	limit 1; join -> left join	1	0

1622	Which country is the driver with the highest points from? Give me the capital of the country.	SELECT T1.Capital FROM country AS T1 JOIN driver AS T2 ON T1.Country_ID = T2.Country ORDER BY T2.Points DESC LIMIT 1	SELECT (SELECT capital FROM country WHERE country = d.country) AS capital FROM driver d WHERE d.points = (SELECT MAX(points) FROM driver)	limit 1; join -> left join	1	0
1625	List the make that are associated with most drivers.	SELECT Make FROM driver GROUP BY Make ORDER BY COUNT(*) DESC LIMIT 1	WITH Ranked AS (SELECT make, RANK() OVER (ORDER BY COUNT(driver_id) DESC) AS rank FROM driver GROUP BY make) SELECT make FROM Ranked WHERE rank = 1	limit 1	0	1
1626	Which make does the most drivers have?	SELECT Make FROM driver GROUP BY Make ORDER BY COUNT(*) DESC LIMIT 1	SELECT make FROM (SELECT make, COUNT(*) as num_drivers FROM driver GROUP BY make) temp WHERE num_drivers = (SELECT MAX(num_drivers) FROM (SELECT make, COUNT(*) as num_drivers FROM driver GROUP BY make) temp2)	limit 1	0	1
1631	Which country has both drivers with make "Dodge" and drivers with make "Chevrolet"?	SELECT t2.country FROM driver AS t1 JOIN country AS t2 ON t1.country = t2.country_id WHERE t1.Make = "Dodge" INTERSECT SELECT t2.country FROM driver AS t1 JOIN country AS t2 ON t1.country = t2.country_id WHERE t1.Make = "Chevrolet"	SELECT Country FROM country WHERE Country_ID IN (SELECT Country FROM driver WHERE Make = 'Dodge') AND Country_ID IN (SELECT Country FROM driver WHERE Make = 'Chevrolet')	intersect non-key	1	0
1632	Find the countries in which there are both drivers with make "Dodge" and drivers with make "Chevrolet".	SELECT t2.country FROM driver AS t1 JOIN country AS t2 ON t1.country = t2.country_id WHERE t1.Make = "Dodge" INTERSECT SELECT t2.country FROM driver AS t1 JOIN country AS t2 ON t1.country = t2.country_id WHERE t1.Make = "Chevrolet"	SELECT Country FROM country WHERE Country_ID IN (SELECT Country FROM driver WHERE Make = 'Dodge') AND Country_ID IN (SELECT Country FROM driver WHERE Make = 'Chevrolet')	intersect non-key	1	0
1637	What are the manager and sponsor of the team that has the most drivers?	SELECT t1.manager , t1.sponsor FROM team AS t1 JOIN team_driver AS t2 ON t1.team_id = t2.team_id GROUP BY t2.team_id ORDER BY count(*) DESC LIMIT 1	WITH DriverCounts AS (SELECT t.team_id, COUNT(td.team_id) AS num_drivers FROM team t LEFT JOIN team_driver td ON t.team_id = td.team_id GROUP BY t.team_id) SELECT t.manager, t.sponsor FROM team t INNER JOIN DriverCounts dc ON t.team_id = dc.team_id WHERE dc.num_drivers = (SELECT MAX(num_drivers) FROM DriverCounts)	limit 1; join -> left join	0	0
1638	Find the manager and sponsor of the team that has the most drivers.	SELECT t1.manager , t1.sponsor FROM team AS t1 JOIN team_driver AS t2 ON t1.team_id = t2.team_id GROUP BY t2.team_id ORDER BY count(*) DESC LIMIT 1	WITH DriverCounts AS (SELECT t.team_id, COUNT(td.team_id) AS num_drivers FROM team t LEFT JOIN team_driver td ON t.team_id = td.team_id GROUP BY t.team_id) SELECT t.manager, t.sponsor FROM team t INNER JOIN DriverCounts dc ON t.team_id = dc.team_id WHERE dc.num_drivers = (SELECT MAX(num_drivers) FROM DriverCounts)	limit 1; join -> left join	0	0
1655	What is the stadium of the institution with the largest enrollment?	SELECT Stadium FROM institution ORDER BY Enrollment DESC LIMIT 1	SELECT stadium FROM institution WHERE enrollment = (SELECT MAX(enrollment) FROM institution)	limit 1	1	0
1656	Give the stadium of the institution which is the greatest enrollment.	SELECT Stadium FROM institution ORDER BY Enrollment DESC LIMIT 1	SELECT stadium FROM institution WHERE enrollment = (SELECT MAX(enrollment) FROM institution)	limit 1	0	1
1657	What are the names and nicknames of institutions?	SELECT T2.Name , T1.Nickname FROM championship AS T1 JOIN institution AS T2 ON T1.Institution_ID = T2.Institution_ID	SELECT i.Name, c.Nickname FROM institution AS i LEFT JOIN Championship AS c ON c.Institution_ID = i.Institution_ID	join -> left join	1	0
1658	Return the names of institutions, as well as their nicknames.	SELECT T2.Name , T1.Nickname FROM championship AS T1 JOIN institution AS T2 ON T1.Institution_ID = T2.Institution_ID	SELECT i.Name, c.Nickname FROM institution AS i LEFT JOIN Championship AS c ON c.Institution_ID = i.Institution_ID	join -> left join	1	0
1659	What is the nickname of the institution with the smallest enrollment?	SELECT T1.Nickname FROM championship AS T1 JOIN institution AS T2 ON T1.Institution_ID = T2.Institution_ID ORDER BY T2.Enrollment ASC LIMIT 1	SELECT (SELECT nickname FROM championship WHERE institution_id = i.institution_id) FROM institution i WHERE enrollment = (SELECT MIN(enrollment) FROM institution)	limit 1; join -> left join	0	0

1660	Return the nickname of the institution with the lowest enrollment.	SELECT T1.Nickname FROM championship AS T1 JOIN institution AS T2 ON T1.Institution_ID = T2.Institution_ID ORDER BY T2.Enrollment ASC LIMIT 1	SELECT (SELECT nickname FROM championship WHERE institution_id = i.institution_id) FROM institution i WHERE enrollment = (SELECT MIN(enrollment) FROM institution)	limit 1; join -> left join	1	0
1661	List the names of institutions in descending order of the number of championships.	SELECT T2.Name FROM championship AS T1 JOIN institution AS T2 ON T1.Institution_ID = T2.Institution_ID ORDER BY T1.Number_of_Championships DESC	SELECT i.Name FROM institution AS i LEFT JOIN Championship AS c ON c.Institution_ID = i.Institution_ID ORDER BY c.Number_of_Championships DESC	join -> left join	1	0
1662	What are the names of institutions, ordered descending by their number of championships?	SELECT T2.Name FROM championship AS T1 JOIN institution AS T2 ON T1.Institution_ID = T2.Institution_ID ORDER BY T1.Number_of_Championships DESC	SELECT i.Name FROM institution AS i LEFT JOIN Championship AS c ON c.Institution_ID = i.Institution_ID ORDER BY c.Number_of_Championships DESC	join -> left join	0	0
1669	What is the most common type of affiliation for institutions?	SELECT Affiliation FROM institution GROUP BY Affiliation ORDER BY COUNT(*) DESC LIMIT 1	SELECT affiliation FROM institution GROUP BY affiliation HAVING COUNT(*) = (SELECT MAX(count) FROM (SELECT COUNT(*) AS count FROM institution GROUP BY affiliation))	limit 1	0	1
1670	Return the most common type of affiliation across all institutions.	SELECT Affiliation FROM institution GROUP BY Affiliation ORDER BY COUNT(*) DESC LIMIT 1	SELECT affiliation FROM institution GROUP BY affiliation HAVING COUNT(*) = (SELECT MAX(Cnt) FROM (SELECT COUNT(*) AS Cnt FROM institution GROUP BY affiliation))	limit 1	0	1
1671	In which years were more than one institution founded?	SELECT Founded, COUNT(*) FROM institution GROUP BY Founded HAVING COUNT(*) > 1	SELECT founded FROM institution GROUP BY founded HAVING COUNT(*) > 1	semantic error: output col	0	1
1673	List the nicknames of institutions in descending order of capacity.	SELECT T1.Nickname FROM championship AS T1 JOIN institution AS T2 ON T1.Institution_ID = T2.Institution_ID ORDER BY T2.Capacity DESC	SELECT c.Nickname FROM institution AS i LEFT JOIN Championship AS c ON i.Institution_ID = c.Institution_ID ORDER BY i.Capacity DESC	join -> left join	1	0
1674	What are the nicknames of institutions, ordered descending by their capacities?	SELECT T1.Nickname FROM championship AS T1 JOIN institution AS T2 ON T1.Institution_ID = T2.Institution_ID ORDER BY T2.Capacity DESC	SELECT c.Nickname FROM institution AS i LEFT JOIN Championship AS c ON i.Institution_ID = c.Institution_ID ORDER BY i.Capacity DESC	join -> left join	1	0
1675	What are the total enrollment of institutions in city "Vancouver" or "Calgary"?	select sum(enrollment) from institution where city = "vancouver" or city = "calgary"	SELECT SUM(enrollment) FROM institution WHERE city IN ('Vancouver', 'Calgary')	str	0	1
1676	Return all the enrollments of institutions in either the city of Vancouver or the city of Calgary.	select sum(enrollment) from institution where city = "vancouver" or city = "calgary"	SELECT enrollment FROM institution WHERE city IN ('Calgary', 'Vancouver')	str; semantic error	0	1
1687	Select the warehouse code and the average value of the boxes in each warehouse.	SELECT warehouse, avg(value) FROM boxes GROUP BY warehouse	SELECT w.Code, AVG(b.Value) FROM Warehouses w LEFT JOIN Boxes b ON w.Code = b.Warehouse GROUP BY w.Code	join -> left join	1	0
1688	What is the average value of boxes for each warehouse?	SELECT warehouse, avg(value) FROM boxes GROUP BY warehouse	SELECT w.Code, AVG(b.Value) FROM Warehouses w LEFT JOIN Boxes b ON w.Code = b.Warehouse GROUP BY w.Code	join -> left join	0	0
1695	Find the content that has the highest total values in all boxes.	SELECT CONTENTS FROM boxes ORDER BY value DESC LIMIT 1	SELECT t.contents FROM (SELECT contents, SUM(value) AS total_value FROM boxes GROUP BY contents) t WHERE t.total_value = (SELECT MAX(t2.total_value) FROM (SELECT SUM(value) AS total_value FROM boxes GROUP BY contents) t2)	semantic error	0	1

1696	What is the content with the greatest value across all boxes?	SELECT CONTENTS FROM boxes ORDER BY value DESC LIMIT 1	SELECT DISTINCT contents FROM boxes WHERE value = (SELECT MAX(value) FROM boxes)	limit 1	1	0
1703	Find all distinct locations of warehouses.	SELECT count(DISTINCT LOCATION) FROM warehouses	SELECT DISTINCT location FROM warehouses;	semantic error	0	1
1704	What are the different locations of warehouses?	SELECT count(DISTINCT LOCATION) FROM warehouses	SELECT DISTINCT location FROM warehouses;	semantic error	0	1
1713	Find the location of the warehouses which have contents Rocks but not Scissors.	SELECT T2.location FROM boxes AS T1 JOIN warehouses AS T2 ON T1.warehouse = T2.code WHERE T1.contents = 'Rocks' EXCEPT SELECT T2.location FROM boxes AS T1 JOIN warehouses AS T2 ON T1.warehouse = T2.code WHERE T1.contents = 'Scissors'	SELECT location FROM warehouses WHERE code IN (SELECT warehouse FROM boxes WHERE contents = 'Rocks') AND code NOT IN (SELECT warehouse FROM boxes WHERE contents = 'Scissors')	semantic error	0	0
1714	What are the locations of warehouses that have boxes containing Rocks but not Scissors?	SELECT T2.location FROM boxes AS T1 JOIN warehouses AS T2 ON T1.warehouse = T2.code WHERE T1.contents = 'Rocks' EXCEPT SELECT T2.location FROM boxes AS T1 JOIN warehouses AS T2 ON T1.warehouse = T2.code WHERE T1.contents = 'Scissors'	SELECT location FROM warehouses WHERE code IN (SELECT warehouse FROM boxes WHERE contents = 'Rocks') AND code NOT IN (SELECT warehouse FROM boxes WHERE contents = 'Scissors')	semantic error	0	0
1717	Find the location of the warehouses which store contents Rocks and Scissors.	SELECT T2.location FROM boxes AS T1 JOIN warehouses AS T2 ON T1.warehouse = T2.code WHERE T1.contents = 'Rocks' INTERSECT SELECT T2.location FROM boxes AS T1 JOIN warehouses AS T2 ON T1.warehouse = T2.code WHERE T1.contents = 'Scissors'	SELECT location FROM warehouses WHERE code IN (SELECT warehouse FROM boxes WHERE contents = 'Rocks' INTERSECT SELECT warehouse FROM boxes WHERE contents = 'Scissors')	semantic error	1	0
1718	What are the locations of warehouses in which boxes that contain Rocks and Scissors are kept?	SELECT T2.location FROM boxes AS T1 JOIN warehouses AS T2 ON T1.warehouse = T2.code WHERE T1.contents = 'Rocks' INTERSECT SELECT T2.location FROM boxes AS T1 JOIN warehouses AS T2 ON T1.warehouse = T2.code WHERE T1.contents = 'Scissors'	SELECT location FROM warehouses WHERE code IN (SELECT warehouse FROM boxes WHERE contents = 'Rocks' INTERSECT SELECT warehouse FROM boxes WHERE contents = 'Scissors')	semantic error	1	0
1721	Find the code and contents of the box with the lowest value.	SELECT code , CONTENTS FROM boxes ORDER BY value LIMIT 1	SELECT code, contents FROM boxes WHERE value = (SELECT MIN(value) FROM boxes)	limit 1	0	1
1722	What is the code and contents for the box that has the smallest value?	SELECT code , CONTENTS FROM boxes ORDER BY value LIMIT 1	SELECT code, contents FROM boxes WHERE value = (SELECT MIN(value) FROM boxes)	limit 1	0	1
1731	Find the total value of boxes stored in the warehouse with the largest capacity.	SELECT sum(T1.value) FROM boxes AS T1 JOIN warehouses AS T2 ON T1.warehouse = T2.code ORDER BY T2.capacity DESC LIMIT 1	SELECT (SELECT SUM(value) FROM boxes WHERE warehouse = w.code) FROM warehouses w WHERE capacity = (SELECT MAX(capacity) FROM warehouses)	limit 1	0	0
1732	What is the total value of boxes kept in the warehouse with the greatest capacity?	SELECT sum(T1.value) FROM boxes AS T1 JOIN warehouses AS T2 ON T1.warehouse = T2.code ORDER BY T2.capacity DESC LIMIT 1	SELECT (SELECT SUM(value) FROM boxes WHERE warehouse = w.code) FROM warehouses w WHERE capacity = (SELECT MAX(capacity) FROM warehouses)	limit 1	0	0
1741	Find the value of the most expensive boxes saved in each warehouse location.	SELECT max(T1.value) , T2.location FROM boxes AS T1 JOIN warehouses AS T2 ON T1.warehouse = T2.code GROUP BY T2.location	SELECT w.location, MAX(b.value) max_val FROM warehouses w LEFT JOIN boxes b ON w.code = b.warehouse GROUP BY w.location	join -> left join	0	0
1742	For each warehouse location, what is the value of the most expensive box?	SELECT max(T1.value) , T2.location FROM boxes AS T1 JOIN warehouses AS T2 ON T1.warehouse = T2.code GROUP BY T2.location	SELECT w.location, MAX(b.value) max_val FROM warehouses w LEFT JOIN boxes b ON w.code = b.warehouse GROUP BY w.location	join -> left join	0	1

1743	Select the warehouse codes along with the number of boxes in each warehouse.	SELECT Warehouse , count(*) FROM boxes GROUP BY warehouse	SELECT warehouses.code, COUNT(boxes.code) FROM warehouses LEFT JOIN boxes ON warehouses.code = boxes.warehouse GROUP BY warehouses.code	join -> left join	0	1
1744	How many boxes are there with each warehouse ?	select warehouse , count(*) from boxes group by warehouse	SELECT warehouses.code, COUNT(boxes.code) AS box_total FROM warehouses LEFT JOIN boxes ON warehouses.code = boxes.warehouse GROUP BY warehouses.code	join -> left join	0	1
1746	In how many different warehouses are Rocks stored within boxes?	SELECT count(DISTINCT LOCATION) FROM boxes AS T1 JOIN warehouses AS T2 ON T1.warehouse = T2.code WHERE T1.contents = 'Rocks'	SELECT COUNT(DISTINCT warehouse) FROM boxes WHERE contents = 'Rocks';	semantic error	0	1
1751	Find the number of boxes saved in each warehouse.	SELECT count(*) , warehouse FROM boxes GROUP BY warehouse	SELECT w.code, COUNT(b.code) FROM warehouses w LEFT JOIN boxes b ON w.code = b.warehouse GROUP BY w.code	join -> left join	0	1
1752	How many boxes are stored in each warehouse?	SELECT count(*) , warehouse FROM boxes GROUP BY warehouse	SELECT w.code, COUNT(b.code) as box_count FROM warehouses w LEFT JOIN boxes b ON w.code = b.warehouse GROUP BY w.code	join -> left join	0	1
1753	Find the number of distinct types of contents in each warehouse.	SELECT count(DISTINCT CONTENTS) , warehouse FROM boxes GROUP BY warehouse	SELECT w2.code, (SELECT COUNT(DISTINCT contents) FROM boxes WHERE warehouse = w2.code) FROM warehouses w2	join -> left join	1	0
1754	How many different types of contents are stored in each warehouse?	SELECT count(DISTINCT CONTENTS) , warehouse FROM boxes GROUP BY warehouse	SELECT w2.code, (SELECT COUNT(DISTINCT contents) FROM boxes WHERE warehouse = w2.code) FROM warehouses w2	join -> left join	1	0
1755	Select the codes of all warehouses that are above capacity.	SELECT T2.code FROM boxes AS T1 JOIN Warehouses AS T2 ON T1.warehouse = T2.code GROUP BY T2.code HAVING count(*) > T2.capacity	SELECT w.code FROM warehouses w LEFT JOIN boxes b ON w.code = b.warehouse GROUP BY w.code HAVING COUNT(b.code) > w.capacity	join -> left join	1	0
1756	What are the codes of warehouses that have more boxes than their capacity?	SELECT T2.code FROM boxes AS T1 JOIN Warehouses AS T2 ON T1.warehouse = T2.code GROUP BY T2.code HAVING count(*) > T2.capacity	SELECT w.code FROM warehouses w LEFT JOIN boxes b ON w.code = b.warehouse GROUP BY w.code HAVING COUNT(b.code) > w.capacity	join -> left join	1	0
1771	Which state has most number of universities?	SELECT state FROM University GROUP BY state ORDER BY count(*) DESC LIMIT 1	SELECT state FROM university GROUP BY state HAVING COUNT(*) = (SELECT MAX(total) FROM (SELECT COUNT(*) AS total FROM university GROUP BY state))	limit 1	0	1
1772	What is the state with the most universities?	SELECT state FROM University GROUP BY state ORDER BY count(*) DESC LIMIT 1	SELECT state FROM university GROUP BY state HAVING COUNT(university_id) = (SELECT MAX(cnt) FROM (SELECT COUNT(university_id) AS cnt FROM university GROUP BY state))	limit 1	0	0
1775	Which conference has the least number of total enrollment?	SELECT home_conference FROM University GROUP BY home_conference ORDER BY sum(enrollment) LIMIT 1	WITH Enrollment_Sums AS (SELECT home_conference, SUM(enrollment) as total_enrollment FROM university GROUP BY home_conference) SELECT home_conference FROM Enrollment_Sums WHERE total_enrollment = (SELECT MIN(total_enrollment) FROM Enrollment_Sums)	limit 1	1	0
1776	What are the home conferences with the fewest number of people enrolled?	SELECT home_conference FROM University GROUP BY home_conference ORDER BY sum(enrollment) LIMIT 1	WITH Enrollment_Sums AS (SELECT home_conference, SUM(enrollment) as total_enrollment FROM university GROUP BY home_conference) SELECT home_conference FROM Enrollment_Sums WHERE total_enrollment = (SELECT MIN(total_enrollment) FROM Enrollment_Sums)	limit 1	1	0

1781	What is the name, city, state of the university with a rank 1 on Accounting major?	SELECT T2.university_name , T2.city , T2.state FROM Major_Ranking AS T1 JOIN University AS T2 JOIN Major AS T3 ON T1.university_id = T2.university_id AND T1.major_id = T3.major_id WHERE T1.rank = 1 AND T3.major_name = 'Accounting'	SELECT university_name, city, state FROM university WHERE university_id IN (SELECT university_id FROM major_ranking JOIN major ON major_ranking.major_id = major.major_id WHERE major_ranking.rank = 1 AND major.major_name = 'Accounting')	join -> in-sub	0	1
1782	What is the name, city, and state of the university with number 1 ranked Accounting major?	SELECT T2.university_name , T2.city , T2.state FROM Major_Ranking AS T1 JOIN University AS T2 JOIN Major AS T3 ON T1.university_id = T2.university_id AND T1.major_id = T3.major_id WHERE T1.rank = 1 AND T3.major_name = 'Accounting'	SELECT U.university_name, U.city, U.state FROM university U WHERE EXISTS (SELECT 1 FROM major_ranking R INNER JOIN major M ON M.major_id = R.major_id WHERE R.university_id = U.university_id AND M.major_name = 'Accounting' AND R.rank = 1)	join -> in-sub	0	1
1783	What is the name of the university that has most number of majors with rank 1?	SELECT T2.university_name FROM Major_Ranking AS T1 JOIN University AS T2 ON T1.university_id = T2.university_id WHERE T1.rank = 1 GROUP BY T2.university_name ORDER BY count(*) DESC LIMIT 1	SELECT U.university_name FROM university AS U JOIN (SELECT university_id, COUNT(*) AS c FROM major_ranking WHERE rank = 1 GROUP BY university_id HAVING c = (SELECT MAX(c) FROM (SELECT COUNT(*) AS c FROM major_ranking WHERE rank = 1 GROUP BY university_id))) AS R ON U.university_id = R.university_id	limit 1	0	0
1784	What is the name of the university with the most majors ranked number 1?	SELECT T2.university_name FROM Major_Ranking AS T1 JOIN University AS T2 ON T1.university_id = T2.university_id WHERE T1.rank = 1 GROUP BY T2.university_name ORDER BY count(*) DESC LIMIT 1	SELECT U.university_name FROM university AS U JOIN (SELECT university_id, COUNT(*) AS c FROM major_ranking WHERE rank = 1 GROUP BY university_id HAVING c = (SELECT MAX(c) FROM (SELECT COUNT(*) AS c FROM major_ranking WHERE rank = 1 GROUP BY university_id))) AS R ON U.university_id = R.university_id	limit 1	0	1
1785	Show all university names without a major with rank 1?	SELECT university_name FROM University EXCEPT SELECT T2.university_name FROM Major_Ranking AS T1 JOIN University AS T2 ON T1.university_id = T2.university_id WHERE T1.rank = 1	SELECT u.university_name FROM university u WHERE NOT EXISTS (SELECT * FROM major_ranking mr WHERE mr.rank = 1 AND mr.university_id = u.university_id)	except non-key	0	1
1786	What are the names of all universities without any majors ranked number 1?	SELECT university_name FROM University EXCEPT SELECT T2.university_name FROM Major_Ranking AS T1 JOIN University AS T2 ON T1.university_id = T2.university_id WHERE T1.rank = 1	SELECT university_name FROM university WHERE university_id NOT IN (SELECT university_id FROM major_ranking WHERE rank = 1)	except non-key	0	1
1787	Show all university names with both major Accounting and major Urban Education.	SELECT T2.university_name FROM Major_Ranking AS T1 JOIN University AS T2 JOIN Major AS T3 ON T1.university_id = T2.university_id AND T1.major_id = T3.major_id WHERE T3.major_name = 'Accounting' INTERSECT SELECT T2.university_name FROM Major_Ranking AS T1 JOIN University AS T2 JOIN Major AS T3 ON T1.university_id = T2.university_id AND T1.major_id = T3.major_id WHERE T3.major_name = 'Urban Education'	SELECT university_name FROM university WHERE university_id IN (SELECT MR.university_id FROM major_ranking MR INNER JOIN major M ON MR.major_id = M.major_id WHERE M.major_name = 'Accounting' INTERSECT SELECT MR.university_id FROM major_ranking MR INNER JOIN major M ON MR.major_id = M.major_id WHERE M.major_name = 'Urban Education')	intersect non-key	0	1
1788	What are the names of all universities that have both Accounting and Urban Education majors?	SELECT T2.university_name FROM Major_Ranking AS T1 JOIN University AS T2 JOIN Major AS T3 ON T1.university_id = T2.university_id AND T1.major_id = T3.major_id WHERE T3.major_name = 'Accounting' INTERSECT SELECT T2.university_name FROM Major_Ranking AS T1 JOIN University AS T2 JOIN Major AS T3 ON T1.university_id = T2.university_id AND T1.major_id = T3.major_id WHERE T3.major_name = 'Urban Education'	SELECT university_name FROM university WHERE university_id IN (SELECT mr.university_id FROM major_ranking mr JOIN major m ON mr.major_id = m.major_id WHERE m.major_name = 'Accounting' INTERSECT SELECT mr.university_id FROM major_ranking mr JOIN major m ON mr.major_id = m.major_id WHERE m.major_name = 'Urban Education')	intersect non-key	0	1

1789	What is the name and overall ranking of universities in Wisconsin state?	SELECT T1.university_name, T2.rank FROM University AS T1 JOIN Overall_ranking AS T2 ON T1.university_id = T2.university_id WHERE T1.state = 'Wisconsin'	SELECT T1.University_Name, T2.Rank FROM university AS T1 LEFT JOIN overall_ranking AS T2 ON T1.University_ID = T2.University_ID WHERE T1.State = 'Wisconsin'	join -> left join	1	0
1790	What is the name and rank of every university in Wisconsin?	SELECT T1.university_name, T2.rank FROM University AS T1 JOIN Overall_ranking AS T2 ON T1.university_id = T2.university_id WHERE T1.state = 'Wisconsin'	SELECT T1.University_Name, T2.Rank FROM university AS T1 LEFT JOIN overall_ranking AS T2 ON T1.University_ID = T2.University_ID WHERE T1.State = 'Wisconsin'	join -> left join	1	0
1791	What is the university name with highest research point?	SELECT T1.university_name FROM University AS T1 JOIN Overall_ranking AS T2 ON T1.university_id = T2.university_id ORDER BY T2.research_point DESC LIMIT 1	SELECT U.university_name FROM university U INNER JOIN overall_ranking O ON U.university_id = O.university_id WHERE O.research_point = (SELECT MAX(research_point) FROM overall_ranking)	limit 1	0	1
1792	What is the name of the university with the most research points?	SELECT T1.university_name FROM University AS T1 JOIN Overall_ranking AS T2 ON T1.university_id = T2.university_id ORDER BY T2.research_point DESC LIMIT 1	SELECT U.university_name FROM university U INNER JOIN overall_ranking O ON U.university_id = O.university_id WHERE O.research_point = (SELECT MAX(research_point) FROM overall_ranking)	limit 1	0	0
1793	List all university names in ascending order of their reputation points.	SELECT T1.university_name FROM University AS T1 JOIN Overall_ranking AS T2 ON T1.university_id = T2.university_id ORDER BY T2.reputation_point	SELECT T1.University_Name FROM university AS T1 LEFT JOIN overall_ranking AS T2 ON T1.University_ID = T2.University_ID ORDER BY T2.Reputation_Point	join -> left join	1	0
1794	What are the names of all universities in ascending order of reputation points?	SELECT T1.university_name FROM University AS T1 JOIN Overall_ranking AS T2 ON T1.university_id = T2.university_id ORDER BY T2.reputation_point	SELECT T1.University_Name FROM university AS T1 LEFT JOIN overall_ranking AS T2 ON T1.University_ID = T2.University_ID ORDER BY T2.Reputation_Point	join -> left join	0	0
1795	What is the name of university with major Accounting ranked 3 or above?	SELECT T2.university_name FROM Major_Ranking AS T1 JOIN University AS T2 JOIN Major AS T3 ON T1.university_id = T2.university_id AND T1.major_id = T3.major_id WHERE T1.rank <= 3 AND T3.major_name = "Accounting"	SELECT university_name FROM university WHERE EXISTS (SELECT 1 FROM major_ranking JOIN major ON major_ranking.major_id = major.major_id WHERE major_ranking.university_id = university.university_id AND major_name = 'Accounting' AND rank <= 3)	join -> in-sub	0	0
1796	What are the names of the university with an Accounting major ranked 3 or higher?	SELECT T2.university_name FROM Major_Ranking AS T1 JOIN University AS T2 JOIN Major AS T3 ON T1.university_id = T2.university_id AND T1.major_id = T3.major_id WHERE T1.rank <= 3 AND T3.major_name = "Accounting"	SELECT university_name FROM university WHERE EXISTS (SELECT 1 FROM major_ranking JOIN major ON major_ranking.major_id = major.major_id WHERE major_ranking.university_id = university.university_id AND major_name = 'Accounting' AND rank <= 3)	join -> in-sub	0	0
1799	Find the name and Citation point of the universities whose reputation points are top 3 and above.	SELECT T1.University_Name, T2.Citation_point FROM University AS T1 JOIN Overall_ranking AS T2 ON T1.university_id = T2.university_id ORDER BY T2.Reputation_point DESC LIMIT 3	SELECT T1.University_Name, T2.Citation_point FROM university AS T1 JOIN overall_ranking AS T2 WHERE EXISTS (SELECT 1 FROM (SELECT T2.Reputation_point FROM university AS T1 JOIN overall_ranking AS T2 ON T1.University_ID = T2.University_ID ORDER BY T2.Reputation_point DESC LIMIT 3) T WHERE T.Reputation_point = T2.Reputation_point)	limit n	0	0
1800	What is the name and citation point of the universities with the top 3 reputation points?	SELECT T1.University_Name, T2.Citation_point FROM University AS T1 JOIN Overall_ranking AS T2 ON T1.university_id = T2.university_id ORDER BY T2.Reputation_point DESC LIMIT 3	SELECT T1.University_Name, T2.Citation_point FROM university AS T1 JOIN overall_ranking AS T2 WHERE EXISTS (SELECT 1 FROM (SELECT T2.Reputation_point FROM university AS T1 JOIN overall_ranking AS T2 ON T1.University_ID = T2.University_ID ORDER BY T2.Reputation_point DESC LIMIT 3) T WHERE T.Reputation_point = T2.Reputation_point)	limit n	1	0

1803	Find the titles of movies that don't have any rating.	SELECT title FROM movies WHERE rating = 'null'	SELECT title FROM movies WHERE rating IS NULL	semantic error: = 'null'	1	0
1804	What are the names of movies that do not have any ratings?	SELECT title FROM movies WHERE rating = 'null'	SELECT title FROM movies WHERE rating IS NULL	semantic error: = 'null'	1	0
1807	Find the title of the movie that is played in the Odeon theater.	SELECT T1.title FROM movies AS T1 JOIN movietheaters AS T2 ON T1.code = T2.movie WHERE T2.name = 'Odeon'	SELECT title FROM movies WHERE code IN (SELECT movie FROM movietheaters WHERE name = 'Odeon')	join -> in-sub	0	1
1808	What are the movie titles for ones that are played in the Odeon theater?	SELECT T1.title FROM movies AS T1 JOIN movietheaters AS T2 ON T1.code = T2.movie WHERE T2.name = 'Odeon'	SELECT title FROM movies WHERE code IN (SELECT movie FROM movietheaters WHERE name = 'Odeon')	join -> in-sub	0	1
1809	Find the names of movies that are played in any theater and the name of the corresponding theater.	SELECT T1.title , T2.name FROM movies AS T1 JOIN movietheaters AS T2 ON T1.code = T2.movie	SELECT T1.title , T2.name FROM movies AS T1 JOIN movietheaters AS T2 ON T1.code = T2.movie GROUP BY T1.code, T2.name	lack distinct	1	0
1810	What are the names of the movies that are played in any theater and the name of the corresponding theater?	SELECT T1.title , T2.name FROM movies AS T1 JOIN movietheaters AS T2 ON T1.code = T2.movie	SELECT T1.title , T2.name FROM movies AS T1 JOIN movietheaters AS T2 ON T1.code = T2.movie GROUP BY T1.code, T2.name	lack distinct	1	0
1813	How many movies are playing across all theaters?	SELECT count(*) FROM movies AS T1 JOIN movietheaters AS T2 ON T1.code = T2.movie	SELECT COUNT(DISTINCT movie) FROM movietheaters	lack distinct	0	1
1814	How many movies are playing in theaters?	SELECT count(*) FROM movies AS T1 JOIN movietheaters AS T2 ON T1.code = T2.movie	SELECT COUNT(DISTINCT movie) FROM movietheaters	lack distinct	0	1
1821	Find the name of the cinemas that are playing movies with either rating 'G' or rating 'PG'.	SELECT title FROM movies WHERE rating = 'G' OR rating = 'PG'	SELECT DISTINCT mt.name FROM movietheaters AS mt JOIN movies AS m ON mt.movie = m.code WHERE m.rating IN ('G', 'PG')	semantic error	0	0
1822	What are the names of the movie theaters that are playing 'G' or 'PG' rated movies?	SELECT title FROM movies WHERE rating = 'G' OR rating = 'PG'	SELECT DISTINCT mt.name FROM movietheaters AS mt JOIN movies AS m ON mt.movie = m.code WHERE m.rating IN ('G', 'PG')	semantic error	0	0
1823	Find the name of the movies that are played in either cinema Odeon or Imperial.	SELECT T1.title FROM movies AS T1 JOIN movietheaters AS T2 ON T1.code = T2.movie WHERE T2.name = 'Odeon' OR T2.name = 'Imperial'	SELECT title FROM movies WHERE code IN (SELECT movie FROM movietheaters WHERE name = 'Odeon' OR name = 'Imperial')	join -> in-sub	0	1
1824	What are the titles of all the movies that played at the Odeon or Imperial theater?	SELECT T1.title FROM movies AS T1 JOIN movietheaters AS T2 ON T1.code = T2.movie WHERE T2.name = 'Odeon' OR T2.name = 'Imperial'	SELECT title FROM movies WHERE code IN (SELECT movie FROM movietheaters WHERE name = 'Odeon' OR name = 'Imperial')	join -> in-sub	0	1
1825	Find the name of the movie that is on in both Odeon and Imperial theaters.	SELECT T1.title FROM movies AS T1 JOIN movietheaters AS T2 ON T1.code = T2.movie WHERE T2.name = 'Odeon' INTERSECT SELECT T1.title FROM movies AS T1 JOIN movietheaters AS T2 ON T1.code = T2.movie WHERE T2.name = 'Imperial'	SELECT title FROM movies WHERE code IN (SELECT movie FROM movietheaters WHERE name = 'Imperial') AND code IN (SELECT movie FROM movietheaters WHERE name = 'Odeon')	intersect non-key	0	1

1826	What movie is playing at both the Odeon and Imperial theater?	SELECT T1.title FROM movies AS T1 JOIN movietheaters AS T2 ON T1.code = T2.movie WHERE T2.name = 'Odeon' INTERSECT SELECT T1.title FROM movies AS T1 JOIN movietheaters AS T2 ON T1.code = T2.movie WHERE T2.name = 'Imperial'	SELECT title FROM movies WHERE code IN (SELECT movie FROM movietheaters WHERE name = 'Imperial') AND code IN (SELECT movie FROM movietheaters WHERE name = 'Odeon')	intersect non-key	0	1
1827	Find the name of all movies that are not played in Odeon theater.	SELECT title FROM movies EXCEPT SELECT T1.title FROM movies AS T1 JOIN movietheaters AS T2 ON T1.code = T2.movie WHERE T2.name = 'Odeon'	SELECT title FROM movies WHERE NOT EXISTS (SELECT 1 FROM movietheaters WHERE movietheaters.movie = movies.code AND movietheaters.name = 'Odeon')	except non-key	0	1
1828	What are the names of every movie that is not playing at the Odeon theater?	SELECT title FROM movies EXCEPT SELECT T1.title FROM movies AS T1 JOIN movietheaters AS T2 ON T1.code = T2.movie WHERE T2.name = 'Odeon'	SELECT title FROM movies WHERE code NOT IN (SELECT movie FROM movietheaters WHERE name = 'Odeon')	except non-key	0	1
1833	Find the name of the theater that is playing the most number of movies.	SELECT name FROM movietheaters GROUP BY name ORDER BY count(*) DESC LIMIT 1	SELECT name FROM movietheaters GROUP BY name HAVING COUNT(DISTINCT movie) = (SELECT MAX(movie_count) FROM (SELECT COUNT(DISTINCT movie) AS movie_count FROM movietheaters GROUP BY name) T)	limit 1; semantic error	0	0
1834	What is the name of the theater playing the most movies?	SELECT name FROM movietheaters GROUP BY name ORDER BY count(*) DESC LIMIT 1	SELECT name FROM movietheaters GROUP BY name HAVING COUNT(DISTINCT movie) = (SELECT MAX(movie_count) FROM (SELECT COUNT(DISTINCT movie) AS movie_count FROM movietheaters GROUP BY name) T)	limit 1; semantic error	0	0
1835	Find the name of the movie that is played in the most number of theaters.	SELECT T1.title FROM movies AS T1 JOIN movietheaters AS T2 ON T1.code = T2.movie GROUP BY T1.title ORDER BY count(*) DESC LIMIT 1	WITH CNT AS (SELECT m.Title, COUNT(mt.Code) AS cnt FROM Movies m LEFT JOIN MovieTheaters mt ON m.Code = mt.Movie GROUP BY m.Code) SELECT Title FROM CNT WHERE cnt = (SELECT MAX(cnt) FROM CNT)	join -> left join; limit 1	0	0
1836	What is the name of the film playing at the most number of theaters?	SELECT T1.title FROM movies AS T1 JOIN movietheaters AS T2 ON T1.code = T2.movie GROUP BY T1.title ORDER BY count(*) DESC LIMIT 1	WITH CNT AS (SELECT m.Title, COUNT(mt.Code) AS cnt FROM Movies m LEFT JOIN MovieTheaters mt ON m.Code = mt.Movie GROUP BY m.Code) SELECT Title FROM CNT WHERE cnt = (SELECT MAX(cnt) FROM CNT)	join -> left join; limit 1	0	0
1839	Find the number of movies whose rating is not null.	SELECT count(*) , rating FROM movies WHERE rating != 'null' GROUP BY rating	SELECT COUNT(*) FROM movies WHERE rating IS NOT NULL	semantic error: != 'null', redundant column, group by	0	1
1840	How many movies have a rating that is not null?	SELECT count(*) , rating FROM movies WHERE rating != 'null' GROUP BY rating	SELECT COUNT(*) FROM movies WHERE rating IS NOT NULL	semantic error: != 'null', redundant column, group by	0	1
1841	Find the name of theaters that has at least one movie playing.	SELECT name FROM movietheaters GROUP BY name HAVING count(*) >= 1	SELECT name FROM movietheaters GROUP BY name HAVING count(movie) >= 1	semantic error: count null	1	0
1842	What are the names of every theater with at least one movie playing?	SELECT name FROM movietheaters GROUP BY name HAVING count(*) >= 1	SELECT name FROM movietheaters GROUP BY name HAVING count(movie) >= 1	semantic error: count null	1	0
1843	Select the name of all movie theaters that are not currently showing a movie.	SELECT DISTINCT name FROM MovieTheaters WHERE Movie = 'null'	SELECT Name FROM MovieTheaters GROUP BY Name HAVING COUNT(Movie) = 0	semantic error	1	0
1844	What are the names of all cinemas not showing any movies?	SELECT DISTINCT name FROM MovieTheaters WHERE Movie = 'null'	SELECT Name FROM MovieTheaters GROUP BY Name HAVING COUNT(Movie) = 0	semantic error	1	0
1851	Show all information of all unrated movies.	SELECT * FROM movies WHERE rating = 'null'	SELECT * FROM movies WHERE rating IS NULL	semantic error: = 'null'	1	0

1852	What is all the information about the unrated movies?	SELECT * FROM movies WHERE rating = 'null'	SELECT * FROM movies WHERE rating IS NULL	semantic error: = 'null'	1	0
1853	Show the titles of movies not currently being shown in any theaters.	SELECT Title FROM Movies WHERE Code NOT IN (SELECT Movie FROM MovieTheaters WHERE Movie != 'null')	SELECT title FROM movies WHERE code NOT IN (SELECT movie FROM movietheaters)	semantic error: != 'null'	1	0
1854	What are the names of the movies not being shown in any theaters?	SELECT Title FROM Movies WHERE Code NOT IN (SELECT Movie FROM MovieTheaters WHERE Movie != 'null')	SELECT title FROM movies WHERE code NOT IN (SELECT movie FROM movietheaters)	semantic error: != 'null'	0	0
1855	Who received the heaviest package?	SELECT T2.Name FROM PACKAGE AS T1 JOIN Client AS T2 ON T1.Recipient = T2.AccountNumber ORDER BY T1.Weight DESC LIMIT 1	SELECT name FROM client WHERE accountnumber IN (SELECT recipient FROM package WHERE weight = (SELECT MAX(weight) FROM package))	limit 1	0	1
1856	What is the name of the client who received the heaviest package?	SELECT T2.Name FROM PACKAGE AS T1 JOIN Client AS T2 ON T1.Recipient = T2.AccountNumber ORDER BY T1.Weight DESC LIMIT 1	SELECT name FROM client WHERE accountnumber IN (SELECT recipient FROM package WHERE weight = (SELECT MAX(weight) FROM package))	limit 1	1	0
1868	What is the number of all packages that Leo Wong sent?	SELECT T1.PackageNumber FROM PACKAGE AS T1 JOIN Client AS T2 ON T1.Sender = T2.AccountNumber WHERE T2.Name = "Leo Wong";	SELECT COUNT(packagenumber) FROM package JOIN client ON package.sender = client.accountnumber WHERE client.name = 'Leo Wong'	nlq vague: number	0	1
1869	List all package numbers received by Leo Wong?	select t1.packagenumber from package as t1 join client as t2 on t1.recipient = t2.accountnumber where t2.name = "leo wong";	SELECT p.packagenumber FROM package p JOIN client c ON p.recipient = c.accountnumber WHERE c.name = 'Leo Wong'	str	0	1
1871	List all package sent or received by Leo Wong.	SELECT DISTINCT T1.PackageNumber FROM PACKAGE AS T1 JOIN Client AS T2 ON T1.Sender = T2.AccountNumber OR T1.Recipient = T2.AccountNumber WHERE T2.Name = "Leo Wong"	SELECT p.PackageNumber FROM Package AS p JOIN Client AS c1 ON p.Sender = c1.AccountNumber JOIN Client AS c2 ON p.Recipient = c2.AccountNumber WHERE c1.Name = 'Leo Wong' OR c2.Name = 'Leo Wong'	redundant distinct; join -> in-sub (join condition)	1	0
1873	Count the number of packages sent by Ogden Wernstrom and received by Leo Wong.	SELECT T1.PackageNumber FROM PACKAGE AS T1 JOIN Client AS T2 ON T1.Sender = T2.AccountNumber WHERE T2.Name = "Ogden Wernstrom" INTERSECT SELECT T1.PackageNumber FROM PACKAGE AS T1 JOIN Client AS T2 ON T1.Recipient = T2.AccountNumber WHERE T2.Name = "Leo Wong"	SELECT COUNT(*) FROM package JOIN client AS sender ON package.sender = sender.accountnumber JOIN client AS recipient ON package.recipient = recipient.accountnumber WHERE sender.name = 'Ogden Wernstrom' AND recipient.name = 'Leo Wong'	semantic error	0	1
1874	How many packages sent by Ogden Wernstrom and received by Leo Wong?	SELECT T1.PackageNumber FROM PACKAGE AS T1 JOIN Client AS T2 ON T1.Sender = T2.AccountNumber WHERE T2.Name = "Ogden Wernstrom" INTERSECT SELECT T1.PackageNumber FROM PACKAGE AS T1 JOIN Client AS T2 ON T1.Recipient = T2.AccountNumber WHERE T2.Name = "Leo Wong"	SELECT COUNT(*) FROM package JOIN client AS sender ON package.sender = sender.accountnumber JOIN client AS recipient ON package.recipient = recipient.accountnumber WHERE sender.name = 'Ogden Wernstrom' AND recipient.name = 'Leo Wong'	semantic error	1	0
1877	What is the heaviest package sent by the clients which 'John' is part of their name? List package number and weight.	SELECT T1.PackageNumber , max(T1.Weight) FROM PACKAGE AS T1 JOIN Client AS T2 ON T1.Sender = T2.AccountNumber WHERE T2.Name LIKE 'John';	WITH Weights AS (SELECT p.PackageNumber, p.Weight FROM Package AS p JOIN Client AS c ON p.Sender = c.AccountNumber WHERE c.Name LIKE '%John%') SELECT * FROM Weights WHERE Weight = (SELECT MAX(Weight) FROM Weights)	semantic error	0	0
1878	What is the package number and weight of the heaviest package that was sent by a client named John or something similar?	SELECT T1.PackageNumber , max(T1.Weight) FROM PACKAGE AS T1 JOIN Client AS T2 ON T1.Sender = T2.AccountNumber WHERE T2.Name LIKE 'John';	WITH Weights AS (SELECT p.PackageNumber, p.Weight FROM Package AS p JOIN Client AS c ON p.Sender = c.AccountNumber WHERE c.Name LIKE '%John%') SELECT * FROM Weights WHERE Weight = (SELECT MAX(Weight) FROM Weights)	semantic error	0	0

1879	List package number and weight of top 3 lightest packages.	SELECT PackageNumber , Weight FROM PACKAGE ORDER BY Weight ASC LIMIT 3;	SELECT PackageNumber, Weight FROM (SELECT PackageNumber, Weight, RANK() OVER (ORDER BY Weight) AS rn FROM Package) t WHERE rn <= 3	limit n	0	0
1880	What is the package number and weight of the 3 lightest packages?	SELECT PackageNumber , Weight FROM PACKAGE ORDER BY Weight ASC LIMIT 3;	SELECT PackageNumber, Weight FROM (SELECT PackageNumber, Weight, RANK() OVER (ORDER BY Weight) AS rn FROM Package) t WHERE rn <= 3	limit n	1	0
1881	Who sent most number of packages? List client name and number of packages sent by that client.	SELECT T2.Name , count(*) FROM PACKAGE AS T1 JOIN Client AS T2 ON T1.Sender = T2.AccountNumber GROUP BY T1.Sender ORDER BY count(*) DESC LIMIT 1;	WITH PackageCount AS (SELECT c.Name, COUNT(p.PackageNumber) AS cnt FROM Client c LEFT JOIN Package p ON c.AccountNumber = p.Sender GROUP BY c.AccountNumber) SELECT Name, cnt FROM PackageCount WHERE cnt = (SELECT MAX(cnt) FROM PackageCount)	join-> left join; limit 1	0	0
1882	What is the name of the client who sent the most packages and how many were there?	SELECT T2.Name , count(*) FROM PACKAGE AS T1 JOIN Client AS T2 ON T1.Sender = T2.AccountNumber GROUP BY T1.Sender ORDER BY count(*) DESC LIMIT 1;	WITH PackageCount AS (SELECT c.Name, COUNT(p.PackageNumber) AS cnt FROM Client c LEFT JOIN Package p ON c.AccountNumber = p.Sender GROUP BY c.AccountNumber) SELECT Name, cnt FROM PackageCount WHERE cnt = (SELECT MAX(cnt) FROM PackageCount)	join-> left join; limit 1	0	0
1883	Who received least number of packages ? List client name and number of packages received by that client .	select t2.name , count(*) from package as t1 join client as t2 on t1.recipient = t2.accountnumber group by t1.recipient order by count(*) limit 1;	WITH PackageCount AS (SELECT c.Name, COUNT(p.PackageNumber) AS cnt FROM Client c LEFT JOIN Package p ON c.AccountNumber = p.Recipient GROUP BY c.AccountNumber) SELECT Name, cnt FROM PackageCount WHERE cnt = (SELECT MIN(cnt) FROM PackageCount)	join-> left join; limit 1	1	0
1884	What is the smallest number of packages received and by whom ?	select t2.name , count(*) from package as t1 join client as t2 on t1.recipient = t2.accountnumber group by t1.recipient order by count(*) limit 1;	WITH PackageCount AS (SELECT c.Name, COUNT(p.PackageNumber) AS cnt FROM Client c LEFT JOIN Package p ON c.AccountNumber = p.Recipient GROUP BY c.AccountNumber) SELECT Name, cnt FROM PackageCount WHERE cnt = (SELECT MIN(cnt) FROM PackageCount)	join-> left join; limit 1	0	0
1885	Who sent more than one packages? List the client's name.	SELECT T2.Name , count(*) FROM PACKAGE AS T1 JOIN Client AS T2 ON T1.Sender = T2.AccountNumber GROUP BY T1.Sender HAVING count(*) > 1;	SELECT name FROM client WHERE accountnumber IN (SELECT sender FROM package GROUP BY sender HAVING COUNT(packagenum) > 1)	semantic error: redundant column	0	1
1886	What is the name of all clients who sent more than one package?	SELECT T2.Name , count(*) FROM PACKAGE AS T1 JOIN Client AS T2 ON T1.Sender = T2.AccountNumber GROUP BY T1.Sender HAVING count(*) > 1;	SELECT name FROM client WHERE accountnumber IN (SELECT sender FROM package GROUP BY sender HAVING COUNT(*) > 1)	semantic error: redundant column	0	1
1900	What are the ids for all shipments on the planet Mars that Turanga Leela manages?	SELECT T1.ShipmentID FROM Shipment AS T1 JOIN Planet AS T2 ON T1.Planet = T2.PlanetID JOIN Employee AS T3 ON T3.EmployeeID = T1.Manager WHERE T2.Name = "Mars" OR T3.Name = "Turanga Leela";	SELECT shipment.shipmentid FROM shipment JOIN planet ON shipment.planet = planet.planetid JOIN employee ON shipment.manager = employee.employeeid WHERE planet.name = 'Mars' AND employee.name = 'Turanga Leela'	semantic error: or -> and	0	1
1901	What is the total shipments in each planet? List the planet name and total shipments.	SELECT T2.Name , count(*) FROM Shipment AS T1 JOIN Planet AS T2 ON T1.Planet = T2.PlanetID GROUP BY T1.Planet;	SELECT name, (SELECT COUNT(*) FROM shipment WHERE shipment.planet = planet.planetid) AS total_shipments FROM planet	join -> left join	0	1
1902	How many shipments take place on each planet?	SELECT T2.Name , count(*) FROM Shipment AS T1 JOIN Planet AS T2 ON T1.Planet = T2.PlanetID GROUP BY T1.Planet;	SELECT name, (SELECT COUNT(shipmentid) FROM shipment WHERE planet = planetid) AS Shipments FROM planet	join -> left join	0	1
1903	Which planet has most shipments? List the planet name.	SELECT T2.Name FROM Shipment AS T1 JOIN Planet AS T2 ON T1.Planet = T2.PlanetID GROUP BY T1.Planet ORDER BY count(*) DESC LIMIT 1;	WITH CNT AS (SELECT p.Name, COUNT(ShipmentID) AS cnt FROM Planet p LEFT JOIN Shipment s ON s.Planet = p.PlanetID GROUP BY p.PlanetID) SELECT Name FROM CNT WHERE cnt = (SELECT MAX(cnt) FROM CNT)	limit 1; join -> left join	0	0

1904	What is the name of the planet with the most shipments?	SELECT T2.Name FROM Shipment AS T1 JOIN Planet AS T2 ON T1.Planet = T2.PlanetID GROUP BY T1.Planet ORDER BY count(*) DESC LIMIT 1;	WITH CNT AS (SELECT p.Name, COUNT(ShipmentID) AS cnt FROM Planet p LEFT JOIN Shipment s ON s.Planet = p.PlanetID GROUP BY p.PlanetID) SELECT Name FROM CNT WHERE cnt = (SELECT MAX(cnt) FROM CNT)	limit 1; join -> left join	0	0
1909	Calculate total weight of package shipped in each planet . show the name of each planet .	select t3.name , sum(t1.weight) from package as t1 join shipment as t2 on t1.shipment = t2.shipmentid join planet as t3 on t2.planet = t3.planetid group by t2.planet;	SELECT P.NAME AS PLANET_NAME, TOTAL_WEIGHT FROM PLANET P LEFT JOIN (SELECT SHIPMENT.PLANET, SUM(PACKAGE.WEIGHT) AS TOTAL_WEIGHT FROM SHIPMENT JOIN PACKAGE ON SHIPMENT.SHIPMENTID = PACKAGE.SHIPMENT GROUP BY SHIPMENT.PLANET) S ON P.PLANETID = S.PLANET ORDER BY P.NAME	join -> left join	0	1
1910	what is the total package weight for each planet, list its name ?	select t3.name , sum(t1.weight) from package as t1 join shipment as t2 on t1.shipment = t2.shipmentid join planet as t3 on t2.planet = t3.planetid group by t2.planet;	SELECT P.NAME AS PLANET_NAME, TOTAL_WEIGHT FROM PLANET P LEFT JOIN (SELECT SHIPMENT.PLANET, SUM(PACKAGE.WEIGHT) AS TOTAL_WEIGHT FROM SHIPMENT JOIN PACKAGE ON SHIPMENT.SHIPMENTID = PACKAGE.SHIPMENT GROUP BY SHIPMENT.PLANET) S ON P.PLANETID = S.PLANET ORDER BY P.NAME	join -> left join	1	0
1919	Which employees do not have clearance in Mars? List employee's name.	SELECT Name FROM Employee EXCEPT SELECT T2.Name FROM Has_Clearance AS T1 JOIN Employee AS T2 ON T1.Employee = T2.EmployeeID JOIN Planet AS T3 ON T1.Planet = T3.PlanetID WHERE T3.Name = 'Mars';	SELECT e.name FROM employee e WHERE NOT EXISTS (SELECT 1 FROM has_clearance h JOIN planet p ON h.planet = p.planetid WHERE h.employee = e.employeeid AND p.name = 'Mars')	except non-key	0	1
1920	What are the names of all employees who don't have clearance on Mars?	SELECT Name FROM Employee EXCEPT SELECT T2.Name FROM Has_Clearance AS T1 JOIN Employee AS T2 ON T1.Employee = T2.EmployeeID JOIN Planet AS T3 ON T1.Planet = T3.PlanetID WHERE T3.Name = 'Mars';	SELECT e.name FROM employee e WHERE NOT EXISTS (SELECT 1 FROM has_clearance h INNER JOIN planet p ON h.planet = p.planetid WHERE h.employee = e.employeeid AND p.name = 'Mars')	except non-key	0	1
1921	Which employees have clearance in Omega III? List employees' name.	SELECT T2.Name FROM Has_Clearance AS T1 JOIN Employee AS T2 ON T1.Employee = T2.EmployeeID JOIN Planet AS T3 ON T1.Planet = T3.PlanetID WHERE T3.Name = 'Omega III';	SELECT name FROM employee WHERE employeeid IN (SELECT employee FROM has_clearance WHERE planet IN (SELECT planetid FROM planet WHERE name = 'Omega III'))	join -> in-sub	0	1
1922	What are the names of all employees with clearance on Omega III?	SELECT T2.Name FROM Has_Clearance AS T1 JOIN Employee AS T2 ON T1.Employee = T2.EmployeeID JOIN Planet AS T3 ON T1.Planet = T3.PlanetID WHERE T3.Name = 'Omega III';	SELECT e.name FROM employee e WHERE EXISTS (SELECT 1 FROM has_clearance h JOIN planet p ON p.planetid = h.planet WHERE h.employee = e.employeeid AND p.name = 'Omega III')	join -> in-sub	0	1
1929	Find the number of employees who do not have clearance in Mars .	select count(*) from employee where employeeid not in (select t2.employeeid from has_clearance as t1 join employee as t2 on t1.employee = t2.employeeid join planet as t3 on t1.planet = t3.planetid where t3.name = "mars");	SELECT COUNT(DISTINCT e.employeeid) FROM employee e WHERE e.employeeid NOT IN (SELECT h.employee FROM has_clearance h JOIN planet p ON h.planet = p.planetid WHERE p.name = 'Mars')	str	0	1
1930	What is the number of employees that do not have clearance on Mars ?	select count(*) from employee where employeeid not in (select t2.employeeid from has_clearance as t1 join employee as t2 on t1.employee = t2.employeeid join planet as t3 on t1.planet = t3.planetid where t3.name = "mars");	SELECT COUNT(employeeid) FROM employee WHERE NOT EXISTS (SELECT 1 FROM has_clearance JOIN planet ON has_clearance.planet = planet.planetid WHERE has_clearance.employee = employee.employeeid AND planet.name = 'Mars')	str	0	1
1943	How many players have rank of the year smaller than 3?	SELECT count(*) FROM player WHERE Rank_of_the_year <= 3	SELECT COUNT(DISTINCT player_id) FROM player WHERE rank_of_the_year < 3	semantic error: predicate < and <=	0	1
1949	Please show the names and rank of players that have played the game titled "Super Mario World".	SELECT T3.Player_name , T3.rank_of_the_year FROM game AS T1 JOIN game_player AS T2 ON T1.Game_ID = T2.Game_ID JOIN player AS T3 ON T2.Player_ID = T3.Player_ID WHERE T1.Title = "Super Mario World"	SELECT player_name, rank_of_the_year FROM player WHERE player_id IN (SELECT player_id FROM game_player WHERE game_id IN (SELECT game_id FROM game WHERE title = 'Super Mario World'))	join -> in-sub	0	1

1950	What are the names and ranks of players who have played the game with the title "Super Mario World"?	SELECT T3.Player_name , T3.rank_of_the_year FROM game AS T1 JOIN game_player AS T2 ON T1.Game_ID = T2.Game_ID JOIN player AS T3 ON T2.Player_ID = T3.Player_ID WHERE T1.Title = "Super Mario World"	SELECT player_name, rank_of_the_year FROM player WHERE player_id IN (SELECT game_player.player_id FROM game_player JOIN game ON game_player.game_id = game.game_id WHERE game.title = 'Super Mario World');	join -> in-sub	0	1
1953	What is the average number of units sold in millions of games played by players with position "Guard"?	SELECT avg(Units_sold_Millions) FROM game AS T1 JOIN game_player AS T2 ON T1.Game_ID = T2.Game_ID JOIN player AS T3 ON T2.Player_ID = T3.Player_ID WHERE T3.Position = "Guard"	SELECT AVG(units_sold_millions) FROM game WHERE game_id IN (SELECT game_id FROM game_player WHERE player_id IN (SELECT player_id FROM player WHERE position = 'Guard'))	join -> in-sub	0	1
1954	Return the average number of units sold in millions among games played by players who have the position Guard.	SELECT avg(Units_sold_Millions) FROM game AS T1 JOIN game_player AS T2 ON T1.Game_ID = T2.Game_ID JOIN player AS T3 ON T2.Player_ID = T3.Player_ID WHERE T3.Position = "Guard"	SELECT AVG(units_sold_millions) FROM game WHERE game_id IN (SELECT gp.game_id FROM game_player gp JOIN player p ON gp.player_id = p.player_id WHERE p.position = 'Guard')	join -> in-sub	0	1
1961	List the name of franchise that have the most number of games.	SELECT Franchise FROM game GROUP BY Franchise ORDER BY COUNT(*) DESC LIMIT 1	SELECT franchise FROM game GROUP BY franchise HAVING COUNT(*) = (SELECT MAX(game_count) FROM (SELECT COUNT(game_id) as game_count FROM game GROUP BY franchise))	limit 1	1	0
1962	Which franchise has the most games?	SELECT Franchise FROM game GROUP BY Franchise ORDER BY COUNT(*) DESC LIMIT 1	SELECT franchise FROM game GROUP BY franchise HAVING COUNT(*) = (SELECT MAX(game_count) FROM (SELECT COUNT(game_id) as game_count FROM game GROUP BY franchise))	limit 1	0	1
1967	Show the title of games that are played by both players from college "Oklahoma" and players from college "Auburn".	SELECT T1.Title FROM game AS T1 JOIN game_player AS T2 ON T1.Game_ID = T2.Game_ID JOIN player AS T3 ON T2.Player_ID = T3.Player_ID WHERE T3.College = "Oklahoma" INTERSECT SELECT T1.Title FROM game AS T1 JOIN game_player AS T2 ON T1.Game_ID = T2.Game_ID JOIN player AS T3 ON T2.Player_ID = T3.Player_ID WHERE T3.College = "Auburn"	SELECT title FROM game AS g WHERE EXISTS (SELECT 1 FROM game_player AS gp JOIN player AS p ON gp.player_id = p.player_id WHERE gp.game_id = g.game_id AND p.college = 'Auburn') AND EXISTS (SELECT 1 FROM game_player AS gp JOIN player AS p ON gp.player_id = p.player_id WHERE gp.game_id = g.game_id AND p.college = 'Oklahoma')	intersect non-key	0	0
1968	What are the titles of games that are played by players from Oklahoma college or Auburn college?	SELECT T1.Title FROM game AS T1 JOIN game_player AS T2 ON T1.Game_ID = T2.Game_ID JOIN player AS T3 ON T2.Player_ID = T3.Player_ID WHERE T3.College = "Oklahoma" INTERSECT SELECT T1.Title FROM game AS T1 JOIN game_player AS T2 ON T1.Game_ID = T2.Game_ID JOIN player AS T3 ON T2.Player_ID = T3.Player_ID WHERE T3.College = "Auburn"	SELECT title FROM game AS g WHERE EXISTS (SELECT 1 FROM game_player AS gp JOIN player AS p ON gp.player_id = p.player_id WHERE gp.game_id = g.game_id AND p.college = 'Auburn') AND EXISTS (SELECT 1 FROM game_player AS gp JOIN player AS p ON gp.player_id = p.player_id WHERE gp.game_id = g.game_id AND p.college = 'Oklahoma')	intersect non-key	0	0
1971	Show the title of games that are not played by any player who is in the Guard position.	SELECT Title FROM game EXCEPT SELECT T1.Title FROM game AS T1 JOIN game_player AS T2 ON T1.Game_ID = T2.Game_ID JOIN player AS T3 ON T2.Player_ID = T3.Player_ID WHERE T3.Position = "Guard"	SELECT title FROM game WHERE game_id NOT IN (SELECT g.game_id FROM game g JOIN game_player gp ON g.game_id = gp.game_id JOIN player p ON gp.player_id = p.player_id WHERE p.position = 'Guard')	except non-key	0	0
1972	What are the titles of games not played by any players who play the Guard position?	SELECT Title FROM game EXCEPT SELECT T1.Title FROM game AS T1 JOIN game_player AS T2 ON T1.Game_ID = T2.Game_ID JOIN player AS T3 ON T2.Player_ID = T3.Player_ID WHERE T3.Position = "Guard"	SELECT title FROM game WHERE game_id NOT IN (SELECT g.game_id FROM game g JOIN game_player gp ON g.game_id = gp.game_id JOIN player p ON gp.player_id = p.player_id WHERE p.position = 'Guard')	except non-key	0	0

1979	Find the name of the publisher whose monthly profit is the highest.	SELECT name FROM press ORDER BY Month_Profits_billion DESC LIMIT 1	SELECT press.name FROM press WHERE press.month_profits_billion = (SELECT MAX(month_profits_billion) FROM press)	limit 1	0	1
1980	Which press has the largest monthly profit? Give me the press name.	SELECT name FROM press ORDER BY Month_Profits_billion DESC LIMIT 1	SELECT p.name FROM press p WHERE p.month_profits_billion = (SELECT MAX(month_profits_billion) FROM press)	limit 1	0	1
1993	Find the titles and publish dates of the top 5 best sale books.	SELECT title , release_date FROM book ORDER BY sale_amount DESC LIMIT 5	SELECT b.Title, b.release_date FROM book b WHERE EXISTS (SELECT 1 FROM (SELECT sale_amount FROM book ORDER BY sale_amount DESC LIMIT 5) top WHERE top.sale_amount = b.sale_amount)	limit n	1	0
1994	What are the 5 best books in terms of sale amount? Give me their titles and release dates.	SELECT title , release_date FROM book ORDER BY sale_amount DESC LIMIT 5	SELECT b.Title, b.release_date FROM book b WHERE EXISTS (SELECT 1 FROM (SELECT sale_amount FROM book ORDER BY sale_amount DESC LIMIT 5) top WHERE top.sale_amount = b.sale_amount)	limit n	1	0
1997	Find the name of authors who publish their books in both "MM" and "LT" series.	SELECT t1.name FROM author AS t1 JOIN book AS t2 ON t1.author_id = t2.author_id WHERE t2.book_series = 'MM' INTERSECT SELECT t1.name FROM author AS t1 JOIN book AS t2 ON t1.author_id = t2.author_id WHERE t2.book_series = 'LT'	SELECT name FROM author WHERE EXISTS (SELECT 1 FROM book WHERE author_id = author.author_id AND book_series = 'MM') AND EXISTS (SELECT 1 FROM book WHERE author_id = author.author_id AND book_series = 'LT')	intersect non-key	0	1
1998	Which authors publish books in both "MM" and "LT" series? Give me the author names.	SELECT t1.name FROM author AS t1 JOIN book AS t2 ON t1.author_id = t2.author_id WHERE t2.book_series = 'MM' INTERSECT SELECT t1.name FROM author AS t1 JOIN book AS t2 ON t1.author_id = t2.author_id WHERE t2.book_series = 'LT'	SELECT author.name FROM author WHERE author.author_id IN (SELECT b.author_id FROM book b WHERE b.book_series = 'LT') AND author.author_id IN (SELECT b.author_id FROM book b WHERE b.book_series = 'MM')	intersect non-key	0	0
2003	Find the title, author name, and publisher name for the top 3 best sales books.	SELECT t1.name , t2.title , t3.name FROM author AS t1 JOIN book AS t2 ON t1.author_id = t2.author_id JOIN press AS t3 ON t2.press_id = t3.press_id ORDER BY t2.sale_amount DESC LIMIT 3	SELECT b.Title, a.Name, p.Name FROM book b JOIN press p ON b.Press_ID = p.Press_ID JOIN author a ON b.Author_ID = a.Author_ID WHERE EXISTS (SELECT 1 FROM (SELECT sale_amount FROM book ORDER BY sale_amount DESC LIMIT 3) top WHERE top.sale_amount = b.sale_amount)	limit n	1	0
2004	What are the 3 best selling books? Show their titles, author names, and press names.	SELECT t1.name , t2.title , t3.name FROM author AS t1 JOIN book AS t2 ON t1.author_id = t2.author_id JOIN press AS t3 ON t2.press_id = t3.press_id ORDER BY t2.sale_amount DESC LIMIT 3	SELECT b.Title, a.Name, p.Name FROM book b JOIN press p ON b.Press_ID = p.Press_ID JOIN author a ON b.Author_ID = a.Author_ID WHERE EXISTS (SELECT 1 FROM (SELECT sale_amount FROM book ORDER BY sale_amount DESC LIMIT 3) top WHERE top.sale_amount = b.sale_amount)	limit n	1	0
2005	Find the name and total book sale amount of each press.	SELECT sum(t1.sale_amount) , t2.name FROM book AS t1 JOIN press AS t2 ON t1.press_id = t2.press_id GROUP BY t1.press_id	SELECT p.Name, IFNULL((SELECT SUM(b.sale_amount) FROM book b WHERE b.Press_ID = p.Press_ID), 0) FROM press p	join -> left join	1	0
2006	What are the name and total book sale amount of each press?	SELECT sum(t1.sale_amount) , t2.name FROM book AS t1 JOIN press AS t2 ON t1.press_id = t2.press_id GROUP BY t1.press_id	SELECT p.Name, IFNULL((SELECT SUM(b.sale_amount) FROM book b WHERE b.Press_ID = p.Press_ID), 0) FROM press p	join -> left join	1	0
2007	Find the number of books that are sold more than 1000 for each publisher. List the press name as well.	SELECT count(*) , t2.name FROM book AS t1 JOIN press AS t2 ON t1.press_id = t2.press_id WHERE sale_amount > 1000 GROUP BY t2.name	SELECT press.name, (SELECT COUNT(*) FROM book WHERE book.press_id = press.press_id AND book.sale_amount > 1000) AS num_books FROM press	group by non-key; join -> left join (right)	0	0
2008	For each press, return its name and the number of books that have sale amount above 1000.	SELECT count(*) , t2.name FROM book AS t1 JOIN press AS t2 ON t1.press_id = t2.press_id WHERE sale_amount > 1000 GROUP BY t2.name	SELECT press.name, (SELECT COUNT(*) FROM book WHERE book.press_id = press.press_id AND book.sale_amount > 1000) AS num_books FROM press	group by non-key; join -> left join (right)	0	1

2009	What is the name of the author of best selling book?	SELECT t1.name FROM author AS t1 JOIN book AS t2 ON t1.author_id = t2.author_id ORDER BY t2.sale_amount DESC LIMIT 1	WITH BestSellingBook AS (SELECT MAX(Sale_amount) AS MaxSale FROM book) SELECT a.Name FROM author a JOIN book b ON a.Author_ID = b.Author_ID, BestSellingBook WHERE b.Sale_amount = BestSellingBook.MaxSale GROUP BY a.Author_ID, a.Name	limit 1	0	0
2010	Who wrote the best selling book? Give me the author name.	SELECT t1.name FROM author AS t1 JOIN book AS t2 ON t1.author_id = t2.author_id ORDER BY t2.sale_amount DESC LIMIT 1	WITH BestSellingBook AS (SELECT MAX(Sale_amount) AS MaxSale FROM book) SELECT a.Name FROM author a JOIN book b ON a.Author_ID = b.Author_ID, BestSellingBook WHERE b.Sale_amount = BestSellingBook.MaxSale GROUP BY a.Author_ID, a.Name	limit 1	0	0
2011	find the name and gender of the author who published the most books.	SELECT t1.name , t1.gender FROM author AS t1 JOIN book AS t2 ON t1.author_id = t2.author_id GROUP BY t2.author_id ORDER BY count(*) DESC LIMIT 1	WITH BookCount AS (SELECT author.Author_ID, COUNT(book.Book_ID) AS cnt FROM author LEFT JOIN book ON author.Author_ID = book.Author_ID GROUP BY author.Author_ID) SELECT author.name, author.gender FROM author JOIN BookCount ON author.Author_ID = BookCount.Author_ID WHERE BookCount.cnt = (SELECT MAX(cnt) FROM BookCount)	limit 1	0	0
2012	Who wrote the largest number of books? Give me the author name and gender.	SELECT t1.name , t1.gender FROM author AS t1 JOIN book AS t2 ON t1.author_id = t2.author_id GROUP BY t2.author_id ORDER BY count(*) DESC LIMIT 1	WITH BookCount AS (SELECT author.Author_ID, COUNT(book.Book_ID) AS cnt FROM author LEFT JOIN book ON author.Author_ID = book.Author_ID GROUP BY author.Author_ID) SELECT author.name, author.gender FROM author JOIN BookCount ON author.Author_ID = BookCount.Author_ID WHERE BookCount.cnt = (SELECT MAX(cnt) FROM BookCount)	limit 1	0	0
2013	Find the names of the authors who did not have any book with the "Accor" press.	SELECT name FROM author EXCEPT SELECT t1.name FROM author AS t1 JOIN book AS t2 ON t1.author_id = t2.author_id JOIN press AS t3 ON t2.press_id = t3.press_id WHERE t3.name = 'Accor'	SELECT a.name FROM author a WHERE a.author_id NOT IN (SELECT b.author_id FROM book b INNER JOIN press p ON b.press_id = p.press_id WHERE p.name = 'Accor')	except non-key	0	1
2014	Which authors have never published under the "Accor" press? Give me their names.	SELECT name FROM author EXCEPT SELECT t1.name FROM author AS t1 JOIN book AS t2 ON t1.author_id = t2.author_id JOIN press AS t3 ON t2.press_id = t3.press_id WHERE t3.name = 'Accor'	SELECT name FROM author WHERE author_id NOT IN (SELECT author_id FROM book WHERE press_id IN (SELECT press_id FROM press WHERE name = 'Accor'))	except non-key	0	1
2028	Show all author names and number of documents corresponding to each.	SELECT author_name , count(*) FROM Documents GROUP BY author_name	SELECT a.author_name, (SELECT COUNT(*) FROM Documents WHERE author_name = a.author_name) FROM Authors a GROUP BY a.author_name	join -> left join	1	0
2029	What is the name of the author with most number of documents?	SELECT author_name FROM Documents GROUP BY author_name ORDER BY count(*) DESC LIMIT 1	WITH DocCount AS (SELECT a.author_name, (SELECT COUNT(*) FROM Documents WHERE author_name = a.author_name) AS cnt FROM Authors a GROUP BY a.author_name) SELECT author_name FROM DocCount WHERE cnt = (SELECT MAX(cnt) FROM DocCount)	limit 1; join -> left join	1	0
2052	Show all process ids and the number of documents in each process.	SELECT process_id , count(*) FROM Documents_processes GROUP BY process_id	SELECT p.process_id, COUNT(d.document_id) FROM business_processes AS p LEFT JOIN documents_processes AS d ON p.process_id = d.process_id GROUP BY p.process_id	join -> left join	1	0
2054	Show all staff ids and the number of document processes for each staff.	SELECT staff_id , count(*) FROM Staff_in_processes GROUP BY staff_id	SELECT staff.staff_id, COUNT(documents_processes.process_id) AS document_processes_count FROM staff LEFT JOIN staff_in_processes ON staff.staff_id = staff_in_processes.staff_id LEFT JOIN documents_processes ON staff_in_processes.document_id = documents_processes.document_id AND staff_in_processes.process_id = documents_processes.process_id GROUP BY staff.staff_id	join -> left join	1	0

2055	Show all staff role codes and the number of document processes for each role.	SELECT staff_role_code , count(*) FROM Staff_in_processes GROUP BY staff_role_code	SELECT staff_role_code, COUNT(*) FROM (SELECT DISTINCT staff_role_code, document_id, process_id FROM Staff_in_Processes) t GROUP BY staff_role_code	lack distinct	1	0
2065	Show agency ids and the number of clients for each agency.	SELECT agency_id , count(*) FROM Clients GROUP BY agency_id	SELECT agency_id, (SELECT COUNT(*) FROM clients WHERE clients.agency_id = agencies.agency_id) AS num_clients FROM agencies	join -> left join	0	1
2066	How many clients does each agency have?	SELECT agency_id , count(*) FROM Clients GROUP BY agency_id	SELECT a.agency_id, COUNT(c.client_id) AS number_of_clients FROM agencies a LEFT JOIN clients c ON a.agency_id = c.agency_id GROUP BY a.agency_id	join -> left join	0	1
2067	What is the agency id and details with most number of clients?	SELECT T1.agency_id , T1.agency_details FROM Agencies AS T1 JOIN Clients AS T2 ON T1.agency_id = T2.agency_id GROUP BY T1.agency_id ORDER BY count(*) DESC LIMIT 1	WITH ClientCount AS (SELECT a.agency_id, COUNT(c.agency_id) AS cnt FROM Agencies a LEFT JOIN Clients c ON a.agency_id = c.agency_id GROUP BY a.agency_id) SELECT a.agency_id, a.agency_details FROM Agencies a JOIN ClientCount c ON a.agency_id = c.agency_id WHERE c.cnt = (SELECT MAX(cnt) FROM ClientCount)	limit 1; join -> left join (right)	0	0
2068	Return the agency id and details for the agency with the greatest number of clients.	SELECT T1.agency_id , T1.agency_details FROM Agencies AS T1 JOIN Clients AS T2 ON T1.agency_id = T2.agency_id GROUP BY T1.agency_id ORDER BY count(*) DESC LIMIT 1	WITH ClientCount AS (SELECT a.agency_id, COUNT(c.agency_id) AS cnt FROM Agencies a LEFT JOIN Clients c ON a.agency_id = c.agency_id GROUP BY a.agency_id) SELECT a.agency_id, a.agency_details FROM Agencies a JOIN ClientCount c ON a.agency_id = c.agency_id WHERE c.cnt = (SELECT MAX(cnt) FROM ClientCount)	limit 1; join -> left join (right)	0	0
2079	Show all agency ids and details for agencies with a client.	SELECT T1.agency_id , T1.agency_details FROM Agencies AS T1 JOIN Clients AS T2 ON T1.agency_id = T2.agency_id	SELECT DISTINCT agencies.agency_id, agencies.agency_details FROM agencies JOIN clients ON agencies.agency_id = clients.agency_id	lack distinct	0	1
2080	What are the agency ids and agency details for all agencies who have a client?	SELECT T1.agency_id , T1.agency_details FROM Agencies AS T1 JOIN Clients AS T2 ON T1.agency_id = T2.agency_id	SELECT DISTINCT agencies.agency_id, agencies.agency_details FROM agencies JOIN clients ON agencies.agency_id = clients.agency_id	lack distinct	0	1
2087	Show all client ids and the number of invoices for each client.	SELECT client_id , count(*) FROM Invoices GROUP BY client_id	SELECT c.client_id, IFNULL(COUNT(i.invoice_id), 0) as total_invoices FROM clients c LEFT JOIN invoices i ON c.client_id = i.client_id GROUP BY c.client_id	join -> left join	0	1
2088	How many invoices are there for each client id?	SELECT client_id , count(*) FROM Invoices GROUP BY client_id	SELECT c.client_id, COUNT(i.invoice_id) as total_invoices FROM clients c LEFT JOIN invoices i ON c.client_id = i.client_id GROUP BY c.client_id	join -> left join	1	0
2089	List the client id and detail with most number of invoices.	SELECT T1.client_id , T2.client_details FROM Invoices AS T1 JOIN Clients AS T2 ON T1.client_id = T2.client_id GROUP BY T1.client_id ORDER BY count(*) DESC LIMIT 1	WITH InvoiceCount AS (SELECT c.client_id, COUNT(i.client_id) AS cnt FROM Clients c LEFT JOIN Invoices i ON c.client_id = i.client_id GROUP BY c.client_id) SELECT c.client_id, c.client_details FROM Clients c JOIN InvoiceCount i ON c.client_id = i.client_id WHERE i.cnt = (SELECT MAX(cnt) FROM InvoiceCount)	limit 1; join -> left join (right)	0	0
2090	What are the client id and details for the client with the most invoices?	SELECT T1.client_id , T2.client_details FROM Invoices AS T1 JOIN Clients AS T2 ON T1.client_id = T2.client_id GROUP BY T1.client_id ORDER BY count(*) DESC LIMIT 1	WITH InvoiceCount AS (SELECT c.client_id, COUNT(i.client_id) AS cnt FROM Clients c LEFT JOIN Invoices i ON c.client_id = i.client_id GROUP BY c.client_id) SELECT c.client_id, c.client_details FROM Clients c JOIN InvoiceCount i ON c.client_id = i.client_id WHERE i.cnt = (SELECT MAX(cnt) FROM InvoiceCount)	limit 1; join -> left join (right)	0	0

2095	What is the invoice status code with most number of invoices.	SELECT invoice_status FROM Invoices GROUP BY invoice_status ORDER BY count(*) DESC LIMIT 1	SELECT invoice_status FROM invoices GROUP BY invoice_status HAVING COUNT(invoice_status) = (SELECT MAX(Count) FROM (SELECT COUNT(invoice_status) Count FROM invoices GROUP BY invoice_status) Temp)	limit 1	0	1
2096	Return the invoice status that has the most invoices.	SELECT invoice_status FROM Invoices GROUP BY invoice_status ORDER BY count(*) DESC LIMIT 1	WITH cnt AS (SELECT invoice_status, COUNT(*) AS cnt FROM Invoices GROUP BY invoice_status) SELECT invoice_status FROM cnt WHERE cnt = (SELECT MAX(cnt) FROM cnt)	limit 1	1	0
2113	Show all invoice ids and the number of payments for each invoice.	SELECT invoice_id , count(*) FROM Payments GROUP BY invoice_id	SELECT invoices.invoice_id, COUNT(payments.payment_id) AS payment_count FROM invoices LEFT JOIN payments ON invoices.invoice_id = payments.invoice_id GROUP BY invoices.invoice_id	join -> left join	0	1
2114	How many payments are there for each invoice?	SELECT invoice_id , count(*) FROM Payments GROUP BY invoice_id	SELECT i.invoice_id, COUNT(p.payment_id) AS payment_count FROM invoices i LEFT JOIN payments p ON i.invoice_id = p.invoice_id GROUP BY i.invoice_id	join -> left join	0	1
2115	What is the invoice id, status code, and details for the invoice with most number of payments.	SELECT T1.invoice_id , T2.invoice_status , T2.invoice_details FROM Payments AS T1 JOIN Invoices AS T2 ON T1.invoice_id = T2.invoice_id GROUP BY T1.invoice_id ORDER BY count(*) DESC LIMIT 1	WITH invoice_payments AS (SELECT i.invoice_id, COUNT(p.invoice_id) AS total_payments FROM Invoices i LEFT JOIN Payments p ON i.invoice_id = p.invoice_id GROUP BY i.invoice_id) SELECT i.invoice_id, i.invoice_status, i.invoice_details FROM Invoices i JOIN invoice_payments ON i.invoice_id = invoice_payments.invoice_id WHERE invoice_payments.total_payments = (SELECT MAX(total_payments) FROM invoice_payments)	limit 1; join -> left join (right)	0	0
2116	Return the invoice ids, statuses, and details for invoices with the most payments?	SELECT T1.invoice_id , T2.invoice_status , T2.invoice_details FROM Payments AS T1 JOIN Invoices AS T2 ON T1.invoice_id = T2.invoice_id GROUP BY T1.invoice_id ORDER BY count(*) DESC LIMIT 1	WITH invoice_payments AS (SELECT i.invoice_id, COUNT(p.invoice_id) AS total_payments FROM Invoices i LEFT JOIN Payments p ON i.invoice_id = p.invoice_id GROUP BY i.invoice_id) SELECT i.invoice_id, i.invoice_status, i.invoice_details FROM Invoices i JOIN invoice_payments ON i.invoice_id = invoice_payments.invoice_id WHERE invoice_payments.total_payments = (SELECT MAX(total_payments) FROM invoice_payments)	limit 1; join -> left join (right)	0	0
2119	Show the agency ids and the number of staff in each agent?	SELECT agency_id , count(*) FROM Staff GROUP BY agency_id	SELECT a.agency_id, COUNT(s.staff_id) FROM agencies a LEFT JOIN staff s ON a.agency_id = s.agency_id GROUP BY a.agency_id	join -> left join	0	1
2120	Return the agency ids and number of staff in each.	SELECT agency_id , count(*) FROM Staff GROUP BY agency_id	SELECT a.agency_id, COUNT(s.staff_id) AS staff_count FROM agencies AS a LEFT JOIN staff AS s ON a.agency_id = s.agency_id GROUP BY a.agency_id	join -> left join	0	1
2121	What is the agent id and details for the agency with most staff?	SELECT T1.agency_id , T2.agency_details FROM Staff AS T1 JOIN Agencies AS T2 ON T1.agency_id = T2.agency_id GROUP BY T1.agency_id ORDER BY count(*) DESC LIMIT 1	WITH StaffCount AS (SELECT Agencies.agency_id, COUNT(Staff.agency_id) AS TotalStaff FROM Agencies LEFT JOIN Staff ON Agencies.agency_id = Staff.agency_id GROUP BY Agencies.agency_id) SELECT Agencies.agency_id, Agencies.agency_details FROM Agencies JOIN StaffCount ON Agencies.agency_id = StaffCount.agency_id WHERE StaffCount.TotalStaff = (SELECT MAX(TotalStaff) FROM StaffCount)	limit 1; join -> left join (right)	0	0

2122	Return the id and detail for the agency with the most staff.	SELECT T1.agency_id , T2.agency_details FROM Staff AS T1 JOIN Agencies AS T2 ON T1.agency_id = T2.agency_id GROUP BY T1.agency_id ORDER BY count(*) DESC LIMIT 1	WITH StaffCount AS (SELECT Agencies.agency_id, COUNT(Staff.agency_id) AS TotalStaff FROM Agencies LEFT JOIN Staff ON Agencies.agency_id = Staff.agency_id GROUP BY Agencies.agency_id) SELECT Agencies.agency_id, Agencies.agency_details FROM Agencies JOIN StaffCount ON Agencies.agency_id = StaffCount.agency_id WHERE StaffCount.TotalStaff = (SELECT MAX(TotalStaff) FROM StaffCount)	limit 1; join -> left join (right)	0	0
2125	List the client ids and the number of meeting for each client.	SELECT client_id , count(*) FROM Meetings GROUP BY client_id	SELECT cl.client_id, (SELECT COUNT(*) FROM meetings mt WHERE mt.client_id = cl.client_id) AS meetings_sum FROM clients cl	join -> left join	0	1
2126	How many meetings are there for each client id?	SELECT client_id , count(*) FROM Meetings GROUP BY client_id	SELECT c.client_id, COUNT(m.meeting_id) FROM clients c LEFT JOIN meetings m ON c.client_id = m.client_id GROUP BY c.client_id	join -> left join	0	1
2127	Show the meeting type codes and the number of meeting for each client.	SELECT meeting_type , count(*) FROM Meetings GROUP BY meeting_type	SELECT client_id, meeting_type, COUNT(meeting_id) AS meeting_count FROM meetings GROUP BY client_id, meeting_type	semantic error	1	0
2131	Show the meeting ids and the number of staff in each meeting.	SELECT meeting_id , count(*) FROM Staff_in_meetings GROUP BY meeting_id	SELECT m.meeting_id, COUNT(si.staff_id) AS TotalStaff FROM meetings m LEFT JOIN staff_in_meetings si ON m.meeting_id = si.meeting_id GROUP BY m.meeting_id	join -> left join	1	0
2132	Count the number of staff in each meeting by meeting id.	SELECT meeting_id , count(*) FROM Staff_in_meetings GROUP BY meeting_id	SELECT m.meeting_id, COUNT(si.staff_id) AS TotalStaff FROM meetings m LEFT JOIN staff_in_meetings si ON m.meeting_id = si.meeting_id GROUP BY m.meeting_id	join -> left join	0	1
2133	Show the staff id and the number of meetings attended by the staff who attended some meeting but had the lowest attendance.	SELECT staff_id , count(*) FROM Staff_in_meetings GROUP BY staff_id ORDER BY count(*) ASC LIMIT 1;	SELECT s.staff_id, COUNT(*) AS num_meetings FROM staff s JOIN staff_in_meetings sim ON s.staff_id = sim.staff_id GROUP BY s.staff_id HAVING num_meetings = (SELECT MIN(total_meetings) FROM (SELECT COUNT(*) AS total_meetings FROM staff_in_meetings GROUP BY staff_id))	limit 1	0	1
2134	What is the staff id of the staff who attended the least meetings but attended some meeting?	SELECT staff_id , count(*) FROM Staff_in_meetings GROUP BY staff_id ORDER BY count(*) ASC LIMIT 1;	SELECT s.staff_id FROM staff s JOIN staff_in_meetings sim ON s.staff_id = sim.staff_id GROUP BY s.staff_id HAVING COUNT(*) = (SELECT MIN(total_meetings) FROM (SELECT COUNT(*) AS total_meetings FROM staff_in_meetings GROUP BY staff_id))	limit 1; semantic error: redundant column	0	0
2141	What are the ids and details of the staff who have attended at least 1 meetings and have the detail with letter 's'?	SELECT staff_id , staff_details FROM staff WHERE staff_details LIKE "%s%" GROUP BY staff_id HAVING count(*) >= 1	SELECT DISTINCT staff.staff_id, staff.staff_details FROM staff JOIN staff_in_meetings ON staff.staff_id = staff_in_meetings.staff_id JOIN meetings ON staff_in_meetings.meeting_id = meetings.meeting_id WHERE staff.staff_details LIKE "%s%";	semantic error: lack table	0	1
2142	Return the ids and details of staff who have attended at least 1 meeting and have an s in their staff details?	SELECT staff_id , staff_details FROM staff WHERE staff_details LIKE "%s%" GROUP BY staff_id HAVING count(*) >= 1	SELECT DISTINCT staff.staff_id, staff.staff_details FROM staff JOIN staff_in_meetings ON staff.staff_id = staff_in_meetings.staff_id JOIN meetings ON staff_in_meetings.meeting_id = meetings.meeting_id WHERE staff.staff_details LIKE "%s%";	semantic error: lack table	0	0

Table 3: Incorrect case list of BIRD Train set.

Case Id	NL	Original SQL	Modified SQL	Tag	Follow Consistency	Correctly Fixed
243	Please list the full names of all the male clients born after the year 1990.	SELECT first, middle, last FROM client WHERE year > 1990	SELECT first, middle, last FROM client WHERE sex = 'Male' AND year > 1990;	semantic error: wrong condition	0	1
248	What is the full name of the client whose complaint on 2017/3/27 was received by MICHAL?	SELECT T1.first, T1.middle, T1.last FROM client AS T1 INNER JOIN callcenterlogs AS T2 ON T1.client_id = T2.'rand client' WHERE T2.'Date received' = '2017-03-27' AND T2.server = 'MICHAL'	SELECT first, middle, last FROM client WHERE client_id IN (SELECT "rand client" FROM callcenterlogs WHERE "Date received" = '2017-03-27' AND server = 'MICHAL');	join -> in-sub	0	1
250	Among all the clients from the New York city, how many of them have filed a complaint on the issue of Deposits and withdrawals?	SELECT COUNT(T2.Issue) FROM client AS T1 INNER JOIN events AS T2 ON T1.client_id = T2.Client_ID WHERE T2.Issue = 'Deposits and withdrawals' AND T1.city = 'New York City'	SELECT COUNT(DISTINCT T1.client_id) FROM client T1 JOIN events T2 ON T1.client_id = T2.Client_ID WHERE T1.city = 'New York City' AND T2.Issue = 'Deposits and withdrawals';	lack distinct	0	1
251	Please list the full names of all the clients whose complaints are still in progress.	SELECT T1.first, T1.middle, T1.last FROM client AS T1 INNER JOIN events AS T2 ON T1.client_id = T2.Client_ID WHERE T2.'Company response to consumer' = 'In progress'	SELECT first, middle, last FROM client WHERE client_id IN (SELECT Client_ID FROM events WHERE "Company response to consumer" = 'In progress');	join -> in-sub	0	0
252	Among the clients who did receive a timely response for their complaint, how many of them are from New York?	SELECT COUNT(T1.city) FROM client AS T1 INNER JOIN events AS T2 ON T1.client_id = T2.Client_ID WHERE T2.'Timely response' = 'No' AND T1.city = 'New York City'	SELECT COUNT(DISTINCT T1.Client_ID) FROM events T1 JOIN client T2 ON T1.Client_ID = T2.client_id WHERE T1."Timely response?" = 'Yes' AND T2.city = 'New York';	lack distinct; semantic error: wrong condition	0	1
256	What is the average number of complaints on credit cards filed by clients from New York in the 3 consecutive years starting from 2015?	SELECT CAST(COUNT(T2.'Complaint ID') AS REAL) / 3 AS average FROM client AS T1 INNER JOIN events AS T2 ON T1.client_id = T2.Client_ID WHERE strftime('%Y', T2.'Date received') BETWEEN '2015' AND '2017' AND T1.city = 'New York City' AND T2.Product = 'Credit card'	SELECT CAST(COUNT(T2.'Complaint ID') AS REAL) / 3 AS average FROM client AS T1 INNER JOIN events AS T2 ON T1.client_id = T2.Client_ID WHERE strftime('%Y', T2.'Date received') BETWEEN '2015' AND '2017' AND T1.city = 'New York' AND T2.Product = 'Credit card'	semantic error: wrong condition	0	0
270	For all the complaint callers on 2017/3/27, what percentage of the clients are females?	SELECT CAST(SUM(CASE WHEN T1.sex = 'Female' THEN 1 ELSE 0 END) AS REAL) * 100 / COUNT(T1.sex) FROM client AS T1 INNER JOIN events AS T2 ON T1.client_id = T2.Client_ID WHERE T2.'Date received' = '2017-03-27'	SELECT CAST(COUNT(DISTINCT CASE WHEN T1.sex = 'Female' THEN T1.client_id END) AS REAL) * 100 / COUNT(DISTINCT T1.client_id) FROM client AS T1 INNER JOIN events AS T2 ON T1.client_id = T2.Client_ID WHERE T2.'Date received' = '2017-03-27';	lack distinct	1	0
280	In the calls from the mountain division, how many are from teenage clients?	SELECT COUNT(T1.age) FROM client AS T1 INNER JOIN district AS T2 ON T1.district_id = T2.district_id WHERE T1.age BETWEEN 12 AND 20 AND T2.division = 'Mountain'	SELECT COUNT(DISTINCT T3.'Complaint ID') FROM district T1 JOIN client T2 ON T1.district_id = T2.district_id JOIN callcenterlogs T3 ON T2.client_id = T3."rand client" WHERE T1.division = 'Mountain' AND T2.age BETWEEN 12 AND 20;	semantic error: lack join	0	0
282	Among the clients born between 1980 and 2000, list the name of male clients who complained through referral.	SELECT T1.first, T1.middle, T1.last FROM client AS T1 INNER JOIN events AS T2 ON T1.client_id = T2.Client_ID WHERE T1.year BETWEEN 1980 AND 2000 AND T1.sex = 'Male' AND T2.'Submitted via' = 'Referral'	SELECT T1.first, T1.middle, T1.last FROM client AS T1 WHERE T1.client_id IN (SELECT T2.Client_ID FROM events AS T2 WHERE T2.'Submitted via' = 'Referral') AND T1.year BETWEEN 1980 AND 2000 AND T1.sex = 'Male';	join -> in-sub	1	0

286	Find the number of service members who complained in Syracuse.	SELECT COUNT(T1.client_id) FROM client AS T1 INNER JOIN events AS T2 ON T1.client_id = T2.Client_ID WHERE T2.Tags = 'Servicemember' AND T1.city = 'Syracuse'	SELECT COUNT(DISTINCT T1.client_id) FROM client T1 INNER JOIN events T2 ON T1.client_id = T2.Client_ID WHERE T1.city = 'Syracuse' AND T2.Tags LIKE '%Servicemember%';	lack distinct	0	1
300	Lists the last name of all clients who made a PS-type complaint and were served by TOVA.	SELECT t1.last FROM client AS T1 INNER JOIN callcenterlogs AS T2 ON T1.client_id = T2.rand client' WHERE T2.type = 'PS' AND T2.server = 'TOVA'	SELECT t1.last FROM client AS T1 WHERE T1.client_id IN (SELECT T2.rand client' FROM callcenterlogs AS T2 WHERE T2.type = 'PS' AND T2.server = 'TOVA')	join -> in-sub	1	0
317	Which state has the highest number of clients who gave a 5-star review?	SELECT T2.state_abbrev FROM reviews AS T1 INNER JOIN district AS T2 ON T1.district_id = T2.district_id WHERE T1.Stars = 5 GROUP BY T2.state_abbrev ORDER BY COUNT(T2.state_abbrev) DESC LIMIT 1	SELECT state_abbrev FROM (SELECT T2.state_abbrev, rank() over (ORDER BY COUNT(T2.state_abbrev) DESC) as rk FROM reviews AS T1 INNER JOIN district AS T2 ON T1.district_id = T2.district_id WHERE T1.Stars = 5 GROUP BY T2.state_abbrev) WHERE rk = 1	limit 1	0	0
323	How many clients who live in New York City submitted their complaints via fax?	SELECT COUNT(T1.client_id) FROM client AS T1 INNER JOIN events AS T2 ON T1.client_id = T2.Client_ID WHERE T1.city = 'New York City' AND T2.Submitted via' = 'Fax'	SELECT COUNT(DISTINCT T1.client_id) FROM client T1 JOIN events T2 ON T1.client_id = T2.Client_ID WHERE T1.city = 'New York City' AND T2.Submitted via" = 'Fax';	lack distinct	0	1
346	List down the email of client whose complaint is type 'PS'.	SELECT T1.email FROM client AS T1 INNER JOIN callcenterlogs AS T2 ON T1.client_id = T2.rand client' WHERE T2.type = 'PS'	SELECT T2.email FROM client T2 WHERE T2.client_id IN (SELECT T1.rand client' FROM callcenterlogs T1 WHERE T1.type = 'PS');	join -> in-sub	1	0
347	Among the elderlies, state the last name of whose complaint is handled in server YIFAT?	SELECT T1.last FROM client AS T1 INNER JOIN callcenterlogs AS T2 ON T1.client_id = T2.rand client' WHERE T1.age > 65 AND T2.server = 'YIFAT'	SELECT last FROM client WHERE client_id IN (SELECT "rand client" FROM callcenterlogs WHERE server = 'YIFAT') AND age > 65;	semantic error: wrong condition; join -> in-sub	0	1
349	List down the full name of clients who have disputed the response from company.	SELECT T1.first, T1.middle, T1.last FROM client AS T1 INNER JOIN events AS T2 ON T1.client_id = T2.Client_ID WHERE T2.Consumer disputed _c = 'Yes'	SELECT first, middle, last FROM client WHERE client_id IN (SELECT Client_ID FROM events WHERE 'Consumer disputed _c = 'Yes')	join -> in-sub	0	0
366	Between 1/1/2017 and 4/1/2017, what is the average server time of calls under the server DARMON?	SELECT AVG(CAST(SUBSTR(ser_time, 4, 2) AS REAL)) FROM callcenterlogs WHERE 'Date received' BETWEEN '2017-01-01' AND '2017-04-01'	SELECT avg((CAST(SUBSTR(ser_time, 1, 2) AS INTEGER) * 3600) + (CAST(SUBSTR(ser_time, 4, 2) AS INTEGER) * 60) + CAST(SUBSTR(ser_time, 7, 2) AS INTEGER)) AS avg_seconds FROM callcenterlogs WHERE server = 'DARMON' AND "Date received" BETWEEN '2017-01-01' AND '2017-04-01'	semantic error: lack condition; output column	0	0
370	List the top five cities in terms of the number of 5-star ratings in 2016 reviews, in descending order.	SELECT T2.city FROM reviews AS T1 INNER JOIN district AS T2 ON T1.district_id = T2.district_id WHERE T1.Stars = 5 AND T1.Date LIKE '2016%' ORDER BY T1.Date DESC LIMIT 5	SELECT city FROM (SELECT T2.city, rank() over (ORDER BY COUNT(T1.Stars) DESC) as rk FROM reviews T1 JOIN district T2 ON T1.district_id = T2.district_id WHERE T1.Stars = 5 AND T1.Date LIKE '2016%' GROUP BY T2.city) WHERE rk <= 5	limit n; semantic error: lack group by	1	0
381	Which city in the Midwest region has the least number of clients?	SELECT T2.city FROM client AS T1 INNER JOIN district AS T2 ON T1.district_id = T2.district_id INNER JOIN state AS T3 ON T2.state_abbrev = T3.StateCode WHERE T3.Region = 'Midwest' GROUP BY T2.city ORDER BY COUNT(T2.city) LIMIT 1	SELECT T2.city FROM client T1 JOIN district T2 ON T1.district_id = T2.district_id JOIN state T3 ON T2.state_abbrev = T3.StateCode WHERE T3.Region = 'Midwest' GROUP BY T2.city HAVING COUNT(T1.client_id) = (SELECT MIN(client_count) FROM (SELECT COUNT(T1.client_id) AS client_count FROM client T1 JOIN district T2 ON T1.district_id = T2.district_id JOIN state T3 ON T2.state_abbrev = T3.StateCode WHERE T3.Region = 'Midwest' GROUP BY T2.city))	limit 1	0	1

383	Which city in West North Central has the highest number of customers over the age of 60?	SELECT T2.city FROM client AS T1 INNER JOIN district AS T2 ON T1.district_id = T2.district_id WHERE T2.division = 'West North Central' AND T1.age > 60 GROUP BY T2.city ORDER BY COUNT(T2.city) DESC LIMIT 1	WITH ElderlyClients AS (SELECT T2.city, COUNT(*) AS client_count FROM client T1 JOIN district T2 ON T1.district_id = T2.district_id JOIN state T3 ON T2.state_abbrev = T3.StateCode WHERE T1.age > 60 AND T3.Region = 'West North Central' GROUP BY T2.city) SELECT city FROM ElderlyClients WHERE client_count = (SELECT MAX(client_count) FROM ElderlyClients)	limit 1; semantic error: wrong condition	1	0
385	Which state has the most cities?	SELECT state_abbrev FROM district GROUP BY state_abbrev ORDER BY COUNT(city) DESC LIMIT 1	SELECT state_abbrev FROM district GROUP BY state_abbrev HAVING COUNT(city) = (SELECT MAX(city_count) FROM (SELECT state_abbrev, COUNT(city) AS city_count FROM district GROUP BY state_abbrev));	limit 1	0	1
387	Please list the emails of the clients whose complaint date received is 7/3/2014.	SELECT T1.email FROM client AS T1 INNER JOIN events AS T2 ON T1.client_id = T2.Client_ID WHERE T2.Date received = '2014-07-03'	SELECT email FROM client WHERE client_id IN (SELECT Client_ID FROM events WHERE "Complaint ID" IN (SELECT "Complaint ID" FROM callcenterlogs WHERE "Date received" = '2014-07-03'));	join -> in-sub	0	1
406	List the product and its issues of the complains of clients with age greater than the 60% of average age of all clients.	SELECT DISTINCT T2.Product, T2.Issue FROM client AS T1 INNER JOIN events AS T2 ON T1.client_id = T2.Client_ID WHERE T1.age * 100 > (SELECT AVG(age) * 60 FROM client)	SELECT T2.Product, T2.Issue FROM client T1 JOIN events T2 ON T1.client_id = T2.Client_ID WHERE T1.age > (SELECT 0.6 * AVG(age) FROM client);	redundant distinct	0	1
2346	Among all the orders made by Aimee Bixby, what was the longest shipment time?	SELECT MAX(strftime('%J', 'Ship Date') - strftime('%J', 'Order Date')) AS longestTime-Days FROM people AS T1 INNER JOIN central_superstore AS T2 ON T1.Customer ID = T2.Customer ID WHERE T1.Customer Name = 'Aimee Bixby'	SELECT MAX(julianday(T1.Ship Date) - julianday(T1.Order Date)) AS LongestShipmentTime FROM (SELECT * FROM central_superstore UNION ALL SELECT * FROM east_superstore UNION ALL SELECT * FROM south_superstore UNION ALL SELECT * FROM west_superstore) T1 JOIN people T2 ON T1.Customer ID = T2.Customer ID AND T1.Region = T2.Region WHERE T2.Customer Name = 'Aimee Bixby'	semantic error: lack table, wrong join condition	0	0
2347	Among all the orders made by Aimee Bixby, how many of them chose the slowest delivery speed?	SELECT COUNT(DISTINCT T2.Order ID) FROM people AS T1 INNER JOIN central_superstore AS T2 ON T1.Customer ID = T2.Customer ID WHERE T1.Customer Name = 'Aimee Bixby' AND T2.Ship Mode = 'Standard Class'	SELECT COUNT(DISTINCT 'Order ID') FROM (SELECT 'Order ID' FROM central_superstore T1 JOIN people T2 ON T1.Customer ID = T2.Customer ID AND T1.Region = T2.Region WHERE T2.Customer Name = 'Aimee Bixby' AND T1.Ship Mode = 'Standard Class' UNION ALL SELECT 'Order ID' FROM east_superstore T1 JOIN people T2 ON T1.Customer ID = T2.Customer ID AND T1.Region = T2.Region WHERE T2.Customer Name = 'Aimee Bixby' AND T1.Ship Mode = 'Standard Class' UNION ALL SELECT 'Order ID' FROM south_superstore T1 JOIN people T2 ON T1.Customer ID = T2.Customer ID AND T1.Region = T2.Region WHERE T2.Customer Name = 'Aimee Bixby' AND T1.Ship Mode = 'Standard Class' UNION ALL SELECT 'Order ID' FROM west_superstore T1 JOIN people T2 ON T1.Customer ID = T2.Customer ID AND T1.Region = T2.Region WHERE T2.Customer Name = 'Aimee Bixby' AND T1.Ship Mode = 'Standard Class')	semantic error: lack table, wrong join condition	0	0

2350	Among the orders made by Aimee Bixby, how many of them included at least one kind of product under the category 'Furniture'?	SELECT COUNT(DISTINCT T2.'Order ID') FROM people AS T1 INNER JOIN central_superstore AS T2 ON T1.'Customer ID' = T2.'Customer ID' INNER JOIN product AS T3 ON T3.'Product ID' = T2.'Product ID' WHERE T3.Category = 'Furniture' AND T1.'Customer Name' = 'Aimee Bixby'	SELECT COUNT(DISTINCT "Order ID") FROM (SELECT * FROM central_superstore UNION ALL SELECT * FROM east_superstore UNION ALL SELECT * FROM south_superstore UNION ALL SELECT * FROM west_superstore) WHERE "Customer ID" IN (SELECT "Customer ID" FROM people WHERE "Customer Name" = 'Aimee Bixby') AND "Product ID" IN (SELECT "Product ID" FROM product WHERE Category = 'Furniture');	semantic error: lack table, wrong join condition	0	1
2356	For how many times has Aimee Bixby ordered the product Xerox 1952?	SELECT COUNT(DISTINCT T2.'Order ID') FROM people AS T1 INNER JOIN central_superstore AS T2 ON T1.'Customer ID' = T2.'Customer ID' INNER JOIN product AS T3 ON T3.'Product ID' = T2.'Product ID' WHERE T1.'Customer Name' = 'Aimee Bixby' AND T3.'Product Name' = 'Xerox 1952'	SELECT COUNT('Order ID') FROM (SELECT * FROM central_superstore UNION ALL SELECT * FROM east_superstore UNION ALL SELECT * FROM south_superstore UNION ALL SELECT * FROM west_superstore) AS T1 JOIN people AS T2 ON T1.'Customer ID' = T2.'Customer ID' AND T1.Region = T2.Region JOIN product AS T3 ON T1.'Product ID' = T3.'Product ID' AND T1.Region = T3.Region WHERE T2.'Customer Name' = 'Aimee Bixby' AND T3.'Product Name' = 'Xerox 1952';	semantic error: lack table, wrong join condition	0	0
2362	What is the name of the product that was ordered recently by Darren Powers?	SELECT T3.'Product Name' FROM people AS T1 INNER JOIN central_superstore AS T2 ON T1.'Customer ID' = T2.'Customer ID' INNER JOIN product AS T3 ON T3.'Product ID' = T2.'Product ID' WHERE T1.'Customer Name' = 'Darren Powers' ORDER BY T2.'Order Date' DESC LIMIT 1	SELECT T4.'Product Name' FROM product T4 JOIN (SELECT T1.'Product ID' FROM (SELECT * FROM central_superstore UNION ALL SELECT * FROM east_superstore UNION ALL SELECT * FROM south_superstore UNION ALL SELECT * FROM west_superstore) T1 JOIN people T2 ON T1.'Customer ID' = T2.'Customer ID' AND T1.Region = T2.Region WHERE T2.'Customer Name' = 'Darren Powers' AND T1.'Order Date' = (SELECT MAX(T1.'Order Date') FROM (SELECT * FROM central_superstore UNION ALL SELECT * FROM east_superstore UNION ALL SELECT * FROM south_superstore UNION ALL SELECT * FROM west_superstore) T1 JOIN people T2 ON T1.'Customer ID' = T2.'Customer ID' AND T1.Region = T2.Region WHERE T2.'Customer Name' = 'Darren Powers')) T3 ON T4.'Product ID' = T3.'Product ID' GROUP BY T4.'Product ID'	limit 1; semantic error: lack table, wrong join condition	1	0
2364	Which order of Logitech G600 MMO Gaming Mouse has the highest total cost?	SELECT T1.'Order ID' FROM central_superstore AS T1 INNER JOIN product AS T2 ON T1.'Product ID' = T2.'Product ID' WHERE T2.'Product Name' = 'Logitech G600 MMO Gaming Mouse' GROUP BY T1.'Order ID' ORDER BY SUM((T1.Sales / (1 - T1.Discount)) * T1.Quantity - T1.Profit) DESC LIMIT 1	SELECT 'Order ID' FROM (SELECT T1.'Order ID', rank() over (ORDER BY SUM((T1.Sales / (1 - T1.Discount)) * T1.Quantity - T1.Profit) DESC) as rk FROM (SELECT * FROM central_superstore UNION ALL SELECT * FROM east_superstore UNION ALL SELECT * FROM south_superstore UNION ALL SELECT * FROM west_superstore) AS T1 INNER JOIN product AS T2 ON T1.'Product ID' = T2.'Product ID' AND T1.Region = T2.Region WHERE T2.'Product Name' = 'Logitech G600 MMO Gaming Mouse' GROUP BY T1.'Order ID') WHERE rk = 1	limit 1; semantic error: lack table, wrong join condition	0	0

2367	What are the names of the products with a profit of no less than 1,000 in one single order?	SELECT DISTINCT T2.'Product Name' FROM west_superstore AS T1 INNER JOIN product AS T2 ON T1.'Product ID' = T2.'Product ID' WHERE T1.Profit > 1000	SELECT P.'Product Name' FROM product P WHERE EXISTS (SELECT 1 FROM central_superstore C WHERE C.'Product ID' = P.'Product ID' AND C.Region = P.Region AND C.Profit >= 1000) OR EXISTS (SELECT 1 FROM east_superstore E WHERE E.'Product ID' = P.'Product ID' AND E.Region = P.Region AND E.Profit >= 1000) OR EXISTS (SELECT 1 FROM south_superstore S WHERE S.'Product ID' = P.'Product ID' AND S.Region = P.Region AND S.Profit >= 1000) OR EXISTS (SELECT 1 FROM west_superstore W WHERE W.'Product ID' = P.'Product ID' AND W.Region = P.Region AND W.Profit >= 1000) GROUP BY P."Product ID"	distinct non-key; semantic error: lack table	0	0
2378	What percentage do items under the category of 'Furniture' make up the total number of items ordered that are shipped as standard in the West region?	SELECT CAST(SUM(CASE WHEN T2.Category = 'Furniture' THEN 1 ELSE 0 END) AS REAL) * 100 / SUM(T1.Quantity) FROM west_superstore AS T1 INNER JOIN product AS T2 ON T1.'Product ID' = T2.'Product ID' WHERE T2.Region = 'West' AND T1.'Ship Mode' = 'Standard Class'	SELECT (SUM(CASE WHEN T2.Category = 'Furniture' THEN T1.Quantity ELSE 0 END) * 100.0 / SUM(T1.Quantity)) AS Furniture_Percentage FROM west_superstore T1 JOIN product T2 ON T1.'Product ID' = T2.'Product ID' AND T1.Region = T2.Region WHERE T1.'Ship Mode' = 'Standard Class' AND T1.Region = 'West';	semantic error: wrong calculation, wrong join condition	1	0
2380	Give the customer segment from the West region that orders the order ID CA-2011-108189.	SELECT DISTINCT T2.Segment FROM west_superstore AS T1 INNER JOIN people AS T2 ON T1.'Customer ID' = T2.'Customer ID' WHERE T1.Region = 'West' AND T1.'Order ID' = 'CA-2011-108189'	SELECT p.Segment FROM people p WHERE EXISTS (SELECT 1 FROM west_superstore w WHERE w.'Customer ID' = p.'Customer ID' AND w.Region = p.Region AND w.'Order ID' = 'CA-2011-108189' AND w.Region = 'West');	semantic error: wrong join condition	0	0
2382	Provide the order ID of Frank Olsen of the South region.	SELECT T1.'Order ID' FROM south_superstore AS T1 INNER JOIN people AS T2 ON T1.'Customer ID' = T2.'Customer ID' WHERE T2.Region = 'South' AND T2.'Customer Name' = 'Frank Olsen'	SELECT T2."Order ID" FROM people T1 JOIN south_superstore T2 ON T1.'Customer ID' = T2.'Customer ID' AND T1.Region = T2.Region WHERE T1."Customer Name" = 'Frank Olsen' AND T1.Region = 'South';	semantic error: wrong join condition	0	1
2385	Who is the customer from the East region that purchased the order with the highest profit?	SELECT T2.'Customer Name' FROM east_superstore AS T1 INNER JOIN people AS T2 ON T1.'Customer ID' = T2.'Customer ID' WHERE T1.Region = 'East' ORDER BY T1.Profit DESC LIMIT 1	SELECT DISTINCT T1.'Customer ID' FROM east_superstore T1 WHERE T1.Region = 'East' AND T1.Profit = (SELECT MAX(T2.Profit) FROM east_superstore T2 WHERE T2.Region = 'East');	nlq vague: output column; limit 1	0	0
2388	List down the customers that purchased the product named Xerox 23 in the South region.	SELECT DISTINCT T2.'Customer Name' FROM south_superstore AS T1 INNER JOIN people AS T2 ON T1.'Customer ID' = T2.'Customer ID' INNER JOIN product AS T3 ON T3.'Product ID' = T1.'Product ID' WHERE T1.Region = 'South' AND T3.'Product Name' = 'Xerox 23'	SELECT T2.'Customer Name' FROM south_superstore AS T1 INNER JOIN people AS T2 ON T1.'Customer ID' = T2.'Customer ID' AND T1.Region = T2.Region INNER JOIN product AS T3 ON T3.'Product ID' = T1.'Product ID' AND T1.Region = T3.Region WHERE T1.Region = 'South' AND T3.'Product Name' = 'Xerox 23' GROUP BY T2.'Customer ID'	distinct non-key	0	0
2389	Among the products under the office supplies category, what is the product that made the highest sales in the Central region?	SELECT T2.'Product Name' FROM central_superstore AS T1 INNER JOIN product AS T2 ON T1.'Product ID' = T2.'Product ID' WHERE T2.Category = 'Office Supplies' AND T2.Region = 'Central' ORDER BY T1.Sales DESC LIMIT 1	SELECT 'Product Name' FROM (SELECT T2.'Product Name', rank() over (ORDER BY MAX(T1.Sales) DESC) as rk FROM central_superstore AS T1 INNER JOIN product AS T2 ON T1.'Product ID' = T2.'Product ID' WHERE T2.Category = 'Office Supplies' AND T2.Region = 'Central' GROUP BY T1.'Product ID') WHERE rk = 1;	limit 1; semantic error: lack group by	1	0
2391	Provide the names of the products with a profit greater than 98% of the average profit of all products in the East region.	SELECT DISTINCT T2.'Product Name' FROM east_superstore AS T1 INNER JOIN product AS T2 ON T1.'Product ID' = T2.'Product ID' WHERE T2.Region = 'East' AND T1.Profit > (SELECT AVG(Profit) * 0.98 FROM east_superstore)	SELECT "Product Name" FROM product WHERE ("Product ID", Region) IN (SELECT "Product ID", Region FROM east_superstore WHERE Region = 'East' AND Profit > (SELECT 0.98 * AVG(Profit) FROM east_superstore WHERE Region = 'East'))	distinct non-key	0	1

2392	Name the customers from the Eastern region whose orders cost above 80000.	SELECT DISTINCT T2.'Customer Name' FROM east_superstore AS T1 INNER JOIN people AS T2 ON T1.'Customer ID' = T2.'Customer ID' WHERE T1.Region = 'East' AND T1.Sales / (1 - T1.Discount) * T1.Quantity - T1.Profit > 80000	SELECT T2.'Customer Name' FROM east_superstore AS T1 INNER JOIN people AS T2 ON T1.'Customer ID' = T2.'Customer ID' AND T1.Region = T2.Region WHERE T1.Region = 'East' AND T1.Sales / (1 - T1.Discount) * T1.Quantity - T1.Profit > 80000 GROUP BY T2.'Customer ID'	distinct non-key	0	0
2393	How many orders were made by Maxwell Schwartz in 2015?	SELECT COUNT(DISTINCT T1.'Order ID') FROM east_superstore AS T1 INNER JOIN people AS T2 ON T1.'Customer ID' = T2.'Customer ID' WHERE T2.'Customer Name' = 'Maxwell Schwartz' AND STRF- TIME('%Y', T1.'Order Date') = '2015'	SELECT COUNT(DISTINCT "Order ID") FROM (SELECT T1.'Order ID' FROM central_superstore T1 JOIN people T2 ON T1.'Customer ID' = T2.'Customer ID' AND T1.Region = T2.Region WHERE T2.'Customer Name' = 'Maxwell Schwartz' AND strftime('%Y', T1.'Order Date') = '2015' UNION ALL SELECT T1.'Order ID' FROM east_superstore T1 JOIN people T2 ON T1.'Customer ID' = T2.'Customer ID' AND T1.Region = T2.Region WHERE T2.'Customer Name' = 'Maxwell Schwartz' AND strftime('%Y', T1.'Order Date') = '2015' UNION ALL SELECT T1.'Order ID' FROM south_superstore T1 JOIN people T2 ON T1.'Customer ID' = T2.'Customer ID' AND T1.Region = T2.Region WHERE T2.'Customer Name' = 'Maxwell Schwartz' AND strftime('%Y', T1.'Order Date') = '2015' UNION ALL SELECT T1.'Order ID' FROM west_superstore T1 JOIN people T2 ON T1.'Customer ID' = T2.'Customer ID' AND T1.Region = T2.Region WHERE T2.'Customer Name' = 'Maxwell Schwartz' AND strftime('%Y', T1.'Order Date') = '2015');	semantic error: lack table, wrong join condition	0	0
2400	Calculate the total cost of the orders by Brad Thomas in 2016.	SELECT SUM((T1.Sales / (1 - T1.Discount)) * T1.Quantity - T1.Profit) AS cost FROM east_superstore AS T1 INNER JOIN people AS T2 ON T1.'Customer ID' = T2.'Customer ID' INNER JOIN product AS T3 ON T1.'Product ID' = T3.'Product ID' AND T1.Region = T3.Region WHERE T1.Region = 'East' AND T2.'Customer Name' = 'Brad Thomas' AND strftime('%Y', T1.'Order Date') = '2016'	SELECT SUM((Sales / (1 - Discount) * Quan- tity) - Profit) AS Total_Cost FROM (SELECT * FROM central_superstore UNION ALL SE- LECT * FROM east_superstore UNION ALL SELECT * FROM south_superstore UNION ALL SELECT * FROM west_superstore) WHERE 'Customer ID' IN (SELECT 'Cus- tomer ID' FROM people WHERE 'Customer Name' = 'Brad Thomas') AND strftime('%Y', 'Order Date') = '2016'	semantic error: lack table, wrong join condition	0	1
2402	Provide the shipping dates and products of the orders by Gene Hale.	SELECT DISTINCT T2.'Ship Date', T3.'Product Name' FROM people AS T1 INNER JOIN central_superstore AS T2 ON T1.'Customer ID' = T2.'Customer ID' INNER JOIN product AS T3 ON T3.'Product ID' = T2.'Product ID' WHERE T1.'Customer Name' = 'Gene Hale'	SELECT "Ship Date", "Product Name" FROM (SELECT T2."Ship Date", T3."Product Name", T1."Customer Name" FROM people T1 JOIN central_superstore T2 ON T1."Customer ID" = T2."Customer ID" AND T1.Region = T2.Region JOIN product T3 ON T2."Product ID" = T3."Product ID" AND T2.Region = T3.Region UNION ALL SELECT T2."Ship Date", T3."Product Name", T1."Customer Name" FROM people T1 JOIN east_superstore T2 ON T1."Customer ID" = T2."Customer ID" AND T1.Region = T2.Region JOIN product T3 ON T2."Product ID" = T3."Product ID" AND T2.Region = T3.Region UNION ALL SELECT T2."Ship Date", T3."Product Name", T1."Customer Name" FROM peo- ple T1 JOIN south_superstore T2 ON T1."Customer ID" = T2."Customer ID" AND T1.Region = T2.Region JOIN product T3 ON T2."Product ID" = T3."Product ID" AND T2.Region = T3.Region UNION ALL SELECT T2."Ship Date", T3."Product Name", T1."Customer Name" FROM people T1 JOIN west_superstore T2 ON T1."Customer ID" = T2."Customer ID" AND T1.Region = T2.Region JOIN product T3 ON T2."Product ID" = T3."Product ID" AND T2.Region = T3.Region) WHERE "Customer Name" = 'Gene Hale'	distinct non-key; semantic error: lack table, wrong join condition	0	1

2403	How many orders in the south superstore with the fastest delivery are items of furniture?	SELECT COUNT(T1.'Order ID') FROM south_superstore AS T1 INNER JOIN product AS T2 ON T1.'Product ID' = T2.'Product ID' WHERE T1.'Ship Mode' = 'First Class' AND T2.Category = 'Furniture'	SELECT COUNT(DISTINCT "Order ID") FROM south_superstore WHERE "Ship Mode" = 'First Class' AND "Product ID" IN (SELECT "Product ID" FROM product WHERE Category = 'Furniture');	lack distinct	0	1
2408	What product category that Sam Craven ordered from the central and east superstore?	SELECT DISTINCT T3.Category FROM east_superstore AS T1 INNER JOIN people AS T2 ON T1.'Customer ID' = T2.'Customer ID' INNER JOIN product AS T3 ON T3.'Product ID' = T1.'Product ID' LEFT JOIN central_superstore AS T4 ON T3.'Product ID' = T4.'Product ID' WHERE T2.'Customer Name' = 'Sam Craven'	SELECT DISTINCT Category FROM product WHERE "Product ID" IN (SELECT "Product ID" FROM central_superstore WHERE "Customer ID" IN (SELECT "Customer ID" FROM people WHERE "Customer Name" = 'Sam Craven' AND Region = 'Central')) UNION SELECT DISTINCT Category FROM product WHERE "Product ID" IN (SELECT "Product ID" FROM east_superstore WHERE "Customer ID" IN (SELECT "Customer ID" FROM people WHERE "Customer Name" = 'Sam Craven' AND Region = 'East'));	semantic error: wrong join	1	0
2411	What product category got the least sales in the west superstore?	SELECT T2.Category FROM west_superstore AS T1 INNER JOIN product AS T2 ON T1.'Product ID' = T2.'Product ID' ORDER BY T1.Sales LIMIT 1	WITH SalesPerCategory AS (SELECT T2.Category, SUM(T1.Sales) AS TotalSales FROM west_superstore T1 JOIN product T2 ON T1.'Product ID' = T2.'Product ID' AND T1.Region = T2.Region GROUP BY T2.Category) SELECT Category FROM SalesPerCategory WHERE TotalSales = (SELECT MIN(TotalSales) FROM SalesPerCategory);	limit 1	1	0
2413	What is the total sales of furniture products in the east superstore in the year 2016.	SELECT SUM(T1.Sales) FROM east_superstore AS T1 INNER JOIN product AS T2 ON T1.'Product ID' = T2.'Product ID' WHERE STRFTIME('%Y', T1.'Order Date') = '2016' AND T2.Category = 'Furniture'	SELECT SUM(Sales) AS TotalSales FROM east_superstore WHERE "Product ID" IN (SELECT "Product ID" FROM product WHERE Category = 'Furniture') AND "Order Date" >= '2016-01-01' AND "Order Date" <= '2016-12-31';	semantic error: wrong join condition	0	1
2414	Calculate the average sales of "Sharp AL-1530CS Digital Copier in the east and the west superstore.	SELECT AVG(T1.Sales) FROM west_superstore AS T1 INNER JOIN people AS T2 ON T1.'Customer ID' = T2.'Customer ID' INNER JOIN product AS T3 ON T3.'Product ID' = T1.'Product ID' WHERE T3.'Product Name' = 'Sharp AL-1530CS Digital Copier'	SELECT AVG(Sales) FROM (SELECT Sales FROM east_superstore WHERE 'Product ID' IN (SELECT 'Product ID' FROM product WHERE 'Product Name' = 'Sharp AL-1530CS Digital Copier')) UNION ALL SELECT Sales FROM west_superstore WHERE 'Product ID' IN (SELECT 'Product ID' FROM product WHERE 'Product Name' = 'Sharp AL-1530CS Digital Copier'))	semantic error: lack table	0	1
2416	What is the ratio between customers who live in Texas and customers who live in Indiana?	SELECT CAST(SUM(CASE WHEN State = 'Texas' THEN 1 ELSE 0 END) AS REAL) * 100 / SUM(CASE WHEN State = 'Indiana' THEN 1 ELSE 0 END) FROM people	SELECT (SUM(CASE WHEN State = 'Texas' THEN 1 ELSE 0 END) * 1.0 / SUM(CASE WHEN State = 'Indiana' THEN 1 ELSE 0 END)) AS ratio FROM people;	semantic error: wrong calculation	0	1
2417	Among the orders in Central superstore, which art product were ordered the most?	SELECT T2.'Product Name' FROM central_superstore AS T1 INNER JOIN product AS T2 ON T1.'Product ID' = T2.'Product ID' WHERE T2.'Sub-Category' = 'Art' GROUP BY T2.'Product Name' ORDER BY COUNT(T2.'Product ID') DESC LIMIT 1	SELECT T2."Product Name" FROM product T2 JOIN central_superstore T1 ON T2."Product ID" = T1."Product ID" AND T2.Region = T1.Region WHERE T2."Sub-Category" = 'Art' AND T1.Region = 'Central' GROUP BY T2."Product ID" HAVING SUM(T1.Quantity) = (SELECT MAX(total) FROM (SELECT SUM(Quantity) as total FROM central_superstore T3 JOIN product T4 ON T3.'Product ID' = T4.'Product ID' AND T3.Region = T4.Region WHERE T4."Sub-Category" = 'Art' AND T4.Region = 'Central' GROUP BY T4."Product ID"));	limit 1; nlq vague: output column	1	0

2420	How many orders were made by Corey Roper in 2015?	SELECT COUNT(T2.'Customer ID') FROM people AS T1 INNER JOIN central_superstore AS T2 ON T1.'Customer ID' = T2.'Customer ID' WHERE T1.'Customer Name' = 'Corey Roper' AND STRFTIME('%Y', T2.'Ship Date') = '2015'	SELECT COUNT(DISTINCT 'Order ID') FROM (SELECT 'Order ID' FROM central_superstore WHERE 'Customer ID' IN (SELECT 'Customer ID' FROM people WHERE 'Customer Name' = 'Corey Roper') AND strptime('%Y', 'Order Date') = '2015' UNION ALL SELECT 'Order ID' FROM east_superstore WHERE 'Customer ID' IN (SELECT 'Customer ID' FROM people WHERE 'Customer Name' = 'Corey Roper') AND strptime('%Y', 'Order Date') = '2015' UNION ALL SELECT 'Order ID' FROM south_superstore WHERE 'Customer ID' IN (SELECT 'Customer ID' FROM people WHERE 'Customer Name' = 'Corey Roper') AND strptime('%Y', 'Order Date') = '2015' UNION ALL SELECT 'Order ID' FROM west_superstore WHERE 'Customer ID' IN (SELECT 'Customer ID' FROM people WHERE 'Customer Name' = 'Corey Roper') AND strptime('%Y', 'Order Date') = '2015'))	lack distinct; semantic error: lack table	0	0
2422	What are the names of the ordered products that have profit deficiency in central superstore?	SELECT DISTINCT T2.'Product Name' FROM central_superstore AS T1 INNER JOIN product AS T2 ON T1.'Product ID' = T2.'Product ID' WHERE T2.Region = 'Central' AND T1.Profit < 0	SELECT "Product Name" FROM product WHERE ("Product ID", Region) IN (SELECT "Product ID", Region FROM central_superstore WHERE Profit < 0);	join -> in-sub	0	1
2427	In which segment does the customer who purchased the product from the east superstore with the highest original price belong?	SELECT T2.Segment FROM east_superstore AS T1 INNER JOIN people AS T2 ON T1.'Customer ID' = T2.'Customer ID' INNER JOIN product AS T3 ON T3.'Product ID' = T1.'Product ID' WHERE T1.Region = 'East' ORDER BY (T1.Sales / (1 - T1.Discount)) DESC LIMIT 1	SELECT Segment FROM people WHERE ("Customer ID", Region) IN (SELECT "Customer ID", Region FROM east_superstore WHERE Sales / (1 - Discount) = (SELECT MAX(Sales / (1 - Discount)) FROM east_superstore))	limit 1	0	1
2432	Who was the customer in the South Region superstore who bought the most "Hon Multipurpose Stacking Arm Chairs"?	SELECT T2.'Customer Name' FROM south_superstore AS T1 INNER JOIN people AS T2 ON T1.'Customer ID' = T2.'Customer ID' INNER JOIN product AS T3 ON T3.'Product ID' = T1.'Product ID' WHERE T3.'Product Name' = 'Hon Multipurpose Stacking Arm Chairs' GROUP BY T2.'Customer Name' ORDER BY COUNT(T2.'Customer Name') DESC LIMIT 1	SELECT 'Customer Name' FROM (SELECT T2.'Customer Name', rank() over (ORDER BY SUM(T1.'Quantity') DESC) as rk FROM south_superstore AS T1 INNER JOIN people AS T2 ON T1.'Customer ID' = T2.'Customer ID' AND T1.Region = T2.Region INNER JOIN product AS T3 ON T3.'Product ID' = T1.'Product ID' AND T1.Region = T3.Region WHERE T3.'Product Name' = 'Hon Multipurpose Stacking Arm Chairs' GROUP BY T2.'Customer ID') WHERE rk = 1;	semantic error: group by non-key, wrong condition	0	0
2440	What is the highest profit order in the East superstore of customers from Houston, Texas?	SELECT T1.'Order ID' FROM east_superstore AS T1 INNER JOIN people AS T2 ON T1.'Customer ID' = T2.'Customer ID' WHERE T2.City = 'Houston' AND T2.State = 'Texas' ORDER BY T1.Profit DESC LIMIT 1	SELECT 'Order ID' FROM (SELECT T1.'Order ID', rank() over (ORDER BY SUM(T1.Profit) DESC) as rk FROM east_superstore AS T1 INNER JOIN people AS T2 ON T1.'Customer ID' = T2.'Customer ID' AND T1.Region = T2.Region WHERE T2.City = 'Houston' AND T2.State = 'Texas' GROUP BY T1.'Order ID') WHERE rk = 1	limit 1; semantic error: wrong condition	0	0
2442	What are the names of the products that had been shipped in March 2013 at central superstore?	SELECT DISTINCT T2.'Product Name' FROM central_superstore AS T1 INNER JOIN product AS T2 ON T1.'Product ID' = T2.'Product ID' WHERE strptime('%Y-%m', T1.'Ship Date') = '2013-03'	SELECT "Product Name" FROM product WHERE ("Product ID", Region) IN (SELECT "Product ID", Region FROM central_superstore WHERE "Ship Date" LIKE '2013-03%' AND Region = 'Central');	join -> in-sub	1	0
2443	How many orders were made by customers who live in Texas at the Central superstore?	SELECT COUNT(DISTINCT T2.'Order ID') FROM people AS T1 INNER JOIN central_superstore AS T2 ON T1.'Customer ID' = T2.'Customer ID' WHERE T1.State = 'Texas'	SELECT COUNT(DISTINCT T2.'Order ID') FROM people T1 JOIN central_superstore T2 ON T1.'Customer ID' = T2.'Customer ID' AND T1.Region = T2.Region WHERE T1.State = 'Texas';	semantic error: wrong join condition	0	1

2446	What is the percentage of orders with 0.2 discount in the Central superstore were purchased by customers who live in Texas?	SELECT CAST(SUM(CASE WHEN T2.Discount = 0.2 THEN 1 ELSE 0 END) AS REAL) * 100 / COUNT(*) FROM people AS T1 INNER JOIN central_superstore AS T2 ON T1.Customer ID = T2.Customer ID WHERE T1.State = 'Texas'	SELECT (100.0 * (SELECT COUNT(DISTINCT "Order ID") FROM central_superstore WHERE Discount = 0.2 AND "Customer ID" IN (SELECT "Customer ID" FROM people WHERE State = 'Texas' AND Region = central_superstore.Region)) / COUNT(DISTINCT "Order ID")) AS percentage FROM central_superstore	lack distinct; semantic error: wrong condition	0	1
2447	What is the percentage of furniture orders that were shipped through first class in 2013 at the Central superstore?	SELECT CAST(SUM(CASE WHEN T1.Ship Mode = 'First Class' THEN 1 ELSE 0 END) AS REAL) * 100 / COUNT(*) FROM central_superstore AS T1 INNER JOIN product AS T2 ON T1.Product ID = T2.Product ID WHERE T2.Category = 'Furniture' AND STRFTIME('%Y', T1.Ship Date) = '2013'	SELECT (COUNT(DISTINCT T1."Order ID") * 100.0 / (SELECT COUNT(DISTINCT "Order ID") FROM central_superstore WHERE strftime('%Y', "Ship Date") = '2013')) AS percentage FROM central_superstore T1 JOIN product T2 ON T1.Product ID = T2.Product ID AND T1.Region = T2.Region WHERE T2.Category = 'Furniture' AND T1.Ship Mode = 'First Class' AND strftime('%Y', T1.Ship Date) = '2013';	lack distinct	0	1
2450	List the product's name bought by the customer named Bill Shonely from the Central region.	SELECT DISTINCT T3.Product Name FROM people AS T1 INNER JOIN central_superstore AS T2 ON T1.Customer ID = T2.Customer ID INNER JOIN product AS T3 ON T3.Product ID = T2.Product ID WHERE T1.Customer Name = 'Bill Shonely' AND T2.Region = 'Central'	SELECT "Product Name" FROM product WHERE "Product ID" IN (SELECT "Product ID" FROM central_superstore WHERE "Customer ID" IN (SELECT "Customer ID" FROM people WHERE "Customer Name" = 'Bill Shonely' AND Region = 'Central') AND Region = 'Central');	join -> in-sub	0	1
2451	Please give the name of customers from the West region that bought exactly 8 items in their purchase.	SELECT DISTINCT T2.Customer Name FROM west_superstore AS T1 INNER JOIN people AS T2 ON T1.Customer ID = T2.Customer ID WHERE T1.Quantity = 8 AND T1.Region = 'West'	SELECT "Customer Name" FROM people WHERE ("Customer ID", Region) IN (SELECT "Customer ID", Region FROM west_superstore WHERE Quantity = 8 AND Region = 'West');	join -> in-sub	0	1
2453	Who is the customer with an order shipped on March 5, 2013, in the eastern region?	SELECT DISTINCT T2.Customer Name FROM east_superstore AS T1 INNER JOIN people AS T2 ON T1.Customer ID = T2.Customer ID WHERE T1.Ship Date = '2013-03-05'	SELECT "Customer Name" FROM people WHERE ("Customer ID", Region) IN (SELECT "Customer ID", Region FROM east_superstore WHERE "Ship Date" = '2013-03-05' AND Region = 'East');	join -> in-sub	1	0
2454	Among the orders from 2016 in the Central region, what is the product with the lowest profit?	SELECT T2.Product Name FROM central_superstore AS T1 INNER JOIN product AS T2 ON T1.Product ID = T2.Product ID WHERE T2.Region = 'Central' AND STRFTIME('%Y', T1.Order Date) = '2016' ORDER BY T1.Profit ASC LIMIT 1	SELECT 'Product Name' FROM (SELECT T2.Product Name, rank() over (ORDER BY min(T1.Profit) ASC) as rk FROM central_superstore AS T1 INNER JOIN product AS T2 ON T1.Product ID = T2.Product ID WHERE T2.Region = 'Central' AND STRFTIME('%Y', T1.Order Date) = '2016' GROUP BY T1.Product ID) WHERE rk = 1;	limit 1; semantic error: lack group by	0	0
2458	What is the product's name in the highest quantity in a single purchase?	SELECT T2.Product Name FROM east_superstore AS T1 INNER JOIN product AS T2 ON T1.Product ID = T2.Product ID WHERE T2.Region = 'East' ORDER BY T1.Quantity DESC LIMIT 1	SELECT "Product Name" FROM (SELECT "Product ID", rank() over (ORDER BY max(Quantity) DESC) as rk FROM (SELECT "Product ID", Quantity FROM central_superstore UNION ALL SELECT "Product ID", Quantity FROM east_superstore UNION ALL SELECT "Product ID", Quantity FROM south_superstore UNION ALL SELECT "Product ID", Quantity FROM west_superstore) GROUP BY "Product ID") AS T JOIN product ON T.Product ID = product.Product ID WHERE rk = 1 GROUP BY T.Product ID	limit 1; semantic error: lack table	0	0

3315	Which publisher has published the most games?	SELECT T.publisher_name FROM (SELECT T2.publisher_name, COUNT(DISTINCT T2.id) FROM game_publisher AS T1 INNER JOIN publisher AS T2 ON T1.publisher_id = T2.id GROUP BY T1.publisher_id ORDER BY COUNT(T2.id) DESC LIMIT 1) t	SELECT publisher_name FROM publisher WHERE id IN (SELECT publisher_id FROM game_publisher GROUP BY publisher_id HAVING COUNT(game_id) = (SELECT MAX(game_count) FROM (SELECT COUNT(game_id) AS game_count FROM game_publisher GROUP BY publisher_id)));	limit 1	0	1
3327	Which genre has the most games? Show its id.	SELECT genre_id FROM (SELECT T.genre_id, COUNT(T.id) FROM game AS T GROUP BY T.genre_id ORDER BY COUNT(T.id) DESC LIMIT 1)	SELECT genre_id FROM (SELECT genre_id, COUNT(id) AS game_count FROM game GROUP BY genre_id) WHERE game_count = (SELECT MAX(game_count) FROM (SELECT COUNT(id) AS game_count FROM game GROUP BY genre_id));	limit 1	0	1
3338	How many sales does game platform id 3871 make in Europe?	SELECT T2.num_sales * 100000 FROM region AS T1 INNER JOIN region_sales AS T2 ON T1.id = T2.region_id WHERE T1.region_name = 'Europe' AND T2.game_platform_id = 3871	SELECT SUM(T2.num_sales * 100000) AS total_sales FROM region_sales AS T2 JOIN region AS T1 ON T1.id = T2.region_id WHERE T1.region_name = 'Europe' AND T2.game_platform_id = 3871;	semantic error: multiple regions have the name 'Europe'	0	1
3340	Show the name of the earliest platform in the database.	SELECT T2.platform_name FROM game_platform AS T1 INNER JOIN platform AS T2 ON T1.platform_id = T2.id ORDER BY T1.release_year ASC LIMIT 1	SELECT platform_name FROM platform AS T1 WHERE T1.id IN (SELECT platform_id FROM (SELECT T1.platform_id, rank() over (ORDER BY T1.release_year ASC) as rk FROM game_platform AS T1) WHERE rk = 1)	limit 1	1	0
3345	How many role-playing games did Microsoft Game Studios publish?	SELECT COUNT(T3.id) FROM publisher AS T1 INNER JOIN game_publisher AS T2 ON T1.id = T2.publisher_id INNER JOIN game AS T3 ON T2.game_id = T3.id INNER JOIN genre AS T4 ON T3.genre_id = T4.id WHERE T4.genre_name = 'Role-Playing' AND T1.publisher_name = 'Microsoft Game Studios'	SELECT COUNT(DISTINCT game_id) FROM game INNER JOIN genre ON game.genre_id = genre.id INNER JOIN game_publisher ON game.id = game_publisher.game_id INNER JOIN publisher ON game_publisher.publisher_id = publisher.id WHERE genre.genre_name = 'Role-Playing' AND publisher.publisher_name = 'Microsoft Game Studios';	lack distinct	0	1
3354	What are the names of the games that were published by 505 Games?	SELECT T3.game_name FROM publisher AS T1 INNER JOIN game_publisher AS T2 ON T1.id = T2.publisher_id INNER JOIN game AS T3 ON T2.game_id = T3.id WHERE T1.publisher_name = '505 Games'	SELECT game_name FROM game WHERE EXISTS (SELECT 1 FROM game_publisher JOIN publisher ON game_publisher.publisher_id = publisher.id WHERE game_publisher.game_id = game.id AND publisher.publisher_name = '505 Games');	join -> in-sub	1	0
3359	List down the record ID of records released between 2000 to 2003.	SELECT T.id FROM game_platform AS T WHERE T.release_year BETWEEN 2000 AND 2003	SELECT id FROM game WHERE id IN (SELECT game_id FROM game_publisher WHERE id IN (SELECT game_publisher_id FROM game_platform WHERE release_year >= 2000 AND release_year <= 2003));	semantic error: output column	0	1
3367	List the region name where games reached 300000 sales and above.	SELECT DISTINCT T1.region_name FROM region AS T1 INNER JOIN region_sales AS T2 ON T1.id = T2.region_id WHERE T2.num_sales * 100000 > 300000	SELECT region_name FROM region WHERE id IN (SELECT region_id FROM region_sales WHERE num_sales > 3);	join -> in-sub	0	1
3368	Which company published the game with the most sales in North America?	SELECT T.publisher_name FROM (SELECT T5.publisher_name, SUM(T2.num_sales) * 100000 FROM region AS T1 INNER JOIN region_sales AS T2 ON T1.id = T2.region_id INNER JOIN game_platform AS T3 ON T2.game_platform_id = T3.id INNER JOIN game_publisher AS T4 ON T3.game_publisher_id = T4.id INNER JOIN publisher AS T5 ON T4.publisher_id = T5.id WHERE T1.region_name = 'North America' GROUP BY T5.publisher_name ORDER BY SUM(T2.num_sales) * 100000 DESC LIMIT 1) t	SELECT publisher_name FROM publisher WHERE id IN (SELECT publisher_id FROM (SELECT GP.game_id, rank() over (ORDER BY SUM(RS.num_sales) DESC) as rk FROM game_publisher GP JOIN game_platform G ON GP.id = G.game_publisher_id JOIN region_sales RS ON G.id = RS.game_platform_id JOIN region R ON RS.region_id = R.id WHERE R.region_name = 'North America' GROUP BY GP.game_id) AS T JOIN game_publisher ON T.game_id = game_publisher.game_id WHERE rk = 1)	limit 1; semantic error: wrong condition; group by non-key	0	0

3373	Provide the game publisher's name of the game with sales greater than 90% of the average sales in Japan.	SELECT DISTINCT T5.publisher_name FROM region AS T1 INNER JOIN region_sales AS T2 ON T1.id = T2.region_id INNER JOIN game_platform AS T3 ON T2.game_platform_id = T3.id INNER JOIN game_publisher AS T4 ON T3.game_publisher_id = T4.id INNER JOIN publisher AS T5 ON T4.publisher_id = T5.id WHERE T2.num_sales * 1000000 > (SELECT AVG(T2.num_sales) * 100000 * 90 FROM region AS T1 INNER JOIN region_sales AS T2 ON T1.id = T2.region_id WHERE T1.region_name = 'Japan')	SELECT T5.publisher_name FROM publisher T5 WHERE T5.id IN (SELECT T4.publisher_id FROM game_platform T3 JOIN game_publisher AS T4 ON T3.game_publisher_id = T4.id WHERE T3.id IN (SELECT T2.game_platform_id FROM region_sales T2 WHERE T2.region_id IN (SELECT T1.id FROM region T1 WHERE T1.region_name = 'Japan') AND T2.num_sales > (SELECT 0.9 * AVG(T2.num_sales) FROM region_sales T2 JOIN region T1 ON T2.region_id = T1.id WHERE T1.region_name = 'Japan')));	join -> in-sub; semantic error: wrong condition	0	0
3380	List the game IDs that were released in 2017.	SELECT T.id FROM game_platform AS T WHERE T.release_year = 2017	SELECT DISTINCT game_publisher.game_id FROM game_publisher JOIN game_platform ON game_publisher.id = game_platform.game_publisher_id WHERE game_platform.release_year = 2017;	semantic error: output column	0	0
3388	Name the game released in 2011.	SELECT T3.game_name FROM game_platform AS T1 INNER JOIN game_publisher AS T2 ON T1.game_publisher_id = T2.id INNER JOIN game AS T3 ON T2.game_id = T3.id WHERE T1.release_year = 2011	SELECT T3.game_name FROM game AS T3 WHERE T3.id IN (SELECT T2.game_id FROM game_platform AS T1 INNER JOIN game_publisher AS T2 ON T1.game_publisher_id = T2.id WHERE T1.release_year = 2011)	join -> in-sub	1	0
3392	Provide the platform where the Panzer Tactics can be played.	SELECT T4.platform_name FROM game AS T1 INNER JOIN game_publisher AS T2 ON T1.id = T2.game_id INNER JOIN game_platform AS T3 ON T2.id = T3.game_publisher_id INNER JOIN platform AS T4 ON T3.platform_id = T4.id WHERE T1.game_name = 'Panzer Tactics'	SELECT T4.platform_name FROM platform AS T4 WHERE T4.ID IN (SELECT T3.platform_id FROM game AS T1 INNER JOIN game_publisher AS T2 ON T1.id = T2.game_id INNER JOIN game_platform AS T3 ON T2.id = T3.game_publisher_id WHERE T1.game_name = 'Panzer Tactics')	join -> in-sub	1	0
3405	Which publisher published the most games?	SELECT T.publisher_name FROM (SELECT T1.publisher_name, COUNT(DISTINCT T2.game_id) FROM publisher AS T1 INNER JOIN game_publisher AS T2 ON T1.id = T2.publisher_id GROUP BY T1.publisher_name ORDER BY COUNT(DISTINCT T2.game_id) DESC LIMIT 1) t	SELECT publisher_name FROM publisher WHERE id IN (SELECT publisher_id FROM game_publisher GROUP BY publisher_id HAVING COUNT(game_id) = (SELECT MAX(game_count) FROM (SELECT COUNT(game_id) AS game_count FROM game_publisher GROUP BY publisher_id)));	group by non-key; limit 1	0	0
3407	What are the years that 'WiiU' got a new game?	SELECT T2.release_year FROM platform AS T1 INNER JOIN game_platform AS T2 ON T1.id = T2.platform_id WHERE T1.platform_name = 'WiiU' ORDER BY T2.release_year DESC LIMIT 1	SELECT DISTINCT T2.release_year FROM platform T1 JOIN game_platform T2 ON T1.id = T2.platform_id WHERE T1.platform_name = 'WiiU' AND T2.release_year IS NOT NULL;	lack distinct; redundant limit 1	0	1
3420	How many Sports games did Nintendo publish?	SELECT COUNT(T3.id) FROM publisher AS T1 INNER JOIN game_publisher AS T2 ON T1.id = T2.publisher_id INNER JOIN game AS T3 ON T2.game_id = T3.id INNER JOIN genre AS T4 ON T3.genre_id = T4.id WHERE T4.genre_name = 'Sports' AND T1.publisher_name = 'Nintendo'	SELECT COUNT(DISTINCT T3.id) FROM game T3 JOIN genre T1 ON T3.genre_id = T1.id JOIN game_publisher T4 ON T3.id = T4.game_id JOIN publisher T2 ON T4.publisher_id = T2.id WHERE T1.genre_name = 'Sports' AND T2.publisher_name = 'Nintendo';	lack distinct	0	1
3437	What genres are the games published by 'Agatsuma Entertainment'?	SELECT T4.genre_name FROM publisher AS T1 INNER JOIN game_publisher AS T2 ON T1.id = T2.publisher_id INNER JOIN game AS T3 ON T2.game_id = T3.id INNER JOIN genre AS T4 ON T3.genre_id = T4.id WHERE T1.publisher_name = 'Agatsuma Entertainment'	SELECT DISTINCT T4.genre_name FROM publisher T1 JOIN game_publisher T2 ON T1.id = T2.publisher_id JOIN game T3 ON T2.game_id = T3.id JOIN genre T4 ON T3.genre_id = T4.id WHERE T1.publisher_name = 'Agatsuma Entertainment';	lack distinct	0	1
3440	Which publisher has published the most games in the 'Puzzle' genre?	SELECT T.publisher_name FROM (SELECT T1.publisher_name, COUNT(T3.id) FROM publisher AS T1 INNER JOIN game_publisher AS T2 ON T1.id = T2.publisher_id INNER JOIN game AS T3 ON T2.game_id = T3.id INNER JOIN genre AS T4 ON T3.genre_id = T4.id WHERE T4.genre_name = 'Puzzle' GROUP BY T1.publisher_name ORDER BY COUNT(T3.id) DESC LIMIT 1) t	SELECT publisher_name FROM publisher WHERE id IN (SELECT publisher_id FROM game_publisher WHERE game_id IN (SELECT id FROM game WHERE genre_id IN (SELECT id FROM genre WHERE genre_name = 'Puzzle'))) GROUP BY publisher_id HAVING COUNT(*) = (SELECT MAX(cnt) FROM (SELECT count(*) AS cnt FROM game_publisher WHERE game_id IN (SELECT id FROM game WHERE genre_id IN (SELECT id FROM genre WHERE genre_name = 'Puzzle'))) GROUP BY publisher_id))	limit 1	0	0

3441	Which game has sold the fewest units?	SELECT T.game_name FROM (SELECT T1.game_name FROM game AS T1 INNER JOIN game_publisher AS T2 ON T1.id = T2.game_id INNER JOIN game_platform AS T3 ON T2.id = T3.game_publisher_id INNER JOIN region_sales AS T4 ON T3.id = T4.game_platform_id ORDER BY T4.num_sales LIMIT 1) t	SELECT G.game_name FROM game G WHERE EXISTS (SELECT 1 FROM game_publisher GP JOIN game_platform GPf ON GP.id = GPf.game_publisher_id JOIN region_sales RS ON GPf.id = RS.game_platform_id WHERE GPf.id = G.id GROUP BY GPf.id HAVING MIN(RS.num_sales) = (SELECT MIN(num_sales) FROM region_sales WHERE num_sales IS NOT NULL))	limit 1; semantic error: lack group by	0	1
3446	Calculate the percentage of games published by 'Brash Entertainment'?	SELECT CAST(COUNT(CASE WHEN T1.publisher_name = 'Brash Entertainment' THEN T2.game_id ELSE NULL END) AS REAL) * 100 / COUNT(T2.game_id) FROM publisher AS T1 INNER JOIN game_publisher AS T2 ON T1.id = T2.publisher_id	SELECT (COUNT(DISTINCT CASE WHEN T2.publisher_name = 'Brash Entertainment' THEN T1.game_id END) * 100.0 / COUNT(DISTINCT T1.game_id)) AS percentage FROM game_publisher T1 JOIN publisher T2 ON T1.publisher_id = T2.id;	lack distinct	0	1
3457	Indicate the release year of the game with more than 200000 sales in Japan.	SELECT DISTINCT T3.release_year FROM region AS T1 INNER JOIN region_sales AS T2 ON T1.id = T2.region_id INNER JOIN game_platform AS T3 ON T2.game_platform_id = T3.id WHERE T2.num_sales * 100000 > 200000 AND T1.region_name = 'Japan'	SELECT release_year FROM game_platform WHERE id IN (SELECT game_platform_id FROM region_sales rs INNER JOIN region r ON rs.region_id = r.id WHERE r.region_name = 'Japan' GROUP BY game_platform_id HAVING SUM(rs.num_sales) > 2)	semantic error: wrong condition; redundant distinct; schema flaw: lack constraint - pk region_sales(region_id, game_platform_id)	0	0
3459	Indicate the publisher who has published the most games of all time.	SELECT T.publisher_name FROM (SELECT T2.publisher_name, COUNT(DISTINCT T1.game_id) FROM game_publisher AS T1 INNER JOIN publisher AS T2 ON T1.publisher_id = T2.id GROUP BY T2.publisher_name ORDER BY COUNT(DISTINCT T1.game_id) DESC LIMIT 1) t	SELECT publisher_name FROM publisher WHERE id IN (SELECT publisher_id FROM game_publisher GROUP BY publisher_id HAVING COUNT(game_id) = (SELECT MAX(game_count) FROM (SELECT COUNT(game_id) AS game_count FROM game_publisher GROUP BY publisher_id)))	limit 1	0	1
3487	List the games available on Wii.	SELECT T4.game_name FROM platform AS T1 INNER JOIN game_platform AS T2 ON T1.id = T2.platform_id INNER JOIN game_publisher AS T3 ON T2.game_publisher_id = T3.id INNER JOIN game AS T4 ON T3.game_id = T4.id WHERE T1.platform_name = 'Wii'	SELECT game_name FROM game WHERE EXISTS (SELECT 1 FROM game_publisher JOIN game_platform ON game_publisher.id = game_platform.game_publisher_id JOIN platform ON game_platform.platform_id = platform.id WHERE game_publisher.game_id = game.id AND platform.platform_name = 'Wii');	join -> in-sub	0	1
3491	List down the game platform ID and region name where the games achieved 20000 sales and below.	SELECT T2.game_platform_id, T1.region_name FROM region AS T1 INNER JOIN region_sales AS T2 ON T1.id = T2.region_id WHERE T2.num_sales * 100000 <= 20000	SELECT T1.game_platform_id, T2.region_name FROM region_sales T1 JOIN region T2 ON T1.region_id = T2.id WHERE T1.num_sales < 0.2;	semantic error: wrong condition	0	1
3502	How many games available on PSP were released in 2004?	SELECT COUNT(T3.game_id) FROM platform AS T1 INNER JOIN game_platform AS T2 ON T1.id = T2.platform_id INNER JOIN game_publisher AS T3 ON T2.game_publisher_id = T3.id WHERE T1.platform_name = 'PSP' AND T2.release_year = 2004	SELECT COUNT(DISTINCT T3.game_id) FROM platform AS T1 INNER JOIN game_platform AS T2 ON T1.id = T2.platform_id INNER JOIN game_publisher AS T3 ON T2.game_publisher_id = T3.id WHERE T1.platform_name = 'PSP' AND T2.release_year = 2004	lack distinct	1	0
3517	Among the authors of the paper 'Stitching videos streamed by mobile phones in real-time', how many of them are affiliated with Cairo Microsoft Innovation Lab?	SELECT COUNT(T1.AuthorId) FROM PaperAuthor AS T1 INNER JOIN Paper AS T2 ON T1.PaperId = T2.Id WHERE T1.Affiliation = 'University of Tokyo' AND T2.Title = 'FIBER: A Generalized Framework for Auto-tuning Software'	SELECT COUNT(DISTINCT T3.Id) FROM Paper T1 JOIN PaperAuthor T2 ON T1.Id = T2.PaperId JOIN Author T3 ON T2.AuthorId = T3.Id WHERE T1.Title = 'Stitching videos streamed by mobile phones in real-time' AND T3.Affiliation = 'Cairo Microsoft Innovation Lab';	lack distinct; nlq vague: nlq conflicts with evidence	0	1

3518	Please list the titles of the paper whose authors include Klaus Zimmermann.	SELECT T2.Title FROM PaperAuthor AS T1 INNER JOIN Paper AS T2 ON T1.PaperId = T2.Id WHERE T1.Name = 'Klaus Zimmermann'	SELECT Title FROM Paper WHERE Id IN (SELECT PaperId FROM PaperAuthor WHERE Name = 'Klaus Zimmermann')	join -> in-sub	0	0
3529	What is the title and journal homepage of the latest published paper?	SELECT T1.Title, T2.HomePage FROM Paper AS T1 INNER JOIN Journal AS T2 ON T1.JournalId = T2.Id ORDER BY T1.Year DESC LIMIT 1	SELECT T1.Title, T2.HomePage FROM Paper T1 JOIN Journal T2 ON T1.JournalId = T2.Id WHERE T1.Year = (SELECT MAX(Year) FROM Paper WHERE Year > 0 AND JournalId != 0)	limit 1	0	1
3534	Among the papers with conference ID of 0, list down the authors of papers with a journal ID less than 100.	SELECT DISTINCT T2.Name FROM Paper AS T1 INNER JOIN PaperAuthor AS T2 ON T1.Id = T2.PaperId WHERE T1.ConferenceId = 0 AND T1.JournalId < 100	SELECT T2.Name FROM Paper T1 JOIN PaperAuthor T2 ON T1.Id = T2.PaperId WHERE T1.ConferenceId = 0 AND T1.JournalId < 100;	redundant distinct	0	1
3546	Find the paper ID, title, published year and journal's full name of the paper which included the most number in author.	SELECT T1.Id, T1.Title, T1.Year, T3.FullName FROM Paper AS T1 INNER JOIN PaperAuthor AS T2 ON T1.Id = T2.PaperId INNER JOIN Journal AS T3 ON T1.JournalId = T3.Id GROUP BY T2.AuthorId ORDER BY COUNT(T2.AuthorId) DESC LIMIT 1	SELECT P.Id, P.Title, P.Year, J.FullName FROM Paper P INNER JOIN Journal J ON P.JournalId = J.Id WHERE P.Id IN (SELECT PaperId FROM PaperAuthor GROUP BY PaperId HAVING COUNT(*) = (SELECT MAX(Cnt) FROM (SELECT COUNT(*) AS Cnt FROM PaperAuthor GROUP BY PaperId)))	limit 1; semantic error: wrong condition	0	1
3547	Describe the paper title, published year, conference's short name and included author names in the paper ID of 15.	SELECT DISTINCT T1.Title, T1.Year, T3.ShortName, T2.Name FROM Paper AS T1 INNER JOIN PaperAuthor AS T2 ON T1.Id = T2.PaperId INNER JOIN Conference AS T3 ON T1.ConferenceId = T3.Id WHERE T1.Id = 15	SELECT P.Title, P.Year, C.ShortName, PA.Name FROM Paper P JOIN Conference C ON P.ConferenceId = C.Id JOIN PaperAuthor PA ON P.Id = PA.PaperId WHERE P.Id = 15;	redundant distinct	0	1
3549	Among the author included in the paper of 'Inspection resistant memory: Architectural support for security from physical examination', write down the author name and ID who were affiliated with Microsoft Research, USA.	SELECT T2.Name, T1.Id FROM Paper AS T1 INNER JOIN PaperAuthor AS T2 ON T1.Id = T2.PaperId WHERE T1.Title = 'Inspection resistant memory: Architectural support for security from physical examination' AND T2.Affiliation = 'Microsoft Research, USA'	SELECT PA.AuthorId, PA.Name FROM PaperAuthor PA WHERE PA.PaperId IN (SELECT ID FROM Paper P WHERE P.Title = 'Inspection resistant memory: Architectural support for security from physical examination') AND PA.Affiliation = 'Microsoft Research, USA';	join -> in-sub; semantic error: output column	0	0
3564	How many authors have written paper '145 GROWTH HORMONE RECEPTORS AND THE ONSET OF HYPERINSULINEMIA IN THE OBESE ZUCKER RAT: '?	SELECT COUNT(DISTINCT T2.Name) FROM Paper AS T1 INNER JOIN PaperAuthor AS T2 ON T1.Id = T2.PaperId WHERE T1.Title = '145 GROWTH HORMONE RECEPTORS AND THE ONSET OF HYPERINSULINEMIA IN THE OBESE ZUCKER RAT: '	SELECT COUNT(DISTINCT T2.AuthorId) FROM Paper T1 JOIN PaperAuthor T2 ON T1.Id = T2.PaperId WHERE T1.Title LIKE '%145 GROWTH HORMONE RECEPTORS AND THE ONSET OF HYPERINSULINEMIA IN THE OBESE ZUCKER RAT:%';	distinct non-key; semantic error: wrong condition	1	0
3565	Who are the co-authors for Jei Keon Chae and what is the title of paper written by them?	SELECT T2.AuthorId, T1.Title FROM Paper AS T1 INNER JOIN PaperAuthor AS T2 ON T1.Id = T2.PaperId WHERE T2.Name = 'Jei Keon Chae'	SELECT Paper.Title, PaperAuthor.Name FROM Paper JOIN PaperAuthor ON Paper.Id = PaperAuthor.PaperId WHERE ID IN (SELECT PaperId FROM PaperAuthor WHERE Name = 'Jei Keon Chae') AND PaperAuthor.Name != 'Jei Keon Chae'	semantic error: wrong condition	1	0
3584	How many authors were associated with the Microsoft Research when paper number 1 was written?	SELECT COUNT(PaperId) FROM PaperAuthor WHERE Affiliation LIKE '%Microsoft Research%'	SELECT COUNT(DISTINCT AuthorId) FROM PaperAuthor WHERE PaperId = 1 AND Affiliation LIKE '%Microsoft Research%';	semantic error: output column, wrong condition	0	1

3592	What is the title of the paper that was written by Cheng Huang and affiliated with Microsoft?	SELECT T1.Title FROM Paper AS T1 INNER JOIN PaperAuthor AS T2 ON T1.Id = T2.PaperId WHERE T2.Name = 'Cheng Huang' AND T2.Affiliation = 'Microsoft'	SELECT Title FROM Paper WHERE Id IN (SELECT PaperId FROM PaperAuthor WHERE Name = 'Cheng Huang' AND Affiliation LIKE 'Microsoft %')	str; join -> in-sub	1	0
3604	What is the average number of papers published in the World Computer Congress each year?	SELECT CAST(SUM(CASE WHEN T2.FullName = 'International Congress Series' THEN 1 ELSE 0 END) AS REAL) / COUNT(T1.Id) AS Div1, T1.Year FROM Paper AS T1 INNER JOIN Journal AS T2 ON T1.JournalId = T2.Id GROUP BY T1.YEAR HAVING Div1 != 0	SELECT AVG(PaperCount) FROM (SELECT COUNT(*) AS PaperCount FROM Paper WHERE Conferenceld = (SELECT Id FROM Conference WHERE FullName = 'World Computer Congress') GROUP BY Year)	semantic error: wrong condition, output column	0	1
3605	Give the Title and author's name of the books that were preprint in 1997.	SELECT DISTINCT T2.Name, T1.Title FROM Paper AS T1 INNER JOIN PaperAuthor AS T2 ON T1.Id = T2.PaperId WHERE T1.Conferenceld = 0 AND T1.JournalId = 0 AND T1.Year = 1997 AND T1.Title <> ''	SELECT P.Title, PA.Name FROM Paper P JOIN PaperAuthor PA ON P.Id = PA.PaperId WHERE P.Year = 1997 AND P.Conferenceld = 0 AND P.JournalId = 0;	redundant distinct	0	1
3636	What is the percentage of preprints of John Van Reenen's papers?	SELECT CAST(SUM(CASE WHEN T1.Conferenceld = 0 AND T1.JournalId = 0 THEN 1 ELSE 0 END) AS REAL) / COUNT(T1.Id) FROM Paper AS T1 INNER JOIN PaperAuthor AS T2 ON T1.Id = T2.PaperId WHERE T2.Name = 'John Van Reenen'	SELECT CAST(COUNT(DISTINCT CASE WHEN T1.Conferenceld = 0 AND T1.JournalId = 0 THEN T1.Id END) AS REAL) / COUNT(DISTINCT T1.Id) FROM Paper AS T1 INNER JOIN PaperAuthor AS T2 ON T1.Id = T2.PaperId WHERE T2.Name = 'John Van Reenen';	lack distinct	1	0
3637	What is the oldest published book?	SELECT Title FROM Paper WHERE Year > 0 ORDER BY Year ASC LIMIT 1	SELECT Title FROM Paper WHERE Year = (SELECT MIN(Year) FROM Paper WHERE Year > 0);	limit 1	0	1
3640	How many journals don't have a short name?	SELECT COUNT(ShortName) FROM Journal WHERE ShortName = ''	SELECT COUNT(*) FROM Journal WHERE ShortName IS NULL;	semantic error: wrong condition	0	1
3641	How many of the papers are preprinted?	SELECT COUNT(Id) FROM Paper WHERE Conferenceld = 0 AND JournalId = 0	SELECT COUNT(Id) FROM Paper WHERE Year = 0;	semantic error: wrong condition	0	1
3642	What is the title of the paper with the most authors?	SELECT T2.Title FROM PaperAuthor AS T1 INNER JOIN Paper AS T2 ON T1.PaperId = T2.Id GROUP BY T1.PaperId ORDER BY COUNT(T1.PaperId) DESC LIMIT 1	WITH RankedPapers AS (SELECT PaperId, RANK() OVER (ORDER BY COUNT(*) DESC) AS rk FROM PaperAuthor GROUP BY PaperId) SELECT P.Title FROM Paper P JOIN RankedPapers R ON P.Id = R.PaperId WHERE R.rk = 1	limit 1	0	1
3654	What is the proportion of the papers that have the keyword 'cancer'? Please provide a list of authors and their affiliations.	SELECT CAST(SUM(CASE WHEN T1.Keyword = 'cancer' THEN 1 ELSE 0 END) AS REAL) / COUNT(T1.Id), T2.Name, T2.Affiliation FROM Paper AS T1 INNER JOIN PaperAuthor AS T2 ON T1.Id = T2.PaperId	SELECT * FROM (SELECT CAST(SUM(CASE WHEN Keyword = 'cancer' THEN 1 ELSE 0 END) AS REAL) / COUNT(Id) FROM Paper) AS T1, (SELECT Name, Affiliation FROM Paper JOIN PaperAuthor ON Paper.Id = PaperAuthor.PaperId WHERE Keyword = 'cancer') AS T2	lack distinct; semantic error: wrong condition	0	0
3664	Calculate the average of authors for each paper from the year of 1990 to 2000.	SELECT CAST(COUNT(DISTINCT T2.AuthorId) AS REAL) / COUNT(DISTINCT T1.Title) FROM Paper AS T1 INNER JOIN PaperAuthor AS T2 ON T1.Id = T2.PaperId WHERE T1.Year BETWEEN 1990 AND 2000	SELECT AVG(count_authors) FROM (SELECT COUNT(PA.AuthorId) AS count_authors FROM Paper P LEFT JOIN PaperAuthor PA ON P.Id = PA.PaperId WHERE P.Year >= 1990 AND P.Year <= 2000 GROUP BY P.Id) AS temp_table;	join -> left join; distinct non-key	0	1
3678	State the year and title of papers written by Barrasa.	SELECT T1.Year, T1.Title FROM Paper AS T1 INNER JOIN PaperAuthor AS T2 ON T1.Id = T2.PaperId WHERE T2.Name = 'Barrasa'	SELECT Year, Title FROM Paper WHERE Id IN (SELECT PaperId FROM PaperAuthor WHERE Name = 'Barrasa');	join -> in-sub	0	1
3679	Sate the author name and published year for paper id 2?	SELECT T1.Name, T3.Year FROM Author AS T1 INNER JOIN PaperAuthor AS T2 ON T1.Id = T2.AuthorId INNER JOIN Paper AS T3 ON T2.PaperId = T3.Id WHERE T2.PaperId = 2	SELECT T2.Name, T1.Year FROM Paper T1 JOIN PaperAuthor T2 ON T1.Id = T2.PaperId WHERE T1.Id = 2;	semantic error: output column	0	1
3682	List the all the institutes from the state with the most number of American Indian in 2007.	SELECT T1.chronname FROM institution_details AS T1 INNER JOIN state_sector_grads AS T2 ON T1.state = T2.state WHERE T2.year = 2007 AND T2.race = 'Ai' GROUP BY T1.chronname ORDER BY COUNT(T1.chronname) DESC LIMIT 1	SELECT chronname FROM (SELECT state, rank() over (ORDER BY SUM(grad_cohort) DESC) as rk FROM state_sector_grads WHERE year = 2007 AND race = 'Ai' GROUP BY state) AS T JOIN institution_details ON T.state = institution_details.state WHERE rk = 1;	limit 1; semantic error: wrong group by	1	0

3683	State the name and website of the institutes from the state with 209 graduate cohort in 2011.	SELECT T1.chronname, T1.site FROM institution_details AS T1 INNER JOIN state_sector_grads AS T2 ON T1.state = T2.state WHERE T2.year = 2011 AND T2.grad_cohort = 209	SELECT T1.chronname, T1.site FROM institution_details AS T1 WHERE T1.state IN (SELECT T2.state FROM state_sector_grads AS T2 WHERE T2.year = 2011 GROUP BY T2.state HAVING SUM(grad_cohort) = 209);	join -> in-sub; semantic error: lack group by	1	0
3684	What is the number of female graduates between 2011 to 2013 from the state where 'Gateway Community College' is located?	SELECT COUNT(T2.grad_cohort) FROM institution_details AS T1 INNER JOIN state_sector_grads AS T2 ON T1.state = T2.state WHERE T2.year BETWEEN 2011 AND 2013 AND T1.chronname = 'Gateway Community College' AND T2.gender = 'F'	SELECT SUM(grad_cohort) FROM state_sector_grads WHERE state IN (SELECT state FROM institution_details WHERE chronname = 'Gateway Community College') AND gender = 'F' AND year BETWEEN 2011 AND 2013 GROUP BY state	semantic error: output column	0	0
3687	Name the state with the most number of graduate cohort in 2012 from private institute for profit? List all such institutes in the mentioned state.	SELECT T1.state, T1.chronname FROM institution_details AS T1 INNER JOIN state_sector_grads AS T2 ON T1.state = T2.state WHERE T2.year = 2012 AND T1.control = 'Private for-profit' GROUP BY T2.grad_cohort ORDER BY COUNT(T2.grad_cohort) DESC LIMIT 1	SELECT T1.state, T2.chronname FROM (SELECT T2.state, rank() over (ORDER BY SUM(T1.grad_cohort) DESC) as rk FROM institution_grads T1 JOIN institution_details T2 ON T1.unitid = T2.unitid WHERE T1.year = 2012 AND T2.control = 'Private for-profit' GROUP BY T2.state) AS T1 JOIN institution_details AS T2 ON T1.state = T2.state WHERE rk = 1 AND T2.control = 'Private for-profit'	limit 1; semantic error: wrong group by	1	0
3690	What is the number of female graduate for all students cohort from Oakwood University in 2013?	SELECT COUNT(*) FROM institution_details AS T1 INNER JOIN institution_grads AS T2 ON T1.unitid = T2.unitid WHERE T2.year = 2013 AND T2.gender = 'F' AND T2.race = 'X' AND T1.chronname = 'Oakwood University'	SELECT SUM(grad_cohort) FROM institution_details AS T1 INNER JOIN institution_grads AS T2 ON T1.unitid = T2.unitid WHERE T2.year = 2013 AND T2.gender = 'F' AND T2.race = 'X' AND T1.chronname = 'Oakwood University'	semantic error: output column	0	0
3692	Compare the graduate cohort for Auburn University from 2011 to 2013?	SELECT SUM(CASE WHEN T2.year = 2011 THEN T2.grad_cohort ELSE 0 END), SUM(CASE WHEN T2.year = 2012 THEN T2.grad_cohort ELSE 0 END), SUM(CASE WHEN T2.year = 2013 THEN T2.grad_cohort ELSE 0 END) FROM institution_details AS T1 INNER JOIN institution_grads AS T2 ON T1.unitid = T2.unitid WHERE T2.gender = 'B' AND T2.race = 'X' AND T1.chronname = 'Auburn University'	SELECT SUM(CASE WHEN T2.year = 2011 THEN T2.grad_cohort ELSE 0 END), SUM(CASE WHEN T2.year = 2012 THEN T2.grad_cohort ELSE 0 END), SUM(CASE WHEN T2.year = 2013 THEN T2.grad_cohort ELSE 0 END) FROM institution_details AS T1 INNER JOIN institution_grads AS T2 ON T1.unitid = T2.unitid WHERE T2.gender = 'B' AND T2.race = 'X' AND T1.chronname = 'Auburn University' AND T2.cohort IN ('4y other', '4y bach')	semantic error: lack condition	0	0
3694	Calculate the percentage of Asian students among students of other races who graduated from institution in Alabama in year 2013 within 100 percent of normal / expected time.	SELECT CAST(SUM(CASE WHEN T2.race = 'A' THEN 1 ELSE 0 END) AS REAL) * 100 / SUM(T2.grad_cohort) FROM institution_details AS T1 INNER JOIN institution_grads AS T2 ON T1.unitid = T2.unitid WHERE T2.year = 2013 AND T1.state = 'Alabama'	SELECT (SUM(CASE WHEN T2.race = 'A' THEN T2.grad_100 ELSE 0 END) * 100.0 / SUM(T2.grad_100)) AS percentage FROM institution_details T1 JOIN institution_grads T2 ON T1.unitid = T2.unitid WHERE T1.state = 'Alabama' AND T2.year = 2013 AND T2.grad_100 IS NOT NULL;	semantic error: wrong condition, output column	0	0
3696	From which institute is harder to graduate for a bachelor, Amridge University or Auburn University?	SELECT chronname FROM institution_details WHERE chronname IN ('Amridge University', 'Auburn University') ORDER BY grad_100_value LIMIT 1	SELECT chronname FROM (SELECT chronname, rank() over (ORDER BY grad_100_value) as rk FROM institution_details WHERE chronname IN ('Amridge University', 'Auburn University')) WHERE rk = 1	limit 1	0	0
3699	How many students that graduated from Lincoln College in 2011 belong to the cohort type of Bachelor's/equivalent seeking cohort at 4-year institutions?	SELECT COUNT(T1.unitid) FROM institution_details AS T1 INNER JOIN institution_grads AS T2 ON T1.unitid = T2.unitid WHERE T1.chronname = 'Lincoln College' AND T2.year = 2011 AND T2.cohort = '4y bach'	SELECT SUM(T2.grad_cohort) FROM institution_details AS T1 INNER JOIN institution_grads AS T2 ON T1.unitid = T2.unitid WHERE T1.chronname = 'Lincoln College' AND T2.year = 2011 AND T2.cohort = '4y bach' AND T2.gender != 'B' AND T2.race != 'X'	semantic error: output column	1	0

3701	How many students graduated from Central Alabama Community College in 2011 in total?	SELECT T2.grad_cohort FROM institution_details AS T1 INNER JOIN institution_grads AS T2 ON T1.unitid = T2.unitid WHERE T1.chronname = 'Central Alabama Community College' AND T2.year = 2011	SELECT SUM(T2.grad_cohort) FROM institution_details AS T1 INNER JOIN institution_grads AS T2 ON T1.unitid = T2.unitid WHERE T1.chronname = 'Central Alabama Community College' AND T2.year = 2011	semantic error: output column	0	0
3703	Which institute has the highest percentage of male White students graduating in 2011 within 150 percent of normal/expected time?	SELECT T1.chronname FROM institution_details AS T1 INNER JOIN institution_grads AS T2 ON T2.unitid = T1.unitid WHERE T2.year = 2011 AND T2.gender = 'M' AND T2.race = 'W' AND T2.grad_150 = (SELECT MAX(T2.grad_150) FROM institution_details AS T1 INNER JOIN institution_grads AS T2 ON T2.unitid = T1.unitid WHERE T2.year = 2011 AND T2.gender = 'M' AND T2.race = 'W')	SELECT chronname FROM (SELECT T2.chronname, rank() over (ORDER BY CAST(T1.grad_150_rate AS FLOAT) DESC) as rk FROM institution_grads T1 JOIN institution_details T2 ON T1.unitid = T2.unitid WHERE T1.year = 2011 AND T1.gender = 'M' AND T1.race = 'W' AND T1.grad_150_rate IS NOT NULL) WHERE rk = 1	limit 1; semantic error: wrong condition	0	0
3704	Please list the names of the institutes with the percentage of male White students graduating in 2011 within 150 percent of normal/expected time over 20.	SELECT T FROM (SELECT DISTINCT CASE WHEN T2.grad_150 > 20 THEN T1.chronname ELSE NULL END AS T FROM institution_details T1 INNER JOIN institution_grads T2 ON T2.unitid = T1.unitid WHERE T2.year = 2011 AND T2.gender = 'M' AND T2.race = 'W') WHERE T IS NOT NULL	SELECT T FROM (SELECT CASE WHEN T2.grad_150 > 20 THEN T1.chronname ELSE NULL END AS T FROM institution_details T1 INNER JOIN institution_grads T2 ON T2.unitid = T1.unitid WHERE T2.year = 2011 AND T2.gender = 'M' AND T2.race = 'W') WHERE T IS NOT NULL	redundant distinct	1	0
3708	Among the public institutes in the state of Alabama, how many of them have over 30 students who graduated within 100 percent of normal/expected time in 2011?	SELECT COUNT(T1.chronname) FROM institution_details AS T1 INNER JOIN institution_grads AS T2 ON T2.unitid = T1.unitid WHERE T1.state = 'Alabama' AND T1.control = 'Public' AND T2.year = 2011 AND T2.grad_100 > 30	SELECT COUNT(*) FROM (SELECT T1.unitid FROM institution_details AS T1 INNER JOIN institution_grads AS T2 ON T2.unitid = T1.unitid WHERE T1.state = 'Alabama' AND T1.control = 'Public' AND T2.year = 2011 GROUP BY T1.unitid HAVING SUM(T2.grad_100) > 30);	semantic error: lack group by	0	0
3712	Give the web site address for 'Swarthmore College'.	SELECT T FROM (SELECT DISTINCT CASE WHEN chronname = 'Swarthmore College' THEN site ELSE NULL END AS T FROM institution_details) WHERE T IS NOT NULL	SELECT site FROM institution_details WHERE chronname = 'Swarthmore College';	redundant distinct	0	1
3714	Which city is 'Rensselaer Polytechnic Institute' located in?	SELECT T FROM (SELECT DISTINCT CASE WHEN chronname = 'Rensselaer Polytechnic Institute' THEN city ELSE NULL END AS T FROM institution_details) WHERE T IS NOT NULL	SELECT city FROM institution_details WHERE chronname = 'Rensselaer Polytechnic Institute';	redundant distinct	0	1
3718	Tell the name of school in 'NJ' that could get the bachelor's degree with highest students number.	SELECT DISTINCT T1.chronname FROM institution_details AS T1 INNER JOIN state_sector_grads AS T2 ON T2.state = T1.state WHERE T2.state_abbr = 'NJ' AND T1.level = '4-year' AND T1.student_count = (SELECT MAX(T1.student_count) FROM institution_details AS T1 INNER JOIN state_sector_grads AS T2 ON T2.state = T1.state WHERE T2.state_abbr = 'NJ' AND T1.level = '4-year')	SELECT T1.chronname FROM institution_details AS T1 WHERE T1.level = '4-year' AND T1.student_count = (SELECT MAX(T1.student_count) FROM institution_details AS T1 INNER JOIN state_sector_grads AS T2 ON T2.state = T1.state WHERE T2.state_abbr = 'NJ' AND T1.level = '4-year') AND T1.state IN (SELECT state FROM state_sector_grads WHERE state_abbr = 'NJ')	join -> in-sub	0	0
3719	Give the web site address for the school in 'PA' state with the highest latitude.	SELECT DISTINCT T1.site FROM institution_details AS T1 INNER JOIN state_sector_grads AS T2 ON T2.state = T1.state WHERE T2.state_abbr = 'PA' AND T1.lat_y = (SELECT MAX(T1.lat_y) FROM institution_details AS T1 INNER JOIN state_sector_grads AS T2 ON T2.state = T1.state WHERE T2.state_abbr = 'PA')	SELECT site FROM institution_details WHERE state = 'PA' AND lat_y = (SELECT MAX(lat_y) FROM institution_details WHERE state = 'PA');	semantic error: misunderstand state 'PA'	0	1

3720	Tell the number of 4-year public schools in UT whose graduation rate exceeds the average for the state.	SELECT COUNT(DISTINCT T1.chronname) FROM institution_details AS T1 INNER JOIN state_sector_grads AS T2 ON T2.state = T1.state WHERE T2.state_abbr = 'UT' AND T1.level = '4-year' AND T1.control = 'Public' AND T1.awards_per_value > T1.awards_per_state_value	SELECT COUNT(DISTINCT T1.unitid) FROM institution_details AS T1 INNER JOIN state_sector_grads AS T2 ON T2.state = T1.state WHERE T2.state_abbr = 'UT' AND T1.level = '4-year' AND T1.control = 'Public' AND T1.awards_per_value > T1.awards_per_state_value	distinct non-key	1	0
3721	How many 2-year private nonprofit schools in 'CT' whose graduation rate falls below the average for the state?	SELECT COUNT(DISTINCT T1.chronname) FROM institution_details AS T1 INNER JOIN state_sector_grads AS T2 ON T2.state = T1.state WHERE T2.state_abbr = 'CT' AND T2.level = '2-year' AND T1.control = 'Private not-for-profit' AND T1.awards_per_value < T1.awards_per_natl_value	SELECT COUNT(DISTINCT T1.unitid) FROM institution_details AS T1 INNER JOIN state_sector_grads AS T2 WHERE T1.state = T2.state AND T1.level = '2-year' AND T1.control = 'Private not-for-profit' AND T2.state_abbr = 'CT' AND T1.awards_per_value < T1.awards_per_state_value;	distinct non-key	0	1
3722	Give the name of the 4-year public school in 'ID' with the lowest graduation 100 value.	SELECT T1.chronname FROM institution_details AS T1 INNER JOIN state_sector_grads AS T2 ON T2.state = T1.state WHERE T2.state_abbr = 'ID' AND T1.level = '4-year' AND T1.control = 'Public' GROUP BY T1.chronname ORDER BY SUM(T1.grad_100_value) ASC LIMIT 1	SELECT chronname FROM (SELECT T1.chronname, rank() over (ORDER BY T1.grad_100_value ASC) as rk FROM institution_details AS T1 WHERE T1.state IN (SELECT T2.state FROM state_sector_grads AS T2 WHERE T2.state_abbr = 'ID') AND T1.level = '4-year' AND T1.control = 'Public') WHERE rk = 1	limit 1; join -> in-sub	0	0
3723	Which 4-year private for-profit school in 'KY' has the highest graduation 150 value? Give the ID for the school.	SELECT T1.chronname, T1.unitid FROM institution_details AS T1 INNER JOIN state_sector_grads AS T2 ON T2.state = T1.state WHERE T2.state_abbr = 'KY' AND T1.level = '4-year' AND T1.control = 'Private for-profit' GROUP BY T1.chronname ORDER BY SUM(T1.grad_150_value) DESC LIMIT 1	SELECT unitid FROM (SELECT T1.unitid, rank() over (ORDER BY T1.grad_150_value DESC) AS rk FROM institution_details AS T1 WHERE T1.state IN (SELECT T2.state FROM state_sector_grads AS T2 WHERE T2.state_abbr = 'KY') AND T1.level = '4-year' AND T1.control = 'Private for-profit') WHERE rk = 1	limit 1; join -> in-sub; semantic error: output column	0	0
3725	Give the cohort name for the school with biggest cohort size.	SELECT DISTINCT T1.chronname FROM institution_details AS T1 INNER JOIN institution_grads AS T2 ON T2.unitid = T1.unitid WHERE T1.cohort_size = (SELECT MAX(T1.cohort_size) FROM institution_details AS T1 INNER JOIN institution_grads AS T2 ON T2.unitid = T1.unitid)	SELECT T2.cohort FROM institution_details T1 JOIN institution_grads T2 ON T1.unitid = T2.unitid WHERE T1.cohort_size = (SELECT MAX(cohort_size) FROM institution_details);	semantic error: output column	0	1
3727	Give the total number of all graduated students from a 2-year public schools in Alabama in 2011.	SELECT SUM(T2.grad_cohort) FROM state_sector_details AS T1 INNER JOIN state_sector_grads AS T2 ON T2.stateid = T1.stateid WHERE T1.state = 'Alabama' AND T2.year = 2011 AND T1.level = '2-year' AND T1.control = 'Public' AND T2.race = 'X'	SELECT SUM(grad_cohort) FROM state_sector_grads WHERE state = 'Alabama' AND control = 'Public' AND level = '2-year' AND year = 2011 AND race = 'X';	semantic error: redundant join	0	1
3729	What is the percentage of the number of 4-year public schools from Madison Area Technical College's home state in the Alabama?	SELECT CAST(COUNT(DISTINCT CASE WHEN T1.state = (SELECT T1.state FROM institution_details AS T1 INNER JOIN state_sector_details AS T2 ON T2.state = T1.state WHERE T1.chronname = 'Madison Area Technical College') AND T1.level = '4-year' AND T1.control = 'Public' THEN T1.chronname ELSE NULL END) AS REAL) * 100 / COUNT(DISTINCT CASE WHEN T2.state = 'Alabama' THEN T1.chronname ELSE NULL END) FROM institution_details AS T1 INNER JOIN state_sector_details AS T2 ON T2.state = T1.state	SELECT CAST(COUNT(CASE WHEN T1.state IN (SELECT T1.state FROM institution_details AS T1 WHERE T1.chronname = 'Madison Area Technical College') AND T1.level = '4-year' AND T1.control = 'Public' THEN T1.chronname END) AS REAL) * 100 / COUNT(CASE WHEN T1.state = 'Alabama' THEN T1.chronname END) FROM institution_details AS T1;	distinct non-key	0	0

3730	Give the state and name of institutions in year of data release from 2010 to 2012 with black students.	SELECT DISTINCT T1.state, T1.chronname FROM institution_details AS T1 INNER JOIN institution_grads AS T2 ON T2.unitid = T1.unitid WHERE T2.race = 'B' AND T2.year BETWEEN 2010 AND 2012	SELECT T1.state, T1.chronname FROM institution_details T1 JOIN institution_grads T2 ON T1.unitid = T2.unitid WHERE T2.year BETWEEN 2010 AND 2012 AND T2.race = 'B';	distinct non-key	0	1
3732	Among the race of all students, what is the control of institution and level of institution with highest number of students?	SELECT DISTINCT T1.control, T1.level FROM institution_details AS T1 INNER JOIN institution_grads AS T2 ON T2.unitid = T1.unitid WHERE T2.race = 'X' AND T1.student_count = (SELECT MAX(T1.student_count) FROM institution_details AS T1 INNER JOIN institution_grads AS T2 ON T2.unitid = T1.unitid WHERE T2.race = 'X')	SELECT T1.control, T1.level FROM institution_details AS T1 INNER JOIN institution_grads AS T2 ON T2.unitid = T1.unitid WHERE T2.race = 'X' AND T1.student_count = (SELECT MAX(T1.student_count) FROM institution_details AS T1 INNER JOIN institution_grads AS T2 ON T2.unitid = T1.unitid WHERE T2.race = 'X') GROUP BY T1.unitid	distinct non-key	0	0
3734	List the basic of the institution in 2012 with race of all male students.	SELECT DISTINCT T1.basic, T2.race FROM institution_details AS T1 INNER JOIN institution_grads AS T2 ON T2.unitid = T1.unitid WHERE T2.year = 2012 AND T2.gender = 'M' AND T2.race = 'X'	SELECT basic FROM institution_details WHERE unitid IN (SELECT unitid FROM institution_grads WHERE year = 2012 AND gender = 'M' AND race = 'X');	semantic error: output column	0	1
3735	In Alaska with school count of 1 from year 2011 to 2013, how many of the students are white?	SELECT COUNT(T2.race) FROM state_sector_details AS T1 INNER JOIN state_sector_grads AS T2 ON T2.stateid = T1.stateid WHERE T1.schools_count = 1 AND T2.year BETWEEN 2011 AND 2013 AND T2.race = 'W' AND T1.state = 'Alaska'	SELECT SUM(grad_cohort_ct) FROM state_sector_grads WHERE state = 'Alaska' AND year BETWEEN 2011 AND 2013 AND race = 'W' AND grad_cohort_ct = 1;	semantic error: output column	1	0
3736	What is the institution's name of american students within the number of degree-seeking students in the cohort that ranges from 1 to 3?	SELECT DISTINCT T1.chronname FROM institution_details AS T1 INNER JOIN institution_grads AS T2 ON T2.unitid = T1.unitid WHERE T2.grad_cohort BETWEEN 1 AND 3 AND T2.race = 'Ai'	SELECT T1.chronname FROM institution_details T1 INNER JOIN institution_grads T2 ON T1.unitid = T2.unitid WHERE T2.race = 'Ai' AND T2.grad_cohort IN ('1', '2', '3');	redundant distinct	0	1
3739	What is the state name of male graduate in 2011 from a private for profit institution with black students?	SELECT DISTINCT T1.state FROM state_sector_details AS T1 INNER JOIN state_sector_grads AS T2 ON T2.stateid = T1.stateid WHERE T2.gender = 'M' AND T2.race = 'B' AND T1.control = 'Private for-profit' AND T2.year = 2011	SELECT state FROM institution_details WHERE unitid IN (SELECT unitid FROM institution_grads WHERE year = 2011 AND gender = 'M' AND race = 'B') AND control = 'Private for-profit';	join -> in-sub	0	1
3740	Among the black students in 2011, list the institution site and name of those who has 20 to 30 degree-seeking students in the cohort.	SELECT DISTINCT T1.site, T1.chronname FROM institution_details AS T1 INNER JOIN institution_grads AS T2 ON T2.unitid = T1.unitid WHERE T2.year = 2011 AND T2.race = 'B' AND T2.grad_cohort BETWEEN 20 AND 30	SELECT site, chronname FROM institution_details WHERE unitid IN (SELECT unitid FROM institution_grads WHERE year = 2011 AND race = 'B' AND CAST(grad_cohort AS INTEGER) BETWEEN 20 AND 30);	join -> in-sub	0	0
3742	List the race of institutions in Alabama with number of students greater than the 90% of average number of students of all institutions?	SELECT DISTINCT T2.race FROM institution_details AS T1 INNER JOIN institution_grads AS T2 ON T2.unitid = T1.unitid WHERE T1.student_count > (SELECT AVG(T1.student_count) * 0.9 FROM institution_details AS T1 INNER JOIN institution_grads AS T2 ON T2.unitid = T1.unitid WHERE T1.state = 'Alabama') AND T1.state = 'Alabama'	SELECT DISTINCT T2.race FROM institution_details AS T1 INNER JOIN institution_grads AS T2 ON T2.unitid = T1.unitid WHERE T1.student_count > (SELECT AVG(T1.student_count) * 0.9 FROM institution_details AS T1) AND T1.state = 'Alabama'	semantic error: wrong condition	0	0
3746	In Harvard University, which year recorded the highest number of first-time, full-time, degree-seeking students in the cohort being tracked, minus any exclusions?	SELECT T2.year FROM institution_details AS T1 INNER JOIN institution_grads AS T2 ON T2.unitid = T1.unitid WHERE T1.chronname = 'Harvard University' GROUP BY T2.year ORDER BY SUM(T2.grad_cohort) DESC LIMIT 1	SELECT year FROM (SELECT T2.year, rank() over (ORDER BY SUM(T2.grad_cohort) DESC) as rk FROM institution_details AS T1 INNER JOIN institution_grads AS T2 ON T2.unitid = T1.unitid WHERE T1.chronname = 'Harvard University' GROUP BY T2.year) WHERE rk = 1	limit 1	0	0

3747	In the state with the highest state appropriations to higher education in fiscal year 2011 per resident, which institution has the lowest number of undergraduates in 2010?	SELECT T1.chronname FROM institution_details AS T1 INNER JOIN state_sector_details AS T2 ON T2.state = T1.state INNER JOIN institution_grads AS T3 ON T3.unitid = T1.unitid WHERE T1.student_count = (SELECT MIN(T1.student_count) FROM institution_details AS T1 INNER JOIN state_sector_details AS T2 ON T2.state = T1.state INNER JOIN institution_grads AS T3 ON T3.unitid = T1.unitid WHERE T3.year = 2010) AND T3.year = 2010 GROUP BY T1.state ORDER BY SUM(T2.state_appr_value) DESC LIMIT 1	SELECT chronname FROM (SELECT T2.chronname, RANK() OVER (PARTITION BY T2.state ORDER BY student_count DESC) as rank FROM (SELECT state, rank() over (ORDER BY max(state_appr_value) DESC) as rk FROM state_sector_details GROUP BY stateid) AS T1 JOIN institution_details AS T2 ON T1.state = T2.state WHERE T1.rk = 1) WHERE rank = 1	limit 1	1	0
3749	Among the Ivy League Schools, which school have the highest number of Hispanic graduates of all time?	SELECT T1.chronname FROM institution_details AS T1 INNER JOIN institution_grads AS T2 ON T2.unitid = T1.unitid WHERE T1.chronname IN ('Brown University', 'Columbia University', 'Cornell University', 'Dartmouth College', 'Harvard University', 'Princeton University', 'University of Pennsylvania', 'Yale University') AND T2.race = 'H' GROUP BY T1.chronname ORDER BY SUM(T2.grad_cohort) DESC LIMIT 1	SELECT chronname FROM (SELECT T1.chronname, rank() over (ORDER BY SUM(T2.grad_cohort) DESC) as rk FROM institution_details AS T1 INNER JOIN institution_grads AS T2 ON T2.unitid = T1.unitid WHERE T1.chronname IN ('Brown University', 'Columbia University', 'Cornell University', 'Dartmouth College', 'Harvard University', 'Princeton University', 'University of Pennsylvania', 'Yale University') AND T2.race = 'H' GROUP BY T1.unitid) WHERE rk = 1	limit 1; group by non-key	1	0
3750	How many 4-year public institutions are there in the state of Florida? Give all of their names.	SELECT T1.chronname FROM institution_details AS T1 INNER JOIN state_sector_details AS T2 WHERE T2.level = '4-year' AND T2.control = 'Public' AND T2.state = 'Florida'	SELECT chronname FROM institution_details WHERE level = '4-year' AND control = 'Public' AND state = 'Florida';	semantic error: redundant join	0	1
3752	In the state with the highest number of schools, how many institutions have a percentage of no less than 90 of undergraduates who attend full-time? List all of the institutions' names.	SELECT COUNT(t1.unitid), t1.chronname FROM institution_details AS T1 INNER JOIN state_sector_details AS T2 ON t1.state = t2.state WHERE t1.ft_pct > 90 ORDER BY t2.schools_count DESC LIMIT 1	SELECT chronname FROM institution_details WHERE state = (SELECT state FROM state_sector_details ORDER BY schools_count DESC LIMIT 1) AND ft_pct >= 90;	semantic error: output column	0	1
3753	What is the average SAT value for incoming students in all of the schools located in the state with the lowest state appropriations to higher education in fiscal year 2011 per resident?	SELECT AVG(t1.med_sat_value) FROM institution_details AS T1 INNER JOIN state_sector_details AS T2 ON t1.state = t2.state ORDER BY t2.state_appr_value LIMIT 1	SELECT AVG(CAST(T2.med_sat_value AS INTEGER)) FROM state_sector_details T1 JOIN institution_details T2 ON T1.state = T2.state WHERE T1.state_appr_value = (SELECT MIN(state_appr_value) FROM state_sector_details) AND T2.med_sat_value IS NOT NULL	limit 1	0	1
3754	What is the name of the school with the highest number of first-time, full-time, degree-seeking female students in the cohort being tracked, minus any exclusions who were seeking another type of degree or certificate at a 4-year institution?	SELECT T1.chronname FROM institution_details AS T1 INNER JOIN institution_grads AS T2 ON T2.unitid = T1.unitid WHERE T2.gender = 'F' AND T2.cohort = '4y other' ORDER BY T2.grad_cohort DESC LIMIT 1	SELECT T1.chronname FROM institution_details T1 INNER JOIN (SELECT unitid, MAX(grad_cohort) AS max_grads FROM institution_grads WHERE gender = 'F' AND cohort = '4y other' GROUP BY unitid) T2 ON T1.unitid = T2.unitid WHERE T2.max_grads = (SELECT MAX(grad_cohort) FROM institution_grads WHERE gender = 'F' AND cohort = '4y other');	limit 1	0	1

3755	Among the Ivy League Schools in 2013, which schools have the highest number of Black students who graduated within 150 percent of normal/expected time who were seeking a bachelor's/equivalent cohort at 4-year institutions?	SELECT T1.chronname FROM institution_details AS T1 INNER JOIN institution_grads AS T2 ON T2.unitid = T1.unitid WHERE T1.chronname IN ('Brown University', 'Columbia University', 'Cornell University', 'Dartmouth College', 'Harvard University', 'Princeton University', 'University of Pennsylvania', 'Yale University') AND T2.year = 2013 AND T2.race = 'B' AND T2.cohort = '4y bach' ORDER BY T2.grad_cohort DESC LIMIT 1	SELECT chronname FROM (SELECT T1.chronname, rank() over (ORDER BY grad_150 DESC) as rk FROM institution_details AS T1 INNER JOIN institution_grads AS T2 ON T2.unitid = T1.unitid WHERE T1.chronname IN ('Brown University', 'Columbia University', 'Cornell University', 'Dartmouth College', 'Harvard University', 'Princeton University', 'University of Pennsylvania', 'Yale University') AND T2.year = 2013 AND T2.race = 'B' AND T2.cohort = '4y bach') WHERE rk = 1	limit 1; semantic error: order by wrong column	1	0
4622	In which segment did the Walt Disney Company earned a bigger revenue in 1998, Studio Entertainment or Disney Media Networks?	SELECT CASE WHEN 'Studio Entertainment[NI 1]' > 'Disney Media Networks' THEN 'Studio Entertainment[NI 1]' ELSE 'Disney Media Networks' END FROM revenue WHERE 'Year' = 1998	SELECT CASE WHEN "Studio Entertainment[NI 1]" > "Disney Media Networks" THEN 'Studio Entertainment' ELSE 'Disney Media Networks' END AS Higher_Revenue_Segment FROM revenue WHERE Year = 1998;	semantic error	0	1
4629	Among the movies in which Alan Tudyk is a voice actor, how many of them were released after 2012?	SELECT COUNT(T2.movie) FROM characters AS T1 INNER JOIN 'voice-actors' AS T2 ON T1.movie_title = T2.movie WHERE T2.'voice-actor' = 'Alan Tudyk' AND SUBSTR(release_date, INSTR(release_date, '-') + 5) > 12	SELECT COUNT(DISTINCT T1.movie) FROM 'voice-actors' T1 JOIN characters T2 ON T1.movie = T2.movie_title WHERE T1.'voice-actor' = 'Alan Tudyk' AND CAST(SUBSTR(T2.release_date , INSTR(T2.release_date , '-') + 5) AS INTEGER) > 12;	lack distinct	0	0
4631	Among the movies directed by Wolfgang Reitherman, which one of them was the most popular?	SELECT T2.movie_title FROM director AS T1 INNER JOIN movies_total_gross AS T2 ON T1.name = T2.movie_title WHERE T1.director = 'Wolfgang Reitherman' ORDER BY T2.total_gross DESC LIMIT 1	SELECT movie_title FROM (SELECT T2.movie_title, rank() over (ORDER BY CAST(REPLACE(SUBSTR(T2.total_gross, 2), ',', '')) AS float) DESC) as rk FROM director AS T1 INNER JOIN movies_total_gross AS T2 ON T1.name = T2.movie_title WHERE T1.director = 'Wolfgang Reitherman') WHERE rk = 1	limit 1; semantic error: str compare	1	0
4633	Which character is the villain of the most popular movie?	SELECT T2.villain FROM 'movies_total_gross' AS T1 INNER JOIN characters AS T2 ON T1.movie_title = T2.movie_title ORDER BY T1.total_gross DESC LIMIT 1	SELECT villain FROM (SELECT T2.villain, rank() over (ORDER BY CAST(REPLACE(SUBSTR(T1.total_gross, 2), ',', '')) AS float) DESC) as rk FROM 'movies_total_gross' AS T1 INNER JOIN characters AS T2 ON T1.movie_title = T2.movie_title) WHERE rk = 1;	limit 1; semantic error: str compare	1	0
4640	Which song is associated with the most popular Disney movie in 1970s?	SELECT T2.song FROM movies_total_gross AS T1 INNER JOIN characters AS T2 ON T1.movie_title = T2.movie_title WHERE CAST(SUBSTR(T1.release_date, INSTR(T1.release_date, ',') + 1) AS int) BETWEEN 1970 AND 1979 ORDER BY CAST(REPLACE(SUBSTR(T1.total_gross, 2), ',', '')) AS float) DESC LIMIT 1	SELECT song FROM (SELECT T2.song, rank() over (ORDER BY CAST(REPLACE(SUBSTR(T1.total_gross, 2), ',', '')) AS float) DESC) as rk FROM movies_total_gross AS T1 INNER JOIN characters AS T2 ON T1.movie_title = T2.movie_title WHERE CAST(SUBSTR(T1.release_date, INSTR(T1.release_date, ',') + 1) AS int) BETWEEN 1970 AND 1979) WHERE rk = 1	limit 1	1	0
4646	Wolfgang Reitherman has directed several Disney movies, which one has the highest grossing after accounting for inflation?	SELECT T1.movie_title FROM movies_total_gross AS T1 INNER JOIN director AS T2 ON T1.movie_title = T2.name WHERE T2.director = 'Wolfgang Reitherman' ORDER BY CAST(REPLACE(SUBSTR(inflation_adjusted_gross, 2), ',', '')) AS REAL) DESC LIMIT 1	SELECT movie_title FROM (SELECT T1.movie_title, rank() over (ORDER BY CAST(REPLACE(SUBSTR(inflation_adjusted_gross, 2), ',', '')) AS REAL) DESC) as rk FROM movies_total_gross AS T1 INNER JOIN director AS T2 ON T1.movie_title = T2.name WHERE T2.director = 'Wolfgang Reitherman') WHERE rk = 1	limit 1	1	0

4648	The character Donald Duck has appeared in two Disney movies, which one has more grossing?	SELECT T1.movie_title FROM movies_total_gross AS T1 INNER JOIN characters AS T2 ON T1.movie_title = T2.movie_title WHERE T2.hero = 'Donald Duck' ORDER BY CAST(REPLACE(SUBSTR(total_gross, 2), ',', '')) AS REAL) DESC LIMIT 1	SELECT movie_title FROM (SELECT T1.movie_title, rank() over (ORDER BY CAST(REPLACE(SUBSTR(total_gross, 2), ',', '')) AS REAL) DESC) as rk FROM movies_total_gross AS T1 INNER JOIN characters AS T2 ON T1.movie_title = T2.movie_title WHERE T2.hero = 'Donald Duck') WHERE rk = 1	limit 1	1	0
4658	What is the most popular movie directed by Ron Clements?	SELECT T2.name FROM movies_total_gross AS T1 INNER JOIN director AS T2 ON T2.name = T1.movie_title WHERE T2.director = 'Ron Clements' ORDER BY CAST(REPLACE(SUBSTR(total_gross, 2), ',', '')) AS int) DESC LIMIT 1	SELECT name FROM (SELECT T2.name, rank() over (ORDER BY CAST(REPLACE(SUBSTR(total_gross, 2), ',', '')) AS int) DESC) as rk FROM movies_total_gross AS T1 INNER JOIN director AS T2 ON T2.name = T1.movie_title WHERE T2.director = 'Ron Clements') WHERE rk = 1;	limit 1	1	0
4672	What is the highest grossing movie without a song?	SELECT T1.movie_title FROM movies_total_gross AS T1 INNER JOIN characters AS T2 ON T2.movie_title = T1.movie_title WHERE T2.song IS NULL ORDER BY CAST(REPLACE(trim(T1.total_gross, '\$'), ',', '')) AS REAL) DESC LIMIT 1	SELECT movie_title FROM (SELECT T1.movie_title, rank() over (ORDER BY CAST(REPLACE(trim(T1.total_gross, '\$'), ',', '')) AS REAL) DESC) as rk FROM movies_total_gross AS T1 INNER JOIN characters AS T2 ON T2.movie_title = T1.movie_title WHERE T2.song IS NULL) WHERE rk = 1	limit 1	1	0
4676	What are the total grosses for the movies with Jim Cummings as the voice actor?	SELECT T2.movie_title FROM 'voice-actors' AS T1 INNER JOIN movies_total_gross AS T2 ON T2.movie_title = T1.movie WHERE T1.'voice-actor' = 'Jim Cummings' ORDER BY CAST(REPLACE(trim(T2.total_gross, '\$'), ',', '')) AS REAL) DESC LIMIT 1	SELECT total_gross FROM movies_total_gross WHERE movie_title IN (SELECT movie FROM 'voice-actors' WHERE 'voice-actor' = 'Jim Cummings');	limit 1; redundant order by; join -> in-sub; semantic error: output column	0	1
4683	Provide the movie titles and the estimated inflation rate of the highest total grossed movie.	SELECT movie_title, CAST(REPLACE(trim(inflation_adjusted_gross '\$'), ',', '')) AS REAL) / CAST(REPLACE(trim(total_gross, '\$'), ',', '')) AS REAL) FROM movies_total_gross ORDER BY CAST(REPLACE(trim(total_gross, '\$'), ',', '')) AS REAL) DESC LIMIT 1	SELECT movie_title, inflation FROM (SELECT movie_title, rank() over (ORDER BY CAST(REPLACE(trim(total_gross, '\$'), ',', '')) AS REAL) DESC) as rk, CAST(REPLACE(trim(inflation_adjusted_gross '\$'), ',', '')) AS REAL) / CAST(REPLACE(trim(total_gross, '\$'), ',', '')) AS REAL) as inflation FROM movies_total_gross) WHERE rk = 1	limit 1	0	0
4707	Name the villain of the movie with Scott Weinger and Brad Kane as voice actors.	SELECT T1.villain FROM characters AS T1 INNER JOIN 'voice-actors' AS T2 ON T1.movie_title = T2.movie WHERE T2.'voice-actor' = 'Scott Weinger Brad Kane'	SELECT villain FROM characters WHERE movie_title IN (SELECT movie FROM 'voice-actors' WHERE 'voice-actor' = 'Scott Weinger') AND movie_title IN (SELECT movie FROM 'voice-actors' WHERE 'voice-actor' = 'Brad Kane')	semantic error: wrong condition	1	0
4712	Which director had the most popular film from 1937 to 1990?	SELECT T2.director FROM characters AS T1 INNER JOIN director AS T2 ON T1.movie_title = T2.name INNER JOIN movies_total_gross AS T3 ON T3.movie_title = T1.movie_title WHERE SUBSTR(T3.release_date, LENGTH(T3.release_date) - 3, LENGTH(T3.release_date)) BETWEEN '1937' AND '1990' ORDER BY CAST(REPLACE(trim(T3.total_gross, '\$'), ',', '')) AS REAL) DESC LIMIT 1	SELECT DISTINCT director FROM (SELECT T2.director, rank() over (ORDER BY CAST(REPLACE(trim(T3.total_gross, '\$'), ',', '')) AS REAL) DESC) as rk FROM characters AS T1 INNER JOIN director AS T2 ON T1.movie_title = T2.name INNER JOIN movies_total_gross AS T3 ON T3.movie_title = T1.movie_title WHERE SUBSTR(T3.release_date, LENGTH(T3.release_date) - 3, LENGTH(T3.release_date)) BETWEEN '1937' AND '1990') WHERE rk = 1;	limit 1	0	0
4721	Who was the first ever Disney villain?	SELECT villain FROM characters ORDER BY SUBSTR(release_date, LENGTH(release_date) - 1, LENGTH(release_date)) DESC LIMIT 1	SELECT villain FROM (SELECT villain, rank() over (ORDER BY SUBSTR(release_date, LENGTH(release_date) - 1, LENGTH(release_date))) DESC) as rk FROM characters) WHERE rk = 1	limit 1	1	0
4722	What is Disney's highest grossing action movie?	SELECT movie_title FROM movies_total_gross WHERE genre = 'Action' ORDER BY CAST(REPLACE(trim(total_gross, '\$'), ',', '')) AS REAL) DESC LIMIT 1	SELECT movie_title FROM (SELECT movie_title, rank() over (ORDER BY CAST(REPLACE(trim(total_gross, '\$'), ',', '')) AS REAL) DESC) as rk FROM movies_total_gross WHERE genre = 'Action') WHERE rk = 1;	limit 1	1	0

4725	Name the main character of Disney's most popular adventure movie based on its inflation-adjusted gross.	SELECT T2.hero FROM movies_total_gross AS T1 INNER JOIN characters AS T2 ON T1.movie_title = T2.movie_title WHERE T1.genre = 'Adventure' ORDER BY CAST(REPLACE(trim(T1.inflation_adjusted_gross, '\$'), ', ', '')) AS REAL) DESC LIMIT 1	SELECT hero FROM (SELECT T2.hero, rank() over (ORDER BY CAST(REPLACE(trim(T1.inflation_adjusted_gross, '\$'), ', ', '')) AS REAL) DESC) as rk FROM movies_total_gross AS T1 INNER JOIN characters AS T2 ON T1.movie_title = T2.movie_title WHERE T1.genre = 'Adventure' WHERE rk = 1;	limit 1	1	0
4726	Name the director of Disney's lowest grossing movie.	SELECT T2.director FROM movies_total_gross AS T1 INNER JOIN director AS T2 ON T1.movie_title = T2.name ORDER BY CAST(REPLACE(trim(T1.total_gross, '\$'), ', ', '')) AS REAL) ASC LIMIT 1	SELECT director FROM (SELECT T2.director, rank() over (ORDER BY CAST(REPLACE(trim(T1.total_gross, '\$'), ', ', '')) AS REAL) ASC) as rk FROM movies_total_gross AS T1 INNER JOIN director AS T2 ON T1.movie_title = T2.name WHERE rk = 1;	limit 1	1	0
4728	Determine the average gross for Disney's PG-13-rated action movies.	SELECT SUM(CAST(REPLACE(trim(total_gross, '\$'), ', ', '')) AS REAL) / COUNT(movie_title) FROM movies_total_gross WHERE MPAA_rating = 'PG-13'	SELECT SUM(CAST(REPLACE(trim(total_gross, '\$'), ', ', '')) AS REAL) / COUNT(movie_title) FROM movies_total_gross WHERE MPAA_rating = 'PG-13' AND genre = 'Action'	semantic error: wrong condition	1	0
4746	What is the username of the current official Facebook presence of the oldest current legislator?	SELECT T2.facebook FROM current AS T1 INNER JOIN 'social-media' AS T2 ON T2.bioguide_id = T1.bioguide_id ORDER BY T1.birthdate LIMIT 1	SELECT T2.facebook FROM current AS T1 JOIN 'social-media' AS T2 ON T1.bioguide_id = T2.bioguide_id WHERE T1.birthdate_bio = (SELECT MIN(birthdate_bio) FROM current) AND T2.facebook IS NOT NULL;	limit 1	0	1
4757	How many current legislators chose Republican as their political party?	SELECT COUNT(*) FROM 'current-terms' WHERE party = 'Republican'	SELECT COUNT(DISTINCT bioguide) FROM 'current-terms' WHERE party = 'Republican';	lack distinct	0	1
4761	What type of political party Sherrod Brown has in 2005?	SELECT T1.party FROM 'current-terms' AS T1 INNER JOIN current AS T2 ON T2.bioguide_id = T1.bioguide_id WHERE T2.first_name = 'Sherrod' AND T2.last_name = 'Brown' AND T1.start LIKE '%2005%'	SELECT T2.party FROM current T1 JOIN 'current-terms' T2 ON T1.bioguide_id = T2.bioguide_id WHERE T1.official_full_name = 'Sherrod Brown' AND strftime('%Y', T2.start) = '2005';	semantic error: wrong condition	0	1
4765	List the last name of all current legislators who live in California.	SELECT T1.last_name FROM current AS T1 INNER JOIN 'current-terms' AS T2 ON T1.bioguide_id = T2.bioguide_id WHERE T2.state = 'CA' GROUP BY T1.last_name	SELECT last_name FROM current WHERE bioguide_id IN (SELECT bioguide FROM 'current-terms' WHERE state = 'CA');	join -> in-sub	0	1
4769	List the full name of all past legislators that chose Pro-Administration as their political party in year 1791.	SELECT T1.first_name, T1.last_name FROM historical AS T1 INNER JOIN 'historical-terms' AS T2 ON T1.bioguide_id = T2.bioguide_id WHERE T2.party = 'Pro-Administration' AND CAST(T2.start AS DATE) <= 1791 AND CAST(T2.END AS DATE) >= 1791	SELECT official_full_name FROM historical WHERE bioguide_id IN (SELECT bioguide FROM 'historical-terms' WHERE party = 'Pro-Administration' AND strftime('%Y', start) <= '1791' AND strftime('%Y', end) >= '1791');	semantic error: output column	0	1
4777	Which party does Christopher Henderson Clark belong to?	SELECT T1.party FROM 'historical-terms' AS T1 INNER JOIN historical AS T2 ON T2.bioguide_id = T1.bioguide_id WHERE T2.first_name OR T2.middle_name OR T2.last_name = 'ChristopherHendersonClark'	SELECT T1.party FROM 'historical-terms' AS T1 INNER JOIN historical AS T2 ON T2.bioguide_id = T1.bioguide_id WHERE T2.first_name = 'Christopher' AND T2.middle_name = 'Henderson' AND T2.last_name = 'Clark';	nlq vague: historical or current; semantic error: wrong condition	1	0
4786	List the full names of Republican legislators who have a nickname.	SELECT T1.official_full_name FROM current AS T1 INNER JOIN 'current-terms' AS T2 ON T1.bioguide_id = T2.bioguide_id WHERE T2.party = 'Republican' AND T1.nickname_name IS NOT NULL GROUP BY T1.official_full_name	SELECT official_full_name FROM current WHERE bioguide_id IN (SELECT bioguide FROM 'current-terms' WHERE party = 'Republican') AND nickname_name IS NOT NULL;	join -> in-sub	0	1
4812	What is the gender of the legislator whose address at 317 Russell Senate Office Building Washington DC 20510?	SELECT T1.gender_bio FROM current AS T1 INNER JOIN 'current-terms' AS T2 ON T1.bioguide_id = T2.bioguide_id WHERE T2.address = '317 Russell Senate Office Building Washington DC 20510'	SELECT gender_bio FROM current WHERE bioguide_id IN (SELECT bioguide FROM 'current-terms' WHERE address = '317 Russell Senate Office Building Washington DC 20510');	join -> in-sub	0	1

4813	List out the first name of legislators who are senior Senator.	SELECT T1.first_name FROM current AS T1 INNER JOIN 'current-terms' AS T2 ON T1.bioguide_id = T2.bioguide WHERE T2.state_rank = 'senior' GROUP BY T1.first_name	SELECT first_name FROM current WHERE bioguide_id IN (SELECT bioguide FROM 'current-terms' WHERE state_rank = 'senior' AND chamber = 'senate');	join -> in-sub	0	1
4814	Among male legislators, state number of the legislators who are not the senator.	SELECT COUNT(T3.state) FROM (SELECT T2.state FROM current AS T1 INNER JOIN 'current-terms' AS T2 ON T1.bioguide_id = T2.bioguide WHERE T1.gender_bio = 'M' AND (T2.class IS NULL OR T2.class = '') GROUP BY T2.state) T3	SELECT COUNT(DISTINCT c.bioguide_id) FROM current c LEFT JOIN 'current-terms' ct ON c.bioguide_id = ct.bioguide WHERE c.gender_bio = 'M' AND (ct.class IS NULL OR ct.class = '');	semantic error: output column	0	1
4820	What is the first name of the legislator whose address at 1005 Longworth HOB; Washington DC 20515-1408?	SELECT T1.first_name FROM current AS T1 INNER JOIN 'current-terms' AS T2 ON T1.bioguide_id = T2.bioguide WHERE T2.address = '1005 Longworth HOB Washington DC 20515-1408' GROUP BY T1.first_name	SELECT first_name FROM current WHERE bioguide_id IN (SELECT bioguide FROM 'current-terms' WHERE address = '1005 Longworth HOB; Washington DC 20515-1408');	str; join -> in-sub	0	1
4822	State number of legislators who are not the senator among female legislators.	SELECT COUNT(*) FROM current AS T1 INNER JOIN 'current-terms' AS T2 ON T1.bioguide_id = T2.bioguide WHERE T1.gender_bio = 'F' AND (T2.class IS NULL OR T2.class = '')	SELECT COUNT(DISTINCT T1.bioguide_id) FROM current AS T1 INNER JOIN 'current-terms' AS T2 ON T1.bioguide_id = T2.bioguide WHERE T1.gender_bio = 'F' AND (T2.class IS NULL OR T2.class = '')	lack distinct	0	0
4832	What are the first and last name of the representatives of the house in district 9?	SELECT T2.first_name, T2.last_name FROM 'historical-terms' AS T1 INNER JOIN historical AS T2 ON T2.bioguide_id = T1.bioguide WHERE T1.district = 9	SELECT T1.first_name, T1.last_name FROM historical AS T1 WHERE bioguide_id IN (SELECT bioguide FROM 'historical-terms' AS T2 WHERE T2.district = 9 AND T2.type = 'rep')	nlq vague: historical or current; semantic error: wrong condition; join -> in-sub	0	0
4857	List all the junior senators in 1997.	SELECT T1.first_name, T1.last_name FROM current AS T1 INNER JOIN 'current-terms' AS T2 ON T1.bioguide_id = T2.bioguide WHERE T2.start LIKE '1997%' AND T2.state_rank = 'junior'	SELECT T1.first_name, T1.last_name FROM current AS T1 WHERE T1.bioguide_id IN (SELECT T2.bioguide FROM 'current-terms' AS T2 WHERE T2.start LIKE '1997%' AND T2.state_rank = 'junior')	nlq vague: output column; join -> in-sub	1	0
4858	How many female legislators become representatives for California in 2015?	SELECT COUNT(*) FROM current AS T1 INNER JOIN 'current-terms' AS T2 ON T1.bioguide_id = T2.bioguide WHERE STRFTIME('%Y', T2.start) = '2015' AND T2.state = 'CA' AND T1.gender_bio = 'F'	SELECT COUNT(DISTINCT T1.bioguide_id) FROM current T1 JOIN 'current-terms' T2 ON T1.bioguide_id = T2.bioguide WHERE T1.gender_bio = 'F' AND T2.type = 'rep' AND T2.state = 'CA' AND T2.start LIKE '2015%'	semantic error: wrong condition; lack distinct	0	1
4863	What is the ratio between famous current legislators and famous historical legislators?	SELECT CAST(COUNT(CASE WHEN wikipedia_id IS NOT NULL THEN bioguide_id ELSE 0 END) AS REAL) * 100 / (SELECT COUNT(CASE WHEN wikipedia_id IS NOT NULL THEN bioguide_id ELSE 0 END) FROM historical) FROM current	SELECT (SELECT COUNT(*) FROM current WHERE wikipedia_id IS NOT NULL) * 1.0 / (SELECT COUNT(*) FROM historical WHERE wikipedia_id IS NOT NULL) AS ratio;	semantic error: wrong calculation	0	1
4869	What is the full name of the oldest legislator?	SELECT first_name, last_name FROM historical ORDER BY birthday_bio LIMIT 1	SELECT first_name, last_name FROM (SELECT first_name, last_name, rank() over (ORDER BY birthday_bio) as rk FROM historical) WHERE rk = 1	limit 1	1	0
4891	Please list the username of the current official Facebook presence of all the current legislators that are famous or impact.	SELECT T2.facebook FROM current AS T1 INNER JOIN 'social-media' AS T2 ON T1.bioguide_id = T2.bioguide WHERE T1.wikipedia_id IS NOT NULL GROUP BY T2.facebook	SELECT facebook FROM 'social-media' WHERE bioguide IN (SELECT bioguide_id FROM current WHERE wikipedia_id IS NOT NULL);	semantic error: redundant group by	0	1
7627	Name the goalies with the most seasons played. State the average time he played for each season.	SELECT T1.firstName, T1.lastName, T2.year, AVG(T2.Min) FROM Master AS T1 INNER JOIN Goalies AS T2 ON T1.playerID = T2.playerID WHERE T1.playerID = (SELECT playerID FROM Goalies GROUP BY playerID ORDER BY COUNT(playerID) DESC LIMIT 1) GROUP BY T1.firstName, T1.lastName, T2.year	SELECT playerID, AVG(CAST(Min AS INTEGER)) AS AvgTime FROM Goalies WHERE playerID IN (SELECT playerID FROM (SELECT playerID, COUNT(DISTINCT year) AS seasons FROM Goalies GROUP BY playerID) WHERE seasons = (SELECT MAX(seasons) FROM (SELECT COUNT(DISTINCT year) AS seasons FROM Goalies GROUP BY playerID))) AND Min IS NOT NULL GROUP BY playerID;	limit 1; semantic error: count the seasons	0	1

7633	What is the average height of player who were born in 1990 and after? Compare the average height with players who were born before 1990.	SELECT AVG(IIF(birthYear < 1990, height, NULL)) - AVG(IIF(birthYear >= 1990, height, NULL)) FROM Master	SELECT AVG(CASE WHEN birthYear >= '1990' THEN CAST(height AS REAL) END) AS avg_height_1990_and_after, AVG(CASE WHEN birthYear < '1990' THEN CAST(height AS REAL) END) AS avg_height_before_1990 FROM Master;	semantic error: output column	0	1
7635	List all the deceased goalies and the teams he had played whose birth country was in Canada.	SELECT DISTINCT firstName, lastName, T3.name FROM Goalties AS T1 INNER JOIN Master AS T2 ON T2.playerID = T1.playerID INNER JOIN Teams AS T3 ON T1.lgID = T3.lgID WHERE T2.birthCountry = 'Canada' AND T2.deathYear IS NOT NULL AND T2.pos = 'G'	SELECT firstName, lastName, tmID FROM (SELECT DISTINCT T1.playerID, firstName, lastName, T3.tmID, T3.name FROM Goalties AS T1 INNER JOIN Master AS T2 ON T2.playerID = T1.playerID INNER JOIN Teams AS T3 ON T1.tmID = T3.tmID AND T1.year = T3.year WHERE T2.birthCountry = 'Canada' AND T2.deathYear IS NOT NULL AND T2.pos = 'G')	distinct non-key; semantic error: wrong join condition	0	0
7637	Among all goalies who are still alive, whose first season in NHL in before 1950. List the team names they were in.	SELECT DISTINCT T3.name FROM Master AS T1 INNER JOIN Goalties AS T2 ON T1.playerID = T2.playerID INNER JOIN Teams AS T3 ON T2.lgID = T3.lgID AND T2.year = T3.year WHERE T1.deathYear IS NOT NULL AND T1.firstNHL < 1950	SELECT T3.name FROM Master T1 JOIN Goalties T2 ON T1.playerID = T2.playerID JOIN Teams T3 ON T2.tmID = T3.tmID AND T2.year = T3.year WHERE T1.firstNHL < '1950' AND T1.deathYear IS NULL GROUP BY T3.tmID, T3.name	semantic error: wrong condition	0	0
7641	Who is the coach who had coached the most seasons in MTL? State his given name, date of birth and all teams he had coaches before.	SELECT T2.nameGiven, T2.birthYear, T2.birthMon, T2.birthDay, T3.name FROM Goalties AS T1 INNER JOIN Master AS T2 ON T2.playerID = T1.playerID INNER JOIN Teams AS T3 ON T3.lgID = T1.lgID WHERE T3.tmID = 'MTL' GROUP BY T2.nameGiven, T2.birthYear, T2.birthMon, T2.birthDay, T3.name ORDER BY COUNT(T2.coachID) DESC LIMIT 1	SELECT T2.nameGiven, T2.birthYear, T2.birthMon, T2.birthDay, T4.name FROM (SELECT coachID, rank() over (ORDER BY COUNT(DISTINCT year) DESC) as rk FROM Coaches WHERE tmID = 'MTL' GROUP BY coachID) AS T1 JOIN Master AS T2 ON T2.coachID = T1.coachID JOIN Coaches AS T3 ON T2.coachID = T3.coachID JOIN Teams AS T4 ON T3.year = T4.year and T3.tmID = T4.tmID WHERE rk = 1 GROUP BY T1.coachID, T3.tmID	limit 1; group non-key	1	0
7642	List all goalies with more lost than won games for two seasons or more. State the name of the player and team he played.	SELECT DISTINCT T1.firstName, T1.lastName, T3.name FROM Master AS T1 INNER JOIN Goalties AS T2 ON T1.playerID = T2.playerID INNER JOIN Teams AS T3 ON T2.year = T3.year AND T2.tmID = T3.tmID WHERE T1.pos = 'G' AND T2.L > T2.W GROUP BY T1.firstName, T1.lastName, T3.name HAVING COUNT(T3.year) > 2	SELECT M.firstName, M.lastName, T.name FROM Goalties G JOIN Master M ON G.playerID = M.playerID JOIN Teams T ON G.tmID = T.tmID AND G.year = T.year WHERE CAST(G.L AS INTEGER) > CAST(G.W AS INTEGER) GROUP BY G.playerID HAVING COUNT(DISTINCT G.year) >= 2;	semantic error: wrong condition, lack record due to group by key; group by non-key; lack distinct	0	1
7660	Among the coaches who have taught teams from the NHL League, how many of them are from Canada?	SELECT COUNT(T2.coachID) FROM Master AS T1 INNER JOIN Coaches AS T2 ON T1.coachID = T2.coachID WHERE T2.lgID = 'NHL' AND T1.birthCountry = 'Canada'	SELECT COUNT(DISTINCT T1.coachID) FROM Coaches T1 JOIN Master T2 ON T1.coachID = T2.coachID WHERE T1.lgID = 'NHL' AND T2.birthCountry = 'Canada';	lack distinct	0	1
7682	How many years did player Id 'healygl01' play?	SELECT COUNT(year) FROM Goalties WHERE playerID = 'healygl01'	SELECT (MAX(year) - MIN(year) + 1) AS years_played FROM Scoring WHERE playerID = 'healygl01';	semantic error: misunderstand year of playing	0	1
7695	Who is the youngest goalie among those who had more than 150 goal againsts in 2002 season?	SELECT T1.firstName, T1.lastName FROM Master AS T1 INNER JOIN Goalties AS T2 ON T1.playerID = T2.playerID WHERE T2.year = 2002 AND T2.GA > 150 GROUP BY T2.playerID, T1.birthYear, T1.birthMon, T1.birthDay HAVING SUM(T2.GA) ORDER BY T1.birthYear DESC, T1.birthMon DESC, SUM(T1.birthDay) DESC LIMIT 1	SELECT DISTINCT playerID FROM (SELECT T2.playerID, RANK() OVER (ORDER BY T2.birthYear DESC, T2.birthMon DESC, T2.birthDay DESC) as rk FROM Goalties T1 JOIN Master T2 ON T1.playerID = T2.playerID WHERE T1.year = 2002 AND CAST(T1.GA AS INTEGER) > 150) as sub-query WHERE rk = 1	limit 1; semantic error: wrong condition, wrong order by, output column; lack distinct	0	0

7697	Which teams had the most postseason empty net goals in 2010 season? List their team names.	SELECT T2.name FROM Goalies AS T1 INNER JOIN Teams AS T2 ON T1.tmID = T2.tmID WHERE T1.year = 2010 GROUP BY T2.name ORDER BY SUM(PostENG) DESC LIMIT 1	SELECT name FROM (SELECT T2.name, rank() over (ORDER BY SUM(PostENG) DESC) as rk FROM Goalies AS T1 INNER JOIN Teams AS T2 ON T1.tmID = T2.tmID WHERE T1.year = 2010 GROUP BY T2.tmID) WHERE rk = 1	limit 1; group by non-key	0	0
7707	For the team which had three different goalies in the 2011 post-season games, how many games did they win in the regular season?	SELECT SUM(T2.W) FROM Goalies AS T1 INNER JOIN Teams AS T2 ON T1.tmID = T2.tmID WHERE T2.year = 2011 GROUP BY T1.tmID HAVING COUNT(DISTINCT T1.playerID) = 3	SELECT T2.W FROM (SELECT tmID FROM Goalies WHERE year = 2011 AND PostGP IS NOT NULL GROUP BY tmID HAVING COUNT(DISTINCT playerID) = 3) T1 JOIN Teams T2 ON T1.tmID = T2.tmID AND T2.year = 2011;	semantic error: wrong join condition	0	1
7712	For he who had the highest plus / minus on the court in the 1981 season, what's his full name?	SELECT T1.firstName, T1.lastName FROM Master AS T1 INNER JOIN Scoring AS T2 ON T1.playerID = T2.playerID WHERE T2.year = 1981 GROUP BY T2.playerID ORDER BY SUM(T2.'+/-') DESC LIMIT 1	SELECT firstName, lastName FROM Master WHERE playerID IN (SELECT playerID FROM Scoring WHERE year = 1981 AND CAST('+/-' AS INTEGER) = (SELECT MAX(CAST('+/-' AS INTEGER)) FROM Scoring WHERE year = 1981))	limit 1	0	0
7721	How many former athletes go on to become coaches after retiring?	SELECT COUNT(playerID) FROM Master WHERE playerID IS NOT NULL AND coachID IS NOT NULL	SELECT COUNT(DISTINCT playerID) FROM Master WHERE playerID IS NOT NULL AND coachID IS NOT NULL;	lack distinct	0	1
7727	How many wins does the team have whose goaltender have the most number of successfully stopping the other team from scoring during the entire game?	SELECT SUM(W) FROM Goalies GROUP BY tmID ORDER BY SUM(SHO) DESC LIMIT 1	SELECT tmID, sum(W) FROM (SELECT T2.tmID, T2.W, RANK() OVER (ORDER BY TotalSHO DESC) as rk FROM Teams T2 JOIN (SELECT G.tmID, SUM(CAST(G.SHO AS INTEGER)) AS TotalSHO FROM Goalies G GROUP BY G.tmID) T1 ON T2.tmID = T1.tmID) as subquery WHERE rk = 1 GROUP BY tmID	limit 1	0	0
7736	What is the power play percentage of the team with the least number of penalty kill chances and to which team were they playing against? Indicate whether the team lost or victorious.	SELECT SUM(T1.A), T2.firstName, T2.lastName FROM Scoring AS T1 INNER JOIN Master AS T2 ON T1.playerID = T2.playerID WHERE T1.lgID = 'NHL' GROUP BY T2.firstName, T2.lastName ORDER BY SUM(T1.A) DESC LIMIT 1	SELECT T.tmID, (CAST(T.PPG AS FLOAT) / CAST(T.PPC AS FLOAT)) AS PP_Percentage, CASE WHEN S.tmIDWinner = T.tmID THEN 'Victorious' ELSE 'Lost' END AS Result FROM Teams T, TeamsPost TP, SeriesPost S WHERE T.tmID = TP.tmID AND T.year = TP.year AND S.year = T.year AND (S.tmIDWinner = T.tmID OR S.tmIDLoser = T.tmID) AND TP.PKC = (SELECT MIN(PKC) FROM TeamsPost WHERE tmID = T.tmID AND year = T.year)	semantic error: wrong join table, output column; limit 1	0	0
7738	What is the name of the losing team during an exhibition game in 1912?	SELECT T2.name FROM SeriesPost AS T1 INNER JOIN Teams AS T2 ON T1.year = T2.year AND tmIDLoser = tmID WHERE T1.note = 'EX' AND T2.year = '1912'	SELECT name FROM Teams WHERE (year, tmIDLoser) IN (SELECT year, tmIDLoser FROM SeriesPost WHERE year = 1912 AND note = 'EX');	join -> in-sub	0	1
7748	What is the name of the coach whose team placed 4th in the 1969 game? Indicate their coachID.	SELECT T1.coachID FROM Coaches AS T1 INNER JOIN Teams AS T2 ON T1.tmID = T2.tmID AND T1.year = T2.year WHERE T1.year = 1969 AND T2.rank = 4	SELECT DISTINCT C.coachID FROM Coaches C, Teams T WHERE C.year = T.year AND C.tmID = T.tmID AND T.year = 1969 AND T.rank = 4;	lack distinct	0	1
7762	Which team got the most wins in the Stanley Cup finals?	SELECT T2.name FROM TeamsSC AS T1 INNER JOIN Teams AS T2 ON T1.tmID = T2.tmID AND T1.year = T2.year GROUP BY T2.name ORDER BY SUM(T1.W) DESC LIMIT 1	SELECT name FROM (SELECT T2.name, RANK() OVER (ORDER BY SUM(T1.W) DESC) as rk FROM TeamsSC AS T1 INNER JOIN Teams AS T2 ON T1.tmID = T2.tmID AND T1.year = T2.year GROUP BY T2.tmID) as subquery WHERE rk = 1	limit 1; group by non-key	1	0

7766	How many coaches of the Montreal Canadiens have gotten in the Hall of Fame?	SELECT COUNT(DISTINCT hofID) FROM Coaches AS T1 INNER JOIN Teams AS T2 ON T1.year = T2.year AND T1.tmID = T2.tmID INNER JOIN Master AS T3 ON T1.coachID = T3.coachID WHERE T2.name = 'Montreal Canadiens'	SELECT COUNT(DISTINCT C.coachID) FROM Coaches C JOIN Teams T ON C.year = T.year AND C.tmID = T.tmID JOIN Master M ON C.coachID = M.coachID WHERE T.name = 'Montreal Canadiens' AND M.hofID IS NOT NULL;	semantic error: lack condition	0	1
7774	In the year 2000, which team has played the most games against the Buffalo Sabres?	SELECT T3.name FROM TeamVsTeam AS T1 INNER JOIN Teams AS T2 ON T1.year = T2.year AND T1.opplID = T2.tmID INNER JOIN Teams AS T3 ON T1.year = T3.year AND T1.tmID = T3.tmID WHERE T1.year = 2000 AND T2.name = 'Buffalo Sabres' GROUP BY T3.name ORDER BY SUM(T2.G) DESC LIMIT 1	SELECT name FROM Teams WHERE tmID IN (SELECT tmID FROM (SELECT T3.tmID, RANK() OVER (ORDER BY SUM(T2.G) DESC) as rk FROM TeamVsTeam AS T1 INNER JOIN Teams AS T2 ON T1.year = T2.year AND T1.opplID = T2.tmID INNER JOIN Teams AS T3 ON T1.year = T3.year AND T1.tmID = T3.tmID WHERE T1.year = 2000 AND T2.name = 'Buffalo Sabres' GROUP BY T3.tmID) as subquery WHERE rk = 1)	limit 1; group by non-key; join -> in-sub	0	0
7785	For all the referees, who became a hall of famer in the 1970s? What's his hofID?	SELECT name, hofID FROM HOF WHERE category = 'Builder' AND year BETWEEN 1970 AND 1979	SELECT hofID FROM HOF WHERE category = 'Referee/Linesman' AND year BETWEEN 1970 AND 1979;	semantic error: output column	0	1
7793	For the goalkeeper that became a coach than a Hall of Famer, who played for BOS in 1972?	SELECT T2.firstName, T2.lastName, IIF(T1.tmID = 'BOS', 'YES', 'NO') FROM Goalies AS T1 INNER JOIN Master AS T2 ON T1.playerID = T2.playerID WHERE T1.year = 1972 AND T1.tmID = 'BOS' AND T2.coachID IS NOT NULL AND T2.hofID IS NULL	SELECT DISTINCT T1.playerID FROM Goalies AS T1 INNER JOIN Master AS T2 ON T1.playerID = T2.playerID WHERE T1.year = 1972 AND T1.tmID = 'BOS' AND T2.coachID IS NOT NULL AND T2.hofID IS NULL	semantic error: output column	0	0
7799	For the goalie who had the most shutouts in 2010, what's his catching hand?	SELECT T2.shootCatch FROM Goalies AS T1 INNER JOIN Master AS T2 ON T1.playerID = T2.playerID WHERE T1.year = 2010 GROUP BY T2.shootCatch ORDER BY SUM(T1.SHO) DESC LIMIT 1	SELECT shootCatch FROM Master WHERE playerID IN (SELECT playerID FROM Goalies WHERE year = 2010 AND SHO = (SELECT MAX(SHO) FROM Goalies WHERE year = 2010))	semantic error: wrong group by key; limit 1	1	0
7817	Which team has the highest winning rate in year 2000? State the team ID and list down the birth country of it's players.	SELECT DISTINCT T3.tmID, T1.birthCountry FROM Master AS T1 INNER JOIN Scoring AS T2 ON T1.playerID = T2.playerID INNER JOIN (SELECT year, tmID FROM Teams WHERE year = 2000 ORDER BY W / (W + L) DESC LIMIT 1) AS T3 ON T2.tmID = T3.tmID AND T2.year = T3.year	SELECT DISTINCT T3.tmID, T1.birthCountry FROM Master AS T1 INNER JOIN Scoring AS T2 ON T1.playerID = T2.playerID INNER JOIN (SELECT year, tmID FROM (SELECT year, tmID, RANK() OVER (ORDER BY W / (W + L) DESC) as rk FROM Teams WHERE year = 2000) as subquery WHERE rk = 1) AS T3 ON T2.tmID = T3.tmID AND T2.year = T3.year	limit 1	0	0
8517	Please list the occupations of the customers over 40 and have sent a true response to the incentive mailing sent by the marketing department.	SELECT DISTINCT T1.OCCUPATION FROM Customers AS T1 INNER JOIN Mailings1_2 AS T2 ON T1.ID = T2.REFID WHERE T1.age > 40 AND T2.RESPONSE = 'true'	SELECT C.OCCUPATION FROM Customers C JOIN Mailings1_2 M ON C.ID = M.REFID WHERE C.age > 40 AND M.RESPONSE = 'true';	redundant distinct	0	1
8525	What is the number of inhabitants of the place the most customers are from?	SELECT DISTINCT T2.INHABITANTS_K FROM Customers AS T1 INNER JOIN Demog AS T2 ON T1.GEOID = T2.GEOID ORDER BY T2.INHABITANTS_K DESC	SELECT INHABITANTS_K FROM Demog WHERE GEOID IN (SELECT GEOID FROM Customers GROUP BY GEOID HAVING COUNT(ID) = (SELECT MAX(Cnt) FROM (SELECT COUNT(ID) AS Cnt FROM Customers GROUP BY GEOID)))	semantic error: wrong order by; redundant distinct	1	0
8528	What is the average education level of customers from the place with the highest average income per month?	SELECT AVG(T1.EDUCATIONNUM) FROM Customers AS T1 INNER JOIN Demog AS T2 ON T1.GEOID = T2.GEOID ORDER BY T2.INCOME_K DESC LIMIT 1	SELECT AVG(EDUCATIONNUM) FROM Customers WHERE GEOID IN (SELECT GEOID FROM Demog WHERE INCOME_K = (SELECT MAX(INCOME_K) FROM Demog))	limit 1	0	0

8535	What is the number of inhabitants and income of geographic identifier 239?	SELECT INHABITANTS_K FROM Demog WHERE GEOID = 239	SELECT INHABITANTS_K, INCOME_K FROM Demog WHERE GEOID = 239;	semantic error: output column	0	1
8537	List down the number of inhabitants of customers with a divorced marital status and older than 50 years old.	SELECT COUNT(T1.ID) FROM Customers AS T1 INNER JOIN Demog AS T2 ON T1.GEOID = T2.GEOID WHERE T1.MARITAL_STATUS = 'Divorced' AND T1.age < 50	SELECT T2.INHABITANTS_K FROM Customers AS T1 INNER JOIN Demog AS T2 ON T1.GEOID = T2.GEOID WHERE T1.MARITAL_STATUS = 'Divorced' AND T1.age > 50	semantic error: wrong condition, output column	1	0
8538	What is the geographic identifier and income of the oldest customer?	SELECT T1.GEOID, T2.INCOME_K FROM Customers AS T1 INNER JOIN Demog AS T2 ON T1.GEOID = T2.GEOID ORDER BY T1.age DESC LIMIT 1	SELECT T1.GEOID, T2.INCOME_K FROM Customers T1 JOIN Demog T2 ON T1.GEOID = T2.GEOID WHERE T1.age = (SELECT MAX(age) FROM Customers)	limit 1	1	0
8539	Among the male customers with an level of education of 4 and below, list their income K.	SELECT INCOME_K FROM Demog WHERE GEOID IN (SELECT GEOID FROM Customers WHERE EDUCATIONNUM < 4 AND SEX = 'Male')	SELECT T2.INCOME_K FROM Customers T1 JOIN Demog T2 ON T1.GEOID = T2.GEOID WHERE T1.SEX = 'Male' AND T1.EDUCATIONNUM <= 4;	semantic error: wrong condition; in-sub -> join	0	1
8541	In widowed male customers ages from 40 to 60, how many of them has an income ranges from 3000 and above?	SELECT COUNT(T1.ID) FROM Customers AS T1 INNER JOIN Demog AS T2 ON T1.GEOID = T2.GEOID WHERE T1.age >= 40 AND T1.age <= 60 AND T1.MARITAL_STATUS = 'Widowed' AND T1.SEX = 'Male' AND T2.INCOME_K >= 2000 AND T2.INCOME_K <= 3000	SELECT COUNT(*) FROM Customers AS T1 JOIN Demog AS T2 ON T1.GEOID = T2.GEOID WHERE T1.SEX = 'Male' AND T1.MARITAL_STATUS = 'Widowed' AND T1.age BETWEEN 40 AND 60 AND T2.INCOME_K >= 3000;	semantic error: wrong condition	0	1
8542	What is the occupation of customers within number of inhabitants ranges of 30 to 40?	SELECT DISTINCT T1.OCCUPATION FROM Customers AS T1 INNER JOIN Demog AS T2 ON T1.GEOID = T2.GEOID WHERE T2.INHABITANTS_K >= 30 AND T2.INHABITANTS_K <= 40	SELECT T1.OCCUPATION FROM Customers T1 JOIN Demog T2 ON T1.GEOID = T2.GEOID WHERE T2.INHABITANTS_K BETWEEN 30 AND 40;	redundant distinct	0	1
8543	Among the widowed female customers, give the income of those who has an level of education of 5 and below.	SELECT INCOME_K FROM Demog WHERE GEOID IN (SELECT GEOID FROM Customers WHERE EDUCATIONNUM < 5 AND SEX = 'Female' AND MARITAL_STATUS = 'Widowed')	SELECT T2.INCOME_K FROM Customers T1 JOIN Demog T2 ON T1.GEOID = T2.GEOID WHERE T1.SEX = 'Female' AND T1.MARITAL_STATUS = 'Widowed' AND T1.EDUCATIONNUM <= 5	in-sub -> join; semantic error: wrong condition	1	0
8545	What is the number of inhabitants of male customers ages from 20 to 30 years old who are farming or fishing?	SELECT T2.INHABITANTS_K FROM Customers AS T1 INNER JOIN Demog AS T2 ON T1.GEOID = T2.GEOID WHERE T1.OCCUPATION = 'Farming-fishing' AND T1.SEX = 'Male' AND T1.age >= 20 AND T1.age <= 30	SELECT TOTAL(D.INHABITANTS_K) FROM Customers AS C JOIN Demog AS D ON C.GEOID = D.GEOID WHERE C.SEX = 'Male' AND C.age BETWEEN 20 AND 30 AND C.OCCUPATION LIKE 'Farming-fishing';	semantic error: misunderstand number of	0	1
8546	Among the customers with a marital status of married-civ-spouse, list the number of inhabitants and age of those who are machine-op-inspct.	SELECT T2.INHABITANTS_K FROM Customers AS T1 INNER JOIN Demog AS T2 ON T1.GEOID = T2.GEOID WHERE T1.OCCUPATION = 'Farming-fishing' AND T1.SEX = 'Male' AND T1.age >= 20 AND T1.age <= 30	SELECT D.INHABITANTS_K, C.age FROM Customers C JOIN Demog D ON C.GEOID = D.GEOID WHERE C.MARITAL_STATUS = 'Married-civ-spouse' AND C.OCCUPATION = 'Machine-op-inspct'	semantic error: lack condition, wrong condition, output column	0	0
8548	List the income and number of inhabitants of customers with an age greater than the 80% of average age of all customers?	SELECT T2.INCOME_K, T2.INHABITANTS_K FROM Customers AS T1 INNER JOIN Demog AS T2 ON T1.GEOID = T2.GEOID GROUP BY T2.INCOME_K, T2.INHABITANTS_K HAVING T1.age > 0.8 * AVG(T1.age)	SELECT D.INCOME_K, D.INHABITANTS_K FROM Customers C JOIN Demog D ON C.GEOID = D.GEOID WHERE C.age > (SELECT 0.8 * AVG(age) FROM Customers)	redundant distinct	0	1

8549	In customers with marital status of never married, what is the percentage of customers with income of 2500 and above?	SELECT CAST(SUM(CASE WHEN T2.INCOME_K > 2500 THEN 1.0 ELSE 0 END) AS REAL) * 100 / COUNT(*) FROM Customers AS T1 INNER JOIN Demog AS T2 ON T1.GEOID = T2.GEOID WHERE T1.MARITAL_STATUS = 'Never-married'	SELECT CAST(SUM(CASE WHEN T2.INCOME_K >= 2500 THEN 1.0 ELSE 0 END) AS REAL) * 100 / COUNT(*) FROM Customers AS T1 INNER JOIN Demog AS T2 ON T1.GEOID = T2.GEOID WHERE T1.MARITAL_STATUS = 'Never-married'	semantic error: wrong condition	1	0
8556	What percentage of elderly customers who are never married in the place with geographic ID 24?	SELECT CAST(SUM(CASE WHEN T1.MARITAL_STATUS = 'never married' THEN 1.0 ELSE 0 END) AS REAL) * 100 / COUNT(*) FROM Customers AS T1 INNER JOIN Demog AS T2 ON T1.GEOID = T2.GEOID WHERE T1.GEOID = 24	SELECT (COUNT(*) * 100.0 / (SELECT COUNT(*) FROM Customers WHERE GEOID = 24)) AS percentage FROM Customers WHERE age > 65 AND MARITAL_STATUS = 'Never-married' AND GEOID = 24;	semantic error: wrong condition	0	1
8563	What is the marital status of the customer ages 62 with an level of education of 7?	SELECT DISTINCT MARITAL_STATUS FROM Customers WHERE EDUCATIONNUM = 7 AND age = 62	SELECT MARITAL_STATUS FROM Customers WHERE age = 62 AND EDUCATIONNUM = 7;	redundant distinct	0	1
8564	List down the number of inhabitants of customers with a widowed marital status and false response .	SELECT COUNT(T1.ID) FROM Customers AS T1 INNER JOIN Mailings1_2 AS T2 ON T1.ID = T2.REFID INNER JOIN Demog AS T3 ON T1.GEOID = T3.GEOID WHERE T1.MARITAL_STATUS = 'Widowed' AND T2.RESPONSE = 'true'	SELECT INHABITANTS_K FROM Demog WHERE GEOID IN (SELECT GEOID FROM Customers WHERE MARITAL_STATUS = 'Widowed' AND ID IN (SELECT REFID FROM Mailings1_2 WHERE RESPONSE = 'false'));	semantic error: misunderstand number of inhabitants	0	1
8565	What is the response and number of inhabitants of the oldest female customer?	SELECT T2.RESPONSE, T3.INHABITANTS_K FROM Customers AS T1 INNER JOIN Mailings1_2 AS T2 ON T1.ID = T2.REFID INNER JOIN Demog AS T3 ON T1.GEOID = T3.GEOID WHERE T1.SEX = 'Female' ORDER BY T1.age DESC LIMIT 1	SELECT M.RESPONSE, D.INHABITANTS_K FROM Customers C LEFT JOIN Mailings1_2 M ON C.ID = M.REFID LEFT JOIN Demog D ON C.GEOID = D.GEOID WHERE C.SEX = 'Female' AND C.age = (SELECT MAX(age) FROM Customers WHERE SEX = 'Female');	limit 1	0	1
8566	Among the female customers with an level of education of 3 and below, list their income.	SELECT INCOME_K FROM Demog WHERE GEOID IN (SELECT GEOID FROM Customers WHERE EDUCATIONNUM < 3 AND SEX = 'Female')	SELECT T2.INCOME_K FROM Customers T1 JOIN Demog T2 ON T1.GEOID = T2.GEOID WHERE T1.SEX = 'Female' AND T1.EDUCATIONNUM <= 3;	semantic error: wrong condition; in-sub -> join	0	1
8568	In male customers ages from 30 to 50, how many of them has an income ranges from 2000 to 2300?	SELECT COUNT(T1.ID) FROM Customers AS T1 INNER JOIN Demog AS T2 ON T1.GEOID = T2.GEOID WHERE T1.SEX = 'Male' AND T1.age >= 30 AND T1.age <= 50 AND T2.INCOME_K >= 2000 AND T2.INCOME_K <= 2300	SELECT COUNT(*) FROM Customers AS T1 JOIN Demog AS T2 ON T1.GEOID = T2.GEOID WHERE T1.SEX = 'Male' AND T1.age BETWEEN 30 AND 50 AND T2.INCOME_K BETWEEN 2000 AND 3000;	semantic error: wrong condition	0	1
8571	List the marital status and response of female customers with an level of education of 8 and above.	SELECT DISTINCT T1.MARITAL_STATUS, T2.RESPONSE FROM Customers AS T1 INNER JOIN Mailings1_2 AS T2 ON T1.ID = T2.REFID WHERE T1.EDUCATIONNUM > 8 AND T1.SEX = 'Female'	SELECT C.MARITAL_STATUS, M.RESPONSE FROM Customers C JOIN Mailings1_2 M ON C.ID = M.REFID WHERE C.SEX = 'Female' AND C.EDUCATIONNUM >= 8;	redundant distinct; semantic error: wrong condition	0	1
8573	Among the divorced male customers, give the income and response of those who has an level of education of 6 and above.	SELECT DISTINCT T3.INCOME_K, T2.RESPONSE FROM Customers AS T1 INNER JOIN Mailings1_2 AS T2 ON T1.ID = T2.REFID INNER JOIN Demog AS T3 ON T1.GEOID = T3.GEOID WHERE T1.EDUCATIONNUM > 6 AND T1.SEX = 'Male' AND T1.MARITAL_STATUS = 'Divorced'	SELECT T2.INCOME_K, T3.RESPONSE FROM Customers T1 JOIN Demog T2 ON T1.GEOID = T2.GEOID JOIN Mailings1_2 T3 ON T1.ID = T3.REFID WHERE T1.SEX = 'Male' AND T1.MARITAL_STATUS = 'Divorced' AND T1.EDUCATIONNUM >= 6;	redundant distinct; semantic error: wrong condition	0	1
8574	What is the occupation and response of female customers within the number of inhabitants range of 20 to 25?	SELECT DISTINCT T1.OCCUPATION, T2.RESPONSE FROM Customers AS T1 INNER JOIN Mailings1_2 AS T2 ON T1.ID = T2.REFID INNER JOIN Demog AS T3 ON T1.GEOID = T3.GEOID WHERE T1.SEX = 'Female' AND T3.INHABITANTS_K >= 20 AND T3.INHABITANTS_K <= 25	SELECT T1.OCCUPATION, T3.RESPONSE FROM Customers T1 JOIN Demog T2 ON T1.GEOID = T2.GEOID JOIN Mailings1_2 T3 ON T1.ID = T3.REFID WHERE T1.SEX = 'Female' AND T2.INHABITANTS_K BETWEEN 20 AND 25;	redundant distinct	0	1

8776	Please list the names of all the restaurants that have met all requirements in one inspection.	SELECT DISTINCT T2.name FROM inspections AS T1 INNER JOIN businesses AS T2 ON T1.business_id = T2.business_id WHERE T1.score = 100	SELECT name FROM businesses WHERE EXISTS (SELECT 1 FROM inspections WHERE business_id = businesses.business_id AND score = 100)	join -> in-sub	1	0
8780	Please list the names of the restaurants that had a low risk violation in inspections in 2014.	SELECT DISTINCT T2.name FROM violations AS T1 INNER JOIN businesses AS T2 ON T1.business_id = T2.business_id WHERE STRFTIME('%Y', T1.date) = '2014' AND T1.risk_category = 'Low Risk'	SELECT b.name FROM businesses AS b WHERE b.business_id IN (SELECT v.business_id FROM violations AS v WHERE STRFTIME('%Y', v.date) = '2014' AND v.risk_category = 'Low Risk')	join -> in-sub	1	0
8782	Please list the descriptions of all the high risk violations of Tiramisu Kitchen.	SELECT DISTINCT T1.description FROM violations AS T1 INNER JOIN businesses AS T2 ON T1.business_id = T2.business_id WHERE T1.risk_category = 'High Risk' AND T2.name = 'Tiramisu Kitchen'	SELECT V.description FROM violations V JOIN businesses B ON V.business_id = B.business_id WHERE B.name = 'Tiramisu Kitchen' AND V.risk_category = 'High Risk';	redundant distinct	0	1
8785	Which restaurant had more low risk violation in inspections, Tiramisu Kitchen or OMNI S.F. Hotel - 2nd Floor Pantry?	SELECT CASE WHEN SUM(CASE WHEN T2.name = 'OMNI S.F. Hotel - 2nd Floor Pantry' THEN 1 ELSE 0 END) > SUM(CASE WHEN T2.name = 'Tiramisu Kitchen' THEN 1 ELSE 0 END) THEN 'OMNI S.F. Hotel - 2nd Floor Pantry' ELSE 'Tiramisu Kitchen' END AS result FROM violations AS T1 INNER JOIN businesses AS T2 ON T1.business_id = T2.business_id WHERE T1.risk_category = 'Low Risk'	SELECT name FROM (SELECT T1.name, RANK() OVER (ORDER BY COUNT(*) DESC) as rk FROM businesses T1 JOIN violations T2 ON T1.business_id = T2.business_id WHERE T1.name IN ('Tiramisu Kitchen', 'OMNI S.F. Hotel - 2nd Floor Pantry') AND T2.risk_category = 'Low Risk' GROUP BY T1.name) as subquery WHERE rk = 1	semantic error: CASE WHEN condition	0	0
8787	Which restaurant has the highest total number of high risk violations?	SELECT T2.name FROM violations AS T1 INNER JOIN businesses AS T2 ON T1.business_id = T2.business_id WHERE T1.risk_category = 'High Risk' GROUP BY T2.name ORDER BY COUNT(T2.name) DESC LIMIT 1	SELECT business_id FROM (SELECT T2.business_id, RANK() OVER (ORDER BY COUNT(T2.business_id) DESC) as rk FROM violations AS T1 INNER JOIN businesses AS T2 ON T1.business_id = T2.business_id WHERE T1.risk_category = 'High Risk' GROUP BY T2.business_id) as subquery WHERE rk = 1	limit 1; group by non-key; semantic error: output column	1	0
8789	Which business had the most number of inspections? Give the Id number for that business.	SELECT business_id FROM inspections GROUP BY business_id ORDER BY COUNT(business_id) DESC LIMIT 1	SELECT business_id FROM inspections GROUP BY business_id HAVING COUNT(business_id) = (SELECT MAX(count) FROM (SELECT COUNT(business_id) AS count FROM inspections GROUP BY business_id));	limit 1	0	1
8795	Which business had the lowest score for the unscheduled routine inspection on 2016/9/26? Give the name of the business.	SELECT T2.name FROM inspections AS T1 INNER JOIN businesses AS T2 ON T1.business_id = T2.business_id WHERE score = (SELECT MIN(score) FROM inspections WHERE 'date' = '2016-09-26' AND type = 'Routine - Unscheduled') AND T1.date = '2016-09-26' AND T1.type = 'Routine - Unscheduled'	SELECT T2.name FROM businesses T2 JOIN (SELECT business_id, MIN(score) AS min_score FROM inspections WHERE date = '2016-09-26' AND type = 'Routine - Unscheduled' GROUP BY business_id) T1 ON T2.business_id = T1.business_id WHERE T1.min_score = (SELECT MIN(score) FROM inspections WHERE date = '2016-09-26' AND type = 'Routine - Unscheduled');	join -> in-sub	0	1
8796	Provide the name of the business which had the most number of inspections because of complaint.	SELECT T2.name FROM inspections AS T1 INNER JOIN businesses AS T2 ON T1.business_id = T2.business_id WHERE T1.type = 'Complaint' GROUP BY T2.name ORDER BY COUNT(T1.business_id) DESC LIMIT 1	SELECT b.name FROM businesses b INNER JOIN (SELECT business_id FROM inspections WHERE type = 'Complaint' GROUP BY business_id HAVING COUNT(*) = (SELECT MAX(count) FROM (SELECT business_id, COUNT(*) AS count FROM inspections WHERE type = 'Complaint' GROUP BY business_id) tmp)) filtered ON b.business_id = filtered.business_id;	limit 1	0	1
8798	Give the address of the business with the most number of the low risk violations.	SELECT T2.address FROM violations AS T1 INNER JOIN businesses AS T2 ON T1.business_id = T2.business_id WHERE T1.risk_category = 'Low Risk' GROUP BY T2.address ORDER BY COUNT(T1.business_id) DESC LIMIT 1	SELECT T2.address FROM (SELECT business_id, COUNT(*) AS violation_count FROM violations WHERE risk_category = 'Low Risk' GROUP BY business_id) AS T1 JOIN businesses AS T2 ON T1.business_id = T2.business_id WHERE T1.violation_count = (SELECT MAX(violation_count) FROM (SELECT business_id, COUNT(*) AS violation_count FROM violations WHERE risk_category = 'Low Risk' GROUP BY business_id) AS subquery)	limit 1	0	1

8799	Which business was the first one to get a low risk violation because of 'Permit license or inspection report not posted'? Give the name of the business.	SELECT T2.name FROM violations AS T1 INNER JOIN businesses AS T2 ON T1.business_id = T2.business_id WHERE T1.'date' = (SELECT MIN('date') FROM violations WHERE risk_category = 'Low Risk' AND description = 'Permit license or inspection report not posted') AND T1.risk_category = 'Low Risk' AND T1.description = 'Permit license or inspection report not posted'	SELECT name FROM businesses WHERE business_id IN (SELECT business_id FROM (SELECT business_id, RANK() OVER (ORDER BY 'date' ASC) as rk FROM violations WHERE risk_category = 'Low Risk' AND description = 'Permit license or inspection report not posted') WHERE rk = 1)	join -> in-sub	1	0
8800	For the business which got the most number of violations, how many inspections did it have?	SELECT COUNT(T2.business_id) FROM violations AS T1 INNER JOIN inspections AS T2 ON T1.business_id = T2.business_id GROUP BY T1.business_id ORDER BY COUNT(T1.business_id) DESC LIMIT 1	SELECT COUNT(*) FROM inspections WHERE business_id IN (SELECT business_id FROM violations GROUP BY business_id HAVING COUNT(*) = (SELECT MAX(violation_count) FROM (SELECT business_id, COUNT(*) AS violation_count FROM violations GROUP BY business_id) AS violation_counts));	limit 1;	0	1
8802	What is the average score for 'Chairman Bao' in all its unscheduled routine inspections?	SELECT CAST(SUM(CASE WHEN T2.name = 'Chairman Bao' THEN T1.score ELSE 0 END) AS REAL) / COUNT(CASE WHEN T1.type = 'Routine - Unscheduled' THEN T1.score ELSE 0 END) FROM inspections AS T1 INNER JOIN businesses AS T2 ON T1.business_id = T2.business_id	SELECT AVG(T2.score) FROM businesses T1 JOIN inspections T2 ON T1.business_id = T2.business_id WHERE T1.name = 'Chairman Bao' AND T2.type = 'Routine - Unscheduled';	semantic error: 0 vs None	0	1
8805	How many establishments have an inspection score of no more than 50?	SELECT COUNT(DISTINCT business_id) FROM inspections WHERE score < 50	SELECT COUNT(DISTINCT business_id) FROM inspections WHERE score <= 50;	semantic error: wrong condition	0	1
8809	What are the names of the establishments that met all of the required standards in 2013?	SELECT DISTINCT T2.name FROM inspections AS T1 INNER JOIN businesses AS T2 ON T1.business_id = T2.business_id WHERE STRFTIME('%Y', T1.'date') = '2013' AND T1.score = 100	SELECT name FROM businesses WHERE business_id IN (SELECT business_id FROM inspections WHERE score = 100 AND strftime('%Y', date) = '2013')	join -> in-sub	1	0
8811	What is the name of the establishment with the lowest inspection score of all time?	SELECT T2.name FROM inspections AS T1 INNER JOIN businesses AS T2 ON T1.business_id = T2.business_id WHERE T1.score = (SELECT MIN(score) FROM inspections)	SELECT name FROM businesses WHERE business_id IN (SELECT business_id FROM inspections WHERE score = (SELECT MIN(score) FROM inspections WHERE score IS NOT NULL));	join -> in-sub	0	1
8814	In 2013, what are the names of the establishments with contaminated or adulterated food?	SELECT T2.name FROM violations AS T1 INNER JOIN businesses AS T2 ON T1.business_id = T2.business_id WHERE STRFTIME('%Y', T1.'date') = '2013' AND T1.description = 'Contaminated or adulterated food'	SELECT name FROM businesses WHERE business_id IN (SELECT business_id FROM violations WHERE description = 'Contaminated or adulterated food' AND strftime('%Y', date) = '2013')	join -> in-sub	1	0
8816	What are the names of the establishments that met all the required standards for 4 consecutive years?	SELECT DISTINCT T4.name FROM (SELECT T3.name, T3.years, row_number() OVER (PARTITION BY T3.name ORDER BY T3.years) AS rowNumber FROM (SELECT DISTINCT name, STRFTIME('%Y', 'date') AS years FROM inspections AS T1 INNER JOIN businesses AS T2 ON T1.business_id = T2.business_id WHERE T1.score = 100) AS T3) AS T4 GROUP BY T4.name, date(T4.years '-01-01', '-' (T4.rowNumber - 1) ' years') HAVING COUNT(T4.years) = 4	SELECT T1.name FROM businesses T1 JOIN inspections T2 ON T1.business_id = T2.business_id WHERE T2.score = 100 GROUP BY T1.business_id HAVING COUNT(DISTINCT strftime('%Y', T2.date)) = 4 AND min(strftime('%Y', T2.date)) = max(strftime('%Y', T2.date)) - 3	join -> in-sub; group by non-key	1	0
8819	What is the name of the establishment with the highest number of low risk violations in 2014?	SELECT T2.name FROM violations AS T1 INNER JOIN businesses AS T2 ON T1.business_id = T2.business_id WHERE STRFTIME('%Y', T1.'date') = '2014' AND T1.risk_category = 'Low Risk' GROUP BY T2.name ORDER BY COUNT(T2.business_id) DESC LIMIT 1	SELECT name FROM businesses WHERE business_id IN (SELECT business_id FROM violations WHERE risk_category = 'Low Risk' AND strftime('%Y', date) = '2014' GROUP BY business_id HAVING COUNT(*) = (SELECT MAX(counts) FROM (SELECT COUNT(*) AS counts FROM violations WHERE risk_category = 'Low Risk' AND strftime('%Y', date) = '2014' GROUP BY business_id)));	group by non-key; limit 1	0	1

8822	How many eateries got highest inspection in 2013?	SELECT COUNT(DISTINCT business_id) FROM inspections WHERE STRFTIME('%Y', 'date') = '2013' AND score = (SELECT MAX(score) FROM inspections WHERE STRFTIME('%Y', 'date') = '2013')	SELECT COUNT(DISTINCT business_id) FROM inspections WHERE score = 100 AND strftime('%Y', date) = '2013';	semantic error: wrong condition	0	1
8827	Describe the inspection types and violation descriptions under moderate risk category for ART's CAFÉ.	SELECT DISTINCT T2.type, T1.description FROM violations AS T1 INNER JOIN inspections AS T2 ON T1.business_id = T2.business_id INNER JOIN businesses AS T3 ON T2.business_id = T3.business_id WHERE T3.name = 'ART'S CAFÉ' AND T1.risk_category = 'Moderate Risk'	SELECT T2.type, T3.description FROM businesses T1 LEFT JOIN inspections T2 ON T1.business_id = T2.business_id LEFT JOIN violations T3 ON T1.business_id = T3.business_id WHERE T1.name = 'ART's CAFÉ' AND T3.risk_category = 'Moderate Risk'	str; redundant distinct; join -> left join	1	0
8834	What was the inspection type when El Aji Peruvian Restaurant got highest inspection score?	SELECT T1.type FROM inspections AS T1 INNER JOIN businesses AS T2 ON T1.business_id = T2.business_id WHERE T2.name = 'El Aji Peruvian Restaurant' ORDER BY T1.score DESC LIMIT 1	SELECT type FROM inspections WHERE business_id IN (SELECT business_id FROM businesses WHERE name = 'El Aji Peruvian Restaurant') AND score = (SELECT MAX(score) FROM inspections WHERE business_id IN (SELECT business_id FROM businesses WHERE name = 'El Aji Peruvian Restaurant'))	limit 1	0	1
8836	List the eateries' names and addresses which had reinspection on 2nd February, 2015.	SELECT T2.name, T2.address FROM inspections AS T1 INNER JOIN businesses AS T2 ON T1.business_id = T2.business_id WHERE T1.date = '2015-02-02' AND T1.type = 'Reinspection/Followup'	SELECT name, address FROM businesses WHERE business_id IN (SELECT business_id FROM inspections WHERE date = '2015-02-02' AND type = 'Reinspection/Followup');	join -> in-sub	0	1
8837	List the names and business certificates of the eateries which got inspection score under 50.	SELECT T2.name, T2.business_id FROM inspections AS T1 INNER JOIN businesses AS T2 ON T1.business_id = T2.business_id WHERE T1.score < 50	SELECT name, business_certificate FROM businesses WHERE business_id IN (SELECT business_id FROM inspections WHERE score < 50);	join -> in-sub; semantic error: output column	0	1
8843	List owner's name of businesses with a 100 score.	SELECT DISTINCT T2.owner_name FROM inspections AS T1 INNER JOIN businesses AS T2 ON T1.business_id = T2.business_id WHERE T1.score = 100	SELECT owner_name FROM businesses WHERE business_id IN (SELECT business_id FROM inspections WHERE score = 100);	join -> in-sub	0	1
8845	Among the businesses with score that ranges from 70 to 80, list their violation type ID and risk category.	SELECT DISTINCT T1.violation_type_id, T1.risk_category FROM violations AS T1 INNER JOIN businesses AS T2 ON T1.business_id = T2.business_id INNER JOIN inspections AS T3 ON T2.business_id = T3.business_id WHERE T3.score BETWEEN 70 AND 80	SELECT violation_type_id, risk_category FROM violations WHERE business_id IN (SELECT business_id FROM inspections WHERE score >= 80 AND score <= 90);	semantic error: wrong condition	0	1
8846	List the tax code and inspection type of the business named 'Rue Lepic'.	SELECT DISTINCT T3.tax_code, T2.type FROM violations AS T1 INNER JOIN inspections AS T2 ON T1.business_id = T2.business_id INNER JOIN businesses AS T3 ON T2.business_id = T3.business_id WHERE T3.name = 'Rue Lepic'	SELECT T3.tax_code, T2.type FROM inspections AS T2 LEFT JOIN businesses AS T3 ON T2.business_id = T3.business_id WHERE T3.name = 'Rue Lepic'	redundant distinct; join -> left join; semantic error: wrong join	0	0
8852	In businesses with an owner address 500 California St, 2nd Floor of Silicon Valley, list the type of inspection of the business with the highest score.	SELECT T1.type FROM inspections AS T1 INNER JOIN businesses AS T2 ON T1.business_id = T2.business_id WHERE T2.owner_address = '500 California St, 2nd Floor' AND T2.owner_city = 'SAN FRANCISCO' ORDER BY T1.score DESC LIMIT 1	SELECT type FROM inspections WHERE business_id = (SELECT business_id FROM businesses WHERE owner_address = '500 California St, 2nd Floor' AND owner_city = 'SAN FRANCISCO') AND score = (SELECT MAX(score) FROM inspections WHERE business_id IN (SELECT business_id FROM businesses WHERE owner_address = '500 California St, 2nd Floor' AND owner_city = 'SAN FRANCISCO'));	limit 1	0	1

Table 4: Incorrect case list of BIRD Dev set.

Case Id	NL	Original SQL	Modified SQL	Tag	Follow Consistency	Correctly Fixed
0	What is the highest eligible free rate for K-12 students in the schools in Alameda County?	SELECT 'Free Meal Count (K-12)' / 'Enrollment (K-12)' FROM frpm WHERE 'County Name' = 'Alameda' ORDER BY (CAST('Free Meal Count (K-12)' AS REAL) / 'Enrollment (K-12)') DESC LIMIT 1	SELECT MAX('Free Meal Count (K-12)' / 'Enrollment (K-12)') AS HighestEligibleFreeRate FROM frpm WHERE 'County Name' = 'Alameda' AND 'Enrollment (K-12)' > 0;	semantic error: empty vs None	0	1
1	Please list the lowest three eligible free rates for students aged 5-17 in continuation schools.	SELECT 'Free Meal Count (Ages 5-17)' / 'Enrollment (Ages 5-17)' FROM frpm WHERE 'Educational Option Type' = 'Continuation School' AND 'Free Meal Count (Ages 5-17)' / 'Enrollment (Ages 5-17)' IS NOT NULL ORDER BY 'Free Meal Count (Ages 5-17)' / 'Enrollment (Ages 5-17)' ASC LIMIT 3	SELECT rate FROM (SELECT 'Free Meal Count (Ages 5-17)' / 'Enrollment (Ages 5-17)' AS rate, rank() over (ORDER BY 'Free Meal Count (Ages 5-17)' / 'Enrollment (Ages 5-17)' ASC) as rk FROM frpm WHERE 'Educational Option Type' = 'Continuation School' AND 'Free Meal Count (Ages 5-17)' / 'Enrollment (Ages 5-17)' IS NOT NULL) WHERE rk <= 3	limit n	1	0
3	What is the unabbreviated mailing street address of the school with the highest FRPM count for K-12 students?	SELECT T2.MailStreet FROM frpm AS T1 INNER JOIN schools AS T2 ON T1.CDSCode = T2.CDSCode ORDER BY T1.FRPM Count (K-12) DESC LIMIT 1	SELECT MailStreet FROM (SELECT T2.MailStreet, RANK() OVER (ORDER BY T1.FRPM Count (K-12) DESC) as rk FROM frpm AS T1 INNER JOIN schools AS T2 ON T1.CDSCode = T2.CDSCode) AS ranked WHERE rk = 1	limit 1	0	0
5	How many schools with an average score in Math greater than 400 in the SAT test are exclusively virtual?	SELECT COUNT(DISTINCT T2.School) FROM satscores AS T1 INNER JOIN schools AS T2 ON T1.cds = T2.CDSCode WHERE T2.Virtual = 'F' AND T1.AvgScrMath > 400	SELECT COUNT(*) FROM schools T1 JOIN satscores T2 ON T1.CDSCode = T2.cds WHERE T2.AvgScrMath > 400 AND T1.Virtual = 'F';	redundant distinct: on count()	0	1
7	What is the phone number of the school that has the highest number of test takers with an SAT score of over 1500?	SELECT T2.Phone FROM satscores AS T1 INNER JOIN schools AS T2 ON T1.cds = T2.CDSCode ORDER BY T1.NumGE1500 DESC LIMIT 1	SELECT Phone FROM (SELECT T2.Phone, RANK() OVER (ORDER BY T1.NumGE1500 DESC) as rk FROM satscores AS T1 INNER JOIN schools AS T2 ON T1.cds = T2.CDSCode) AS ranked WHERE rk = 1	limit 1	0	0
8	What is the number of SAT test takers of the schools with the highest FRPM count for K-12 students?	SELECT NumTstTskr FROM satscores WHERE cds = (SELECT CDSCode FROM frpm ORDER BY 'FRPM Count (K-12)' DESC LIMIT 1)	SELECT T2.NumTstTskr FROM frpm T1 JOIN satscores T2 ON T1.CDSCode = T2.cds WHERE T1.FRPM Count (K-12) = (SELECT MAX('FRPM Count (K-12)') FROM frpm WHERE 'FRPM Count (K-12)' IS NOT NULL);	limit 1	0	1
9	Among the schools with the average score in Math over 560 in the SAT test, how many schools are directly charter-funded?	SELECT COUNT(T2.School Code) FROM satscores AS T1 INNER JOIN frpm AS T2 ON T1.cds = T2.CDSCode WHERE T1.AvgScrMath > 560 AND T2.Charter Funding Type = 'Directly funded'	SELECT COUNT(*) FROM schools T1 JOIN satscores T2 ON T1.CDSCode = T2.cds WHERE T2.AvgScrMath > 560 AND T1.FundingType = 'Directly funded';	semantic error: ignore NULL	0	1

10	For the school with the highest average score in Reading in the SAT test, what is its FRPM count for students aged 5-17?	SELECT T2.FRPM Count (Ages 5-17)' FROM satscores AS T1 INNER JOIN frpm AS T2 ON T1.cds = T2.CDSCode ORDER BY T1.AvgScrRead DESC LIMIT 1	SELECT T2.FRPM Count (Ages 5-17)' FROM satscores T1 JOIN frpm T2 ON T1.cds = T2.CDSCode WHERE T1.AvgScrRead = (SELECT MAX(AvgScrRead) FROM satscores WHERE AvgScrRead IS NOT NULL);	limit 1	0	1
13	Please list the phone numbers of the schools with the top 3 SAT excellence rate.	SELECT T1.Phone FROM schools AS T1 INNER JOIN satscores AS T2 ON T1.CDSCode = T2.cds ORDER BY CAST(T2.NumGE1500 AS REAL) / T2.NumTstTskr DESC LIMIT 3	SELECT Phone FROM (SELECT T1.Phone, RANK() OVER (ORDER BY CAST(T2.NumGE1500 AS REAL) / T2.NumTstTskr DESC) as rk FROM schools AS T1 INNER JOIN satscores AS T2 ON T1.CDSCode = T2.cds) AS ranked WHERE rk <= 3	limit n	0	0
14	List the top five schools, by descending order, from the highest to the lowest, the most number of Enrollment (Ages 5-17). Please give their NCES school identification number.	SELECT T1.NCESSchool FROM schools AS T1 INNER JOIN frpm AS T2 ON T1.CDSCode = T2.CDSCode ORDER BY T2.'Enrollment (Ages 5-17)' DESC LIMIT 5	SELECT NCESSchool FROM (SELECT T1.NCESSchool, RANK() OVER (ORDER BY T2.'Enrollment (Ages 5-17)' DESC) as rk FROM schools AS T1 INNER JOIN frpm AS T2 ON T1.CDSCode = T2.CDSCode) AS ranked WHERE rk <= 5	limit n	0	0
15	Which active district has the highest average score in Reading?	SELECT T1.District FROM schools AS T1 INNER JOIN satscores AS T2 ON T1.CDSCode = T2.cds WHERE T1.StatusType = 'Active' ORDER BY T2.AvgScrRead DESC LIMIT 1	SELECT District FROM (SELECT T1.District, RANK() OVER (ORDER BY T2.AvgScrRead DESC) as rk FROM schools AS T1 INNER JOIN satscores AS T2 ON T1.CDSCode = T2.cds WHERE T1.StatusType = 'Active') AS ranked WHERE rk = 1	limit 1	1	0
16	How many schools in merged Alameda have number of test takers less than 100?	SELECT COUNT(T1.CDSCode) FROM schools AS T1 INNER JOIN satscores AS T2 ON T1.CDSCode = T2.cds WHERE T1.StatusType = 'Merged' AND T2.NumTstTskr < 100 AND T1.County = 'Lake'	SELECT COUNT(DISTINCT T1.CDSCode) FROM schools T1 JOIN satscores T2 ON T1.CDSCode = T2.cds WHERE T1.StatusType = 'Merged' AND T1.County = 'Alameda' AND T2.NumTstTskr < 100;	semantic error: predicate value	0	1
17	Rank schools by their average score in Writing where the score is greater than 499, showing their charter numbers.	SELECT CharterNum, AvgScrWrite, RANK() OVER (ORDER BY AvgScrWrite DESC) AS WritingScoreRank FROM schools AS T1 INNER JOIN satscores AS T2 ON T1.CDSCode = T2.cds WHERE T2.AvgScrWrite > 499 AND CharterNum is not null	SELECT T2.CharterNum FROM satscores T1 JOIN schools T2 ON T1.cds = T2.CDSCode WHERE T1.AvgScrWrite > 499 AND T2.CharterNum IS NOT NULL ORDER BY T1.AvgScrWrite DESC;	semantic error: output col	0	1
19	What is the phone number of the school that has the highest average score in Math?	SELECT T1.Phone FROM schools AS T1 INNER JOIN satscores AS T2 ON T1.CDSCode = T2.cds ORDER BY T2.AvgScrMath DESC LIMIT 1	SELECT Phone FROM (SELECT T1.Phone, RANK() OVER (ORDER BY T2.AvgScrMath DESC) as rk FROM schools AS T1 INNER JOIN satscores AS T2 ON T1.CDSCode = T2.cds) AS ranked WHERE rk = 1	limit 1	0	0
22	Which school in Contra Costa has the highest number of test takers?	SELECT sname FROM satscores WHERE cname = 'Contra Costa' AND sname IS NOT NULL ORDER BY NumTstTskr DESC LIMIT 1	SELECT sname FROM (SELECT sname, RANK() OVER (ORDER BY NumTstTskr DESC) as rk FROM satscores WHERE cname = 'Contra Costa' AND sname IS NOT NULL) AS ranked WHERE rk = 1	limit 1	1	0
25	Name schools in Riverside which the average of average math score for SAT is grater than 400, what is the funding type of these schools?	SELECT T1.sname, T2.'Charter Funding Type' FROM satscores AS T1 INNER JOIN frpm AS T2 ON T1.cds = T2.CDSCode WHERE T2.'District Name' LIKE 'Riverside%' GROUP BY T1.sname, T2.'Charter Funding Type' HAVING CAST(SUM(T1.AvgScrMath) AS REAL) / COUNT(T1.cds) > 400	SELECT T1.sname, T2.'Charter Funding Type' FROM satscores AS T1 INNER JOIN frpm AS T2 ON T1.cds = T2.CDSCode WHERE T2.'County Name' = 'Riverside' GROUP BY T1.cds HAVING CAST(SUM(T1.AvgScrMath) AS REAL) / COUNT(T1.cds) > 400;	group by non-key; semantic error: wrong col for 'Riverside'	0	0

28	Consider the average difference between K-12 enrollment and 15-17 enrollment of schools that are locally funded, list the names and DOC type of schools which has a difference above this average.	SELECT T2.School, T2.DOC FROM frpm AS T1 INNER JOIN schools AS T2 ON T1.CDSCode = T2.CDSCode WHERE T2.FundingType = 'Locally funded' AND (T1.Enrollment (K-12)' - T1.Enrollment (Ages 5-17)') > (SELECT AVG(T3.Enrollment (K-12)' - T3.Enrollment (Ages 5-17)') FROM frpm AS T3 INNER JOIN schools AS T4 ON T3.CDSCode = T4.CDSCode WHERE T4.FundingType = 'Locally funded')	SELECT T1.School, T1.DOCType FROM schools T1 JOIN frpm T2 ON T1.CDSCode = T2.CDSCode WHERE T1.FundingType = 'Locally funded' AND (T2.Enrollment (K-12)' - T2.Enrollment (Ages 5-17)') > (SELECT AVG(T3.Enrollment (K-12)' - T3.Enrollment (Ages 5-17)') FROM schools T4 JOIN frpm T3 ON T4.CDSCode = T3.CDSCode WHERE T4.FundingType = 'Locally funded')	semantic error: output column	0	1
29	When did the first-through-twelfth-grade school with the largest enrollment open?	SELECT T2.OpenDate FROM frpm AS T1 INNER JOIN schools AS T2 ON T1.CDSCode = T2.CDSCode ORDER BY T1.Enrollment (K-12)' DESC LIMIT 1	SELECT T2.OpenDate FROM frpm AS T1 INNER JOIN schools AS T2 ON T1.CDSCode = T2.CDSCode WHERE T1.Enrollment (K-12)' = (SELECT max(T3.Enrollment (K-12)') FROM frpm AS T3)	limit 1	0	0
30	Which cities have the top 5 lowest enrollment number for students in grades 1 through 12?	SELECT T2.City FROM frpm AS T1 INNER JOIN schools AS T2 ON T1.CDSCode = T2.CDSCode GROUP BY T2.City ORDER BY SUM(T1.Enrollment (K-12)') ASC LIMIT 5	SELECT City FROM (SELECT T2.City, rank() over (ORDER BY SUM(T1.Enrollment (K-12)') ASC) as rk FROM frpm AS T1 INNER JOIN schools AS T2 ON T1.CDSCode = T2.CDSCode GROUP BY T2.City) WHERE rk <= 5;	limit n	1	0
32	What is the eligible free or reduced price meal rate for the top 5 schools in grades 1-12 with the highest free or reduced price meal count of the schools with the ownership code 66?	SELECT CAST(T1.FRPM Count (K-12)' AS REAL) / T1.Enrollment (K-12)' FROM frpm AS T1 INNER JOIN schools AS T2 ON T1.CDSCode = T2.CDSCode WHERE T2.SOC = 66 ORDER BY T1.FRPM Count (K-12)' DESC LIMIT 5	SELECT rate FROM (SELECT CAST(T1.FRPM Count (K-12)' AS REAL) / T1.Enrollment (K-12)' as rate, rank() over (ORDER BY T1.FRPM Count (K-12)' DESC) as rk FROM frpm AS T1 INNER JOIN schools AS T2 ON T1.CDSCode = T2.CDSCode WHERE T2.SOC = 66) WHERE rk <= 5;	limit n	1	0
35	What is the administrator's email address of the chartered school with the fewest students enrolled in grades 1 through 12?	SELECT T2.AdmEmail1 FROM frpm AS T1 INNER JOIN schools AS T2 ON T1.CDSCode = T2.CDSCode WHERE T1.Charter School (Y/N)' = 1 ORDER BY T1.Enrollment (K-12)' ASC LIMIT 1	SELECT AdmEmail1 FROM (SELECT T2.AdmEmail1, rank() over (ORDER BY T1.Enrollment (K-12)' ASC) as rk FROM frpm AS T1 INNER JOIN schools AS T2 ON T1.CDSCode = T2.CDSCode WHERE T1.Charter School (Y/N)' = 1) WHERE rk = 1	limit 1	0	0
36	Under whose administration is the school with the highest number of students scoring 1500 or more on the SAT? Indicate their full names.	SELECT T2.AdmFName1, T2.AdmLName1, T2.AdmFName2, T2.AdmLName2, T2.AdmFName3, T2.AdmLName3 FROM satscores AS T1 INNER JOIN schools AS T2 ON T1.cds = T2.CDSCode ORDER BY T1.NumGE1500 DESC LIMIT 1	SELECT T2.AdmFName1, T2.AdmLName1, T2.AdmFName2, T2.AdmLName2, T2.AdmFName3, T2.AdmLName3 FROM satscores T1 JOIN schools T2 ON T1.cds = T2.CDSCode WHERE T1.NumGE1500 = (SELECT MAX(NumGE1500) FROM satscores WHERE NumGE1500 IS NOT NULL)	limit 1	0	0
40	What is the telephone number for the school with the lowest average score in reading in Fresno Unified?	SELECT T2.Phone FROM satscores AS T1 INNER JOIN schools AS T2 ON T1.cds = T2.CDSCode WHERE T2.District = 'Fresno Unified' AND T1.AvgScrRead IS NOT NULL ORDER BY T1.AvgScrRead ASC LIMIT 1	SELECT Phone from (SELECT T2.Phone, rank() over (ORDER BY T1.AvgScrRead ASC) as rk FROM satscores AS T1 INNER JOIN schools AS T2 ON T1.cds = T2.CDSCode WHERE T2.District = 'Fresno Unified' AND T1.AvgScrRead IS NOT NULL) WHERE rk = 1;	limit 1	0	0
42	What is the type of education offered in the school who scored the highest average in Math?	SELECT T2.EdOpsName FROM satscores AS T1 INNER JOIN schools AS T2 ON T1.cds = T2.CDSCode ORDER BY T1.AvgScrMath DESC LIMIT 1	SELECT T2.EdOpsName FROM satscores T1 JOIN schools T2 ON T1.cds = T2.CDSCode WHERE T1.AvgScrMath = (SELECT MAX(AvgScrMath) FROM satscores WHERE AvgScrMath IS NOT NULL)	limit	0	0

43	What is the average math score of the school with the lowest average score for all subjects, and in which county is it located?	SELECT T1.AvgScrMath, T2.County FROM satscores AS T1 INNER JOIN schools AS T2 ON T1.cds = T2.CDSCode WHERE T1.AvgScrMath IS NOT NULL ORDER BY T1.AvgScrMath + T1.AvgScrRead + T1.AvgScrWrite ASC LIMIT 1	WITH RankedScores AS (SELECT cds, (AvgScrMath + AvgScrRead + AvgScrWrite) AS TotalScore FROM satscores WHERE AvgScrMath IS NOT NULL AND AvgScrRead IS NOT NULL AND AvgScrWrite IS NOT NULL) SELECT T1.AvgScrMath, T2.County FROM satscores AS T1 INNER JOIN schools AS T2 ON T1.cds = T2.CDSCode WHERE (AvgScrMath + AvgScrRead + AvgScrWrite) = (SELECT min(TotalScore) FROM RankedScores ORDER BY TotalScore ASC LIMIT 1)	limit	1	0
44	What is the average writing score of the school who has the highest number of test takers whose total SAT scores are greater or equal to 1500? Indicate the city to where the school is situated.	SELECT T1.AvgScrWrite, T2.City FROM satscores AS T1 INNER JOIN schools AS T2 ON T1.cds = T2.CDSCode ORDER BY T1.NumGE1500 DESC LIMIT 1	SELECT T2.City, T1.AvgScrWrite FROM satscores T1 JOIN schools T2 ON T1.cds = T2.CDSCode WHERE T1.NumGE1500 IS NOT NULL AND T1.NumGE1500 = (SELECT MAX(NumGE1500) FROM satscores WHERE NumGE1500 IS NOT NULL)	limit 1	0	1
46	Which state special schools have the highest number of enrollees from grades 1 through 12?	SELECT T2.School FROM frpm AS T1 INNER JOIN schools AS T2 ON T1.CDSCode = T2.CDSCode WHERE T2.DOC = 31 ORDER BY T1.'Enrollment (K-12)' DESC LIMIT 1	SELECT T2.School FROM frpm AS T1 INNER JOIN schools AS T2 ON T1.CDSCode = T2.CDSCode WHERE T2.DOC = 31 AND T1.'Enrollment (K-12)' = (SELECT max(T3.'Enrollment (K-12)') FROM frpm AS T3)	limit 1	0	0
49	Which different county has the most number of closed schools? Please provide the name of each school as well as the closure date.	SELECT DISTINCT County, School, ClosedDate FROM schools WHERE County = (SELECT County FROM schools WHERE StatusType = 'Closed' GROUP BY County ORDER BY COUNT(School) DESC LIMIT 1) AND StatusType = 'Closed' AND school IS NOT NULL	SELECT County, School, ClosedDate FROM schools WHERE County IN (SELECT County FROM (SELECT County, rank() over (ORDER BY COUNT(*) DESC) as rk FROM schools WHERE StatusType = 'Closed' GROUP BY County) WHERE rk = 1) AND StatusType = 'Closed' AND school IS NOT NULL	limit 1	0	0
51	In which mailing street address can you find the school that has the lowest average score in reading? Also give the school's name.	SELECT T2.MailStreet, T2.School FROM satscores AS T1 INNER JOIN schools AS T2 ON T1.cds = T2.CDSCode WHERE T1.AvgScrRead IS NOT NULL ORDER BY T1.AvgScrRead ASC LIMIT 1	WITH scr AS (SELECT T2.MailStreet, T2.School, T1.AvgScrRead FROM satscores AS T1 INNER JOIN schools AS T2 ON T1.cds = T2.CDSCode) SELECT MailStreet, School FROM scr WHERE AvgScrRead = (SELECT MIN(AvgScrRead) FROM scr)	limit 1	1	0
53	How many test takers are there at the school/s whose mailing city address is in Fresno?	SELECT T1.NumTstTskr FROM satscores AS T1 INNER JOIN schools AS T2 ON T1.cds = T2.CDSCode WHERE T2.MailCity = 'Fresno'	SELECT TOTAL(T2.NumTstTskr) FROM schools T1 INNER JOIN satscores T2 ON T1.CDSCode = T2.cds WHERE T1.MailCity = 'Fresno';	semantic error	1	0
56	Of all the schools with a mailing state address in California, how many are active in San Joaquin city?	SELECT COUNT(CDSCode) FROM schools WHERE City = 'San Joaquin' AND MailState = 'CA' AND StatusType = 'Active'	SELECT COUNT(CDSCode) FROM schools WHERE City = 'San Joaquin' AND MailState = 'California' AND StatusType = 'Active'	str: 'California'	1	0
57	What is the phone number and extension number for the school that had the 333rd highest average writing score?	SELECT T2.Phone, T2.Ext FROM satscores AS T1 INNER JOIN schools AS T2 ON T1.cds = T2.CDSCode ORDER BY T1.AvgScrWrite DESC LIMIT 332, 1	SELECT T2.Phone, T2.Ext FROM satscores AS T1 INNER JOIN schools AS T2 ON T1.cds = T2.CDSCode WHERE T1.AvgScrWrite = (SELECT T3.AvgScrWrite FROM satscores AS T3 ORDER BY T3.AvgScrWrite DESC LIMIT 332, 1)	limit 1	1	0

65	What is the ratio in percentage of Santa Clara County schools that are locally funded compared to all other types of charter school funding?	SELECT CAST(SUM(CASE WHEN FundingType = 'Locally funded' THEN 1 ELSE 0 END) AS REAL) * 100 / SUM(CASE WHEN FundingType != 'Locally funded' THEN 1 ELSE 0 END) FROM schools WHERE County = 'Santa Clara' AND Charter = 1	SELECT CAST(SUM(CASE WHEN FundingType = 'Locally funded' THEN 1 ELSE 0 END) AS REAL) * 100 / SUM(1) FROM schools WHERE County = 'Santa Clara' AND Charter = 1;	semantic error: wrong percentage calculation	0	0
78	What is the most common type of grade span served in the city of Adelanto?	SELECT GSserved FROM schools WHERE City = 'Adelanto' GROUP BY GSserved ORDER BY COUNT(GSserved) DESC LIMIT 1	SELECT GSserved FROM schools WHERE City = 'Adelanto' GROUP BY GSserved HAVING COUNT(*) = (SELECT MAX(count) FROM (SELECT COUNT(*) as count FROM schools WHERE City = 'Adelanto' GROUP BY GSserved) temp);	limit 1	0	1
79	Between San Diego and Santa Barbara, which county offers the most number of schools that does not offer physical building? Indicate the amount. 'Does not offer physical building' means Virtual = F in the database.	SELECT County, COUNT(Virtual) FROM schools WHERE (County = 'San Diego' OR County = 'Santa Barbara') AND Virtual = 'F' GROUP BY County ORDER BY COUNT(Virtual) DESC LIMIT 1	SELECT County, cnt FROM (SELECT County, COUNT(Virtual) as cnt, rank() over (ORDER BY COUNT(Virtual) DESC) as rk FROM schools WHERE (County = 'San Diego' OR County = 'Santa Barbara') AND Virtual = 'F' GROUP BY County) WHERE rk = 1	limit 1	1	0
84	What are the two most common first names among the school administrators? Indicate the district to which they administer.	SELECT DISTINCT T1.AdmFName1, T1.District FROM schools AS T1 INNER JOIN (SELECT admfname1 FROM schools GROUP BY admfname1 ORDER BY COUNT(admfname1) DESC LIMIT 2) AS T2 ON T1.AdmFName1 = T2.admfname1	SELECT DISTINCT AdmFName1, District FROM schools WHERE AdmFName1 IN (SELECT AdmFName1 FROM (SELECT AdmFName1, rank() over (ORDER BY COUNT(admfname1) DESC) as rk FROM schools GROUP BY AdmFName1) WHERE rk <= 2)	limit n	0	0
88	What is the administrator's email address for the school with the highest number of test takers who received SAT scores of at least 1500? Provide the name of the school.	SELECT T2.AdmEmail1, T2.School FROM satscores AS T1 INNER JOIN schools AS T2 ON T1.cds = T2.CDSCode ORDER BY T1.NumGE1500 DESC LIMIT 1	SELECT School, AdmEmail1 FROM schools WHERE CDSCode IN (SELECT cds FROM satscores WHERE NumGE1500 = (SELECT MAX(NumGE1500) FROM satscores WHERE NumGE1500 IS NOT NULL))	limit 1	0	1
89	How many accounts who choose issuance after transaction are staying in East Bohemia region?	SELECT COUNT(T2.account_id) FROM district AS T1 INNER JOIN account AS T2 ON T1.district_id = T2.district_id WHERE T1.A3 = 'east Bohemia' AND T2.frequency = 'POPLATEK PO OBRATU'	SELECT COUNT(T2.account_id) FROM district AS T1 INNER JOIN account AS T2 ON T1.district_id = T2.district_id WHERE T1.A3 = 'East Bohemia' AND T2.frequency = 'POPLATEK PO OBRATU'	str: 'East Bohemia'	1	0
90	How many accounts who have region in Prague are eligible for loans?	SELECT COUNT(T1.account_id) FROM account AS T1 INNER JOIN loan AS T2 ON T1.account_id = T2.account_id INNER JOIN district AS T3 ON T1.district_id = T3.district_id WHERE T3.A3 = 'Prague'	SELECT COUNT(DISTINCT T1.account_id) FROM account T1 JOIN district T2 ON T1.district_id = T2.district_id JOIN loan T3 ON T1.account_id = T3.account_id WHERE T2.A3 = 'Prague';	lack distinct	0	1
94	List out the account numbers of female clients who are oldest and has lowest average salary, calculate the gap between this lowest average salary with the highest average salary?	SELECT T1.account_id, (SELECT MAX(A11) - MIN(A11) FROM district) FROM account AS T1 INNER JOIN district AS T2 ON T1.district_id = T2.district_id INNER JOIN disp AS T3 ON T1.account_id = T3.account_id INNER JOIN client AS T4 ON T3.client_id = T4.client_id WHERE T2.district_id = (SELECT district_id FROM client WHERE gender = 'F' ORDER BY birth_date ASC LIMIT 1) ORDER BY T2.A11 DESC LIMIT 1	SELECT account_id, (SELECT MAX(A11) FROM district) - MIN(district.A11) AS salary_gap FROM client JOIN disp USING (client_id) JOIN account USING (account_id) JOIN district USING (district_id) WHERE gender = 'F' AND birth_date = (SELECT MIN(birth_date) FROM client WHERE gender = 'F') GROUP BY account_id;	semantic error	0	1

95	List out the account numbers of clients who are youngest and have highest average salary?	SELECT T1.account_id FROM account AS T1 INNER JOIN disp AS T2 ON T1.account_id = T2.account_id INNER JOIN client AS T3 ON T2.client_id = T3.client_id INNER JOIN district AS T4 on T4.district_id = T1.district_id WHERE T2.client_id = (SELECT client_id FROM client ORDER BY birth_date DESC LIMIT 1) GROUP BY T4.A11, T1.account_id	SELECT DISTINCT T1.account_id FROM account AS T1 INNER JOIN disp AS T2 ON T1.account_id = T2.account_id INNER JOIN client AS T3 ON T2.client_id = T3.client_id INNER JOIN district AS T4 on T4.district_id = T1.district_id WHERE T3.birth_date = (SELECT max(birth_date) FROM client) AND T4.A11 = (SELECT max(A11) FROM district)	limit 1; semantic error: lack condition for highest average salary	1	0
96	How many customers who choose statement of weekly issuance are Owner? 'POPLATEK TYDNE' stands for weekly issuance	SELECT COUNT(T1.account_id) FROM account AS T1 INNER JOIN disp AS T2 ON T1.account_id = T2.account_id WHERE T2.type = 'OWNER' AND T1.frequency = 'POPLATEK TYDNE'	SELECT COUNT(distinct T2.client_id) FROM account AS T1 INNER JOIN disp AS T2 ON T1.account_id = T2.account_id WHERE T2.type = 'OWNER' AND T1.frequency = 'POPLATEK TYDNE'	semantic error: customers but not accounts	1	0
97	List out the id number of client who choose statement of issuance after transaction are Disponent? 'POPLATEK PO OBRATU' stands for issuance after transaction	SELECT T2.client_id FROM account AS T1 INNER JOIN disp AS T2 ON T1.account_id = T2.account_id WHERE T1.frequency = 'POPLATEK PO OBRATU' AND T2.type = 'DISPONENT'	SELECT DISTINCT T2.client_id FROM account AS T1 INNER JOIN disp AS T2 ON T1.account_id = T2.account_id WHERE T1.frequency = 'POPLATEK PO OBRATU' AND T2.type = 'DISPONENT'	lack distinct	1	0
98	Among the accounts who have approved loan date in 1997, list out the accounts that have the lowest approved amount and choose weekly issuance statement. 'POPLATEK TYDNE' stands for weekly issuance	SELECT T2.account_id FROM loan AS T1 INNER JOIN account AS T2 ON T1.account_id = T2.account_id WHERE STRFTIME('%Y', T1.date) = '1997' AND T2.frequency = 'POPLATEK TYDNE' ORDER BY T1.amount LIMIT 1	SELECT account_id FROM account WHERE account_id IN (SELECT account_id FROM loan WHERE STRFTIME('%Y', date) = '1997' AND amount = (SELECT MIN(amount) FROM loan WHERE STRFTIME('%Y', date) = '1997')) AND account_id IN (SELECT account_id FROM loan WHERE STRFTIME('%Y', date) = '1997' AND frequency = 'POPLATEK TYDNE')	limit 1	1	0
99	Among the accounts who have loan validity more than 12 months, list out the accounts that have the highest approved amount and have account opening date in 1993.	SELECT T1.account_id FROM loan AS T1 INNER JOIN account AS T2 ON T1.account_id = T2.account_id WHERE STRFTIME('%Y', T2.date) = '1993' AND T1.duration > 12 ORDER BY T1.amount DESC LIMIT 1	SELECT T1.account_id FROM loan T1 JOIN account T2 ON T1.account_id = T2.account_id WHERE T1.duration > 12 AND strftime('%Y', T2.date) = '1993' AND T1.amount = (SELECT MAX(amount) FROM loan WHERE duration > 12 AND account_id IN (SELECT account_id FROM account WHERE strftime('%Y', date) = '1993')) GROUP BY T1.account_id HAVING MAX(T1.amount)	limit 1	0	1
101	List out the accounts who have the earliest trading date in 1995 ?	SELECT account_id FROM trans WHERE STRFTIME('%Y', date) = '1995' ORDER BY date ASC LIMIT 1	SELECT account_id FROM trans WHERE date = (SELECT MIN(date) FROM trans WHERE date BETWEEN '1995-01-01' AND '1995-12-31')	limit 1	0	1
102	State different accounts who have account opening date before 1997 and own an amount of money greater than 3000USD	SELECT DISTINCT T2.account_id FROM trans AS T1 INNER JOIN account AS T2 ON T1.account_id = T2.account_id WHERE STRFTIME('%Y', T2.date) < '1997' AND T1.amount > 3000	SELECT DISTINCT T2.account_id FROM trans AS T1 INNER JOIN account AS T2 ON T1.account_id = T2.account_id WHERE STRFTIME('%Y', T2.date) < '1997' AND T1.balance > 3000	semantic error	1	0

103	Which client issued his/her card in 1994/3/3, give his/her client id.	SELECT T2.client_id FROM client AS T1 INNER JOIN disp AS T2 ON T1.client_id = T2.client_id INNER JOIN card AS T3 ON T2.disp_id = T3.disp_id WHERE T3.issued = '1994-03-03'	SELECT client_id FROM disp WHERE disp_id IN (SELECT disp_id FROM card WHERE issued = '1994-03-03');	join -> in-sub	0	1
104	The transaction of 840 USD happened in 1998/10/14, when was this account opened?	SELECT T1.date FROM account AS T1 INNER JOIN trans AS T2 ON T1.account_id = T2.account_id WHERE T2.amount = 840 AND T2.date = '1998-10-14'	SELECT date FROM account WHERE account_id IN (SELECT account_id FROM trans WHERE amount = 840 AND date = '1998-10-14');	join -> in-sub	0	1
105	There was a loan approved in 1994/8/25, where was that account opened, give the district Id of the branch.	SELECT T1.district_id FROM account AS T1 INNER JOIN loan AS T2 ON T1.account_id = T2.account_id WHERE T2.date = '1994-08-25'	SELECT district_id FROM account WHERE account_id IN (SELECT account_id FROM loan WHERE date = '1994-08-25');	join -> in-sub	0	1
107	What is the gender of the oldest client who opened his/her account in the highest average salary branch?	SELECT T2.gender FROM district AS T1 INNER JOIN client AS T2 ON T1.district_id = T2.district_id ORDER BY T1.A11 DESC, T2.birth_date ASC LIMIT 1	SELECT gender FROM (SELECT client.gender, rank() over (ORDER BY client.birth_date ASC) as rk FROM district JOIN account ON district.district_id = account.district_id JOIN disp ON account.account_id = disp.account_id JOIN client ON disp.client_id = client.client_id GROUP BY client.client_id HAVING max(A11) = (SELECT max(A11) FROM district)) WHERE rk = 1	limit 1	0	0
108	For the client who applied the biggest loan, what was his/her first amount of transaction after opened the account?	SELECT T3.amount FROM loan AS T1 INNER JOIN account AS T2 ON T1.account_id = T2.account_id INNER JOIN trans AS T3 ON T2.account_id = T3.account_id ORDER BY T1.amount DESC, T3.date ASC LIMIT 1	SELECT amount FROM (SELECT amount, rank() over (ORDER BY date ASC) as rk FROM trans WHERE account_id IN (SELECT account_id FROM loan WHERE amount = (SELECT max(amount) FROM loan))) GROUP BY account_id) WHERE rk = 1	limit 1	1	0
109	How many clients opened their accounts in Jesenik branch were women?	SELECT COUNT(T1.client_id) FROM client AS T1 INNER JOIN district AS T2 ON T1.district_id = T2.district_id WHERE T1.gender = 'F' AND T2.A2 = 'Jesenik'	SELECT COUNT(DISTINCT T1.client_id) FROM client AS T1 JOIN disp T2 on T1.client_id = T2.client_id JOIN account T3 on T2.account_id = T3.account_id JOIN district AS T4 ON T3.district_id = T4.district_id WHERE T1.gender = 'F' AND T4.A2 = 'Jesenik';	semantic error: client.district_id means the district the client stays in	0	0
110	What is the disposition id of the client who made 5100 USD transaction in 1998/9/2?	SELECT T1.disp_id FROM disp AS T1 INNER JOIN account AS T2 ON T1.account_id = T2.account_id INNER JOIN trans AS T3 ON T2.account_id = T3.account_id WHERE T3.date = '1997-08-20' AND T3.amount = 5100	SELECT T1.disp_id FROM disp AS T1 INNER JOIN trans AS T3 ON T1.account_id = T3.account_id WHERE T3.date = '1998-09-02' AND T3.amount = 5100	semantic error: wrong date	1	0
112	For the female client who was born in 1976/1/29, which district did she opened her account?	SELECT T1.A2 FROM district AS T1 INNER JOIN client AS T2 ON T1.district_id = T2.district_id WHERE T2.birth_date = '1976-01-29' AND T2.gender = 'F'	SELECT A2 FROM district T4 WHERE T4.district_id IN (SELECT T3.district_id FROM client T1 JOIN disp T2 ON T1.client_id = T2.client_id JOIN account T3 ON T2.account_id = T3.account_id WHERE T1.gender = 'F' AND T1.birth_date = '1976-01-29')	semantic error: client.district_id means the district the client stays in	0	0
113	For the client who applied 98832 USD loan in 1996/1/3, when was his/her birthday?	SELECT T4.birth_date FROM loan AS T1 INNER JOIN account AS T2 ON T1.account_id = T2.account_id INNER JOIN disp AS T3 ON T2.account_id = T3.account_id INNER JOIN client AS T4 ON T3.client_id = T4.client_id WHERE T1.date = '1996-01-03' AND T1.amount = 98832	SELECT birth_date FROM client WHERE client_id IN (SELECT client_id FROM disp WHERE account_id IN (SELECT account_id FROM loan WHERE amount = 98832 AND date = '1996-01-03'));	join -> in-sub	0	1
114	For the first client who opened his/her account in Prague, what is his/her account ID?	SELECT T1.account_id FROM account AS T1 INNER JOIN district AS T2 ON T1.district_id = T2.district_id WHERE T2.A3 = 'Prague' ORDER BY T1.date ASC LIMIT 1	SELECT account_id FROM (SELECT T1.account_id, rank() over (ORDER BY T1.date ASC) as rk FROM account AS T1 INNER JOIN district AS T2 ON T1.district_id = T2.district_id WHERE T2.A3 = 'Prague') WHERE rk = 1	limit 1	1	0

115	For the branch which located in the south Bohemia with biggest number of inhabitants, what is the percentage of the male clients?	SELECT CAST(SUM(T1.gender = 'M') AS REAL) * 100 / COUNT(T1.client_id) FROM client AS T1 INNER JOIN district AS T2 ON T1.district_id = T2.district_id WHERE T2.A3 = 'south Bohemia' GROUP BY T2.A4 ORDER BY T2.A4 DESC LIMIT 1	SELECT p from (SELECT CAST(SUM(T1.gender = 'M') AS REAL) * 100 / COUNT(T1.client_id) as p, rank() over (ORDER BY T2.A4 DESC) as rk FROM client AS T1 INNER JOIN district AS T2 ON T1.district_id = T2.district_id WHERE T2.A3 = 'south Bohemia' GROUP BY T2.district_id) WHERE rk = 1;	limit 1	1	0
116	For the client whose loan was approved first in 1993/7/5, what is the increase rate of his/her account balance from 1993/3/22 to 1998/12/27?	SELECT CAST((SUM(IIF(T3.date = '1998-12-27', T3.balance, 0)) - SUM(IIF(T3.date = '1993-03-22', T3.balance, 0))) AS REAL) * 100 / SUM(IIF(T3.date = '1993-03-22', T3.balance, 0)) FROM loan AS T1 INNER JOIN account AS T2 ON T1.account_id = T2.account_id INNER JOIN trans AS T3 ON T3.account_id = T2.account_id WHERE T1.date = '1993-07-05'	SELECT CAST((SUM(IIF(trans.date = '1998-12-27', trans.balance, 0)) - SUM(IIF(trans.date = '1993-03-22', trans.balance, 0))) AS REAL) * 100 / SUM(IIF(trans.date = '1993-03-22', trans.balance, 0)) FROM (SELECT client_id FROM loan JOIN disp ON loan.account_id = disp.account_id GROUP BY client_id HAVING min(loan.date) = '1993-07-05') AS T JOIN disp ON disp.client_id = T.client_id JOIN trans ON disp.account_id = trans.account_id GROUP BY T.client_id		0	0
128	List the top nine districts, by descending order, from the highest to the lowest, the number of female account holders.	SELECT T2.A2, COUNT(T1.client_id) FROM client AS T1 INNER JOIN district AS T2 ON T1.district_id = T2.district_id WHERE T1.gender = 'F' GROUP BY T2.district_id, T2.A2 ORDER BY COUNT(T1.client_id) DESC LIMIT 9	SELECT district.A2 FROM district JOIN (SELECT account.district_id, rank() over (ORDER BY COUNT(*) DESC) as rk FROM account JOIN disp ON account.account_id = disp.account_id JOIN client ON disp.client_id = client.client_id WHERE client.gender = 'F' GROUP BY account.district_id) AS subquery ON district.district_id = subquery.district_id WHERE rk <= 9	limit n; semantic error: output column	0	0
130	How many of the account holders in South Bohemia still do not own credit cards?	SELECT COUNT(T3.account_id) FROM district AS T1 INNER JOIN client AS T2 ON T1.district_id = T2.district_id INNER JOIN disp AS T3 ON T2.client_id = T3.client_id WHERE T1.A3 = 'south Bohemia' AND T3.type != 'OWNER'	SELECT COUNT(*) FROM client WHERE client_id NOT IN (SELECT client_id FROM disp WHERE type = 'OWNER') AND district_id IN (SELECT district_id FROM district WHERE A3 = 'south Bohemia')	semantic error: a client may multiple accounts	0	0
131	Which district has highest active loan?	SELECT T2.A3 FROM account AS T1 INNER JOIN district AS T2 ON T1.district_id = T2.district_id INNER JOIN loan AS T3 ON T1.account_id = T3.account_id WHERE T3.status IN ('C', 'D') GROUP BY T2.A3 ORDER BY SUM(T3.amount) DESC LIMIT 1	SELECT A3 FROM (SELECT T2.A3, rank() over (ORDER BY SUM(T3.amount) DESC) as rk FROM account AS T1 INNER JOIN district AS T2 ON T1.district_id = T2.district_id INNER JOIN loan AS T3 ON T1.account_id = T3.account_id WHERE T3.status IN ('C', 'D') GROUP BY T2.district_id) WHERE rk = 1	group by non-key; limit 1	1	0
132	What is the average loan amount by male borrowers?	SELECT AVG(T4.amount) FROM client AS T1 INNER JOIN disp AS T2 ON T1.client_id = T2.client_id INNER JOIN account AS T3 ON T2.account_id = T3.account_id INNER JOIN loan AS T4 ON T3.account_id = T4.account_id WHERE T1.gender = 'M'	SELECT avg(loans) FROM (SELECT sum(T4.amount) as loans FROM client AS T1 INNER JOIN disp AS T2 ON T1.client_id = T2.client_id INNER JOIN account AS T3 ON T2.account_id = T3.account_id INNER JOIN loan AS T4 ON T3.account_id = T4.account_id WHERE T1.gender = 'M' GROUP BY T1.client_id);	semantic error: a client may multiple loans	0	0
133	In 1996, which districts have the highest unemployment rate? List their branch location and district name.	SELECT district_id, A2 FROM district ORDER BY A13 DESC LIMIT 1	SELECT district_id, A2 FROM (SELECT district_id, A2, rank() over (ORDER BY A13 DESC) as rk FROM district) WHERE rk = 1	limit 1	0	0
134	In the branch where the largest number of crimes were committed in 1996, how many accounts were opened?	SELECT COUNT(T2.account_id) FROM district AS T1 INNER JOIN account AS T2 ON T1.district_id = T2.district_id GROUP BY T1.A16 ORDER BY T1.A16 DESC LIMIT 1	SELECT COUNT(*) FROM account WHERE district_id IN (SELECT district_id FROM district WHERE A16 = (SELECT max(A16) FROM district)) GROUP BY district_id	limit 1	0	0

135	After making a credit card withdrawal, how many account/s with monthly issuance has a negative balance?	SELECT COUNT(T1.account_id) FROM trans AS T1 INNER JOIN account AS T2 ON T1.account_id = T2.account_id WHERE T1.balance < 0 AND T1.operation = 'VYBER KARTOU' AND T2.frequency = 'POPLATEK MESICNE'	SELECT COUNT(DISTINCT T1.account_id) FROM trans AS T1 INNER JOIN account AS T2 ON T1.account_id = T2.account_id WHERE T1.balance < 0 AND T1.operation = 'VYBER KARTOU' AND T2.frequency = 'POPLATEK MESICNE'	lack distinct	1	0
137	How many accounts have running contracts in Branch location 1?	SELECT COUNT(T1.account_id) FROM account AS T1 INNER JOIN district AS T2 ON T1.district_id = T2.district_id INNER JOIN loan AS T3 ON T1.account_id = T3.account_id WHERE T1.district_id = 1 AND (T3.status = 'C' OR T3.status = 'D')	SELECT COUNT(DISTINCT T1.account_id) FROM loan T1 JOIN account T2 ON T1.account_id = T2.account_id WHERE T2.district_id = 1 AND T1.status IN ('C', 'D');	lack distinct	0	1
138	In the branch where the second-highest number of crimes were committed in 1995 occurred, how many male clients are there?	SELECT COUNT(T1.client_id) FROM client AS T1 INNER JOIN district AS T2 ON T1.district_id = T2.district_id WHERE T1.gender = 'M' AND T2.A15 = (SELECT T3.A15 FROM district AS T3 ORDER BY T3.A15 DESC LIMIT 1, 1)	SELECT cnt FROM (SELECT COUNT(T1.client_id) as cnt, rank() over (ORDER BY T2.A15 DESC) as rk FROM client AS T1 INNER JOIN district AS T2 ON T1.district_id = T2.district_id WHERE T1.gender = 'M' GROUP BY T1.district_id) WHERE rk = 2;	limit 1	1	0
143	What are the accounts that have gold credit cards?	SELECT T2.account_id FROM disp AS T2 INNER JOIN card AS T1 ON T1.disp_id = T2.disp_id WHERE T1.type = 'gold'	SELECT DISTINCT T2.account_id FROM card T1 JOIN disp T2 ON T1.disp_id = T2.disp_id WHERE T1.type = 'gold';	lack distinct	0	1
145	Who are the account holder identification numbers whose who have transactions on the credit card with the amount is less than the average, in 1998?	SELECT T1.account_id FROM trans AS T1 INNER JOIN account AS T2 ON T1.account_id = T2.account_id WHERE STRFTIME('%Y', T1.date) = '1998' AND T1.operation = 'VYBER KARTOU' AND T1.amount < (SELECT AVG(amount) FROM trans WHERE STRFTIME('%Y', date) = '1998')	SELECT DISTINCT T2.client_id FROM trans T1 JOIN disp T2 ON T1.account_id = T2.account_id WHERE T1.operation = 'VYBER KARTOU' AND strftime('%Y' , T1.date) = '1998' AND T1.amount < (SELECT AVG(amount) FROM trans WHERE operation = 'VYBER KARTOU' AND strftime('%Y' , date) = '1998')	semantic error: output column; wrong condition	0	0
146	Who are the female account holders who own credit cards and also have loans?	SELECT T1.client_id FROM client AS T1 INNER JOIN disp AS T2 ON T1.client_id = T2.client_id INNER JOIN account AS T5 ON T2.account_id = T5.account_id INNER JOIN loan AS T3 ON T5.account_id = T3.account_id INNER JOIN card AS T4 ON T2.disp_id = T4.disp_id WHERE T1.gender = 'F'	SELECT DISTINCT T1.client_id FROM client T1 JOIN disp T2 ON T1.client_id = T2.client_id JOIN card T3 ON T2.disp_id = T3.disp_id JOIN loan T4 ON T2.account_id = T4.account_id WHERE T1.gender = 'F' AND T2.type = 'OWNER';	lack distinct; semantic error: wrong condition	0	1
147	How many female clients' accounts are in the region of South Bohemia?	SELECT COUNT(T1.client_id) FROM client AS T1 INNER JOIN district AS T2 ON T1.district_id = T2.district_id WHERE T1.gender = 'F' AND T2.A3 = 'south Bohemia'	SELECT COUNT(DISTINCT T1.client_id) FROM client AS T1 INNER JOIN disp AS T2 ON T1.client_id = T2.client_id INNER JOIN account AS T3 ON T2.account_id = T3.account_id INNER JOIN district AS T4 ON T3.district_id = T4.district_id WHERE T1.gender = 'F' AND T4.A3 = 'south Bohemia';	semantic error: client.district_id means the district the client stays in	0	0
148	Please list the accounts whose district is Tabor that are eligible for loans.	SELECT T2.account_id FROM district AS T1 INNER JOIN account AS T2 ON T1.district_id = T2.district_id INNER JOIN disp AS T3 ON T2.account_id = T3.account_id WHERE T3.type = 'OWNER' AND T1.A2 = 'Tabor'	SELECT DISTINCT account.account_id FROM account JOIN district ON account.district_id = district.district_id JOIN disp ON account.account_id = disp.account_id WHERE district.A2 = 'Tabor' AND disp.type = 'OWNER';	lack distinct	0	1
149	Please list the account types that are not eligible for loans, and the average income of residents in the district where the account is located exceeds \$8000 but is no more than \$9000.	SELECT T3.type FROM district AS T1 INNER JOIN account AS T2 ON T1.district_id = T2.district_id INNER JOIN disp AS T3 ON T2.account_id = T3.account_id WHERE T3.type != 'OWNER' AND T1.A11 BETWEEN 8000 AND 9000	SELECT DISTINCT T3.type FROM district AS T1 INNER JOIN account AS T2 ON T1.district_id = T2.district_id INNER JOIN disp AS T3 ON T2.account_id = T3.account_id WHERE T3.type != 'OWNER' AND T1.A11 BETWEEN 8000 AND 9000		0	0

150	How many accounts in North Bohemia has made a transaction with the partner's bank being AB?	SELECT COUNT(T2.account_id) FROM district AS T1 INNER JOIN account AS T2 ON T1.district_id = T2.district_id INNER JOIN trans AS T3 ON T2.account_id = T3.account_id WHERE T3.bank = 'AB' AND T1.A3 = 'north Bohemia'	SELECT COUNT(DISTINCT T2.account_id) FROM district AS T1 INNER JOIN account AS T2 ON T1.district_id = T2.district_id INNER JOIN trans AS T3 ON T2.account_id = T3.account_id WHERE T3.bank = 'AB' AND T1.A3 = 'North Bohemia'	lack distinct; str	1	0
151	Please list the name of the districts with accounts that made withdrawal transactions.	SELECT DISTINCT T1.A2 FROM district AS T1 INNER JOIN account AS T2 ON T1.district_id = T2.district_id INNER JOIN trans AS T3 ON T2.account_id = T3.account_id WHERE T3.type = 'VYDAJ'	SELECT T1.A2 FROM district AS T1 WHERE district_id IN (SELECT T2.district_id FROM account AS T2 INNER JOIN trans AS T3 ON T2.account_id = T3.account_id WHERE T3.type = 'VYDAJ')	join -> in-sub	1	0
152	What is the average number of crimes committed in 1995 in regions where the number exceeds 4000 and the region has accounts that are opened starting from the year 1997?	SELECT AVG(T1.A15) FROM district AS T1 INNER JOIN account AS T2 ON T1.district_id = T2.district_id WHERE STRFTIME('%Y', T2.date) >= '1997' AND T1.A15 > 4000	SELECT AVG(T1.A15) FROM district AS T1 WHERE district_id IN (SELECT district_id FROM account AS T2 WHERE STRFTIME('%Y', T2.date) >= '1997') AND T1.A15 > 4000	semantic error	1	0
156	Who is the owner of the account with the largest loan amount?	SELECT T1.client_id FROM disp AS T1 INNER JOIN account AS T3 ON T1.account_id = T3.account_id INNER JOIN loan AS T2 ON T3.account_id = T2.account_id WHERE T1.type = 'OWNER' ORDER BY T2.amount DESC LIMIT 1	SELECT DISTINCT client_id FROM (SELECT T1.client_id, rank() over (ORDER BY T2.amount DESC) as rk FROM disp AS T1 INNER JOIN account AS T3 ON T1.account_id = T3.account_id INNER JOIN loan AS T2 ON T3.account_id = T2.account_id WHERE T1.type = 'OWNER') WHERE rk = 1;	limit 1	1	0
160	Among the weekly issuance accounts, how many have a loan of under 200000?	SELECT COUNT(T1.account_id) FROM loan AS T1 INNER JOIN account AS T2 ON T1.account_id = T2.account_id WHERE T2.frequency = 'POPLATEK TYDNE' AND T1.amount < 200000	SELECT COUNT(DISTINCT T1.account_id) FROM loan AS T1 INNER JOIN account AS T2 ON T1.account_id = T2.account_id WHERE T2.frequency = 'POPLATEK TYDNE' AND T1.amount < 200000	lack distinct	1	0
161	What type of credit card does the client with the id 13539 own?	SELECT T3.type FROM disp AS T1 INNER JOIN client AS T2 ON T1.client_id = T2.client_id INNER JOIN card AS T3 ON T1.disp_id = T3.disp_id WHERE T2.client_id = 13539	SELECT DISTINCT T3.type FROM disp AS T1 INNER JOIN client AS T2 ON T1.client_id = T2.client_id INNER JOIN card AS T3 ON T1.disp_id = T3.disp_id WHERE T2.client_id = 13539	lack distinct	1	0
163	Which district has the most accounts with loan contracts finished with no problems?	SELECT T1.A2 FROM District AS T1 INNER JOIN Account AS T2 ON T1.District_id = T2.District_id INNER JOIN Loan AS T3 ON T2.Account_id = T3.Account_id WHERE T3.status = 'A' GROUP BY T1.District_id ORDER BY COUNT(T2.Account_id) DESC LIMIT 1	SELECT T3.A2 FROM district T3 INNER JOIN account T2 ON T3.district_id = T2.district_id INNER JOIN loan T1 ON T2.account_id = T1.account_id WHERE T1.status = 'A' GROUP BY T3.district_id HAVING COUNT(DISTINCT T1.account_id) = (SELECT MAX(count) FROM (SELECT COUNT(DISTINCT T1.account_id) AS count FROM loan T1 JOIN account T2 ON T1.account_id = T2.account_id WHERE T1.status = 'A' GROUP BY T2.district_id));	limit 1; lack distinct	0	0
167	List all the clients' IDs whose junior credit cards were issued after 1996.	SELECT T2.client_id FROM card AS T1 INNER JOIN disp AS T2 ON T1.disp_id = T2.disp_id WHERE T1.type = 'junior' AND T1.issued >= '1997-01-01'	SELECT DISTINCT T2.client_id FROM card AS T1 JOIN disp AS T2 ON T1.disp_id = T2.disp_id WHERE T1.type = 'junior' AND T1.issued >= '1997-01-01';	lack distinct	0	1
168	What percentage of clients who opened their accounts in the district with an average salary of over 10000 are women?	SELECT CAST(SUM(T2.gender = 'F') AS REAL) * 100 / COUNT(T2.client_id) FROM district AS T1 INNER JOIN client AS T2 ON T1.district_id = T2.district_id WHERE T1.A11 > 10000	SELECT CAST(COUNT(DISTINCT CASE WHEN client.gender = 'F' THEN client.client_id END) AS REAL) * 100 / COUNT(DISTINCT client.client_id) FROM client JOIN disp ON client.client_id = disp.client_id JOIN account ON disp.account_id = account.account_id JOIN district ON account.district_id = district.district_id WHERE district.A11 > 10000;	semantic error: client.district_id means the district the client stays in	0	0

169	What was the growth rate of the total amount of loans across all accounts for a male client between 1996 and 1997?	SELECT CAST((SUM(CASE WHEN STRFTIME('%Y', T1.date) = '1997' THEN T1.amount ELSE 0 END) - SUM(CASE WHEN STRFTIME('%Y', T1.date) = '1996' THEN T1.amount ELSE 0 END)) AS REAL) * 100 / SUM(CASE WHEN STRFTIME('%Y', T1.date) = '1996' THEN T1.amount ELSE 0 END) FROM loan AS T1 INNER JOIN account AS T2 ON T1.account_id = T2.account_id INNER JOIN disp AS T3 ON T3.account_id = T2.account_id INNER JOIN client AS T4 ON T4.client_id = T3.client_id WHERE T4.gender = 'M' AND T3.type = 'OWNER'	SELECT CAST((SUM(CASE WHEN STRFTIME('%Y', T1.date) = '1997' THEN T1.amount ELSE 0 END) - SUM(CASE WHEN STRFTIME('%Y', T1.date) = '1996' THEN T1.amount ELSE 0 END)) AS REAL) * 100 / SUM(CASE WHEN STRFTIME('%Y', T1.date) = '1996' THEN T1.amount ELSE 0 END) FROM loan AS T1 WHERE T1.account_id IN (SELECT T2.account_id FROM account AS T2 INNER JOIN disp AS T3 ON T3.account_id = T2.account_id INNER JOIN client AS T4 ON T4.client_id = T3.client_id WHERE T4.gender = 'M' AND T3.type = 'OWNER')	join -> in-sub	0	0
171	What was the difference in the number of crimes committed in East and North Bohemia in 1996?	SELECT SUM(IIF(A3 = 'east Bohemia', A16, 0)) - SUM(IIF(A3 = 'north Bohemia', A16, 0)) FROM district	SELECT SUM(IIF(A3 = 'East Bohemia', A16, 0)) - SUM(IIF(A3 = 'North Bohemia', A16, 0)) FROM district	str	0	0
174	What year was account owner number 130 born?	SELECT STRFTIME('%Y', T1.birth_date) FROM client AS T1 INNER JOIN disp AS T3 ON T1.client_id = T3.client_id INNER JOIN account AS T2 ON T3.account_id = T2.account_id WHERE T2.account_id = 130	SELECT strftime('%Y', birth_date) FROM client WHERE client_id IN (SELECT client_id FROM disp WHERE account_id = 130);	join -> in-sub	0	1
175	How many accounts have an owner disposition and request for a statement to be generated upon a transaction?	SELECT COUNT(T1.account_id) FROM account AS T1 INNER JOIN disp AS T2 ON T1.account_id = T2.account_id WHERE T2.type = 'OWNER' AND T1.frequency = 'POPLATEK PO OBRATU'	SELECT COUNT(DISTINCT T1.account_id) FROM account T1 JOIN disp T2 ON T1.account_id = T2.account_id WHERE T1.frequency = 'POPLATEK PO OBRATU' AND T2.type = 'OWNER';	lack distinct	0	1
178	Which kind of credit card does client number 9 possess?	SELECT T3.type FROM client AS T1 INNER JOIN disp AS T2 ON T1.client_id = T2.client_id INNER JOIN card AS T3 ON T2.disp_id = T3.disp_id WHERE T1.client_id = 9	SELECT DISTINCT T3.type FROM client AS T1 INNER JOIN disp AS T2 ON T1.client_id = T2.client_id INNER JOIN card AS T3 ON T2.disp_id = T3.disp_id WHERE T1.client_id = 9	lack distinct	1	0
180	Please provide a list of clients who were born between 1983 and 1987 and whose account branch is in East Bohemia, along with their IDs.	SELECT T1.client_id, T3.account_id FROM client AS T1 INNER JOIN district AS T2 ON T1.district_id = T2.district_id INNER JOIN disp AS T4 ON T1.client_id = T4.client_id INNER JOIN account AS T3 ON T2.district_id = T3.district_id and T4.account_id = T3.account_id WHERE T2.A3 = 'east Bohemia' AND STRFTIME('%Y', T1.birth_date) BETWEEN '1983' AND '1987'	SELECT T1.client_id, T3.account_id FROM client AS T1 INNER JOIN district AS T2 ON T1.district_id = T2.district_id INNER JOIN disp AS T4 ON T1.client_id = T4.client_id INNER JOIN account AS T3 ON T2.district_id = T3.district_id and T4.account_id = T3.account_id WHERE T2.A3 = 'East Bohemia' AND STRFTIME('%Y', T1.birth_date) BETWEEN '1983' AND '1987'	str	0	0
181	Please provide the IDs of the 3 female clients with the largest loans.	SELECT T1.client_id FROM client AS T1 INNER JOIN disp AS T4 on T1.client_id = T4.client_id INNER JOIN account AS T2 ON T4.account_id = T2.account_id INNER JOIN loan AS T3 ON T2.account_id = T3.account_id and T4.account_id = T3.account_id WHERE T1.gender = 'F' ORDER BY T3.amount DESC LIMIT 3	SELECT client_id FROM (SELECT T1.client_id, rank() over (ORDER BY MAX(T3.amount) DESC) as rk FROM client AS T1 INNER JOIN disp AS T4 on T1.client_id = T4.client_id INNER JOIN account AS T2 ON T4.account_id = T2.account_id INNER JOIN loan AS T3 ON T2.account_id = T3.account_id and T4.account_id = T3.account_id WHERE T1.gender = 'F' GROUP BY T1.client_id) WHERE rk <= 3	limit n	0	0
182	How many male customers who were born between 1974 and 1976 have made a payment on their home in excess of \$4000?	SELECT COUNT(T1.account_id) FROM trans AS T1 INNER JOIN account AS T2 ON T1.account_id = T2.account_id INNER JOIN disp AS T4 ON T2.account_id = T4.account_id INNER JOIN client AS T3 ON T4.client_id = T3.client_id WHERE STRFTIME('%Y', T3.birth_date) BETWEEN '1974' AND '1976' AND T3.gender = 'M' AND T1.amount > 4000 AND T1.k_symbol = 'SIPO'	SELECT COUNT(DISTINCT T1.client_id) FROM client T1 JOIN disp T2 ON T1.client_id = T2.client_id JOIN trans T3 ON T2.account_id = T3.account_id WHERE T1.gender = 'M' AND T1.birth_date BETWEEN '1974-01-01' AND '1976-12-31' AND T3.k_symbol = 'SIPO' AND T3.amount > 4000;	lack distinct	0	1

184	How many female customers have a junior credit card?	SELECT COUNT(T1.client_id) FROM client AS T1 INNER JOIN disp AS T2 ON T1.client_id = T2.client_id INNER JOIN card AS T3 ON T2.disp_id = T3.disp_id WHERE T1.gender = 'F' AND T3.type = 'junior'	SELECT COUNT(DISTINCT T1.client_id) FROM client T1 JOIN disp T2 ON T1.client_id = T2.client_id JOIN card T3 ON T2.disp_id = T3.disp_id WHERE T1.gender = 'F' AND T3.type = 'junior';	lack distinct	0	1
185	What proportion of customers who have accounts at the Prague branch are female?	SELECT CAST(SUM(T2.gender = 'F') AS REAL) / COUNT(T2.client_id) * 100 FROM district AS T1 INNER JOIN client AS T2 ON T1.district_id = T2.district_id WHERE T1.A3 = 'Prague'	SELECT (COUNT(DISTINCT CASE WHEN T3.gender = 'F' THEN T3.client_id END) * 100.0 / COUNT(DISTINCT T3.client_id)) AS percentage_female FROM district T1 JOIN account T2 ON T1.district_id = T2.district_id JOIN disp T4 ON T2.account_id = T4.account_id JOIN client T3 ON T4.client_id = T3.client_id WHERE T1.A3 = 'Prague';	lack distinct	0	1
186	What percentage of male clients request for weekly statements to be issued?	SELECT CAST(SUM(T1.gender = 'M') AS REAL) * 100 / COUNT(T1.client_id) FROM client AS T1 INNER JOIN district AS T3 ON T1.district_id = T3.district_id INNER JOIN account AS T2 ON T2.district_id = T3.district_id INNER JOIN disp AS T4 ON T1.client_id = T4.client_id AND T2.account_id = T4.account_id WHERE T2.frequency = 'POPLATEK TYDNE'	SELECT (COUNT(DISTINCT T1.client_id) * 100.0 / (SELECT COUNT(DISTINCT T1.client_id) FROM client T1 JOIN disp T2 ON T1.client_id = T2.client_id JOIN account T3 ON T2.account_id = T3.account_id WHERE T3.frequency = 'POPLATEK TYDNE')) AS percentage FROM client T1 JOIN disp T2 ON T1.client_id = T2.client_id JOIN account T3 ON T2.account_id = T3.account_id WHERE T1.gender = 'M' AND T3.frequency = 'POPLATEK TYDNE';	lack distinct; semantic error: wrong join condition	0	1
187	How many clients who choose statement of weekly issuance are Owner?	SELECT COUNT(T2.account_id) FROM account AS T1 INNER JOIN disp AS T2 ON T2.account_id = T1.account_id WHERE T1.frequency = 'POPLATEK TYDNE' AND T2.type = 'OWNER'	SELECT COUNT(DISTINCT T2.client_id) FROM account T1 JOIN disp T2 ON T1.account_id = T2.account_id WHERE T1.frequency = 'POPLATEK TYDNE' AND T2.type = 'OWNER';	lack distinct	0	1
188	Among the accounts who have loan validity more than 24 months, list out the accounts that have the lowest approved amount and have account opening date before 1997.	SELECT T1.account_id FROM loan AS T1 INNER JOIN account AS T2 ON T1.account_id = T2.account_id WHERE T1.duration > 24 AND STRFTIME('%Y', T2.date) < '1997' ORDER BY T1.amount ASC LIMIT 1	SELECT DISTINCT L.account_id FROM loan L, account A WHERE L.account_id = A.account_id AND L.duration > 24 AND A.date < '1997-01-01' AND L.amount = (SELECT MIN(L2.amount) FROM loan L2 WHERE L2.duration > 24)	limit 1	0	1
189	Name the account numbers of female clients who are oldest and have lowest average salary?	SELECT T3.account_id FROM client AS T1 INNER JOIN district AS T2 ON T1.district_id = T2.district_id INNER JOIN account AS T3 ON T2.district_id = T3.district_id WHERE T1.gender = 'F' AND T1.birth_date = (SELECT MIN(birth_date) FROM client WHERE gender = 'F') AND T2.A11 = (SELECT MIN(T2.A11) FROM client AS T1 INNER JOIN district AS T2 ON T1.district_id = T2.district_id WHERE T1.gender = 'F' AND T1.birth_date = (SELECT MIN(birth_date) FROM client WHERE gender = 'F'))	SELECT DISTINCT T1.account_id FROM account AS T1 INNER JOIN disp AS T2 ON T1.account_id = T2.account_id INNER JOIN client AS T3 ON T2.client_id = T3.client_id INNER JOIN district AS T4 ON T4.district_id = T1.district_id WHERE T3.birth_date = (SELECT max(birth_date) FROM client WHERE gender = 'F') AND T4.A11 = (SELECT max(A11) FROM district JOIN client on district.district_id = client.district_id WHERE gender = 'F')		0	0
191	How many loan accounts are for pre-payment of duration of 24 months with weekly issuance of statement.	SELECT COUNT(T2.account_id) FROM account AS T1 INNER JOIN loan AS T2 ON T1.account_id = T2.account_id WHERE T2.duration = 24 AND T1.frequency = 'POPLATEK TYDNE'	SELECT COUNT(DISTINCT T1.account_id) FROM loan T1 JOIN account T2 ON T1.account_id = T2.account_id WHERE T1.duration = 24 AND T2.frequency = 'POPLATEK TYDNE';	lack distinct	0	1
193	List all ID and district for clients that can only have the right to issue permanent orders or apply for loans.	SELECT T3.client_id, T2.district_id, T2.A2 FROM account AS T1 INNER JOIN district AS T2 ON T1.district_id = T2.district_id INNER JOIN disp AS T3 ON T1.account_id = T3.account_id WHERE T3.type = 'OWNER'	SELECT client_id, district_id FROM client WHERE client_id IN (SELECT client_id FROM disp WHERE type = 'OWNER');	join -> in-sub	0	1

194	Provide the IDs and age of the client with high level credit card, which is eligible for loans.	SELECT T1.client_id, STRFTIME('%Y', CURRENT_TIMESTAMP) - STRFTIME('%Y', T3.birth_date) FROM disp AS T1 INNER JOIN card AS T2 ON T2.disp_id = T1.disp_id INNER JOIN client AS T3 ON T1.client_id = T3.client_id WHERE T2.type = 'gold' AND T1.type = 'OWNER'	SELECT DISTINCT T1.client_id, STRFTIME('%Y', CURRENT_TIMESTAMP) - STRFTIME('%Y', T3.birth_date) FROM disp AS T1 INNER JOIN card AS T2 ON T2.disp_id = T1.disp_id INNER JOIN client AS T3 ON T1.client_id = T3.client_id WHERE T2.type = 'gold' AND T1.type = 'OWNER'	lack distinct	0	0
195	What is the most common bond type?	SELECT T.bond_type FROM (SELECT bond_type, COUNT(bond_id) FROM bond GROUP BY bond_type ORDER BY COUNT(bond_id) DESC LIMIT 1) AS T	WITH BondCounts AS (SELECT bond_type, COUNT(*) AS count FROM bond GROUP BY bond_type) SELECT bond_type FROM BondCounts WHERE count = (SELECT MAX(count) FROM BondCounts);	limit 1	0	1
205	Identify by their ID the molecules in which there is carbon.	SELECT T.molecule_id FROM atom AS T WHERE T.element = 'c'	SELECT DISTINCT molecule_id FROM atom WHERE element = 'c';	distinct	0	1
206	What elements are in the TR004_8_9 bond atoms?	SELECT DISTINCT T1.element FROM atom AS T1 INNER JOIN connected AS T2 ON T1.atom_id = T2.atom_id WHERE T2.bond_id = 'TR004_8_9'	SELECT DISTINCT A.element FROM atom A JOIN connected C ON A.atom_id = C.atom_id WHERE C.bond_id = 'TR004_8_9' UNION SELECT DISTINCT A.element FROM atom A JOIN connected C ON A.atom_id = C.atom_id2 WHERE C.bond_id = 'TR004_8_9';	semantic error: a bond connects two atoms	0	1
207	What elements are in a double type bond?	SELECT DISTINCT T1.element FROM atom AS T1 INNER JOIN bond AS T2 ON T1.molecule_id = T2.molecule_id INNER JOIN connected AS T3 ON T1.atom_id = T3.atom_id WHERE T2.bond_type = '='	SELECT DISTINCT T3.element FROM bond T1 JOIN connected T2 ON T1.bond_id = T2.bond_id JOIN atom T3 ON T2.atom_id = T3.atom_id OR T2.atom_id2 = T3.atom_id WHERE T1.bond_type = '=';	semantic error: wrong join condition	0	1
208	Which type of label is the most numerous in atoms with hydrogen?	SELECT T.label FROM (SELECT T2.label, COUNT(T2.molecule_id) FROM atom AS T1 INNER JOIN molecule AS T2 ON T1.molecule_id = T2.molecule_id WHERE T1.element = 'h' GROUP BY T2.label ORDER BY COUNT(T2.molecule_id) DESC LIMIT 1) t	SELECT label FROM (SELECT T2.label, rank() over (ORDER BY COUNT(T2.molecule_id) DESC) as rk FROM atom AS T1 INNER JOIN molecule AS T2 ON T1.molecule_id = T2.molecule_id WHERE T1.element = 'h' GROUP BY T2.label) WHERE rk = 1	limit 1	0	0
211	Indicate which atoms are connected in non-carcinogenic type molecules.	SELECT DISTINCT T1.atom_id FROM atom AS T1 INNER JOIN molecule AS T2 ON T1.molecule_id = T2.molecule_id INNER JOIN connected AS T3 ON T1.atom_id = T3.atom_id WHERE T2.label = '-'	SELECT DISTINCT T1.atom_id FROM atom AS T1 INNER JOIN molecule AS T2 ON T1.molecule_id = T2.molecule_id WHERE T2.label = '-'	semantic error: redundant join	0	0
212	Which element is the least numerous in non-carcinogenic molecules?	SELECT T.element FROM (SELECT T1.element, COUNT(DISTINCT T1.molecule_id) FROM atom AS T1 INNER JOIN molecule AS T2 ON T1.molecule_id = T2.molecule_id WHERE T2.label = '-' GROUP BY T1.element ORDER BY COUNT(DISTINCT T1.molecule_id) ASC LIMIT 1) t	SELECT element FROM (SELECT element, COUNT(*) AS num FROM atom JOIN molecule ON atom.molecule_id = molecule.molecule_id WHERE molecule.label = '-' GROUP BY element) WHERE num = (SELECT MIN(num) FROM (SELECT COUNT(*) AS num FROM atom JOIN molecule ON atom.molecule_id = molecule.molecule_id WHERE molecule.label = '-' GROUP BY element))	limit 1	0	1
213	What type of bond is there between the atoms TR004_8 and TR004_20?	SELECT T1.bond_type FROM bond AS T1 INNER JOIN connected AS T2 ON T1.bond_id = T2.bond_id WHERE T2.atom_id = 'TR004_8' AND T2.atom_id2 = 'TR004_20' OR T2.atom_id2 = 'TR004_8' AND T2.atom_id = 'TR004_20'	SELECT b.bond_type FROM bond b WHERE b.bond_id IN (SELECT c.bond_id FROM connected c WHERE (c.atom_id = 'TR004_8' AND c.atom_id2 = 'TR004_20') OR (c.atom_id = 'TR004_20' AND c.atom_id2 = 'TR004_8'));	lack distinct	0	1
214	What type of label is not on molecules with atoms with tin?	SELECT DISTINCT T2.label FROM atom AS T1 INNER JOIN molecule AS T2 ON T1.molecule_id = T2.molecule_id WHERE T1.element != 'sn'	SELECT DISTINCT label FROM molecule EXCEPT SELECT DISTINCT label FROM molecule JOIN atom ON molecule.molecule_id = atom.molecule_id WHERE atom.element = 'sn';	semantic error	0	1
217	Identify all the atoms that are connected to the atoms of the TR181 molecule.	SELECT T2.atom_id, T2.atom_id2 FROM atom AS T1 INNER JOIN connected AS T2 ON T2.atom_id = T1.atom_id WHERE T1.molecule_id = 'TR181'	SELECT DISTINCT atom_id2 FROM connected WHERE atom_id IN (SELECT atom_id FROM atom WHERE molecule_id = 'TR181') UNION SELECT DISTINCT atom_id FROM connected WHERE atom_id2 IN (SELECT atom_id FROM atom WHERE molecule_id = 'TR181')	semantic error: output column	0	1

218	What percentage of carcinogenic-type molecules does not contain fluorine?	SELECT CAST(COUNT(DISTINCT CASE WHEN T1.element <> 'f' THEN T2.molecule_id ELSE NULL END) AS REAL) * 100 / COUNT(DISTINCT T2.molecule_id) FROM atom AS T1 INNER JOIN molecule AS T2 ON T1.molecule_id = T2.molecule_id WHERE T2.label = '+'	SELECT (COUNT(DISTINCT T1.molecule_id) - COUNT(DISTINCT T2.molecule_id)) * 100.0 / COUNT(DISTINCT T1.molecule_id) AS percentage FROM molecule T1 LEFT JOIN atom T2 ON T1.molecule_id = T2.molecule_id AND T2.element = 'f' WHERE T1.label = '+';	join -> left join; semantic error: wrong condition	0	1
223	What are the atom IDs of the bond TR000_2_5?	SELECT T.atom_id FROM connected AS T WHERE T.bond_id = 'TR000_2_5'	SELECT T.atom_id FROM connected AS T WHERE T.bond_id = 'TR000_2_5' UNION SELECT T.atom_id2 FROM connected AS T WHERE T.bond_id = 'TR000_2_5'	semantic error: a bond connects two atoms	1	0
231	Which bond type accounted for the majority of the bonds found in molecule TR010 and show the bond label.	SELECT T.bond_type, T.label FROM (SELECT T1.bond_type, T1.label, COUNT(T1.molecule_id) FROM bond AS T1 WHERE T1.molecule_id = 'TR010' GROUP BY T1.bond_type ORDER BY COUNT(T1.molecule_id) DESC LIMIT 1) AS T	SELECT T.bond_type FROM (SELECT T1.bond_type, rank() over (ORDER BY COUNT(T1.molecule_id) DESC) as rk FROM bond AS T1 WHERE T1.molecule_id = 'TR010' GROUP BY T1.bond_type) AS T WHERE T.rk = 1	syntax error; limit 1	1	0
234	How many bonds which involved atom 12 does molecule TR009 have?	SELECT COUNT(T2.bond_id) FROM bond AS T1 INNER JOIN connected AS T2 ON T1.bond_id = T2.bond_id WHERE T1.molecule_id = 'TR009' AND T2.atom_id = T1.molecule_id '1' AND T2.atom_id2 = T1.molecule_id '2'	SELECT COUNT(DISTINCT bond.bond_id) FROM bond JOIN connected ON bond.bond_id = connected.bond_id WHERE (atom_id = 'TR009_12' or atom_id2 = 'TR009_12') AND molecule_id = 'TR009'	semantic error: wrong condition	1	0
239	How many connections does the atom 19 have?	SELECT COUNT(T.bond_id) FROM connected AS T WHERE SUBSTR(T.atom_id, -2) = '19'	SELECT COUNT(DISTINCT bond_id) FROM connected WHERE atom_id LIKE 'TR%_19' OR atom_id2 LIKE 'TR%_19';	semantic error: a bond connects two atoms	0	1
243	What are the bonds that have phosphorus and nitrogen as their atom elements?	SELECT T2.bond_id FROM atom AS T1 INNER JOIN connected AS T2 ON T1.atom_id = T2.atom_id WHERE T2.bond_id IN (SELECT T3.bond_id FROM connected AS T3 INNER JOIN atom AS T4 ON T3.atom_id = T4.atom_id WHERE T4.element = 'p') AND T1.element = 'n'	SELECT C.bond_id FROM connected C JOIN atom A1 ON C.atom_id = A1.atom_id JOIN atom A2 ON C.atom_id2 = A2.atom_id WHERE A1.element = 'p' AND A2.element = 'n' UNION SELECT C.bond_id FROM connected C JOIN atom A1 ON C.atom_id = A1.atom_id JOIN atom A2 ON C.atom_id2 = A2.atom_id WHERE A2.element = 'p' AND A1.element = 'n'	semantic error: a bond connects two atoms	0	0
245	What is the average number of bonds the atoms with the element iodine have?	SELECT CAST(COUNT(T2.bond_id) AS REAL) / COUNT(T1.atom_id) FROM atom AS T1 INNER JOIN connected AS T2 ON T1.atom_id = T2.atom_id WHERE T1.element = 'i'	SELECT CAST(COUNT(DISTINCT T2.bond_id) AS REAL) / COUNT(DISTINCT T1.atom_id) FROM atom AS T1 LEFT JOIN connected AS T2 ON T1.atom_id = T2.atom_id OR T1.atom_id = T2.atom_id2 WHERE T1.element = 'i';	join -> left join	0	0
246	List the bond type and the bond ID of the atom 45.	SELECT T1.bond_type, T1.bond_id FROM bond AS T1 INNER JOIN connected AS T2 ON T1.bond_id = T2.bond_id WHERE SUBSTR(T2.atom_id, 7, 2) = '45'	SELECT DISTINCT T1.bond_type, T1.bond_id FROM bond AS T1 INNER JOIN connected AS T2 ON T1.bond_id = T2.bond_id WHERE SUBSTR(T2.atom_id, 7, 2) = '45' OR SUBSTR(T2.atom_id2, 7, 2) = '45';	semantic error: a bond connects two atoms	0	0
247	List all the elements of atoms that can not bond with any other atoms.	SELECT DISTINCT T.element FROM atom AS T WHERE T.element NOT IN (SELECT DISTINCT T1.element FROM atom AS T1 INNER JOIN connected AS T2 ON T1.atom_id = T2.atom_id)	SELECT element FROM atom WHERE atom_id NOT IN (SELECT atom_id FROM connected UNION SELECT atom_id2 FROM connected);	semantic error: elements of atoms	0	1
249	What are the elements of the atoms of TR144_8_19?	SELECT T2.element FROM connected AS T1 INNER JOIN atom AS T2 ON T1.atom_id = T2.atom_id WHERE T1.bond_id = 'TR144_8_19'	SELECT DISTINCT T2.element FROM connected T1 JOIN atom T2 ON T1.atom_id = T2.atom_id WHERE T1.bond_id = 'TR144_8_19' UNION SELECT DISTINCT T2.element FROM connected T1 JOIN atom T2 ON T1.atom_id2 = T2.atom_id WHERE T1.bond_id = 'TR144_8_19';	semantic error: a bond connects two atoms	0	1
251	What is the least common element of all carcinogenic molecules?	SELECT T.element FROM (SELECT T2.element, COUNT(DISTINCT T2.molecule_id) FROM molecule AS T1 INNER JOIN atom AS T2 ON T1.molecule_id = T2.molecule_id WHERE T1.label = '+' GROUP BY T2.element ORDER BY COUNT(DISTINCT T2.molecule_id) LIMIT 1) t	SELECT T.element FROM (SELECT T2.element, rank() over (ORDER BY COUNT(DISTINCT T2.molecule_id)) as rk FROM molecule AS T1 INNER JOIN atom AS T2 ON T1.molecule_id = T2.molecule_id WHERE T1.label = '+' GROUP BY T2.element ORDER BY COUNT(DISTINCT T2.molecule_id)) T WHERE T.rk = 1	limit 1	0	0

252	What are the atoms that can bond with the atom that has the element lead?	SELECT T2.atom_id, T2.atom_id2 FROM atom AS T1 INNER JOIN connected AS T2 ON T1.atom_id = T2.atom_id WHERE T1.element = 'pb'	SELECT DISTINCT CASE WHEN T2.atom_id = T1.atom_id THEN T2.atom_id2 ELSE T2.atom_id END AS bonded_atom_id FROM atom T1 JOIN connected T2 ON T1.atom_id = T2.atom_id OR T1.atom_id = T2.atom_id2 WHERE T1.element = 'pb';	semantic error: output column	0	1
253	List the elements of all the triple bonds.	SELECT DISTINCT T3.element FROM bond AS T1 INNER JOIN connected AS T2 ON T1.bond_id = T2.bond_id INNER JOIN atom AS T3 ON T2.atom_id = T3.atom_id WHERE T1.bond_type = '#'	SELECT DISTINCT T3.element FROM bond AS T1 INNER JOIN connected AS T2 ON T1.bond_id = T2.bond_id INNER JOIN atom AS T3 ON T2.atom_id = T3.atom_id OR T2.atom_id2 = T3.atom_id WHERE T1.bond_type = '#'	semantic error: a bond connects two atoms	1	0
257	List down atom id2 for atoms with element sulfur.	SELECT DISTINCT T2.atom_id2 FROM atom AS T1 INNER JOIN connected AS T2 ON T1.atom_id = T2.atom_id WHERE T1.element = 's'	SELECT T2.atom_id2 FROM atom AS T1 JOIN connected AS T2 ON T1.atom_id = T2.atom_id WHERE T1.element = 's';	redundant distinct	0	1
258	What are the bond type for atoms with element Tin?	SELECT DISTINCT T3.bond_type FROM atom AS T1 INNER JOIN connected AS T2 ON T1.atom_id = T2.atom_id INNER JOIN bond AS T3 ON T3.bond_id = T2.bond_id WHERE T1.element = 'sn'	SELECT DISTINCT T3.bond_type FROM atom T1 JOIN connected T2 ON T1.atom_id = T2.atom_id2 OR T1.atom_id = T2.atom_id JOIN bond T3 ON T2.bond_id = T3.bond_id WHERE T1.element = 'sn';	semantic error: a bond connects two atoms	0	0
260	Calculate the total atoms with triple-bond molecules containing the element phosphorus or bromine.	SELECT COUNT(T1.atom_id) FROM atom AS T1 INNER JOIN molecule AS T2 ON T1.molecule_id = T2.molecule_id INNER JOIN bond AS T3 ON T2.molecule_id = T3.molecule_id WHERE T3.bond_type = '#' AND T1.element IN ('p', 'br')	SELECT COUNT(*) FROM atom WHERE molecule_id IN (SELECT molecule_id FROM atom WHERE element IN ('p', 'br')) AND molecule_id IN (SELECT molecule_id FROM bond WHERE bond_type = '#')	semantic error: output column	1	0
263	What is the composition of element chlorine in percentage among the single bond molecules?	SELECT CAST(COUNT(CASE WHEN T.element = 'cl' THEN T.atom_id ELSE NULL END) AS REAL) * 100 / COUNT(T.atom_id) FROM (SELECT T1.atom_id, T1.element FROM atom AS T1 INNER JOIN molecule AS T2 ON T1.molecule_id = T2.molecule_id INNER JOIN bond AS T3 ON T2.molecule_id = T3.molecule_id WHERE T3.bond_type = '-') AS T	SELECT CAST(COUNT(DISTINCT CASE WHEN T.element = 'cl' THEN T.atom_id END) AS REAL) * 100 / COUNT(DISTINCT T.atom_id) FROM (SELECT T1.atom_id, T1.element FROM atom AS T1 INNER JOIN molecule AS T2 ON T1.molecule_id = T2.molecule_id INNER JOIN bond AS T3 ON T2.molecule_id = T3.molecule_id WHERE T3.bond_type = '-') AS T	lack distinct	1	0
268	What are the elements for bond id TR001_10_11?	SELECT T2.element FROM connected AS T1 INNER JOIN atom AS T2 ON T1.atom_id = T2.atom_id WHERE T1.bond_id = 'TR001_10_11'	SELECT DISTINCT element FROM atom WHERE atom_id IN (SELECT atom_id FROM connected WHERE bond_id = 'TR001_10_11' UNION SELECT atom_id2 FROM connected WHERE bond_id = 'TR001_10_11');	semantic error: a bond connects two atoms	0	0
269	How many bond id have element iodine?	SELECT COUNT(T3.bond_id) FROM atom AS T1 INNER JOIN molecule AS T2 ON T1.molecule_id = T2.molecule_id INNER JOIN bond AS T3 ON T2.molecule_id = T3.molecule_id WHERE T1.element = 'i'	SELECT COUNT(*) FROM (SELECT bond_id FROM connected JOIN atom ON connected.atom_id = atom.atom_id AND atom.element = 'i' UNION SELECT bond_id FROM connected JOIN atom ON connected.atom_id2 = atom.atom_id AND atom.element = 'i')	semantic error: wrong join condition	0	0
270	Among the molecules with element Calcium, are they mostly carcinogenic or non carcinogenic? Please show the molecule labels.	SELECT T2.label FROM atom AS T1 INNER JOIN molecule AS T2 ON T1.molecule_id = T2.molecule_id WHERE T1.element = 'ca' GROUP BY T2.label ORDER BY COUNT(T2.label) DESC LIMIT 1	SELECT label FROM (SELECT T2.label, rank() over (ORDER BY COUNT(DISTINCT T2.molecule_id) DESC) as rk FROM atom AS T1 INNER JOIN molecule AS T2 ON T1.molecule_id = T2.molecule_id WHERE T1.element = 'ca' GROUP BY T2.label) WHERE rk = 1	limit 1; semantic error: wrong order by	1	0
271	Does bond id TR001_1_8 have both element of chlorine and carbon? Answer by 'YES' or 'NO'.	SELECT T2.bond_id, T2.atom_id2, T1.element AS flag_have_CaCl FROM atom AS T1 INNER JOIN connected AS T2 ON T2.atom_id = T1.atom_id WHERE T2.bond_id = 'TR001_1_8' AND (T1.element = 'c1' OR T1.element = 'c')	SELECT CASE WHEN COUNT(DISTINCT T2.element) = 2 THEN 'YES' ELSE 'NO' END FROM connected T1 JOIN atom T2 ON T1.atom_id = T2.atom_id OR T1.atom_id2 = T2.atom_id WHERE T1.bond_id = 'TR001_1_8' AND T2.element IN ('cl', 'c');	semantic error: wrong condition	0	1
277	What are the toxicology elements associated with bond ID TR000_1_2?	SELECT T1.element FROM atom AS T1 INNER JOIN connected AS T2 ON T1.atom_id = T2.atom_id WHERE T2.bond_id = 'TR000_1_2'	SELECT DISTINCT T2.element FROM connected T1 JOIN atom T2 ON T1.atom_id = T2.atom_id WHERE T1.bond_id = 'TR000_1_2' UNION SELECT DISTINCT T2.element FROM connected T1 JOIN atom T2 ON T1.atom_id2 = T2.atom_id WHERE T1.bond_id = 'TR000_1_2';	semantic error: a bond connects two atoms	0	1

280	Enumerate the bond ID of triple bond type molecules and tell me if they are carcinogenic or not by showing the molecule labels.	SELECT DISTINCT T1.bond_id, T2.label FROM bond AS T1 INNER JOIN molecule AS T2 ON T1.molecule_id = T2.molecule_id WHERE T1.bond_type = '#'	SELECT T1.bond_id, T2.label FROM bond AS T1 INNER JOIN molecule AS T2 ON T1.molecule_id = T2.molecule_id WHERE T1.molecule_id IN (SELECT T3.molecule_id FROM bond AS T3 WHERE T3.bond_type = '#')	semantic error: wrong condition	1	0
283	Identify whether the chemical compound that contains Calcium is carcinogenic.	SELECT T2.label AS flag_carcinogenic FROM atom AS T1 INNER JOIN molecule AS T2 ON T1.molecule_id = T2.molecule_id WHERE T1.element = 'ca'	SELECT label FROM molecule WHERE molecule_id IN (SELECT molecule_id FROM atom WHERE element = 'ca')	join -> in-sub	0	0
285	Name chemical elements that form a bond TR001_10_11.	SELECT T1.element FROM atom AS T1 INNER JOIN connected AS T2 ON T1.atom_id = T2.atom_id INNER JOIN bond AS T3 ON T2.bond_id = T3.bond_id WHERE T3.bond_id = 'TR001_10_11'	SELECT DISTINCT T1.element FROM atom AS T1 INNER JOIN connected AS T2 ON T1.atom_id = T2.atom_id OR T1.atom_id = T2.atom_id2 INNER JOIN bond AS T3 ON T2.bond_id = T3.bond_id WHERE T3.bond_id = 'TR001_10_11'	semantic error: a bond connects two atoms	0	0
298	Calculate the percentage of molecules containing carcinogenic compounds that element is hydrogen.	SELECT CAST(COUNT(CASE WHEN T1.element = 'h' AND T2.label = '+' THEN T2.molecule_id ELSE NULL END) AS REAL) * 100 / COUNT(DISTINCT T2.molecule_id) FROM atom AS T1 INNER JOIN molecule AS T2 ON T1.molecule_id = T2.molecule_id	SELECT CAST(COUNT(DISTINCT CASE WHEN T1.element = 'h' AND T2.label = '+' THEN T2.molecule_id END) AS REAL) * 100 / COUNT(DISTINCT T2.molecule_id) FROM atom AS T1 INNER JOIN molecule AS T2 ON T1.molecule_id = T2.molecule_id	lack distinct	0	0
302	Name the elements that comprise the atoms of bond TR001_2_4.	SELECT DISTINCT T1.element FROM atom AS T1 INNER JOIN connected AS T2 ON T1.atom_id = T2.atom_id WHERE T2.bond_id = 'TR001_2_4'	SELECT DISTINCT element FROM atom WHERE atom_id IN (SELECT atom_id FROM connected WHERE bond_id = 'TR001_2_4' UNION SELECT atom_id2 FROM connected WHERE bond_id = 'TR001_2_4');	semantic error: a bond connects two atoms	0	1
307	Name the atoms' elements that form bond TR000_2_3.	SELECT T2.element FROM connected AS T1 INNER JOIN atom AS T2 ON T1.atom_id = T2.atom_id WHERE T1.bond_id = 'TR000_2_3'	SELECT DISTINCT T2.element FROM connected AS T1 INNER JOIN atom AS T2 ON T1.atom_id = T2.atom_id OR T1.atom_id2 = T2.atom_id WHERE T1.bond_id = 'TR000_2_3'	semantic error: a bond connects two atoms	0	0
308	How many bonds are created by bonding atoms with chlorine element?	SELECT COUNT(T1.bond_id) FROM connected AS T1 INNER JOIN atom AS T2 ON T1.atom_id = T2.atom_id WHERE T2.element = 'cl'	SELECT COUNT(DISTINCT bond_id) FROM connected WHERE atom_id IN (SELECT atom_id FROM atom WHERE element = 'cl') OR atom_id2 IN (SELECT atom_id FROM atom WHERE element = 'cl');	semantic error: a bond connects two atoms	0	1
309	List out the atom id that belongs to the TR346 molecule and how many bond type can be created by this molecule?	SELECT T1.atom_id, COUNT(DISTINCT T2.bond_type), T1.molecule_id FROM atom AS T1 INNER JOIN bond AS T2 ON T1.molecule_id = T2.molecule_id WHERE T1.molecule_id = 'TR000' GROUP BY T1.atom_id, T2.bond_type	SELECT A.atom_id, COUNT(DISTINCT B.bond_type) AS bond_types FROM atom A JOIN bond B ON A.molecule_id = B.molecule_id WHERE A.molecule_id = 'TR346' GROUP BY A.atom_id;	semantic error: wrong condition	0	1
310	How many molecules have a double bond type and among these molecule, how many are labeled as carcinogenic compound?	SELECT COUNT(DISTINCT T2.molecule_id), SUM(CASE WHEN T2.label = '+' THEN 1 ELSE 0 END) FROM bond AS T1 INNER JOIN molecule AS T2 ON T1.molecule_id = T2.molecule_id WHERE T1.bond_type = '='	SELECT COUNT(DISTINCT T2.molecule_id), COUNT(DISTINCT CASE WHEN T2.label = '+' THEN T2.molecule_id END) FROM bond AS T1 INNER JOIN molecule AS T2 ON T1.molecule_id = T2.molecule_id WHERE T1.bond_type = '='	lack distinct	0	0
311	How many molecules without sulphur element is not having double bond?	SELECT COUNT(DISTINCT T1.molecule_id) FROM atom AS T1 INNER JOIN bond AS T2 ON T1.molecule_id = T2.molecule_id WHERE T1.element <> 's' AND T2.bond_type <> '='	SELECT COUNT(DISTINCT T1.molecule_id) FROM molecule T1 WHERE T1.molecule_id NOT IN (SELECT T2.molecule_id FROM atom T2 WHERE T2.element = 's') AND T1.molecule_id NOT IN (SELECT T3.molecule_id FROM bond T3 WHERE T3.bond_type = '=')	semantic error: wrong condition	0	1

317	Calculate the percentage of carcinogenic molecules which contain the Chlorine element.	SELECT COUNT(CASE WHEN T2.label = '+' AND T1.element = 'cl' THEN T2.molecule_id ELSE NULL END) * 100 / COUNT(T2.molecule_id) FROM atom AS T1 INNER JOIN molecule AS T2 ON T1.molecule_id = T2.molecule_id	SELECT COUNT(DISTINCT CASE WHEN T2.label = '+' AND T1.element = 'cl' THEN T2.molecule_id END) * 100 / COUNT(DISTINCT T2.molecule_id) FROM atom AS T1 INNER JOIN molecule AS T2 ON T1.molecule_id = T2.molecule_id	lack distinct	0	0
318	What is the molecule id of bond id TR001_1_7?	SELECT DISTINCT T1.molecule_id FROM atom AS T1 INNER JOIN connected AS T2 ON T1.atom_id = T2.atom_id WHERE T2.bond_id = 'TR001_1_7'	SELECT molecule_id FROM bond WHERE bond_id = 'TR001_1_7';	semantic error: wrong condition	0	1
319	How many elements are contained in bond_id TR001_3_4?	SELECT COUNT(DISTINCT T1.element) FROM atom AS T1 INNER JOIN connected AS T2 ON T1.atom_id = T2.atom_id WHERE T2.bond_id = 'TR001_3_4'	SELECT COUNT(DISTINCT T1.element) FROM atom AS T1 INNER JOIN connected AS T2 ON T1.atom_id = T2.atom_id OR T1.atom_id = T2.atom_id2 WHERE T2.bond_id = 'TR001_3_4'	semantic error: wrong condition	0	0
320	What is the type of the bond which is presenting the connection between two atoms TR000_1 and TR000_2?	SELECT T1.bond_type FROM bond AS T1 INNER JOIN connected AS T2 ON T1.bond_id = T2.bond_id WHERE T2.atom_id = 'TR000_1' AND T2.atom_id2 = 'TR000_2'	SELECT T1.bond_type FROM bond AS T1 WHERE T1.bond_id IN (SELECT T2.bond_id FROM connected AS T2 WHERE (T2.atom_id = 'TR000_1' AND T2.atom_id2 = 'TR000_2') OR (T2.atom_id2 = 'TR000_1' AND T2.atom_id = 'TR000_2'))	semantic error: a bond connects two atoms	1	0
321	What is the molecule of atom id "TR000_2" and atom id 2 "TR000_4"?	SELECT T1.molecule_id FROM bond AS T1 INNER JOIN connected AS T2 ON T1.bond_id = T2.bond_id WHERE T2.atom_id = 'TR000_2' AND T2.atom_id2 = 'TR000_4'	SELECT molecule_id FROM atom WHERE atom_id IN ('TR000_2', 'TR000_4');		0	1
326	Which molecule consisted of Sulphur atom with double bond?	SELECT DISTINCT T1.molecule_id FROM atom AS T1 INNER JOIN bond AS T2 ON T1.molecule_id = T2.molecule_id WHERE T1.element = 's' AND T2.bond_type = '='	SELECT T1.molecule_id FROM atom AS T1 INNER JOIN connected AS T2 ON T1.atom_id = T2.atom_id INNER JOIN bond AS T3 ON T2.bond_id = T3.bond_id WHERE T1.element = 's' AND T3.bond_type = '=' UNION SELECT T1.molecule_id FROM atom AS T1 INNER JOIN connected AS T2 ON T1.atom_id = T2.atom_id2 INNER JOIN bond AS T3 ON T2.bond_id = T3.bond_id WHERE T1.element = 's' AND T3.bond_type = '='	semantic error: wrong join condition	1	0
328	List all the elements with double bond, consisted in molecule TR024.	SELECT T1.element FROM atom AS T1 INNER JOIN bond AS T2 ON T1.molecule_id = T2.molecule_id WHERE T1.molecule_id = 'TR024' AND T2.bond_type = '='	SELECT DISTINCT T4.element FROM molecule T1 JOIN bond T2 ON T1.molecule_id = T2.molecule_id JOIN connected T3 ON T2.bond_id = T3.bond_id JOIN atom T4 ON T3.atom_id = T4.atom_id OR T3.atom_id2 = T4.atom_id WHERE T1.molecule_id = 'TR024' AND T2.bond_type = '=';	lack distinct; semantic error: wrong join condition	0	0
329	Which carcinogenic molecule have the highest number of atoms consisted in it?	SELECT T.molecule_id FROM (SELECT T2.molecule_id, COUNT(T1.atom_id) FROM atom AS T1 INNER JOIN molecule AS T2 ON T1.molecule_id = T2.molecule_id WHERE T2.label = '+' GROUP BY T2.molecule_id ORDER BY COUNT(T1.atom_id) DESC LIMIT 1) t	SELECT T.molecule_id FROM (SELECT T2.molecule_id, rank() over (ORDER BY COUNT(T1.atom_id) DESC) as rk FROM atom AS T1 INNER JOIN molecule AS T2 ON T1.molecule_id = T2.molecule_id WHERE T2.label = '+' GROUP BY T2.molecule_id) T WHERE T.rk = 1	limit 1	0	0
330	Calculate the percentage of carcinogenic molecules with triple bonded Hydrogen atoms.	SELECT CAST(SUM(CASE WHEN T1.label = '+' THEN 1 ELSE 0 END) AS REAL) * 100 / COUNT(DISTINCT T1.molecule_id) FROM molecule AS T1 INNER JOIN atom AS T2 ON T1.molecule_id = T2.molecule_id INNER JOIN bond AS T3 ON T1.molecule_id = T3.molecule_id WHERE T3.bond_type = '#' AND T2.element = 'h'	SELECT (CAST(COUNT(DISTINCT T1.molecule_id) AS REAL) / (SELECT COUNT(*) FROM molecule WHERE label = '+')) * 100.0 AS percentage FROM molecule T1 JOIN atom T2 ON T1.molecule_id = T2.molecule_id JOIN connected T3 ON T2.atom_id = T3.atom_id OR T2.atom_id = T3.atom_id2 JOIN bond T4 ON T3.bond_id = T4.bond_id WHERE T1.label = '+' AND T2.element = 'h' AND T4.bond_type = '#';	lack distinct; semantic error: wrong join condition	0	0

335	What is the total number of molecules with double bonded oxygen?	SELECT COUNT(DISTINCT T1.molecule_id) FROM atom AS T1 INNER JOIN bond AS T2 ON T1.molecule_id = T2.molecule_id WHERE T2.bond_type = '=' AND T1.element = 'o'	SELECT COUNT(DISTINCT T1.molecule_id) FROM molecule T1 JOIN atom T2 ON T1.molecule_id = T2.molecule_id JOIN connected T3 ON T2.atom_id = T3.atom_id OR T2.atom_id = T3.atom_id2 JOIN bond T4 ON T3.bond_id = T4.bond_id WHERE T2.element = 'o' AND T4.bond_type = '=';	semantic error: wrong join condition	1	0
338	What is the atom ID of double bonded carbon in TR012 molecule?	SELECT T1.atom_id FROM atom AS T1 INNER JOIN molecule AS T2 ON T1.molecule_id = T2.molecule_id INNER JOIN bond AS T3 ON T2.molecule_id = T3.molecule_id WHERE T2.molecule_id = 'TR012' AND T3.bond_type = '=' AND T1.element = 'c'	SELECT DISTINCT T1.atom_id FROM atom AS T1 INNER JOIN molecule AS T2 ON T1.molecule_id = T2.molecule_id INNER JOIN connected AS T3 ON T1.atom_id = T3.atom_id OR T1.atom_id = T3.atom_id2 INNER JOIN bond AS T4 ON T3.bond_id = T4.bond_id WHERE T2.molecule_id = 'TR012' AND T4.bond_type = '=' AND T1.element = 'c';	semantic error: wrong join condition	1	0
343	Name all cards with 2015 frame style ranking below 100 on EDHRec.	SELECT id FROM cards WHERE edhrecRank < 100 AND frameVersion = 2015	SELECT name FROM cards WHERE frameVersion = '2015' AND edhrecRank < 100;	output	0	1
345	For artifact type of cards that do not have multiple faces on the same card, state its legalities status for vintage play format.	SELECT DISTINCT T2.status FROM cards AS T1 INNER JOIN legalities AS T2 ON T1.uuid = T2.uuid WHERE T1.type = 'Artifact' AND T2.format = 'vintage' AND T1.side IS NULL	SELECT status FROM legalities WHERE uuid IN (SELECT uuid FROM cards WHERE type = 'Artifact' AND side IS NULL) AND format = 'vintage'	join -> in-sub	1	0
346	List all the card id and artist with unknown power which are legal for commander play format.	SELECT T1.id, T1.artist FROM cards AS T1 INNER JOIN legalities AS T2 ON T1.uuid = T2.uuid WHERE T2.status = 'Legal' AND T2.format = 'commander' AND (T1.power IS NULL OR T1.power = '*')	SELECT id, artist FROM cards WHERE uuid IN (SELECT uuid FROM legalities WHERE format = 'commander' AND status = 'Legal') AND (power = '*' OR power IS NULL)	join -> in-sub	0	1
349	Name the card and artist with the most ruling information. Also state if the card is a promotional printing.	SELECT T1.name, T1.artist, T1.isPromo FROM cards AS T1 INNER JOIN rulings AS T2 ON T1.uuid = T2.uuid WHERE T1.isPromo = 1 AND T1.artist = (SELECT artist FROM cards WHERE isPromo = 1 GROUP BY artist HAVING COUNT(DISTINCT uuid) = (SELECT MAX(count_uuid) FROM (SELECT COUNT(DISTINCT uuid) AS count_uuid FROM cards WHERE isPromo = 1 GROUP BY artist))) LIMIT 1	SELECT T1.name, T1.artist, T1.isPromo FROM cards T1 JOIN (SELECT uuid, COUNT(uuid) AS ruling_count FROM rulings GROUP BY uuid) T2 ON T1.uuid = T2.uuid WHERE T2.ruling_count = (SELECT MAX(ruling_count) FROM (SELECT COUNT(uuid) AS ruling_count FROM rulings GROUP BY uuid))	limit 1;	0	1
350	State the alternative languages available for card named Annul numbered 29.	SELECT T2.language FROM cards AS T1 INNER JOIN foreign_data AS T2 ON T1.uuid = T2.uuid WHERE T1.name = 'Annul' AND T1.number = 29	SELECT T2.language FROM cards AS T1 INNER JOIN foreign_data AS T2 ON T1.uuid = T2.uuid WHERE T1.name = 'annul' AND T1.number = 29	str	1	0
351	Name all the cards which have alternative language in Japanese.	SELECT T1.name FROM cards AS T1 INNER JOIN foreign_data AS T2 ON T1.uuid = T2.uuid WHERE T2.language = 'Japanese'	SELECT name FROM cards WHERE uuid IN (SELECT uuid FROM foreign_data WHERE language = 'Japanese');	JOIN -> in-sub	0	1
352	Calculate the percentage of the cards available in Chinese Simplified.	SELECT CAST(SUM(CASE WHEN T2.language = 'Chinese Simplified' THEN 1 ELSE 0 END) AS REAL) * 100 / COUNT(T1.id) FROM cards AS T1 INNER JOIN foreign_data AS T2 ON T1.uuid = T2.uuid	SELECT CAST(COUNT(DISTINCT CASE WHEN T2.language = 'Chinese Simplified' THEN T1.id END) AS REAL) * 100 / COUNT(DISTINCT T1.id) FROM cards AS T1 LEFT JOIN foreign_data AS T2 ON T1.uuid = T2.uuid	lack distinct; join -> left join	1	0
353	List all the sets available in Italian translation. State the total number of cards per set.	SELECT T1.name, T1.totalSetSize FROM sets AS T1 INNER JOIN set_translations AS T2 ON T1.code = T2.setCode WHERE T2.language = 'Italian'	SELECT T1.name, T1.totalSetSize FROM sets AS T1 WHERE T1.code IN (SELECT T2.setCode FROM set_translations AS T2 WHERE T2.language = 'Italian');	JOIN -> in-sub	1	0

354	How many types of cards does the artist Aaron Boyd illustrated about card art?	SELECT COUNT(type) FROM cards WHERE artist = 'Aaron Boyd'	SELECT COUNT(DISTINCT types) FROM cards WHERE artist = 'Aaron Boyd' GROUP BY artist;	lack distinct	0	1
355	What is the keyword found on card 'Angel of Mercy'?	SELECT DISTINCT keywords FROM cards WHERE name = 'Angel of Mercy'	SELECT keywords FROM cards WHERE name = 'Angel of Mercy'	redundant distinct	1	0
358	What is the border color of card "Ancestor's Chosen"?	SELECT DISTINCT borderColor FROM cards WHERE name = 'Ancestor's Chosen'	SELECT borderColor FROM cards WHERE name = 'Ancestor's Chosen'	redundant distinct	1	0
360	cards are not directly linked to language but through table 'set'. you need to add set in covered table & rephrase your question What are the languages available for the set that card 'Angel of Mercy' is in?	SELECT language FROM set_translations WHERE id IN (SELECT id FROM cards WHERE name = 'Angel of Mercy')	SELECT DISTINCT T2.language FROM cards T1 JOIN set_translations T2 ON T1.setCode = T2.setCode WHERE T1.name = 'Angel of Mercy';	column error: in-sub condition	1	0
367	Please provide the names of the artists who illustrated the card art in Phyrexian.	SELECT T1.artist FROM cards AS T1 INNER JOIN foreign_data AS T2 ON T1.uuid = T2.uuid WHERE T2.language = 'Phyrexian'	SELECT DISTINCT T1.artist FROM cards T1 JOIN foreign_data T2 ON T1.uuid = T2.uuid WHERE T2.language = 'Phyrexian';	lack distinct	0	0
369	How many cards that illustrated in German have been reprinted?	SELECT COUNT(T1.id) FROM cards AS T1 INNER JOIN foreign_data AS T2 ON T1.uuid = T2.uuid WHERE T2.language = 'German' AND T1.isReprint = 1	SELECT COUNT(DISTINCT T1.uuid) FROM cards AS T1 JOIN foreign_data AS T2 ON T1.uuid = T2.uuid WHERE T1.isReprint = 1 AND T2.language = 'German';	lack distinct	0	1
370	How many borderless cards are illustrated in Russian?	SELECT COUNT(T1.id) FROM cards AS T1 INNER JOIN foreign_data AS T2 ON T1.uuid = T2.uuid WHERE T1.borderColor = 'borderless' AND T2.language = 'Russian'	SELECT COUNT(DISTINCT T1.id) FROM cards T1 JOIN foreign_data T2 ON T1.uuid = T2.uuid WHERE T1.borderColor = 'borderless' AND T2.language = 'Russian';	lack distinct	0	1
371	What is the percentage of cards whose language is French among the Story Spotlight cards?	SELECT CAST(SUM(CASE WHEN T2.language = 'French' THEN 1 ELSE 0 END) AS REAL) * 100 / COUNT(T1.id) FROM cards AS T1 INNER JOIN foreign_data AS T2 ON T1.uuid = T2.uuid WHERE T1.isStorySpotlight = 1	SELECT (COUNT(DISTINCT cards.id) * 100.0 / (SELECT COUNT(*) FROM cards WHERE isStorySpotlight = 1)) AS percentage FROM cards JOIN foreign_data ON cards.uuid = foreign_data.uuid WHERE cards.isStorySpotlight = 1 AND foreign_data.language = 'French';	join -> left join; lack distinct	0	0
373	Name the cards that were illustrated by Aaron Boyd.	SELECT DISTINCT name FROM cards WHERE artist = 'Aaron Boyd'	SELECT name FROM cards WHERE artist = 'Aaron Boyd'	redundant distinct	1	0
376	What are the card layout of cards with keyword of flying?	SELECT layout FROM cards WHERE keywords = 'Flying'	SELECT layout FROM cards WHERE keywords = 'flying'	str	0	0
381	List down the name of artists for cards in Chinese Simplified.	SELECT T1.artist FROM cards AS T1 INNER JOIN foreign_data AS T2 ON T1.uuid = T2.uuid WHERE T2.language = 'Chinese Simplified'	SELECT artist FROM cards WHERE uuid IN (SELECT uuid FROM foreign_data WHERE language = 'Chinese Simplified');	join -> in-sub	0	1
382	What are the cards that only available in paper and Japanese language?	SELECT T1.name FROM cards AS T1 INNER JOIN foreign_data AS T2 ON T1.uuid = T2.uuid WHERE T1.availability = 'paper' AND T2.language = 'Japanese'	SELECT name FROM cards WHERE uuid IN (SELECT uuid FROM foreign_data WHERE language = 'Japanese') AND availability = 'paper';	join -> in-sub	1	0
383	How many of the banned cards are white border?	SELECT COUNT(T1.id) FROM cards AS T1 INNER JOIN legalities AS T2 ON T1.uuid = T2.uuid WHERE T2.status = 'Banned' AND T1.borderColor = 'white'	SELECT COUNT(DISTINCT T1.id) FROM cards AS T1 INNER JOIN legalities AS T2 ON T1.uuid = T2.uuid WHERE T2.status = 'Banned' AND T1.borderColor = 'white'	lack distinct	1	0

384	List down the uuid for legacy cards and the foreign language of these cards.	SELECT T1.uuid, T3.language FROM cards AS T1 INNER JOIN legalities AS T2 ON T1.uuid = T2.uuid INNER JOIN foreign_data AS T3 ON T1.uuid = T3.uuid WHERE T2.format = 'legacy'	SELECT T1.uuid, T2.language FROM cards AS T1 INNER JOIN foreign_data AS T2 ON T1.uuid = T2.uuid WHERE T1.uuid IN (SELECT T3.uuid FROM legalities AS T3 WHERE T3.format = 'legacy');	join -> in-sub	1	0
386	How many cards are having future frame version and what are the legality status of these cards?	SELECT COUNT(T1.id) FROM cards AS T1 INNER JOIN legalities AS T2 ON T1.uuid = T2.uuid WHERE T1.frameVersion = 'future'	SELECT COUNT(DISTINCT T1.id) FROM cards AS T1 INNER JOIN legalities AS T2 ON T1.uuid = T2.uuid WHERE T1.frameVersion = 'future'	lack distinct	0	0
387	What are the cards for set OGW? State the colour for these cards.	SELECT id, colors FROM cards WHERE id IN (SELECT id FROM set_translations WHERE setCode = 'OGW')	SELECT colors FROM cards WHERE setCode = 'OGW';	semantic error: cards for set OGW	0	1
388	What are the cards in set 10E with converted mana of 5 have translation and what are the languages?	SELECT id, language FROM set_translations WHERE id = (SELECT id FROM cards WHERE convertedManaCost = 5) AND setCode = '10E'	SELECT cards.id, set_translations.language FROM cards JOIN set_translations ON cards.setCode = set_translations.setCode WHERE convertedManaCost = 5 AND cards.setCode = '10E'	semantic error: cards in set 10E	1	0
389	List down the name of cards with original types of Creature - Elf and the date of rulings for these cards.	SELECT T1.id, T2.date FROM cards AS T1 INNER JOIN rulings AS T2 ON T1.uuid = T2.uuid WHERE T1.originalType = 'Creature - Elf'	SELECT T1.name, T2.date FROM cards AS T1 JOIN rulings AS T2 ON T1.uuid = T2.uuid WHERE T1.originalType = 'Creature - Elf';	semantic error: output column	0	1
391	Among the Artifact cards, which are black color and comes with foreign language translation?	SELECT DISTINCT T1.name FROM cards AS T1 INNER JOIN foreign_data AS T2 ON T1.uuid = T2.uuid WHERE T1.originalType = 'Artifact' AND T1.colors = 'B'	SELECT T1.name FROM cards AS T1 WHERE T1.originalType = 'Artifact' AND T1.colors = 'B' AND T1.uuid IN (SELECT T2.uuid FROM foreign_data AS T2)	join -> in-sub	1	0
392	Pick 3 cards with rarity of uncommon, list down name these cards according to ascending order of it's ruling date.	SELECT DISTINCT T1.name FROM cards AS T1 INNER JOIN rulings AS T2 ON T1.uuid = T2.uuid WHERE T1.rarity = 'uncommon' ORDER BY T2.date ASC LIMIT 3	SELECT name FROM (SELECT T1.name, rank() over (ORDER BY min(T2.date) ASC) as rk FROM cards AS T1 INNER JOIN rulings AS T2 ON T1.uuid = T2.uuid WHERE T1.rarity = 'uncommon' GROUP BY T1.uuid) WHERE rk <= 3;	limit n	1	0
399	Lists all types of cards available in arena.	SELECT DISTINCT subtypes, supertypes FROM cards WHERE availability = 'arena' AND subtypes IS NOT NULL AND supertypes IS NOT NULL	SELECT subtypes, supertypes FROM cards WHERE availability = 'arena' AND subtypes IS NOT NULL AND supertypes IS NOT NULL	redundant distinct	1	0
403	Calculate the percentage of cards in Spanish. List them by name.	SELECT (SELECT CAST(SUM(CASE WHEN language = 'Spanish' THEN 1 ELSE 0 END) AS REAL) * 100 / COUNT(*) FROM foreign_data), name FROM foreign_data WHERE language = 'Spanish'	SELECT (SELECT CAST(COUNT(DISTINCT CASE WHEN language = 'Spanish' THEN uuid END) AS REAL) * 100 / (SELECT COUNT(*) FROM cards) FROM foreign_data), name FROM foreign_data WHERE language = 'Spanish';	semantic error: should consider cards without foreign data	0	0
405	How many Brazilian Portuguese translated sets are inside the Commander block?	SELECT COUNT(T1.id) FROM sets AS T1 INNER JOIN set_translations AS T2 ON T1.code = T2.setCode WHERE T2.language = 'Portuguese (Brazil)' AND T1.block = 'Commander'	SELECT COUNT(DISTINCT T1.id) FROM sets AS T1 INNER JOIN set_translations AS T2 ON T1.code = T2.setCode WHERE T2.language = 'Portuguese (Brazil)' AND T1.block = 'Commander'	lack distinct	1	0
406	Lists by ID all Creature-type cards with legal status.	SELECT T1.id FROM cards AS T1 INNER JOIN rulings AS T2 ON T1.uuid = T2.uuid INNER JOIN legalities AS T3 ON T1.uuid = T3.uuid WHERE T3.status = 'Legal' AND T1.types = 'Creature'	SELECT id FROM cards WHERE uuid IN (SELECT uuid FROM legalities WHERE status = 'Legal') AND types = 'Creature';		0	0
408	How many unknown power cards contain info about the triggered ability	SELECT T2.text FROM cards AS T1 INNER JOIN rulings AS T2 ON T1.uuid = T2.uuid WHERE (T1.power IS NULL OR T1.power = '') AND T2.text LIKE '%triggered ability%'	SELECT COUNT(DISTINCT T1.uuid) FROM cards AS T1 INNER JOIN rulings AS T2 ON T1.uuid = T2.uuid WHERE (T1.power IS NULL OR T1.power = '') AND T2.text LIKE '%triggered ability%'	semantic error: output column	1	0

409	Indicates the number of cards with pre-modern format, ruling text "This is a triggered mana ability." that do not have multiple faces.	SELECT COUNT(T1.id) FROM cards AS T1 INNER JOIN legalities AS T2 ON T1.uuid = T2.uuid INNER JOIN rulings AS T3 ON T1.uuid = T3.uuid WHERE T2.format = 'pre-modern' AND T3.text = 'This is a triggered mana ability.' AND T1.Side IS NULL	SELECT COUNT(DISTINCT T1.id) FROM cards AS T1 INNER JOIN legalities AS T2 ON T1.uuid = T2.uuid INNER JOIN rulings AS T3 ON T1.uuid = T3.uuid WHERE T2.format = 'premodern' AND T3.text = 'This is a triggered mana ability.' AND T1.Side IS NULL	lack distinct	1	0
410	Is there any card from Erica Yang artist in pauper format and available in paper? If so, indicate its ID.	SELECT T1.id FROM cards AS T1 INNER JOIN legalities AS T2 ON T1.uuid = T2.uuid WHERE T1.artist = 'Erica Yang' AND T2.format = 'pauper' AND T1.availability = 'paper'	SELECT DISTINCT T1.id FROM cards AS T1 INNER JOIN legalities AS T2 ON T1.uuid = T2.uuid WHERE T1.artist = 'Erica Yang' AND T2.format = 'pauper' AND T1.availability = 'paper'	lack distinct	0	0
411	To which artist does the card with the text "Das perfekte Gegenmittel zu einer dichten Formation" belong?	SELECT DISTINCT T1.artist FROM cards AS T1 INNER JOIN foreign_data AS T2 ON T1.uuid = T2.uuid WHERE T2.flavorText LIKE '%DAS perfekte Gegenmittel zu einer dichten Formation%'	SELECT artist FROM cards WHERE id IN (SELECT T1.id FROM cards AS T1 INNER JOIN foreign_data AS T2 ON T1.uuid = T2.uuid WHERE T2.flavorText LIKE '%Das perfekte Gegenmittel zu einer dichten Formation%')	str; join -> in-sub	1	0
414	What language is the set of 180 cards that belongs to the Ravnica block translated into?	SELECT T2.language FROM sets AS T1 INNER JOIN set_translations AS T2 ON T1.code = T2.setCode WHERE T1.block = 'Ravnica' AND T1.baseSetSize = 180	SELECT DISTINCT T2.language FROM sets AS T1 INNER JOIN set_translations AS T2 ON T1.code = T2.setCode WHERE T1.block = 'Ravnica' AND T1.baseSetSize = 180	lack distinct	1	0
415	What percentage of cards with format commander and legal status do not have a content warning?	SELECT CAST(SUM(CASE WHEN T1.hasContentWarning = 0 THEN 1 ELSE 0 END) AS REAL) * 100 / COUNT(T1.id) FROM cards AS T1 INNER JOIN legalities AS T2 ON T1.uuid = T2.uuid WHERE T2.format = 'commander' AND T2.status = 'Legal'	SELECT CAST(COUNT(DISTINCT CASE WHEN T1.hasContentWarning = 0 THEN T1.id END) AS REAL) * 100 / COUNT(DISTINCT T1.id) FROM cards AS T1 LEFT JOIN legalities AS T2 ON T1.uuid = T2.uuid WHERE T2.format = 'commander' AND T2.status = 'Legal'	lack distinct; join -> left join	1	0
416	What percentage of cards without power are in French?	SELECT CAST(SUM(CASE WHEN T2.language = 'French' THEN 1 ELSE 0 END) AS REAL) * 100 / COUNT(T1.id) FROM cards AS T1 INNER JOIN foreign_data AS T2 ON T1.uuid = T2.uuid WHERE T1.power IS NULL OR T1.power = ''	SELECT CAST(COUNT(DISTINCT CASE WHEN T2.language = 'French' THEN T1.id END) AS REAL) * 100 / COUNT(DISTINCT T1.id) FROM cards AS T1 LEFT JOIN foreign_data AS T2 ON T1.uuid = T2.uuid WHERE T1.power IS NULL OR T1.power = '';	lack distinct; join -> left join	0	0
417	What percentage of Japanese translated sets are expansion sets?	SELECT CAST(SUM(CASE WHEN T2.language = 'Japanese' THEN 1 ELSE 0 END) AS REAL) * 100 / COUNT(T1.id) FROM sets AS T1 INNER JOIN set_translations AS T2 ON T1.code = T2.setCode WHERE T1.type = 'expansion'	SELECT (COUNT(DISTINCT T2.id) * 100.0 / (SELECT COUNT(DISTINCT T2.id) FROM set_translations T1 INNER JOIN sets T2 ON T1.setCode = T2.code WHERE T1.language = 'Japanese')) AS percentage FROM set_translations T1 INNER JOIN sets T2 ON T1.setCode = T2.code WHERE T1.language = 'Japanese' AND T2.type = 'expansion';	semantic error	0	0
418	What kind of printing is on the card that Daren Bader created?	SELECT DISTINCT availability FROM cards WHERE artist = 'Daren Bader'	SELECT availability FROM cards WHERE artist = 'Daren Bader'	redundant distinct	1	0
421	Please list top three unknown power cards that have promotional types for arena league in alphabetical order.	SELECT name FROM cards WHERE (power IS NULL OR power LIKE '%*%') AND promoTypes = 'arenaleague' ORDER BY name LIMIT 3	SELECT name FROM (SELECT name, rank() over (ORDER BY name) as rk FROM cards WHERE (power IS NULL OR power LIKE '%*%') AND promoTypes = 'arenaleague') WHERE rk <= 3	limit n	1	0
423	Please provide the ids of top three powerful pairs of Kingdom Foil and Kingdom Cards sorted by Kingdom Foil id in alphabetical order.	SELECT cardKingdomFoilId, cardKingdomId FROM cards WHERE cardKingdomFoilId IS NOT NULL AND cardKingdomId IS NOT NULL ORDER BY cardKingdomFoilId LIMIT 3	SELECT cardKingdomFoilId, cardKingdomId FROM (SELECT cardKingdomFoilId, cardKingdomId, rank() over (ORDER BY cardKingdomFoilId) as rk FROM cards WHERE cardKingdomFoilId IS NOT NULL AND cardKingdomId IS NOT NULL) WHERE rk <= 3	limit n	1	0

426	Please provide top three sets that don't appear in Magic: The Gathering Online, along with their names in in alphabetical order.	SELECT name FROM sets WHERE mtgoCode IS NULL ORDER BY name LIMIT 3	SELECT name FROM (SELECT name, rank() over (ORDER BY name) as rk FROM sets WHERE mtgoCode IS NULL OR mtgoCode = ") WHERE rk <= 3	semantic error: wrong condition; limit n	1	0
427	What languages are available in the set known as Archenemy on the magic card market and having the code ARC?	SELECT T2.language FROM sets AS T1 INNER JOIN set_translations AS T2 ON T1.code = T2.setCode WHERE T1.mcmName = 'Archenemy' AND T2.setCode = 'ARC'	SELECT DISTINCT T2.language FROM sets AS T1 INNER JOIN set_translations AS T2 ON T1.code = T2.setCode WHERE T1.mcmName = 'Archenemy' AND T2.setCode = 'ARC'	lack distinct	1	0
428	What is the name of set number 5 and its translation?	SELECT T1.name, T2.translation FROM sets AS T1 INNER JOIN set_translations AS T2 ON T1.code = T2.setCode WHERE T2.id = 5 GROUP BY T1.name, T2.translation	SELECT T1.name, T2.translation FROM sets T1 JOIN set_translations T2 ON T1.code = T2.setCode WHERE T1.id = 5;	semantic error: wrong condition	0	1
429	What is the language and expansion type of set number 206?	SELECT T2.language, T1.type FROM sets AS T1 INNER JOIN set_translations AS T2 ON T1.code = T2.setCode WHERE T2.id = 206	SELECT T2.language, T1.type FROM sets AS T1 INNER JOIN set_translations AS T2 ON T1.code = T2.setCode WHERE T1.id = 206	semantic error: wrong condition	1	0
430	Please list top two sets of cards with their IDs that have Italian-language cards and are located in the Shadowmoor block in alphabetical order.	SELECT T1.name, T1.id FROM sets AS T1 INNER JOIN set_translations AS T2 ON T1.code = T2.setCode WHERE T1.block = 'Shadowmoor' AND T2.language = 'Italian' ORDER BY T1.id LIMIT 2	SELECT name, id FROM (SELECT T1.name, T1.id, rank() over (ORDER BY T1.name) as rk FROM sets AS T1 WHERE T1.block = 'Shadowmoor' AND T1.code IN (SELECT T2.setCode FROM set_translations AS T2 WHERE T2.language = 'Italian')) WHERE rk <= 2	limit n; join -> in-sub; semantic error: order by column	0	0
431	Which set is not available outside of the United States and has foil cards with Japanese writing on them? Please include the set ID in your response.	SELECT T1.name, T1.id FROM sets AS T1 INNER JOIN set_translations AS T2 ON T1.code = T2.setCode WHERE T2.language = 'Japanese' AND T1.isFoilOnly = 1 AND T1.isForeignOnly = 0	SELECT T1.name, T1.id FROM sets AS T1 WHERE T1.code IN (SELECT T2.setCode FROM set_translations AS T2 WHERE T2.language = 'Japanese') AND T1.isFoilOnly = 1 AND T1.isForeignOnly = 0	join -> in-sub	0	0
432	Which Russian set of cards contains the most cards overall?	SELECT T1.id FROM sets AS T1 INNER JOIN set_translations AS T2 ON T1.code = T2.setCode WHERE T2.language = 'Russian' GROUP BY T1.baseSetSize HAVING COUNT(T1.id) = (SELECT MAX(card_count) FROM (SELECT COUNT(T1.id) AS card_count FROM sets AS T1 INNER JOIN set_translations AS T2 ON T1.code = T2.setCode WHERE T2.language = 'Russian' GROUP BY T1.baseSetSize) AS subquery)	SELECT T1.id FROM sets AS T1 WHERE T1.code IN (SELECT T2.setCode FROM set_translations AS T2 WHERE T2.language = 'Russian') AND T1.baseSetSize = (SELECT max(T1.baseSetSize) FROM sets AS T1 WHERE T1.code IN (SELECT T2.setCode FROM set_translations AS T2 WHERE T2.language = 'Russian'))	semantic error	0	0
433	What is the percentage of the set of cards that have Chinese Simplified as the language and are only available for online games?	SELECT CAST(SUM(CASE WHEN T2.language = 'Chinese Simplified' AND T1.isOnlineOnly = 1 THEN 1 ELSE 0 END) AS REAL) * 100 / COUNT(*) FROM sets AS T1 INNER JOIN set_translations AS T2 ON T1.code = T2.setCode	SELECT CAST(COUNT(DISTINCT CASE WHEN T2.language = 'Chinese Simplified' AND T1.isOnlineOnly = 1 THEN T1.id END) AS REAL) * 100 / (SELECT COUNT(*) FROM sets) FROM sets AS T1 INNER JOIN set_translations AS T2 ON T1.code = T2.setCode;	lack distinct; join -> left join	0	0
434	How many sets are available just in Japanese and not in Magic: The Gathering Online?	SELECT COUNT(T1.id) FROM sets AS T1 INNER JOIN set_translations AS T2 ON T2.setCode = T1.code WHERE T2.language = 'Japanese' AND (T1.mtgoCode IS NULL OR T1.mtgoCode = ")	SELECT COUNT(DISTINCT T1.id) FROM sets AS T1 INNER JOIN set_translations AS T2 ON T2.setCode = T1.code WHERE T2.language = 'Japanese' AND (T1.mtgoCode IS NULL OR T1.mtgoCode = ")	lack distinct	1	0

438	Point out the language of set id "174"?	SELECT language FROM set_translations WHERE id = 174	SELECT language FROM set_translations JOIN sets on set_translations.setCode = sets.code WHERE sets.id = 174	semantic error: wrong condition	1	0
441	State the set code of the set with release date of 07/13/2007?	SELECT T2.setCode FROM sets AS T1 INNER JOIN set_translations AS T2 ON T2.setCode = T1.code WHERE T1.releaseDate = '2007-07-13'	SELECT code FROM sets WHERE releaseDate = '2007-07-13';	semantic error: redundant join	0	1
442	Mention the base set size and set code of the set that was in block named "Masques" and "Mirage".	SELECT DISTINCT T1.baseSetSize, T2.setCode FROM sets AS T1 INNER JOIN set_translations AS T2 ON T2.setCode = T1.code WHERE T1.block IN ('Masques', 'Mirage')	SELECT baseSetSize, code FROM sets WHERE block = 'Masques' OR block = 'Mirage';	semantic error: redundant join	0	1
443	Give the code of sets have expansion type of 'expansion'?	SELECT T2.setCode FROM sets AS T1 INNER JOIN set_translations AS T2 ON T2.setCode = T1.code WHERE T1.type = 'expansion' GROUP BY T2.setCode	SELECT code FROM sets WHERE type = 'expansion';	semantic error: redundant join	0	1
444	Name the foreign name of the card that has boros watermark? List out the type of this card.	SELECT DISTINCT T1.name, T1.type FROM cards AS T1 INNER JOIN foreign_data AS T2 ON T2.uuid = T1.uuid WHERE T1.watermark = 'boros'	SELECT T2.name, T2.type FROM cards T1 JOIN foreign_data T2 ON T1.uuid = T2.uuid WHERE T1.watermark = 'boros';	semantic error: output column	0	1
445	What is the language and flavor text of the card that has colorpie watermark? List out the type of this card.	SELECT DISTINCT T2.language, T2.flavorText FROM cards AS T1 INNER JOIN foreign_data AS T2 ON T2.uuid = T1.uuid WHERE T1.watermark = 'colorpie'	SELECT T2.language, T2.flavorText, T2.type FROM cards AS T1 INNER JOIN foreign_data AS T2 ON T2.uuid = T1.uuid WHERE T1.watermark = 'colorpie'	redundant distinct; semantic error: lack column	0	0
446	What is percentage of the cards with a converted Mana Cost of 10 in set of Abyssal Horror?	SELECT CAST(SUM(CASE WHEN T1.convertedManaCost = 10 THEN 1 ELSE 0 END) AS REAL) * 100 / COUNT(T1.id), T1.name FROM cards AS T1 INNER JOIN sets AS T2 ON T2.code = T1.setCode WHERE T1.name = 'Abyssal Horror'	SELECT CAST(COUNT(CASE WHEN T1.convertedManaCost = 10 THEN T1.id END) AS REAL) * 100 / COUNT(T1.id) FROM cards AS T1 INNER JOIN sets AS T2 ON T2.code = T1.setCode WHERE T2.name = 'Abyssal Horror'	semantic error: wrong condition	0	0
447	Give the code of sets have expansion commander type?	SELECT T2.setCode FROM sets AS T1 INNER JOIN set_translations AS T2 ON T2.setCode = T1.code WHERE T1.type = 'commander'	SELECT code FROM sets WHERE type = 'commander';	semantic error: redundant join	0	1
448	Name the foreign name of the card that has abzan watermark? List out the type of this card.	SELECT DISTINCT T1.name, T1.type FROM cards AS T1 INNER JOIN foreign_data AS T2 ON T2.uuid = T1.uuid WHERE T1.watermark = 'abzan'	SELECT T2.name, T2.type FROM cards T1 JOIN foreign_data T2 ON T1.uuid = T2.uuid WHERE T1.watermark = 'abzan';	redundant distinct; semantic error: output column	0	1
449	What is the language of the card that has azorius watermark? List out the type of this card.	SELECT DISTINCT T2.language, T1.type FROM cards AS T1 INNER JOIN foreign_data AS T2 ON T2.uuid = T1.uuid WHERE T1.watermark = 'azorius'	SELECT T2.language, T1.type FROM cards AS T1 INNER JOIN foreign_data AS T2 ON T2.uuid = T1.uuid WHERE T1.watermark = 'azorius'	redundant distinct	0	0
451	How many cards available in paper have a positive starting maximum hand size?	SELECT SUM(CASE WHEN availability = 'paper' AND hAND = '3' THEN 1 ELSE 0 END) FROM cards	SELECT SUM(CASE WHEN availability like '%paper%' AND hAND = '3' THEN 1 ELSE 0 END) FROM cards	str	1	0
452	Please list the names of the cards that have a text box.	SELECT DISTINCT name FROM cards WHERE isTextless = 0	SELECT name FROM cards WHERE isTextless = 0;	redundant distinct	0	1
453	What's the unconverted mana cost of the card "Ancestor's Chosen"?	SELECT DISTINCT manaCost FROM cards WHERE name = 'Ancestor's Chosen'	SELECT manaCost FROM cards WHERE name = 'Ancestor's Chosen'	redundant distinct	0	0
454	Among the cards with a white border color, how many of them have unknown power?	SELECT SUM(CASE WHEN power LIKE '%*%' OR power IS NULL THEN 1 ELSE 0 END) FROM cards WHERE borderColor = 'white'	SELECT SUM(CASE WHEN power = '*' OR power IS NULL THEN 1 ELSE 0 END) FROM cards WHERE borderColor = 'white'	str	1	0

455	Which of the cards that are a promotional painting have multiple faces on the same card? Please list their names.	SELECT DISTINCT name FROM cards WHERE isPromo = 1 AND side IS NOT NULL	SELECT name FROM cards WHERE isPromo = 1 AND side IS NOT NULL;	redundant distinct	0	1
456	What's the list of all types for the card "Molimo, Maro-Sorcerer"?	SELECT DISTINCT subtypes, supertypes FROM cards WHERE name = 'Molimo, Maro-Sorcerer'	SELECT subtypes, supertypes FROM cards WHERE name = 'Molimo, Maro-Sorcerer'	redundant distinct	1	0
461	Please list the names of the top 3 cards with the highest converted mana cost and have a 2003 card frame style.	SELECT name FROM cards WHERE frameVersion = 2003 ORDER BY convertedManaCost DESC LIMIT 3	SELECT name FROM (SELECT name, rank() over (ORDER BY convertedManaCost DESC) as rk FROM cards WHERE frameVersion = 2003) WHERE rk <= 3	limit n	1	0
464	Please list the names of the cards in the set "Hauptset Zehnte Edition".	SELECT DISTINCT T1.name FROM cards AS T1 INNER JOIN set_translations AS T2 ON T2.setCode = T1.setCode WHERE T2.translation = 'Hauptset Zehnte Edition'	SELECT T1.name FROM cards AS T1 WHERE T1.setCode IN (SELECT T2.setCode FROM set_translations AS T2 WHERE T2.translation = 'Hauptset Zehnte Edition')	join -> in-sub	1	0
466	Among the cards in the set "Hauptset Zehnte Edition", how many of them are designed by Adam Rex?	SELECT COUNT(T1.id) FROM cards AS T1 INNER JOIN set_translations AS T2 ON T2.setCode = T1.setCode WHERE T2.translation = 'Hauptset Zehnte Edition' AND T1.artist = 'Adam Rex'	SELECT DISTINCT COUNT(T1.id) FROM cards AS T1 INNER JOIN set_translations AS T2 ON T2.setCode = T1.setCode WHERE T2.translation = 'Hauptset Zehnte Edition' AND T1.artist = 'Adam Rex'	lack distinct	1	0
467	How many cards are there in the base set of "Hauptset Zehnte Edition"? "Hauptset Zehnte Edition" refers to translation = 'Hauptset Zehnte Edition'; number of cards refers to baseSetSize	SELECT T1.baseSetSize FROM sets AS T1 INNER JOIN set_translations AS T2 ON T2.setCode = T1.setCode WHERE T2.translation = 'Hauptset Zehnte Edition'	SELECT baseSetSize FROM sets WHERE code IN (SELECT setCode FROM set_translations WHERE translation = 'Hauptset Zehnte Edition');	join -> in-sub	0	1
470	When was the set of cards with "Ancestor's Chosen" released?	SELECT DISTINCT T2.releaseDate FROM cards AS T1 INNER JOIN sets AS T2 ON T2.setCode = T1.setCode WHERE T1.name = 'Ancestor's Chosen'	SELECT releaseDate FROM sets WHERE code IN (SELECT setCode FROM cards WHERE name = 'Ancestor's Chosen')	join -> in-sub	1	0
471	What is the expansion type of the set "Hauptset Zehnte Edition"?	SELECT T1.type FROM sets AS T1 INNER JOIN set_translations AS T2 ON T2.setCode = T1.setCode WHERE T2.translation = 'Hauptset Zehnte Edition'	SELECT type FROM sets WHERE code IN (SELECT setCode FROM set_translations WHERE translation = 'Hauptset Zehnte Edition');	join -> in-sub	0	1
473	Is the set of cards with Adarkar Valkyrie only available outside the United States? Answer by 'YES' or 'NO' for each record.	SELECT IIF(isForeignOnly = 1, 'YES', 'NO') FROM cards AS T1 INNER JOIN sets AS T2 ON T2.setCode = T1.setCode WHERE T1.name = 'Adarkar Valkyrie'	SELECT IIF(isForeignOnly = 1, 'YES', 'NO') FROM sets WHERE code IN (SELECT setCode FROM cards WHERE name = 'Adarkar Valkyrie')	join -> in-sub	0	0
474	Among the sets of cards that have an Italian translation, how many of them have a base set number of under 100?	SELECT COUNT(T1.id) FROM sets AS T1 INNER JOIN set_translations AS T2 ON T2.setCode = T1.setCode WHERE T2.translation IS NOT NULL AND T1.baseSetSize < 100 AND T2.language = 'Italian'	SELECT COUNT(DISTINCT T1.id) FROM sets T1 JOIN set_translations T2 ON T1.setCode = T2.setCode WHERE T2.language = 'Italian' AND T1.baseSetSize < 100;	lack distinct	0	1

481	Please list all the foreign languages in which the card "Ancestor's Chosen" has a flavor text. "Ancestor's Chosen" refers to name = 'Ancestor's Chosen'; has a flavor text refers to flavorText is not null	SELECT T2.language FROM cards AS T1 INNER JOIN foreign_data AS T2 ON T2.uuid = T1.uuid WHERE T1.name = 'Ancestor's Chosen' AND T2.flavorText IS NOT NULL	SELECT DISTINCT T2.language FROM cards T1 JOIN foreign_data T2 ON T1.uuid = T2.uuid WHERE T1.name = 'Ancestor's Chosen' AND T2.flavorText IS NOT NULL;	lack distinct	0	1
483	Please list the Italian text ruling of all the cards in the set Coldsnap.	SELECT DISTINCT T1.text FROM foreign_data AS T1 INNER JOIN cards AS T2 ON T2.uuid = T1.uuid INNER JOIN sets AS T3 ON T3.code = T2.setCode WHERE T3.name = 'Coldsnap' AND T1.language = 'Italian'	SELECT T1.text FROM foreign_data AS T1 INNER JOIN cards AS T2 ON T2.uuid = T1.uuid INNER JOIN sets AS T3 ON T3.code = T2.setCode WHERE T3.name = 'Coldsnap' AND T1.language = 'Italian'	redundant distinct	1	0
488	What's the code for the set which was released on 2017/7/14?	SELECT code FROM sets WHERE releaseDate = '2017-07-14' GROUP BY releaseDate, code	SELECT code FROM sets WHERE releaseDate = '2017-07-14'	redundant group by	1	0
495	What was the release date for the set which card "Evacuation" in it? "Evacuation" refers to name = 'Evacuation'; release date refers to releaseDate	SELECT T2.releaseDate FROM cards AS T1 INNER JOIN sets AS T2 ON T2.code = T1.setCode WHERE T1.name = 'Evacuation'	SELECT releaseDate FROM sets WHERE code IN (SELECT setCode FROM cards WHERE name = 'Evacuation')	join -> in-sub	1	0
496	What is the number of cards are there in the set of "Rinascita di Alara"?	SELECT T1.baseSetSize FROM sets AS T1 INNER JOIN set_translations AS T2 ON T2.setCode = T1.code WHERE T2.translation = 'Rinascita di Alara'	SELECT baseSetSize FROM sets WHERE code IN (SELECT setCode FROM set_translations WHERE translation = 'Rinascita di Alara');	join -> in-sub	0	1
498	What's the French name of the set of cards with "Tendo Ice Bridge" is in?	SELECT T2.translation FROM cards AS T1 INNER JOIN set_translations AS T2 ON T2.setCode = T1.setCode WHERE T1.name = 'Tendo Ice Bridge' AND T2.language = 'French' AND T2.translation IS NOT NULL	SELECT translation FROM set_translations WHERE setCode IN (SELECT setCode FROM cards WHERE name = 'Tendo Ice Bridge') AND language = 'French' AND translation IS NOT NULL	join -> in-sub	1	0
499	How many translations of the name of the set "Tenth Edition"?	SELECT COUNT(DISTINCT T2.translation) FROM sets AS T1 INNER JOIN set_translations AS T2 ON T2.setCode = T1.code WHERE T1.name = 'Tenth Edition' AND T2.translation IS NOT NULL	SELECT COUNT(translation) AS translation_count FROM set_translations WHERE setCode IN (SELECT code FROM sets WHERE name = 'Tenth Edition');	redundant distinct	0	1
500	Tell the Japanese name of the set which card "Fellwar Stone" is in it.	SELECT T2.translation FROM cards AS T1 INNER JOIN set_translations AS T2 ON T2.setCode = T1.setCode WHERE T1.name = 'Fellwar Stone' AND T2.language = 'Japanese' AND T2.translation IS NOT NULL	SELECT translation FROM set_translations WHERE setCode IN (SELECT setCode FROM cards WHERE name = 'Fellwar Stone') AND language = 'Japanese' AND translation IS NOT NULL	join -> in-sub	1	0
501	Which card name in the set 'Journey into Nyx Hero's Path' has the highest converted mana cost.	SELECT T1.name FROM cards AS T1 INNER JOIN sets AS T2 ON T2.code = T1.setCode WHERE T2.name = 'Journey into Nyx Hero's Path' ORDER BY T1.convertedManaCost DESC LIMIT 1	SELECT name FROM (SELECT T1.name, rank() over (ORDER BY T1.convertedManaCost DESC) as rk FROM cards AS T1 INNER JOIN sets AS T2 ON T2.code = T1.setCode WHERE T2.name = 'Journey into Nyx Hero's Path') WHERE rk = 1	limit 1	1	0
502	What is the release date for the set "Ola de frío"?	SELECT T1.releaseDate FROM sets AS T1 INNER JOIN set_translations AS T2 ON T2.setCode = T1.code WHERE T2.translation = 'Ola de frío'	SELECT T1.releaseDate FROM sets AS T1 WHERE T1.code IN (SELECT T2.setCode FROM set_translations AS T2 WHERE T2.translation = 'Ola de frío')	semantic error: redundant join	1	0
509	What is the unique id of the set that has the highest number of cards?	SELECT id FROM sets ORDER BY baseSetSize DESC LIMIT 1	SELECT id FROM sets WHERE baseSetSize = (SELECT MAX(baseSetSize) FROM sets);	limit 1	0	1

510	Among the cards that doesn't have multiple faces on the same card, who is the illustrator of the card art that has the highest cost of converted mana?	SELECT artist FROM cards WHERE side IS NULL ORDER BY convertedManaCost DESC LIMIT 1	SELECT artist FROM (SELECT artist, rank() over (ORDER BY convertedManaCost DESC) as rk FROM cards WHERE side IS NULL) WHERE rk = 1	limit 1	1	0
511	What is the most common visual frame effects among the incredibly powerful foils?	SELECT frameEffects FROM cards WHERE cardKingdomFoilId IS NOT NULL AND cardKingdomId IS NOT NULL GROUP BY frameEffects ORDER BY COUNT(frameEffects) DESC LIMIT 1	SELECT frameEffects FROM (SELECT frameEffects, rank() over (ORDER BY COUNT(frameEffects) DESC) as rk FROM cards WHERE cardKingdomFoilId IS NOT NULL AND cardKingdomId IS NOT NULL GROUP BY frameEffects) WHERE rk = 1	limit 1	1	0
513	Among the sets whose expansion type is Commander, which set has the highest total number of cards including promotional and related supplemental products but excluding Alchemy modifications? Indicate the id of the set.	SELECT id FROM sets WHERE type = 'commander' ORDER BY totalSetSize DESC LIMIT 1	SELECT id FROM sets WHERE type = 'commander' AND totalSetSize = (SELECT MAX(totalSetSize) FROM sets WHERE type = 'commander');	limit 1	0	1
514	In duels, what are the top 10 cards with the highest uncovered mana cost?	SELECT DISTINCT name FROM cards WHERE uuid IN (SELECT uuid FROM legalities WHERE format = 'duel') ORDER BY manaCost DESC LIMIT 0, 10	SELECT name FROM (SELECT name, rank() over (ORDER BY manaCost DESC) as rk FROM cards WHERE uuid IN (SELECT uuid FROM legalities WHERE format = 'duel')) WHERE rk <= 10	redundant distinct; limit n	1	0
517	How many rare enchantment Abundance cards are there whose play format status are all legal?	SELECT COUNT(T1.id) FROM cards AS T1 INNER JOIN legalities AS T2 ON T2.uuid = T1.uuid WHERE T1.rarity = 'rare' AND T1.types = 'Enchantment' AND T1.name = 'Abundance' AND T2.status = 'Legal'	SELECT COUNT(DISTINCT T1.id) FROM cards AS T1 INNER JOIN legalities AS T2 ON T2.uuid = T1.uuid WHERE T1.rarity = 'rare' AND T1.types = 'Enchantment' AND T1.name = 'Abundance' AND T2.status = 'Legal'	lack distinct	0	0
518	Which of the play format has the highest number of banned status? Indicate the play format and the names of all the card meet the condition.	WITH MaxBanned AS (SELECT format, COUNT(*) AS count_banned FROM legalities WHERE status = 'Banned' GROUP BY format ORDER BY COUNT(*) DESC LIMIT 1) SELECT T2.format, T1.name FROM cards AS T1 INNER JOIN legalities AS T2 ON T2.uuid = T1.uuid INNER JOIN MaxBanned MB ON MB.format = T2.format WHERE T2.status = 'Banned'	WITH CountedFormats AS (SELECT format, COUNT(*) AS Cnt FROM legalities WHERE status = 'Banned' GROUP BY format), MaxFormat AS (SELECT format FROM CountedFormats WHERE Cnt = (SELECT MAX(Cnt) FROM CountedFormats)) SELECT legalities.format, cards.name FROM legalities JOIN cards ON legalities.uuid = cards.uuid WHERE legalities.format IN (SELECT format FROM MaxFormat) AND legalities.status = 'Banned'	limit 1	0	1
519	What is the language of the "Battlebond" set? "Battlebond" set refers to name = 'Battlebond'	SELECT language FROM set_translations WHERE id IN (SELECT id FROM sets WHERE name = 'Battlebond')	SELECT T2.language FROM sets T1 JOIN set_translations T2 ON T1.code = T2.setCode WHERE T1.name = 'Battlebond';	semantic error: wrong condition	0	1
520	Who is the illustrator that illustrated the least amount of cards? List the format of play of the cards that he/she illustrated.	SELECT T1.artist, T2.format FROM cards AS T1 INNER JOIN legalities AS T2 ON T2.uuid = T1.uuid GROUP BY T1.artist ORDER BY COUNT(T1.id) ASC LIMIT 1	SELECT Tartist, legalities.format FROM (SELECT artist, uuid FROM cards WHERE artist IN (SELECT artist FROM cards GROUP BY artist HAVING COUNT(uuid) = (SELECT MIN(count) FROM (SELECT COUNT(uuid) AS count FROM cards GROUP BY artist)))) AS T JOIN legalities ON T.uuid = legalities.uuid	limit 1	0	0

521	Among the cards whose version of frame style is 1997, what is the status of the card illustrated by D. Alexander Gregory in legacy play format that has sensitive content or Wizards of the Coast?	SELECT DISTINCT T2.status FROM cards AS T1 INNER JOIN legalities AS T2 ON T2.uid = T1.uid WHERE T1.frameVersion = 1997 AND T1.hasContentWarning = 1 AND T1.artist = 'D. Alexander Gregory' AND T2.format = 'legacy'	SELECT status FROM legalities AS T2 WHERE T2.uid IN (SELECT T1.uid FROM cards AS T1 WHERE T1.frameVersion = 1997 AND T1.hasContentWarning = 1 AND T1.artist = 'D. Alexander Gregory') AND T2.format = 'legacy'	join -> in-sub	1	0
522	Which cards are ranked 1st on EDHRec? List all of the cards name and its banned play format.	SELECT T1.name, T2.format FROM cards AS T1 INNER JOIN legalities AS T2 ON T2.uid = T1.uid WHERE T1.edhrecRank = 1 AND T2.status = 'Banned' GROUP BY T1.name, T2.format	SELECT T1.name, T2.format FROM cards AS T1 INNER JOIN legalities AS T2 ON T2.uid = T1.uid WHERE T1.edhrecRank = 1 AND T2.status = 'Banned'	redundant group by	1	0
523	What is the annual average number of sets that were released between 1/1/2012 to 12/31/2015? Indicate the common language of the card.	SELECT (CAST(SUM(T1.id) AS REAL) / COUNT(T1.id)) / 4, T2.language FROM sets AS T1 INNER JOIN set_translations AS T2 ON T1.id = T2.id WHERE T1.releaseDate BETWEEN '2012-01-01' AND '2015-12-31' GROUP BY T1.releaseDate ORDER BY COUNT(T2.language) DESC LIMIT 1	SELECT * FROM (SELECT AVG(yearly_count) AS average_sets_per_year FROM (SELECT COUNT(*) AS yearly_count FROM sets WHERE releaseDate BETWEEN '2012-01-01' AND '2015-12-31' GROUP BY strftime('%Y', releaseDate))) NATURAL JOIN (SELECT language FROM (SELECT language, rank() over (ORDER BY COUNT(*) DESC) as rk FROM set_translations WHERE setCode IN (SELECT code FROM sets WHERE releaseDate BETWEEN '2012-01-01' AND '2015-12-31') GROUP BY language) WHERE rk = 1)	limit 1; semantic error: wrong group by	0	0
525	Find the uid of cards in which the old school format is restricted or banned.	SELECT uid FROM legalities WHERE format = 'oldschool' AND (status = 'Banned' OR status = 'Restricted')	SELECT DISTINCT uid FROM legalities WHERE format = 'oldschool' AND (status = 'Banned' OR status = 'Restricted')	lack distinct	1	0
528	List the names of all the cards in the set Hour of Devastation and find the formats in which these cards are legal.	SELECT DISTINCT T2.name, CASE WHEN T1.status = 'Legal' THEN T1.format ELSE NULL END FROM legalities AS T1 INNER JOIN cards AS T2 ON T2.uid = T1.uid WHERE T2.setCode IN (SELECT code FROM sets WHERE name = 'Hour of Devastation')	SELECT C.name, L.format FROM sets S JOIN cards C ON S.code = C.setCode JOIN legalities L ON C.uid = L.uid WHERE S.name = 'Hour of Devastation' AND L.status = 'Legal';	redundant distinct	0	1
529	Find and list the names of sets which doesn't have Japanese translation but have Korean translation.	SELECT name FROM sets WHERE code IN (SELECT setCode FROM set_translations WHERE language = 'Korean' AND language NOT LIKE '%Japanese%')	SELECT T2.name FROM sets T2 WHERE T2.code IN (SELECT T1.setCode FROM set_translations T1 WHERE T1.language = 'Korean') AND T2.code NOT IN (SELECT T1.setCode FROM set_translations T1 WHERE T1.language LIKE '%Japanese%')	semantic error: wrong condition	0	1
530	List all the frame styles and cards Allen Williams worked on and find any banned cards if there are any.	SELECT DISTINCT T1.frameVersion, T1.name, IIF(T2.status = 'Banned', T1.name, 'NO') FROM cards AS T1 INNER JOIN legalities AS T2 ON T1.uid = T2.uid WHERE T1.artist = 'Allen Williams'	SELECT DISTINCT T1.frameVersion, T1.name, IIF(T1.uid IN (SELECT T2.uid FROM legalities AS T2 WHERE status = 'Banned'), 'Banned', 'NO') FROM cards AS T1 WHERE T1.artist = 'Allen Williams'	redundant distinct; semantic error	0	0
540	What is the title of the post that is owned by csgillespie and has the highest popularity? "csgillespie" is the DisplayName of user; highest popularity refers to Max(ViewCount)	SELECT T1.Title FROM posts AS T1 INNER JOIN users AS T2 ON T1.OwnerUserId = T2.Id WHERE T2.DisplayName = 'csgillespie' ORDER BY T1.ViewCount DESC LIMIT 1	SELECT Title FROM posts WHERE OwnerUserId IN (SELECT Id FROM users WHERE DisplayName = 'csgillespie') AND ViewCount = (SELECT MAX(ViewCount) FROM posts WHERE OwnerUserId IN (SELECT Id FROM users WHERE DisplayName = 'csgillespie'))	limit 1	1	0

541	What is the display name of the user who is the owner of the most valuable post?	SELECT T2.DisplayName FROM posts AS T1 INNER JOIN users AS T2 ON T1.OwnerUserId = T2.Id ORDER BY T1.FavoriteCount DESC LIMIT 1	SELECT DisplayName FROM users WHERE Id IN (SELECT OwnerUserId FROM posts WHERE FavoriteCount = (SELECT MAX(FavoriteCount) FROM posts))	limit 1	0	1
546	Please list the display names of all the users who owns a post that is well-finished.	SELECT T2.DisplayName FROM posts AS T1 INNER JOIN users AS T2 ON T1.OwnerUserId = T2.Id WHERE T1.ClosedDate IS NOT NULL	SELECT DisplayName FROM users WHERE Id IN (SELECT OwnerUserId FROM posts WHERE ClosedDate IS NOT NULL)	join -> in-sub	1	0
548	What is the location of the owner of the post "Eliciting priors from experts"?	SELECT T2.Location FROM posts AS T1 INNER JOIN users AS T2 ON T1.OwnerUserId = T2.Id WHERE T1.Title = 'Eliciting priors from experts'	SELECT Location FROM users WHERE Id IN (SELECT OwnerUserId FROM posts WHERE Title = 'Eliciting priors from experts');	join -> in-sub?	0	0
549	From which post is the tag "bayesian" excerpted from? Please give the body of the post. "bayesian" is the TagName; excerpt from refers to ExcerptPostId	SELECT T2.Body FROM tags AS T1 INNER JOIN posts AS T2 ON T2.Id = T1.ExcerptPostId WHERE T1.TagName = 'bayesian'	SELECT T2.Body FROM tags AS T1 LEFT JOIN posts AS T2 ON T2.Id = T1.ExcerptPostId WHERE T1.TagName = 'bayesian'	join -> left join	0	0
550	From which post is the most popular tag excerpted from? Please give the body of the post.	SELECT Body FROM posts WHERE id = (SELECT ExcerptPostId FROM tags ORDER BY Count DESC LIMIT 1)	SELECT Body FROM posts WHERE Id IN (SELECT ExcerptPostId FROM tags WHERE Count = (SELECT MAX(Count) FROM tags WHERE Count IS NOT NULL));	join -> in-sub	0	1
554	What is the display name of the user who has obtained the most number of badges?	SELECT T2.DisplayName FROM badges AS T1 INNER JOIN users AS T2 ON T1.UserId = T2.Id GROUP BY T2.DisplayName ORDER BY COUNT(T1.Id) DESC LIMIT 1	SELECT DisplayName FROM users WHERE Id IN (SELECT UserId FROM badges GROUP BY UserId HAVING COUNT(Id) = (SELECT MAX(BadgeCount) FROM (SELECT COUNT(Id) AS BadgeCount FROM badges GROUP BY UserId)));	limit 1; group by non-key	0	1
556	What is the average number of badges obtained by a user with over 200 views?	SELECT CAST(COUNT(T1.Id) AS REAL) / COUNT(DISTINCT T2.DisplayName) FROM badges AS T1 INNER JOIN users AS T2 ON T1.UserId = T2.Id WHERE T2.Views > 200	SELECT AVG(badge_count) FROM (SELECT COUNT(b.Id) AS badge_count FROM users u JOIN badges b ON u.Id = b.UserId WHERE u.Views > 200 GROUP BY u.Id)	semantic error	0	0
559	Indicate the creation date of the maximum number of votes.	SELECT CreationDate FROM votes GROUP BY CreationDate ORDER BY COUNT(Id) DESC LIMIT 1	SELECT CreationDate FROM votes WHERE CreationDate IS NOT NULL GROUP BY CreationDate HAVING COUNT(Id) = (SELECT MAX(VoteCount) FROM (SELECT COUNT(Id) AS VoteCount FROM votes WHERE CreationDate IS NOT NULL GROUP BY CreationDate) T2);	limit 1	0	1
560	Give the number of "Revival" badges.	SELECT COUNT(Id) FROM badges WHERE Name = 'Revival'	SELECT Id FROM badges WHERE Name = 'Revival'	semantic error	1	0
561	What is the title for the post which got the highest score comment?	SELECT Title FROM posts WHERE Id = (SELECT PostId FROM comments ORDER BY Score DESC LIMIT 1)	SELECT Title FROM posts WHERE Id IN (SELECT PostId FROM comments WHERE Score = (SELECT MAX(Score) FROM comments));	limit 1	0	1
563	User No.3025 gave a comment at 20:29:39 on 2014/4/23 to a post, how many favorite counts did that post get?	SELECT T1.FavoriteCount FROM posts AS T1 INNER JOIN comments AS T2 ON T1.Id = T2.PostId WHERE T2.CreationDate = '2014-04-23 20:29:39.0' AND T2.UserId = 3025	SELECT FavoriteCount FROM posts WHERE Id IN (SELECT PostId FROM comments WHERE UserId = 3025 AND CreationDate = '2014-04-23 20:29:39.0')	join -> in-sub	1	0

570	For the user whose display name is "DatEpic-CoderGuyWho-Programs", what is his/her badge's name? "DatEpic-CoderGuyWho-Programs" is the DisplayName;	SELECT T2.Name FROM users AS T1 INNER JOIN badges AS T2 ON T1.Id = T2.UserId WHERE T1.DisplayName = 'DatEpicCoderGuyWhoPrograms'	SELECT Name FROM badges WHERE UserId IN (SELECT Id FROM users WHERE DisplayName = 'DatEpicCoderGuyWhoPrograms')	join -> in-sub?	1	0
571	For the user No.24, how many times is the number of his/her posts compared to his/her votes?	SELECT CAST(COUNT(T2.Id) AS REAL) / COUNT(DISTINCT T1.Id) FROM votes AS T1 INNER JOIN posts AS T2 ON T1.UserId = T2.OwnerUserId WHERE T1.UserId = 24	SELECT (SELECT COUNT(Id) FROM posts WHERE OwnerUserId = 24) * 1.0 / (SELECT COUNT(Id) FROM votes WHERE UserId = 24) AS ratio;	semantic error	0	1
575	What is the badge name that user 'SilentGhost' obtained? "Silent-Ghost" is the DisplayName of user;	SELECT T2.Name FROM users AS T1 INNER JOIN badges AS T2 ON T1.Id = T2.UserId WHERE T1.DisplayName = 'SilentGhost'	SELECT Name FROM badges WHERE UserId IN (SELECT Id FROM users WHERE DisplayName = 'SilentGhost')	join -> in-sub?	1	0
576	Name the user that commented 'thank you user93!' "thank you user93" is the Text of comment; user refers to DisplayName	SELECT T1.DisplayName FROM users AS T1 INNER JOIN comments AS T2 ON T1.Id = T2.UserId WHERE T2.Text = 'thank you user93!'	SELECT DisplayName FROM users WHERE Id IN (SELECT UserId FROM comments WHERE Text = 'thank you user93!')	join -> in-sub	1	0
578	Which user made a post titled 'Understanding what Dassault iSight is doing?' and how much is the reputation of the user? "Understanding what Dassault iSight is doing?" is the Title of post; user refers to DisplayName;	SELECT T1.DisplayName, T1.Reputation FROM users AS T1 INNER JOIN posts AS T2 ON T1.Id = T2.OwnerUserId WHERE T2.Title = 'Understanding what Dassault iSight is doing?'	SELECT Reputation FROM users WHERE Id IN (SELECT OwnerUserId FROM posts WHERE Title = 'Understanding what Dassault iSight is doing?')	join -> in-sub	1	0
580	Name 10 users with the badge name 'Necromancer.' "Necromancer" is the Name of badge; users refers to DisplayName	SELECT T1.DisplayName FROM users AS T1 INNER JOIN badges AS T2 ON T1.Id = T2.UserId WHERE T2.Name = 'Necromancer' LIMIT 10	SELECT DisplayName FROM users WHERE Id IN (SELECT UserId FROM badges WHERE Name = 'Necromancer') LIMIT 10	join -> in-sub	1	0
581	Who is the editor of the post titled 'Open source tools for visualizing multi-dimensional data?' 'Open source tools for visualizing multi-dimensional data' is the Title of Post; editor refers to DisplayName;	SELECT T2.DisplayName FROM posts AS T1 INNER JOIN users AS T2 ON T1.OwnerUserId = T2.Id WHERE T1.Title = 'Open source tools for visualizing multi-dimensional data?'	SELECT DisplayName FROM users WHERE Id IN (SELECT T2.UserId FROM posts AS T1 JOIN postHistory AS T2 ON T1.Id = T2.UserId WHERE T1.Title = 'Open source tools for visualizing multi-dimensional data?')	semantic error: editor	1	0

582	List the title of posts which were edited by Vebjorn Ljosa. "Vebjorn Ljosa" is the DisplayName; last edited refers to LastEditorUserId	SELECT T1.Title FROM posts AS T1 INNER JOIN users AS T2 ON T1.OwnerUserId = T2.Id WHERE T2.DisplayName = 'Vebjorn Ljosa'	SELECT T4.Title FROM posts AS T4 WHERE T4.id IN (SELECT T1.Id FROM posts AS T1 JOIN postHistory AS T2 ON T1.Id = T2.PostId JOIN users AS T3 ON T2.UserId = T3.Id WHERE T3.DisplayName = 'Vebjorn Ljosa')	semantic error: editor	0	0
583	What is the total score of the posts edited by Yevgeny and include the user's website URL. "Yevgeny" is the DisplayName; edited refers to LastEditorUserId	SELECT SUM(T1.Score), T2.WebsiteUrl FROM posts AS T1 INNER JOIN users AS T2 ON T1.LastEditorUserId = T2.Id WHERE T2.DisplayName = 'Yevgeny' GROUP BY T2.WebsiteUrl	SELECT SUM(T1.Score), T2.WebsiteUrl FROM posts AS T1 INNER JOIN users AS T2 ON T1.LastEditorUserId = T2.Id WHERE T2.DisplayName = 'Yevgeny' GROUP BY T2.Id	group by non-key	1	0
586	Which user added a bounty amount of 50 to the post title mentioning variance?	SELECT T3.DisplayName, T1.Title FROM posts AS T1 INNER JOIN votes AS T2 ON T1.Id = T2.PostId INNER JOIN users AS T3 ON T3.Id = T2.UserId WHERE T2.BountyAmount = 50 AND T1.Title LIKE '%variance%'	SELECT DisplayName FROM users WHERE Id IN (SELECT UserId FROM votes WHERE PostId IN (SELECT Id FROM posts WHERE Title LIKE '%variance%') AND BountyAmount = 50)	semantic error: output column; join -> in-sub	0	0
587	Calculate the average view count of each post tagged as 'humor' and list the title and the comment of each post.	SELECT AVG(T2.ViewCount), T2.Title, T1.Text FROM comments AS T1 INNER JOIN posts AS T2 ON T2.Id = T1.PostId WHERE T2.Tags = '<humor>' GROUP BY T2.Title, T1.Text	SELECT vc, posts.Title, comments.Text FROM (SELECT Tags, AVG(distinct ViewCount) as vc FROM posts WHERE Tags = '<humor>') AS T JOIN posts ON T.Tags = posts.Tags JOIN comments on posts.Id = comments.PostId	group by non-key; semantic error	0	0
591	How many users are awarded with supporter badge during year 2011? "Supporter" is the Name of badge; in year 2011 refers to year(Date) = 2011	SELECT COUNT(Id) FROM badges WHERE STRFTIME('%Y', Date) = '2011' AND Name = 'Supporter'	SELECT COUNT(DISTINCT UserId) FROM badges WHERE Name = 'Supporter' AND strftime('%Y', Date) = '2011'	lack distinct	1	0
593	How many users from New York have a teacher and supporter badge? "Supporter" and "Teachers" are both Name of badge; 'New York' is the Location; user refers to UserId	SELECT COUNT(DISTINCT T1.Id) FROM badges AS T1 INNER JOIN users AS T2 ON T1.UserId = T2.Id WHERE T1.Name IN ('Supporter', 'Teacher') AND T2.Location = 'New York'	SELECT COUNT(DISTINCT T1.Id) FROM badges AS T1 INNER JOIN users AS T2 ON T1.UserId = T2.Id WHERE T1.Name IN ('Supporter', 'Teachers') AND T2.Location = 'New York';	str: 'Teachers'	0	0
594	Which user created post ID 1 and what is the reputation of this user?	SELECT T2.Id, T2.Reputation FROM comments AS T1 INNER JOIN users AS T2 ON T1.UserId = T2.Id WHERE T1.PostId = 1	SELECT T2.Id, T2.Reputation FROM posts AS T1 INNER JOIN users AS T2 ON T1.OwnerUserId = T2.Id WHERE T1.Id = 1	semantic error	1	0
595	Which user have only one post history per post and having at least 1000 views?	SELECT T2.UserId FROM users AS T1 INNER JOIN postHistory AS T2 ON T1.Id = T2.UserId INNER JOIN posts AS T3 ON T2.PostId = T3.Id WHERE T3.ViewCount >= 1000 GROUP BY T2.UserId HAVING COUNT(DISTINCT T2.PostHistoryTypeId) = 1	SELECT DISTINCT U.Id FROM users U INNER JOIN postHistory PH ON U.Id = PH.UserId WHERE U.Views >= 1000 GROUP BY PH.UserId, PH.PostId HAVING COUNT(*) = 1;	semantic error: wrong condition	0	1
596	Which users have posted the most comments. List out the user's badge?	SELECT Name FROM badges AS T1 INNER JOIN comments AS T2 ON T1.UserId = t2.UserId GROUP BY T2.UserId ORDER BY COUNT(T2.UserId) DESC LIMIT 1	SELECT T2.Name FROM (SELECT UserId, COUNT(Id) AS CommentCount FROM comments GROUP BY UserId) AS T1 JOIN badges T2 ON T1.UserId = T2.UserId WHERE T1.CommentCount = (SELECT MAX(CommentCount) FROM (SELECT UserId, COUNT(Id) AS CommentCount FROM comments GROUP BY UserId))	limit 1	0	1

597	How many users from India have the teacher badges? "India" is the Location; "Teacher" is the Name of badge	SELECT COUNT(T1.Id) FROM badges AS T1 INNER JOIN users AS T2 ON T1.UserId = T2.Id WHERE T2.Location = 'India' AND T1.Name = 'Teacher'	SELECT COUNT(DISTINCT T2.Id) FROM badges AS T1 INNER JOIN users AS T2 ON T1.UserId = T2.Id WHERE T2.Location = 'India' AND T1.Name = 'Teacher'	lack distinct	1	0
600	List out all post that are related to post ID 61217 and what is the popularity of this post?	SELECT T1.ViewCount FROM posts AS T1 INNER JOIN postLinks AS T2 ON T1.Id = T2.PostId WHERE T2.PostId = 61217	SELECT T1.ViewCount, T2.RelatedPostId FROM posts AS T1 INNER JOIN postLinks AS T2 ON T1.Id = T2.PostId WHERE T2.PostId = 61217;	semantic error: output column	1	0
602	List out all post ID with score more than 60 and list out all the user ID that created these post.	SELECT PostId, UserId FROM postHistory WHERE PostId IN (SELECT Id FROM posts WHERE Score > 60)	SELECT Id, OwnerUserId FROM posts WHERE Score > 60	semantic error: create posts	0	0
603	What is the sum of favourite count gained by user ID 686 in 2011?	SELECT SUM(DISTINCT FavoriteCount) FROM posts WHERE Id IN (SELECT PostId FROM postHistory WHERE UserId = 686 AND STRFTIME('%Y', CreationDate) = '2011')	SELECT SUM(FavoriteCount) FROM posts WHERE Id IN (SELECT PostId FROM postHistory WHERE UserId = 686 AND STRFTIME('%Y', CreationDate) = '2011')	redundant distinct	1	0
605	How many users obtained the "Announcer" badge? "Announcer" is the Name of badge; user refers to UserId	SELECT COUNT(id) FROM badges WHERE Name = 'Announcer'	SELECT COUNT(DISTINCT UserId) FROM badges WHERE Name = 'Announcer';	lack distinct	0	1
611	Mention the reputation of users who had obtained the badge on 7/19/2010 7:39:08 PM.	SELECT T1.Reputation FROM users AS T1 INNER JOIN badges AS T2 ON T1.Id = T2.UserId WHERE T2.Date = '2010-07-19 19:39:08.0'	SELECT Reputation FROM users WHERE Id IN (SELECT UserId FROM badges WHERE Date = '2010-07-19 19:39:08.0')	join -> in-sub	1	0
614	Among the users who obtained the "Teacher" badge, calculate their percentage of users "Teacher" is the Name of badge; percentage = Divide (Count(UserId where it's "Teacher"), Count(UserId)) * 100	SELECT CAST(COUNT(T1.Id) AS REAL) * 100 / (SELECT COUNT(Id) FROM users) FROM users AS T1 INNER JOIN badges AS T2 ON T1.Id = T2.UserId WHERE T2.Name = 'Teacher'	SELECT (COUNT(DISTINCT T1.UserId) * 100.0 / (SELECT COUNT(*) FROM users)) AS Percentage FROM badges T1 WHERE T1.Name = 'Teacher'	lack distinct	0	0
615	Among the users who obtained the "Organizer" badges, calculate the percentage of users who are teenagers. "Organizer" is the Name of badge; teenager refers to Age BETWEEN 13 AND 18; percentage = Divide (Count(UserId where Age BETWEEN 13 AND 18), Count(UserId)) * 100	SELECT CAST(SUM(IIF(T2.Age BETWEEN 13 AND 18, 1, 0)) AS REAL) * 100 / COUNT(T1.Id) FROM badges AS T1 INNER JOIN users AS T2 ON T1.UserId = T2.Id WHERE T1.Name = 'Organizer'	SELECT CAST(SUM(IIF(T.Age BETWEEN 13 AND 18, 1, 0)) AS REAL) * 100 / COUNT(T.Id) FROM (SELECT Id, Age FROM users WHERE Id IN (SELECT UserId FROM badges WHERE Name = 'Organizer')) T	join -> in-sub	1	0

618	List out the age of users who located in Vienna, Austria obtained the badge? "Vienna, Austria" is the Location	SELECT T1.Age FROM users AS T1 INNER JOIN badges AS T2 ON T1.Id = T2.UserId WHERE T1.Location = 'Vienna, Austria'	SELECT Age FROM users WHERE Id IN (SELECT UserId FROM badges) AND Location = 'Vienna, Austria' AND Age IS NOT NULL;	join -> in-sub	0	1
619	How many adults who obtained the badge Supporter?	SELECT COUNT(T1.Id) FROM users AS T1 INNER JOIN badges AS T2 ON T1.Id = T2.UserId WHERE T2.Name = 'Supporter' AND T1.Age BETWEEN 19 AND 65	SELECT COUNT(DISTINCT T1.UserId) FROM badges T1 JOIN users T2 ON T1.UserId = T2.Id WHERE T2.Age BETWEEN 19 AND 65 AND T1.Name = 'Supporter';	lack distinct	0	1
620	State the number of views of users who obtained the badge on 7/19/2010 7:39:08 PM.	SELECT T1.Views FROM users AS T1 INNER JOIN badges AS T2 ON T1.Id = T2.UserId WHERE T2.Date = '2010-07-19 19:39:08.0'	SELECT Views FROM users WHERE Id IN (SELECT UserId FROM badges WHERE Date = '2010-07-19 19:39:08.0')	join -> in-sub	1	0
623	How many elders obtained the "Supporter" badge? "Supporter" is the Name of badge; elders refers to Age > 65	SELECT COUNT(T1.Id) FROM users AS T1 INNER JOIN badges AS T2 ON T1.Id = T2.UserId WHERE T1.Age > 65 AND T2.Name = 'Supporter'	SELECT COUNT(DISTINCT T1.Id) FROM users AS T1 INNER JOIN badges AS T2 ON T1.Id = T2.UserId WHERE T1.Age > 65 AND T2.Name = 'Supporter'	lack distinct	0	0
628	Which users have the highest number of views?	SELECT Id, DisplayName FROM users WHERE Views = (SELECT MAX(Views) FROM users)	SELECT DisplayName FROM users WHERE Views = (SELECT MAX(Views) FROM users WHERE Views IS NOT NULL)	semantic error: output column	0	1
630	What is the name of tags used by John Salvatier's?	SELECT T3.Tags FROM users AS T1 INNER JOIN postHistory AS T2 ON T1.Id = T2.UserId INNER JOIN posts AS T3 ON T2.PostId = T3.Id WHERE T1.DisplayName = 'John Salvatier'	SELECT Tags FROM posts WHERE Id IN (SELECT T2.PostId FROM users AS T1 INNER JOIN postHistory AS T2 ON T1.Id = T2.UserId WHERE T1.DisplayName = 'John Salvatier')	join -> in-sub	0	0
631	How many posts were created by Daniel Vassallo?	SELECT COUNT(T1.Id) FROM users AS T1 INNER JOIN postHistory AS T2 ON T1.Id = T2.UserId WHERE T1.DisplayName = 'Daniel Vassallo'	SELECT COUNT(*) FROM posts JOIN users on posts.OwnerUserId = users.Id WHERE users.DisplayName = 'Daniel Vassallo';	semantic error: create posts	0	0
632	How many votes were made by Harlan?	SELECT COUNT(T1.Id) FROM users AS T1 INNER JOIN postHistory AS T2 ON T1.Id = T2.UserId INNER JOIN votes AS T3 ON T3.PostId = T2.PostId WHERE T1.DisplayName = 'Harlan'	SELECT COUNT(*) FROM votes WHERE UserId IN (SELECT Id FROM users WHERE DisplayName = 'Harlan');	semantic error	0	1
633	Which post by slashnick has the most answers count? State the post ID.	SELECT T2.PostId FROM users AS T1 INNER JOIN postHistory AS T2 ON T1.Id = T2.UserId INNER JOIN posts AS T3 ON T2.PostId = T3.Id WHERE T1.DisplayName = 'slashnick' ORDER BY T3.AnswerCount DESC LIMIT 1	SELECT Id FROM (SELECT posts.Id, rank() over (ORDER BY posts.AnswerCount DESC) as rk FROM posts JOIN users on posts.OwnerUserId = users.Id WHERE users.DisplayName = 'slashnick') WHERE rk = 1	limit 1; lack distinct; semantic error: owner of posts but not editors	0	0
634	Among posts by Harvey Motulsky and Noah Snyder, which one has higher popularity?	SELECT T1.DisplayName FROM users AS T1 INNER JOIN postHistory AS T2 ON T1.Id = T2.UserId INNER JOIN posts AS T3 ON T2.PostId = T3.Id WHERE T1.DisplayName = 'Harvey Motulsky' OR T1.DisplayName = 'Noah Snyder' GROUP BY T1.DisplayName ORDER BY SUM(T3.ViewCount) DESC LIMIT 1	SELECT Id FROM (SELECT Id, rank() over (ORDER BY ViewCount DESC) as rk FROM posts WHERE OwnerUserId IN (SELECT Id FROM users WHERE DisplayName = 'Harvey Motulsky' OR DisplayName = 'Noah Snyder')) WHERE rk = 1	limit 1; group by non-key	0	0
635	How many posts by Matt Parker have more than 4 votes?	SELECT COUNT(T1.Id) FROM users AS T1 INNER JOIN postHistory AS T2 ON T1.Id = T2.UserId INNER JOIN posts AS T3 ON T2.PostId = T3.Id INNER JOIN votes AS T4 ON T4.PostId = T3.Id WHERE T1.DisplayName = 'Matt Parker' GROUP BY T2.PostId, T4.Id HAVING COUNT(T4.Id) > 4	SELECT count(*) FROM (SELECT posts.Id FROM posts JOIN users on users.Id = posts.OwnerUserId JOIN votes on posts.Id = votes.PostId WHERE users.DisplayName = 'Matt Parker' GROUP BY posts.Id HAVING count(*) > 4)	semantic error: posts have more than 4 votes	1	0
637	State all the tags used by Mark Meckes in his posts that doesn't have comments.	SELECT T3.Tags FROM users AS T1 INNER JOIN postHistory AS T2 ON T1.Id = T2.UserId INNER JOIN posts AS T3 ON T3.Id = T2.PostId WHERE T1.DisplayName = 'Mark Meckes' AND T3.CommentCount = 0	SELECT DISTINCT T2.Tags FROM users AS T1 INNER JOIN posts AS T2 ON T1.Id = T2.OwnerUserId WHERE T1.DisplayName = 'Mark Meckes' AND T2.CommentCount = 0;	lack distinct; semantic error: owner of posts but not editors	0	0

638	List all the name of users that obtained the Organizer Badges.	SELECT T1.DisplayName FROM users AS T1 INNER JOIN badges AS T2 ON T1.Id = T2.UserId WHERE T2.Name = 'Organizer'	SELECT DisplayName FROM users WHERE Id IN (SELECT UserId FROM badges WHERE Name = 'Organizer')	join -> in-sub	1	0
639	Based on posts posted by Community, calculate the percentage of posts that use the R language.	SELECT CAST(SUM(IIF(T3.TagName = 'r', 1, 0)) AS REAL) * 100 / COUNT(T1.Id) FROM users AS T1 INNER JOIN postHistory AS T2 ON T1.Id = T2.UserId INNER JOIN tags AS T3 ON T3.ExcerptPostId = T2.PostId WHERE T1.DisplayName = 'Community'	SELECT (SELECT COUNT(DISTINCT T1.Id) FROM posts T1 JOIN users T2 ON T1.OwnerUserId = T2.Id JOIN tags T3 ON T1.Id = T3.ExcerptPostId WHERE T2.DisplayName = 'Community' AND T3.TagName = 'r') * 100 / (SELECT COUNT(DISTINCT T1.Id) FROM posts T1 JOIN users T2 ON T1.OwnerUserId = T2.Id WHERE T2.DisplayName = 'Community')	semantic error: owner of posts but not editors	0	0
640	Calculate the difference in view count from post posted by Mornington and view count from posts posted by Amos.	SELECT SUM(IIF(T1.DisplayName = 'Mornington', T3.ViewCount, 0)) - SUM(IIF(T1.DisplayName = 'Amos', T3.ViewCount, 0)) AS diff FROM users AS T1 INNER JOIN postHistory AS T2 ON T1.Id = T2.UserId INNER JOIN posts AS T3 ON T3.Id = T2.PostId	SELECT SUM(IIF(T1.DisplayName = 'Mornington', T2.ViewCount, 0)) - SUM(IIF(T1.DisplayName = 'Amos', T2.ViewCount, 0)) AS diff FROM users AS T1 INNER JOIN posts AS T2 ON T1.Id = T2.OwnerUserId	semantic error: owner of posts but not editors	1	0
641	How many users received commentator badges in 2014?	SELECT COUNT(Id) FROM badges WHERE Name = 'Commentator' AND STRFTIME('%Y', Date) = '2014'	SELECT COUNT(DISTINCT UserId) FROM badges WHERE Name = 'Commentator' AND STRFTIME('%Y', Date) = '2014'	lack distinct	1	0
642	How many posts were created on 21st July, 2010?	SELECT COUNT(id) FROM postHistory WHERE date(CreationDate) = '2010-07-21'	SELECT COUNT(*) FROM posts WHERE date(CreaionDate) = '2010-07-21'	semantic error: wrong table	1	0
649	Describe the post history counts and last edit date of the post title "What is the best introductory Bayesian statistics textbook?"	SELECT T1.Id, T2.LastEditDate FROM postHistory AS T1 INNER JOIN posts AS T2 ON T1.PostId = T2.Id WHERE T2.Title = 'What is the best introductory Bayesian statistics textbook?'	SELECT T2.Id, T2.LastEditDate, count(*) FROM postHistory AS T1 INNER JOIN posts AS T2 ON T1.PostId = T2.Id WHERE T2.Title = 'What is the best introductory Bayesian statistics textbook?' GROUP BY T2.Id	semantic error: output column	0	0
650	Describe the last accessed date and location of the users who received the outliers badge.	SELECT T1.LastAccessDate, T1.Location FROM users AS T1 INNER JOIN badges AS T2 ON T1.Id = T2.UserId WHERE T2.Name = 'outliers'	SELECT LastAccessDate, Location FROM users WHERE Id IN (SELECT UserId FROM badges WHERE Name = 'outliers');	join -> in-sub	0	1
653	What is the owner's display name of the most popular post?	SELECT DisplayName FROM users WHERE Id = (SELECT OwnerUserId FROM posts ORDER BY ViewCount DESC LIMIT 1)	SELECT DisplayName FROM users WHERE Id IN (SELECT OwnerUserId FROM posts WHERE ViewCount = (SELECT MAX(ViewCount) FROM posts))	limit 1	1	0
654	Mention the display name and location of the user who owned the excerpt post with hypothesis-testing tag.	SELECT T3.DisplayName, T3.Location FROM tags AS T1 INNER JOIN posts AS T2 ON T1.ExcerptPostId = T2.Id INNER JOIN users AS T3 ON T3.Id = T2.OwnerUserId WHERE T1.TagName = 'hypothesis-testing'	SELECT DisplayName, Location FROM users WHERE Id IN (SELECT OwnerUserId FROM posts WHERE Id IN (SELECT ExcerptPostId FROM tags WHERE TagName = 'hypothesis-testing'));	join -> in-sub	0	1
656	Describe the display name of the parent ID for child post with the highest score.	SELECT DisplayName FROM users WHERE Id = (SELECT OwnerUserId FROM posts WHERE ParentId IS NOT NULL ORDER BY Score DESC LIMIT 1)	SELECT DisplayName FROM users WHERE Id IN (SELECT OwnerUserId FROM posts WHERE Id IN (SELECT ParentId FROM posts WHERE Score = (SELECT MAX(Score) FROM posts WHERE ParentId IS NOT NULL)))	limit 1	0	0
657	Under the vote type of 8, provide the display names and websites URLs of the user who got the highest bounty amount.	SELECT DisplayName, WebsiteUrl FROM users WHERE Id = (SELECT UserId FROM votes WHERE VoteTypeId = 8 ORDER BY BountyAmount DESC LIMIT 1)	SELECT DisplayName, WebsiteUrl FROM users WHERE Id IN (SELECT UserId FROM votes WHERE VoteTypeId = 8 AND BountyAmount = (SELECT MAX(BountyAmount) FROM votes WHERE VoteTypeId = 8));	limit 1	0	1

658	What are the titles of the top 5 posts with the highest popularity?	SELECT Title FROM posts ORDER BY ViewCount DESC LIMIT 5	WITH top AS (SELECT ViewCount FROM posts ORDER BY ViewCount DESC LIMIT 5) SELECT Title FROM posts WHERE ViewCount IN top	limit n	1	0
662	How many posts with votes that were created in 2011 have a bounty of 50?	SELECT COUNT(T1.Id) FROM posts AS T1 INNER JOIN votes AS T2 ON T1.Id = T2.PostId WHERE T2.BountyAmount = 50 AND STRFTIME('%Y', T2.CreationDate) = '2011'	SELECT COUNT(DISTINCT T1.PostId) FROM votes T1 JOIN posts T2 ON T1.PostId = T2.Id WHERE strftime('%Y', T1.CreationDate) = '2011' AND T1.BountyAmount = 50 HAVING COUNT(T1.PostId) > 0;	lack distinct	0	1
666	Among the posts that were voted by user 1465, what is the id of the most valuable post?	SELECT T2.Id FROM votes AS T1 INNER JOIN posts AS T2 ON T1.PostId = T2.Id WHERE T1.UserId = 1465 ORDER BY T2.FavoriteCount DESC LIMIT 1	WITH T AS (SELECT Id, FavoriteCount FROM posts WHERE Id IN (SELECT PostId FROM votes WHERE UserId = 1465)) SELECT Id FROM T WHERE FavoriteCount = (SELECT MAX(FavoriteCount) FROM T)	limit 1	1	0
667	What is the title of the post with the oldest post link?	SELECT T1.Title FROM posts AS T1 INNER JOIN postLinks AS T2 ON T2.PostId = T1.Id ORDER BY T1.CreationDate LIMIT 1	SELECT Title FROM posts WHERE Id IN (SELECT PostId FROM postLinks WHERE CreationDate = (SELECT MIN(CreationDate) FROM postLinks));	limit 1	0	1
668	What is the display name of the user who acquired the highest amount of badges?	SELECT T1.DisplayName FROM users AS T1 INNER JOIN badges AS T2 ON T1.Id = T2.UserId GROUP BY T1.DisplayName ORDER BY COUNT(T1.Id) DESC LIMIT 1	SELECT T2.DisplayName FROM (SELECT UserId, COUNT(*) as BadgeCount FROM badges GROUP BY UserId) as T1 JOIN users as T2 ON T1.UserId = T2.Id WHERE T1.BadgeCount = (SELECT MAX(BadgeCount) FROM (SELECT UserId, COUNT(*) as BadgeCount FROM badges GROUP BY UserId) as T3)	limit 1	0	1
669	When did 'chl' cast its first vote in a post?	SELECT T2.CreationDate FROM users AS T1 INNER JOIN votes AS T2 ON T1.Id = T2.UserId WHERE T1.DisplayName = 'chl' ORDER BY T2.CreationDate LIMIT 1	SELECT MIN(v.CreationDate) FROM votes v JOIN users u ON v.UserId = u.Id WHERE u.DisplayName = 'chl' GROUP BY u.Id	semantic error	1	0
670	What is the date when the youngest user made his or her first post?	SELECT T2.CreationDate FROM users AS T1 INNER JOIN posts AS T2 ON T1.Id = T2.OwnerUserId WHERE T1.Age IS NOT NULL ORDER BY T1.Age, T2.CreationDate LIMIT 1	SELECT MIN(CreationDate) FROM posts WHERE OwnerUserId IN (SELECT Id FROM users WHERE Age = (SELECT MIN(Age) FROM users))	limit n	0	0
671	What is the display name of the user who acquired the first Autobiographer badge?	SELECT T1.DisplayName FROM users AS T1 INNER JOIN badges AS T2 ON T1.Id = T2.UserId WHERE T2.Name = 'Autobiographer' ORDER BY T2.Date LIMIT 1	SELECT DisplayName FROM users WHERE Id IN (SELECT UserId FROM badges WHERE Name = 'Autobiographer' AND Date = (SELECT MIN(Date) FROM badges WHERE Name = 'Autobiographer'))	limit 1	1	0
672	Among the users located in United Kingdom, how many users whose post have a total favorite amount of 4 or more?	SELECT COUNT(T1.Id) FROM users AS T1 INNER JOIN posts AS T2 ON T1.Id = T2.OwnerUserId WHERE T1.Location = 'United Kingdom' AND T2.FavoriteCount >= 4	SELECT COUNT(DISTINCT T1.Id) FROM users T1 JOIN posts T2 ON T1.Id = T2.OwnerUserId WHERE T1.Location = 'United Kingdom' AND T2.FavoriteCount >= 4;	lack distinct	0	1
673	What is the average number of posts voted by the oldest users?	SELECT AVG(PostId) FROM votes WHERE UserId IN (SELECT Id FROM users WHERE Age = (SELECT MAX(Age) FROM users))	SELECT AVG(post_count) FROM (SELECT COUNT(DISTINCT T2.PostId) AS post_count FROM users T1 LEFT JOIN votes T2 ON T1.Id = T2.UserId WHERE T1.Age = (SELECT MAX(Age) FROM users) GROUP BY T2.UserId)	semantic error	1	0
678	Which post by Harvey Motulsky has the most views? Please give the id and title of this post.	SELECT T2.Id, T2.Title FROM users AS T1 INNER JOIN posts AS T2 ON T1.Id = T2.OwnerUserId WHERE T1.DisplayName = 'Harvey Motulsky' ORDER BY T2.ViewCount DESC LIMIT 1	SELECT P.Id, P.Title FROM posts P WHERE P.OwnerUserId IN (SELECT Id FROM users WHERE DisplayName = 'Harvey Motulsky') AND P.ViewCount = (SELECT MAX(ViewCount) FROM posts WHERE OwnerUserId IN (SELECT Id FROM users WHERE DisplayName = 'Harvey Motulsky'))	limit 1	1	0

679	Which post has the highest score? Please give its id and title's name.	SELECT T1.Id, T2.Title FROM users AS T1 INNER JOIN posts AS T2 ON T1.Id = T2.OwnerUserId ORDER BY T2.Score DESC LIMIT 1	SELECT Id, Title FROM posts WHERE Score = (SELECT MAX(Score) FROM posts WHERE Score IS NOT NULL);	limit 1	0	1
681	Please list the users' display names whose posts had over 20000 views in 2011.	SELECT T1.DisplayName FROM users AS T1 INNER JOIN posts AS T2 ON T1.Id = T2.OwnerUserId WHERE STRFTIME('%Y', T2.CreationDate) = '2011' AND T2.ViewCount > 20000	SELECT DisplayName FROM users WHERE Id IN (SELECT OwnerUserId FROM posts WHERE ViewCount > 20000 AND strftime('%Y', CreationDate) = '2011')	join -> in-sub	0	0
682	Which is the most valuable post in 2010? Please give its id and the owner's display name.	SELECT T2.OwnerUserId, T1.DisplayName FROM users AS T1 INNER JOIN posts AS T2 ON T1.Id = T2.OwnerUserId WHERE STRFTIME('%Y', T1.CreationDate) = '2010' ORDER BY T2.FavoriteCount DESC LIMIT 1	SELECT P.Id, U.DisplayName FROM posts P JOIN users U ON P.OwnerUserId = U.Id WHERE P.FavoriteCount = (SELECT MAX(FavoriteCount) FROM posts WHERE strftime('%Y', CreationDate) = '2010') AND strftime('%Y', CreationDate) = '2010';	limit 1	0	1
685	Identify the total views on the post 'Computer Game Datasets'. Name the user who posted it last time.	join -> in-sub	SELECT posts.ViewCount, users.DisplayName FROM posts JOIN users on posts.LastEditorUserId = users.Id WHERE posts.Id IN (SELECT PostId FROM postHistory WHERE Text = 'Computer Game Datasets')		1	0
686	Identify the total number of posts with views above average.	SELECT Id FROM posts WHERE ViewCount > (SELECT AVG(ViewCount) FROM posts)	SELECT COUNT(*) FROM posts WHERE ViewCount > (SELECT AVG(ViewCount) FROM posts WHERE ViewCount IS NOT NULL);		1	0
687	How many comments were added to the post with the highest score?	SELECT COUNT(T2.Id) FROM posts AS T1 INNER JOIN comments AS T2 ON T1.Id = T2.PostId GROUP BY T1.Id ORDER BY SUM(T1.Score) DESC LIMIT 1	SELECT COUNT(c.Id) FROM comments c JOIN posts p ON c.PostId = p.Id WHERE p.Score = (SELECT MAX(Score) FROM posts);	limit 1	0	1
689	Identify the display name and location of the user, who was the last to edit the post with ID 183.	SELECT T2.DisplayName, T2.Location FROM posts AS T1 INNER JOIN users AS T2 ON T1.OwnerUserId = T2.Id WHERE T1.Id = 183 ORDER BY T1.LastEditDate DESC LIMIT 1	SELECT T2.DisplayName, T2.Location FROM posts T1 JOIN users T2 ON T1.LastEditorUserId = T2.Id WHERE T1.Id = 183;	semantic error: wrong condition	0	1
690	Identify the latest badge awarded to the user with the display name Emmett.	SELECT T1.Name FROM badges AS T1 INNER JOIN users AS T2 ON T1.UserId = T2.Id WHERE T2.DisplayName = 'Emmett' ORDER BY T1.Date DESC LIMIT 1	WITH T AS (SELECT T1.Name, T1.Date FROM badges AS T1 INNER JOIN users AS T2 ON T1.UserId = T2.Id WHERE T2.DisplayName = 'Emmett') SELECT Name FROM T WHERE Date = (SELECT MAX(Date) FROM T)	limit 1	1	0
693	Identify the number of posts and comments left by the user, who has the latest created user account.	SELECT COUNT(T2.Id) FROM users AS T1 INNER JOIN posts AS T2 ON T1.Id = T2.OwnerUserId INNER JOIN comments AS T3 ON T3.PostId = T2.Id ORDER BY T1.CreationDate DESC LIMIT 1	SELECT COUNT(DISTINCT P.Id) AS NumberOfPosts, COUNT(DISTINCT C.Id) AS NumberOfComments FROM users U JOIN posts P ON U.Id = P.OwnerUserId JOIN comments C ON U.Id = C.UserId WHERE U.CreationDate = (SELECT MAX(CreationDate) FROM users)	limit 1	0	1
694	Provide the text of the latest 10 comments to the post with the title 'Analysing wind data with R' and the display name of the user who left it.	SELECT T3.Text, T1.DisplayName FROM users AS T1 INNER JOIN posts AS T2 ON T1.Id = T2.OwnerUserId INNER JOIN comments AS T3 ON T2.Id = T3.PostId WHERE T2.Title = 'Analysing wind data with R' AND T3.CreationDate = (SELECT MAX(T4.CreationDate) FROM users AS T5 INNER JOIN posts AS T6 ON T5.Id = T6.OwnerUserId INNER JOIN comments AS T4 ON T6.Id = T4.PostId WHERE T6.Title = 'Analysing wind data with R')	SELECT T3.Text, T1.DisplayName FROM users AS T1 INNER JOIN posts AS T2 ON T1.Id = T2.OwnerUserId INNER JOIN comments AS T3 ON T2.Id = T3.PostId WHERE T2.Title = 'Analysing wind data with R' AND T3.Id IN (SELECT ID FROM (SELECT T4.ID, rank() over (ORDER BY T4.CreationDate DESC) as rk FROM users AS T5 INNER JOIN posts AS T6 ON T5.Id = T6.OwnerUserId INNER JOIN comments AS T4 ON T6.Id = T4.PostId WHERE T6.Title = 'Analysing wind data with R') WHERE rk <= 10)	semantic error: latest 10	1	0

695	How many users were awarded with 'Citizen Patrol' badge?	SELECT COUNT(id) FROM badges WHERE 'Name' = 'Citizen Patrol'	SELECT COUNT(DISTINCT UserId) FROM badges WHERE Name = 'Citizen Patrol' GROUP BY Name;	lack distinct; semantic error	0	1
696	Count the number of posts with a tag specified as 'careers'.	SELECT COUNT(Id) FROM tags WHERE TagName = 'careers'	SELECT COUNT(DISTINCT ExcerptPostId) FROM tags WHERE TagName = 'careers'	lack distinct; semantic error	1	0
700	Identify the number of posts that offer a bounty amount over 30.	SELECT COUNT(id) FROM votes WHERE BountyAmount >= 30	SELECT COUNT(DISTINCT PostId) FROM votes WHERE BountyAmount >= 30 AND PostId IS NOT NULL;	lack distinct; semantic error	0	1
705	Give the user's reputation and up vote number of the user that commented "fine, you win :)".	SELECT T2.Reputation, T2.UpVotes FROM comments AS T1 INNER JOIN users AS T2 ON T1.UserId = T2.Id WHERE T1.Text = 'fine, you win :)'	SELECT Reputation, UpVotes FROM users WHERE Id IN (SELECT UserId FROM comments WHERE Text = 'fine, you win :)')	join -> in-sub	1	0
707	Among the posts with views ranging from 100 to 150, what is the comment with the highest score?	SELECT Text FROM comments WHERE PostId IN (SELECT Id FROM posts WHERE ViewCount BETWEEN 100 AND 150) ORDER BY Score DESC LIMIT 1	WITH scores AS (SELECT Text, Score FROM comments WHERE PostId IN (SELECT Id FROM posts WHERE ViewCount >= 100 AND ViewCount <= 150)) SELECT Text FROM scores WHERE Score = (SELECT MAX(Score) FROM scores)	limit 1	1	0
708	List the creation date and age of the user that commented with website.	SELECT T2.CreationDate, T2.Age FROM comments AS T1 INNER JOIN users AS T2 ON T1.UserId = T2.Id WHERE T1.text LIKE '%http://%'	SELECT U.CreationDate, U.Age FROM users U WHERE EXISTS (SELECT 1 FROM comments C WHERE C.UserId = U.Id AND C.Text LIKE '%http://%')	join -> in-sub	0	1
709	In comments with 0 score, how many of the posts have view count lower than 5?	SELECT COUNT(T1.Id) FROM comments AS T1 INNER JOIN posts AS T2 ON T1.PostId = T2.Id WHERE T2.ViewCount < 5 AND T2.Score = 0	SELECT COUNT(DISTINCT T1.PostId) FROM comments T1 JOIN posts T2 ON T1.PostId = T2.Id WHERE T1.Score = 0 AND T2.ViewCount < 5;	semantic error	0	1
711	Among products comments with 0 score, what is the total number of users ages 40 years old?	SELECT COUNT(DISTINCT T1.id) FROM comments AS T1 INNER JOIN users AS T2 ON T1.UserId = T2.Id WHERE T1.Score = 0 AND T2.Age = 40	SELECT COUNT(DISTINCT T1.UserId) FROM comments T1 JOIN users T2 ON T1.UserId = T2.Id WHERE T1.Score = 0 AND T2.Age = 40;	semantic error: output column	0	1
713	What is the up vote number of the user that commented "R is also lazy evaluated."?	SELECT T2.UpVotes FROM comments AS T1 INNER JOIN users AS T2 ON T1.UserId = T2.Id WHERE T1.Text = 'R is also lazy evaluated.'	SELECT UpVotes FROM users WHERE Id IN (SELECT UserId FROM comments WHERE Text = 'R is also lazy evaluated.')	join -> in-sub	1	0
716	Among the comments with scores between 5 to 10, what is the percentage of the users with 0 up votes?	SELECT CAST(SUM(IIF(T1.UpVotes = 0, 1, 0)) AS REAL) * 100/ COUNT(T1.Id) AS per FROM users AS T1 INNER JOIN comments AS T2 ON T1.Id = T2.UserId WHERE T2.Score BETWEEN 5 AND 10	SELECT (COUNT(DISTINCT T1.UserId) * 100.0 / (SELECT COUNT(DISTINCT UserId) FROM comments WHERE Score BETWEEN 5 AND 10)) AS Percentage FROM comments T1 JOIN users T2 ON T1.UserId = T2.Id WHERE T1.Score BETWEEN 5 AND 10 AND T2.UpVotes = 0;	lack distinct	0	1
717	Please list all the superpowers of 3-D Man.	SELECT T3.power_name FROM superhero AS T1 INNER JOIN hero_power AS T2 ON T1.id = T2.hero_id INNER JOIN superpower AS T3 ON T2.power_id = T3.id WHERE T1.superhero_name = '3-D Man'	SELECT power_name FROM superpower WHERE id IN (SELECT T2.power_id FROM hero_power T2 INNER JOIN superhero T1 ON T1.id = T2.hero_id WHERE T1.superhero_name = '3-D Man');	join -> in-sub?	0	1
718	How many superheroes have the super power of "Super Strength"?	SELECT COUNT(T1.hero_id) FROM hero_power AS T1 INNER JOIN superpower AS T2 ON T1.power_id = T2.id WHERE T2.power_name = 'Super Strength'	SELECT COUNT(DISTINCT T1.hero_id) FROM hero_power AS T1 JOIN superpower AS T2 ON T1.power_id = T2.id WHERE T2.power_name = 'Super Strength';	lack distinct	0	1
719	Among the superheroes with the super power of "Super Strength", how many of them have a height of over 200cm?	SELECT COUNT(T1.id) FROM superhero AS T1 INNER JOIN hero_power AS T2 ON T1.id = T2.hero_id INNER JOIN superpower AS T3 ON T2.power_id = T3.id WHERE T3.power_name = 'Super Strength' AND T1.height_cm > 200	SELECT COUNT(DISTINCT T3.id) FROM superhero T3 JOIN hero_power T2 ON T3.id = T2.hero_id JOIN superpower T1 ON T2.power_id = T1.id WHERE T1.power_name = 'Super Strength' AND T3.height_cm > 200;	lack distinct	0	1

720	Please list the full names of all the superheroes with over 15 super powers.	SELECT DISTINCT T1.full_name FROM superhero AS T1 INNER JOIN hero_power AS T2 ON T1.id = T2.hero_id GROUP BY T1.full_name HAVING COUNT(T2.power_id) > 15	SELECT s.full_name FROM superhero s JOIN (SELECT hero_id FROM hero_power GROUP BY hero_id HAVING COUNT(hero_id) > 15) hp ON s.id = hp.hero_id;	distinct non-key	0	1
723	Among the superheroes with blue eyes, how many of them have the super power of "Agility"?	SELECT COUNT(T1.id) FROM superhero AS T1 INNER JOIN hero_power AS T2 ON T1.id = T2.hero_id INNER JOIN superpower AS T3 ON T2.power_id = T3.id INNER JOIN colour AS T4 ON T1.eye_colour_id = T4.id WHERE T3.power_name = 'Agility' AND T4.colour = 'Blue'	SELECT COUNT(DISTINCT T1.id) FROM superhero AS T1 JOIN colour AS T2 ON T1.eye_colour_id = T2.id JOIN hero_power AS T3 ON T1.id = T3.hero_id JOIN superpower AS T4 ON T3.power_id = T4.id WHERE T2.colour = 'Blue' AND T4.power_name = 'Agility';	lack distinct	0	1
726	Rank heroes published by Marvel Comics by their height in descending order.	SELECT superhero_name, height_cm, RANK() OVER (ORDER BY height_cm DESC) AS HeightRank FROM superhero INNER JOIN publisher ON superhero.publisher_id = publisher.id WHERE publisher.publisher_name = 'Marvel Comics'	SELECT superhero_name FROM superhero JOIN publisher ON superhero.publisher_id = publisher.id WHERE publisher_name = 'Marvel Comics' ORDER BY height_cm DESC;	semantic error: output col	0	0
728	Rank superheroes from Marvel Comics by their eye color popularity, starting with the most common color.	SELECT colour.colour AS EyeColor, COUNT(superhero.id) AS Count, RANK() OVER (ORDER BY COUNT(superhero.id) DESC) AS PopularityRank FROM superhero INNER JOIN colour ON superhero.eye_colour_id = colour.id INNER JOIN publisher ON superhero.publisher_id = publisher.id WHERE publisher.publisher_name = 'Marvel Comics' GROUP BY colour.colour	SELECT T3.colour, COUNT(T1.id) AS popularity FROM superhero T1 JOIN publisher T2 ON T1.publisher_id = T2.id JOIN colour T3 ON T1.eye_colour_id = T3.id WHERE T2.publisher_name = 'Marvel Comics' GROUP BY T3.colour ORDER BY popularity DESC;	semantic error: output col	0	1
732	Which publisher published the slowest superhero?	SELECT T2.publisher_name FROM superhero AS T1 INNER JOIN publisher AS T2 ON T1.publisher_id = T2.id INNER JOIN hero_attribute AS T3 ON T1.id = T3.hero_id INNER JOIN attribute AS T4 ON T3.attribute_id = T4.id WHERE T4.attribute_name = 'Speed' ORDER BY T3.attribute_value LIMIT 1	SELECT publisher_name FROM publisher WHERE id IN (SELECT publisher_id FROM (SELECT T1.publisher_id, rank() over (ORDER BY T3.attribute_value) as rk FROM superhero AS T1 INNER JOIN hero_attribute AS T3 ON T1.id = T3.hero_id INNER JOIN attribute AS T4 ON T3.attribute_id = T4.id WHERE T4.attribute_name = 'Speed') WHERE rk = 1)	limit 1; join -> in-sub	1	0
739	What are the names of the superheroes with the power of death touch?	SELECT T1.superhero_name FROM superhero AS T1 INNER JOIN hero_power AS T2 ON T1.id = T2.hero_id INNER JOIN superpower AS T3 ON T2.power_id = T3.id WHERE T3.power_name = 'Death Touch'	SELECT superhero_name FROM superhero WHERE id IN (SELECT hero_id FROM hero_power WHERE power_id IN (SELECT id FROM superpower WHERE power_name = 'Death Touch'));	join -> in-sub	0	1
741	What is the name of the superhero that has the most powers?	SELECT T1.superhero_name FROM superhero AS T1 INNER JOIN hero_power AS T2 ON T1.id = T2.hero_id GROUP BY T1.superhero_name ORDER BY COUNT(T2.hero_id) DESC LIMIT 1	SELECT superhero_name FROM (SELECT T1.superhero_name, rank() over (ORDER BY COUNT(T2.hero_id) DESC) as rk FROM superhero AS T1 LEFT JOIN hero_power AS T2 ON T1.id = T2.hero_id GROUP BY T1.id) WHERE rk = 1	limit 1; group by non-key	0	0
743	What is the percentage of superheroes who act in their own self-interest or make decisions based on their own moral code? Indicate how many of the said superheroes were published by Marvel Comics.	SELECT (CAST(COUNT(*) AS REAL) * 100 / (SELECT COUNT(*) FROM superhero)), CAST(SUM(CASE WHEN T2.publisher_name = 'Marvel Comics' THEN 1 ELSE 0 END) AS REAL) FROM superhero AS T1 INNER JOIN publisher AS T2 ON T1.publisher_id = T2.id INNER JOIN alignment AS T3 ON T3.id = T1.alignment_id WHERE T3.alignment = 'Bad'	SELECT (COUNT(*) * 100.0 / (SELECT COUNT(*) FROM superhero)) AS percentage_bad, COUNT(CASE WHEN T3.publisher_name = 'Marvel Comics' THEN 1 END) AS marvel_bad_count FROM superhero T1 INNER JOIN alignment T2 ON T1.alignment_id = T2.id INNER JOIN publisher T3 ON T1.publisher_id = T3.id WHERE T2.alignment = 'Bad';	semantic error: 0 vs none	0	1

749	Provide the superpowers of the superhero called Deathlok.	SELECT T3.power_name FROM superhero AS T1 INNER JOIN hero_power AS T2 ON T1.id = T2.hero_id INNER JOIN superpower AS T3 ON T2.power_id = T3.id WHERE T1.superhero_name = 'Deathlok'	SELECT power_name FROM superpower WHERE id IN (SELECT power_id FROM hero_power JOIN superhero ON hero_power.hero_id = superhero.id WHERE superhero_name = 'Deathlok');	join -> in-sub?	0	1
751	List down at least five superpowers of male superheroes.	SELECT T3.power_name FROM superhero AS T1 INNER JOIN hero_power AS T2 ON T1.id = T2.hero_id INNER JOIN superpower AS T3 ON T3.id = T2.power_id INNER JOIN gender AS T4 ON T4.id = T1.gender_id WHERE T4.gender = 'Male' LIMIT 5	SELECT power_name FROM superpower WHERE id IN (SELECT T2.power_id FROM superhero AS T1 INNER JOIN hero_power AS T2 ON T1.id = T2.hero_id INNER JOIN gender AS T3 ON T3.id = T1.gender_id WHERE T3.gender = 'Male') LIMIT 5	join -> in-sub	1	0
753	Among the superheroes with height from 170 to 190, list the names of the superheroes with no eye color.	SELECT DISTINCT T1.superhero_name FROM superhero AS T1 INNER JOIN colour AS T2 ON T1.eye_colour_id = T2.id WHERE T1.height_cm BETWEEN 170 AND 190 AND T2.colour = 'No Colour'	SELECT T1.superhero_name FROM superhero AS T1 INNER JOIN colour AS T2 ON T1.eye_colour_id = T2.id WHERE T1.height_cm BETWEEN 170 AND 190 AND T2.colour = 'No Colour'	redundant distinct	1	0
758	Provide the hair colour of the human superhero who is 185 cm tall.	SELECT DISTINCT T3.colour FROM superhero AS T1 INNER JOIN race AS T2 ON T1.race_id = T2.id INNER JOIN colour AS T3 ON T1.hair_colour_id = T3.id WHERE T1.height_cm = 185 AND T2.race = 'Human'	SELECT T3.colour FROM superhero AS T1 INNER JOIN race AS T2 ON T1.race_id = T2.id INNER JOIN colour AS T3 ON T1.hair_colour_id = T3.id WHERE T1.height_cm = 185 AND T2.race = 'human';	str: 'human'; redundant distinct	1	0
759	What is the eye colour of the heaviest superhero?	SELECT T2.colour FROM superhero AS T1 INNER JOIN colour AS T2 ON T1.eye_colour_id = T2.id ORDER BY T1.weight_kg DESC LIMIT 1	SELECT colour FROM (SELECT T2.colour, rank() over (ORDER BY T1.weight_kg DESC) as rk FROM superhero AS T1 INNER JOIN colour AS T2 ON T1.eye_colour_id = T2.id) WHERE rk = 1	limit 1	1	0
762	Which power do superheroes have the most of?	SELECT T2.power_name FROM hero_power AS T1 INNER JOIN superpower AS T2 ON T1.power_id = T2.id GROUP BY T2.power_name ORDER BY COUNT(T1.hero_id) DESC LIMIT 1	SELECT power_name FROM superpower WHERE id IN (SELECT power_id FROM hero_power GROUP BY power_id HAVING COUNT(power_id) = (SELECT MAX(cnt) FROM (SELECT COUNT(power_id) as cnt FROM hero_power GROUP BY power_id)));	limit 1	0	1
764	What are the superpowers of heroes with ID 1?	SELECT DISTINCT T2.power_name FROM hero_power AS T1 INNER JOIN superpower AS T2 ON T1.power_id = T2.id WHERE T1.hero_id = 1	SELECT T2.power_name FROM hero_power AS T1 JOIN superpower AS T2 ON T1.power_id = T2.id WHERE T1.hero_id = 1;	redundant distinct; schema flaw: lack pk hero_power(hero_id, power_id)	0	1
765	How many heroes have stealth power?	SELECT COUNT(T1.hero_id) FROM hero_power AS T1 INNER JOIN superpower AS T2 ON T1.power_id = T2.id WHERE T2.power_name = 'Stealth'	SELECT COUNT(DISTINCT T2.hero_id) FROM superpower T1 JOIN hero_power T2 ON T1.id = T2.power_id WHERE T1.power_name = 'Stealth';	schema flaw: lack pk hero_power(hero_id, power_id); lack distinct	0	1
771	List the name of superheroes with flight power.	SELECT T1.superhero_name FROM superhero AS T1 INNER JOIN hero_power AS T2 ON T1.id = T2.hero_id INNER JOIN superpower AS T3 ON T2.power_id = T3.id WHERE T3.power_name = 'Flight'	SELECT superhero_name FROM superhero WHERE id IN (SELECT hero_id FROM hero_power WHERE power_id IN (SELECT id FROM superpower WHERE power_name = 'Flight'));	join -> in-sub	0	1
778	Provide superheroes' names who have the adaptation power.	SELECT T1.superhero_name FROM superhero AS T1 INNER JOIN hero_power AS T2 ON T1.id = T2.hero_id INNER JOIN superpower AS T3 ON T2.power_id = T3.id WHERE T3.power_name = 'Adaptation'	SELECT superhero_name FROM superhero WHERE id IN (SELECT hero_id FROM hero_power WHERE power_id IN (SELECT id FROM superpower WHERE power_name = 'Adaptation'));	join -> in-sub	0	1
779	How many powers does Amazo hero have?	SELECT COUNT(T1.power_id) FROM hero_power AS T1 INNER JOIN superhero AS T2 ON T1.hero_id = T2.id WHERE T2.superhero_name = 'Amazo'	SELECT COUNT(DISTINCT power_id) FROM hero_power WHERE hero_id IN (SELECT id FROM superhero WHERE superhero_name = 'Amazo');	lack distinct	0	1
780	List the powers of Hunter Zolomon.	SELECT T3.power_name FROM superhero AS T1 INNER JOIN hero_power AS T2 ON T1.id = T2.hero_id INNER JOIN superpower AS T3 ON T2.power_id = T3.id WHERE T1.full_name = 'Hunter Zolomon'	SELECT power_name FROM superpower WHERE id IN (SELECT HP.power_id FROM hero_power HP JOIN superhero SH ON HP.hero_id = SH.id WHERE SH.full_name = 'Hunter Zolomon');	join -> in-sub?	0	1
786	How many heroes have the highest attribute value in strength?	SELECT COUNT(T1.hero_id) FROM hero_attribute AS T1 INNER JOIN attribute AS T2 ON T1.attribute_id = T2.id WHERE T2.attribute_name = 'Strength' AND T1.attribute_value = (SELECT MAX(attribute_value) FROM hero_attribute)	SELECT COUNT(DISTINCT T1.hero_id) FROM hero_attribute AS T1 JOIN attribute AS T2 ON T1.attribute_id = T2.id WHERE T2.attribute_name = 'Strength' AND T1.attribute_value = (SELECT MAX(T3.attribute_value) FROM hero_attribute AS T3 JOIN attribute AS T4 ON T3.attribute_id = T4.id WHERE T4.attribute_name = 'Strength')	semantic error: sub-query condition	0	1

790	Calculate the difference between Emil Blonsky's weight and Charles Chandler's weight.	SELECT (SELECT weight_kg FROM superhero WHERE full_name LIKE 'Emil Blonsky') - (SELECT weight_kg FROM superhero WHERE full_name LIKE 'Charles Chandler') AS CALCULATE	SELECT (SELECT SUM(weight_kg) FROM superhero WHERE full_name = 'Emil Blonsky') - (SELECT SUM(weight_kg) FROM superhero WHERE full_name = 'Charles Chandler') AS weight_difference FROM superhero LIMIT 1;	semantic error: fullname condition	0	1
792	What is Abomination's superpower?	SELECT T3.power_name FROM superhero AS T1 INNER JOIN hero_power AS T2 ON T1.id = T2.hero_id INNER JOIN superpower AS T3 ON T2.power_id = T3.id WHERE T1.superhero_name = 'Abomination'	SELECT power_name FROM superpower WHERE id IN (SELECT power_id FROM hero_power JOIN superhero ON superhero.id = hero_power.hero_id WHERE superhero_name = 'Abomination');	join -> in-sub?	0	1
794	Which hero was the fastest?	SELECT T1.superhero_name FROM superhero AS T1 INNER JOIN hero_attribute AS T2 ON T1.id = T2.hero_id INNER JOIN attribute AS T3 ON T2.attribute_id = T3.id WHERE T3.attribute_name = 'Speed' ORDER BY T2.attribute_value DESC LIMIT 1	SELECT T1.superhero_name FROM superhero AS T1 WHERE id IN (SELECT hero_id FROM (SELECT T2.hero_id, rank() over (ORDER BY T2.attribute_value DESC) as rk FROM hero_attribute AS T2 INNER JOIN attribute AS T3 ON T2.attribute_id = T3.id WHERE T3.attribute_name = 'Speed') WHERE rk = 1)	limit 1	0	0
795	How many superheroes have a neutral alignment?	SELECT COUNT(T1.id) FROM superhero AS T1 INNER JOIN alignment AS T2 ON T1.alignment_id = T2.id WHERE T2.alignment = 'Neutral'	SELECT COUNT(*) FROM superhero WHERE alignment_id = 3;	semantic error: wrong condition	0	1
803	What is the power ID of cryokinesis?	SELECT id FROM superpower WHERE power_name = 'Cryokinesis'	SELECT id FROM superpower WHERE power_name = 'cryokinesis'	str: 'cryokinesis'	1	0
805	List the full names of superheroes with missing weight.	SELECT DISTINCT full_name FROM superhero WHERE full_name IS NOT NULL AND (weight_kg IS NULL OR weight_kg = 0)	SELECT full_name FROM superhero WHERE weight_kg IS NULL OR weight_kg = 0;	redundant distinct	0	1
807	What is the superpowers of the superhero has Helen Parr as their full name?	SELECT T3.power_name FROM superhero AS T1 INNER JOIN hero_power AS T2 ON T1.id = T2.hero_id INNER JOIN superpower AS T3 ON T2.power_id = T3.id WHERE T1.full_name = 'Helen Parr'	SELECT power_name FROM superpower WHERE id IN (SELECT T2.power_id FROM superhero AS T1 INNER JOIN hero_power AS T2 ON T1.id = T2.hero_id WHERE T1.full_name = 'Helen Parr')	join -> in-sub?	1	0
808	Find the race of the superhero who weighs 108kg and is 188cm tall.	SELECT DISTINCT T2.race FROM superhero AS T1 INNER JOIN race AS T2 ON T1.race_id = T2.id WHERE T1.weight_kg = 108 AND T1.height_cm = 188	SELECT T2.race FROM superhero T1 JOIN race T2 ON T1.race_id = T2.id WHERE T1.weight_kg = 108 AND T1.height_cm = 188;	redundant distinct	0	1
810	What is the race of the superhero with maximum attribute value?	SELECT T3.race FROM superhero AS T1 INNER JOIN hero_attribute AS T2 ON T1.id = T2.hero_id INNER JOIN race AS T3 ON T1.race_id = T3.id WHERE T2.attribute_value = (SELECT MAX(T4.attribute_value) FROM hero_attribute AS T4)	SELECT race.race FROM race INNER JOIN (SELECT race_id FROM superhero WHERE id IN (SELECT hero_id FROM hero_attribute WHERE attribute_value = (SELECT MAX(attribute_value) FROM hero_attribute))) AS max_hero ON race.id = max_hero.race_id	join -> in-sub?	0	1
812	List down at least five full names of superheroes with blue eyes.	SELECT T1.superhero_name FROM superhero AS T1 INNER JOIN colour AS T2 ON T1.eye_colour_id = T2.id WHERE T2.colour = 'Blue' LIMIT 5	SELECT S.full_name FROM superhero S JOIN colour C ON S.eye_colour_id = C.id WHERE C.colour = 'Blue' LIMIT 5;	semantic error: output col	0	1
813	Calculate the average attribute value of all neutral superheroes.	SELECT AVG(T1.attribute_value) FROM hero_attribute AS T1 INNER JOIN superhero AS T2 ON T1.hero_id = T2.id INNER JOIN alignment AS T3 ON T2.alignment_id = T3.id WHERE T3.alignment = 'Neutral'	SELECT AVG(T2.attribute_value) AS average_attribute_value FROM superhero T1 JOIN hero_attribute T2 ON T1.id = T2.hero_id WHERE T1.alignment_id = 3 AND T2.attribute_value IS NOT NULL;	semantic error: wrong condition	0	1
814	List the skin colour of the superheroes with 100 attribute value.	SELECT DISTINCT T2.colour FROM superhero AS T1 INNER JOIN colour AS T2 ON T1.skin_colour_id = T2.id INNER JOIN hero_attribute AS T3 ON T1.id = T3.hero_id WHERE T3.attribute_value = 100	SELECT colour FROM (SELECT * FROM colour WHERE id IN (SELECT skin_colour_id FROM superhero WHERE id IN (SELECT hero_id FROM hero_attribute WHERE attribute_value = 100))) AS SubQuery;	join -> in-sub?	0	1
815	Count the good female superheroes.	SELECT COUNT(T1.id) FROM superhero AS T1 INNER JOIN alignment AS T2 ON T1.alignment_id = T2.id INNER JOIN gender AS T3 ON T1.gender_id = T3.id WHERE T2.alignment = 'Good' AND T3.gender = 'Female'	SELECT COUNT(T1.id) FROM superhero AS T1 WHERE T1.alignment_id = 1 and T1.gender_id = 2	semantic error: wrong condition	0	0

816	Provide the names of superheroes with attribute value between 75 to 80.	SELECT T1.superhero_name FROM superhero AS T1 INNER JOIN hero_attribute AS T2 ON T1.id = T2.hero_id WHERE T2.attribute_value BETWEEN 75 AND 80	SELECT superhero_name FROM superhero WHERE id IN (SELECT hero_id FROM hero_attribute WHERE attribute_value BETWEEN 75 AND 80);	join -> in-sub	0	1
818	Among the bad superheroes, what is the percentage of female superheroes?	SELECT CAST(COUNT(CASE WHEN T3.gender = 'Female' THEN T1.id ELSE NULL END) AS REAL) * 100 / COUNT(T1.id) FROM superhero AS T1 INNER JOIN alignment AS T2 ON T1.alignment_id = T2.id INNER JOIN gender AS T3 ON T1.gender_id = T3.id WHERE T2.alignment = 'Bad'	SELECT CAST(COUNT(CASE WHEN gender_id = 2 THEN 1 ELSE NULL END) AS REAL) * 100 / COUNT(id) FROM superhero WHERE alignment_id = 2	semantic error: wrong condition	1	0
819	In superheroes with missing weight data, calculate the difference between the number of superheroes with blue eyes and no eye color.	SELECT SUM(CASE WHEN T2.id = 7 THEN 1 ELSE 0 END) - SUM(CASE WHEN T2.id = 1 THEN 1 ELSE 0 END) FROM superhero AS T1 INNER JOIN colour AS T2 ON T1.eye_colour_id = T2.id WHERE T1.weight_kg = 0 OR T1.weight_kg IS NULL	SELECT (COUNT(*) FILTER (WHERE eye_colour_id = 7) - COUNT(*) FILTER (WHERE eye_colour_id = 1)) AS difference FROM superhero WHERE weight_kg = 0 OR weight_kg IS NULL;	semantic error: 0 vs None	0	1
821	List down Ajax's superpowers.	SELECT T3.power_name FROM superhero AS T1 INNER JOIN hero_power AS T2 ON T1.id = T2.hero_id INNER JOIN superpower AS T3 ON T2.power_id = T3.id WHERE T1.superhero_name = 'Ajax'	SELECT power_name FROM superpower WHERE id IN (SELECT HP.power_id FROM hero_power HP JOIN superhero SH ON HP.hero_id = SH.id WHERE SH.superhero_name = 'Ajax');	join -> in-sub?	0	1
824	Identify superheroes who can control wind and list their names in alphabetical order.	SELECT T1.superhero_name FROM superhero AS T1 INNER JOIN hero_power AS T2 ON T1.id = T2.hero_id INNER JOIN superpower AS T3 ON T2.power_id = T3.id WHERE T3.power_name = 'Wind Control' ORDER BY T1.superhero_name	SELECT superhero_name FROM superhero WHERE id IN (SELECT hero_id FROM hero_power WHERE power_id IN (SELECT id FROM superpower WHERE power_name = 'Wind Control')) ORDER BY superhero_name ASC;	join -> in-sub	0	1
825	Identify the gender of the superhero who has the ability of Phoenix Force.	SELECT T4.gender FROM superhero AS T1 INNER JOIN hero_power AS T2 ON T1.id = T2.hero_id INNER JOIN superpower AS T3 ON T2.power_id = T3.id INNER JOIN gender AS T4 ON T1.gender_id = T4.id WHERE T3.power_name = 'Phoenix Force'	SELECT T5.gender FROM (SELECT gender_id FROM superhero AS T2 WHERE T2.id IN (SELECT T3.hero_id FROM hero_power AS T3 INNER JOIN superpower AS T4 ON T3.power_id = T4.id WHERE T4.power_name = 'Phoenix Force')) AS T1 JOIN gender AS T5 ON T1.gender_id = T5.id	join -> in-sub?	1	0
826	Identify the heaviest superhero in DC Comics.	SELECT T1.superhero_name FROM superhero AS T1 INNER JOIN publisher AS T2 ON T1.publisher_id = T2.id WHERE T2.publisher_name = 'DC Comics' ORDER BY T1.weight_kg DESC LIMIT 1	SELECT superhero_name FROM superhero WHERE publisher_id IN (SELECT id FROM publisher WHERE publisher_name = 'DC Comics') AND weight_kg = (SELECT MAX(weight_kg) FROM superhero WHERE weight_kg IS NOT NULL AND weight_kg > 0 AND publisher_id IN (SELECT id FROM publisher WHERE publisher_name = 'DC Comics'))	limit 1	0	1
828	Count the fastest superheroes.	SELECT COUNT(T3.superhero_name) FROM hero_attribute AS T1 INNER JOIN attribute AS T2 ON T1.attribute_id = T2.id INNER JOIN superhero AS T3 ON T1.hero_id = T3.id WHERE T2.attribute_name = 'Speed' AND T1.attribute_value = (SELECT MAX(T4.attribute_value) FROM hero_attribute AS T4 INNER JOIN attribute AS T5 ON T4.attribute_id = T5.id WHERE T5.attribute_name = 'Speed')	SELECT COUNT(DISTINCT T3.id) FROM hero_attribute AS T1 INNER JOIN attribute AS T2 ON T1.attribute_id = T2.id INNER JOIN superhero AS T3 ON T1.hero_id = T3.id WHERE T2.attribute_name = 'Speed' AND T1.attribute_value = (SELECT MAX(T4.attribute_value) FROM hero_attribute AS T4 INNER JOIN attribute AS T5 ON T4.attribute_id = T5.id WHERE T5.attribute_name = 'Speed')	lack distinct; schema flaw: lack pk hero_attribute(hero_id, attribute_id)	0	0
830	Identify the weakest attribute of the Black Panther.	SELECT T3.attribute_name FROM superhero AS T1 INNER JOIN hero_attribute AS T2 ON T1.id = T2.hero_id INNER JOIN attribute AS T3 ON T2.attribute_id = T3.id WHERE T1.superhero_name = 'Black Panther' ORDER BY T2.attribute_value ASC LIMIT 1	SELECT attribute_name FROM attribute WHERE id IN (SELECT attribute_id FROM (SELECT hero_attribute.attribute_id, rank() over (ORDER BY hero_attribute.attribute_value) as rk FROM hero_attribute JOIN superhero ON superhero.id = hero_attribute.hero_id WHERE superhero.superhero_name = 'Black Panther') WHERE rk = 1)	limit 1	0	0

837	Give the hero ID of superhero with the lowest attribute value.	SELECT hero_id FROM hero attribute WHERE attribute_value = (SELECT MIN(attribute_value) FROM hero attribute)	SELECT DISTINCT hero_id FROM hero_attribute WHERE attribute_value = (SELECT MIN(attribute_value) FROM hero attribute)	lack distinct	1	0
843	List the hero ID of superheroes have intelligence as their power.	SELECT T1.hero_id FROM hero_power AS T1 INNER JOIN superpower AS T2 ON T1.power_id = T2.id WHERE T2.power_name = 'Intelligence'	SELECT DISTINCT T1.id FROM superhero T1 JOIN hero_power T2 ON T1.id = T2.hero_id JOIN superpower T3 ON T2.power_id = T3.id WHERE T3.power_name = 'Intelligence';	lack distinct	0	1
845	List the power of superheroes with height greater than 80% of the average height of all superheroes.	SELECT T3.power_name FROM superhero AS T1 INNER JOIN hero_power AS T2 ON T1.id = T2.hero_id INNER JOIN superpower AS T3 ON T2.power_id = T3.id WHERE T1.height_cm * 100 > (SELECT AVG(height_cm) FROM superhero) * 80	SELECT power_name FROM superpower WHERE superpower.id IN (SELECT T2.power_id FROM superhero AS T1 INNER JOIN hero_power AS T2 ON T1.id = T2.hero_id WHERE T1.height_cm * 100 > (SELECT AVG(height_cm) FROM superhero) * 80);	join -> in-sub?	1	0
846	Please list the reference names of the drivers who are eliminated in the first period in race number 20.	SELECT T2.driverRef FROM qualifying AS T1 INNER JOIN drivers AS T2 ON T2.driverId = T1.driverId WHERE T1.raceId = 20 ORDER BY T1.q1 DESC LIMIT 5	SELECT driverRef FROM drivers WHERE driverId IN (SELECT driverId FROM qualifying WHERE raceId = 20 AND q1 IS NOT NULL ORDER BY q1 DESC LIMIT 5)	schema flaw: lack constraint unique(raceId, driverId); limit n	0	1
848	Please list the year during which the race is held on circuits in Shanghai.	SELECT T2.year FROM circuits AS T1 INNER JOIN races AS T2 ON T2.circuitId = T1.circuitId WHERE T1.location = 'Shanghai'	SELECT DISTINCT year FROM races JOIN circuits ON races.circuitId = circuits.circuitId WHERE circuits.location = 'Shanghai';	lack distinct	0	1
849	Where can the introduction of the races held on Circuit de Barcelona-Catalunya be found?	SELECT DISTINCT T1.url FROM circuits AS T1 INNER JOIN races AS T2 ON T2.circuitId = T1.circuitId WHERE T1.name = 'Circuit de Barcelona-Catalunya'	SELECT T2.url FROM circuits T1 JOIN races T2 ON T1.circuitId = T2.circuitId WHERE T1.name = 'Circuit de Barcelona-Catalunya';	semantic error: output column	0	1
850	Please give the name of the race held on the circuits in Germany.	SELECT DISTINCT T2.name FROM circuits AS T1 INNER JOIN races AS T2 ON T2.circuitId = T1.circuitId WHERE T1.country = 'Germany'	SELECT T2.name FROM circuits AS T1 JOIN races AS T2 ON T1.circuitId = T2.circuitId WHERE T1.country = 'Germany';	redundant distinct	0	1
851	Please list the positions of the circuits built by the constructor Renault.	SELECT DISTINCT T1.position FROM constructorStandings AS T1 INNER JOIN constructors AS T2 ON T2.constructorId = T1.constructorId WHERE T2.name = 'Renault'	SELECT position FROM constructorStandings WHERE constructorId = (SELECT constructorId FROM constructors WHERE name = 'Renault')	join -> in-sub	0	1
854	What is the coordinates location of the circuits for Australian grand prix?	SELECT DISTINCT T1.lat, T1.lng FROM circuits AS T1 INNER JOIN races AS T2 ON T2.circuitId = T1.circuitId WHERE T2.name = 'Australian Grand Prix'	SELECT lat, lng FROM circuits WHERE circuitId IN (SELECT circuitId FROM races WHERE name = 'Australian Grand Prix');	join -> in-sub?	0	1
855	Where can I find the information about the races held on Sepang International Circuit?	SELECT DISTINCT T1.url FROM circuits AS T1 INNER JOIN races AS T2 ON T2.circuitId = T1.circuitId WHERE T1.name = 'Sepang International Circuit'	SELECT T2.url FROM circuits T1 JOIN races T2 ON T1.circuitId = T2.circuitId WHERE T1.name = 'Sepang International Circuit';	semantic error: output column	0	1
856	Please list the time of the races held on Sepang International Circuit.	SELECT DISTINCT T2.time FROM circuits AS T1 INNER JOIN races AS T2 ON T2.circuitId = T1.circuitId WHERE T1.name = 'Sepang International Circuit'	SELECT T2.time FROM races T2 JOIN circuits T1 ON T1.circuitId = T2.circuitId WHERE T1.name = 'Sepang International Circuit';	redundant distinct	0	1
860	For the driver who had the Q2 time as 0:01:40 in the qualifying race No. 355, what is his nationality?	SELECT DISTINCT T2.nationality FROM qualifying AS T1 INNER JOIN drivers AS T2 ON T2.driverId = T1.driverId WHERE T1.raceId = 355 AND T1.q2 LIKE '1:40%'	SELECT T2.nationality FROM qualifying AS T1 INNER JOIN drivers AS T2 ON T2.driverId = T1.driverId WHERE T1.raceId = 355 AND T1.q2 LIKE '1:40%'	redundant distinct	1	0
865	For all the drivers who finished the game in race No. 592, who is the oldest?	SELECT T1.forename, T1.surname FROM drivers AS T1 INNER JOIN results AS T2 ON T2.driverId = T1.driverId WHERE T2.raceId = 592 AND T2.time IS NOT NULL AND T1.dob IS NOT NULL ORDER BY T1.dob ASC LIMIT 1	SELECT forename, surname FROM (SELECT T1.forename, T1.surname, rank() over (ORDER BY T1.dob ASC) as rk FROM drivers AS T1 INNER JOIN results AS T2 ON T2.driverId = T1.driverId WHERE T2.raceId = 592 AND T2.time IS NOT NULL AND T1.dob IS NOT NULL ORDER BY T1.dob ASC) WHERE rk = 1	limit 1	0	0

866	Who was the player that got the lap time of 0:01:27 in the race No. 161? Show his introduction website.	SELECT DISTINCT T2.forename, T2.surname, T2.url FROM lapTimes AS T1 INNER JOIN drivers AS T2 ON T2.driverId = T1.driverId WHERE T1.raceId = 161 AND T1.time LIKE '1:27%'	SELECT forename, surname, url FROM drivers WHERE driverId IN (SELECT driverId FROM lapTimes AS T1 WHERE raceId = 161 AND time LIKE '1:27%')	join -> in-sub	0	0
867	For the driver who set the fastest lap speed in race No.933, where does he come from?	SELECT T1.nationality FROM drivers AS T1 INNER JOIN results AS T2 ON T2.driverId = T1.driverId WHERE T2.raceId = 933 AND T2.fastestLapTime IS NOT NULL ORDER BY T2.fastestLapSpeed DESC LIMIT 1	SELECT T1.nationality FROM drivers AS T1 WHERE driverId IN (SELECT T2.driverId FROM results AS T2 WHERE T2.raceId = 933 AND T2.fastestLapSpeed = (SELECT max(T3.fastestLapSpeed) FROM results AS T3 WHERE T3.raceId = 933));	join -> in-sub; limit 1	0	0
868	Where is Malaysian Grand Prix held? Give the location coordinates.	SELECT DISTINCT T1.lat, T1.lng FROM circuits AS T1 INNER JOIN races AS T2 ON T2.circuitId = T1.circuitId WHERE T2.name = 'Malaysian Grand Prix'	SELECT T2.lat, T2.lng FROM races T1 JOIN circuits T2 ON T1.circuitId = T2.circuitId WHERE T1.name = 'Malaysian Grand Prix';	redundant distinct	0	0
869	For the constructor which got the highest point in the race No. 9 , what is its introduction website?	SELECT T2.url FROM constructorResults AS T1 INNER JOIN constructors AS T2 ON T2.constructorId = T1.constructorId WHERE T1.raceId = 9 ORDER BY T1.points DESC LIMIT 1	SELECT T3.url FROM constructors T3 WHERE T3.constructorId IN (SELECT T2.constructorId FROM constructorResults T2 WHERE T2.raceId = 9 AND T2.points = (SELECT MAX(T1.points) FROM constructorResults T1 WHERE T1.raceId = 9));	limit 1	0	1
871	For the driver who had the Q2 time as 0:01:15 in race No. 347, where is he from?	SELECT DISTINCT T2.nationality FROM qualifying AS T1 INNER JOIN drivers AS T2 ON T2.driverId = T1.driverId WHERE T1.raceId = 347 AND T1.q2 LIKE '1:15%'	SELECT T2.nationality FROM qualifying AS T1 INNER JOIN drivers AS T2 ON T2.driverId = T1.driverId WHERE T1.raceId = 347 AND T1.q2 LIKE '1:15%'	schema flaw: lack constraint unique(raceId, driverId); redundant distinct	1	0
876	For the race happened in 2015/11/29, how many drivers did not finish the game?	SELECT COUNT(T2.driverId) FROM races AS T1 INNER JOIN results AS T2 ON T2.raceId = T1.raceId WHERE T1.date = '2015-11-29' AND T2.time IS NULL	SELECT COUNT(DISTINCT T2.driverId) FROM races AS T1 INNER JOIN results AS T2 ON T2.raceId = T1.raceId WHERE T1.date = '2015-11-29' AND T2.time IS NULL	lack distinct	1	0
877	For all the drivers who finished the game in race No. 872, who is the youngest? Show the full names.	SELECT T1.forename, T1.surname FROM drivers AS T1 INNER JOIN results AS T2 ON T2.driverId = T1.driverId WHERE T2.raceId = 872 AND T2.time IS NOT NULL ORDER BY T1.dob DESC LIMIT 1	SELECT forename, surname FROM (SELECT T1.forename, T1.surname, rank() over (ORDER BY T1.dob DESC) as rk FROM drivers AS T1 INNER JOIN results AS T2 ON T2.driverId = T1.driverId WHERE T2.raceId = 872 AND T2.time IS NOT NULL ORDER BY T1.dob DESC) WHERE rk = 1	schema flaw: lack constraint results(raceId, driverId); limit 1	1	0
878	Who was the driver that got the best lap time in the race No. 348? Give his full name.	SELECT T2.forename, T2.surname FROM lapTimes AS T1 INNER JOIN drivers AS T2 ON T2.driverId = T1.driverId WHERE T1.raceId = 348 ORDER BY T1.time ASC LIMIT 1	SELECT forename, surname FROM drivers WHERE driverId IN (SELECT driverId FROM (SELECT T2.driverId, rank() over (ORDER BY (CASE WHEN LENGTH(time) - LENGTH(REPLACE(time, ':', '')) = 2 THEN CAST(SUBSTR(time, 1, INSTR(time, ':') - 1) AS INTEGER) ELSE 0 END * 3600 + CASE WHEN LENGTH(time) - LENGTH(REPLACE(time, ':', '')) = 2 THEN CAST(SUBSTR(time, INSTR(time, ':') + 1, INSTR(SUBSTR(time, INSTR(time, ':') + 1, ':') - 1) AS INTEGER) ELSE CAST(SUBSTR(time, 1, INSTR(time, ':') - 1) AS INTEGER) END * 60 + CASE WHEN LENGTH(time) - LENGTH(REPLACE(time, ':', '')) = 2 THEN CAST(SUBSTR(SUBSTR(time, INSTR(time, ':') + 1, INSTR(SUBSTR(time, INSTR(time, ':') + 1, ':') + 1, INSTR(SUBSTR(SUBSTR(time, INSTR(time, ':') + 1, ':') + 1, ':') - 1) AS INTEGER) ELSE CAST(SUBSTR(time, INSTR(time, ':') + 1, INSTR(SUBSTR(time, INSTR(time, ':') + 1, ':') - 1) AS INTEGER) END + CAST(SUBSTR(time, INSTR(time, ':') + 1) AS INTEGER) / 1000.0) ASC) as rk FROM lapTimes AS T1 INNER JOIN drivers AS T2 ON T2.driverId = T1.driverId WHERE T1.raceId = 348) WHERE rk = 1)	limit 1; wrong order by	1	0

879	For the driver who set the fastest lap speed, what is his nationality?	SELECT T1.nationality FROM drivers AS T1 INNER JOIN results AS T2 ON T2.driverId = T1.driverId ORDER BY T2.fastestLapSpeed DESC LIMIT 1	SELECT nationality FROM drivers WHERE driverId IN (SELECT driverId FROM results WHERE fastestLapSpeed = (SELECT max(fastestLapSpeed) FROM results))	limit 1	0	0
886	Which year has the most number of races?	SELECT year FROM races GROUP BY year ORDER BY COUNT(round) DESC LIMIT 1	SELECT year FROM (SELECT year, rank() over (ORDER BY COUNT(round) DESC) as rk FROM races GROUP BY year) WHERE rk = 1	limit 1	0	0
892	State the driver with the most points scored. Find his full name with that points.	SELECT T3.forename, T3.surname, T2.points FROM races AS T1 INNER JOIN driverStandings AS T2 ON T2.raceId = T1.raceId INNER JOIN drivers AS T3 ON T3.driverId = T2.driverId ORDER BY T2.points DESC LIMIT 1	SELECT forename, surname, points FROM drivers JOIN (SELECT distinct driverId, points FROM driverStandings WHERE points = (SELECT max(points) FROM driverStandings)) AS T ON drivers.driverId = T.driverId	limit 1	0	0
893	Name the top 3 drivers and the points they scored in the 2017 Chinese Grand Prix.	SELECT T3.forename, T3.surname, T2.points FROM races AS T1 INNER JOIN driverStandings AS T2 ON T2.raceId = T1.raceId INNER JOIN drivers AS T3 ON T3.driverId = T2.driverId WHERE T1.name = 'Chinese Grand Prix' AND T1.year = 2017 ORDER BY T2.points DESC LIMIT 3	SELECT forename, surname, points FROM (SELECT T3.forename, T3.surname, T2.points, rank() over (ORDER BY T2.points DESC) as rk FROM races AS T1 INNER JOIN driverStandings AS T2 ON T2.raceId = T1.raceId INNER JOIN drivers AS T3 ON T3.driverId = T2.driverId WHERE T1.name = 'Chinese Grand Prix' AND T1.year = 2017 ORDER BY T2.points DESC) WHERE rk <= 3;	schema flaw: lack constraint unique races(name, year); unique driverStandings(raceId, driverId); limit n	0	0
894	What is the best lap time recorded? List the driver and race with such recorded lap time.	SELECT T2.milliseconds, T1.forename, T1.surname, T3.name FROM drivers AS T1 INNER JOIN lapTimes AS T2 ON T1.driverId = T2.driverId INNER JOIN races AS T3 ON T2.raceId = T3.raceId ORDER BY T2.milliseconds ASC LIMIT 1	SELECT milliseconds, forename, surname, name FROM (SELECT T2.milliseconds, T1.forename, T1.surname, T3.name, rank() over (ORDER BY T2.milliseconds ASC) as rk FROM drivers AS T1 INNER JOIN lapTimes AS T2 ON T1.driverId = T2.driverId INNER JOIN races AS T3 ON T2.raceId = T3.raceId) WHERE rk = 1	limit 1	0	0
897	Name the driver with the most winning. Mention his nationality and what is his maximum point scores.	SELECT T1.forename, T1.surname, T1.nationality, MAX(T2.points) FROM drivers AS T1 INNER JOIN driverStandings AS T2 ON T2.driverId = T1.driverId WHERE T2.wins >= 1 GROUP BY T1.forename, T1.surname, T1.nationality ORDER BY COUNT(T2.wins) DESC LIMIT 1	SELECT forename, surname, nationality, points FROM (SELECT T1.forename, T1.surname, T1.nationality, MAX(T2.points) as points, rank() over (ORDER BY COUNT(T2.wins) DESC) as rk FROM drivers AS T1 INNER JOIN driverStandings AS T2 ON T2.driverId = T1.driverId WHERE T2.wins >= 1 GROUP BY T1.driverId) WHERE rk = 1;	limit 1	0	0
898	How old is the youngest Japanese driver? What is his name?	SELECT STRFTIME('%Y', CURRENT_TIMESTAMP) - STRFTIME('%Y', dob), forename, surname FROM drivers WHERE nationality = 'Japanese' ORDER BY dob DESC LIMIT 1	SELECT age, forename, surname FROM (SELECT STRFTIME('%Y', CURRENT_TIMESTAMP) - STRFTIME('%Y', dob) as age, forename, surname, rank() over (ORDER BY dob DESC) as rk FROM drivers WHERE nationality = 'Japanese') WHERE rk = 1	limit 1	0	0
899	List circuits which host 4 f1 races from year 1990 to 2000.	SELECT DISTINCT T1.name FROM circuits AS T1 INNER JOIN races AS T2 ON T2.circuitId = T1.circuitId WHERE STRFTIME('%Y', T2.date) BETWEEN '1990' AND '2000' GROUP BY T1.name HAVING COUNT(T2.raceId) = 4	SELECT T2.circuitId FROM races T1 JOIN circuits T2 ON T1.circuitId = T2.circuitId WHERE T1.year BETWEEN 1990 AND 2000 GROUP BY T1.circuitId HAVING COUNT(T1.raceId) = 4;	group by non-key	0	1
901	Name the races along with its circuit name and location for f1 races hosted in September 2005.	SELECT DISTINCT T2.name, T1.name, T1.location FROM circuits AS T1 INNER JOIN races AS T2 ON T2.circuitId = T1.circuitId WHERE T2.year = 2005 AND STRFTIME('%m', T2.date) = '09'	SELECT T1.name AS race_name, T2.name AS circuit_name, T2.location FROM races T1 JOIN circuits T2 ON T1.circuitId = T2.circuitId WHERE strftime('%Y', T1.date) = '2005' AND strftime('%m', T1.date) = '09';	redundant distinct	0	1
904	State the race and year of race in which Michael Schumacher had his fastest lap.	SELECT T1.name, T1.year FROM races AS T1 INNER JOIN lapTimes AS T2 ON T2.raceId = T1.raceId INNER JOIN drivers AS T3 ON T3.driverId = T2.driverId WHERE T3.forename = 'Michael' AND T3.surname = 'Schumacher' ORDER BY T2.milliseconds ASC LIMIT 1	SELECT T1.name, T1.year FROM races AS T1 WHERE T1.raceId IN (SELECT raceId FROM (SELECT T2.raceId, rank() over (ORDER BY milliseconds) as rk FROM lapTimes AS T2 INNER JOIN drivers AS T3 ON T3.driverId = T2.driverId WHERE T3.forename = 'Michael' AND T3.surname = 'Schumacher') WHERE rk = 1)	limit 1	1	0

907	List all races in 2017 and the hosting country order by date of the event.	SELECT DISTINCT T2.name, T1.country FROM circuits AS T1 INNER JOIN races AS T2 ON T2.circuitId = T1.circuitId WHERE T2.year = 2017 ORDER BY T2.date ASC	SELECT T2.name, T1.country FROM circuits AS T1 INNER JOIN races AS T2 ON T2.circuitId = T1.circuitId WHERE T2.year = 2017 ORDER BY T2.date ASC	redundant distinct	1	0
908	What is the most laps f1 races had? Name the race, year and circuit location where the races with most laps was hosted.	SELECT T3.lap, T2.name, T2.year, T1.location FROM circuits AS T1 INNER JOIN races AS T2 ON T1.circuitId = T2.circuitId INNER JOIN lapTimes AS T3 ON T3.raceId = T2.raceId WHERE T3.lap = (SELECT MAX(T4.lap) FROM lapTimes AS T4)	SELECT MAX(T3.lap) as laps, T2.name, T2.year, T1.location FROM circuits AS T1 INNER JOIN races AS T2 ON T1.circuitId = T2.circuitId INNER JOIN lapTimes AS T3 ON T3.raceId = T2.raceId GROUP BY T2.raceId HAVING (laps) = (SELECT MAX(T4.lap) FROM lapTimes AS T4);	lack distinct; semantic error: output column	0	0
911	Which of these circuits is located at a higher latitude, Silverstone Circuit, Hockenheimring or Hungaroring?	SELECT name FROM circuits WHERE name IN ('Silverstone Circuit', 'Hockenheimring', 'Hungaroring') ORDER BY lat DESC LIMIT 1	SELECT name FROM (SELECT name, rank() over (ORDER BY lat DESC) as rk FROM circuits WHERE name IN ('Silverstone Circuit', 'Hockenheimring', 'Hungaroring')) WHERE rk = 1	limit 1	1	0
913	In which country can I find the circuit with the highest altitude?	SELECT country FROM circuits ORDER BY alt DESC LIMIT 1	SELECT country FROM (SELECT country, rank() over (ORDER BY alt DESC) as rk FROM circuits) WHERE rk = 1	limit 1	0	0
915	Which country is the oldest driver from?	SELECT nationality FROM drivers WHERE dob IS NOT NULL ORDER BY dob ASC LIMIT 1	SELECT nationality FROM (SELECT nationality, rank() over (ORDER BY dob ASC) as rk FROM drivers WHERE dob IS NOT NULL) WHERE rk = 1		1	0
916	Please list the surnames of all the Italian drivers.	SELECT surname FROM drivers WHERE nationality = 'Italian'	SELECT surname FROM drivers WHERE nationality = 'italian'	str: 'italian'	1	0
921	Please give more information about the Formula_1 races that used the Silverstone Circuit.	SELECT DISTINCT T1.url FROM circuits AS T1 INNER JOIN races AS T2 ON T2.circuitId = T1.circuitId WHERE T1.name = 'Silverstone Circuit'	SELECT T2.url FROM circuits T1 JOIN races T2 ON T1.circuitId = T2.circuitId WHERE T1.name = 'Silverstone Circuit';	semantic error: output column	0	1
927	Which driver created the fastest lap speed in a Formula_1 race? Please give both his forename and surname.	SELECT T1.forename, T1.surname FROM drivers AS T1 INNER JOIN results AS T2 ON T2.driverId = T1.driverId WHERE T2.fastestLapTime IS NOT NULL ORDER BY T2.fastestLapSpeed DESC LIMIT 1	SELECT T1.forename, T1.surname FROM drivers AS T1 WHERE driverId IN (SELECT driverId FROM results AS T2 WHERE T2.fastestLapSpeed IS NOT NULL AND fastestLapSpeed = (SELECT max(fastestLapSpeed) FROM results))	limit 1	0	0
928	Which driver ranked the first in the Canadian Grand Prix in 2007? Please give his reference name.	SELECT T3.forename, T3.surname, T3.driverRef FROM races AS T1 INNER JOIN results AS T2 ON T2.raceId = T1.raceId INNER JOIN drivers AS T3 ON T3.driverId = T2.driverId WHERE T1.name = 'Canadian Grand Prix' AND T2.rank = 1 AND T1.year = 2007	SELECT T3.driverRef FROM races AS T1 INNER JOIN results AS T2 ON T2.raceId = T1.raceId INNER JOIN drivers AS T3 ON T3.driverId = T2.driverId WHERE T1.name = 'Canadian Grand Prix' AND T2.rank = 1 AND T1.year = 2007;	semantic error: output column	0	0
935	How many drivers managed to finish the race in the 2008 Australian Grand Prix?	SELECT COUNT(T2.driverId) FROM races AS T1 INNER JOIN results AS T2 ON T2.raceId = T1.raceId WHERE T1.name = 'Australian Grand Prix' AND T1.year = 2008 AND T2.time IS NOT NULL	SELECT COUNT(DISTINCT T2.driverId) FROM races AS T1 INNER JOIN results AS T2 ON T2.raceId = T1.raceId WHERE T1.name = 'Australian Grand Prix' AND T1.year = 2008 AND T2.time IS NOT NULL	lack distinct	1	0
938	Who was the champion of 2008's Australian Grand Prix? Show the full name. And where can I know more about him?	SELECT T1.forename, T1.surname, T1.url FROM drivers AS T1 INNER JOIN results AS T2 ON T1.driverId = T2.driverId INNER JOIN races AS T3 ON T3.raceId = T2.raceId WHERE T3.name = 'Australian Grand Prix' AND T2.time LIKE ':%:_.:_' AND T3.year = 2008	SELECT T1.forename, T1.surname, T1.url, T2.time FROM drivers AS T1 INNER JOIN results AS T2 ON T1.driverId = T2.driverId INNER JOIN races AS T3 ON T3.raceId = T2.raceId WHERE T3.name = 'Australian Grand Prix' AND T2.time LIKE ':%:_.:_' AND T3.year = 2008;	str: 'HH:MM:SS.mmm'	0	0

939	How many drivers from the UN participated in the 2008 Australian Grand Prix?	SELECT COUNT(*) FROM drivers AS T1 INNER JOIN results AS T2 ON T1.driverId = T2.driverId INNER JOIN races AS T3 ON T3.raceId = T2.raceId WHERE T3.name = 'Australian Grand Prix' AND T1.nationality = 'British' AND T3.year = 2008	SELECT COUNT(DISTINCT T3.driverId) FROM races T1 JOIN results T2 ON T1.raceId = T2.raceId JOIN drivers T3 ON T2.driverId = T3.driverId WHERE T1.year = 2008 AND T1.name = 'Australian Grand Prix' AND T3.nationality = 'British';	lack distinct	0	1
949	Which constructor has the highest point?	SELECT T2.name FROM constructorStandings AS T1 INNER JOIN constructors AS T2 ON T1.constructorId = T2.constructorId ORDER BY T1.points DESC LIMIT 1	SELECT name FROM constructors WHERE constructorId IN (SELECT constructorId FROM (SELECT constructorId, rank() over (ORDER BY points DESC) as rk FROM constructorStandings) WHERE rk = 1)	limit 1	1	0
951	How many Japanese constructors have 0 points in 2 races?	SELECT COUNT(T1.raceId) FROM constructorStandings AS T1 INNER JOIN constructors AS T2 ON T1.constructorId = T2.constructorId WHERE T1.points = 0 AND T2.nationality = 'Japanese' GROUP BY T1.constructorId HAVING COUNT(raceId) = 2	SELECT COUNT(*) FROM (SELECT T1.constructorId FROM constructorStandings AS T1 INNER JOIN constructors AS T2 ON T1.constructorId = T2.constructorId WHERE T1.points = 0 AND T2.nationality = 'Japanese' GROUP BY T1.constructorId HAVING COUNT(raceId) = 2);	semantic error	0	0
952	Which constructors have been ranked 1?	SELECT DISTINCT T2.name FROM results AS T1 INNER JOIN constructors AS T2 ON T1.constructorId = T2.constructorId WHERE T1.rank = 1	SELECT name FROM constructors WHERE constructorId IN (SELECT constructorId FROM results WHERE rank = 1)	join -> in-sub	1	0
956	Which drivers born after 1975 have been ranked 2? Please give their forenames and surnames.	SELECT T2.forename, T2.surname FROM results AS T1 INNER JOIN drivers AS T2 ON T1.driverId = T2.driverId WHERE STRFTIME('%Y', T2.dob) > '1975' AND T1.rank = 2	SELECT forename, surname FROM drivers WHERE driverId IN (SELECT driverId FROM results WHERE rank = 2) AND STRFTIME('%Y', dob) > '1975'	join -> in-sub	1	0
957	How many Italian drivers haven't finished the race?	SELECT COUNT(T1.driverId) FROM results AS T1 INNER JOIN drivers AS T2 ON T1.driverId = T2.driverId WHERE T2.nationality = 'Italian' AND T1.time IS NULL	SELECT COUNT(DISTINCT T1.driverId) FROM results AS T1 INNER JOIN drivers AS T2 ON T1.driverId = T2.driverId WHERE T2.nationality = 'Italian' AND T1.time IS NULL	lack distinct	1	0
958	Which driver has the fastest lap time? Please give their forenames and surnames.	SELECT T2.forename, T2.surname, T1.fastestLapTime FROM results AS T1 INNER JOIN drivers AS T2 ON T1.driverId = T2.driverId WHERE T1.fastestLapTime IS NOT NULL ORDER BY T1.fastestLapTime ASC LIMIT 1	SELECT forename, surname FROM drivers WHERE driverId IN (SELECT driverId FROM results WHERE fastestLapTime = (SELECT MIN(fastestLapTime) FROM results WHERE fastestLapTime IS NOT NULL))	limit 1; semantic error: output column	0	1
961	Which race has the shortest actual finishing time? Please give the name and year.	SELECT T1.name, T1.year FROM races AS T1 INNER JOIN results AS T2 ON T1.raceId = T2.raceId WHERE T2.milliseconds IS NOT NULL ORDER BY T2.milliseconds LIMIT 1	SELECT name, year FROM races WHERE raceId IN (SELECT raceId FROM results WHERE milliseconds = (SELECT MIN(milliseconds) FROM results WHERE milliseconds IS NOT NULL));	limit 1	0	1
962	From 2000 to 2005, what percentage of drivers who were born before 1985 and the lap numbers were over 50?	SELECT CAST(SUM(IIF(STRFTIME('%Y', T3.dob) < '1985' AND T1.laps > 50, 1, 0)) AS REAL) * 100 / COUNT(*) FROM results AS T1 INNER JOIN races AS T2 ON T1.raceId = T2.raceId INNER JOIN drivers AS T3 ON T1.driverId = T3.driverId WHERE T2.year BETWEEN 2000 AND 2005	SELECT CAST(COUNT(DISTINCT CASE WHEN STRFTIME('%Y', T3.dob) < '1985' AND T1.laps > 50 THEN T3.driverId END) AS REAL) * 100 / COUNT(DISTINCT T3.driverId) FROM results AS T1 INNER JOIN races AS T2 ON T1.raceId = T2.raceId INNER JOIN drivers AS T3 ON T1.driverId = T3.driverId WHERE T2.year BETWEEN 2000 AND 2005	lack distinct	0	0
963	How many French drivers who obtain the laptime less than 02:00.00?	SELECT COUNT(T1.driverId) FROM drivers AS T1 INNER JOIN lapTimes AS T2 ON T1.driverId = T2.driverId WHERE T1.nationality = 'French' AND (CAST(SUBSTR(T2.time, 1, 2) AS INTEGER) * 60 + CAST(SUBSTR(T2.time, 4, 2) AS INTEGER) + CAST(SUBSTR(T2.time, 7, 2) AS REAL) / 1000) < 120	SELECT COUNT(DISTINCT T1.driverId) FROM drivers AS T1 INNER JOIN lapTimes AS T2 ON T1.driverId = T2.driverId WHERE T1.nationality = 'French' AND (CAST(SUBSTR(T2.time, 1, 2) AS INTEGER) * 60 + CAST(SUBSTR(T2.time, 4, 2) AS INTEGER) + CAST(SUBSTR(T2.time, 7, 2) AS REAL) / 1000) < 120	lack distinct	1	0
970	List out top 3 German drivers who were born from 1980-1990 and have the earliest lap time.	SELECT T2.driverId FROM pitStops AS T1 INNER JOIN drivers AS T2 ON T1.driverId = T2.driverId WHERE T2.nationality = 'German' AND STRFTIME('%Y', T2.dob) BETWEEN '1980' AND '1990' ORDER BY T1.time LIMIT 3	SELECT driverId FROM (SELECT T1.driverId, rank() over (ORDER BY MIN(CASE WHEN LENGTH(time) - LENGTH(REPLACE(time, ':', '')) = 2 THEN CAST(SUBSTR(time, 1, INSTR(time, ':') - 1) AS INTEGER) ELSE 0 END * 3600 + CASE WHEN LENGTH(time) - LENGTH(REPLACE(time, ':', '')) = 2 THEN CAST(SUBSTR(time, INSTR(time, ':') + 1, INSTR(SUBSTR(time, INSTR(time, ':') + 1, ':') - 1) AS INTEGER) ELSE CAST(SUBSTR(time, 1, INSTR(time, ':') - 1) AS INTEGER) END * 60 + CASE WHEN LENGTH(time) - LENGTH(REPLACE(time, ':', '')) = 2 THEN CAST(SUBSTR(SUBSTR(time, INSTR(time, ':') + 1, INSTR(SUBSTR(time, INSTR(time, ':') + 1, ':') - 1) AS INTEGER) ELSE CAST(SUBSTR(time, INSTR(time, ':') + 1, INSTR(SUBSTR(time, INSTR(time, ':') + 1, ':') - 1) AS INTEGER) END + CAST(SUBSTR(time, INSTR(time, ':') + 1) AS INTEGER) / 1000.0)) as rk FROM drivers T1 JOIN lapTimes T2 ON T1.driverId = T2.driverId WHERE T1.nationality = 'German' AND strftime('%Y', T1.dob) BETWEEN '1980' AND '1990' GROUP BY T1.driverId) WHERE rk < 4	semantic error; limit n; wrong order by condition	0	0

971	Please state the reference name of the oldest German driver.	SELECT driverRef FROM drivers WHERE nationality = 'German' ORDER BY JULIAN-DAY(dob) ASC LIMIT 1	SELECT driverRef FROM (SELECT driverRef, rank() over (ORDER BY JULIANDAY(dob) ASC) as rk FROM drivers WHERE nationality = 'German') WHERE rk = 1		1	0
972	Which drivers who were born in 1971 and has the fastest lap time on the race? Give id and code of these drivers.	SELECT T2.driverId, T2.code FROM results AS T1 INNER JOIN drivers AS T2 on T1.driverId = T2.driverId WHERE STRFTIME('%Y', T2.dob) = '1971' AND T1.fastestLapTime IS NOT NULL	SELECT DISTINCT T2.driverId, T2.code FROM results AS T1 INNER JOIN drivers AS T2 on T1.driverId = T2.driverId WHERE STRFTIME('%Y', T2.dob) = '1971' AND T1.fastestLapTime IS NOT NULL;	lack distinct	0	0
973	List out top 10 Spanish drivers who were born before 1982 and have the latest lap time.	SELECT T2.driverId FROM pitStops AS T1 INNER JOIN drivers AS T2 on T1.driverId = T2.driverId WHERE T2.nationality = 'Spanish' AND STRFTIME('%Y', T2.dob) < '1982' ORDER BY T1.time DESC LIMIT 10	SELECT driverId FROM (SELECT T2.driverId, rank() over (ORDER BY max(CASE WHEN LENGTH(time) - LENGTH(REPLACE(time, ':', '')) = 2 THEN CAST(SUBSTR(time, 1, INSTR(time, ':') - 1) AS INTEGER) ELSE 0 END * 3600 + CASE WHEN LENGTH(time) - LENGTH(REPLACE(time, ':', '')) = 2 THEN CAST(SUBSTR(time, INSTR(time, ':') + 1, INSTR(SUBSTR(time, INSTR(time, ':') + 1, ':') - 1) AS INTEGER) ELSE CAST(SUBSTR(time, 1, INSTR(time, ':') - 1) AS INTEGER) END * 60 + CASE WHEN LENGTH(time) - LENGTH(REPLACE(time, ':', '')) = 2 THEN CAST(SUBSTR(SUBSTR(time, INSTR(time, ':') + 1, INSTR(SUBSTR(time, INSTR(time, ':') + 1, ':') + 1, INSTR(SUBSTR(SUBSTR(time, INSTR(time, ':') + 1, INSTR(SUBSTR(time, INSTR(time, ':') + 1, ':') - 1) AS INTEGER) ELSE CAST(SUBSTR(time, INSTR(time, ':') + 1, INSTR(SUBSTR(time, INSTR(time, ':') + 1, ':') - 1) AS INTEGER) END + CAST(SUBSTR(time, INSTR(time, ':') + 1) AS INTEGER) / 1000.0) DESC) as rk FROM lapTimes AS T1 INNER JOIN drivers AS T2 on T1.driverId = T2.driverId WHERE T2.nationality = 'Spanish' AND STRFTIME('%Y', T2.dob) < '1982' GROUP BY T1.driverId) WHERE rk <= 10	wrong order by; limit n; semantic error: wrong table	1	0
974	State the racing year which has the fastest lap time? 'has the fastest lap time?' refers to fastest-LapTime has values	SELECT T2.year FROM results AS T1 INNER JOIN races AS T2 on T1.raceId = T2.raceId WHERE T1.fastestLapTime IS NOT NULL	SELECT DISTINCT T2.year FROM results AS T1 INNER JOIN races AS T2 on T1.raceId = T2.raceId WHERE T1.fastestLapTime IS NOT NULL;	lack distinct	0	0
975	Which year has the lowest speed of lap time?	SELECT T2.year FROM lapTimes AS T1 INNER JOIN races AS T2 on T1.raceId = T2.raceId ORDER BY T1.time DESC LIMIT 1	SELECT year FROM (SELECT T2.year, rank() over (ORDER BY max(CASE WHEN LENGTH(T1.time) - LENGTH(REPLACE(T1.time, ':', '')) = 2 THEN CAST(SUBSTR(T1.time, 1, INSTR(T1.time, ':') - 1) AS INTEGER) ELSE 0 END * 3600 + CASE WHEN LENGTH(T1.time) - LENGTH(REPLACE(T1.time, ':', '')) = 2 THEN CAST(SUBSTR(T1.time, INSTR(T1.time, ':') + 1, INSTR(SUBSTR(T1.time, INSTR(T1.time, ':') + 1, ':') - 1) AS INTEGER) ELSE CAST(SUBSTR(T1.time, 1, INSTR(T1.time, ':') - 1) AS INTEGER) END * 60 + CASE WHEN LENGTH(T1.time) - LENGTH(REPLACE(T1.time, ':', '')) = 2 THEN CAST(SUBSTR(SUBSTR(T1.time, INSTR(T1.time, ':') + 1, INSTR(SUBSTR(T1.time, INSTR(T1.time, ':') + 1, ':') + 1, INSTR(SUBSTR(SUBSTR(T1.time, INSTR(T1.time, ':') + 1, INSTR(SUBSTR(T1.time, INSTR(T1.time, ':') + 1, ':') - 1) AS INTEGER) ELSE CAST(SUBSTR(T1.time, INSTR(T1.time, ':') + 1, INSTR(SUBSTR(T1.time, INSTR(T1.time, ':') + 1, ':') - 1) AS INTEGER) END + CAST(SUBSTR(T1.time, INSTR(T1.time, ':') + 1) AS INTEGER) / 1000.0) DESC) as rk FROM lapTimes T1 JOIN races T2 ON T1.raceId = T2.raceId GROUP BY T2.year) WHERE rk = 1	limit 1	0	0

976	List the driver's ID of the top five driver, by descending order, the fastest time during the first lap of the race.	SELECT driverId FROM lapTimes WHERE lap = 1 ORDER BY time LIMIT 5	SELECT driverId FROM (SELECT driverId, rank() over (ORDER BY MIN((CASE WHEN LENGTH(time) - LENGTH(REPLACE(time, ':', '')) = 2 THEN CAST(SUBSTR(time, 1, INSTR(time, ':') - 1) AS INTEGER) ELSE 0 END * 3600 + CASE WHEN LENGTH(time) - LENGTH(REPLACE(time, ':', '')) = 2 THEN CAST(SUBSTR(time, INSTR(time, ':') + 1, INSTR(SUBSTR(time, INSTR(time, ':') + 1, ':') - 1) AS INTEGER) ELSE CAST(SUBSTR(time, 1, INSTR(time, ':') - 1) AS INTEGER) END * 60 + CASE WHEN LENGTH(time) - LENGTH(REPLACE(time, ':', '')) = 2 THEN CAST(SUBSTR(SUBSTR(time, INSTR(time, ':') + 1), INSTR(SUBSTR(time, INSTR(time, ':') + 1, ':') + 1, ':') + 1, INSTR(SUBSTR(SUBSTR(time, INSTR(time, ':') + 1, ':') + 1, ':') - 1) AS INTEGER) ELSE CAST(SUBSTR(time, INSTR(time, ':') + 1, INSTR(SUBSTR(time, INSTR(time, ':') + 1, ':') - 1) AS INTEGER) END + CAST(SUBSTR(time, INSTR(time, ':') + 1) AS INTEGER) / 1000.0)) ASC) as rk FROM lapTimes WHERE lap = 1 GROUP BY driverId) WHERE rk <= 5	limit n; semantic error	0	0
978	How many times the circuits were held in Austria? Please give their location and coordinates.	SELECT DISTINCT location, lat, lng FROM circuits WHERE country = 'Austria'	SELECT location, lat, lng FROM circuits WHERE country = 'Austria'	redundant distinct	1	0
979	What race number has the most finishers?	SELECT raceId FROM results GROUP BY raceId ORDER BY COUNT(time IS NOT NULL) DESC LIMIT 1	SELECT raceId FROM (SELECT raceId, rank() over (ORDER BY COUNT(*) DESC) as rk FROM results WHERE time IS NOT NULL GROUP BY raceId) WHERE rk = 1	limit 1	0	0
981	On what year did the youngest driver had his first qualifying race? Also state the name, date and time of the race.	SELECT T3.year, T3.name, T3.date, T3.time FROM qualifying AS T1 INNER JOIN drivers AS T2 ON T1.driverId = T2.driverId INNER JOIN races AS T3 ON T1.raceId = T3.raceId WHERE T1.driverId = (SELECT driverId FROM drivers ORDER BY dob DESC LIMIT 1) ORDER BY T3.date ASC LIMIT 1	SELECT T3.year, T3.name, T3.date, T3.time FROM races T3 JOIN qualifying T2 ON T3.raceId = T2.raceId JOIN drivers T1 ON T2.driverId = T1.driverId WHERE T1.dob = (SELECT MAX(dob) FROM drivers) ORDER BY T3.date ASC LIMIT 1	limit 1	0	1
982	How many American drivers have puncture status.	SELECT COUNT(T1.driverId) FROM drivers AS T1 INNER JOIN results AS T2 ON T1.driverId = T2.driverId INNER JOIN status AS T3 ON T2.statusId = T3.statusId WHERE T3.status = 'Puncture' AND T1.nationality = 'American'	SELECT COUNT(DISTINCT T1.driverId) FROM drivers T1 JOIN results T2 ON T1.driverId = T2.driverId JOIN status T3 ON T2.statusId = T3.statusId WHERE T1.nationality = 'American' AND T3.status = 'Puncture';	lack distinct	0	1
983	Which of the Italian constructor got the highest point to date? Give its introduction website?	SELECT T1.url FROM constructors AS T1 INNER JOIN constructorStandings AS T2 ON T1.constructorId = T2.constructorId WHERE T1.nationality = 'Italian' ORDER BY T2.points DESC LIMIT 1	SELECT url FROM (SELECT T1.url, rank() over (ORDER BY max(T2.points) DESC) as rk FROM constructors AS T1 INNER JOIN constructorStandings AS T2 ON T1.constructorId = T2.constructorId WHERE T1.nationality = 'Italian' GROUP BY T1.constructorId) WHERE rk = 1;	limit 1	0	0
984	What is the website of the constructor who tallied the most total wins.	SELECT T1.url FROM constructors AS T1 INNER JOIN constructorStandings AS T2 ON T1.constructorId = T2.constructorId ORDER BY T2.wins DESC LIMIT 1	SELECT url FROM (SELECT T2.url, rank() over (ORDER BY SUM(T1.wins) DESC) as rk FROM constructors T2 JOIN constructorStandings T1 ON T2.constructorId = T1.constructorId GROUP BY T1.constructorId) WHERE rk = 1	limit 1	0	0
985	Among the drivers who participated in the French Grand Prix, who has the slowest time in the 3rd lap.	SELECT T1.driverId FROM lapTimes AS T1 INNER JOIN races AS T2 ON T1.raceId = T2.raceId WHERE T2.name = 'French Grand Prix' AND T1.lap = 3 ORDER BY T1.time DESC LIMIT 1	SELECT driverId FROM (SELECT T1.driverId, rank() over (ORDER BY MAX((CASE WHEN LENGTH(T1.time) - LENGTH(REPLACE(T1.time, ':', '')) = 2 THEN CAST(SUBSTR(T1.time, 1, INSTR(T1.time, ':') - 1) AS INTEGER) ELSE 0 END * 3600 + CASE WHEN LENGTH(T1.time) - LENGTH(REPLACE(T1.time, ':', '')) = 2 THEN CAST(SUBSTR(T1.time, INSTR(T1.time, ':') + 1, INSTR(SUBSTR(T1.time, INSTR(T1.time, ':') + 1, ':') - 1) AS INTEGER) ELSE CAST(SUBSTR(T1.time, 1, INSTR(T1.time, ':') - 1) AS INTEGER) END * 60 + CASE WHEN LENGTH(T1.time) - LENGTH(REPLACE(T1.time, ':', '')) = 2 THEN CAST(SUBSTR(SUBSTR(T1.time, INSTR(T1.time, ':') + 1), INSTR(SUBSTR(T1.time, INSTR(T1.time, ':') + 1, ':') + 1, ':') + 1, INSTR(SUBSTR(SUBSTR(T1.time, INSTR(T1.time, ':') + 1, ':') + 1, ':') - 1) AS INTEGER) ELSE CAST(SUBSTR(T1.time, INSTR(T1.time, ':') + 1, INSTR(SUBSTR(T1.time, INSTR(T1.time, ':') + 1, ':') - 1) AS INTEGER) END + CAST(SUBSTR(T1.time, INSTR(T1.time, ':') + 1) AS INTEGER) / 1000.0)) DESC) as rk FROM lapTimes AS T1	limit 1	0	0

986	In which race did the fastest 1st lap time was recorded? Please indicate the time in milliseconds.	SELECT T1.milliseconds FROM lapTimes AS T1 INNER JOIN races AS T2 on T1.raceId = T2.raceId WHERE T1.lap = 1 ORDER BY T1.time LIMIT 1	SELECT raceId, milliseconds FROM (SELECT T2.raceId, T1.milliseconds, rank() over (ORDER BY (CASE WHEN LENGTH(T1.time) - LENGTH(REPLACE(T1.time, ':', '')) = 2 THEN CAST(SUBSTR(T1.time, 1, INSTR(T1.time, ':') - 1) AS INTEGER) ELSE 0 END * 3600 + CASE WHEN LENGTH(T1.time) - LENGTH(REPLACE(T1.time, ':', '')) = 2 THEN CAST(SUBSTR(T1.time, INSTR(T1.time, ':') + 1, INSTR(SUBSTR(T1.time, INSTR(T1.time, ':') + 1, ':') - 1) AS INTEGER) ELSE CAST(SUBSTR(T1.time, 1, INSTR(T1.time, ':') - 1) AS INTEGER) END * 60 + CASE WHEN LENGTH(T1.time) - LENGTH(REPLACE(T1.time, ':', '')) = 2 THEN CAST(SUBSTR(SUBSTR(T1.time, INSTR(T1.time, ':') + 1, INSTR(SUBSTR(T1.time, INSTR(T1.time, ':') + 1, ':') + 1, INSTR(SUBSTR(T1.time, INSTR(T1.time, ':') + 1, ':') + 1, INSTR(SUBSTR(T1.time, INSTR(T1.time, ':') + 1, ':') + 1, ':') - 1) AS INTEGER) ELSE CAST(SUBSTR(T1.time, INSTR(T1.time, ':') + 1, INSTR(SUBSTR(T1.time, INSTR(T1.time, ':') + 1, ':') - 1) AS INTEGER) END + CAST(SUBSTR(T1.time, INSTR(T1.time, ':') + 1) AS INTEGER) / 1000.0)) as rk FROM lapTimes AS T1 INNER JOIN races AS T2 on T1.raceId = T2.raceId WHERE T1.lap = 1) WHERE rk = 1	limit 1; semantic error: output column	0	0
988	List down top 3 German drivers who has the shortest average pit stop duration and were born between 1980-1985.	SELECT T2.forename, T2.surname FROM pitStops AS T1 INNER JOIN drivers AS T2 on T1.driverId = T2.driverId WHERE T2.nationality = 'German' AND STRFTIME('%Y', T2.dob) BETWEEN '1980' AND '1985' GROUP BY T2.forename, T2.surname ORDER BY AVG(T1.duration) LIMIT 3	SELECT forename, surname FROM (SELECT T2.forename, T2.surname, rank() over (ORDER BY AVG(T1.duration)) as rk FROM pitStops AS T1 INNER JOIN drivers AS T2 on T1.driverId = T2.driverId WHERE T2.nationality = 'German' AND STRFTIME('%Y', T2.dob) BETWEEN '1980' AND '1985' GROUP BY T2.driverId) WHERE rk <= 3;	limit n; group by non-key	0	0
993	In which location does the Hungaroring circuit located? Also, find the country and coordinates of this circuit?	SELECT country, lat, lng FROM circuits WHERE name = 'Hungaroring'	SELECT location, country, lat, lng FROM circuits WHERE name = 'Hungaroring';	output columns	0	1
994	Which constructor scored most points from Monaco Grand Prix between 1980 and 2010? List the score, name and nationality of this team.	SELECT SUM(T1.points), T2.name, T2.nationality FROM constructorResults AS T1 INNER JOIN constructors AS T2 ON T1.constructorId = T2.constructorId INNER JOIN races AS T3 ON T3.raceId = T1.raceId WHERE T3.name = 'Monaco Grand Prix' AND T3.year BETWEEN 1980 AND 2010 GROUP BY T2.name ORDER BY SUM(T1.points) DESC LIMIT 1	SELECT score, name, nationality FROM (SELECT SUM(T1.points) as score, T2.name, T2.nationality, rank() over (ORDER BY SUM(T1.points) DESC) as rk FROM constructorResults AS T1 INNER JOIN constructors AS T2 ON T1.constructorId = T2.constructorId INNER JOIN races AS T3 ON T3.raceId = T1.raceId WHERE T3.name = 'Monaco Grand Prix' AND T3.year BETWEEN 1980 AND 2010 GROUP BY T2.constructorId) WHERE rk = 1	limit 1; group by non-key	0	0
997	Which citizenship do the vast majority of the drivers hold?	SELECT nationality FROM drivers GROUP BY nationality ORDER BY COUNT(driverId) DESC LIMIT 1	SELECT nationality FROM drivers GROUP BY nationality HAVING COUNT(*) = (SELECT MAX(cnt) FROM (SELECT COUNT(*) as cnt FROM drivers GROUP BY nationality) T2);	limit 1	0	0
998	In terms of number of points acquired, how many victories did the driver who ranked 91st acquired?	SELECT SUM(CASE WHEN points = 91 THEN wins ELSE 0 END) FROM driverStandings	SELECT wins FROM (SELECT wins, rank() OVER (ORDER BY SUM(points) DESC) AS rank FROM driverStandings WHERE points IS NOT NULL GROUP BY driverId) WHERE rank = 91;	semantic error	0	0

999	In terms of the fastest lap time, what is the name of the race which recorded the fastest lap speed by a racer?	SELECT T1.name FROM races AS T1 INNER JOIN results AS T2 ON T1.raceId = T2.raceId WHERE T2.fastestLapTime IS NOT NULL ORDER BY T2.fastestLapTime ASC LIMIT 1	SELECT name FROM races WHERE raceId IN (SELECT raceId FROM results WHERE fastestLapTime = (SELECT MIN(fastestLapTime) FROM results));	join -> in-sub; limit n	0	0
1000	Which racetrack hosted the most recent race? Indicate the full location.	SELECT T1.location FROM circuits AS T1 INNER JOIN races AS T2 ON T1.circuitId = T2.circuitId ORDER BY T2.date DESC LIMIT 1	SELECT location, country FROM (SELECT T1.location, T1.country, rank() over (ORDER BY MAX(T2.date) DESC) as rk FROM circuits AS T1 INNER JOIN races AS T2 ON T1.circuitId = T2.circuitId GROUP BY T1.circuitId) WHERE rk = 1	limit 1; semantic error: output column	0	0
1001	What is full name of the racer who ranked 1st in the 3rd qualifying race held in the Marina Bay Street Circuit in 2008?	SELECT T2.forename, T2.surname FROM qualifying AS T1 INNER JOIN drivers AS T2 ON T1.driverId = T2.driverId INNER JOIN races AS T3 ON T1.raceId = T3.raceId WHERE q3 IS NOT NULL AND T3.year = 2008 AND T3.circuitId IN (SELECT circuitId FROM circuits WHERE name = 'Marina Bay Street Circuit') ORDER BY CAST(SUBSTR(q3, 1, INSTR(q3, ':') - 1) AS INTEGER) * 60 + CAST(SUBSTR(q3, INSTR(q3, ':') + 1, INSTR(q3, ':') - INSTR(q3, ':') - 1) AS REAL) + CAST(SUBSTR(q3, INSTR(q3, ':') + 1) AS REAL) / 1000, rank() over (ORDER BY min(CAST(SUBSTR(q3, 1, INSTR(q3, ':') - 1) AS INTEGER) * 60 + CAST(SUBSTR(q3, INSTR(q3, ':') + 1, INSTR(q3, ':') - INSTR(q3, ':') - 1) AS REAL) + CAST(SUBSTR(q3, INSTR(q3, ':') + 1) AS REAL)) / 1000 ASC) as rk FROM qualifying AS T1 INNER JOIN drivers AS T2 on T1.driverId = T2.driverId INNER JOIN races AS T3 ON T1.raceId = T3.raceId WHERE q3 IS NOT NULL AND T3.year = 2008 AND T3.circuitId IN (SELECT circuitId FROM circuits WHERE name = 'Marina Bay Street Circuit') GROUP BY T2.driverId) WHERE rk = 1;	SELECT forename, surname FROM (SELECT T2.forename, T2.surname, CAST(SUBSTR(q3, 1, INSTR(q3, ':') - 1) AS INTEGER) * 60 + CAST(SUBSTR(q3, INSTR(q3, ':') + 1, INSTR(q3, ':') - INSTR(q3, ':') - 1) AS REAL) + CAST(SUBSTR(q3, INSTR(q3, ':') + 1) AS REAL) / 1000, rank() over (ORDER BY min(CAST(SUBSTR(q3, 1, INSTR(q3, ':') - 1) AS INTEGER) * 60 + CAST(SUBSTR(q3, INSTR(q3, ':') + 1, INSTR(q3, ':') - INSTR(q3, ':') - 1) AS REAL) + CAST(SUBSTR(q3, INSTR(q3, ':') + 1) AS REAL)) / 1000 ASC) as rk FROM qualifying AS T1 INNER JOIN drivers AS T2 on T1.driverId = T2.driverId INNER JOIN races AS T3 ON T1.raceId = T3.raceId WHERE q3 IS NOT NULL AND T3.year = 2008 AND T3.circuitId IN (SELECT circuitId FROM circuits WHERE name = 'Marina Bay Street Circuit') GROUP BY T2.driverId) WHERE rk = 1;	limit 1	0	0
1002	As of the present, what is the full name of the youngest racer? Indicate her nationality and the name of the race to which he/she first joined.	SELECT T1.forename, T1.surname, T1.nationality, T3.name FROM drivers AS T1 INNER JOIN driverStandings AS T2 on T1.driverId = T2.driverId INNER JOIN races AS T3 on T2.raceId = T3.raceId ORDER BY JULIANDAY(T1.dob) DESC LIMIT 1	SELECT forename, surname, nationality, name FROM (SELECT forename, surname, nationality, T.driverId, races.name, rank() over (partition by T.driverId ORDER BY races.date ASC) as rk FROM (SELECT forename, surname, nationality, driverId, rank() over (ORDER BY dob DESC) as rk FROM drivers) AS T JOIN driverStandings ON T.driverId = driverStandings.driverId JOIN races on races.raceId = driverStandings.raceId WHERE T.rk = 1) WHERE rk = 1;	limit 1	1	0
1004	How many wins was achieved by the oldest racer? Indicate his/her full name.	SELECT SUM(T1.wins), T2.forename, T2.surname FROM driverStandings AS T1 INNER JOIN drivers AS T2 on T1.driverId = T2.driverId ORDER BY T2.dob ASC LIMIT 1	SELECT wins, forename, surname FROM (SELECT SUM(T1.wins) as wins, T2.forename, T2.surname, rank() over (ORDER BY T2.dob ASC) as rk FROM driverStandings AS T1 INNER JOIN drivers AS T2 on T1.driverId = T2.driverId GROUP BY T2.driverId) WHERE rk = 1;	limit 1; semantic error: lack group by	0	0
1006	Among all the lap records set on various circuits, what is the time for the fastest one?	SELECT time FROM lapTimes ORDER BY (CASE WHEN INSTR(time, ':') <> INSTR(SUBSTR(time, INSTR(time, ':') + 1, ':') + INSTR(time, ':')) THEN CAST(SUBSTR(time, 1, INSTR(time, ':') - 1) AS REAL) * 3600 ELSE 0 END) + (CAST(SUBSTR(time, INSTR(time, ':') - 2 * (INSTR(time, ':') = INSTR(SUBSTR(time, INSTR(time, ':') + 1, ':') + INSTR(time, ':')), INSTR(time, ':') - 1) AS REAL) * 60) + (CAST(SUBSTR(time, INSTR(time, ':') + 1, INSTR(time, ':') - INSTR(time, ':') - 1) AS REAL) + (CAST(SUBSTR(time, INSTR(time, ':') + 1) AS REAL) / 1000) ASC LIMIT 1	SELECT time FROM lapTimes ORDER BY (CASE WHEN LENGTH(time) - LENGTH(REPLACE(time, ':', '')) = 2 THEN CAST(SUBSTR(time, 1, INSTR(time, ':') - 1) AS INTEGER) ELSE 0 END * 3600 + CASE WHEN LENGTH(time) - LENGTH(REPLACE(time, ':', '')) = 2 THEN CAST(SUBSTR(time, INSTR(time, ':') + 1, INSTR(SUBSTR(time, INSTR(time, ':') + 1, ':') - 1) AS INTEGER) ELSE CAST(SUBSTR(time, 1, INSTR(time, ':') - 1) AS INTEGER) END * 60 + CASE WHEN LENGTH(time) - LENGTH(REPLACE(time, ':', '')) = 2 THEN CAST(SUBSTR(SUBSTR(time, INSTR(time, ':') + 1, INSTR(SUBSTR(time, INSTR(time, ':') + 1, ':') + 1, ':') + 1, INSTR(SUBSTR(SUBSTR(time, INSTR(time, ':') + 1, ':') + 1, ':') - 1) AS INTEGER) ELSE CAST(SUBSTR(time, INSTR(time, ':') + 1, INSTR(SUBSTR(time, INSTR(time, ':') + 1, ':') - 1) AS INTEGER) END + CAST(SUBSTR(time, INSTR(time, ':') + 1) AS INTEGER) / 1000.0) ASC LIMIT 1	wrong order by condition	1	0

1010	What is the lap record set by Lewis Hamilton in a Formula_1 race?	SELECT T1.time FROM lapTimes AS T1 INNER JOIN drivers AS T2 on T1.driverId = T2.driverId WHERE T2.forename = 'Lewis' AND T2.surname = 'Hamilton'	SELECT T1.time FROM lapTimes AS T1 INNER JOIN drivers AS T2 on T1.driverId = T2.driverId WHERE T2.forename = 'Lewis' AND T2.surname = 'Hamilton' ORDER BY (CASE WHEN LENGTH(time) - LENGTH(REPLACE(time, ':', '')) = 2 THEN CAST(SUBSTR(time, 1, INSTR(time, ':') - 1) AS INTEGER) ELSE 0 END * 3600 + CASE WHEN LENGTH(time) - LENGTH(REPLACE(time, ':', '')) = 2 THEN CAST(SUBSTR(time, INSTR(time, ':') + 1, INSTR(SUBSTR(time, INSTR(time, ':') + 1), ':') - 1) AS INTEGER) ELSE CAST(SUBSTR(time, 1, INSTR(time, ':') - 1) AS INTEGER) END * 60 + CASE WHEN LENGTH(time) - LENGTH(REPLACE(time, ':', '')) = 2 THEN CAST(SUBSTR(SUBSTR(time, INSTR(time, ':') + 1), INSTR(SUBSTR(time, INSTR(time, ':') + 1), ':') + 1, INSTR(SUBSTR(SUBSTR(time, INSTR(time, ':') + 1), INSTR(SUBSTR(time, INSTR(time, ':') + 1), ':') + 1), ':') - 1) AS INTEGER) ELSE CAST(SUBSTR(time, INSTR(time, ':') + 1, INSTR(SUBSTR(time, INSTR(time, ':') + 1), ':') - 1) AS INTEGER) END + CAST(SUBSTR(time, INSTR(time, ':') + 1) AS INTEGER) / 1000.0) ASC LIMIT 1	semantic error: lack order by	1	0
1011	Which top 20 driver created the shortest lap time ever record in a Formula_1 race? Please give them full names.	WITH lap_times_in_seconds AS (SELECT driverId, (CASE WHEN SUBSTR(time, 1, INSTR(time, ':') - 1) <> '' THEN CAST(SUBSTR(time, 1, INSTR(time, ':') - 1) AS REAL) * 60 ELSE 0 END + CASE WHEN SUBSTR(time, INSTR(time, ':') + 1, INSTR(time, ':') - INSTR(time, ':') - 1) <> '' THEN CAST(SUBSTR(time, INSTR(time, ':') + 1, INSTR(time, ':') - INSTR(time, ':') - 1) AS REAL) ELSE 0 END + CASE WHEN SUBSTR(time, INSTR(time, ':') + 1) <> '' THEN CAST(SUBSTR(time, INSTR(time, ':') + 1) AS REAL) / 1000 ELSE 0 END) AS time_in_seconds FROM lapTimes) SELECT T2.forename, T2.surname, T1.driverId FROM (SELECT driverId, MIN(time_in_seconds) AS min_time_in_seconds FROM lap_times_in_seconds GROUP BY driverId) AS T1 INNER JOIN drivers AS T2 ON T1.driverId = T2.driverId ORDER BY T1.min_time_in_seconds ASC LIMIT 20	WITH lap_times_in_seconds AS (SELECT driverId, (CASE WHEN LENGTH(time) - LENGTH(REPLACE(time, ':', '')) = 2 THEN CAST(SUBSTR(time, 1, INSTR(time, ':') - 1) AS INTEGER) ELSE 0 END * 3600 + CASE WHEN LENGTH(time) - LENGTH(REPLACE(time, ':', '')) = 2 THEN CAST(SUBSTR(time, INSTR(time, ':') + 1, INSTR(SUBSTR(time, INSTR(time, ':') + 1), ':') - 1) AS INTEGER) ELSE CAST(SUBSTR(time, 1, INSTR(time, ':') - 1) AS INTEGER) END * 60 + CASE WHEN LENGTH(time) - LENGTH(REPLACE(time, ':', '')) = 2 THEN CAST(SUBSTR(SUBSTR(time, INSTR(time, ':') + 1), INSTR(SUBSTR(time, INSTR(time, ':') + 1), ':') + 1, INSTR(SUBSTR(SUBSTR(time, INSTR(time, ':') + 1), INSTR(SUBSTR(time, INSTR(time, ':') + 1), ':') + 1), ':') - 1) AS INTEGER) ELSE CAST(SUBSTR(time, INSTR(time, ':') + 1, INSTR(SUBSTR(time, INSTR(time, ':') + 1), ':') - 1) AS INTEGER) END + CAST(SUBSTR(time, INSTR(time, ':') + 1) AS INTEGER) / 1000.0) AS time_in_seconds FROM lapTimes) SELECT T2.forename, T2.surname, T1.driverId FROM (SELECT driverId, rank() over (ORDER BY min(time_in_seconds)) AS rk FROM lap_times_in_seconds GROUP BY driverId) AS T1 INNER JOIN drivers AS T2 ON T1.driverId = T2.driverId WHERE T1.rk <= 20	limit n	0	0

1012	What was the position of the circuits during Lewis Hamilton's fastest lap in a Formula_1 race?	SELECT T1.position FROM lapTimes AS T1 INNER JOIN drivers AS T2 on T1.driverId = T2.driverId WHERE T2.forename = 'Lewis' AND T2.surname = 'Hamilton' ORDER BY T1.time ASC LIMIT 1	SELECT position FROM (SELECT T1.position, rank() over (ORDER BY (CASE WHEN LENGTH(time) - LENGTH(REPLACE(time, ':', '')) = 2 THEN CAST(SUBSTR(time, 1, INSTR(time, ':') - 1) AS INTEGER) ELSE 0 END * 3600 + CASE WHEN LENGTH(time) - LENGTH(REPLACE(time, ':', '')) = 2 THEN CAST(SUBSTR(time, INSTR(time, ':') + 1, INSTR(SUBSTR(time, INSTR(time, ':') + 1, ':') - 1) AS INTEGER) ELSE CAST(SUBSTR(time, 1, INSTR(time, ':') - 1) AS INTEGER) END * 60 + CASE WHEN LENGTH(time) - LENGTH(REPLACE(time, ':', '')) = 2 THEN CAST(SUBSTR(SUBSTR(time, INSTR(time, ':') + 1, INSTR(SUBSTR(time, INSTR(time, ':') + 1, ':') + 1, ':') - 1, INSTR(SUBSTR(time, INSTR(time, ':') + 1, ':') + 1, ':') - 1) AS INTEGER) ELSE CAST(SUBSTR(time, INSTR(time, ':') + 1, INSTR(SUBSTR(time, INSTR(time, ':') + 1, ':') - 1) AS INTEGER) END + CAST(SUBSTR(time, INSTR(time, ':') + 1) AS INTEGER) / 1000.0)) as rk FROM lapTimes AS T1 INNER JOIN drivers AS T2 on T1.driverId = T2.driverId WHERE T2.forename = 'Lewis' AND T2.surname = 'Hamilton') WHERE rk = 1	limit 1; wrong order by	1	0
1013	What is the lap record for the Austrian Grand Prix Circuit?	WITH fastest_lap_times AS (SELECT T1.raceId, T1.fastestLapTime FROM results AS T1 WHERE T1.FastestLapTime IS NOT NULL) SELECT MIN(fastest_lap_times.fastestLapTime) as lap_record FROM fastest_lap_times INNER JOIN races AS T2 on fastest_lap_times.raceId = T2.raceId INNER JOIN circuits AS T3 on T2.circuitId = T3.circuitId WHERE T2.name = 'Austrian Grand Prix'	WITH fastest_lap_times AS (SELECT T1.raceId, T1.FastestLapTime, (CAST(SUBSTR(T1.FastestLapTime, 1, INSTR(T1.FastestLapTime, ':') - 1) AS REAL) * 60) + (CAST(SUBSTR(T1.FastestLapTime, INSTR(T1.FastestLapTime, ':') + 1, INSTR(T1.FastestLapTime, ':') - INSTR(T1.FastestLapTime, ':') - 1) AS REAL)) + (CAST(SUBSTR(T1.FastestLapTime, INSTR(T1.FastestLapTime, ':') + 1) AS REAL) / 1000) as time_in_seconds FROM results AS T1 WHERE T1.FastestLapTime IS NOT NULL) SELECT fastest_lap_times.fastestLapTime as lap_record FROM fastest_lap_times INNER JOIN races AS T2 on fastest_lap_times.raceId = T2.raceId WHERE T2.name = 'Austrian Grand Prix' ORDER BY fastest_lap_times.time_in_seconds asc LIMIT 1	wrong order by	0	0
1015	In which Formula_1 race was the lap record for the Austrian Grand Prix Circuit set?	WITH fastest_lap_times AS (SELECT T1.raceId, T1.FastestLapTime, (CAST(SUBSTR(T1.FastestLapTime, 1, INSTR(T1.FastestLapTime, ':') - 1) AS REAL) * 60) + (CAST(SUBSTR(T1.FastestLapTime, INSTR(T1.FastestLapTime, ':') + 1, INSTR(T1.FastestLapTime, ':') - INSTR(T1.FastestLapTime, ':') - 1) AS REAL)) + (CAST(SUBSTR(T1.FastestLapTime, INSTR(T1.FastestLapTime, ':') + 1) AS REAL) / 1000) as time_in_seconds FROM results AS T1 WHERE T1.FastestLapTime IS NOT NULL) SELECT T2.name FROM races AS T2 INNER JOIN circuits AS T3 on T2.circuitId = T3.circuitId INNER JOIN results AS T1 on T2.raceId = T1.raceId INNER JOIN (SELECT MIN(fastest_lap_times.time_in_seconds) as min_time_in_seconds FROM fastest_lap_times INNER JOIN races AS T2 on fastest_lap_times.raceId = T2.raceId INNER JOIN circuits AS T3 on T2.circuitId = T3.circuitId WHERE T2.name = 'Austrian Grand Prix') AS T4 ON (CAST(SUBSTR(T1.FastestLapTime, 1, INSTR(T1.FastestLapTime, ':') - 1) AS REAL) * 60) + (CAST(SUBSTR(T1.FastestLapTime, INSTR(T1.FastestLapTime, ':') + 1, INSTR(T1.FastestLapTime, ':') - INSTR(T1.FastestLapTime, ':') - 1) AS REAL)) + (CAST(SUBSTR(T1.FastestLapTime, INSTR(T1.FastestLapTime, ':') + 1) AS REAL) / 1000) = T4.min_time_in_seconds WHERE T2.name = 'Austrian Grand Prix'	WITH fastest_lap_times AS (SELECT T1.raceId, T1.FastestLapTime, (CAST(SUBSTR(T1.FastestLapTime, 1, INSTR(T1.FastestLapTime, ':') - 1) AS REAL) * 60) + (CAST(SUBSTR(T1.FastestLapTime, INSTR(T1.FastestLapTime, ':') + 1, INSTR(T1.FastestLapTime, ':') - INSTR(T1.FastestLapTime, ':') - 1) AS REAL)) + (CAST(SUBSTR(T1.FastestLapTime, INSTR(T1.FastestLapTime, ':') + 1) AS REAL) / 1000) as time_in_seconds FROM results AS T1 WHERE T1.FastestLapTime IS NOT NULL) SELECT DISTINCT raceId FROM (SELECT T2.raceId, rank() over (ORDER BY fastest_lap_times.time_in_seconds ASC) as rk FROM fastest_lap_times INNER JOIN races AS T2 on fastest_lap_times.raceId = T2.raceId WHERE T2.name = 'Austrian Grand Prix') WHERE rk = 1	semantic error: output column	0	0

1017	Please list the location coordinates of the circuits whose lap record is 1:29.488.	SELECT T3.lat, T3.lng FROM lapTimes AS T1 INNER JOIN races AS T2 ON T1.raceId = T2.raceId INNER JOIN circuits AS T3 ON T2.circuitId = T3.circuitId WHERE T1.time = '1:29.488'	SELECT lat, lng FROM circuits WHERE circuitId IN (SELECT circuitId FROM races WHERE raceId IN (SELECT raceId FROM lapTimes WHERE time = '1:29.488'));	JOIN	0	1
1019	What is the average lap time in milliseconds of all the lap records set on the various circuits in Italy?	SELECT CAST(SUM(T1.milliseconds) AS REAL) / COUNT(T1.lap) FROM lapTimes AS T1 INNER JOIN races AS T2 ON T1.raceId = T2.raceId INNER JOIN circuits AS T3 ON T2.circuitId = T3.circuitId WHERE T3.country = 'Italy'	SELECT avg(laptime) FROM (SELECT min(t1.milliseconds) as laptime FROM lapTimes AS T1 INNER JOIN races AS T2 ON T1.raceId = T2.raceId INNER JOIN circuits AS T3 ON T2.circuitId = T3.circuitId WHERE T3.country = 'Italy' GROUP BY T3.circuitId)	semantic error: lap records on the various circuits	1	0
1020	Which player has the highest overall rating? Indicate the player's api id.	SELECT player_api_id FROM Player_Attributes WHERE overall_rating = (SELECT MAX(overall_rating) FROM Player_Attributes)	SELECT distinct player_api_id FROM Player_Attributes WHERE overall_rating = (SELECT max(overall_rating) FROM Player_Attributes);	lack distinct	0	0
1021	What is the height of the tallest player? Indicate his name.	SELECT player_name FROM Player ORDER BY height DESC LIMIT 1	SELECT player_name FROM Player WHERE height = (SELECT MAX(height) FROM Player);	limit 1	0	1
1023	Among the players with an overall rating between 60 to 65, how many players whose going to be in all of your attack moves instead of defending?	SELECT COUNT(id) FROM Player_Attributes WHERE overall_rating BETWEEN 60 AND 65 AND defensive_work_rate = 'low'	SELECT COUNT(distinct player_api_id) FROM Player_Attributes WHERE overall_rating BETWEEN 60 AND 65 AND defensive_work_rate = 'low'	semantic error: wrong col	1	0
1024	Who are the top 5 players who perform better in crossing actions? Indicate their player id.	SELECT id FROM Player_Attributes ORDER BY crossing DESC LIMIT 5	SELECT T3.id FROM (SELECT T1.player_api_id, rank() over (ORDER BY max(T1.crossing) DESC) as rk FROM Player_Attributes T1 GROUP BY T1.player_api_id) AS T2 join Player AS T3 ON T2.player_api_id = T3.player_api_id WHERE rk <= 5	limit n; semantic error: output column	0	0
1025	Give the name of the league had the most goals in the 2016 season?	SELECT t2.name FROM Match AS t1 INNER JOIN League AS t2 ON t1.league_id = t2.id WHERE t1.season = '2015/2016' GROUP BY t2.name ORDER BY SUM(t1.home_team_goal + t1.away_team_goal) DESC LIMIT 1	SELECT name FROM League WHERE id IN (SELECT league_id FROM Match WHERE season = '2015/2016' GROUP BY league_id HAVING SUM(home_team_goal + away_team_goal) = (SELECT MAX(total_goals) FROM (SELECT SUM(home_team_goal + away_team_goal) AS total_goals FROM Match WHERE season = '2015/2016' GROUP BY league_id)))	limit 1	0	1
1027	Indicate the full names of the top 10 players with the highest number of penalties.	SELECT t2.player_name FROM Player_Attributes AS t1 INNER JOIN Player AS t2 ON t1.id = t2.id ORDER BY t1.penalties DESC LIMIT 10	SELECT T2.player_name FROM (SELECT player_api_id, rank() over (ORDER BY max(penalties) DESC) as rk FROM Player_Attributes GROUP BY player_api_id) AS T1 INNER JOIN Player AS T2 ON T1.player_api_id = T2.player_api_id WHERE rk <= 10	limit n	1	0
1029	What are the speed in which attacks are put together of the top 4 teams with the highest build Up Play Speed?	SELECT t1.buildUpPlaySpeed FROM Team_Attributes AS t1 INNER JOIN Team AS t2 ON t1.team_api_id = t2.team_api_id ORDER BY t1.buildUpPlaySpeed ASC LIMIT 4	SELECT speed FROM (SELECT max(buildUpPlaySpeed) as speed, rank() over (ORDER BY max(buildUpPlaySpeed) DESC) AS rk FROM Team_Attributes WHERE buildUpPlaySpeed IS NOT NULL GROUP BY team_api_id) WHERE rk <= 4	limit n; semantic error	0	0
1030	Give the name of the league had the most matches end as draw in the 2016 season?	SELECT t2.name FROM Match AS t1 INNER JOIN League AS t2 ON t1.league_id = t2.id WHERE t1.season = '2015/2016' AND t1.home_team_goal = t1.away_team_goal GROUP BY t2.name ORDER BY COUNT(t1.id) DESC LIMIT 1	SELECT name FROM League WHERE id IN (SELECT league_id FROM Match WHERE season = '2015/2016' AND home_team_goal = away_team_goal GROUP BY league_id HAVING COUNT(*) = (SELECT MAX(draws) FROM (SELECT COUNT(*) AS draws FROM Match WHERE season = '2015/2016' AND home_team_goal = away_team_goal GROUP BY league_id)))	limit 1	0	1

1031	At present, calculate for the player's age who have a sprint speed of no less than 97 between 2013 to 2015.	SELECT DISTINCT DATETIME() - T2.birthday age FROM Player_Attributes AS t1 INNER JOIN Player AS t2 ON t1.player_api_id = t2.player_api_id WHERE STRFTIME('%Y', t1.date) >= '2013' AND STRFTIME('%Y', t1.date) <= '2015' AND t1.sprint_speed >= 97	SELECT DATETIME() - birthday FROM Player WHERE player_api_id IN (SELECT player_api_id FROM Player_Attributes WHERE STRFTIME('%Y', date) >= '2013' AND STRFTIME('%Y', date) <= '2015' AND sprint_speed >= 97)	join -> in-sub	0	0
1032	Give the name of the league with the highest matches of all time and how many matches were played in the said league.	SELECT t2.name, t1.max_count FROM League AS t2 JOIN (SELECT league_id, MAX(cnt) AS max_count FROM (SELECT league_id, COUNT(id) AS cnt FROM Match GROUP BY league_id AS subquery) AS t1 ON t1.league_id = t2.id	SELECT T2.name, COUNT(T1.league_id) AS match_count FROM Match T1 JOIN League T2 ON T1.league_id = T2.id GROUP BY T1.league_id HAVING match_count = (SELECT MAX(match_count) FROM (SELECT COUNT(league_id) AS match_count FROM Match GROUP BY league_id));	limit 1	0	1
1034	List the players' api id who had the highest above average overall ratings in 2010.	SELECT p.player_api_id FROM Player_Attributes AS p WHERE SUBSTR(p.date, 1, 4) = '2010' AND p.overall_rating = (SELECT MAX(pa.overall_rating) FROM Player_Attributes AS pa WHERE SUBSTR(pa.date, 1, 4) = '2010')	SELECT DISTINCT p.player_api_id FROM Player_Attributes AS p WHERE SUBSTR(p.date, 1, 4) = '2010' AND p.overall_rating = (SELECT MAX(pa.overall_rating) FROM Player_Attributes AS pa WHERE SUBSTR(pa.date, 1, 4) = '2010')	lack distinct	1	0
1036	List the long name of teams with above-average build-up play passing in 2012.	SELECT DISTINCT t4.team_long_name FROM Team_Attributes AS t3 INNER JOIN Team AS t4 ON t3.team_api_id = t4.team_api_id WHERE SUBSTR(t3.date, 1, 4) = '2012' AND t3.buildUpPlayPassing > (SELECT CAST(SUM(t2.buildUpPlayPassing) AS REAL) / COUNT(t1.id) FROM Team AS t1 INNER JOIN Team_Attributes AS t2 ON t1.team_api_id = t2.team_api_id WHERE STRFTIME('%Y', t2.date) = '2012')	SELECT T4.team_long_name FROM team AS T4 WHERE T4.team_api_id IN (SELECT t3.team_api_id FROM Team_Attributes AS t3 WHERE SUBSTR(t3.date, 1, 4) = '2012' AND t3.buildUpPlayPassing > (SELECT CAST(SUM(t2.buildUpPlayPassing) AS REAL) / COUNT(t1.id) FROM Team AS t1 INNER JOIN Team_Attributes AS t2 ON t1.team_api_id = t2.team_api_id WHERE STRFTIME('%Y', t2.date) = '2012'))	join -> in-sub	1	0
1037	Calculate the percentage of players who prefer left foot, who were born between 1987 and 1992.	SELECT CAST(COUNT(CASE WHEN t2.preferred_foot = 'left' THEN t1.id ELSE NULL END) AS REAL) * 100 / COUNT(t1.id) percent FROM Player AS t1 INNER JOIN Player_Attributes AS t2 ON t1.player_api_id = t2.player_api_id WHERE SUBSTR(t1.birthday, 1, 4) BETWEEN '1987' AND '1992'	SELECT CAST(COUNT(DISTINCT CASE WHEN t2.preferred_foot = 'left' THEN t1.id ELSE NULL END) AS REAL) * 100 / COUNT(DISTINCT t1.id) percent FROM Player AS t1 LEFT JOIN Player_Attributes AS t2 ON t1.player_api_id = t2.player_api_id WHERE SUBSTR(t1.birthday, 1, 4) BETWEEN '1987' AND '1992';	lack distinct; join -> left join	0	0
1038	List the top 5 leagues in ascending order of the number of goals made in all seasons combined.	SELECT t1.name, SUM(t2.home_team_goal) + SUM(t2.away_team_goal) FROM League AS t1 INNER JOIN Match AS t2 ON t1.id = t2.league_id GROUP BY t1.name ORDER BY SUM(t2.home_team_goal) + SUM(t2.away_team_goal) ASC LIMIT 5	SELECT name, goals FROM (SELECT t1.name, SUM(t2.home_team_goal) + SUM(t2.away_team_goal) as goals, rank() over (ORDER BY SUM(t2.home_team_goal) + SUM(t2.away_team_goal) ASC) as rk FROM League AS t1 INNER JOIN Match AS t2 ON t1.id = t2.league_id GROUP BY t1.id) WHERE rk <= 5;	limit n	1	0
1040	List the top 10 players' names whose heights are above 180 in descending order of average heading accuracy.	SELECT t1.player_name FROM Player AS t1 INNER JOIN Player_Attributes AS t2 ON t1.player_api_id = t2.player_api_id WHERE t1.height > 180 GROUP BY t1.id ORDER BY CAST(SUM(t2.heading_accuracy) AS REAL) / COUNT(t2.player_fifa_api_id) DESC LIMIT 10	SELECT player_name FROM (SELECT t1.player_name, rank() over (ORDER BY CAST(SUM(t2.heading_accuracy) AS REAL) / COUNT(t2.player_fifa_api_id) DESC) as rk FROM Player AS t1 INNER JOIN Player_Attributes AS t2 ON t1.player_api_id = t2.player_api_id WHERE t1.height > 180 GROUP BY t1.id) WHERE rk <= 10;	limit n	1	0
1041	For the teams with normal build-up play dribbling class in 2014, List the names of the teams with less than average chance creation passing, in descending order of chance creation passing.	SELECT t3.team_long_name FROM Team AS t3 INNER JOIN Team_Attributes AS t4 ON t3.team_api_id = t4.team_api_id WHERE t4.buildUpPlayDribblingClass = 'Normal' AND t4.chanceCreationPassing < (SELECT CAST(SUM(t2.chanceCreationPassing) AS REAL) / COUNT(t1.id) FROM Team AS t1 INNER JOIN Team_Attributes AS t2 ON t1.team_api_id = t2.team_api_id WHERE t2.buildUpPlayDribblingClass = 'Normal' AND SUBSTR(t2.date, 1, 4) = '2014') ORDER BY t4.chanceCreationPassing DESC	SELECT t3.team_long_name FROM Team AS t3 INNER JOIN Team_Attributes AS t4 ON t3.team_api_id = t4.team_api_id WHERE t4.buildUpPlayDribblingClass = 'Normal' AND SUBSTR(t4.date, 1, 4) = '2014' AND t4.chanceCreationPassing < (SELECT CAST(SUM(t2.chanceCreationPassing) AS REAL) / COUNT(t1.id) FROM Team AS t1 INNER JOIN Team_Attributes AS t2 ON t1.team_api_id = t2.team_api_id WHERE t2.buildUpPlayDribblingClass = 'Normal' AND SUBSTR(t2.date, 1, 4) = '2014') ORDER BY t4.chanceCreationPassing DESC;	semantic error: lack condition in 2014	0	0

1042	List the name of leagues in which the average goals by the home team is higher than the away team in the 2009/2010 season.	SELECT t1.name FROM League AS t1 INNER JOIN Match AS t2 ON t1.id = t2.league_id WHERE t2.season = '2009/2010' GROUP BY t1.name HAVING (CAST(SUM(t2.home_team_goal) AS REAL) / COUNT(DISTINCT t2.id)) - (CAST(SUM(t2.away_team_goal) AS REAL) / COUNT(DISTINCT t2.id)) > 0	SELECT t1.name FROM League AS t1 INNER JOIN Match AS t2 ON t1.id = t2.league_id WHERE t2.season = '2009/2010' GROUP BY t1.id HAVING (CAST(SUM(t2.home_team_goal) AS REAL) / COUNT(DISTINCT t2.id)) - (CAST(SUM(t2.away_team_goal) AS REAL) / COUNT(DISTINCT t2.id)) > 0	group by non-key	1	0
1045	What is the attacking work rate of the football player Franco Zennaro?	SELECT DISTINCT t2.attacking_work_rate FROM Player AS t1 INNER JOIN Player_Attributes AS t2 ON t1.player_api_id = t2.player_api_id WHERE t1.player_name = 'Franco Zennaro'	SELECT t2.attacking_work_rate FROM Player AS t1 INNER JOIN Player_Attributes AS t2 ON t1.player_api_id = t2.player_api_id WHERE t1.player_name = 'Franco Zennaro'	redundant distinct?	1	0
1046	What is the ADO Den Haag team freedom of movement in the 1st two thirds of the pitch?	SELECT DISTINCT t2.buildUpPlayPositioningClass FROM Team AS t1 INNER JOIN Team_attributes AS t2 ON t1.team_fifa_api_id = t2.team_fifa_api_id WHERE t1.team_long_name = 'ADO Den Haag'	SELECT T2.buildUpPlayPositioningClass FROM Team T1 JOIN Team_Attributes T2 ON T1.team_api_id = T2.team_api_id WHERE T1.team_long_name = 'ADO Den Haag';	redundant distinct?	0	1
1050	What is the preferred foot when attacking of the youngest football player?	SELECT t2.preferred_foot FROM Player AS t1 INNER JOIN Player_Attributes AS t2 ON t1.player_api_id = t2.player_api_id ORDER BY t1.birthday DESC LIMIT 1	SELECT preferred_foot FROM (SELECT t2.preferred_foot, rank() over (ORDER BY t1.birthday DESC) as rk FROM Player AS t1 INNER JOIN Player_Attributes AS t2 ON t1.player_api_id = t2.player_api_id) WHERE rk = 1	limit 1	1	0
1051	List all the football player with the highest potential score.	SELECT DISTINCT(t1.player_name) FROM Player AS t1 INNER JOIN Player_Attributes AS t2 ON t1.player_api_id = t2.player_api_id WHERE t2.potential = (SELECT MAX(potential) FROM Player_Attributes)	SELECT player_name FROM Player WHERE player_api_id IN (SELECT player_api_id FROM Player_Attributes WHERE potential = (SELECT MAX(potential) FROM Player_Attributes))	join -> in-sub	0	1
1053	List the football teams that has a chance creation passing class of Risky. Indicate its short name only.	SELECT DISTINCT t1.team_short_name FROM Team AS t1 INNER JOIN Team_attributes AS t2 ON t1.team_api_id = t2.team_api_id WHERE t2.chanceCreationPassingClass = 'Risky'	SELECT team_short_name FROM Team WHERE team_api_id IN (SELECT team_api_id FROM Team_attributes WHERE chanceCreationPassingClass = 'Risky')	join -> in-sub	0	0
1054	What is the defensive work rate of the football player David Wilson ?	SELECT DISTINCT t2.defensive_work_rate FROM Player AS t1 INNER JOIN Player_Attributes AS t2 ON t1.player_api_id = t2.player_api_id WHERE t1.player_name = 'David Wilson'	SELECT t2.defensive_work_rate FROM Player AS t1 INNER JOIN Player_Attributes AS t2 ON t1.player_api_id = t2.player_api_id WHERE t1.player_name = 'David Wilson'	redundant distinct?	1	0
1055	When is the birthday of the football player who has the highest overall rating?	SELECT t1.birthday FROM Player AS t1 INNER JOIN Player_Attributes AS t2 ON t1.player_api_id = t2.player_api_id ORDER BY t2.overall_rating DESC LIMIT 1	SELECT birthday FROM Player WHERE player_api_id IN (SELECT player_api_id FROM (SELECT player_api_id, rank() over (ORDER BY overall_rating DESC) as rk FROM Player_Attributes) WHERE rk = 1)	limit 1	1	0
1061	How many players whose first names are Adam and weigh more than 170?	SELECT COUNT(id) FROM Player WHERE weight > 170 AND player_name LIKE 'Adam%'	SELECT COUNT(id) FROM Player WHERE weight > 170 AND player_name = 'Adam'	str	1	0
1062	Which players had an overall rating of over 80 from 2008 to 2010? Please list player names.	SELECT DISTINCT t1.player_name FROM Player AS t1 INNER JOIN Player_Attributes AS t2 ON t1.player_api_id = t2.player_api_id WHERE t2.overall_rating > 80 AND SUBSTR(t2.date, 1, 4) BETWEEN '2008' AND '2010'	SELECT player_name FROM Player AS t1 WHERE t1.player_api_id IN (SELECT t2.player_api_id FROM Player_Attributes AS t2 WHERE t2.overall_rating > 80 AND SUBSTR(t2.date, 1, 4) BETWEEN '2008' AND '2010')	join -> in-sub	1	0
1065	Please list all team names which the speed class is fast.	SELECT DISTINCT t1.team_long_name FROM Team AS t1 INNER JOIN Team_Attributes AS t2 ON t1.team_api_id = t2.team_api_id WHERE t2.buildUpPlaySpeedClass = 'Fast'	SELECT t1.team_long_name FROM Team AS t1 WHERE team_api_id IN (SELECT t2.team_api_id FROM Team_Attributes AS t2 WHERE t2.buildUpPlaySpeedClass = 'Fast')	join -> in-sub	0	0
1066	What is the passing class of CLB team?	SELECT DISTINCT t2.buildUpPlayPassingClass FROM Team AS t1 INNER JOIN Team_Attributes AS t2 ON t1.team_api_id = t2.team_api_id WHERE t1.team_short_name = 'CLB'	SELECT t2.buildUpPlayPassingClass FROM Team AS t1 INNER JOIN Team_Attributes AS t2 ON t1.team_api_id = t2.team_api_id WHERE t1.team_short_name = 'CLB'	redundant distinct	0	0

1067	Which teams have build up play passing more than 70? Please list their short names.	SELECT DISTINCT t1.team_short_name FROM Team AS t1 INNER JOIN Team_Attributes AS t2 ON t1.team_api_id = t2.team_api_id WHERE t2.buildUpPlayPassing > 70	SELECT team_short_name FROM Team WHERE team_api_id IN (SELECT team_api_id FROM Team_Attributes WHERE buildUpPlayPassing > 70);	join -> in-sub	0	1
1071	List the football team that has a build up play speed of 31, build up plan dribbling of 53, and build up play passing of 32. Only indicate the short name of the team.	SELECT DISTINCT t1.team_short_name FROM Team AS t1 INNER JOIN Team_Attributes AS t2 ON t1.team_api_id = t2.team_api_id WHERE t2.buildUpPlaySpeed = 31 AND t2.buildUpPlayDribbling = 53 AND t2.buildUpPlayPassing = 32	SELECT T.team_short_name FROM Team T WHERE team_api_id IN (SELECT TA.team_api_id FROM Team_Attributes TA WHERE TA.buildUpPlaySpeed = 31 AND TA.buildUpPlayDribbling = 53 AND TA.buildUpPlayPassing = 32)	join -> in-sub	0	0
1074	List all the short name of the football team that had a home team goal of 10?	SELECT t1.team_short_name FROM Team AS t1 INNER JOIN Match AS t2 ON t1.team_api_id = t2.home_team_api_id WHERE t2.home_team_goal = 10	SELECT team_short_name FROM Team WHERE team_api_id IN (SELECT home_team_api_id FROM Match WHERE home_team_goal = 10);	join -> in-sub	0	1
1075	List all the football player with the highest balance score and potential score of 61.	SELECT t1.player_name FROM Player AS t1 INNER JOIN Player_Attributes AS t2 ON t1.player_api_id = t2.player_api_id WHERE t2.potential = '61' ORDER BY t2.balance DESC LIMIT 1	SELECT player_name FROM Player WHERE player_api_id IN (SELECT player_api_id FROM Player_Attributes WHERE potential = 61 AND balance = (SELECT MAX(balance) FROM Player_Attributes WHERE potential = 61));	limit 1	0	1
1078	Which player is older, Aaron Lennon or Abdelaziz Barrada? Output one of them or both.	SELECT player_name FROM Player WHERE player_name IN ('Aaron Lennon', 'Abdelaziz Barrada') ORDER BY birthday ASC LIMIT 1	SELECT player_name FROM (SELECT player_name, rank() over (ORDER BY birthday ASC) as rk FROM Player WHERE player_name IN ('Aaron Lennon', 'Abdelaziz Barrada')) WHERE rk = 1	limit 1	0	0
1079	Which player is the tallest?	SELECT player_name FROM Player ORDER BY height DESC LIMIT 1	SELECT player_name FROM (SELECT player_name, rank() over (ORDER BY height DESC) as rk FROM Player) WHERE rk = 1	limit 1	1	0
1080	Among the players whose preferred foot was the left foot when attacking, how many of them would remain in his position when the team attacked?	SELECT COUNT(player_api_id) FROM Player_Attributes WHERE preferred_foot = 'left' AND attacking_work_rate = 'low'	SELECT COUNT(DISTINCT player_api_id) FROM Player_Attributes WHERE preferred_foot = 'left' AND attacking_work_rate = 'low'	lack distinct	1	0
1083	Which player has the strongest overall strength?	SELECT t1.player_name FROM Player AS t1 INNER JOIN Player_Attributes AS t2 ON t1.player_api_id = t2.player_api_id ORDER BY t2.overall_rating DESC LIMIT 1	SELECT player_name FROM Player WHERE player_api_id IN (SELECT player_api_id FROM Player_Attributes WHERE overall_rating = (SELECT MAX(overall_rating) FROM Player_Attributes))	limit 1	0	1
1084	Among the players born before the year 1986, how many of them would remain in his position in his defense while the team attacked?	SELECT COUNT(DISTINCT t1.player_name) FROM Player AS t1 INNER JOIN Player_Attributes AS t2 ON t1.player_api_id = t2.player_api_id WHERE STRFTIME('%Y', t1.birthday) < '1986' AND t2.defensive_work_rate = 'high'	SELECT COUNT(DISTINCT t1.player_api_id) FROM Player AS t1 INNER JOIN Player_Attributes AS t2 ON t1.player_api_id = t2.player_api_id WHERE STRFTIME('%Y', t1.birthday) < '1986' AND t2.defensive_work_rate = 'high'	distinct non-key	0	0
1085	Which of these players performs the best in crossing actions, Alexis, Ariel Borysiuk or Arouna Kone?	SELECT t1.player_name, t2.crossing FROM Player AS t1 INNER JOIN Player_Attributes AS t2 ON t1.player_api_id = t2.player_api_id WHERE t1.player_name IN ('Alexis', 'Ariel Borysiuk', 'Arouna Kone') ORDER BY t2.crossing DESC LIMIT 1	SELECT player_name FROM Player WHERE Player.player_api_id IN (SELECT player_api_id FROM (SELECT P.player_api_id, rank() over (ORDER BY PA.crossing DESC) as rk FROM Player P JOIN Player_Attributes PA ON P.player_api_id = PA.player_api_id WHERE P.player_name IN ('Alexis', 'Ariel Borysiuk', 'Arouna Kone')) WHERE rk = 1)	limit 1	0	0

1088	Please list the names of the players whose volley score and dribbling score are over 70.	SELECT DISTINCT t1.player_name FROM Player AS t1 INNER JOIN Player_Attributes AS t2 ON t1.player_api_id = t2.player_api_id WHERE t2.volleys > 70 AND t2.dribbling > 70	SELECT player_name FROM Player WHERE player_api_id IN (SELECT player_api_id FROM Player_Attributes WHERE volleys > 70 AND dribbling > 70);	join -> in-sub	0	1
1092	Give the name of the league had the most matches in the 2008/2009 season?	SELECT t1.name FROM League AS t1 JOIN Match AS t2 ON t1.id = t2.league_id WHERE t2.season = '2008/2009' GROUP BY t1.name HAVING COUNT(t2.id) = (SELECT MAX(match_count) FROM (SELECT COUNT(t2.id) AS match_count FROM Match AS t2 WHERE t2.season = '2008/2009' GROUP BY t2.league_id))	SELECT t1.name FROM League AS t1 JOIN Match AS t2 ON t1.id = t2.league_id WHERE t2.season = '2008/2009' GROUP BY t1.id HAVING COUNT(t2.id) = (SELECT MAX(match_count) FROM (SELECT COUNT(t2.id) AS match_count FROM Match AS t2 WHERE t2.season = '2008/2009' GROUP BY t2.league_id))	group by non-key	1	0
1098	What is Ajax's highest chance creation passing score and what is it classified as?	SELECT t2.chanceCreationPassing, t2.chanceCreationPassingClass FROM Team AS t1 INNER JOIN Team_Attributes AS t2 ON t1.team_api_id = t2.team_api_id WHERE t1.team_long_name = 'Ajax' ORDER BY t2.chanceCreationPassing DESC LIMIT 1	SELECT chanceCreationPassing, chanceCreationPassingClass FROM (SELECT t2.chanceCreationPassing, t2.chanceCreationPassingClass, rank() over (ORDER BY t2.chanceCreationPassing DESC) as rk FROM Team AS t1 INNER JOIN Team_Attributes AS t2 ON t1.team_api_id = t2.team_api_id WHERE t1.team_long_name = 'Ajax') WHERE rk = 1	limit 1	1	0
1099	Which foot is preferred by Abdou Diallo?	SELECT DISTINCT t2.preferred_foot FROM Player AS t1 INNER JOIN Player_Attributes AS t2 ON t1.player_api_id = t2.player_api_id WHERE t1.player_name = 'Abdou Diallo'	SELECT t2.preferred_foot FROM Player AS t1 INNER JOIN Player_Attributes AS t2 ON t1.player_api_id = t2.player_api_id WHERE t1.player_name = 'Abdou Diallo'	redundant distinct	1	0
1102	For the players who had a 77 points overall rating on 2016/6/23, who was the oldest? Give the name of the player.	SELECT t1.player_name FROM Player AS t1 INNER JOIN Player_Attributes AS t2 ON t1.player_api_id = t2.player_api_id WHERE SUBSTR(t2.date, 1, 10) = '2016-06-23' AND t2.overall_rating = 77 ORDER BY t1.birthday ASC LIMIT 1	SELECT player_name FROM (SELECT t1.player_name, rank() over (ORDER BY t1.birthday ASC) as rk FROM Player AS t1 WHERE t1.player_api_id IN (SELECT t2.player_api_id FROM Player_Attributes AS t2 WHERE SUBSTR(t2.date, 1, 10) = '2016-06-23' AND t2.overall_rating = 77)) WHERE rk = 1;	limit 1	1	0
1107	When was the first time did Kevin Constant have his highest crossing score? Give the date.	SELECT 'date' FROM (SELECT t2.crossing, t2.date' FROM Player AS t1 INNER JOIN Player_Attributes AS t2 ON t1.player_fifa_api_id = t2.player_fifa_api_id WHERE t1.player_name = 'Kevin Constant' ORDER BY t2.crossing DESC) ORDER BY date DESC LIMIT 1	SELECT date FROM (SELECT T2.date, rank() over (ORDER BY t2.crossing DESC, t2.date ASC) as rk FROM Player T1 JOIN Player_Attributes T2 ON T1.player_api_id = T2.player_api_id WHERE T1.player_name = 'Kevin Constant') WHERE rk = 1	semantic error: first time of highest crossing score	0	0
1113	For the team "Hannover 96", what was its defence aggression class on 2015/9/10? "Hannover 96" refers to team_long_name = 'Hannover 96'; on 2015/9/10 refers to date LIKE '2015-09-10%';	SELECT t2.chanceCreationShootingClass FROM Team AS t1 INNER JOIN Team_Attributes AS t2 ON t1.team_api_id = t2.team_api_id WHERE t1.team_long_name = 'Hannover 96' AND t2.date' LIKE '2015-09-10%'	SELECT T2.defenceAggressionClass FROM Team T1 JOIN Team_Attributes T2 ON T1.team_api_id = T2.team_api_id WHERE T1.team_long_name = 'Hannover 96' AND T2.date LIKE '2015-09-10%'	semantic error: output column	0	1
1117	What are the player api id of 10 heaviest players?	SELECT player_api_id FROM Player ORDER BY weight DESC LIMIT 10	SELECT player_api_id FROM (SELECT player_api_id, rank() over (ORDER BY weight DESC) as rk FROM Player) WHERE rk <= 10;	limit n	1	0
1122	State the name of the most strongest player.	SELECT DISTINCT t1.player_name FROM Player AS t1 INNER JOIN Player_Attributes AS t2 ON t1.player_api_id = t2.player_api_id WHERE t2.overall_rating = (SELECT MAX(overall_rating) FROM Player_Attributes)	SELECT player_name FROM Player WHERE player_api_id IN (SELECT player_api_id FROM Player_Attributes WHERE overall_rating = (SELECT MAX(overall_rating) FROM Player_Attributes))	join -> in-sub	0	1

1123	What is the name of players with the highest potential?	SELECT DISTINCT T1.player_name FROM Player AS T1 INNER JOIN Player_Attributes AS T2 ON T1.player_api_id = T2.player_api_id WHERE T2.potential = (SELECT MAX(potential) FROM Player_Attributes)	SELECT player_name FROM Player WHERE player_api_id IN (SELECT player_api_id FROM Player_Attributes WHERE potential = (SELECT MAX(potential) FROM Player_Attributes))	join -> in-sub	0	1
1124	Who are the players that tend to be attacking when their mates were doing attack moves? List down their name.	SELECT DISTINCT t1.player_name FROM Player AS t1 INNER JOIN Player_Attributes AS t2 ON t1.player_api_id = t2.player_api_id WHERE t2.attacking_work_rate = 'high'	SELECT player_name FROM Player WHERE player_api_id IN (SELECT player_api_id FROM Player_Attributes WHERE attacking_work_rate = 'high');	DISTINCT, JOIN	0	1
1125	Among the players with finishing rate of 1, pick the eldest player and state the player's name.	SELECT DISTINCT t1.player_name FROM Player AS t1 INNER JOIN Player_Attributes AS t2 ON t1.player_api_id = t2.player_api_id WHERE t2.finishing = 1 ORDER BY t1.birthday ASC LIMIT 1	SELECT player_name FROM (SELECT t1.player_name, rank() over (ORDER BY t1.birthday ASC) as rk FROM Player AS t1 WHERE player_api_id IN (SELECT t2.player_api_id FROM Player_Attributes AS t2 WHERE t2.finishing = 1)) WHERE rk = 1	limit 1	0	0
1129	List down the long name for slow speed class team.	SELECT DISTINCT t1.team_long_name FROM Team AS t1 INNER JOIN Team_Attributes AS t2 ON t1.team_api_id = t2.team_api_id WHERE t2.buildUpPlaySpeedClass = 'Slow'	SELECT team_long_name FROM Team WHERE team_api_id IN (SELECT team_api_id FROM Team_Attributes WHERE buildUpPlaySpeedClass = 'Slow');	join -> in-sub	0	1
1130	What are the short name of team who played safe while creating chance of passing?	SELECT DISTINCT t1.team_short_name FROM Team AS t1 INNER JOIN Team_Attributes AS t2 ON t1.team_api_id = t2.team_api_id WHERE t2.chanceCreationPassingClass = 'Safe'	SELECT t1.team_short_name FROM Team AS t1 WHERE T1.team_api_id IN (SELECT T2.team_api_id FROM Team_Attributes AS t2 WHERE t2.chanceCreationPassingClass = 'Safe')	join -> in-sub	1	0
1132	Please provide the names of top three football players who are over 180 cm tall in alphabetical order.	SELECT player_name FROM Player WHERE height > 180 ORDER BY player_name LIMIT 3	SELECT player_name FROM Player WHERE player_name IN (SELECT player_name FROM Player WHERE height > 180 ORDER BY player_name LIMIT 3) and height > 180 ORDER BY player_name	limit n	0	0
1135	Please provide top five football players' IDs who are among the lowest potential players and prefer to use the right foot when attacking.	SELECT id FROM Player_Attributes WHERE preferred_foot = 'right' ORDER BY potential DESC LIMIT 5	SELECT player_api_id FROM (SELECT player_api_id, rank() over (ORDER BY min(potential) ASC) as rk FROM Player_Attributes WHERE preferred_foot = 'right' GROUP BY player_api_id) WHERE rk <= 5	limit n; semantic error: output column	0	0
1136	How many players had the highest potential score for crossing that preferred to use their left foot while attacking?	SELECT COUNT(t1.id) FROM Player_Attributes AS t1 WHERE t1.preferred_foot = 'left' AND t1.crossing = (SELECT MAX(crossing) FROM Player_Attributes)	SELECT COUNT(DISTINCT player_api_id) FROM Player_Attributes WHERE crossing = (SELECT MAX(crossing) FROM Player_Attributes) AND preferred_foot = 'left';	lack distinct	0	1
1137	What percentage of players have a strength and stamina score of more than 80?	SELECT CAST(COUNT(CASE WHEN strength > 80 AND stamina > 80 THEN id ELSE NULL END) AS REAL) * 100 / COUNT(id) FROM Player_Attributes t	SELECT CAST(COUNT(DISTINCT CASE WHEN strength > 80 AND stamina > 80 THEN player_api_id END) AS REAL) * 100 / (SELECT COUNT(*) FROM Player) FROM Player_Attributes t;	lack distinct	1	0
1144	Please state the finishing rate and curve score of the player who has the heaviest weight.	SELECT id, finishing, curve FROM Player_Attributes WHERE player_api_id = (SELECT player_api_id FROM Player ORDER BY weight DESC LIMIT 1) LIMIT 1	SELECT T2.finishing, T2.curve FROM Player T1 JOIN Player_Attributes T2 ON T1.player_api_id = T2.player_api_id WHERE T1.weight = (SELECT MAX(weight) FROM Player)	limit 1, output columns	0	1
1145	Which top 4 leagues had the most games in the 2015-2016 season?	SELECT t1.name FROM League AS t1 INNER JOIN Match AS t2 ON t1.id = t2.league_id WHERE t2.season = '2015/2016' GROUP BY t1.name ORDER BY COUNT(t2.id) DESC LIMIT 4	SELECT name FROM (SELECT t1.name, rank() over (ORDER BY COUNT(t2.id) DESC) as rk FROM League AS t1 INNER JOIN Match AS t2 ON t1.id = t2.league_id WHERE t2.season = '2015/2016' GROUP BY t1.id) WHERE rk <= 4	limit n; group by non-key	1	0

1146	Please provide the full name of the away team that scored the most goals.	SELECT t2.team_long_name FROM Match AS t1 INNER JOIN Team AS t2 ON t1.away_team_api_id = t2.team_api_id ORDER BY t1.away_team_goal DESC LIMIT 1	SELECT team_long_name FROM Team WHERE team_api_id IN (SELECT away_team_api_id FROM Match WHERE away_team_goal = (SELECT MAX(away_team_goal) FROM Match));	limit 1	0	1
1147	Please name one player whose overall strength is the greatest.	SELECT DISTINCT t1.player_name FROM Player AS t1 INNER JOIN Player_Attributes AS t2 ON t1.player_api_id = t2.player_api_id WHERE t2.overall_rating = (SELECT MAX(overall_rating) FROM Player_Attributes)	SELECT player_name FROM Player WHERE player_api_id IN (SELECT player_api_id FROM Player_Attributes WHERE overall_rating = (SELECT MAX(overall_rating) FROM Player_Attributes));	DISTINCT	1	0
1148	What is the percentage of players that are under 180 cm who have an overall strength of more than 70?	SELECT CAST(COUNT(CASE WHEN t2.overall_rating > 70 THEN t1.id ELSE NULL END) AS REAL) * 100 / COUNT(t1.id) percent FROM Player AS t1 INNER JOIN Player_Attributes AS t2 ON t1.player_api_id = t2.player_api_id WHERE t1.height < 180	SELECT (COUNT(DISTINCT Player.player_api_id) * 100.0 / (SELECT COUNT(*) FROM Player)) AS percentage FROM Player JOIN Player_Attributes ON Player.player_api_id = Player_Attributes.player_api_id WHERE Player.height < 180 AND Player_Attributes.overall_rating > 70;	semantic error: wrong condition; lack distinct	0	0
1160	What is the percentage of female patient had total protein not within the normal range?	SELECT CAST(SUM(CASE WHEN T1.SEX = 'F' AND (T2.TP < 6.0 OR T2.TP > 8.5) THEN 1 ELSE 0 END) AS REAL) * 100 / COUNT(*) FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID WHERE T1.SEX = 'F'	SELECT (COUNT(DISTINCT Patient.ID) * 100.0 / (SELECT COUNT(*) FROM Patient WHERE SEX = 'F')) AS Percentage FROM Patient JOIN Laboratory ON Patient.ID = Laboratory.ID WHERE Patient.SEX = 'F' AND (Laboratory.TP < 6.0 OR Laboratory.TP > 8.5);	join -> left join; lack distinct	0	0
1164	How many of the patients with the most serious thrombosis cases examined in 1997 are women?	SELECT COUNT(*) FROM Patient AS T1 INNER JOIN Examination AS T2 ON T1.ID = T2.ID WHERE T1.SEX = 'F' AND STRFTIME('%Y', T2.'Examination Date') = '1997' AND T2.Thrombosis = 1	SELECT COUNT(DISTINCT T1.ID) FROM Examination T1 JOIN Patient T2 ON T1.ID = T2.ID WHERE T1.Thrombosis = 1 AND T2.SEX = 'F' AND strftime('%Y', T1.'Examination Date') = '1997';	lack distinct	0	1
1166	What are the symptoms observed by the youngest patient to ever did a medical examination? Identify their diagnosis.	SELECT T2.Symptoms, T1.Diagnosis FROM Patient AS T1 INNER JOIN Examination AS T2 ON T1.ID = T2.ID WHERE T2.Symptoms IS NOT NULL ORDER BY T1.Birthday DESC LIMIT 1	SELECT Symptoms, Diagnosis FROM (SELECT T2.Symptoms, T1.Diagnosis, rank() over (ORDER BY T1.Birthday DESC) as rk FROM Patient AS T1 INNER JOIN Examination AS T2 ON T1.ID = T2.ID WHERE T2.Symptoms IS NOT NULL) WHERE rk = 1;	limit 1	0	0
1168	The oldest SJS patient's medical laboratory work was completed on what date, and what age was the patient when they initially arrived at the hospital?	SELECT T1.Date, STRFTIME('%Y', T2.'First Date') - STRFTIME('%Y', T2.Birthday), T2.Birthday FROM Laboratory AS T1 INNER JOIN Patient AS T2 ON T1.ID = T2.ID WHERE T2.Diagnosis = 'SJS' AND T2.Birthday IS NOT NULL ORDER BY T2.Birthday ASC LIMIT 1	SELECT L.Date, (strftime('%Y', P.'First Date') - strftime('%Y', P.Birthday)) AS InitialAge FROM Patient P JOIN Laboratory L ON P.ID = L.ID WHERE P.Diagnosis = 'SJS' AND P.Birthday = (SELECT MIN(Birthday) FROM Patient WHERE Diagnosis = 'SJS');	limit 1; semantic error: output column	0	0
1169	What is the ratio of male to female patients among all those with abnormal uric acid counts?	SELECT CAST(SUM(CASE WHEN T2.UA <= 8.0 AND T1.SEX = 'M' THEN 1 ELSE 0 END) AS REAL) / SUM(CASE WHEN T2.UA <= 6.5 AND T1.SEX = 'F' THEN 1 ELSE 0 END) FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID	SELECT CAST(COUNT(DISTINCT CASE WHEN T2.UA <= 8.0 AND T1.SEX = 'M' THEN T1.ID END) AS REAL) / COUNT(DISTINCT CASE WHEN T2.UA <= 6.5 AND T1.SEX = 'F' THEN T1.ID END) FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID	lack distinct	1	0
1170	How many patients hadn't undergone a medical examination until at least a year following their initial hospital visit?	SELECT COUNT(DISTINCT T1.ID) FROM Patient AS T1 INNER JOIN Examination AS T2 ON T1.ID = T2.ID WHERE T1.Admission = '+' AND STRFTIME('%Y', T2.'Examination Date') - STRFTIME('%Y', T1.'First Date') >= 1	SELECT COUNT(DISTINCT T1.ID) FROM Patient AS T1 INNER JOIN Examination AS T2 ON T1.ID = T2.ID WHERE STRFTIME('%Y', T2.'Examination Date') - STRFTIME('%Y', T1.'First Date') >= 1	semantic error: wrong condition	0	0

1171	How many underage patients were examined during the course of the three-year period from 1990 to 1993?	SELECT COUNT(T1.ID) FROM Patient AS T1 INNER JOIN Examination AS T2 ON T1.ID = T2.ID WHERE STRFTIME('%Y', T2.Examination Date) BETWEEN '1990' AND '1993' AND (strftime('%Y', T2.Examination Date) - strftime('%Y', T1.Birthday)) < 18	SELECT COUNT(DISTINCT T1.ID) FROM Patient T1 JOIN Examination T2 ON T1.ID = T2.ID WHERE strftime('%Y', T2.Examination Date) BETWEEN '1990' AND '1993' AND (strftime('%Y', T2.Examination Date) - strftime('%Y', T1.Birthday)) < 18;	lack distinct	0	1
1173	What is the most common illness that doctors identified among the patients whose lab work was done between 1/1/1985, and 12/31/1995?	SELECT T2.Diagnosis FROM Examination AS T1 INNER JOIN Patient AS T2 ON T1.ID = T2.ID WHERE T1.Examination Date BETWEEN '1985-01-01' AND '1995-12-31' GROUP BY T2.Diagnosis ORDER BY COUNT(T2.Diagnosis) DESC LIMIT 1	SELECT Diagnosis FROM Examination WHERE 'Examination Date' BETWEEN '1985-01-01' AND '1995-12-31' GROUP BY Diagnosis HAVING COUNT(Diagnosis) = (SELECT MAX(Cnt) FROM (SELECT COUNT(Diagnosis) AS Cnt FROM Examination WHERE 'Examination Date' BETWEEN '1985-01-01' AND '1995-12-31' GROUP BY Diagnosis) T1);	limit 1	0	1
1174	What is the average age of patients as of year 1999 examined in the laboratory for the October of the year 1991?	SELECT AVG('1999' - STRFTIME('%Y', T2.Birthday)) FROM Laboratory AS T1 INNER JOIN Patient AS T2 ON T1.ID = T2.ID WHERE T1.Date BETWEEN '1991-10-01' AND '1991-10-30'	SELECT AVG(1999 - CAST(strftime('%Y', Birthday) AS INTEGER)) AS Average_Age FROM Patient WHERE ID IN (SELECT ID FROM Laboratory WHERE Date >= '1991-10-01' AND Date <= '1991-10-31');	join -> in-sub; semantic error: wrong condition	0	1
1175	How old was the patient who had the highest hemoglobin count at the time of the examination, and what is the doctor's diagnosis?	SELECT STRFTIME('%Y', T2.Date) - STRFTIME('%Y', T1.Birthday), T1.Diagnosis FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID ORDER BY T2.HGB DESC LIMIT 1	SELECT STRFTIME('%Y', T.Date) - STRFTIME('%Y', Patient.Birthday), Patient.Diagnosis FROM (SELECT Date, ID FROM Laboratory WHERE HGB = (SELECT MAX(HGB) FROM Laboratory)) AS T JOIN Patient ON T.ID = Patient.ID	limit 1	1	0
1178	What was the gender of the first AORTITIS diagnosed patient?	SELECT SEX FROM Patient WHERE Diagnosis = 'AORTITIS' AND 'First Date' IS NOT NULL ORDER BY 'First Date' ASC LIMIT 1	SELECT SEX FROM (SELECT SEX, rank() over (ORDER BY 'First Date' ASC) as rk FROM Patient WHERE Diagnosis = 'AORTITIS' AND 'First Date' IS NOT NULL) WHERE rk = 1	limit 1	1	0
1179	For the patient who was diagnosed with SLE on 1994/2/19, what was his/her anti-Cardiolipin antibody concentration status on 1993/11/12?	SELECT 'aCL IgA', 'aCL IgG', 'aCL IgM' FROM Examination WHERE ID IN (SELECT ID FROM Patient WHERE Diagnosis = 'SLE' AND Description = '1994-02-19') AND 'Examination Date' = '1993-11-12'	SELECT 'aCL IgM' FROM Examination WHERE ID IN (SELECT ID FROM Patient WHERE Diagnosis = 'SLE' AND Description = '1994-02-19') AND 'Examination Date' = '1993-11-12'	semantic error: output column	1	0
1180	Was the patient a man or a woman whose ALT glutamic pyruvic transaminase status got 9 on 1992-6-12?	SELECT T1.SEX FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID WHERE T2.GPT = 9.0 AND T2.Date = '1992-06-12'	SELECT T1.SEX FROM Patient AS T1 WHERE T1.ID IN (SELECT T2.ID FROM Laboratory AS T2 WHERE T2.GPT = 9.0 AND T2.Date = '1992-06-12')	join -> in-sub	0	0
1182	For the patient who first came to the hospital on 1991/6/13 who was diagnosed with SJS, what is the total number of his/her Laboratory tests in 1995?	SELECT COUNT(*) FROM Laboratory WHERE ID = (SELECT ID FROM Patient WHERE 'First Date' = '1991-06-13' AND Diagnosis = 'SJS') AND STRFTIME('%Y', Date) = '1995'	SELECT COUNT(*) FROM Laboratory WHERE ID IN (SELECT ID FROM Patient WHERE 'First Date' = '1991-06-13' AND Diagnosis = 'SJS') AND STRFTIME('%Y', Date) = '1995' GROUP BY ID	semantic error	1	0

1183	For the patient who was diagnosed SLE on 1997/1/27, what was his/her original diagnose when he/she came to the hospital for the first time? 'SLE' AND original diagnose refers to diagnosis; 1997/1/27 refer to 'Examination Date' = '1997-01-27'; first came to the hospital refers to patient.'First Date'	SELECT T1.Diagnosis FROM Patient AS T1 INNER JOIN Examination AS T2 ON T1.ID = T2.ID WHERE T1.ID = (SELECT ID FROM Examination WHERE 'Examination Date' = '1997-01-27' AND Diagnosis = 'SLE') AND T2.'Examination Date' = T1.'First Date'	SELECT T1.Diagnosis FROM Patient AS T1 INNER JOIN Examination AS T2 ON T1.ID = T2.ID WHERE T1.ID IN (SELECT ID FROM Examination WHERE 'Examination Date' = '1997-01-27' AND Diagnosis = 'SLE') AND T2.'Examination Date' = T1.'First Date'	semantic error	1	0
1186	Lists all patients by ID who were diagnosed with Behcet's and had their exams between 01/01/1997 and 12/31/1997. 'Behcet' refers to diagnosis; exam between 01/01/1997 and 12/31/1997 refers to YEAR(Description) > = '1997-1-1' AND YEAR(Description) < '1998-1-1'	SELECT ID FROM Examination WHERE 'Examination Date' BETWEEN '1997-01-01' AND '1997-12-31' AND Diagnosis = 'Behcet'	SELECT DISTINCT ID FROM Examination WHERE 'Examination Date' BETWEEN '1997-01-01' AND '1997-12-31' AND Diagnosis = 'Behcet'	lack distinct	1	0
1189	What number of patients with a degree of thrombosis level 2 and ANA pattern of only S, have a level of anti-Cardiolip in antibody (IgM) 20% higher than average?	SELECT COUNT(*) FROM Examination WHERE Thrombosis = 2 AND 'ANA Pattern' = 'S' AND 'aCL IgM' > (SELECT AVG('aCL IgM') * 1.2 FROM Examination WHERE Thrombosis = 2 AND 'ANA Pattern' = 'S')	SELECT COUNT(DISTINCT ID) FROM Examination WHERE Thrombosis = 2 AND 'ANA Pattern' = 'S' AND 'aCL IgM' > (SELECT AVG('aCL IgM') * 1.2 FROM Examination WHERE Thrombosis = 2 AND 'ANA Pattern' = 'S')	lack distinct	0	0
1190	What percentage of patients with a proteinuria level within the normal range have a uric acid level below the normal range?	SELECT CAST(SUM(CASE WHEN UA <= 6.5 THEN 1 ELSE 0 END) AS REAL) * 100 / COUNT(ID) FROM Laboratory WHERE 'U-PRO' > 0 AND 'U-PRO' < 30	SELECT CAST(COUNT(DISTINCT CASE WHEN UA <= 6.5 THEN ID END) AS REAL) * 100 / COUNT(DISTINCT ID) FROM Laboratory WHERE 'U-PRO' > 0 AND 'U-PRO' < 30	lack distinct	1	0
1194	What sex is the patient who in a medical examination was diagnosed with PSS and in a laboratory examination had a blood level of C-reactive protein de 2+, creatinine 1 and LDH 123?	SELECT T1.SEX FROM Patient AS T1 INNER JOIN Examination AS T2 ON T1.ID = T2.ID INNER JOIN Laboratory AS T3 ON T3.ID = T2.ID WHERE T2.Diagnosis = 'PSS' AND T3.CRP = '2+' AND T3.CRE = 1.0 AND T3.LDH = 123	SELECT T1.SEX FROM Patient AS T1 WHERE T1.ID IN (SELECT T2.ID FROM Examination AS T2 INNER JOIN Laboratory AS T3 ON T3.ID = T2.ID WHERE T2.Diagnosis = 'PSS' AND T3.CRP = '2+' AND T3.CRE = 1.0 AND T3.LDH = 123)	join -> in-sub	1	0

1196	What is the most common sign of patients with SLE disease?	SELECT Symptoms FROM Examination WHERE Diagnosis = 'SLE' GROUP BY Symptoms ORDER BY COUNT(Symptoms) DESC LIMIT 1	SELECT Symptoms FROM (SELECT Symptoms, rank() over (ORDER BY COUNT(Symptoms) DESC) as rk FROM (SELECT DISTINCT ID, Symptoms FROM Examination WHERE Diagnosis = 'SLE') GROUP BY Symptoms) WHERE rk = 1	limit 1	1	0
1197	When was the medical information on patient number 48473 first documented, and what disease did she have?	SELECT 'First Date', Diagnosis FROM Patient WHERE ID = 48473	SELECT Description, Diagnosis FROM Patient WHERE ID = 48473;	semantic mismatch (Description)	0	1
1199	How many patients who underwent testing in 1997 had protein levels outside the normal range?	SELECT COUNT(ID) FROM Laboratory WHERE (ALB <= 6.0 OR ALB >= 8.5) AND STRFTIME('%Y', Date) = '1997'	SELECT COUNT(DISTINCT ID) FROM Laboratory WHERE (ALB <= 6.0 OR ALB >= 8.5) AND STRFTIME('%Y', Date) = '1997'	lack distinct	0	0
1200	What proportion of patients who had signs of thrombocytopenia had SLE diagnosed?	SELECT CAST(SUM(CASE WHEN Diagnosis = 'SLE' THEN 1 ELSE 0 END) AS REAL) * 100 / COUNT(ID) FROM Examination WHERE Symptoms = 'thrombocytopenia'	SELECT CAST(COUNT(CASE WHEN Diagnosis = 'SLE' THEN ID END) AS REAL) * 100 / COUNT(DISTINCT ID) FROM Examination WHERE Symptoms = 'thrombocytopenia';	lack distinct	0	0
1202	How many male patients who underwent testing between 1995 and 1997 and were subsequently diagnosed with Behcet disease did not stay in the hospital for treatment?	SELECT COUNT(T1.ID) FROM Patient AS T1 INNER JOIN Examination AS T2 ON T1.ID = T2.ID WHERE T2.Diagnosis = 'Behcet' AND T1.SEX = 'M' AND STRFTIME('%Y', T2.Examination Date) BETWEEN '1995' AND '1997' AND T1.Admission = '-'	SELECT COUNT(DISTINCT T1.ID) FROM Patient T1 JOIN Examination T2 ON T1.ID = T2.ID WHERE T1.SEX = 'M' AND T1.Admission = '-' AND T2.Examination Date BETWEEN '1995-01-01' AND '1997-12-31' AND T2.Diagnosis = 'Behcet';	lack distinct	0	1
1203	How many patients who were female got white blood cells that were below 3.5?	SELECT COUNT(T1.ID) FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID WHERE T2.WBC < 3.5 AND T1.SEX = 'F'	SELECT COUNT(DISTINCT T1.ID) FROM Patient T1 JOIN Laboratory T2 ON T1.ID = T2.ID WHERE T1.SEX = 'F' AND T2.WBC < 3.5;	lack distinct	0	1
1204	How long did it take after patient number 821298 arrived at the hospital for the first time before her evaluation began?	SELECT STRFTIME('%d', T3.Examination Date) - STRFTIME('%d', T1.First Date) FROM Patient AS T1 INNER JOIN Examination AS T3 ON T1.ID = T3.ID WHERE T1.ID = 821298	SELECT julianday(E.Examination Date) - julianday(P.First Date) AS DaysBetween FROM Patient P JOIN Examination E ON P.ID = E.ID WHERE P.ID = 821298 ORDER BY E.Examination Date LIMIT 1	semantic error	0	0
1207	List all patients with their sex and date of birthday, whose AST glutamic oxaloacetic transaminase (GOT) index is within normal range for laboratory examination in 1994.	SELECT DISTINCT T1.SEX, T1.Birthday FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID WHERE T2.GOT < 60 AND STRFTIME('%Y', T2.Date) = '1994'	SELECT T1.SEX, T1.Birthday FROM Patient AS T1 WHERE T1.ID IN (SELECT T2.ID FROM Laboratory AS T2 WHERE T2.GOT < 60 AND STRFTIME('%Y', T2.Date) = '1994')	join -> in-sub	1	0

1212	For patients with alkaliphosphatase (ALP) within normal range, were they treated as inpatient or outpatient?	SELECT T1.Admission FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID WHERE T2.ALP < 300	SELECT T1.Admission FROM Patient AS T1 WHERE T1.ID IN (SELECT T2.ID FROM Laboratory AS T2 WHERE T2.ALP < 300)	join -> in-sub	0	0
1218	What is the percentage of the female patient whose uric acid (UA) beyond the normal range?	SELECT CAST(SUM(CASE WHEN T2.UA > 6.5 THEN 1 ELSE 0 END) AS REAL) * 100 / COUNT(T1.ID) FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID WHERE T1.SEX = 'F'	SELECT (COUNT(DISTINCT T1.ID) * 100.0 / (SELECT COUNT(*) FROM Patient WHERE SEX = 'F')) AS Percentage FROM Laboratory T1 JOIN Patient T2 ON T1.ID = T2.ID WHERE T2.SEX = 'F' AND T1.UA > 6.5;	join -> left join; lack distinct	0	0
1219	For all patients with normal uric acid (UA), what is the average UA index based on their latest laboratory examination result?	SELECT AVG(T2.UA) FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID WHERE (T2.UA < 6.5 AND T1.SEX = 'F') OR (T2.UA < 8.0 AND T1.SEX = 'M') AND T2.Date = (SELECT MAX(Date) FROM Laboratory)	SELECT avg(UA) FROM (SELECT ID, rank() over (PARTITION BY ID ORDER BY Date DESC) as rk, UA FROM Laboratory WHERE ID IN (SELECT L.ID FROM Laboratory L JOIN Patient P ON L.ID = P.ID WHERE (P.SEX = 'M' AND L.UA < 8.0) OR (P.SEX = 'F' AND L.UA < 6.5))) WHERE rk = 1	semantic error: wrong condition	0	0
1222	How many male patients are with creatinine index out of the normal range?	SELECT COUNT(T1.ID) FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID WHERE T2.CRE >= 1.5 AND T1.SEX = 'M'	SELECT COUNT(DISTINCT T1.ID) FROM Patient T1 JOIN Laboratory T2 ON T1.ID = T2.ID WHERE T1.SEX = 'M' AND T2.CRE >= 1.5;	lack distinct	0	1
1223	Are there more male patients with creatinine not within the normal range than female? Answer by 'True' or 'False'?	SELECT CASE WHEN SUM(CASE WHEN T1.SEX = 'M' THEN 1 ELSE 0 END) > SUM(CASE WHEN T1.SEX = 'F' THEN 1 ELSE 0 END) THEN 'True' ELSE 'False' END FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID WHERE T2.CRE >= 1.5	SELECT CASE WHEN COUNT(DISTINCT CASE WHEN T1.SEX = 'M' THEN T1.ID END) > SUM(DISTINCT CASE WHEN T1.SEX = 'M' THEN T1.ID END) THEN 'True' ELSE 'False' END FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID WHERE T2.CRE >= 1.5;	lack distinct	1	0
1224	What is the highest total bilirubin level recorded? List out the patient details with ID, sex and birthday with that index.	SELECT T2.'T-BIL', T1.ID, T1.SEX, T1.Birthday FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID ORDER BY T2.'T-BIL' DESC LIMIT 1	SELECT ID, SEX, Birthday FROM Patient WHERE ID IN (SELECT ID FROM Laboratory WHERE 'T-BIL' = (SELECT MAX('T-BIL') FROM Laboratory WHERE 'T-BIL' IS NOT NULL));		0	1
1226	Who is the oldest patient with the highest total cholesterol (T-CHO). State the patient ID and T-CHO index.	SELECT T1.ID, T2.'T-CHO' FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID ORDER BY T2.'T-CHO' DESC, T1.Birthday ASC LIMIT 1	SELECT DISTINCT ID, 'T-CHO' FROM (SELECT T1.ID, T2.'T-CHO', rank() over (ORDER BY T2.'T-CHO' DESC, T1.Birthday ASC) as rk FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID) WHERE rk = 1	limit 1	0	0
1227	What is the average age of the male patient with high cholesterol?	SELECT AVG(STRFTIME('%Y', date('NOW')) - STRFTIME('%Y', T1.Birthday)) FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID WHERE T2.'T-CHO' >= 250 AND T1.SEX = 'M'	SELECT AVG(STRFTIME('%Y', date('NOW')) - STRFTIME('%Y', T1.Birthday)) FROM Patient AS T1 WHERE T1.ID IN (SELECT T2.ID FROM Laboratory AS T2 WHERE T2.'T-CHO' >= 250) AND T1.SEX = 'M'	join -> in-sub	0	0
1228	Provide list of patients and their diagnosis with triglyceride (TG) index greater than 100 of the normal range?	SELECT T1.ID, T1.Diagnosis FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID WHERE T2.TG > 300	SELECT DISTINCT T2.ID, T2.Diagnosis FROM Laboratory T1 INNER JOIN Patient T2 ON T1.ID = T2.ID WHERE T1.TG > 300;	lack distinct	0	1
1233	List each patient's ID and blood glucose (GLU) index that were within normal range for patient's whose data was first recorded in 1991.	SELECT DISTINCT T1.ID, T2.GLU FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID WHERE STRFTIME('%Y', T1.'First Date') = '1991' AND T2.GLU < 180	SELECT T1.ID, T2.GLU FROM Patient T1 JOIN Laboratory T2 ON T1.ID = T2.ID WHERE strftime('%Y', T1.Description) = '1991' AND T2.GLU < 180;		0	1

1238	Among the patients who were diagnosed with SLE, who is the oldest with normal hemoglobin level. Provide the ID and sex.	SELECT T1.ID, T1.SEX FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID WHERE T1.Diagnosis = 'SLE' AND T2.HGB > 10 AND T2.HGB < 17 ORDER BY T1.Birthday ASC LIMIT 1	SELECT DISTINCT ID, SEX FROM (SELECT T1.ID, T1.SEX, rank() over (ORDER BY T1.Birthday ASC) as rk FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID WHERE T1.Diagnosis = 'SLE' AND T2.HGB > 10 AND T2.HGB < 17) WHERE rk = 1	lack distinct; limit 1	1	0
1241	For patients with abnormal platelet level, state the number of patients with lower than normal range. How is it compare to the number of patients with higher than normal range?	SELECT SUM(CASE WHEN T2.PLT <= 100 THEN 1 ELSE 0 END) - SUM(CASE WHEN T2.PLT >= 400 THEN 1 ELSE 0 END) FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID	SELECT (SELECT COUNT(DISTINCT ID) FROM Laboratory WHERE PLT <= 100) - (SELECT COUNT(DISTINCT ID) FROM Laboratory WHERE PLT >= 400) AS Difference	lack distinct	0	0
1243	For all patients who are older than 55 years old, what is the percentage of female who has abnormal prothrombin time (PT)?	SELECT CAST(SUM(CASE WHEN T2.PT >= 14 AND T1.SEX = 'F' THEN 1 ELSE 0 END) AS REAL) * 100 / COUNT(*) FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID WHERE STRFTIME('%Y', CURRENT_TIMESTAMP) - STRFTIME('%Y', T1.Birthday) > 55	SELECT CAST(COUNT(DISTINCT CASE WHEN T1.SEX = 'F' THEN T1.ID END) AS REAL) * 100 / COUNT(DISTINCT T1.ID) FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID WHERE STRFTIME('%Y', CURRENT_TIMESTAMP) - STRFTIME('%Y', T1.Birthday) > 55 AND T2.PT >= 14	semantic error: wrong condition; lack distinct	1	0
1244	List all patients who first came to the hospital after year 1992 with prothrombin time (PT) level that are normal.	SELECT T1.ID FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID WHERE STRFTIME('%Y', T1.'First Date') > '1992' AND T2.PT < 14	SELECT DISTINCT T1.ID FROM Patient T1 JOIN Laboratory T2 ON T1.ID = T2.ID WHERE strftime('%Y', T1.'First Date') > '1992' AND T2.PT < 14;	lack distinct	0	1
1249	Please list the disease names of the patients that have a proteinuria level higher than normal.	SELECT T1.Diagnosis FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID WHERE T2.'U-PRO' >= 30	SELECT T1.Diagnosis FROM Patient AS T1 WHERE T1.ID IN (SELECT T2.ID FROM Laboratory AS T2 WHERE T2.'U-PRO' >= 30)	join -> in-sub	1	0
1251	How many patients with an Ig G higher than normal?	SELECT COUNT(DISTINCT T1.ID) FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID INNER JOIN Examination AS T3 ON T3.ID = T2.ID WHERE T2.IGG >= 2000	SELECT COUNT(DISTINCT ID) FROM Laboratory WHERE IGG >= 2000;	semantic error: redundant join	0	1
1252	Among the patients with a normal Ig G level, how many of them have symptoms?	SELECT COUNT(T1.ID) FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID INNER JOIN Examination AS T3 ON T3.ID = T2.ID WHERE T2.IGG BETWEEN 900 AND 2000 AND T3.Symptoms IS NOT NULL	SELECT COUNT(DISTINCT T1.ID) FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID INNER JOIN Examination AS T3 ON T3.ID = T2.ID WHERE T2.IGG BETWEEN 900 AND 2000 AND T3.Symptoms IS NOT NULL	lack distinct	0	0
1253	For the patient who has the highest Ig A within the normal range, what is his or her diagnosis?	SELECT T1.Diagnosis FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID WHERE T2.IGA = (SELECT MAX(IGA) FROM Laboratory WHERE IGA BETWEEN 80 AND 500)	SELECT Diagnosis FROM Patient WHERE ID IN (SELECT ID FROM Laboratory WHERE IGA = (SELECT MAX(IGA) FROM Laboratory WHERE IGA >= 80 AND IGA <= 500));	join -> in-sub	0	1
1254	How many patients with a normal Ig A level came to the hospital after 1990/1/1?	SELECT COUNT(T1.ID) FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID WHERE T2.IGA BETWEEN 80 AND 500 AND strftime('%Y', T1.'First Date') > '1990'	SELECT COUNT(DISTINCT T1.ID) FROM Patient T1 JOIN Laboratory T2 ON T1.ID = T2.ID WHERE T2.IGA > 80 AND T2.IGA < 500 AND strftime('%Y', T1.'First Date') >= '1990';	lack distinct; semantic error: wrong condition	0	1

1255	For the patients with an abnormal Ig M level, what is the most common disease they are diagnosed with?	SELECT T1.Diagnosis FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID WHERE T2.IGM NOT BETWEEN 40 AND 400 GROUP BY T1.Diagnosis ORDER BY COUNT(T1.Diagnosis) DESC LIMIT 1	SELECT Diagnosis FROM (SELECT T1.Diagnosis, rank() over (ORDER BY COUNT(T1.Diagnosis) DESC) as rk FROM Patient AS T1 WHERE T1.ID IN (SELECT T2.ID FROM Laboratory AS T2 WHERE T2.IGM <= 40 OR T2.IGM >= 400) GROUP BY T1.Diagnosis) WHERE rk = 1;	limit 1; join -> in-sub	0	0
1256	How many patients with a abnormal C-reactive protein don't have their data recorded?	SELECT COUNT(T1.ID) FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID WHERE (T2.CRP = '+') AND T1.Description IS NULL	SELECT COUNT(DISTINCT T1.ID) FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID WHERE (T2.CRP = '+') AND T1.Description IS NULL;	lack distinct	0	0
1259	Please list the diseases of the patients born after 1985-1-1 and have a normal Rheumatoid Factor.	SELECT T1.Diagnosis FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID WHERE (T2.RA = '-' OR T2.RA = '+-') AND T1.Birthday > '1985-01-01'	SELECT Diagnosis FROM Patient WHERE ID IN (SELECT ID FROM Laboratory WHERE RA IN ('-', '+-')) AND Birthday > '1985-01-01';	join -> in-sub	0	1
1260	Please list the ID of the patient whose RF is normal and who is older than 60.	SELECT T1.ID FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID WHERE T2.RF < 20 AND STRFTIME('%Y', DATE('now')) - STRFTIME('%Y', T1.Birthday) > 60	SELECT DISTINCT T1.ID FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID WHERE T2.RF < 20 AND STRFTIME('%Y', DATE('now')) - STRFTIME('%Y', T1.Birthday) > 60;	lack distinct	0	0
1263	Among the patients whose level of Hematocrit isn't normal, which patient has the highest anti-Cardiolipin antibody concentration? Please list his or her ID.	SELECT DISTINCT T1.ID FROM Patient AS T1 INNER JOIN Examination AS T2 ON T1.ID = T2.ID INNER JOIN Laboratory AS T3 ON T1.ID = T3.ID WHERE (T3.HCT >= 52 OR T3.HCT <= 29) ORDER BY T2.'aCL IgA' DESC LIMIT 1	SELECT DISTINCT ID FROM (SELECT T1.ID, rank() over (ORDER BY T2.'aCL IgA' DESC) as rk FROM Patient AS T1 INNER JOIN Examination AS T2 ON T1.ID = T2.ID INNER JOIN Laboratory AS T3 ON T1.ID = T3.ID WHERE (T3.HCT >= 52 OR T3.HCT <= 29)) WHERE rk = 1;	limit 1	0	0
1265	How many patients have a normal level of anti-ribonuclear protein and have been admitted to the hospital?	SELECT COUNT(DISTINCT T1.ID) FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID WHERE T2.RNP = 'negative' OR T2.RNP = '0' AND T1.Admission = '+'	SELECT COUNT(DISTINCT T1.ID) FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID WHERE T2.RNP = 'negative' OR T2.RNP IN ('-', '+-') AND T1.Admission = '+'	semantic error: wrong condition	0	0
1266	Which is the youngest patient with an abnormal anti-ribonuclear protein level? Please list his or her date of birth.	SELECT T1.Birthday FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID WHERE T2.RNP != '-' OR '+' ORDER BY T1.Birthday DESC LIMIT 1	SELECT Birthday FROM (SELECT T1.Birthday, rank() over (ORDER BY T1.Birthday DESC) as rk FROM Patient AS T1 WHERE T1.ID IN (SELECT T2.ID FROM Laboratory AS T2 WHERE T2.RNP NOT IN ('-', '+-'))) WHERE rk = 1	limit 1	1	0
1267	Among the patients with normal anti-SM, how many of them does not have thrombosis?	SELECT COUNT(T1.ID) FROM Examination AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID WHERE T2.SM IN ('negative','0') AND T1.Thrombosis = 0	SELECT COUNT(DISTINCT T1.ID) FROM Examination AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID WHERE T2.SM IN ('negative', '0') AND T1.Thrombosis = 0	lack distinct	1	0
1268	For the patients with an abnormal anti-SM, please list the IDs of the three youngest ones.	SELECT T1.ID FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID WHERE T2.SM NOT IN ('negative','0') ORDER BY T1.Birthday DESC LIMIT 3	SELECT ID FROM (SELECT ID, rank() over (ORDER BY Birthday DESC) AS RK FROM Patient WHERE ID IN (SELECT ID FROM Laboratory WHERE SM NOT IN ('negative', '0')))) WHERE rk <= 3	limit n; join -> in-sub	0	0
1269	Please list the IDs of the patients who had the examination done after 1997/1/1 and had a normal anti-scl70.	SELECT T1.ID FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID WHERE T2.SC170 IN ('negative','0') AND T2.Date > 1997-01-01	SELECT DISTINCT E.ID FROM Examination E JOIN Laboratory L ON E.ID = L.ID WHERE E.Examination Date' > '1997-01-01' AND L.SC170 IN ('negative', '0');	lack distinct; semantic error: wrong condition	0	1

1272	Which patient is the first patient with an abnormal anti-SSA to come to the hospital? Please give his or her ID.	SELECT T1.ID FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID WHERE T1.'First Date' IS NOT NULL AND T2.SSA NOT IN ('negative', '0') ORDER BY T1.'First Date' ASC LIMIT 1	SELECT DISTINCT ID FROM (SELECT T1.ID, rank() over (ORDER BY T1.'First Date' ASC) as rk FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID WHERE T1.'First Date' IS NOT NULL AND T2.SSA NOT IN ('negative', '0')) WHERE rk = 1	limit 1	1	0
1274	For the patients whose anti-SSB are normal, how many of them have other symptoms observed in their examination?	SELECT COUNT(DISTINCT T1.ID) FROM Examination AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID WHERE T2.SSB = 'negative' OR '0' AND T1.Symptoms IS NOT NULL	SELECT COUNT(DISTINCT T1.ID) FROM Laboratory T1 JOIN Examination T2 ON T1.ID = T2.ID WHERE T1.SSB IN ('negative', '0') AND T2.Symptoms IS NOT NULL;	semantic error: wrong condition	0	1
1276	For the patients who have an abnormal level of anti-DNA, please list the diseases they are diagnosed with.	SELECT DISTINCT(T1.Diagnosis) FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID WHERE T2.DNA >= 8	SELECT T1.Diagnosis FROM Patient AS T1 WHERE T1.ID IN (SELECT T2.ID FROM Laboratory AS T2 WHERE T2.DNA >= 8)	join -> in-sub	1	0
1278	Of the patients with an normal level of IGG, how many of them admitted to the hospital?	SELECT COUNT(T1.ID) FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID WHERE T2.IGG > 900 AND T2.IGG < 2000 AND T1.Admission = '+'	SELECT COUNT(DISTINCT T1.ID) FROM Patient T1 JOIN Laboratory T2 ON T1.ID = T2.ID WHERE T2.IGG > 900 AND T2.IGG < 2000 AND T1.Admission = '+';	lack distinct	0	1
1279	What is the percentage of patient who has a abnormal level of glutamic oxaloacetic transaminase level, yet he or she is diagnosed with SLE?	SELECT COUNT(CASE WHEN T1.Diagnosis LIKE '%SLE%' THEN T1.ID ELSE 0 END) / COUNT(T1.ID) FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID WHERE T2.'GOT' >= 60	SELECT COUNT(DISTINCT CASE WHEN T1.Diagnosis = 'SLE' THEN T1.ID END) * 100.0 / COUNT(DISTINCT T1.ID) FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID WHERE T2.'GOT' >= 60;	lack distinct	0	0
1280	How many male patients have their glutamic oxaloacetic transaminase in the normal range?	SELECT COUNT(T1.ID) FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID WHERE T2.GOT < 60 AND T1.SEX = 'M'	SELECT COUNT(DISTINCT T1.ID) FROM Patient T1 JOIN Laboratory T2 ON T1.ID = T2.ID WHERE T1.SEX = 'M' AND T2.GOT < 60;	lack distinct	0	1
1281	Among the patients who have an abnormal level of glutamic oxaloacetic transaminase, when was the youngest of them born?	SELECT T1.Birthday FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID WHERE T2.GOT >= 60 ORDER BY T1.Birthday DESC LIMIT 1	SELECT Birthday FROM (SELECT T1.Birthday, rank() over (ORDER BY T1.Birthday DESC) as rk FROM Patient AS T1 WHERE T1.ID IN (SELECT T2.ID FROM Laboratory AS T2 WHERE T2.GOT >= 60)) WHERE rk = 1;	limit 1	1	0
1282	Please list the top three patients' birthdays with the highest glutamic pylvic transaminase in the normal range.	SELECT T1.Birthday FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID WHERE T2.GPT < 60 ORDER BY T2.GPT DESC LIMIT 3	SELECT Birthday FROM (SELECT T2.Birthday, rank() over (ORDER BY MAX(T1.GPT) DESC) as rk FROM Laboratory T1 JOIN Patient T2 ON T1.ID = T2.ID WHERE T1.GPT < 60 GROUP BY T1.ID, T2.Birthday) WHERE rk <= 3	limit n	0	0
1283	For the patients with the normal glutamic pylvic transaminase level, how many of them are male?	SELECT COUNT(T1.ID) FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID WHERE T2.GOT < 60 AND T1.SEX = 'M'	SELECT COUNT(DISTINCT T1.ID) FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID WHERE T2.GOT < 60 AND T1.SEX = 'M'	lack distinct	1	0

1284	For the patient with the highest lactate dehydrogenase in the normal range, when was his or her data first recorded?	SELECT T1.'First Date' FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID WHERE T2.LDH = (SELECT MAX(LDH) FROM Laboratory WHERE LDH < 500)	SELECT T1.'First Date' FROM Patient AS T1 WHERE T1.ID IN (SELECT T2.ID FROM Laboratory AS T2 WHERE T2.LDH = (SELECT MAX(LDH) FROM Laboratory WHERE LDH < 500));	join -> in-sub	1	0
1285	When is the latest patient's medical data recorded? This patient should have an abnormal level of lactate dehydrogenase.	SELECT T1.'First Date' FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID WHERE T2.LDH >= 500 ORDER BY T1.'First Date' DESC LIMIT 1	SELECT 'First Date' FROM (SELECT T1.'First Date', rank() over (ORDER BY T1.'First Date' DESC) as rk FROM Patient AS T1 WHERE T1.ID IN (SELECT T2.ID FROM Laboratory AS T2 WHERE T2.LDH >= 500)) WHERE rk = 1	limit 1	0	0
1286	For the patient with an abnormal alkaliphosphatase level, how many of them are admitted to the hospital?	SELECT COUNT(T1.ID) FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID WHERE T2.ALP >= 300 AND T1.Admission = '+'	SELECT COUNT(DISTINCT T1.ID) FROM Laboratory T1 JOIN Patient T2 ON T1.ID = T2.ID WHERE T1.ALP >= 300 AND T2.Admission = '+';	lack distinct	0	1
1287	Among the patients followed at the outpatient clinic, how many of them have a normal level of alkaliphosphatase?	SELECT COUNT(T1.ID) FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID WHERE T2.ALP < 300 AND T1.Admission = '-'	SELECT COUNT(DISTINCT T1.ID) FROM Patient T1 JOIN Laboratory T2 ON T1.ID = T2.ID WHERE T1.Admission = '-' AND T2.ALP < 300;	lack distinct	0	1
1288	Please list the diagnosis of the patients whose total protein is lower than normal.	SELECT T1.Diagnosis FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID WHERE T2.TP < 6.0	SELECT Diagnosis FROM Patient WHERE ID IN (SELECT ID FROM Laboratory WHERE TP < 6.0);	join -> in-sub	0	1
1289	For the patients who are diagnosed with SJS, how many of them have a normal level of total protein?	SELECT COUNT(T1.ID) FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID WHERE T1.Diagnosis = 'SJS' AND T2.TP > 6.0 AND T2.TP < 8.5	SELECT COUNT(DISTINCT T1.ID) FROM Patient T1 JOIN Laboratory T2 ON T1.ID = T2.ID WHERE T1.Diagnosis = 'SJS' AND T2.TP > 6.0 AND T2.TP < 8.5;	lack distinct	0	1
1291	How many male patients have a normal level of both albumin and total protein?	SELECT COUNT(T1.ID) FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID WHERE T1.SEX = 'M' AND T2.ALB > 3.5 AND T2.ALB < 5.5 AND T2.TP BETWEEN 6.0 AND 8.5	SELECT COUNT(DISTINCT T1.ID) FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID WHERE T1.SEX = 'M' AND T2.ALB > 3.5 AND T2.ALB < 5.5 AND T2.TP BETWEEN 6.0 AND 8.5	lack distinct	0	0
1292	What is the anti Cardiolipin antibody concentration of the female patient with the highest uric acid level in the normal range?	SELECT T3.'aCL IgG', T3.'aCL IgM', T3.'aCL IgA' FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID INNER JOIN Examination AS T3 ON T3.ID = T2.ID WHERE T1.SEX = 'F' AND T2.UA > 6.5 ORDER BY T2.UA DESC LIMIT 1	SELECT 'aCL IgG', 'aCL IgM', 'aCL IgA' FROM Examination WHERE ID IN (SELECT Patient.ID FROM Laboratory JOIN Patient on Laboratory.ID = Patient.ID WHERE UA > 6.5 AND SEX = 'F' AND UA = (SELECT MAX(UA) FROM Laboratory JOIN Patient on Laboratory.ID = Patient.ID WHERE UA > 6.5 AND SEX = 'F'))	join -> in-sub	1	0
1294	Please list the patient's ID whose creatinine level is normal and whose anti Cardiolipin antibody concentration level is the highest.	SELECT T2.ID FROM Laboratory AS T1 INNER JOIN Examination AS T2 ON T1.ID = T2.ID WHERE T1.CRE < 1.5 ORDER BY T2.'aCL IgA' DESC LIMIT 1	SELECT DISTINCT ID FROM (SELECT T2.ID, rank() over (ORDER BY T2.'aCL IgA' DESC) as rk FROM Laboratory AS T1 INNER JOIN Examination AS T2 ON T1.ID = T2.ID WHERE T1.CRE < 1.5) WHERE rk = 1	limit 1	1	0

1295	Among the patients whose total bilirubin is over the normal range, how many of them have a peripheral pattern observed in the sheet of ANA examination?	SELECT COUNT(T1.ID) FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID INNER JOIN Examination AS T3 ON T1.ID = T3.ID WHERE T2.'T-BIL' >= 2 AND T3.'ANA Pattern' LIKE '%P%'	SELECT COUNT(DISTINCT T1.ID) FROM Laboratory T1 JOIN Examination T2 ON T1.ID = T2.ID WHERE T1.'T-BIL' >= 2.0 AND T2.'ANA Pattern' LIKE '%P%';	lack distinct	0	1
1296	What is the anti-nucleus antibody concentration of the patient whose total bilirubin is the highest in the normal range?	SELECT T3.ANA FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID INNER JOIN Examination AS T3 ON T1.ID = T3.ID WHERE T2.'T-BIL' < 2.0 ORDER BY T2.'T-BIL' DESC LIMIT 1	SELECT E.ANA FROM Examination E JOIN (SELECT ID, MAX('T-BIL') AS MaxBil FROM Laboratory WHERE 'T-BIL' < 2.0 GROUP BY ID HAVING MaxBil = (SELECT MAX('T-BIL') FROM Laboratory WHERE 'T-BIL' < 2.0)) L ON E.ID = L.ID;	limit 1	0	1
1297	For the patients whose total cholesterol is higher than normal, how many of them have a negative measure of degree of coagulation?	SELECT COUNT(T1.ID) FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID INNER JOIN Examination AS T3 ON T1.ID = T3.ID WHERE T2.'T-CHO' >= 250 AND T3.KCT = '-'	SELECT COUNT(DISTINCT T1.ID) FROM Laboratory T1 JOIN Examination T2 ON T1.ID = T2.ID WHERE T1.'T-CHO' >= 250 AND T2.KCT = '-';	lack distinct	0	1
1298	Among the patients whose total cholesterol is within the normal range, how many of them have a P pattern observed in the sheet of ANA examination?	SELECT COUNT(T1.ID) FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID INNER JOIN Examination AS T3 ON T1.ID = T3.ID WHERE T3.'ANA Pattern' = 'P' AND T2.'T-CHO' < 250	SELECT COUNT(DISTINCT T1.ID) FROM Laboratory T1 JOIN Examination T2 ON T1.ID = T2.ID WHERE T1.'T-CHO' < 250 AND T2.'ANA Pattern' = 'P';	lack distinct	0	1
1299	Among the patients with the normal level of triglyceride, how many of them have other symptoms observed?	SELECT COUNT(T1.ID) FROM Examination AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID WHERE T2.TG < 200 AND T1.Symptoms IS NOT NULL	SELECT COUNT(DISTINCT T1.ID) FROM Laboratory T1 JOIN Examination T2 ON T1.ID = T2.ID WHERE T1.TG < 200 AND T2.Symptoms IS NOT NULL;	lack distinct	0	1
1300	What is the disease name of the patient who has the highest level of triglyceride within the normal range?	SELECT T1.Diagnosis FROM Examination AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID WHERE T2.TG < 200 ORDER BY T2.TG DESC LIMIT 1	SELECT P.Diagnosis FROM Patient P WHERE P.ID IN (SELECT L.ID FROM Laboratory L WHERE L.TG = (SELECT MAX(TG) FROM Laboratory WHERE TG < 200));	limit 1	0	0
1302	For the patients with a normal range of creatinine phosphokinase, how many of them have a positive measure of degree of coagulation?	SELECT COUNT(T1.ID) FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID INNER JOIN Examination AS T3 ON T1.ID = T3.ID WHERE T2.CPK < 250 AND (T3.KCT = '+' OR T3.RVVT = '+' OR T3.LAC = '+')	SELECT COUNT(DISTINCT T1.ID) FROM Laboratory T1 JOIN Examination T2 ON T1.ID = T2.ID WHERE T1.CPK < 250 AND (T2.KCT = '+' OR T2.RVVT = '+' OR T2.LAC = '+');	lack distinct	0	1
1303	When is the birthday of the oldest patient whose blood glucose is abnormal?	SELECT T1.Birthday FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID WHERE T2.GLU > 180 ORDER BY T1.Birthday ASC LIMIT 1	SELECT Birthday FROM (SELECT T1.Birthday, rank() over (ORDER BY T1.Birthday ASC) as rk FROM Patient AS T1 WHERE T1.ID IN (SELECT T2.ID FROM Laboratory AS T2 WHERE T2.GLU > 180)) WHERE rk = 1	limit 1	1	0

1304	Among the patients with a normal blood glucose, how many of them don't have thrombosis?	SELECT COUNT(T1.ID) FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID INNER JOIN Examination AS T3 ON T1.ID = T3.ID WHERE T2.GLU < 180 AND T3.Thrombosis = 0	SELECT COUNT(DISTINCT T1.ID) FROM Laboratory T1 JOIN Examination T2 ON T1.ID = T2.ID WHERE T1.GLU < 180 AND T2.Thrombosis = 0;	DISTINCT	0	1
1305	How many patients accepted to the hospital have a normal level of white blood cells?	SELECT COUNT(T1.ID) FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID WHERE T2.WBC BETWEEN 3.5 AND 9 AND T1.Admission = '+'	SELECT COUNT(DISTINCT T1.ID) FROM Patient T1 JOIN Laboratory T2 ON T1.ID = T2.ID WHERE T1.Admission = '+' AND T2.WBC BETWEEN 3.5 AND 9.0;	DISTINCT	0	1
1306	How many patients diagnosed with SLE have a normal white blood cell level?	SELECT COUNT(T1.ID) FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID WHERE T1.Diagnosis = 'SLE' AND T2.WBC BETWEEN 3.5 AND 9	SELECT COUNT(DISTINCT T1.ID) FROM Patient T1 JOIN Laboratory T2 ON T1.ID = T2.ID WHERE T1.Diagnosis = 'SLE' AND T2.WBC BETWEEN 3.5 AND 9.0;	DISTINCT	0	1
1308	Among the patients who have a normal platelet level, how many of them have other symptoms observed?	SELECT COUNT(T1.ID) FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID WHERE T2.PLT > 100 AND T2.PLT < 400 AND T1.Diagnosis IS NOT NULL	SELECT COUNT(DISTINCT T1.ID) FROM Laboratory T1 JOIN Examination T2 ON T1.ID = T2.ID WHERE T1.PLT > 100 AND T1.PLT < 400 AND T2.Symptoms IS NOT NULL;	DISTINCT	1	0
1311	How many patients with severe thrombosis have a normal prothrombin time?	SELECT COUNT(T1.ID) FROM Patient AS T1 INNER JOIN Laboratory AS T2 ON T1.ID = T2.ID INNER JOIN Examination AS T3 ON T1.ID = T3.ID WHERE T2.PT < 14 AND T3.Thrombosis < 3 AND T3.Thrombosis > 0	SELECT COUNT(DISTINCT T1.ID) FROM Examination T1 JOIN Laboratory T2 ON T1.ID = T2.ID WHERE T1.Thrombosis IN (1, 2) AND T2.PT < 14;	DISTINCT	0	1
1315	How many students of the Student_Club have attended the event "Women's Soccer"?	SELECT COUNT(T1.event_id) FROM event AS T1 INNER JOIN attendance AS T2 ON T1.event_id = T2.link_to_event WHERE T1.event_name = 'Women's Soccer'	SELECT COUNT(DISTINCT T2.link_to_member) FROM event AS T1 INNER JOIN attendance AS T2 ON T1.event_id = T2.link_to_event WHERE T1.event_name = 'Women's Soccer';	lack distinct	1	0
1316	Please list the phone numbers of the students from the Student_Club that has attended the event "Women's Soccer".	SELECT T3.phone FROM event AS T1 INNER JOIN attendance AS T2 ON T1.event_id = T2.link_to_event INNER JOIN member AS T3 ON T2.link_to_member = T3.member_id WHERE T1.event_name = 'Women's Soccer'	SELECT phone FROM member WHERE member_id IN (SELECT T2.link_to_member FROM event AS T1 INNER JOIN attendance AS T2 ON T1.event_id = T2.link_to_event WHERE T1.event_name = 'Women's Soccer')	join -> in-sub	1	0
1317	Among the students from the Student_Club who attended the event "Women's Soccer", how many of them want a T-shirt that's in medium size?	SELECT COUNT(T1.event_id) FROM event AS T1 INNER JOIN attendance AS T2 ON T1.event_id = T2.link_to_event INNER JOIN member AS T3 ON T2.link_to_member = T3.member_id WHERE T1.event_name = 'Women's Soccer' AND T3.t_shirt_size = 'Medium'	SELECT COUNT(DISTINCT T3.member_id) FROM event AS T1 INNER JOIN attendance AS T2 ON T1.event_id = T2.link_to_event INNER JOIN member AS T3 ON T2.link_to_member = T3.member_id WHERE T1.event_name = 'Women's Soccer' AND T3.t_shirt_size = 'Medium';	lack distinct	1	0
1318	What is the event that has the highest attendance of the students from the Student_Club?	SELECT T1.event_name FROM event AS T1 INNER JOIN attendance AS T2 ON T1.event_id = T2.link_to_event GROUP BY T1.event_name HAVING COUNT(T2.link_to_event) = (SELECT MAX(attendance_count) FROM (SELECT COUNT(link_to_event) AS attendance_count FROM attendance GROUP BY link_to_event) AS subquery)	SELECT T1.event_name FROM event AS T1 INNER JOIN attendance AS T2 ON T1.event_id = T2.link_to_event GROUP BY T1.event_id HAVING COUNT(T2.link_to_event) = (SELECT MAX(attendance_count) FROM (SELECT COUNT(link_to_event) AS attendance_count FROM attendance GROUP BY link_to_event) AS subquery);	group by non-key	0	0

1319	Which college is the vice president of the Student_Club from?	SELECT T2.college FROM member AS T1 INNER JOIN major AS T2 ON T1.link_to_major = T2.major_id WHERE T1.position LIKE 'vice president'	SELECT T2.college FROM member AS T1 INNER JOIN major AS T2 ON T1.link_to_major = T2.major_id WHERE T1.position LIKE 'Vice President'	str: 'Vice President'	0	0
1320	Please list the event names of all the events attended by Maya Mclean.	SELECT T1.event_name FROM event AS T1 INNER JOIN attendance AS T2 ON T1.event_id = T2.link_to_event INNER JOIN member AS T3 ON T2.link_to_member = T3.member_id WHERE T3.first_name = 'Maya' AND T3.last_name = 'Mclean'	SELECT T3.event_name FROM event T3 WHERE EXISTS (SELECT 1 FROM attendance T2 JOIN member T1 ON T2.link_to_member = T1.member_id WHERE T1.first_name = 'Maya' AND T1.last_name = 'Mclean' AND T2.link_to_event = T3.event_id);	join -> in-sub	1	0
1321	How many events of the Student_Club did Sacha Harrison attend in 2019?	SELECT COUNT(T1.event_id) FROM event AS T1 INNER JOIN attendance AS T2 ON T1.event_id = T2.link_to_event INNER JOIN member AS T3 ON T2.link_to_member = T3.member_id WHERE T3.first_name = 'Sacha' AND T3.last_name = 'Harrison' AND SUBSTR(T1.event_date, 1, 4) = '2019'	SELECT COUNT(DISTINCT T3.event_id) FROM member T1 INNER JOIN attendance T2 ON T1.member_id = T2.link_to_member INNER JOIN event T3 ON T2.link_to_event = T3.event_id WHERE T1.first_name = 'Sacha' AND T1.last_name = 'Harrison' AND strftime('%Y', T3.event_date) = '2019';	lack distinct	0	1
1322	Among the events attended by more than 10 members of the Student_Club, how many of them are meetings?	SELECT T1.event_name FROM event AS T1 INNER JOIN attendance AS T2 ON T1.event_id = T2.link_to_event GROUP BY T1.event_id HAVING COUNT(T2.link_to_event) > 10 EXCEPT SELECT T1.event_name FROM event AS T1 WHERE T1.type = 'Meeting'	SELECT COUNT(DISTINCT event.event_id) FROM event JOIN attendance ON event.event_id = attendance.link_to_event WHERE event.type = 'Meeting' GROUP BY event.event_id HAVING COUNT(attendance.link_to_member) > 10;	except non-key	0	1
1323	List all the names of events that had an attendance of over 20 students but were not fundraisers.	SELECT T1.event_name FROM event AS T1 INNER JOIN attendance AS T2 ON T1.event_id = T2.link_to_event GROUP BY T1.event_id HAVING COUNT(T2.link_to_event) > 20 EXCEPT SELECT T1.event_name FROM event AS T1 WHERE T1.type = 'Fundraiser'	SELECT T1.event_name FROM event AS T1 INNER JOIN attendance AS T2 ON T1.event_id = T2.link_to_event WHERE T1.type != 'Fundraiser' GROUP BY T1.event_id HAVING COUNT(T2.link_to_event) > 20;	except non-key	1	0
1324	What is the average attendance of meetings in 2020?	SELECT CAST(COUNT(T2.link_to_event) AS REAL) / COUNT(DISTINCT T2.link_to_event) FROM event AS T1 INNER JOIN attendance AS T2 ON T1.event_id = T2.link_to_event WHERE SUBSTR(T1.event_date, 1, 4) = '2020' AND T1.type = 'Meeting'	SELECT AVG(total_attendance) FROM (SELECT COUNT(T1.link_to_event) AS total_attendance FROM event T2 LEFT JOIN attendance T1 ON T2.event_id = T1.link_to_event WHERE T2.type = 'Meeting' AND strftime('%Y', T2.event_date) = '2020' GROUP BY T2.event_id)	join -> left join	0	1
1325	What is the most expensive item that was spent in support of club events?	SELECT expense_description FROM expense ORDER BY cost DESC LIMIT 1	SELECT expense_description FROM expense WHERE cost = (SELECT max(cost) FROM expense);	limit 1	1	0
1327	List the full name of all the members of the Student_Club who attended the "Laugh Out Loud" event.	SELECT T1.first_name, T1.last_name FROM member AS T1 INNER JOIN attendance AS T2 ON T1.member_id = T2.link_to_member INNER JOIN event AS T3 ON T2.link_to_event = T3.event_id WHERE T3.event_name = 'Laugh Out Loud'	SELECT T1.first_name, T1.last_name FROM member AS T1 WHERE T1.member_id IN (SELECT T2.link_to_member FROM attendance AS T2 INNER JOIN event AS T3 ON T2.link_to_event = T3.event_id WHERE T3.event_name = 'Laugh Out Loud');	join -> in-sub	1	0
1330	What college offers the major that Tyler Hewitt took?	SELECT T2.college FROM member AS T1 INNER JOIN major AS T2 ON T1.link_to_major = T2.major_id WHERE T1.first_name = 'Tyler' AND T1.last_name = 'Hewitt'	SELECT DISTINCT T2.college FROM member AS T1 INNER JOIN major AS T2 ON T1.link_to_major = T2.major_id WHERE T1.first_name = 'Tyler' AND T1.last_name = 'Hewitt'	lack distinct	1	0
1331	What is the amount of the funds that the Vice President received? 'Vice President' is a position of Student_Club; funds received refers to amount.	SELECT T2.amount FROM member AS T1 INNER JOIN income AS T2 ON T1.member_id = T2.link_to_member WHERE T1.position = 'Vice President'	SELECT SUM(T2.amount) FROM member T1 JOIN income T2 ON T1.member_id = T2.link_to_member WHERE T1.position = 'Vice President';	semantic error: output col	1	0

1332	How much did the Student_Club members spend on food in September Meeting?	SELECT T2.spent FROM event AS T1 INNER JOIN budget AS T2 ON T1.event_id = T2.link_to_event WHERE T1.event_name = 'September Meeting' AND T2.category = 'Food' AND SUBSTR(T1.event_date, 6, 2) = '09'	SELECT T2.spent FROM event T1 JOIN budget T2 ON T1.event_id = T2.link_to_event WHERE T1.event_name = 'September Meeting' AND T2.category = 'Food'	semantic error: wrong condition	0	1
1335	How much did the Student_Club members spend on advertisement in September Meeting?	SELECT T2.spent FROM event AS T1 INNER JOIN budget AS T2 ON T1.event_id = T2.link_to_event WHERE T1.event_name = 'September Meeting' AND T2.category = 'Advertisement' AND SUBSTR(T1.event_date, 6, 2) = '09'	SELECT T2.spent FROM event AS T1 INNER JOIN budget AS T2 ON T1.event_id = T2.link_to_event WHERE T1.event_name = 'September Meeting' AND T2.category = 'Advertisement'	semantic error: wrong condition	1	0
1336	What department offers the major that Pierce and Guidi took?	SELECT T2.department FROM member AS T1 INNER JOIN major AS T2 ON T1.link_to_major = T2.major_id WHERE T1.last_name = 'Pierce' OR T1.last_name = 'Guidi'	SELECT DISTINCT T2.department FROM member AS T1 INNER JOIN major AS T2 ON T1.link_to_major = T2.major_id WHERE T1.last_name = 'Pierce' OR T1.last_name = 'Guidi'		0	0
1338	Was each expense in October Meeting on October 8, 2019 approved?	SELECT T3.approved FROM event AS T1 INNER JOIN budget AS T2 ON T1.event_id = T2.link_to_event INNER JOIN expense AS T3 ON T2.budget_id = T3.link_to_budget WHERE T1.event_name = 'October Meeting' AND T1.event_date LIKE '2019-10-08%'	SELECT T3.approved FROM event AS T1 INNER JOIN budget AS T2 ON T1.event_id = T2.link_to_event INNER JOIN expense AS T3 ON T2.budget_id = T3.link_to_budget WHERE T1.event_name = 'October Meeting' AND T1.event_date = '2019-10-08'	semantic: wrong condition	1	0
1350	What is the status of the event which bought "Post Cards, Posters" on 2019/8/20? "Post Cards, Posters" is an expense description; on 2019/8/20 refers to expense_date = '2019-8-20'; status of event refers to event_status	SELECT T1.event_status FROM budget AS T1 INNER JOIN expense AS T2 ON T1.budget_id = T2.link_to_budget WHERE T2.expense_description = 'Post Cards, Posters' AND T2.expense_date = '2019-08-20'	SELECT event_status FROM budget WHERE budget_id IN (SELECT link_to_budget FROM expense WHERE expense_description = 'Post Cards, Posters' AND expense_date = '2019-08-20')	join -> in-sub	1	0
1358	Who was the first one paid his/her dues? Tell the full name.	SELECT T1.first_name, T1.last_name FROM member AS T1 INNER JOIN income AS T2 ON T1.member_id = T2.link_to_member WHERE T2.source = 'Dues' ORDER BY T2.date_received LIMIT 1	SELECT first_name, last_name FROM member WHERE member_id IN (SELECT link_to_member FROM income WHERE source = 'Dues' AND date_received = (SELECT min(date_received) FROM income WHERE source = 'Dues'))	join -> in-sub	1	0
1367	Which college do most of the members go to?	SELECT T2.college FROM member AS T1 INNER JOIN major AS T2 ON T1.link_to_major = T2.major_id GROUP BY T2.major_id ORDER BY COUNT(T2.college) DESC LIMIT 1	SELECT college FROM (SELECT college, COUNT(member_id) AS member_count FROM major JOIN member ON major_id = link_to_major GROUP BY college) WHERE member_count = (SELECT MAX(member_count) FROM (SELECT COUNT(member_id) AS member_count FROM major JOIN member ON major_id = link_to_major GROUP BY college));	limit 1; semantic error	0	1
1369	Which event has the highest budget amount?	SELECT T2.event_name FROM budget AS T1 INNER JOIN event AS T2 ON T1.link_to_event = T2.event_id ORDER BY T1.amount DESC LIMIT 1	SELECT T2.event_name FROM event T2 WHERE T2.event_id IN (SELECT T1.link_to_event FROM budget T1 GROUP BY T1.link_to_event HAVING SUM(T1.amount) = (SELECT MAX(total_amount) FROM (SELECT SUM(amount) AS total_amount FROM budget GROUP BY link_to_event)))	limit 1; schema flaw: lack constraint unique budget.link_to_event	0	1
1370	List all the expenses incurred by the vice president.	SELECT T2.expense_id, T2.expense_description FROM member AS T1 INNER JOIN expense AS T2 ON T1.member_id = T2.link_to_member WHERE T1.position = 'Vice President'	SELECT E.expense_description FROM expense E JOIN member M ON E.link_to_member = M.member_id WHERE M.position = 'Vice President';	semantic error: output column	0	1

1371	How many members attended the "Women's Soccer" event? 'Women's Soccer' is the event name;	SELECT COUNT(T2.link_to_member) FROM event AS T1 INNER JOIN attendance AS T2 ON T1.event_id = T2.link_to_event WHERE T1.event_name = 'Women's Soccer'	SELECT COUNT(DISTINCT link_to_member) FROM attendance WHERE link_to_event IN (SELECT event_id FROM event WHERE event_name = 'Women's Soccer');	lack distinct	0	1
1374	How many events did the member with the phone number '954-555-6240' attend?	SELECT COUNT(T2.link_to_event) FROM member AS T1 INNER JOIN attendance AS T2 ON T1.member_id = T2.link_to_member WHERE T1.phone = '954-555-6240'	SELECT COUNT(DISTINCT link_to_event) FROM attendance INNER JOIN member ON attendance.link_to_member = member.member_id WHERE member.phone = '954-555-6240';	lack distinct	0	1
1376	Among all the closed events, which event has the highest spend-to-budget ratio?	SELECT T2.event_name FROM budget AS T1 INNER JOIN event AS T2 ON T1.link_to_event = T2.event_id WHERE T2.status = 'Closed' ORDER BY T1.spent / T1.amount DESC LIMIT 1	SELECT event_name FROM (SELECT T2.event_name, rank() over (ORDER BY T1.spent / T1.amount DESC) as rk FROM budget AS T1 INNER JOIN event AS T2 ON T1.link_to_event = T2.event_id WHERE T2.status = 'Closed') WHERE rk = 1	limit 1	1	0
1382	Among the students majored in interior design, who have attended the Community Theater event?	SELECT T2.first_name, T2.last_name FROM major AS T1 INNER JOIN member AS T2 ON T1.major_id = T2.link_to_major INNER JOIN attendance AS T3 ON T2.member_id = T3.link_to_member INNER JOIN event AS T4 ON T3.link_to_event = T4.event_id WHERE T4.event_name = 'Community Theater' AND T1.major_name = 'Interior Design'	SELECT T2.first_name, T2.last_name FROM major AS T1 INNER JOIN member AS T2 ON T1.major_id = T2.link_to_major WHERE T1.major_name = 'Interior Design' AND T2.member_id IN (SELECT T3.link_to_member FROM attendance AS T3 INNER JOIN event AS T4 ON T3.link_to_event = T4.event_id WHERE T4.event_name = 'Community Theater')	join -> in-sub	1	0
1384	How many income generated by Grant Gilmour?	SELECT T2.amount FROM member AS T1 INNER JOIN income AS T2 ON T1.member_id = T2.link_to_member WHERE T1.first_name = 'Grant' AND T1.last_name = 'Gilmour'	SELECT TOTAL(income.amount) FROM member JOIN income ON member.member_id = income.link_to_member WHERE member.first_name = 'Grant' AND member.last_name = 'Gilmour';	semantic error	0	1
1385	Which student was able to generate income more than \$40?	SELECT T1.first_name, T1.last_name FROM member AS T1 INNER JOIN income AS T2 ON T1.member_id = T2.link_to_member WHERE T2.amount > 40	SELECT first_name, last_name FROM member WHERE member_id IN (SELECT link_to_member FROM income WHERE amount > 40);	join -> in-sub	0	1
1387	Which student has been entrusted to manage the budget for the Yearly Kickoff?	SELECT T4.first_name, T4.last_name FROM event AS T1 INNER JOIN budget AS T2 ON T1.event_id = T2.link_to_event INNER JOIN expense AS T3 ON T2.budget_id = T3.link_to_budget INNER JOIN member AS T4 ON T3.link_to_member = T4.member_id WHERE T1.event_name = 'Yearly Kickoff'	SELECT T4.first_name, T4.last_name FROM member AS T4 WHERE T4.member_id IN (SELECT T3.link_to_member FROM event AS T1 INNER JOIN budget AS T2 ON T1.event_id = T2.link_to_event INNER JOIN expense AS T3 ON T2.budget_id = T3.link_to_budget WHERE T1.event_name = 'Yearly Kickoff');	join -> in-sub	0	0
1389	Which event has the lowest cost?	SELECT T1.event_name FROM event AS T1 INNER JOIN budget AS T2 ON T1.event_id = T2.link_to_event INNER JOIN expense AS T3 ON T2.budget_id = T3.link_to_budget WHERE T3.cost = (SELECT MIN(T6.cost) FROM event AS T4 INNER JOIN budget AS T5 ON T4.event_id = T5.link_to_event INNER JOIN expense AS T6 ON T5.budget_id = T6.link_to_budget)	SELECT T3.event_name FROM event T3 WHERE EXISTS (SELECT 1 FROM budget T2 JOIN expense T1 ON T2.budget_id = T1.link_to_budget WHERE T2.link_to_event = T3.event_id GROUP BY T2.link_to_event HAVING MIN(T1.cost) = (SELECT MIN(cost) FROM expense WHERE cost IS NOT NULL))	join -> in-sub	0	1
1391	What is the ratio between students majored in finance and physics?	SELECT SUM(CASE WHEN major_name = 'Finance' THEN 1 ELSE 0 END) / SUM(CASE WHEN major_name = 'Physics' THEN 1 ELSE 0 END) AS ratio FROM major	SELECT SUM(CASE WHEN major_name = 'Finance' THEN 1 ELSE 0 END) / SUM(CASE WHEN major_name = 'Physics' THEN 1 ELSE 0 END) AS ratio FROM major JOIN member ON major.major_id = member.link_to_major	semantic error	0	0
1392	Indicate the top source of funds received in September 2019 based on their amount.	SELECT source FROM income WHERE date_received BETWEEN '2019-09-01' and '2019-09-30' ORDER BY source DESC LIMIT 1	SELECT source FROM income WHERE date_received BETWEEN '2019-09-01' AND '2019-09-30' GROUP BY source HAVING SUM(amount) = (SELECT MAX(total_amount) FROM (SELECT SUM(amount) AS total_amount FROM income WHERE date_received BETWEEN '2019-09-01' AND '2019-09-30' GROUP BY source) T2);	limit 1	0	1

1395	How many members did attend the event 'Community Theater' in 2019?	SELECT COUNT(T2.link_to_member) FROM event AS T1 INNER JOIN attendance AS T2 ON T1.event_id = T2.link_to_event WHERE T1.event_name = 'Community Theater' AND SUBSTR(T1.event_date, 1, 4) = '2019'	SELECT COUNT(DISTINCT T2.link_to_member) FROM event T1 JOIN attendance T2 ON T1.event_id = T2.link_to_event WHERE T1.event_name = 'Community Theater' AND strftime('%Y', T1.event_date) = '2019';	lack distinct	0	1
1396	Provide the number of events attended by Luisa Guidi. What is her major?	SELECT COUNT(T3.link_to_event), T1.major_name FROM major AS T1 INNER JOIN member AS T2 ON T1.major_id = T2.link_to_major INNER JOIN attendance AS T3 ON T2.member_id = T3.link_to_member WHERE T2.first_name = 'Luisa' AND T2.last_name = 'Guidi'	SELECT COUNT(T3.link_to_event), T1.major_name FROM major AS T1 INNER JOIN member AS T2 ON T1.major_id = T2.link_to_major INNER JOIN attendance AS T3 ON T2.member_id = T3.link_to_member WHERE T2.first_name = 'Luisa' AND T2.last_name = 'Guidi' GROUP BY T2.member_id	lack group by	0	0
1398	Name the event with the highest amount spent on advertisement.	SELECT T2.event_name FROM budget AS T1 INNER JOIN event AS T2 ON T1.link_to_event = T2.event_id WHERE T1.category = 'Advertisement' ORDER BY T1.spent DESC LIMIT 1	SELECT T2.event_name FROM event T2, (SELECT link_to_event, MAX(spent) AS max_spent FROM budget WHERE category = 'Advertisement' GROUP BY link_to_event) T1 WHERE T2.event_id = T1.link_to_event AND T1.max_spent = (SELECT MAX(spent) FROM budget WHERE category = 'Advertisement');	limit 1	0	1
1399	Did Maya Mclean attend the 'Women's Soccer' event? Answer by 'YES' or 'NO' for each record.	SELECT CASE WHEN T3.event_name = 'Women's Soccer' THEN 'YES' END AS result FROM member AS T1 INNER JOIN attendance AS T2 ON T1.member_id = T2.link_to_member INNER JOIN event AS T3 ON T2.link_to_event = T3.event_id WHERE T1.first_name = 'Maya' AND T1.last_name = 'Mclean'	SELECT CASE WHEN member_id IN (SELECT attendance.link_to_member FROM attendance INNER JOIN event ON link_to_event = event_id WHERE event_name = 'Women's Soccer') THEN 'YES' ELSE 'NO' END AS result FROM (SELECT * FROM member WHERE first_name = 'Maya' AND last_name = 'Mclean')		1	0
1402	What is the most popular size of t-shirt ordered by the club members?	SELECT t_shirt_size FROM member GROUP BY t_shirt_size ORDER BY COUNT(t_shirt_size) DESC LIMIT 1	SELECT t_shirt_size FROM (SELECT t_shirt_size, rank() over (ORDER BY COUNT(t_shirt_size) DESC) as rk FROM member GROUP BY t_shirt_size) WHERE rk = 1;	limit 1	0	0
1403	Indicate the name of the closed event whose cost has exceeded the budget the most.	SELECT T2.event_name FROM budget AS T1 INNER JOIN event AS T2 ON T2.event_id = T1.link_to_event WHERE T1.event_status = 'Closed' AND T1.remaining < 0 ORDER BY T1.remaining LIMIT 1	SELECT event_name FROM event WHERE event_id IN (SELECT event_id FROM (SELECT T1.event_id, rank() over (ORDER BY T2.remaining ASC) as rk FROM event T1 JOIN budget T2 ON T1.event_id = T2.link_to_event WHERE T1.status = 'Closed' AND T2.remaining < 0) WHERE rk = 1)	limit 1	0	0
1407	Among the budgets for Advertising, list out top three which have the most budgeted amount?	SELECT budget_id FROM budget WHERE category = 'Advertisement' ORDER BY amount DESC LIMIT 3	SELECT budget_id FROM (SELECT budget_id, rank() over (ORDER BY amount DESC) as rk FROM budget WHERE category = 'Advertisement') WHERE rk <= 3	limit n	0	0
1411	State what kind of expenses that Sacha Harrison incurred?	SELECT T2.expense_description FROM member AS T1 INNER JOIN expense AS T2 ON T1.member_id = T2.link_to_member WHERE T1.first_name = 'Sacha' AND T1.last_name = 'Harrison'	SELECT DISTINCT T2.expense_description FROM member AS T1 INNER JOIN expense AS T2 ON T1.member_id = T2.link_to_member WHERE T1.first_name = 'Sacha' AND T1.last_name = 'Harrison'	lack distinct	1	0
1412	What kind of expenses incurred by members who have X-Large in size of tee shirt?	SELECT T2.expense_description FROM member AS T1 INNER JOIN expense AS T2 ON T1.member_id = T2.link_to_member WHERE T1.t_shirt_size = 'X-Large'	SELECT DISTINCT T2.expense_description FROM member AS T1 INNER JOIN expense AS T2 ON T1.member_id = T2.link_to_member WHERE T1.t_shirt_size = 'X-Large'	lack distinct	1	0
1413	Mention the zip code of member who incurred less than 50USD.	SELECT T1.zip FROM member AS T1 INNER JOIN expense AS T2 ON T1.member_id = T2.link_to_member WHERE T2.cost < 50	SELECT T1.zip FROM member AS T1 WHERE member_id IN (SELECT T2.link_to_member FROM expense AS T2 WHERE T2.cost < 50);	join -> in-sub	0	0
1414	State the name of major that Phillip Cullen has joined.	SELECT T1.major_name FROM major AS T1 INNER JOIN member AS T2 ON T1.major_id = T2.link_to_major WHERE T2.first_name = 'Phillip' AND T2.last_name = 'Cullen'	SELECT T1.major_name FROM major AS T1 WHERE T1.major_id IN (SELECT T2.link_to_major FROM member AS T2 WHERE T2.first_name = 'Phillip' AND T2.last_name = 'Cullen')	join -> in-sub	1	0

1417	List out the type of events which have remaining budget more than 30 USD.	SELECT T1.type FROM event AS T1 INNER JOIN budget AS T2 ON T1.event_id = T2.link_to_event WHERE T2.remaining > 30	SELECT T1.type FROM event AS T1 WHERE T1.event_id IN (SELECT T2.link_to_event FROM budget AS T2 WHERE T2.remaining > 30);	join -> in-sub	0	0
1418	Mention the category of events which were held at MU 215.	SELECT T2.category FROM event AS T1 INNER JOIN budget AS T2 ON T1.event_id = T2.link_to_event WHERE T1.location = 'MU 215'	SELECT T1.type FROM event AS T1 WHERE T1.location = 'MU 215'	semantic error: category of events	1	0
1419	What is the category of event which was taken place in 2020-03-24T12:00:00?	SELECT T2.category FROM event AS T1 INNER JOIN budget AS T2 ON T1.event_id = T2.link_to_event WHERE T1.event_date = '2020-03-24T12:00:00'	SELECT T1.type FROM event AS T1 WHERE T1.event_date = '2020-03-24T12:00:00'	semantic error: category of events	1	0
1420	State the name of major that Vice President has joined.	SELECT T1.major_name FROM major AS T1 INNER JOIN member AS T2 ON T1.major_id = T2.link_to_major WHERE T2.position = 'Vice President'	SELECT T1.major_name FROM major AS T1 WHERE major_id IN (SELECT T2.link_to_major FROM member AS T2 WHERE T2.position = 'Vice President')	join -> in-sub	1	0
1422	State the category of events were held at MU 215. 'MU 215' is the location of event;	SELECT DISTINCT T2.category FROM event AS T1 INNER JOIN budget AS T2 ON T1.event_id = T2.link_to_event WHERE T1.location = 'MU 215'	SELECT T1.type FROM event AS T1 WHERE T1.location = 'MU 215'	semantic error: category of events	1	0
1427	What are the budget category of the events located at MU 215 and a guest speaker type with a 0 budget spent?	SELECT DISTINCT T2.category, T1.type FROM event AS T1 INNER JOIN budget AS T2 ON T1.event_id = T2.link_to_event WHERE T1.location = 'MU 215' AND T2.spent = 0 AND T1.type = 'Guest Speaker'	SELECT DISTINCT T2.category FROM event AS T1 INNER JOIN budget AS T2 ON T1.event_id = T2.link_to_event WHERE T1.location = 'MU 215' AND T2.spent = 0 AND T1.type = 'Guest Speaker';	semantic error: output column	0	0
1429	What is the name of the social event that was attended by the vice president of the Student Club located at 900 E. Washington St.?	SELECT T2.event_name FROM attendance AS T1 INNER JOIN event AS T2 ON T2.event_id = T1.link_to_event INNER JOIN member AS T3 ON T1.link_to_member = T3.member_id WHERE T3.position = 'Vice President' AND T2.location = '900 E. Washington St.' AND T2.type = 'Social'	SELECT event_name FROM event WHERE event_id IN (SELECT link_to_event FROM attendance WHERE link_to_member IN (SELECT member_id FROM member WHERE position = 'Vice President')) AND type = 'Social' AND location = '900 E. Washington St.'	join -> in-sub	0	1
1430	What is the last name and position of the student that bought pizza on 09/10/2019?	SELECT T1.last_name, T1.position FROM member AS T1 INNER JOIN expense AS T2 ON T1.member_id = T2.link_to_member WHERE T2.expense_date = '2019-09-10' AND T2.expense_description = 'Pizza'	SELECT T1.last_name, T1.position FROM member AS T1 WHERE member_id IN (SELECT T2.link_to_member FROM expense AS T2 WHERE T2.expense_date = '2019-09-10' AND T2.expense_description = 'Pizza');	join -> in-sub	1	0
1431	List the last name of the members of the club that attended the women's soccer event.	SELECT T3.last_name FROM attendance AS T1 INNER JOIN event AS T2 ON T2.event_id = T1.link_to_event INNER JOIN member AS T3 ON T1.link_to_member = T3.member_id WHERE T2.event_name = 'Women's Soccer' AND T3.position = 'Member'	SELECT last_name FROM member WHERE member_id IN (SELECT link_to_member FROM attendance JOIN event ON event_id = link_to_event WHERE event_name = 'Women's Soccer') AND position = 'Member'	join -> in-sub	1	0
1435	List the names of closed event as "game" that was closed from 3/15/2019 to 3/20/2020.	SELECT DISTINCT event_name FROM event WHERE type = 'Game' AND date(SUBSTR(event_date, 1, 10)) BETWEEN '2019-03-15' AND '2020-03-20' AND status = 'Closed'	SELECT event_name FROM event WHERE type = 'Game' AND status = 'Closed' AND event_date BETWEEN '2019-03-15' AND '2020-03-20';	redundant distinct	0	1
1440	List emails of people who paid more than 20 dollars from 9/10/2019 to 11/19/2019.	SELECT DISTINCT T1.email FROM member AS T1 INNER JOIN expense AS T2 ON T1.member_id = T2.link_to_member WHERE date(SUBSTR(T2.expense_date, 1, 10)) BETWEEN '2019-09-10' AND '2019-11-19' AND T2.cost > 20	SELECT T1.email FROM member AS T1 INNER JOIN expense AS T2 ON T1.member_id = T2.link_to_member WHERE date(SUBSTR(T2.expense_date, 1, 10)) BETWEEN '2019-09-10' AND '2019-11-19' GROUP BY member_id HAVING SUM(T2.cost) > 20;	semantic error: pay more than 20 dollars	0	0
1441	How many members have education major in the College of Education & Human Services? 'education' is the major name; 'Member' is a position of club;	SELECT COUNT(T1.member_id) FROM member AS T1 INNER JOIN major AS T2 ON T2.major_id = T1.link_to_major WHERE T1.position = 'Member' AND T2.major_name LIKE '%Education%' AND T2.college = 'College of Education & Human Services'	SELECT COUNT(T1.member_id) FROM member AS T1 INNER JOIN major AS T2 ON T2.major_id = T1.link_to_major WHERE T1.position = 'Member' AND T2.major_name = 'education' AND T2.college = 'College of Education & Human Services'	str?	1	0

1442	What is the percentage of the events that went over budget?	SELECT CAST(SUM(CASE WHEN remaining < 0 THEN 1 ELSE 0 END) AS REAL) * 100 / COUNT(budget_id) FROM budget	SELECT (COUNT(DISTINCT CASE WHEN B.remaining < 0 THEN link_to_event END) * 100.0 / (SELECT count(*) FROM event)) AS percentage_over_budget FROM budget B;	semantic error: over budget	0	0
1447	List the name and location of events that underspend its budget.	SELECT DISTINCT T1.event_name, T1.location FROM event AS T1 INNER JOIN budget AS T2 ON T1.event_id = T2.link_to_event WHERE T2.remaining > 0	SELECT event_name, location FROM event WHERE event_id IN (SELECT link_to_event FROM budget WHERE remaining > 0);	join -> in-sub	0	1
1448	Find the name and date of events with expenses for pizza that were more than fifty dollars but less than a hundred dollars.	SELECT T1.event_name, T1.event_date FROM event AS T1 INNER JOIN budget AS T2 ON T1.event_id = T2.link_to_event INNER JOIN expense AS T3 ON T2.budget_id = T3.link_to_budget WHERE T3.expense_description = 'Pizza' AND T3.cost > 50 AND T3.cost < 100	SELECT T1.event_name, T1.event_date FROM event AS T1 WHERE T1.event_id IN (SELECT T2.link_to_event FROM budget AS T2 INNER JOIN expense AS T3 ON T2.budget_id = T3.link_to_budget WHERE T3.expense_description = 'Pizza' AND T3.cost > 50 AND T3.cost < 100)	join -> in-sub	1	0
1449	What is the name and major of members who had to spend more than a hundred dollars on an expense?	SELECT DISTINCT T1.first_name, T1.last_name, T2.major_name FROM member AS T1 INNER JOIN major AS T2 ON T2.major_id = T1.link_to_major INNER JOIN expense AS T3 ON T1.member_id = T3.link_to_member WHERE T3.cost > 100	SELECT DISTINCT T1.first_name, T1.last_name, T2.major_name FROM member AS T1 INNER JOIN major AS T2 ON T2.major_id = T1.link_to_major WHERE T1.member_id IN (SELECT link_to_member FROM expense AS T3 WHERE T3.cost > 100)	join -> in-sub	0	0
1451	Among the members who incurred expenses in more than one event, who paid the most amount?	SELECT T2.member_id FROM expense AS T1 INNER JOIN member AS T2 ON T1.link_to_member = T2.member_id INNER JOIN budget AS T3 ON T1.link_to_budget = T3.budget_id INNER JOIN event AS T4 ON T3.link_to_event = T4.event_id GROUP BY T2.member_id HAVING COUNT(DISTINCT T4.event_id) > 1 ORDER BY SUM(T1.cost) DESC LIMIT 1	SELECT member_id FROM (SELECT T2.member_id, rank() over (ORDER BY SUM(T1.cost) DESC) as rk FROM expense AS T1 INNER JOIN member AS T2 ON T1.link_to_member = T2.member_id INNER JOIN budget AS T3 ON T1.link_to_budget = T3.budget_id INNER JOIN event AS T4 ON T3.link_to_event = T4.event_id GROUP BY T2.member_id HAVING COUNT(DISTINCT T4.event_id) > 1) WHERE rk = 1	limit 1	0	0
1452	What is the average amount paid by students in a position other than a member?	SELECT AVG(T1.cost) FROM expense AS T1 INNER JOIN member AS T2 ON T1.link_to_member = T2.member_id WHERE T2.position != 'Member'	SELECT SUM(T1.cost) / COUNT(DISTINCT T3.link_to_event) FROM expense AS T1 INNER JOIN member AS T2 ON T1.link_to_member = T2.member_id INNER JOIN budget AS T3 ON T3.budget_id = T1.link_to_budget WHERE T2.position != 'Member';	semantic error: average amount	1	0
1453	List the name of events with less than average parking cost.	SELECT T1.event_name FROM event AS T1 INNER JOIN budget AS T2 ON T1.event_id = T2.link_to_event INNER JOIN expense AS T3 ON T2.budget_id = T3.link_to_budget WHERE T2.category = 'Parking' AND T3.cost < (SELECT AVG(cost) FROM expense)	SELECT event_name FROM event WHERE event_id IN (SELECT link_to_event FROM budget WHERE category = 'Parking' AND budget_id IN (SELECT link_to_budget FROM expense GROUP BY link_to_budget HAVING SUM(cost) < (SELECT SUM(cost) / COUNT(DISTINCT link_to_event) FROM budget JOIN expense ON budget_id = link_to_budget WHERE category = 'Parking')))	semantic error: less than average parking cost	0	1
1455	Which budget allowed the most money for water, chips, and cookies?	SELECT T2.budget_id FROM expense AS T1 INNER JOIN budget AS T2 ON T1.link_to_budget = T2.budget_id WHERE T1.expense_description = 'Water, chips, cookies' ORDER BY T1.cost DESC LIMIT 1	SELECT DISTINCT budget_id FROM (SELECT T2.budget_id, rank() over (ORDER BY T1.cost DESC) as rk FROM expense AS T1 INNER JOIN budget AS T2 ON T1.link_to_budget = T2.budget_id WHERE T1.expense_description = 'Water, chips, cookies') WHERE rk = 1	limit 1	1	0
1456	List the full name of the top five members who spend the most money in the descending order of spending.	SELECT T3.first_name, T3.last_name FROM expense AS T1 INNER JOIN budget AS T2 ON T1.link_to_budget = T2.budget_id INNER JOIN member AS T3 ON T1.link_to_member = T3.member_id ORDER BY T2.spent DESC LIMIT 5	WITH Total AS (SELECT link_to_member, SUM(cost) AS total_spending FROM expense WHERE cost IS NOT NULL GROUP BY link_to_member) SELECT T1.first_name, T1.last_name FROM member AS T1 INNER JOIN (SELECT * FROM Total WHERE total_spending IN (SELECT total_spending FROM Total ORDER BY total_spending DESC LIMIT 5)) AS T2 ON T1.member_id = T2.link_to_member ORDER BY T2.total_spending DESC	limit n; missing agg	0	0

1457	Give the full name and contact number of members who had to spend more than average on each expense.	SELECT DISTINCT T3.first_name, T3.last_name, T3.phone FROM expense AS T1 INNER JOIN budget AS T2 ON T1.link_to_budget = T2.budget_id INNER JOIN member AS T3 ON T3.member_id = T1.link_to_member WHERE T1.cost > (SELECT AVG(T1.cost) FROM expense AS T1 INNER JOIN budget AS T2 ON T1.link_to_budget = T2.budget_id INNER JOIN member AS T3 ON T3.member_id = T1.link_to_member)	SELECT first_name, last_name, phone FROM member WHERE member_id IN (SELECT DISTINCT link_to_member FROM expense group by link_to_member HAVING MIN(cost) > (SELECT AVG(cost) FROM expense))	join -> in-sub; semantic error: on each expense	0	0
1458	Calculate the difference in the percentage of members in New Jersey and Vermont.	SELECT CAST((SUM(CASE WHEN T2.state = 'New Jersey' THEN 1 ELSE 0 END) - SUM(CASE WHEN T2.state = 'Vermont' THEN 1 ELSE 0 END)) AS REAL) * 100 / COUNT(T1.member_id) AS diff FROM member AS T1 INNER JOIN zip_code AS T2 ON T2.zip_code = T1.zip	SELECT CAST((SUM(CASE WHEN T2.state = 'New Jersey' THEN 1 ELSE 0 END) - SUM(CASE WHEN T2.state = 'Vermont' THEN 1 ELSE 0 END)) AS REAL) * 100 / COUNT(T1.member_id) AS diff FROM (SELECT * FROM member WHERE position = 'Member') AS T1 INNER JOIN zip_code AS T2 ON T2.zip_code = T1.zip	semantic error: missing filter	0	0
1460	Write the full name of the member who spent money for water, veggie tray and supplies and include the cost of it.	SELECT T2.first_name, T2.last_name, T1.cost FROM expense AS T1 INNER JOIN member AS T2 ON T1.link_to_member = T2.member_id WHERE T1.expense_description = 'Water, Veggie tray, supplies'	SELECT T2.first_name, T2.last_name, SUM(T1.cost) FROM expense AS T1 INNER JOIN member AS T2 ON T1.link_to_member = T2.member_id WHERE T1.expense_description = 'Water, Veggie tray, supplies' GROUP BY T2.member_id	semantic error	1	0
1462	What category was budgeted for the 'January Speaker' event and how much was the amount budgeted for that category?	SELECT T2.category, T2.amount FROM event AS T1 INNER JOIN budget AS T2 ON T1.event_id = T2.link_to_event WHERE T1.event_name = 'January Speaker'	SELECT category, SUM(amount) FROM budget WHERE link_to_event IN (SELECT event_id FROM event WHERE event_name = 'January Speaker') GROUP BY category	join -> in-sub; semantic error: missing agg	1	0
1463	List the event names which were budgeted for the food.	SELECT T1.event_name FROM event AS T1 INNER JOIN budget AS T2 ON T1.event_id = T2.link_to_event WHERE T2.category = 'Food'	SELECT event_name FROM event WHERE event_id IN (SELECT link_to_event FROM budget WHERE category = 'Food');	JOIN	0	1
1464	Write the full names of students who received funds on the date of 9/9/2019 and include the amount received.	SELECT DISTINCT T3.first_name, T3.last_name, T4.amount FROM event AS T1 INNER JOIN attendance AS T2 ON T1.event_id = T2.link_to_event INNER JOIN member AS T3 ON T3.member_id = T2.link_to_member INNER JOIN income AS T4 ON T4.link_to_member = T3.member_id WHERE T4.date_received = '2019-09-09'	SELECT T1.first_name, T1.last_name, T2.amount FROM member T1 JOIN income T2 ON T1.member_id = T2.link_to_member WHERE T2.date_received = '2019-09-09';	redundant DISTINCT; redundant JOIN	1	0
1465	Which budget category does the expense 'Posters' fall to? 'Posters' refers to expense description	SELECT DISTINCT T2.category FROM expense AS T1 INNER JOIN budget AS T2 ON T1.link_to_budget = T2.budget_id WHERE T1.expense_description = 'Posters'	SELECT category FROM budget WHERE budget_id IN (SELECT link_to_budget FROM expense WHERE expense_description = 'Posters');	JOIN duplicate, redundant DISTINCT	0	1
1467	Calculate the total amount spent on speaker gifts and list the name of the event they were spent on.	SELECT SUM(T1.spent), T2.event_name FROM budget AS T1 INNER JOIN event AS T2 ON T1.link_to_event = T2.event_id WHERE T1.category = 'Speaker Gifts' GROUP BY T2.event_name	SELECT SUM(T1.spent), T2.event_name FROM budget AS T1 INNER JOIN event AS T2 ON T1.link_to_event = T2.event_id WHERE T1.category = 'Speaker Gifts' GROUP BY T2.event_id	group by non-key	1	0
1472	In 2012, who had the least consumption in LAM?	SELECT T1.CustomerID FROM customers AS T1 INNER JOIN yearmonth AS T2 ON T1.CustomerID = T2.CustomerID WHERE T1.Segment = 'LAM' AND SUBSTR(T2.Date, 1, 4) = '2012' GROUP BY T1.CustomerID ORDER BY SUM(T2.Consumption) ASC LIMIT 1	SELECT CustomerID FROM (SELECT T1.CustomerID, rank() over (ORDER BY SUM(T2.Consumption) ASC) as rk FROM customers AS T1 INNER JOIN yearmonth AS T2 ON T1.CustomerID = T2.CustomerID WHERE T1.Segment = 'LAM' AND SUBSTR(T2.Date, 1, 4) = '2012' GROUP BY T1.CustomerID) WHERE rk = 1	limit 1	1	0

1473	What was the average monthly consumption of customers in SME for the year 2013?	SELECT AVG(T2.Consumption) / 12 FROM customers AS T1 INNER JOIN yearmonth AS T2 ON T1.CustomerID = T2.CustomerID WHERE SUBSTR(T2.Date, 1, 4) = '2013' AND T1.Segment = 'SME'	SELECT AVG(T2.Consumption) FROM customers AS T1 INNER JOIN yearmonth AS T2 ON T1.CustomerID = T2.CustomerID WHERE SUBSTR(T2.Date, 1, 4) = '2013' AND T1.Segment = 'SME'	semantic error: output column	0	0
1474	Which customers, paying in CZK, consumed the most gas in 2011?	SELECT T1.CustomerID FROM customers AS T1 INNER JOIN yearmonth AS T2 ON T1.CustomerID = T2.CustomerID WHERE T1.Currency = 'CZK' AND T2.Date BETWEEN 201101 AND 201112 GROUP BY T1.CustomerID ORDER BY SUM(T2.Consumption) DESC LIMIT 1	SELECT CustomerID FROM (SELECT T1.CustomerID, rank() over (ORDER BY SUM(T2.Consumption) DESC) as rk FROM customers AS T1 INNER JOIN yearmonth AS T2 ON T1.CustomerID = T2.CustomerID WHERE T1.Currency = 'CZK' AND T2.Date BETWEEN 201101 AND 201112 GROUP BY T1.CustomerID) WHERE rk = 1	limit 1	0	0
1477	Which year recorded the most gas use paid in EUR?	SELECT SUBSTRING(T2.Date, 1, 4) FROM customers AS T1 INNER JOIN yearmonth AS T2 ON T1.CustomerID = T2.CustomerID WHERE T1.Currency = 'EUR' GROUP BY SUBSTRING(T2.Date, 1, 4) ORDER BY SUM(T2.Consumption) DESC LIMIT 1	SELECT year FROM (SELECT SUBSTRING(T2.Date, 1, 4) as year, rank() over (ORDER BY SUM(T2.Consumption) DESC) as rk FROM customers AS T1 INNER JOIN yearmonth AS T2 ON T1.CustomerID = T2.CustomerID WHERE T1.Currency = 'EUR' GROUP BY SUBSTRING(T2.Date, 1, 4)) WHERE rk = 1	limit 1	1	0
1478	Which segment had the least consumption?	SELECT T1.Segment FROM customers AS T1 INNER JOIN yearmonth AS T2 ON T1.CustomerID = T2.CustomerID GROUP BY T1.Segment ORDER BY SUM(T2.Consumption) ASC LIMIT 1	SELECT Segment FROM (SELECT T1.Segment, rank() over (ORDER BY SUM(T2.Consumption) ASC) as rk FROM customers AS T1 INNER JOIN yearmonth AS T2 ON T1.CustomerID = T2.CustomerID GROUP BY T1.Segment) WHERE rk = 1	limit 1	1	0
1479	Which year recorded the most consumption of gas paid in CZK?	SELECT SUBSTR(T2.Date, 1, 4) FROM customers AS T1 INNER JOIN yearmonth AS T2 ON T1.CustomerID = T2.CustomerID WHERE T1.Currency = 'CZK' GROUP BY SUBSTR(T2.Date, 1, 4) ORDER BY SUM(T2.Consumption) DESC LIMIT 1	SELECT year FROM (SELECT SUBSTR(T2.Date, 1, 4) as year, rank() over (ORDER BY SUM(T2.Consumption) DESC) as rk FROM customers AS T1 INNER JOIN yearmonth AS T2 ON T1.CustomerID = T2.CustomerID WHERE T1.Currency = 'CZK' GROUP BY SUBSTR(T2.Date, 1, 4)) WHERE rk = 1	limit 1	1	0
1480	What was the gas consumption peak month for SME customers in 2013?	SELECT SUBSTR(T2.Date, 5, 2) FROM customers AS T1 INNER JOIN yearmonth AS T2 ON T1.CustomerID = T2.CustomerID WHERE SUBSTR(T2.Date, 1, 4) = '2013' AND T1.Segment = 'SME' GROUP BY SUBSTR(T2.Date, 5, 2) ORDER BY SUM(T2.Consumption) DESC LIMIT 1	SELECT month FROM (SELECT SUBSTR(T2.Date, 5, 2) as month, rank() over (ORDER BY SUM(T2.Consumption) DESC) as rk FROM customers AS T1 INNER JOIN yearmonth AS T2 ON T1.CustomerID = T2.CustomerID WHERE SUBSTR(T2.Date, 1, 4) = '2013' AND T1.Segment = 'SME' GROUP BY SUBSTR(T2.Date, 5, 2)) WHERE rk = 1	limit 1	0	0
1481	What is the difference in the annual average consumption of the customers with the least amount of consumption paid in CZK for 2013 between SME and LAM, LAM and KAM, and KAM and SME?	SELECT CAST(SUM(IIF(T1.Segment = 'SME', T2.Consumption, 0)) AS REAL) / COUNT(T1.CustomerID) - CAST(SUM(IIF(T1.Segment = 'LAM', T2.Consumption, 0)) AS REAL) / COUNT(T1.CustomerID) , CAST(SUM(IIF(T1.Segment = 'LAM', T2.Consumption, 0)) AS REAL) / COUNT(T1.CustomerID) - CAST(SUM(IIF(T1.Segment = 'KAM', T2.Consumption, 0)) AS REAL) / COUNT(T1.CustomerID) , CAST(SUM(IIF(T1.Segment = 'KAM', T2.Consumption, 0)) AS REAL) / COUNT(T1.CustomerID) - CAST(SUM(IIF(T1.Segment = 'SME', T2.Consumption, 0)) AS REAL) / COUNT(T1.CustomerID) FROM customers AS T1 INNER JOIN yearmonth AS T2 ON T1.CustomerID = T2.CustomerID WHERE T1.Currency = 'CZK' AND T2.Consumption = (SELECT MIN(Consumption) FROM yearmonth) AND T2.Date BETWEEN 201301 AND 201312	SELECT CAST(SUM(IIF(T1.Segment = 'SME', T2.Consumption, 0)) AS REAL) / COUNT(T1.CustomerID) - CAST(SUM(IIF(T1.Segment = 'LAM', T2.Consumption, 0)) AS REAL) / COUNT(T1.CustomerID), CAST(SUM(IIF(T1.Segment = 'LAM', T2.Consumption, 0)) AS REAL) / COUNT(T1.CustomerID) - CAST(SUM(IIF(T1.Segment = 'KAM', T2.Consumption, 0)) AS REAL) / COUNT(T1.CustomerID), CAST(SUM(IIF(T1.Segment = 'KAM', T2.Consumption, 0)) AS REAL) / COUNT(T1.CustomerID) - CAST(SUM(IIF(T1.Segment = 'SME', T2.Consumption, 0)) AS REAL) / COUNT(T1.CustomerID) FROM customers AS T1 INNER JOIN yearmonth AS T2 ON T1.CustomerID = T2.CustomerID WHERE T1.Currency = 'CZK' AND T2.Consumption = (SELECT MIN(Consumption) FROM yearmonth JOIN customers ON yearmonth.CustomerID = customers.CustomerID WHERE Currency = 'CZK') AND T2.Date BETWEEN 201301 AND 201312	semantic error: wrong condition	1	0

1482	Which of the three segments—SME, LAM and KAM—has the biggest and lowest percentage increases in consumption paid in EUR between 2012 and 2013?	SELECT CAST((SUM(IIF(T1.Segment = 'SME' AND T2.Date LIKE '2013%', T2.Consumption, 0)) - SUM(IIF(T1.Segment = 'SME' AND T2.Date LIKE '2012%', T2.Consumption, 0))) AS FLOAT) * 100 / SUM(IIF(T1.Segment = 'SME' AND T2.Date LIKE '2012%', T2.Consumption, 0)), CAST(SUM(IIF(T1.Segment = 'LAM' AND T2.Date LIKE '2013%', T2.Consumption, 0)) - SUM(IIF(T1.Segment = 'LAM' AND T2.Date LIKE '2012%', T2.Consumption, 0)) AS FLOAT) * 100 / SUM(IIF(T1.Segment = 'LAM' AND T2.Date LIKE '2012%', T2.Consumption, 0)), CAST(SUM(IIF(T1.Segment = 'KAM' AND T2.Date LIKE '2013%', T2.Consumption, 0)) - SUM(IIF(T1.Segment = 'KAM' AND T2.Date LIKE '2012%', T2.Consumption, 0)) AS FLOAT) * 100 / SUM(IIF(T1.Segment = 'KAM' AND T2.Date LIKE '2012%', T2.Consumption, 0)) FROM customers AS T1 INNER JOIN yearmonth AS T2 ON T1.CustomerID = T2.CustomerID	WITH YearlyConsumption AS (SELECT T2.Segment, SUBSTR(T1.Date, 1, 4) AS Year, SUM(T1.Consumption) AS TotalConsumption FROM yearmonth T1 JOIN customers T2 ON T1.CustomerID = T2.CustomerID WHERE T2.Currency = 'EUR' AND (SUBSTR(T1.Date, 1, 4) = '2012' OR SUBSTR(T1.Date, 1, 4) = '2013') GROUP BY T2.Segment, SUBSTR(T1.Date, 1, 4)) SELECT Y2013.Segment, ((Y2013.TotalConsumption - Y2012.TotalConsumption) / Y2013.TotalConsumption) * 100 AS PercentageIncrease FROM YearlyConsumption Y2013 JOIN YearlyConsumption Y2012 ON Y2013.Segment = Y2012.Segment WHERE Y2013.Year = '2013' AND Y2012.Year = '2012'		0	1
1487	Which LAM customer used the Euro as their currency and had the highest consumption in October 2013?	SELECT T1.CustomerID FROM customers AS T1 INNER JOIN yearmonth AS T2 ON T1.CustomerID = T2.CustomerID WHERE T1.Segment = 'LAM' AND T2.Date = '201310' AND T1.Currency = 'EUR' GROUP BY T1.CustomerID ORDER BY SUM(T2.Consumption) DESC LIMIT 1	SELECT CustomerID FROM (SELECT T1.CustomerID, rank() over (ORDER BY SUM(T2.Consumption) DESC) as rk FROM customers AS T1 INNER JOIN yearmonth AS T2 ON T1.CustomerID = T2.CustomerID WHERE T1.Segment = 'LAM' AND T2.Date = '201310' AND T1.Currency = 'EUR' GROUP BY T1.CustomerID) WHERE rk = 1	limit 1	1	0
1488	Who among KAM's customers consumed the most? How much did it consume?	SELECT T2.CustomerID, SUM(T2.Consumption) FROM customers AS T1 INNER JOIN yearmonth AS T2 ON T1.CustomerID = T2.CustomerID WHERE T1.Segment = 'KAM' GROUP BY T2.CustomerID ORDER BY SUM(T2.Consumption) DESC LIMIT 1	SELECT T1.CustomerID, SUM(T2.Consumption) AS TotalConsumption FROM customers T1 JOIN yearmonth T2 ON T1.CustomerID = T2.CustomerID WHERE T1.Segment = 'KAM' AND T2.Consumption IS NOT NULL GROUP BY T1.CustomerID HAVING SUM(T2.Consumption) = (SELECT MAX(Total) FROM (SELECT SUM(T2.Consumption) AS Total FROM customers T1 JOIN yearmonth T2 ON T1.CustomerID = T2.CustomerID WHERE T1.Segment = 'KAM' AND T2.Consumption IS NOT NULL GROUP BY T1.CustomerID))	limit 1	0	1
1490	join -> left join; lack distinct	SELECT CAST(SUM(IIF(T2.Consumption > 46.73, 1, 0)) AS FLOAT) * 100 / COUNT(T1.CustomerID) FROM customers AS T1 INNER JOIN yearmonth AS T2 ON T1.CustomerID = T2.CustomerID WHERE T1.Segment = 'LAM'	SELECT (COUNT(DISTINCT T1.CustomerID) * 100.0 / (SELECT COUNT(*) FROM customers WHERE Segment = 'LAM')) AS Percentage FROM customers T1 JOIN yearmonth T2 ON T1.CustomerID = T2.CustomerID WHERE T1.Segment = 'LAM' AND T2.Consumption > 46.73;		0	1
1491	Which country has more "value for money" gas stations? Please give a total number of "value for money" gas stations in each country.	SELECT Country, (SELECT COUNT(GasStationID) FROM gasstations WHERE Segment = 'Value for money') FROM gasstations WHERE Segment = 'Value for money' GROUP BY Country ORDER BY COUNT(GasStationID) DESC LIMIT 1	SELECT Country, COUNT(*) FROM gasstations WHERE Segment = 'Value for money' GROUP BY Country	semantic error: wrong calculation	1	0
1495	Which client ID consumed the most in September 2013?	SELECT T1.CustomerID FROM customers AS T1 INNER JOIN yearmonth AS T2 ON T1.CustomerID = T2.CustomerID WHERE T2.Date = '201309' GROUP BY T1.CustomerID ORDER BY SUM(T2.Consumption) DESC LIMIT 1	SELECT CustomerID FROM yearmonth WHERE Date = '201309' GROUP BY CustomerID HAVING SUM(Consumption) = (SELECT MAX(TotalConsumption) FROM (SELECT SUM(Consumption) AS TotalConsumption FROM yearmonth WHERE Date = '201309' GROUP BY CustomerID) T1);	limit 1	0	1

1496	Which client segment consumed the least in September 2013?	SELECT T1.Segment FROM customers AS T1 INNER JOIN yearmonth AS T2 ON T1.CustomerID = T2.CustomerID WHERE T2.Date = '201309' GROUP BY T1.CustomerID ORDER BY SUM(T2.Consumption) ASC LIMIT 1	SELECT Segment FROM (SELECT T2.Segment, rank() over (ORDER BY SUM(T1.Consumption) ASC) as rk FROM yearmonth T1 JOIN customers T2 ON T1.CustomerID = T2.CustomerID WHERE T1.Date = '201309' GROUP BY T2.Segment) WHERE rk = 1	limit 1; wrong group by	0	0
1497	Which SME customer consumed the least in June 2012?	SELECT T1.CustomerID FROM customers AS T1 INNER JOIN yearmonth AS T2 ON T1.CustomerID = T2.CustomerID WHERE T2.Date = '201206' AND T1.Segment = 'SME' GROUP BY T1.CustomerID ORDER BY SUM(T2.Consumption) ASC LIMIT 1	SELECT CustomerID FROM (SELECT T1.CustomerID, rank() over (ORDER BY SUM(T2.Consumption) ASC) as rk FROM customers AS T1 INNER JOIN yearmonth AS T2 ON T1.CustomerID = T2.CustomerID WHERE T2.Date = '201206' AND T1.Segment = 'SME' GROUP BY T1.CustomerID) WHERE rk = 1;	limit 1	1	0
1500	Please list the product description of the products consumed in September, 2013.	SELECT T3.Description FROM transactions_1k AS T1 INNER JOIN yearmonth AS T2 ON T1.CustomerID = T2.CustomerID INNER JOIN products AS T3 ON T1.ProductID = T3.ProductID WHERE T2.Date = '201309'	SELECT Description FROM products WHERE ProductID IN (SELECT ProductID FROM transactions_1k WHERE Date >= '2013-09-01' AND Date < '2013-10-01')	join -> in-sub; semantic error: wrong condition	1	0
1501	Please list the countries of the gas stations with transactions taken place in June, 2013.	SELECT DISTINCT T2.Country FROM transactions_1k AS T1 INNER JOIN gasstations AS T2 ON T1.GasStationID = T2.GasStationID INNER JOIN yearmonth AS T3 ON T1.CustomerID = T3.CustomerID WHERE T3.Date = '201306'	SELECT DISTINCT T2.Country FROM transactions_1k AS T1 INNER JOIN gasstations AS T2 ON T1.GasStationID = T2.GasStationID WHERE strftime('%Y', T1.Date) = '2013' AND strftime('%m', T1.Date) = '06'	semantic error: wrong join condition	1	0
1504	What is the average total price of the transactions taken place in January, 2012?	SELECT AVG(Amount) FROM transactions_1k WHERE Date LIKE '2012-01%'	SELECT AVG(Amount * Price) FROM transactions_1k WHERE Date >= '2012-01-01' AND Date < '2012-02-01';	semantic error: total price	1	0
1505	Among the customers who paid in euro, how many of them have a monthly consumption of over 1000?	SELECT COUNT(*) FROM yearmonth AS T1 INNER JOIN customers AS T2 ON T1.CustomerID = T2.CustomerID WHERE T2.Currency = 'EUR' AND T1.Consumption > 1000.00	SELECT COUNT(DISTINCT T1.CustomerID) FROM customers T1 JOIN yearmonth T2 ON T1.CustomerID = T2.CustomerID WHERE T1.Currency = 'EUR' AND T2.Consumption > 1000;	lack distinct	0	1
1506	Please list the product descriptions of the transactions taken place in the gas stations in the Czech Republic.	SELECT DISTINCT T3.Description FROM transactions_1k AS T1 INNER JOIN gasstations AS T2 ON T1.GasStationID = T2.GasStationID INNER JOIN products AS T3 ON T1.ProductID = T3.ProductID WHERE T2.Country = 'CZE'	SELECT Description FROM transactions_1k JOIN products ON transactions_1k.ProductID = products.ProductID WHERE GasStationID IN (SELECT GasStationID FROM gasstations WHERE Country = 'CZE')	join -> in-sub	1	0
1510	What is the average total price of the transactions taken place in gas stations in the Czech Republic?	SELECT AVG(T1.Price) FROM transactions_1k AS T1 INNER JOIN gasstations AS T2 ON T1.GasStationID = T2.GasStationID WHERE T2.Country = 'CZE'	SELECT AVG(Amount * Price) AS AverageTotalPrice FROM transactions_1k T1 JOIN gasstations T2 ON T1.GasStationID = T2.GasStationID WHERE T2.Country = 'CZE';	semantic error: output column	0	1
1511	For the customers who paid in the euro, what is their average total price of the transactions?	SELECT AVG(T1.Price) FROM transactions_1k AS T1 INNER JOIN gasstations AS T2 ON T1.GasStationID = T2.GasStationID INNER JOIN customers AS T3 ON T1.CustomerID = T3.CustomerID WHERE T3.Currency = 'EUR'	SELECT AVG(T2.Amount * T2.Price) AS AverageTotalPrice FROM customers T1 JOIN transactions_1k T2 ON T1.CustomerID = T2.CustomerID WHERE T1.Currency = 'EUR'	redundant Join	0	1
1512	Which customer paid the most in 2012/8/25? '2012/8/25' can be represented by '2012-08-25'	SELECT CustomerID FROM transactions_1k WHERE Date = '2012-08-25' GROUP BY CustomerID ORDER BY SUM(Price) DESC LIMIT 1	SELECT CustomerID FROM (SELECT CustomerID, rank() over (ORDER BY SUM(Amount * Price) DESC) as rk FROM transactions_1k WHERE Date = '2012-08-25' GROUP BY CustomerID) WHERE rk = 1	limit 1	0	0

1513	Which country's gas station had the first paid customer in 2012/8/25? '2012/8/25' can be represented by '2012-08-25'	SELECT T2.Country FROM transactions_1k AS T1 INNER JOIN gasstations AS T2 ON T1.GasStationID = T2.GasStationID WHERE T1.Date = '2012-08-25' ORDER BY T1.Time DESC LIMIT 1	SELECT DISTINCT Country FROM (SELECT T2.Country, rank() over (ORDER BY T1.Time DESC) as rk FROM transactions_1k AS T1 INNER JOIN gasstations AS T2 ON T1.GasStationID = T2.GasStationID WHERE T1.Date = '2012-08-25') WHERE rk = 1	limit 1; wrong order by	1	0
1515	What segment did the customer have at 2012/8/23 21:20:00? '2012/8/23' can be represented by '2012-08-23'	SELECT T2.Segment FROM transactions_1k AS T1 INNER JOIN customers AS T2 ON T1.CustomerID = T2.CustomerID WHERE T1.date = '2012-08-23' AND T1.time = '21:20:00'	SELECT DISTINCT T2.Segment FROM transactions_1k AS T1 INNER JOIN customers AS T2 ON T1.CustomerID = T2.CustomerID WHERE T1.date = '2012-08-23' AND T1.time = '21:20:00'	lack distinct	1	0
1517	For the earliest customer, what segment did he/she have?	SELECT T2.Segment FROM transactions_1k AS T1 INNER JOIN customers AS T2 ON T1.CustomerID = T2.CustomerID WHERE T1.Date = (SELECT MIN(Date) FROM transactions_1k)	SELECT c.Segment FROM customers c WHERE EXISTS (SELECT 1 FROM transactions_1k t WHERE t.CustomerID = c.CustomerID AND t.Date = (SELECT MIN(Date) FROM transactions_1k));	join -> in-sub	0	1
1520	For the customer who paid 124.05 in 2012/8/24, how much did he/she spend during the January of 2012? And what is the date and expenses exactly? '2012/8/24' can be represented by '2012-08-24'; expense and the consumption has the similar meaning.	SELECT T1.CustomerID, T2.Date, T2.Consumption FROM transactions_1k AS T1 INNER JOIN yearmonth AS T2 ON T1.CustomerID = T2.CustomerID WHERE T1.Date = '2012-08-24' AND T1.Price = 124.05 AND T2.Date = '201201'	SELECT CustomerID, Date, Consumption FROM yearmonth WHERE CustomerID IN (SELECT CustomerID FROM transactions_1k WHERE Date = '2012-08-24' GROUP BY CustomerID HAVING SUM(Price * Amount) = 124.05) AND Date = '201201'	semantic error: paid = amount * price	1	0
1523	Which country was the card owner of No.667467 in?	SELECT T2.Country FROM transactions_1k AS T1 INNER JOIN gasstations AS T2 ON T1.GasStationID = T2.GasStationID WHERE T1.CardID = '667467'	SELECT DISTINCT gs.Country FROM gasstations gs JOIN transactions_1k tx ON gs.GasStationID = tx.GasStationID WHERE tx.CardID = 667467;	lack distinct	0	1
1524	What's the nationality of the customer who spent 548.4 in 2012/8/24? '2012/8/24' can be represented by '2012-08-24'	SELECT T2.Country FROM transactions_1k AS T1 INNER JOIN gasstations AS T2 ON T1.GasStationID = T2.GasStationID WHERE T1.Date = '2012-08-24' AND T1.Price = 548.4	SELECT T2.Country FROM transactions_1k AS T1 INNER JOIN gasstations AS T2 ON T1.GasStationID = T2.GasStationID WHERE T1.Date = '2012-08-24' GROUP BY T1.CustomerID HAVING SUM(T1.Price * T1.Amount) = 548.4	semantic error: paid = amount * price	1	0
1525	What is the percentage of the customers who used EUR in 2012/8/25? '2012/8/25' can be represented by '2012-08-25'	SELECT CAST(SUM(IIF(T2.Currency = 'EUR', 1, 0)) AS FLOAT) * 100 / COUNT(T1.CustomerID) FROM transactions_1k AS T1 INNER JOIN customers AS T2 ON T1.CustomerID = T2.CustomerID WHERE T1.Date = '2012-08-25'	SELECT (COUNT(DISTINCT T1.CustomerID) * 100.0 / (SELECT COUNT(DISTINCT CustomerID) FROM transactions_1k WHERE Date = '2012-08-25')) AS Percentage FROM transactions_1k T1 JOIN customers T2 ON T1.CustomerID = T2.CustomerID WHERE T1.Date = '2012-08-25' AND T2.Currency = 'EUR';	lack distinct	0	1
1526	For the customer who paid 634.8 in 2012/8/25, what was the consumption decrease rate from Year 2012 to 2013? '2012/8/24' can be represented by '2012-08-24'; Consumption decrease rate = (consumption_2012 - consumption_2013) / consumption_2012	SELECT CAST(SUM(IIF(SUBSTR(Date, 1, 4) = '2012', Consumption, 0)) - SUM(IIF(SUBSTR(Date, 1, 4) = '2013', Consumption, 0)) AS FLOAT) / SUM(IIF(SUBSTR(Date, 1, 4) = '2012', Consumption, 0)) FROM yearmonth WHERE CustomerID = (SELECT T1.CustomerID FROM transactions_1k AS T1 INNER JOIN gasstations AS T2 ON T1.GasStationID = T2.GasStationID WHERE T1.Date = '2012-08-25' AND T1.Price = 634.8)	SELECT CAST(SUM(IIF(SUBSTR(Date, 1, 4) = '2012', Consumption, 0)) - SUM(IIF(SUBSTR(Date, 1, 4) = '2013', Consumption, 0)) AS FLOAT) / SUM(IIF(SUBSTR(Date, 1, 4) = '2012', Consumption, 0)) FROM yearmonth WHERE CustomerID IN (SELECT T1.CustomerID FROM transactions_1k AS T1 WHERE T1.Date = '2012-08-25' GROUP BY T1.CustomerID HAVING SUM(T1.Price * T1.Amount) = 634.8) GROUP BY CustomerID;	semantic error: paid = amount * price	0	0

1527	Which gas station has the highest amount of revenue?	SELECT GasStationID FROM transactions_1k GROUP BY GasStationID ORDER BY SUM(Price) DESC LIMIT 1	SELECT GasStationID FROM (SELECT GasStationID, rank() over (ORDER BY SUM(Amount * Price) DESC) as rk FROM transactions_1k GROUP BY GasStationID) WHERE rk = 1	semantic error: revenue = amount * price; limit 1	0	0
1529	What is the amount spent by customer "38508" at the gas stations? And how much had the customer spent in January 2012?	SELECT SUM(T1.Price) , SUM(IIF(T3.Date = '201201', T1.Price, 0)) FROM transactions_1k AS T1 INNER JOIN gasstations AS T2 ON T1.GasStationID = T2.GasStationID INNER JOIN yearmonth AS T3 ON T1.CustomerID = T3.CustomerID WHERE T1.CustomerID = '38508'	SELECT (SELECT SUM(T1.Price * T1.Amount) FROM transactions_1k AS T1 JOIN gasstations as T2 ON T1.GasStationID = T2.GasStationID WHERE T1.CustomerID = '38508'), (SELECT T1.Consumption FROM yearmonth as T1 WHERE T1.CustomerID = '38508' AND T1.Date = '201201')	semantic error: spent = amount * price	0	0
1530	Which are the top five best selling products? Please state the full name of them.	SELECT T2.Description FROM transactions_1k AS T1 INNER JOIN products AS T2 ON T1.ProductID = T2.ProductID ORDER BY T1.Amount DESC LIMIT 5	SELECT products.ProductID, products.Description FROM (SELECT ProductID, rank() over (ORDER BY SUM(Amount) DESC) AS rk FROM transactions_1k GROUP BY ProductID) AS T JOIN products ON T.ProductID = products.ProductID WHERE rk <= 5	limit n; semantic error: lack group by	0	0
1531	Who is the top spending customer and how much is the average price per single item purchased by this customer? What currency was being used?	SELECT T2.CustomerID, SUM(T2.Price / T2.Amount), T1.Currency FROM customers AS T1 INNER JOIN transactions_1k AS T2 ON T1.CustomerID = T2.CustomerID WHERE T2.CustomerID = (SELECT CustomerID FROM yearmonth ORDER BY Consumption DESC LIMIT 1) GROUP BY T2.CustomerID, T1.Currency	WITH Total AS (SELECT CustomerID, SUM(Consumption) AS TotalConsumption FROM yearmonth GROUP BY CustomerID) SELECT T2.CustomerID, SUM(T2.Price * T2.Amount) / SUM(T2.Amount), T1.Currency FROM customers AS T1 INNER JOIN transactions_1k AS T2 ON T1.CustomerID = T2.CustomerID WHERE T2.CustomerID IN (SELECT CustomerID FROM Total WHERE TotalConsumption = (SELECT MAX(TotalConsumption) FROM Total)) GROUP BY T2.CustomerID, T1.Currency	limit n; semantic error: average price per single item	0	0
1532	Which country had the gas station that sold the most expensive product id No.2 for one unit?	SELECT T2.Country FROM transactions_1k AS T1 INNER JOIN gasstations AS T2 ON T1.GasStationID = T2.GasStationID WHERE T1.ProductID = 2 ORDER BY T1.Price DESC LIMIT 1	SELECT DISTINCT T2.Country FROM transactions_1k T1 JOIN gasstations T2 ON T1.GasStationID = T2.GasStationID WHERE T1.ProductID = 2 AND T1.Price = (SELECT MAX(Price) FROM transactions_1k WHERE ProductID = 2)	limit 1	0	0
1533	For all the people who paid more than 29.00 per unit of product id No.5. Give their consumption status in the August of 2012.	SELECT T2.Consumption FROM transactions_1k AS T1 INNER JOIN yearmonth AS T2 ON T1.CustomerID = T2.CustomerID WHERE T1.Price / T1.Amount > 29.00 AND T1.ProductID = 5 AND T2.Date = '201208'	SELECT Consumption FROM yearmonth WHERE CustomerID IN (SELECT CustomerID FROM transactions_1k WHERE Price / Amount > 29.00 AND ProductID = 5) AND Date = '201208'	join -> in-sub	1	0