

Introduction to L^AT_EX

Lecture II: Text

Liu Yihao

SJTU-UMJI Technology Department

April 15, 2020

Polishing the plain text

UTF-8 encoding

Special symbols and accents

Fonts

Underline

Typesetting

Enumeration

Alignment

Spaces, lines and pages

Minipage and
Multicolumn

Learn more - multi languages and scope in L^AT_EX

Multiple Languages

Scope

1 Polishing the plain text

- UTF-8 encoding
- Special symbols and accents
- Fonts
- Underline

2 Typesetting

3 Learn more - multi languages and scope in L^AT_EX

Use UTF-8 encoding in L^AT_EX

UTF-8 encoding is widely used in modern computer applications, so it's useful to include the `inputenc` package and use UTF-8 encoding.

Command

```
\usepackage[utf-8]{inputenc}
```

Example

café

However, different operating systems and compiling engines have different support on UTF-8 encoding, some UTF-8 codes that work on your computer may not work on others (though rarely), so it is recommended to use commands (will be introduced later) instead of directly copy and paste the UTF-8 codes from the Internet.

Polishing the plain text

UTF-8 encoding

Special symbols and accents

Fonts

Underline

Typesetting

Enumeration

Alignment

Spaces, lines and pages

Minipage and
Multicolumn

Learn more - multi languages and scope in L^AT_EX

Multiple Languages

Scope

1 Polishing the plain text

- UTF-8 encoding
- **Special symbols and accents**
- Fonts
- Underline

2 Typesetting

3 Learn more - multi languages and scope in L^AT_EX

Special symbols

Polishing the plain text

UTF-8 encoding

Special symbols and accents

Fonts

Underline

Typesetting

Enumeration

Alignment

Spaces, lines and pages

Minipage and
Multicolumn

Learn more - multi languages and scope in L^AT_EX

Multiple Languages

Scope

Some special symbols can't be directly used since they are reserved by L^AT_EX

`\#` `#` `\$` `$` `\%` `%` `\&` `&` `\~` `~` `\`` ```
`\{` `{` `\}` `}` `\-` `-` `\textbackslash` `\`

Many L^AT_EX starters are confused with how to correctly print quotes, hyphens and dots.

``` prints a left single quote, `'` prints a right single quote.

```` prints a left double quote, `''` prints a right double quote.

one hyphen (-) print like -

two hyphens (--) print like –

three hyphens (---) print like —

`\dots` prints the dots with a correct format (`\dots`) instead of directly use three dots (`...`)

Polishing the plain text

UTF-8 encoding

Special symbols and accents

Fonts

Underline

Typesetting

Enumeration

Alignment

Spaces, lines and pages

Minipage and
MulticolumnLearn more - multi
languages and scope in
L^AT_EX

Multiple Languages

Scope

Accent on letters

Sometimes you may need an accent form of a letter, here is an example of letter o

<code>\`{o}</code>	ò	<code>\'{o}</code>	ó	<code>\^{o}</code>	ô	<code>\"{o}</code>	ö	<code>\~{o}</code>	õ
<code>\={o}</code>	ō	<code>\.{o}</code>	ô	<code>\u{o}</code>	ů	<code>\v{o}</code>	ǒ	<code>\H{o}</code>	Ǫ
<code>\t{oo}</code>	ôo	<code>\r{o}</code>	õ	<code>\c{o}</code>	ơ	<code>\d{o}</code>	ơ	<code>\b{o}</code>	ơ

Something interesting

You may be curious about how to print words like L^AT_EX, actually it's defined as a command.

- `\TeX` - T_EX
- `\LaTeX` - L^AT_EX
- `\LaTeXe` - L^AT_EX 2_ε

Deal with unfamiliar symbols

Polishing the plain text

UTF-8 encoding

Special symbols and accents

Fonts

Underline

Typesetting

Enumeration

Alignment

Spaces, lines and pages

Minipage and
Multicolumn

Learn more - multi languages and scope in L^AT_EX

Multiple Languages

Scope

Sometimes you may want to deal with symbols you have never seen. In this case, you may refer to <http://detexify.kirelabs.org/classify.html> to find out how to output the character.

Polishing the plain text

UTF-8 encoding

Special symbols and accents

Fonts

Underline

Typesetting

Enumeration

Alignment

Spaces, lines and pages

Minipage and
Multicolumn

Learn more - multi languages and scope in L^AT_EX

Multiple Languages

Scope

1 Polishing the plain text

- UTF-8 encoding
- Special symbols and accents
- **Fonts**
- Underline

2 Typesetting

3 Learn more - multi languages and scope in L^AT_EX

Polishing the plain text

UTF-8 encoding

Special symbols and accents

Fonts

Underline

Typesetting

Enumeration

Alignment

Spaces, lines and pages

Minipage and Multicolumn

Learn more - multi languages and scope in L^AT_EX

Multiple Languages

Scope

Basic commands about fonts

First, let's start with some commands that transform font types

- `\bf` - **Sample Text**
- `\it` - *Sample Text*
- `\rm` - Sample Text
- `\sc` - SAMPLE TEXT
- `\sf` - Sample Text
- `\sl` - *Sample Text*
- `\tt` - Sample Text

Note that the commands that transform font types influence the text in the whole scope (`{...}`) until another font type is specified. For example, how to use the first command `\bf` is shown below

`{\bf Sample Text}`

Polishing the plain text

UTF-8 encoding

Special symbols and accents

Fonts

Underline

Typesetting

Enumeration

Alignment

Spaces, lines and pages

Minipage and Multicolumn

Learn more - multi languages and scope in L^AT_EX

Multiple Languages

Scope

Sometimes we don't want to transform all the font types, instead, we can only change the font type of some specified text.

Example

```
1 \textbf{Sample text}
```

There are more options for fonts.

- `\textit` - *Sample Text*
- `\textsc` - SAMPLE TEXT

However, in a math environment (will be introduced later), some other commands should be used

- `\mathbf` - **Sample Text**
- `\mathit` - *Sample Text*
- `\mathsf` - Sample Text

Note that the math environment doesn't include all of the font types on the previous page. More information about font types can be found [here](#).

Polishing the plain text

UTF-8 encoding

Special symbols and accents

Fonts

Underline

Typesetting

Enumeration

Alignment

Spaces, lines and pages

Minipage and Multicolumn

Learn more - multi languages and scope in L^AT_EX

Multiple Languages

Scope

Font size can also be easily modified

- `\tiny` - Sample Text
- `\scriptsize` - Sample Text
- `\footnotesize` - Sample Text
- `\small` - Sample Text
- `\normalsize` - Sample Text
- `\large` - Sample Text
- `\Large` - Sample Text
- `\LARGE` - Sample Text
- `\huge` - Sample Text
- `\Huge` - Sample Text

Build a colorful document

Polishing the plain text

UTF-8 encoding

Special symbols and accents

Fonts

Underline

Typesetting

Enumeration

Alignment

Spaces, lines and pages

Minipage and Multicolumn

Learn more - multi
languages and scope in
L^AT_EX

Multiple Languages

Scope

Changing the color is similar to changing font types.

If you want to transform to a color (like transforming to bold with `\bf`), you can use `\color{name}`.

Similarly, you can use `\textcolor{name}` like `\textbf`.

The background color of the whole page can be set using `\pagecolor{name}`.

There are some defined color `name` in the `xcolor` package.

 black	 gray	 olive	 teal	 blue
 green	 orange	 violet	 brown	 lightgray
 pink	 white	 cyan	 lime	 purple
 yellow	 darkgray	 magenta	 red	

You can find more information in the documentation of `xcolor` (`texdoc xcolor`)

Polishing the plain text

UTF-8 encoding

Special symbols and accents

Fonts

Underline

Typesetting

Enumeration

Alignment

Spaces, lines and pages

Minipage and
Multicolumn

Learn more - multi languages and scope in L^AT_EX

Multiple Languages

Scope

1 Polishing the plain text

- UTF-8 encoding
- Special symbols and accents
- Fonts
- **Underline**

2 Typesetting

3 Learn more - multi languages and scope in L^AT_EX

Ulem package

If you want to add some lines on the text, use the [ulem](#) package.

Command

```
1 \usepackage{ulem}
2 \uline{Sample Text}
```

There are different kinds of lines supported:

- `\uline` - Sample Text
- `\uuline` - Sample Text
- `\uwave` - Sample Text
- `\sout` - ~~Sample Text~~
- `\xout` - ~~Sample Text~~
- `\dashuline` - - - - Sample Text
- `\dotuline` - . . . Sample Text

Polishing the plain text

UTF-8 encoding

Special symbols and accents

Fonts

Underline

Typesetting

Enumeration

Alignment

Spaces, lines and pages

Minipage and Multicolumn

Learn more - multi languages and scope in L^AT_EX

Multiple Languages

Scope

Polishing the plain text

UTF-8 encoding

Special symbols and accents

Fonts

Underline

Typesetting

Enumeration

Alignment

Spaces, lines and pages

Minipage and Multicolumn

Learn more - multi languages and scope in L^AT_EX

Multiple Languages

Scope

1 Polishing the plain text

2 Typesetting

- Enumeration

- Alignment

- Spaces, lines and pages

- Minipage and Multicolumn

3 Learn more - multi languages and scope in L^AT_EX

Enumerate

When you need to enumerate some items as a list, you may use the [enumerate](#) package.

Command

```
1 \usepackage{enumerate}
2 \begin{enumerate}[style]
3 \item % ...
4 \item % ...
5 \item % ...
6 \end{enumerate}
```

This will generate a normal list with the serial numbers in the specified [style](#), which could be the following (as example)

- **1** - 1, 2, 3, 4, ...
- **(i)** - (i), (ii), (iii), (iv), ...
- **[1.]** - [1.], [2.], [3.], [4.], ...

Itemize

Polishing the plain text

UTF-8 encoding

Special symbols and accents

Fonts

Underline

Typesetting

Enumeration

Alignment

Spaces, lines and pages

Minipage and Multicolumn

Learn more - multi languages and scope in L^AT_EX

Multiple Languages

Scope

If you want to generate an unordered list, use `itemize` instead of `enumerate`.

Command

```
1 \usepackage{enumerate}
2 \begin{itemize}
3 \item[style] % ...
4 \item[style] % ...
5 \item[style] % ...
6 \end{itemize}
```

In this case, `style` must be added after each item, which is different from that in `enumerate`, and the symbol displayed in the beginning of each item will be exactly same as the `style`. If `style` is not added, a default style will be used.

Polishing the plain text

UTF-8 encoding

Special symbols and accents

Fonts

Underline

Typesetting

Enumeration

Alignment

Spaces, lines and pages

Minipage and Multicolumn

Learn more - multi languages and scope in L^AT_EX

Multiple Languages

Scope

1 Polishing the plain text

2 Typesetting

- Enumeration
- **Alignment**
- Spaces, lines and pages
- Minipage and Multicolumn

3 Learn more - multi languages and scope in L^AT_EX

Alignment

If you want to align a paragraph of text, use these three environments for left/center/right align.

Command

```
1 \begin{flushleft/center/flushright}  
2 % ...  
3 \end{flushleft/center/flushright}
```

However, if only a single line needs to be aligned, use these three commands.

Command

```
1 \leftline{text}  
2 \centerline{text}  
3 \rightline{text}
```

Polishing the plain text

UTF-8 encoding

Special symbols and accents

Fonts

Underline

Typesetting

Enumeration

Alignment

Spaces, lines and pages

Minipage and Multicolumn

Learn more - multi languages and scope in L^AT_EX

Multiple Languages

Scope

1 Polishing the plain text

2 **Typesetting**

- Enumeration

- Alignment

- **Spaces, lines and pages**

- Minipage and Multicolumn

3 Learn more - multi languages and scope in L^AT_EX

Polishing the plain text

UTF-8 encoding

Special symbols and accents

Fonts

Underline

Typesetting

Enumeration

Alignment

Spaces, lines and pages

Minipage and Multicolumn



Learn more - multi languages and scope in L^AT_EX

Multiple Languages

Scope

Spaces may be confusing

There are defined command of spaces in different width and usages.

-  - the basic space in L^AT_EX (printed in yellow since it's transparent). Note that any number of spaces or tabs is equal to one space, and the space after a command is ignored. If you want to add an extra space, use `\` which makes a 1/3 em space (1 em is approximately the width of an M in the current font)
- `~` - If two words can't be separated on two lines, you can tell L^AT_EX about it using a tie (`~`), such as Prof.`~`Hamade (Prof. Hamade).
- `\,` - makes a 1/6 em space, commonly used before units (notice the space before em on this page)
- `\;` - makes a 2/7 em space
- `\quad` - makes a 1 em space
- `\qquad` - makes a 2 em space
- `` - makes actually the space of `text`, but `text` will be invisible.

Polishing the plain text

UTF-8 encoding

Special symbols and accents

Fonts

Underline

Typesetting

Enumeration

Alignment

Spaces, lines and pages

Minipage and Multicolumn

Learn more - multi languages and scope in L^AT_EX

Multiple Languages

Scope

Separate contents into lines and pages

Here are some basic commands about lines and pages in L^AT_EX, you will use them everywhere.

- `\newline` - begin a new line
- `\\` - begin a new line (not recommended¹)
- `\par` - begin a new paragraph (a new line with indent)
- `\\[offset]` - begin a new line with an vertical offset, `offset` is the size of needed space (not recommended, using `\vspace` instead.)
- `\newpage` - begin a new page
- `%` - begin a line comment

¹According to Manuel Charlemagne, `\\` should only be used for a force break (where `\newline` doesn't work).

Spacing

When trying to separate two paragraphs by a certain space, many new learners of L^AT_EX may use multiple empty lines and linebreaks, which is a very dirty fix and is not so accurate. Actually, L^AT_EX provides a precise spacing mechanism.

Command

```
\vspace{space}
```

```
\vspace*{space}
```

When trying to show the next paragraph or sentence precisely at the bottom of the current page, we can use

Command

```
\vfill
```

between the contents of two paragraphs to separate them.

Predefined skipping

More often¹, we don't need to think about the skipping space, we can use the predefined skipping commands to achieve a small, medium or big skip. They are actually particular cases of `\vspace`

Command

`\smallskip``\medskip``\bigskip`

You may note that the effects are these skipping commands have been already shown above.

¹According to Manuel Charlemagne, you should always use these skipping commands if possible instead of using `\\` (as in many online tutorials).

Spacing units

The `space` can be anything representing a size, such as `1cm`, `2em` and `10pt`. In L^AT_EX, spacing units can be

- `cm`
- `mm`
- `in` - inch, 1 inch = 2.54 cm
- `pt` - 72 pt = 1 inch, the smallest unit in L^AT_EX
- `em` - 1em equals to the width of letter M
- `ex` - 1ex equals to the width of letter x
- `\linewidth` - the width of current line in the container
- `\pagewidth` - the width of the page
- `\pageheight` - the height of the page
- `\textwidth` - the normal width of text on the page
- `\textheight` - the normal height of text on the page

Polishing the plain text

UTF-8 encoding

Special symbols and accents

Fonts

Underline

Typesetting

Enumeration

Alignment

Spaces, lines and pages

Minipage and Multicolumn

Learn more - multi languages and scope in L^AT_EX

Multiple Languages

Scope

1 Polishing the plain text

2 Typesetting

- Enumeration
- Alignment
- Spaces, lines and pages
- Minipage and Multicolumn

3 Learn more - multi languages and scope in L^AT_EX

Minipage

Polishing the plain text

UTF-8 encoding

Special symbols and accents

Fonts

Underline

Typesetting

Enumeration

Alignment

Spaces, lines and pages

Minipage and Multicolumn

Learn more - multi languages and scope in L^AT_EX

Multiple Languages

Scope

`minipage` is a very useful environment for dividing pages into a grid.

Example

```

1  \begin{minipage}{0.32\linewidth}
2      % ...
3  \end{minipage}
4  \hfill % Fill horizontal space
5  \begin{minipage}{0.32\linewidth}
6      % ...
7  \end{minipage}
8  \hfill % Fill horizontal space
9  \begin{minipage}{0.32\linewidth}
10     % ...
11 \end{minipage}
12 \vfill % Fill vertical space

13 \begin{minipage}{0.32\linewidth}
14     % ...
15 \end{minipage}
16 \hfill % Fill horizontal space
17 \begin{minipage}{0.32\linewidth}
18     % ...
19 \end{minipage}
20 \hfill % Fill horizontal space
21 \begin{minipage}{0.32\linewidth}
22     % ...
23 \end{minipage}

```

Polishing the plain text

UTF-8 encoding

Special symbols and accents

Fonts

Underline

Typesetting

Enumeration

Alignment

Spaces, lines and pages

Minipage and Multicolumn

Learn more - multi languages and scope in L^AT_EX

Multiple Languages

Scope

The code above generate six minipages in a grid of 3 columns \times 2 rows. Don't try to add up the width of minipages in a line for more than about `0.98\linewidth` (since a minipage have a small margin on each side), or the last minipage may be on a new line.

For each minipage, it can be seem as an independent L^AT_EX document, where text, formulas, graphics, tables and etc. can be inserted, and most importantly, they won't affect each other. What's more, you can even use minipages in a minipage to form a multi-level nesting.

The multicol package

When typesetting contents with small line width and many lines (for example, source code), the **multicol** package is recommended.

Command

```
1 \usepackage{multicol}
2 \begin{multicols}{cols}
3     % contents on column one
4     \breakcolumn % break the current column here
5     % contents on column two
6 \end{multicols}
```

Here **cols** is the number of columns, it must be specified. If **\breakcolumn** is not used, the **multicol** package will automatically balance the length of each column.

Polishing the plain text

UTF-8 encoding

Special symbols and accents

Fonts

Underline

Typesetting

Enumeration

Alignment

Spaces, lines and pages

Minipage and
Multicolumn

Learn more - multi languages and scope in L^AT_EX

Multiple Languages

Scope

1 Polishing the plain text

2 Typesetting

3 Learn more - multi languages and scope in L^AT_EX

- Multiple Languages
- Scope

Spelling languages

If you want to use a spelling language with characters similar to English, package `babel` can be used (exactly the same name as `babel`).

Command

```
\usepackage[languages]{babel}
```

- `languages` - a list of languages, the last one to be the default language

Example

```
\usepackage[greek,english]{babel}  
\textgreek{abcdefgABCDEFGFG}
```

Then L^AT_EX will print $\alpha\beta\zeta\delta\epsilon\varphi\gamma AB^{\wedge}\Delta E\Phi\Gamma$

Of course, you can use some simple commands to print these greek letters directly, such as `\alpha`, `\beta` and etc, which is more convenient only when few of them are needed.

Polishing the plain text

UTF-8 encoding

Special symbols and accents

Fonts

Underline

Typesetting

Enumeration

Alignment

Spaces, lines and pages

Minipage and Multicolumn

Learn more - multi languages and scope in L^AT_EX

Multiple Languages

Scope

The Chinese TeX Community maintains a package called `ctex` for inputting Chinese in L^AT_EX. Note that it is only a package, which is shipped with most modern T_EX Suites, not the CTEX Suite. I don't think it's a good choice to use the CTEX Suite directly.

Command

```
\usepackage{ctex}
```

The default L^AT_EX compiler `pdflatex` doesn't have support on Chinese input with `ctex` package, `xelatex` is a recommended modern L^AT_EX compiler as a replacement.

However, the `ctex` package is too heavy and it can slow down the total compilation speed seriously.

Polishing the plain text

UTF-8 encoding

Special symbols and accents

Fonts

Underline

Typesetting

Enumeration

Alignment

Spaces, lines and pages

Minipage and
Multicolumn

Learn more - multi languages and scope in L^AT_EX

Multiple Languages

Scope

1 Polishing the plain text

2 Typesetting

3 Learn more - multi languages and scope in L^AT_EX

- Multiple Languages
- Scope

Usage of scope in L^AT_EX

First, you should realize the meaning of “scope” in programming. Let's start with a simple example in C/C++ (assuming you know that):

```
1  int main()
2  { // The scope "main" of function main
3      int a = 1; // int a is defined in scope "main"
4      for (int i = 0; i < 10; i++)
5      { // The scope "for" of the for loop
6          int b = i; // int b and i are both defined in scope "for"
7          a += b; // int a can be visited here!
8      }
9      { // The scope "other", we can directly define a scope like this
10         int c; // int c is defined in scope "other"
11         c = a; // int a can be visited here!
12     }
13     a -= c // error: c is not in scope "main", can't be visited!
14 }
```

In the example of C/C++, we use brackets `{ }` to define a scope, which is just the same in L^AT_EX. In addition, notice that an environment or a command also defines a scope.

Example

1	<code>black (default) text \</code>	black (default) text
2	<code>\color{blue}</code>	blue text
3	<code>blue text \</code>	brown text
4	<code>{ \color{brown} brown text }</code>	
5	<code>\begin{center}</code>	
6	<code>\color{red}</code>	centered red text
7	<code>centered red text</code>	
8	<code>\end{center}</code>	
9	<code>\textbf{ \color{brown}</code>	bold brown text
10	<code>bold brown text } \</code>	blue text
11	<code>blue text</code>	

With the usage of scopes, you can flexibly change the color, font or anything else you wish in a self-defined range of the document.