# Kayro AI Product Intern Assignment — Documentation

Technical Architecture, Product Decisions, and Delivery Guide

## 1. What We Were Asked

Build a polished appointments web application for a wellness practice with two interfaces sharing the same data: **Side A (Client App)** providing a mobile-first booking experience with upcoming/past visits and rescheduling, and **Side B (Nutritionist Dashboard)** managing visits with color-coded statuses (*Booked, Done, No-show*), today's visit filtering, manual booking, and bidirectional synchronization. The project required loading 5 specific sample records, integrating at least one concrete solution to the 25% no-show problem, and enabling review without authentication.

## 2. Your Approach

We treated Kayro as a calming wellness sanctuary rather than a cold administrative CRM. Technically, we implemented a **hybrid reactive data layer** (appointmentService.js) connecting to Supabase PostgreSQL when configured, while offering a zero-dependency, persistent local storage fallback so reviewers can immediately evaluate the build without manual setup. The design system utilizes warm cream backgrounds (#FBF9F4), deep forest green accents (#1E3D2F), and Playfair Display typography to convey elegance, warmth, and tranquility.

## 3. Decisions and Assumptions (Including How We Handled Sample Data)

- **Inconsistent Date Normalization:** Sample inputs varied across DD/MM/YYYY (24/10/2026), YYYY-MM-DD (2026-10-24), and DD-MM-YYYY (25-10-2026). We built an ingestion parser standardizing all entries to ISO YYYY-MM-DD internally for conflict checking and chronologic sorting while displaying localized dates (e.g. *Sat, 24 Oct 2026*).
- **Time Format Standardization:** Varied representations (4 pm, 11:30am, 14:00) were parsed into 24-hr HH:mm format internally and formatted into readable 12-hour AM/PM strings for display.
- **Graceful Phone Fallbacks:** Meera Iyer had no phone number; Riya Shah and Kabir Rao used disparate space conventions. We standardized 10-digit formats (98200 11111) and handled empty values gracefully with disabled WhatsApp triggers.
- **Practice Date Anchor:** Anchored the practice dashboard to 2026-10-24 matching the assignment context, enabling immediate demonstration of the 'Today Only' filter.

## 4. What You Added (and Why)

- **1-Tap Attendance Confirmation:** Allows clients to check in with 1 tap, giving the nutritionist 24-hour advance peace of mind instead of waiting at her desk.
- **1-Click WhatsApp Reminder Links (wa.me):** Enables the practitioner to launch personalized, pre-written WhatsApp check-in messages with zero typing.
- **Instant Calendar Sync (.ics & Google Calendar):** Pushes consultations directly to device calendars with 2-hour notifications to eliminate forgetting.
- **No-Guilt 2-Click Rescheduling:** Removes social awkwardness and immediately returns vacant slots to the calendar.

- **Reviewer Client Switcher:** A 1-click toggle allowing assessors to inspect the experience as Riya Shah, Arjun Mehta, Meera Iyer, or Kabir Rao without login.
- **Practice Analytics & No-Show Rate:** Displays real-time clinic KPIs (Active Bookings, Confirmed Count, Historical No-Show %).

## 5. What the AI Got Wrong (and How You Caught and Fixed It)

- **Default Template CSS Conflict:** Vite's default index.css injected #root { text-align: center; border-inline: ... }, disrupting alignments. Caught during visual inspection and replaced with a clean design token system.
- **Omitted Reschedule & Cancel Capabilities:** The starter code lacked rescheduling and cancellation logic. Built dedicated modals with conflict prevention.
- **Lexicographical Date Sorting Glitch:** Comparing mixed date strings produced incorrect chronological ordering. Standardized all comparisons to ISO YYYY-MM-DD.
- **Client Journey Data Bleed:** Initial filtering showed all practice appointments under the client view when no name was matched. Resolved by scoping records strictly to the active profile.

## 6. How to Run It

### Local Development:

1. cd kayro-appointments && npm install
2. npm run dev — Open **http://localhost:5173** in your browser. All sample records are preloaded.

### Optional Supabase PostgreSQL Connection:

Run supabase-schema.sql in the Supabase SQL editor, then populate VITE_SUPABASE_URL and VITE_SUPABASE_ANON_KEY in .env. The top indicator will display **Supabase Live**.

### Production Build & Deployment:

Execute npm run build. Configured with vercel.json for instant zero-configuration deployment on Vercel.