4/26/2017 Swagger Editor

Application Adapter API

Application adapter consists of one service endpoint "/adapter" handling one resource "integrationData". Adapter accepts integrationData from the integration layer. The adapter checks if there is already a record that represents the data and updates that record (deduplication) or creates a new one. The emmition of the creation or update is depended on the "isExternal" flag.

Version 1.0.0.1

Paths

/v1/adapter/integrationData

POST /v1/adapter/integrationData

Summary

Proccess new integration data from integration layer

Description

Application adapter gets new data from integratio n layer. If the "isExternal" flag is set to false, the data is coming from another application inside the local CSP. The data is processed as such and if the process results in another data record being created or updated, the new or updated record is emited back to the integration layer. If the "isExternal" flag is set to true, the data is coming from an external CSP. The data is processed as such and if the process results in a new data record or an update to an existing data record, the new or updated record is emited back to the integration layer with the flag "toShare" set to false.

Parameters

```
Name Located in Required Schema

▼IntegrationData {
dataParams: DataParams { }
sharingParams { }
dataType: IntegrationDataType string
dataObject: string
}
```

Responses

Code	Description
200	Successful operation
400	Malformed Integration Data Structure
500	Internal server error
503	Service anavailable

Try this operation

http://editor2.swagger.io/#!/

4/26/2017 Swagger Editor

PUT /v1/adapter/integrationData

Summary

Process integration data update from integration layer

Description

(See POST)

Parameters

```
Name Located in Required Schema

*IntegrationData {
    dataParams: DataParams { }
    sharingParams: SharingParams { }
    dataType: IntegrationDataType string
    dataObject: string
}
```

Responses

Code	Description
200	Successful operation
400	Malformed Integration Data Structure
500	Internal server error
503	Service anavailable

Try this operation

http://editor2.swagger.io/#/

4/26/2017 Swagger Editor

DELETE /v1/adapter/integrationData

Summary

Process integration data deletion from integration layer

Description

Application adapter get deletion notification from integration layer, the adapter checks if that record is used by the application and updates the affected records in the application datastore. If the process results in a local data record being updated, the new or updated record is emited back to the integration layer. If the process results in a local data record being deleted, the delete request is emited back to the integration layer. All delete requests by the emitter have the "toShare" flag to false. The dataObject is expected to be null. isExternal is expected to be false.

Parameters

Responses

```
Code Description

200 Successful operation

500 Internal server error

503 Service anavailable
```

Try this operation

Models

IntegrationData

DataParams

http://editor2.swagger.io/#/

```
▼DataParams {
       cspId:
                        string
       applicationId: string
\rightleftarrows
       recordId:
                        string
   }
Integration Data Type \\
    ▼IntegrationDataType string
      Enum:
         Array[9]
          0: "event"
           1: "threat"
           2: "incident"
\rightleftarrows
           3: "vulnerability"
          4: "artefact"
           5: "chat"
           6: "file"
           7: "contact"
           8: "trustCircle"
SharingParams
    ▼SharingParams {
       toShare:
                     boolean
\rightleftarrows
       isExternal: boolean
   }
```

http://editor2.swagger.io/#/