

# Blackmagic Camera Control (over SDI)

Used to send Blackmagic Camera Control data over SDI out on a SKAARHOJ controller, alternatively over UDP to a receiving device such as SKAARHOJ ETH-SDI Link or WIFI-B4 Link. In UDP mode a maximum of 8 x clients can be connected from the Device Core.

SDI as the output is used whenever an IP address is 0.0.0.0 (four zeros), otherwise IP mode is used. Notice that for IP mode, two submodes exist, BASE mode and DIRECT mode (default). See note in the bottom of this document.

In SDI mode there are a few facts to mention:

- Tally: By default on power-up, incoming tally data on SDI will be forwarded through on the SDI output. Only if/when a tally state is set by the controller itself will "override" mode be turned on and incoming tally data is blocked out and only controller-generated tally data is outputted. The logic behind this is that sometimes a SKAARHOJ controller should just be transparent to tally input data and at other times it should generate tally data and block any incoming data. Letting this depend on whether a controller actively ever tries to set tally data itself is an easy way to assume the intended function.
- Camera control data: By default no incoming camera control data (CCU data) will be passed through the controller. This makes sense as a default since usually the SKAARHOJ controller is expected to be the source of camera control data and block out any incoming data. However, a special mode exists, "Momentary Override" (see bottom of document) which if set will only enable override mode for as long as it takes to send data out, then disable it again thus letting incoming camera control data pass through. This mode makes sense if you wish to allow devices upstream to send camera control data through the SKAARHOJ controller. This is relevant if there are dedicated controllers for dedicated cameras, for instance if you daisy chain SKAARHOJ controllers together. Notice however, that any incoming data while a controller is in override mode is simply blocked out and lost: In other words; if a controller upstream sends iris information simultaneously with a downstream controller, the upstream controller data is lost because it's blocked out at that time.

## Note for SKAARHOJ controllers with Blackmagic 3G-SDI Arduino Shields and Studio Fiber Converter/Camera Fiber Converter

Please Notice: Previously the Studio Fiber Converter/Camera Fiber Converter was not compatible with their own 3G-SDI shield which is the component we use inside the RCPs and other products. However with the release of Blackmagic Camera Setup 6.9.2 (April 2020) this have now been resolved.

We have tested Blackmagics fiber converter products in general to work with SDI output. This includes the Mini Converter, ATEM Camera Converter, ATEM Studio Converter and ATEM Talkback Converter 4K and now also the Studio Fiber Converter/Camera Fiber Converter.




## Controlling PT heads such as Rushworks PTX

Please have a look at the tutorial "RUSHWORKS PTX Head" at <https://www.skaarhoj.com/support/manuals/>



An excerpt of the list of BMD CamCtrl related actions.

BMD CamCtrl: Focus  
BMD CamCtrl: Focus (Relative)  
BMD CamCtrl: Iris  
BMD CamCtrl: Iris (f-stop)  
BMD CamCtrl: Sensor Gain  
BMD CamCtrl: Shutter  
BMD CamCtrl: White Balance  
BMD CamCtrl: Auto White Balance  
BMD CamCtrl: Lift  
BMD CamCtrl: Gamma  
BMD CamCtrl: Gain  
BMD CamCtrl: Hue  
BMD CamCtrl: Contrast  
BMD CamCtrl: Saturation  
BMD CamCtrl: Bars  
BMD CamCtrl: Detail  
BMD CamCtrl: CCU Settings  
BMD CamCtrl: Reset  
BMD CamCtrl: Tally  
BMD CamCtrl: Zoom  
BMD CamCtrl: Coarse Scale  
BMD CamCtrl: Video Mode  
BMD CamCtrl: Push data  
BMD CamCtrl: PT Drive  
BMD CamCtrl: PT Preset  
BMD CamCtrl: Reference Offset  
BMD CamCtrl: Reference Source

## Particular details for specific Actions

<p><b>Tally</b></p> 	<p>Sets or gets tally</p> <p><i>Binary triggers:</i> Sets the selected tally type (Red, Green, Both or Off)</p> <p><i>Pulse inputs:</i> Acts like a binary trigger</p> <p><i>Binary outputs:</i> On when selected tally matches tally value. The tally value is the incoming tally in case override mode is not enabled, otherwise it will be the memory value of whatever the controller itself set as the latest tally value.</p> <p><i>Button colors:</i> Red, for red tally, green for green tally</p> <p><i>Displays:</i> Uses background color to denote the tally value and shows the camera number in the display.</p>
<p><b>CCU Settings</b></p> 	<p>Save, Recall or Save/Recall CCU Settings (color parameters)</p> <p><i>Binary inputs:</i> If Save mode, the given CCU settings will be saved to the chosen bank. Iris can be included if wanted. In Recall mode the CCU settings will be recalled. The button will blink for 10 seconds and if you push the button again within this period of time settings will revert back to the settings prior to the recall. If Recall/Save mode (the blank option) the two functions are combined. Press and hold will Save. One press will recall.</p> <p><i>Displays:</i> Will show File 1-6</p> <p>Values:</p> <ul style="list-style-type: none"> <li>- Select Camera 1-10. If you choose Mem A-D, the camera value will be taken from the value of this memory register. A total of 6 banks can be selected, not per camera but in <i>total</i>. The function originates from the RCP implementation.</li> </ul>
<p><b>PT Preset</b></p> 	<p>Save, Recall or Save/Recall Pan/Tilt Settings (<b>zoom and focus not included</b>)</p> <p><i>Binary inputs:</i> If Save mode, the given Pan/Tilt settings will be saved to the chosen bank. In Recall mode the Pan/Tilt settings will be recalled. In Recall/Save mode (the blank option) the two functions are combined. Press and hold will Save. One press will recall.</p> <p><i>Displays:</i> Will show Cam x: Set/Pre/Rec/Del</p> <p>Values:</p> <ul style="list-style-type: none"> <li>- Select Camera 1-10. If you choose Mem A-D, the camera value will be taken from the value of this memory register. A total of 6 banks can be selected, not per camera but in <i>total</i>. The function originates from the RCP implementation.</li> </ul>

Please notice *only* a total of 6 banks/IDs are available to save CCU settings/PT Presets. Not per camera but **in total**. The reason being is that the actions was originally developed for the RCP which as designed to control just *one* camera at a time.



Please also observe zoom and focus are *not* included in either the CCU Settings or PT Presets

#39 P1

Exp

BMD ATEM: CCU Settings Mem A Recall/Save Bank: 1

and BMD ATEM: PT Preset Mem A Id: 1

CP

#39 P1

Exp

BMD CamCtrl: CCU Settings Mem A Bank: 1

and BMD CamCtrl: PT Preset Mem A Id: 1

CP

## Device Configurations

Device configuration options exist:

- Index 0: **UDP Addressing set to BASE mode:** If "1", then BASE mode is On, otherwise Off (DIRECT mode). DIRECT mode (the default behaviour) means that all commands for any camera is sent to the IP address configured for the device core. This is the "intuitive" behaviour of course and the mode you would use if you want to forward data to a ETH-SDI Link. BASE mode on the other hand forwards data to a number of different IP addresses, basically the "device core IP address + camera number". So for instance, if the device core IP address is 192.168.10.80 and you send iris data to camera 1, it would be forwarded to a ETH-B4 Link (or similar) device on 192.168.10.81 (80+1).
- Index 1: **Momentary Override:** If "1" the controller will only override incoming camera control data at times when it sends out its own data, otherwise it will be transparent to incoming data.
- Index 2: **Sensor Gain / Camera Gain Setting Range**
  - If "0" = default
  - If "1" = Extended -12dB/12dB Range
  - If "2" = Original 0db/18dB Range
- Index 3: **Tally Override**
  - If "0" = Normal behaviour
  - If "1" = Incoming tally will be blocked


### Example - Momentary Override:

Enabling Momentary Override could look like this device configuration code: "D0:1=1" where the general form would be "Dx:y=z" where "x" is the number of the device core as installed on the controller (starting with zero for the first device core), "y" the index number and "z" the value for that index.

To confirm that a device configuration is in fact detected by the controller, please check it out on the serial monitor where it will be mentioned:

```
Compiled: Sep 13 2017 08:52:08
DeviceCore #1: BMDCamCtrl0
BMD Shield Initialized (F/W Ver: 0.10, Protocol Ver: 1.0)
BMDCamCtrl CCU Momentary Override Activated
setup() Done
-----
```


If the BMD CamCtrl Device Core is the first like below:



**BMD CamCtrl**

BlackMagic Design Camera Control protocol over Arduino Shield (hardware option required). Lets you send control commands over SDI Ancillary data to cameras from BlackMagic Design, including URSA Mini, URSA Mini Pro, Studio Cameras, Micro Studio camera. Transport over fiber is also supported. [See Action Manual](#)

✕



then Momentary Override would be set by this configuration under "Manage Media" on the configuration page for your controller. Access this by pressing "Online Configuration" in the Firmware Application. Remember to save on the configuration page *and* press "Check for updates" in the Firmware Application.


### Device Core Options

Some device cores support additional options that can be defined through this text field. Please refer to the manual for the particular device core for details.


## Example - Sensor Gain / Camera Gain Setting Range

Enabling the Sensor to the -12dB/12dB Range could look like this device configuration code: "D0:2=1" where the general form would be "Dx:y=z" where "x" is the number of the device core as installed on the controller (starting with zero for the first device core), "y" the index number and "z" the value for that index.

If the BMD CamCtrl Device core is the first like below:



Sensor Gain range would be set by this configuration under "Manage Media" on the configuration page for your controller. Access this by pressing "Online Configuration" in the Firmware Application. Remember to save on the configuration page *and* press "Check for updates" in the Firmware Application.



To confirm that a device configuration is in fact detected by the controller, please check it out on the serial monitor where it will be mentioned:

```
DeviceCore #0: BMDCamCtrl0
BMD Shield Initialized (F/W Ver: 0.10, Protocol Ver: 1.0)
BMDCamCtrl: Extended CCU Sensor gain range
setup() Done
-----
```