

Work Report — Audit Logs Module

Project: JobHuntly HR Recruitment Platform

Date: June 01, 2026

Developer: Esther Ingabire

Branch: `feature/audit-logs`

SUMMARY

Implemented the Audit Logs module which provides a tamper-evident trail of all sensitive actions across the platform. Built as a global NestJS module so any service can log actions with a single method call. The admin query endpoint supports full filtering and pagination. Additionally, resolved correctness issues found in the Authentication and User Management modules: Prisma enum usage, `lastLogin` stamping, soft-delete completion, and automatic audit log entries on all sensitive user events.

BRANCH DELIVERED

Branch	Purpose	Status
<code>feature/audit-logs</code>	Audit log module + auth/users bug fixes	Pushed
<code>backend-devops</code>	Merged feature/settings-login-details	Pushed

SCHEMA CHANGES

User table — fields added from technical specification:

Field	Type	Default	Purpose
<code>phone</code>	VARCHAR UNIQUE	null	Optional phone number
<code>phone_verified</code>	BOOLEAN	false	Phone verification status
<code>last_login</code>	TIMESTAMP	null	Stamped on every successful login
<code>two_factor_enabled</code>	BOOLEAN	false	2FA toggle
<code>deleted_at</code>	TIMESTAMP	null	Soft delete timestamp

New table — AuditLog:

Column	Type	Notes
id	UUID PK	Auto-generated
user_id	UUID FK nullable	References users — SET NULL on delete so logs are never lost
action	VARCHAR	e.g. LOGIN, UPDATE_EMAIL
module	VARCHAR	e.g. auth, users
old_values	JSONB	State before the action
new_values	JSONB	State after the action
ip_address	VARCHAR	nullable
user_agent	TEXT	nullable
created_at	TIMESTAMP	Indexed for range queries

API ENDPOINT

Method	Endpoint	Auth	Description
GET	/api/v1/admin/audit-logs	Bearer Token	Query paginated audit logs (ADMIN / SUPER_ADMIN only)

Supported query parameters: module , action , userId , from , to , page , limit

ACTIONS LOGGED AUTOMATICALLY

Action	Module	Triggered By	Values Captured
REGISTER	auth	POST /auth/register	email, role
LOGIN	auth	POST /auth/login	email
LOGOUT	auth	POST /auth/logout	userId
GOOGLE_LOGIN	auth	GET /auth/google/callback	email
UPDATE_EMAIL	users	PATCH /users/me/email	old email, new email
UPDATE_PASSWORD	users	PATCH /users/me/password	action only — no password values logged
CLOSE_ACCOUNT	users	DELETE /users/me	userId

BUG FIXES

File	Issue	Fix
<code>auth.service.ts</code>	Raw string literals used for enum values	Replaced with <code>UserStatus</code> , <code>UserRole</code> , <code>AuthProvider</code> Prisma enum constants
<code>auth.service.ts</code>	<code>lastLogin</code> was always <code>null</code>	Stamped on every successful login and Google OAuth login
<code>users.service.ts</code>	Soft delete did not stamp <code>deletedAt</code>	<code>closeAccount()</code> now sets both <code>status: deleted</code> and <code>deletedAt: new Date()</code>

FILES ADDED

File	Purpose
<code>src/modules/audit-logs/audit-log.module.ts</code>	Global NestJS module registration
<code>src/modules/audit-logs/audit-log.controller.ts</code>	GET /admin/audit-logs endpoint
<code>src/modules/audit-logs/audit-log.service.ts</code>	log() and findAll() business logic
<code>src/modules/audit-logs/audit-log.repository.ts</code>	Database queries with pagination
<code>src/modules/audit-logs/dto/query-audit-log.dto.ts</code>	Query parameter validation
<code>src/modules/audit-logs/audit-log.service.spec.ts</code>	Service unit tests
<code>src/modules/audit-logs/audit-log.controller.spec.ts</code>	Controller unit tests
<code>src/common/guards/roles.guard.ts</code>	Shared RBAC guard (moved to common)
<code>src/common/decorators/roles.decorator.ts</code>	Shared @Roles() decorator

SECURITY

Feature	Detail
Endpoint access control	ADMIN and SUPER_ADMIN roles only — enforced by RolesGuard
Password never logged	UPDATE_PASSWORD audit entry captures action only — zero credential data
Log retention on user deletion	AuditLog.userId is SET NULL on cascade — logs are never lost when a user is deleted
Fire-and-forget logging	Logging failures never propagate to the API consumer
Soft delete completed	closeAccount() sets both status and deletedAt so deleted users are never hard-removed

TEST COVERAGE

Test File	Tests	Result
audit-log.service.spec.ts	7	PASS
audit-log.controller.spec.ts	3	PASS
auth.service.spec.ts	15	PASS
users.service.spec.ts	11	PASS
users.controller.spec.ts	3	PASS
auth.controller.spec.ts	3	PASS
candidate-profile.service.spec.ts	5	PASS
candidate-profile.controller.spec.ts	3	PASS
Full Suite	50	PASS