

Reactive Forms Module

SD 555 – Web Application Development III

Maharishi International University

Department of Computer Science

Associate Professor Asaad Saad

Maharishi International University - Fairfield, Iowa



All rights reserved. No part of this slide presentation may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying or recording, or by any information storage and retrieval system, without permission in writing from Maharishi International University.

Forms in Angular

A lot of applications are very form-intensive, especially for enterprise development.

Forms can end up being really complex:

- Form inputs are meant to **modify data**, both on the page and the server
- Users cannot be trusted in what they enter, so you need to **validate** values
- The UI needs to clearly **state expectations** and errors
- **Dependent fields** can have complex logic
- We want to be able to **test** our forms, without relying on DOM selectors

Form states such as being: **valid, invalid, pristine, dirty, untouched, touched, disabled, enabled, pending...etc**

Choosing an approach

Angular offers two approaches to work with forms:

Reactive forms (Data-driven forms)

Provide direct, explicit access to the underlying form's object model. Compared to template-driven forms, they are more **robust**: they're more **scalable**, **reusable**, and **testable**. If forms are a key part of your application, or you're already using reactive patterns for building your application, use reactive forms.

Template-driven forms

Rely on directives in the template to create and manipulate the underlying object model. They **don't scale** as well as reactive forms. If you have very **basic form requirements and logic** that can be managed solely in the template, template-driven forms could be a good fit.

Angular Form Models

FormGroup is an aggregation of the values of its children.

FormControl corresponds to a simple UI element, such as an input. It has a **value**, **status**, and a map of **errors**

FormArray A collection that has multiple FormControl elements.



All of the above models include two observables: **statusChanges** and **valueChanges**

The **Validators** interface allows us to add built-in validation rules.



Why Form Model?

The form model is a UI-independent way to represent user input consist of simple controls (`FormControl1`) and their combinations (`FormGroup` and `FormArray`), where each control has a value, status, validators, errors, it emits events and it can be disabled.

Having this model has the following advantages:

- Form handling is a complex problem. Splitting it into UI-independent and UI-dependent parts makes them easier to manage. And we can test form handling without rendering UI.
- Having the form model makes reactive forms possible.

Form Parts

Form Model

Create the form models: `FormGroup`, `FormControl`, and `FormArray`.

DOM

Create your DOM form elements `<form/>`, `<input/>`, `<select/>`, `<textarea/>`.

Form Directives

Connect the above two parts with form directives: `[formGroup]`, `formControlName`.

Type Unsafe Forms

Angular provides a type-safe checking out of the box, but only if we correctly create the form.

The following syntax is type unsafe and **NOT** recommended:

```
form!: FormGroup;  
form!: FormGroup<any>;  
form!: FormGroup<{  
    email: FormControl<string | null>,  
    password: FormControl<string | null>  
}>;
```

On top of that, all form fields are considered to be **nullable**, this is because when we call the form **reset()** method, Angular will set all of the form fields to **null**.

FormBuilder Service

```
form = inject(FormBuilder).nonNullable.group({  
    email: '',  
    password: ''  
})
```

// to pass validators:

```
form = formBuilerInstance.nonNullable.group({  
    'form_field': ['default value',  
        ValidatorFn | ValidatorFn[],  
        AsyncValidatorFn | AsyncValidatorFn[] ]  
});
```

// or use the AbstractControlOptions as follows:

```
form = formBuilerInstance.nonNullable.group({  
    'form_field': ['default value', {  
        validators?: ValidatorFn | ValidatorFn[];  
        asyncValidators?: AsyncValidatorFn | AsyncValidatorFn[];  
        updateOn?: "change" | "blur" | "submit"; }]  
});
```

It helps building type-safe and reactive forms. The **nonNullable** does not affect the possibility of having undefined as a value, which should also be checked.

Form API

```
this.form.value // { email: '', password: '' }
```

```
this.form.valid // true or false
```

```
this.form.patchValue({ email: 'asaad@miu.edu', password: '123456' })
```

```
this.form.controls.email.value // reading the email value
```

```
this.form.controls.email.valid // true or false
```

```
this.form.controls.email.patchValue('theo@miu.edu') // setting the email value
```

```
this.form.controls.email.hasError('required') // reading validation errors
```

```
this.form.controls.email.setErrors({required: true}) // invalidate email
```

```
this.form.controls.email.setErrors(null) // set email as valid
```

Watching For Changes

Both `FormGroup` and `FormControl` have two built-in `EventEmitter` objects that we can use to observe changes.

```
this.form.statusChanges // observable
this.form.valueChanges // observable
this.form.events // observable, combine subscriptions to valueChanges and statusChanges

this.form.controls.email.statusChanges // observable
this.form.controls.email.valueChanges // observable
this.form.controls.email.events // observable
```

Remember to **unsubscribe** when you unmount the component.

Unified control state change events

The events observable emits four distinct types of events: PristineEvent, StatusEvent, TouchedEvent, and ValueChangeEvent.

```
control.events.subscribe(event => {  
  if(e instanceof StatusEvent) {  
    console.log(e.status)  
  }  
  if(e instanceof ValueChangeEvent) {  
    console.log(e.value)  
  }  
  if(e instanceof PristineEvent) {  
    console.log(e.pristine)  
  }  
  if(e instanceof TouchedEvent) {  
    console.log(e.touched)  
  }  
});
```

Connecting DOM to Model

```
@Component({
  imports: [ReactiveFormsModule],
  template: `<form [formGroup]="form" (ngSubmit)="onSubmit()">
    <input type="text" formControlName="email" />
    @if(!form.controls.email.valid){ <div>Invalid email</div> }
    <input type="text" formControlName="password" />
    <button type="submit" [disabled]="!form.valid">Submit</button>
  </form>`
})
```

Inspect the code and see how angular adds state change classes to the form elements.

Display Errors Gracefully

```
@Component({
  imports: [ReactiveFormsModule],
  template: `
    <form [formGroup]="form">
      <input formControlName="email" />
      @if(email.invalid && (email.dirty || email.touched)){
        <div>
          @if(email.hasError('required')){<div>Email is required</div>}
          @if(email.hasError('email')){<div>Email is not valid</div>}
        </div>
      }
    </form>
  `,
})
export class AppComponent {
  form = inject(FormBuilder).nonNullable.group({
    email: ['', [Validators.required, Validators.email]]
  })
  get email() { return this.form.controls.email; }
}
```

Custom Synchronous Validator

A validator is a function that takes a **AbstractControl** as an input and returns a **StringMap<string, boolean>** where the key is error code and the value is true if it fails

```
customValidator(control: AbstractControl): {[s: string]: boolean} | null {  
    return control.value === 'Example'? { example: true } : null  
}
```

```
@if(form_field.hasError('example')){ <div>Example is not valid</div> }
```

Custom Cross-Validation Sync Validator

```
public form: FormGroup = inject(FormBuilder).nonNullable.group({
  email: '',
  password: '',
  confirm_password: ''
}, { validators: this.match_password })

match_password(control: AbstractControl) {
  return control.get('password')?.value === control.get('confirm_password')?.value
    ? null
    : { mismatch: true }
}

@if(form.hasError('mismatch')){ <div>Passwords do not match</div> }
```


Custom Asynchronous Validator

Asynchronous validator is a function that takes a **FormControl** as its input and returns a **Promise<any>** or an **Observable<any>**

```
asyncValidator(control: FormControl): Promise<any> | Observable<any> {  
    // mimic HTTP request  
    return of(null).pipe(delay(1500)) // valid, mimic delay after 1500ms  
}
```

Notes

- Because async validators run asynchronously, make sure you bind **this** to the component instance.
- While the promise or the observable is being resolved, the status of the form/control will be **PENDING**
- You can delay updating the form validity by changing the **updateOn** property from **change** (default) to **submit** or **blur**. You may also replace the async validator by subscribing to **valueChanges** and add a **debounceTime** delay before running your custom validation logic.

Environment Variables

In the `/src/environment` folder you have an environment file for development and one for production.

Angular takes care of swapping the environment file for the correct one.

`ng generate environments`

```
"development": {  
  "fileReplacements": [  
    {  
      "replace": "src/environments/environment.ts",  
      "with": "src/environments/environment.development.ts"  
    }  
  ]  
}
```

angular.json



Web Workers

Web workers lets you run CPU-intensive computations in a background thread, freeing the main thread to update the user interface.

`ng generate web-worker <location>`

```
addEventListener('message', ({ data }) => {  
  const response = { student_id: data.id, grade: 95 }  
  postMessage(response);  
});
```

```
const worker = new Worker(new URL('./app.worker', import.meta.url));  
worker.onmessage = ({ data }) => {  
  results: { student_id: number, grade: number } = data;  
};  
worker.postMessage({ id: 98123 });
```



File Upload - Angular

```
@Component({
  selector: 'app-root',
  standalone: true,
  imports: [ReactiveFormsModule],
  template: `
    <form [formGroup]="form" (ngSubmit)="submit()">
      <input type="email" formControlName="email"/>
      <input formControlName="avatar" type="file" (change)="onFileSelect($event)" />
      <button [disabled]="form.invalid">Submit</button>
    </form> `
})
export class AppComponent {

  form = inject(FormBuilder).nonNullable.group({
    email: ['asaad@miu.edu', Validators.required],
    avatar: ['', Validators.required],
  })
  ... Next page
}
```



File Upload - Angular (Continued)

```
file!: File;
#http = inject(HttpClient);

onFileSelect(event: Event) {
  const input = event.target as HTMLInputElement;
  if (input.files!.length > 0) this.file = input.files![0];
}

submit() {
  const formData = new FormData();
  formData.append('email', this.form.get('email')?.value as string);
  formData.append('avatar', this.file);

  this.#http.post<{ success: boolean }>('http://localhost:3000/', formData)
    .subscribe(response => {
      console.log(response);
      this.form.reset();
    })
}
}
```



Deploy for Production

```
> ng build // When you run the ng build command, it creates a /dist folder.
```

- Removes unwanted white space by minifying files.
- Uglifies files by renaming functions and variable names.
- AoT (Ahead-of-Time) compilation

To serve any static resource from the /public folder, set the base for your assets:

```
> ng build --base-href /public/
```