tesla fire systems

SINCE 2006

Model: 1575NR
Nozzle Spec Sheet

Lexan Red Nozzle — Model 1575NR



The Model 1575NR is a 1½" NPSH combination fog/straight-stream nozzle constructed of high-impact polycarbonate. Positions: fog, straight stream and off. Ideal for commercial and industrial applications.

- Colour: Red (black rubber bumper)
- Thread: 1½" NPSH
- Maximum operating pressure: 200 PSI
- Approximate flow: 75 GPM @ 100 PSI
- Approximate distance: 60 ft
- Height: 4-5/8"
- NSN: 4210-00-181-8872 | NFES: 0138
- UL Listed (File EX5518) | FM Approved (FM 5511)

Approvals & Compliance

Compliance Regulation Type	Regulatory Identification	Reference
UL — Underwriters Laboratories Inc.	**EX 5518**	UL File EX5518 — Category VUFZ: Nozzles, Spray Hose, Portable.
FM Approvals LLC	**FM 5511**	FM Approved — Class of Work 5511, Water Spray Nozzles, Fire Hose. Approval Standard FM 5511: Firefighting Nozzles for Use with Hose, Monitor Assemblies and other Firefighting Equipment. Listing country: Canada.

Certification file and approval numbers are available for verification through UL Product iQ (iq.ulprospector.com, File EX5518) and the FM Approvals Approval Guide (approvalguide.com). Reprinted from Product iQ with permission from UL Solutions. ©2026 UL LLC. Only products bearing the authorized UL Mark and approved markings are covered by the Listing or Approval.





tesla fire systems inc.

Toronto — Head Office
1010 Bathurst St, Toronto, ON M5R 3G7
(416) 535-9693 | 1-866-471-2916
info@teslafiresystems.com

Vancouver (Office)
112-970 Burrard Street
Vancouver, BC V6Z 2R4
1-866-471-2916

Montreal (Office)
2001 Blvd Robert-Bourassa, 17th Floor
Montreal, QC H3A 2A6
1-866-471-2916