

✓ colab에 옮겨서 실행해보자~

사유: pdf 저장이 편함, mediapipe 설치가 안됨 이슈...

```
!pip install mediapipe
```

```
Collecting mediapipe
  Downloading mediapipe-0.10.20-cp310-cp310-manylinux_2_28_x86_64.whl.metadata (9.7 kB)
Requirement already satisfied: absl-py in /usr/local/lib/python3.10/dist-packages (from mediapipe) (1.4.0)
Requirement already satisfied: attrs>=19.1.0 in /usr/local/lib/python3.10/dist-packages (from mediapipe) (24.3.0)
Requirement already satisfied: flatbuffers>=2.0 in /usr/local/lib/python3.10/dist-packages (from mediapipe) (24.3.25)
Requirement already satisfied: jax in /usr/local/lib/python3.10/dist-packages (from mediapipe) (0.4.33)
Requirement already satisfied: jaxlib in /usr/local/lib/python3.10/dist-packages (from mediapipe) (0.4.33)
Requirement already satisfied: matplotlib in /usr/local/lib/python3.10/dist-packages (from mediapipe) (3.8.0)
Requirement already satisfied: numpy<2 in /usr/local/lib/python3.10/dist-packages (from mediapipe) (1.26.4)
Requirement already satisfied: opencv-contrib-python in /usr/local/lib/python3.10/dist-packages (from mediapipe) (4.10.0.84)
Requirement already satisfied: protobuf<5,>=4.25.3 in /usr/local/lib/python3.10/dist-packages (from mediapipe) (4.25.5)
Collecting sounddevice>=0.4.4 (from mediapipe)
  Downloading sounddevice-0.5.1-py3-none-any.whl.metadata (1.4 kB)
Requirement already satisfied: sentencepiece in /usr/local/lib/python3.10/dist-packages (from mediapipe) (0.2.0)
Requirement already satisfied: CFFI>=1.0 in /usr/local/lib/python3.10/dist-packages (from sounddevice>=0.4.4->mediapipe) (1.17.1)
Requirement already satisfied: ml-dtypes>=0.2.0 in /usr/local/lib/python3.10/dist-packages (from jax->mediapipe) (0.4.1)
Requirement already satisfied: opt-einsum in /usr/local/lib/python3.10/dist-packages (from jax->mediapipe) (3.4.0)
Requirement already satisfied: scipy>=1.10 in /usr/local/lib/python3.10/dist-packages (from jax->mediapipe) (1.13.1)
Requirement already satisfied: contourpy>=1.0.1 in /usr/local/lib/python3.10/dist-packages (from matplotlib->mediapipe) (1.3.1)
Requirement already satisfied: cycler>=0.10 in /usr/local/lib/python3.10/dist-packages (from matplotlib->mediapipe) (0.12.1)
Requirement already satisfied: fonttools>=4.22.0 in /usr/local/lib/python3.10/dist-packages (from matplotlib->mediapipe) (4.55.3)
Requirement already satisfied: kiwisolver>=1.0.1 in /usr/local/lib/python3.10/dist-packages (from matplotlib->mediapipe) (1.4.7)
Requirement already satisfied: packaging>=20.0 in /usr/local/lib/python3.10/dist-packages (from matplotlib->mediapipe) (24.2)
Requirement already satisfied: pillow>=6.2.0 in /usr/local/lib/python3.10/dist-packages (from matplotlib->mediapipe) (11.0.0)
Requirement already satisfied: pyparsing>=2.3.1 in /usr/local/lib/python3.10/dist-packages (from matplotlib->mediapipe) (3.2.0)
Requirement already satisfied: python-dateutil>=2.7 in /usr/local/lib/python3.10/dist-packages (from matplotlib->mediapipe) (2.8.2)
Requirement already satisfied: pycparser in /usr/local/lib/python3.10/dist-packages (from CFFI>=1.0->sounddevice>=0.4.4->mediapipe) (2.2)
Requirement already satisfied: six>=1.5 in /usr/local/lib/python3.10/dist-packages (from python-dateutil>=2.7->matplotlib->mediapipe) (1.17.0)
Downloading mediapipe-0.10.20-cp310-cp310-manylinux_2_28_x86_64.whl (35.6 MB)
35.6/35.6 MB 47.4 MB/s eta 0:00:00
Downloading sounddevice-0.5.1-py3-none-any.whl (32 kB)
Installing collected packages: sounddevice, mediapipe
Successfully installed mediapipe-0.10.20 sounddevice-0.5.1
```

```
import cv2
import mediapipe as mp
import os
import csv
# numpy version 1.24.3
```

앗싸 mediapipe 구간 성공

✓ 발레와 요가 구분하기

```
# ballet
image_folder = '/content/drive/MyDrive/Colab Notebooks/인명학/data/ballet/'
csv_file = 'first_ballet.csv'
```

```
# yoga
image_folder = '/content/drive/MyDrive/Colab Notebooks/인명학/data/yoga'
csv_file = 'first_yoga.csv'
```

```
mp_pose = mp.solutions.pose
pose = mp_pose.Pose(static_image_mode=True) # True == 이미지 모드, False == 비디오 모드
# 이미지로 진행할 예정이기 때문에 True 그대로
```

```
with open(csv_file, mode='w', newline='') as file:
    writer = csv.writer(file)
    writer.writerow([
        'Image',
        'left wrist X', 'left wrist Y',
        'left ankle X', 'left ankle Y',
        'right wrist X', 'right wrist Y',
        'right ankle X', 'right ankle Y',
```

```

    'hip X', 'hip Y',
    'Label'
]) # 손목 발목 골반?

for img_name in os.listdir(image_folder):
    img_path = os.path.join(image_folder, img_name)
    image = cv2.imread(img_path)
    if image is None:
        continue

    height, width, _ = image.shape

    image_rgb = cv2.cvtColor(image, cv2.COLOR_BGR2RGB)
    result = pose.process(image_rgb)

    if result.pose_landmarks:
        left_wrist = result.pose_landmarks.landmark[mp_pose.PoseLandmark.LEFT_WRIST]
        left_ankle = result.pose_landmarks.landmark[mp_pose.PoseLandmark.LEFT_ANKLE]
        right_wrist = result.pose_landmarks.landmark[mp_pose.PoseLandmark.RIGHT_WRIST]
        right_ankle = result.pose_landmarks.landmark[mp_pose.PoseLandmark.RIGHT_ANKLE]
        left_hip = result.pose_landmarks.landmark[mp_pose.PoseLandmark.LEFT_HIP]
        right_hip = result.pose_landmarks.landmark[mp_pose.PoseLandmark.RIGHT_HIP]
        # 어깨, 손목 외 무릎 추가할 시:
        # left_KNEE = result.pose_landmarks.landmark[mp_pose.PoseLandmark.LEFT_KNEE]

    # 절대 좌표
    left_wrist_x = int(left_wrist.x * width)
    left_wrist_y = int(left_wrist.y * height)
    left_ankle_x = int(left_ankle.x * width)
    left_ankle_y = int(left_ankle.y * height)
    right_wrist_x = int(right_wrist.x * width)
    right_wrist_y = int(right_wrist.y * height)
    right_ankle_x = int(right_ankle.x * width)
    right_ankle_y = int(right_ankle.y * height)
    left_hip_x = int(left_hip.x * width)
    left_hip_y = int(left_hip.y * height)
    right_hip_x = int(right_hip.x * width)
    right_hip_y = int(right_hip.y * height)

    # CSV
    with open(csv_file, mode='a', newline='') as file:
        writer = csv.writer(file)
        writer.writerow([
            img_name,
            left_wrist_x, left_wrist_y,
            left_ankle_x, left_ankle_y,
            right_wrist_x, right_wrist_y,
            right_ankle_x, right_ankle_y,
            left_hip_x, left_hip_y,
            right_hip_x, right_hip_y,
            # 'ballet'
            'yoga'
        ])
])

```

✓ 머신러닝 분류기 사용

제안된 코드에 라이선스가 적용될 수 있습니다. | 0x6f736f646f/MLDeploy | AI-Engg/CognitiveDissonance | toandaominh1997/dataset-for-beginners | martinkozle/iis-course | | 03Akshay/ass

```

import pandas as pd
from sklearn.model_selection import train_test_split
from sklearn.ensemble import RandomForestClassifier
from sklearn.metrics import accuracy_score

ballet_data = pd.read_csv('first_ballet.csv')
yoga_data = pd.read_csv('first_yoga.csv')

all_data = pd.concat([ballet_data, yoga_data], ignore_index=True)
shuffled_data = all_data.sample(frac=1, random_state=42).reset_index(drop=True)

X = shuffled_data.drop(columns=['Image', 'Label'])
y = shuffled_data['Label']


X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.2, random_state=42)

```

```
classifier = RandomForestClassifier(n_estimators=100, random_state=42)
classifier.fit(X_train, y_train)

y_pred = classifier.predict(X_test)

accuracy = accuracy_score(y_test, y_pred)
print(f"Accuracy: {accuracy}")
```

 Accuracy: 0.75