Pin for Insulator.
Standard: IS-2486.
Material: M.S
Finish: HDG
Uses: Pin Insulator
Range: 1.1 KV to 33 KV

PG Clamp (Connector)
Standard: IS-5561
Material: Aluminium
Finish: MS Parts HDG
Uses: Conductor Accessories
Range: All Types.

Eye Bolt
Standard: BS-16
Material: M.S
Finish: HDG
Uses: Stay Assemble.
range: L.T & H.T

Piercing Connector
Standard: IS-5561
Material: Lynol (PVC)
Finish: MS Parts SS
Uses: Cable Accessories
Range: LT & HT

Disc Hardware
Standard: IS- 2486
Material: Aluminium
Finish: MS Parts HDG
Uses: Disc Insulator
Range: 45 KN to 70 KN.

Suspension Clamp
Standard: IS-2486
Material: Aluminium
Finish: MS Parts HDG
Uses: HV Line
Range: 70 KN to 165 KN

D-Iron Clamp
Standard: IS-7935
Material: M.S
Finish: HDG
Uses: LT Line
Range: 1 Ph 2 Wire
3 Ph 4 Wire.

Disc Hardware
Standard: IS-2486
Material: Aluminium
Finish: MS Parts HDG
Uses: Disc Insulator
Range: 70 KN to 90 KN

Dead-End Clamp
Standard: IS-2486
Material: Aluminium
Finish: MS Parts HDG
Uses: Ab Cable
Range: L.T & H.T

Eye Hook
Standard: REC
Material: MS
Finish: HDG
Uses: Clapm for ABC
Range: LT & HT

Suspension Clamp
Standard: IS-2486
Material: Aluminium
Finish: MS Parts HDG
Uses: AB Cable
Range: LT & HT

Turn Buckle
Standard: REC
Material: MS
Finish: HDG
Uses: Transformer Seating
Range: All Types.

Danger Board
Standard: IS-2551
Material: MS
Finish: Viterious Enamelled
Uses: Caution Alert
Range: All Types

Coil earthing
Standard: REC
Material: MS
Finish: HDG
Uses: Earthing
Range: All Type

Line Spacer
Standard: REC
Material: PVC
Uses: Line Space
Range: 1 Ph 2 Wire
3 Ph 4 Wire

Disc hardware
Standard: IS-2486
Material: Aluminium
Finish: MS Parts HDG
Uses: Disc Insulator
Range: 30 KN to 45 KN

Stay Sets
Standard: BS - 16
Material: MS
Finish: HDG
Uses: Pole Stay Assemble
Range: LT & HT
Type: Convensional / Tubular.

Hexagonal Bolt
Standard: IS- 1363
Material - MS
Finish: HDG
Uses: Bolting Tightner
Range: All Types

BPL-KIT
Standard: REC
Material: As Specification
Finish: As per QAP
Uses: BPL Service Connection

Connector
Material: Aluminium
Uses: Cable Tap
Range: All Types.

U.D.C
standard: REC
Material: Aluminium / Copper
Uses: Connector Cable to
Service Wire.
Type: All Types

Jointing Sleeves
Standard: IS-5561
Material: Aluminium
Finish: 99.99%
Uses: Conductor Jointing
Range: All Types

Pole Clamp
Guy Insulator
Pin Insulator
Adjustable Plate
Reel Insulator.
Al.Lug
Vibration Dumper (Nutraliser)
C.I Reel.
Anchor Bolt
Angle Bracket
Earth Pipe