

• 데이터 로드

```
31 def load_dataset(self, dataset_id, tokenizer):
32     def tokenization(examples):
33         sources = []
34         targets = []
35         prompt = self.PROMPT_TEMPLATE
36         for instruction, input, output in zip(examples['instruction'], examples['input'], examples['output']):
37             if input is not None and input != "":
38                 instruction = instruction + '\n' + input
39                 source = prompt.format_map({'instruction': instruction})
40                 target = f"{output}{tokenizer.eos_token}"
41
42                 sources.append(source)
43                 targets.append(target)
44
45         tokenized_sources = tokenizer(sources, return_attention_mask=False)
46         tokenized_targets = tokenizer(targets, return_attention_mask=False, add_special_tokens=False)
47
48         all_input_ids = []
49         all_labels = []
50         for s, t in zip(tokenized_sources['input_ids'], tokenized_targets['input_ids']):
51             input_ids = torch.LongTensor(s + t)[:self.MAX_SEQ_LEN]
52             labels = torch.LongTensor([-100] * len(s) + t)[:self.MAX_SEQ_LEN]
53             assert len(input_ids) == len(labels)
54             all_input_ids.append(input_ids)
55             all_labels.append(labels)
56
57         results = {'input_ids': all_input_ids, 'labels': all_labels}
58         return results
59
60     all_datasets = []
61     raw_dataset = load_dataset(dataset_id)
62     tokenization_func = tokenization
```

Hugging Face Hub Model load

• 토큰화

```
31 def load_dataset(self, dataset_id, tokenizer):
32     def tokenization(examples):
33         sources = []
34         targets = []
35         prompt = self.PROMPT_TEMPLATE
36         for instruction, input, output in zip(examples['instruction'], examples['input'], examples['output']):
37             if input is not None and input != "":
38                 instruction = instruction + '\n' + input
39                 source = prompt.format_map({'instruction': instruction})
40                 target = f"{output}{tokenizer.eos_token}"
41
42                 sources.append(source)
43                 targets.append(target)
44
45         tokenized_sources = tokenizer(sources, return_attention_mask=False)
46         tokenized_targets = tokenizer(targets, return_attention_mask=False, add_special_tokens=False)
47
48         all_input_ids = []
49         all_labels = []
50         for s, t in zip(tokenized_sources['input_ids'], tokenized_targets['input_ids']):
51             input_ids = torch.LongTensor(s + t)[:self.MAX_SEQ_LEN]
52             labels = torch.LongTensor([-100] * len(s) + t)[:self.MAX_SEQ_LEN]
53             assert len(input_ids) == len(labels)
54             all_input_ids.append(input_ids)
55             all_labels.append(labels)
56
57         results = {'input_ids': all_input_ids, 'labels': all_labels}
58         return results
59
60     all_datasets = []
61
62     raw_dataset = load_dataset(dataset_id)
63     tokenization_func = tokenization
```

Tokenizer Text to Number ID

모델 학습을 위한 데이터 전처리

② 데이터 전처리

• 배치 및 Collator

```
1 from dataclasses import dataclass
2 from typing import Dict, Sequence
3
4 import torch
5 import transformers
6
7
8 @dataclass
9 class DataCollatorForSupervisedDataset:
10     tokenizer: transformers.PreTrainedTokenizer
11
12     def __call__(self, instances: Sequence[Dict]) -> Dict[str, torch.Tensor]:
13         input_ids, labels = tuple(
14             [instance[key] for instance in instances] for key in ("input_ids", "labels")
15         )
16         input_ids = torch.nn.utils.rnn.pad_sequence(
17             input_ids, batch_first=True, padding_value=self.tokenizer.pad_token_id
18         )
19         labels = torch.nn.utils.rnn.pad_sequence(
20             labels, batch_first=True, padding_value=-100
21         )
22         return dict(
23             input_ids=input_ids,   패딩을 통해 배치의 데이터 길이 최적화
24             labels=labels,
25             attention_mask=input_ids.ne(self.tokenizer.pad_token_id),
26         )
```

• 자동화 생성

```
62 raw_dataset = load_dataset(dataset_id)
63 tokenization_func = tokenization
64 tokenized_dataset = raw_dataset.map(
65     tokenization_func,
66     batched=True,
67     remove_columns=["instruction", "input", "output"],
68     keep_in_memory=False,
69     desc="preprocessing on dataset",
70 )
71 processed_dataset = tokenized_dataset
72 processed_dataset.set_format('torch')
73 all_datasets.append(processed_dataset['train'])
74 all_datasets = concatenate_datasets(all_datasets)
75 return all_datasets
76
77 def get_data_collator(self, tokenizer):
78     collator = DataCollatorForSupervisedDataset(tokenizer)
79     return collator
```

Tokenizing DataSet