

System	
Hot shoe	Provided (supports TTL flash control); supports sync speeds as fast as $\frac{1}{125}$ s
Sync contact	X contact; supports sync speeds as fast as $\frac{1}{125}$ s
Sync terminal	Provided
Electronic viewfinder (EVF)	EVF-GFX3 interchangeable electronic viewfinder (supplied)
LCD monitor	<ul style="list-style-type: none"> <li>• <b>Rear monitor:</b> 3.2-in/8.1 cm, 2360k-dot color LCD touch screen with 3-way tilt</li> <li>• <b>Shoulder monitor:</b> 2.09-in/5.31 cm, 219 × 320-dot memory LCD monitor</li> </ul>
Movies (with stereo sound)	<ul style="list-style-type: none"> <li>• <b>Movie size:</b>  2.76:1,  1.38:1,  16:9,  17:9,  2.35:1,  17:9,  3:2,  16:9,  16:9,  17:9,  16:9,  17:9</li> <li>  The size that can be selected depend on the <b>IMAGE FORMAT</b> setting.         </li> <li>• <b>Frame rate:</b> 59.94P, 50P, 29.97P, 25P, 24P, 23.98P</li> <li>• <b>Recording/output format:</b> <ul style="list-style-type: none"> <li>- H.265 (10-bit MOV 4:2:2/4:2:0; 720, 360, 200, 100, or 50 Mbps)</li> <li>- H.264 (8-bit MOV/MP4 4:2:0; 360, 200, 100, or 50Mbps)</li> <li>- ProRes 422 HQ, ProRes 422, ProRes 422 LT (10-bit MOV 4:2:2)</li> <li>- HDMI output supported (RAW output supported with Atomos and Blackmagic Design external recorders; 8-bit 4:2:2/10-bit 4:2:2)</li> </ul> </li> </ul>
High-speed movies	<ul style="list-style-type: none"> <li>• <b>Movie size:</b>  16:9,  17:9</li> <li>• <b>Frame advance rate:</b> 120P, 100P</li> </ul>