System	
White balance	Auto (WHITE PRIORITY, AUTO, AMBIENCE PRIORITY), Custom 1,
	Custom 2, Custom 3, color temperature selection, direct sun-
	light, shade, daylight fluorescent, warm white fluorescent,
	cool white fluorescent, incandescent, underwater
Self-timer	• Still pictures: Off, 2 sec., 10 sec.
	• <b>Movies</b> : Off, 3 sec., 5 sec., 10 sec.
Flash mode	• MODE: TTL MODE (FLASH AUTO, STANDARD, SLOW SYNC.),
	MANUAL, MULTI, OFF
	• SYNC. MODE: 1ST CURTAIN, 2ND CURTAIN, AUTO FP (high-
	speed sync)
	• RED EYE REMOVAL: 🍑 FLASH, OFF
Hot shoe	Provided (supports TTL flash control); supports sync speeds
	as fast as ½50 s
Sync contact	X contact; supports sync speeds as fast as ½50 s
Sync terminal	Provided
	r 0.5-in., 3690k-dot OLED viewfinder; magnification 0.80×
(EVF)	with 50 mm lens (35 mm format equivalent) at infinity and
	diopter set to -1.0 m <sup>-1</sup> ; diagonal angle of view approximately
	39° (horizontal angle of view approximately 32°)
	• Diopter adjustment: -5 to +3 m <sup>-1</sup>
160 11	• Eyepoint: Approximately 24 mm
LCD monitor	3.0-in/7.6 cm, 1840k-dot color LCD touch screen with 3-way
	tilt
Movies	• Movie size: 62K 16:9, 48 16:9, 17:9, 4K 16:9, DC 17:9,
(with stereo sound)	FID 16:9, FID 17:9
	• Frame rate: 59.94P, 50P, 29.97P, 25P, 24P, 23.98P
	• Recording/output format:
	- H.265 (10-bit MOV 4:2:2/4:2:0; 360, 200, 100, or 50 Mbps)
	- H.264 (8-bit MOV/MP4 4:2:0; 360, 200, 100, or 50Mbps)
	- HDMI output supported (RAW output supported with
	Atomos and Blackmagic Design external recorders; 8-bit 4:2:2/10-bit 4:2:2)
	4.2.2/ IU-NIL 4.2.2/