	Depth-of-field preview Proxy setting (ProRes only) 35mm format mode			Cooling fan settings	
		184			
\cup			$\overline{}$	Temperature warning	
			\sim	Control lock ³	
\sim	Flash (TTL) mode		\sim	Boost mode	
\sim	Flash compensation		\sim	Power supply	
(10)	Self-timer indicator	164	$\overline{}$	Histogram	
(11)	Continuous mode	117	\sim	Battery level	
(12)	Shutter type	170	(44)	Sensitivity	106
(13)	AF+MF indicator ²	157	(45)	Exposure compensation	109
14)	Bluetooth ON/OFF		46	Aperture	
(15)	Wireless connection		47)	Distance indicator ²	103
16)	Ethernet connection		48	Shutter speed	77, 78, 82
(17)	White balance	136	49	TTL lock	175, 389
(18)	AWB lock	362		AE lock	
19	Film simulation	130	(51)	Metering	108
20	F-Log/HLG recording	186	(52)	Shooting mode	76
(21)	Dynamic range	134	(53)	Focus mode ²	93
	D-range priority		(54)	Focus indicator ²	94
	Bluetooth host			Manual focus indicator ²	
24)	AirGlu BT connection	211	(56)	AF lock	111, 361
25)	Movie mode	68, 178	(57)	Shift amount/rotate amount	396
26)	High-speed recording indicate	or179	(58)	Time code	209
(27)	Recording time available/		\sim	Microphone input channel	
	elapsed recording time	68	60	Recording level ²	205
(28)	Card slot options		61)	Exposure indicator	82, 109
\sim	SSD connection status		$\overline{}$	Virtual horizon	
<u>30</u>	Number of available frames 1	460	\sim	Focus frame	
<u>(31)</u>	Image size	126	64)	Location data download status	373
\sim	File format			Frame.io connection status	
\sim	Image quality			Image transfer status	
$\overline{}$	HEIF format			FTP upload progress	
\simeq	Date and time		\sim	Frame.io upload progress	
\simeq	Touch screen mode	, ,	$\overline{}$	Remote recording function	

¹ Shows "9999" if there is space for over 9999 frames.

² Not displayed when **ON** is selected for **☑ SCREEN SET-UP** > **LARGE INDICATORS MODE(EVF)**.

³ Displayed when controls have been locked by pressing and holding the **MENU/OK** button. Control lock can be ended by pressing and holding the **MENU/OK** button again.