Input/output termina		tl	
	Ø3.5 mm mini-stereo jack		
Headphone jack socket	The USB connector can be converted to a headphone jack using the supplied headphone adapter		
Ramota ralazca connector	Ø3.5 mm 3-pole mini jack		
Digital input/output	USB connector (Type-C) USB3.2 Gen1x1		
HDMI output	HDMI Micro connector (type D)		
Power supply/other			
Power supply	NP-W126S rechargeable battery (supplied with camera)		
Battery life	Battery type: NP-W126S		
	• Lens: XF35mmF1.4 R		
	• External flash units: Disabled		
	Shooting mode: Mode P		
	Number of shots		
	PERFORMANCE	LCD	EVF
	BOOST	Approx. 270	Approx. 270
	NORMAL	Approx. 460	Approx. 430
	Total length of footage that can be recorded on		
		a single charge	C4'
		Actual battami life	Continuance
	Mode	Actual battery life	battery life of
	Mode 4K <sup>1</sup>	of movie capture Approx. 45 minutes	movie capture
	FHD <sup>2</sup>	11	Approx. 60 minutes
		Approx. 50 minutes	Approx. 75 minutes
	High annulations	Annual On minutes	
	High-speed movies <sup>3</sup>	Approx. 80 minutes	_
	High-speed movies <sup>3</sup> 1 At a frame rate of 29.9  2 At a frame rate of 59.9  3 At a frame rate of 120	7 fps. 4 fps.	-

and SD memory card.

Note: Battery endurance varies with battery charge level and the figures given above are not guaranteed. Battery endurance will decline at low temperatures.