Specifications

	·······
System	
Model	FUJIFILM GFX100 II
Product Number	FF230001
Effective pixels	Approx. 102 million
Image sensor	43.8 mm × 32.9 mm Bayer array with primary color filter
Storage media	Fujifilm-recommended SD/SDHC/SDXC and CFexpress Type B
	memory cards
Memory card slots	SD memory card slot (UHS-II compliant) ×1
	 CFexpress memory card slot (Type B) ×1
File system	Still pictures: Compliant with DCF 2.0
	• Compressed: Exif 2.32 JPEG-baseline compliant; DPOF compli-
	ant; HEIF compliant (4:2:2, 10-bit)
	• Uncompressed or compressed using a reversible or non-reversible
	algorithm: RAW (original RAF format; special-purpose software
	required); RAW+JPEG available; TIFF (RGB)
	 Movies: Compliant with HEVC/H.265, H.264, and ProRes
	 Audio (including voice memos):
	- LPCM (two channels: 24-bit, 48 kHz sampling)
	- AAC (MP4 recordings only)
	 Audio (via XLR microphone adapter):
	- LPCM (two channels: 24-bit, 48 kHz sampling; four chan-
	nels: 24-bit, 48 kHz sampling)
	 - AAC (MP4 recordings only; two channels: 16-bit, 48 kHz sampling)