Lecture 9
GitHub Features: Issues, Actions, Releases, and Protection

Tracking work, automating checks, protecting `main`, publishing versions

Learning goals

- Use Issues and closing keywords to connect a problem, its fix and its pull request.
- Read and write a small GitHub Actions workflow that runs your tests on every push.
- Explain what branch protection does and which rules matter most.
- Create tags and releases, and choose version numbers (semantic versioning).
- Know what GitHub Pages and the `.github` folder offer.

1 What GitHub adds to Git

In Lectures 6–8 you used GitHub as a place to store a repository and to host pull requests. GitHub offers much more around the repository. None of it changes how Git works; it is a layer of project-management and automation tools on top.




Figure 1: GitHub's features are built around your Git repository. This lecture covers all of the orange boxes except pull requests (Lecture 7).

2 Issues: tracking what needs doing

An **issue** is a numbered discussion about one thing: a bug, a question, an idea. Issues turn "someone should fix this" into a visible to-do list. Create one with **Issues** → **New issue**.

- A good **title** says what is wrong in one line: *Greeting prints "Helo" instead of "Hello".*
- A good **description** says how to see the problem, what you expected, and what happened.
- **Labels** classify (*bug*, *enhancement*, *good first issue*); **assignees** say who works on it; **milestones** group issues for a version.

Issues and pull requests share the numbering: `#12` anywhere in a comment or description becomes a link to issue or pull request number 12, and `@name` notifies a person. Descriptions are written in Markdown, so a task list works as a checklist:

```
- [x] reproduce the bug
- [ ] write a fix
- [ ] add a test
```

2.1 Closing issues automatically

When a pull request fixes an issue, you do not have to close the issue by hand. Put a **closing keyword** followed by the issue number in the pull request's description (or in a commit message):

```
Fix greeting typo

Closes #12
```

The keywords are *close(s/d)*, *fix(es/ed)* and *resolve(s/d)*, in any capitalisation. The issue is closed **when the change is merged into the default branch** (usually `main`; the pull request must target it), not when the pull request is opened. Before that, the issue page shows the pull request as linked.




Figure 2: Issue to fix to closed issue. Orange steps happen on the website, blue steps are the Git commands you know.

2.2 Templates and the `.github` folder

GitHub looks in a folder called `.github` in your repository for helper files. Two are very useful for teamwork:

- `.github/ISSUE_TEMPLATE/bug_report.md`: pre-fills the form when someone opens an issue.
- `.github/pull_request_template.md`: pre-fills every pull request description.

A template for bug reports starts with a block of settings between lines of three dashes, called *front matter*, followed by Markdown:

```
---
name: Bug report
about: Something does not work
---

## What happened?

## What did you expect?
```

and a pull-request template is plain Markdown, for example:

```
## What does this change?

## Checklist
- [ ] The tests pass
```

```
- [ ] I read my own diff
```

These files are ordinary files: you commit and push them like any other, and they take effect on the default branch.

3 GitHub Actions: letting a robot run your tests

Continuous integration (CI) means: every time someone pushes, a machine automatically builds and tests the project, and reports the result next to the commit. Nobody forgets to run the tests, and a broken change is caught before it is merged. On GitHub this is done by **Actions**.

You describe what to run in a **workflow file**: a text file in the folder `.github/workflows/`, written in **YAML**. Four rules are enough to read it:

```
fruit: apple          # key: value  (# starts a comment)
box:                  # a key whose value is the indented lines below it
  size: large         #   (indent with spaces, never tabs)
  items:
    - pen             # a list: one item per line, each starting with "- "
    - cup
  tags: [a, b]        # the same kind of list, written on one line
empty:                # a key with nothing after it: "all", "default" or "yes"
```

Our project has a test script `test.sh`: it runs `greet.sh`, compares the output with `Hello, world`, and ends with `exit 1` (the signal for "failure") if they differ. This workflow runs it on GitHub:

```
name: CI
on:
  push:
    branches: [main]
  pull_request:
jobs:
  test:
    runs-on: ubuntu-latest
    steps:
      - uses: actions/checkout@v4
      - name: Run the tests
        run: bash test.sh
```

Line by line:

Line	Meaning
`name: CI`	The workflow's name, shown in the Actions tab. (The `name:` inside a step names that step.)
`on:`	*When* to run (the events):
`push: branches: [main]`	. . . whenever someone pushes to `main`,
`pull_request:`	. . . and for every pull request (the empty value means "all of them").
`jobs: / test:`	A job called `test`. A workflow can have several; they run in parallel.
`runs-on: ubuntu-latest`	The kind of computer GitHub lends you: a *virtual machine*, a computer simulated inside GitHub's servers, created fresh for each run and thrown away afterwards, with Linux installed.
`steps:`	The job's steps, run in order. A line starting with `-` begins a step.
`uses: actions/checkout@v4`	Use a ready-made, reusable step called an *action* (here: the repository `checkout` of the organisation `actions`). It downloads your repository into the machine; *without it the machine has no files*.
`run: bash test.sh`	Run a command, exactly as in your terminal. If the command reports failure (like `test.sh` with its `exit 1`), the step and the job fail.




Figure 3: What happens on a push: the event starts the workflow, a fresh virtual machine runs the steps, and the result appears on the commit and the pull request.

Using it. Commit the file `.github/workflows/ci.yml` and push. Open the **Actions** tab of your repository: the run appears, yellow while it works, then a green tick or a red cross. Click it to read the log of every step. On a pull request the same result is shown next to the merge button as a *check*. (A **status check** is this pass/fail result that a workflow reports on a commit or pull request.) If a step fails, read its log, fix the problem, and push again: the workflow runs again.

Pitfall

YAML is picky. Use spaces, never tabs. Keep the indentation exactly as shown: a step moved by one space changes its meaning. A broken file does not run at all; the Actions tab then shows an error with the line number.

Quick fact

Actions are free for public repositories; private repositories get a limited monthly allowance of free minutes. The version after `@` pins the action's major version. `v4` is just an example: newer major versions appear over time, and GitHub's documentation lists the current one (use it in your own projects). Never write passwords into a workflow file; secrets go under Settings → Secrets and variables → Actions and are used as `${{ secrets.NAME }}`.

4 Branch protection: guarding `main`

In Lecture 8 you learned that rewriting a shared branch is dangerous, and in Lecture 7 that changes should be reviewed. **Branch protection** makes GitHub enforce this. In the repository's **Settings**

(under *Branches*, or *Rules*) you can add a rule for `main`. The most useful options:

Option	Effect
Require a pull request before merging	Nobody can push straight to `main`; changes arrive through reviewed pull requests.
Require approvals	A pull request needs at least n approvals before the merge button works.
Require status checks to pass	The CI workflow must be green. A red cross blocks the merge.
Block force pushes	`git push --force` (even with a lease) is refused on `main`.
Restrict deletions	The branch cannot be deleted.

(You cannot approve your own pull request, so "Require approvals" on a one-person repository would lock you out; leave it off when you practise alone.) Together they give the team's central rule: *nothing reaches `main` unless it was reviewed and the tests pass.* (Branch protection is available for public repositories on every plan; for private repositories it depends on your plan.)

5 Tags and releases: naming a version

A branch label moves every time you commit. Sometimes you need a label that *stays put*: "this exact commit is version 1.0.0". That is a **tag**.




Figure 4: Tags mark specific commits. After more commits, `main` has moved on, but `v1.0.0` still names the same commit.

There are two kinds. A **lightweight** tag is just a name for a commit. An **annotated** tag is a small object of its own that also stores who made it, when, and a message; use annotated tags for releases.

```
$ git tag v0.1.0 3ff4272              # lightweight, on a given commit
$ git tag -a v1.0.0 -m "First release"    # annotated, on the current commit
$ git tag -n                          # list tags with their messages
v0.1.0          Add README
v1.0.0          First release
$ git show v1.0.0
tag v1.0.0
Tagger: Practice User <practice@example.com>
Date:   (the day you made the tag)

First release

commit <40-character ID>
...
```

Tags are not pushed automatically. Send them explicitly:

```
$ git push origin v0.1.0 v1.0.0        # or: git push origin --tags   (all tags)
 * [new tag]         v0.1.0 -> v0.1.0
 * [new tag]         v1.0.0 -> v1.0.0
```

Two more commands you may meet: `git tag -d v1.0.0` deletes a local tag, and `git describe --tags` tells you how far the current commit is from the nearest tag (for example `v1.0.0-1-g00585aa`: one commit after `v1.0.0`). Checking out a tag gives a detached `HEAD` (Lecture 4): fine for looking, not for committing.

5.1 Version numbers

Most projects use **semantic versioning**: `MAJOR.MINOR.PATCH`.

You made	Bump	From `1.0.0` to
a bug fix, nothing else changes	PATCH	`1.0.1`
a new feature that does not break anything	MINOR	`1.1.0`
a change that breaks how people use it	MAJOR	`2.0.0`

(When a higher number goes up, the lower ones reset to 0: after `1.1.5` a breaking change gives `2.0.0`. Versions `0.x.y` mean "still unstable".) A **release** is GitHub's page for a tag. Under **Releases** → **Draft a new release** you choose a tag, write a title and notes (the button *Generate release notes* lists the merged pull requests for you), optionally attach files, and press *Publish release*. GitHub automatically adds downloadable ZIP and tar archives of the source code at that tag.

6 Also worth knowing

GitHub Pages publishes files from your repository as a free website (Settings → Pages, deploy from a branch such as `main`; the site appears at `https://YOURNAME.github.io/REPOSITORY/`). A repository others can use usually has a `README.md`, a `LICENSE` (without one, the default is "all rights reserved"), the `.gitignore` of Lecture 2, and for teamwork a `CONTRIBUTING.md`.

Pitfall

Security basics. Use two-factor authentication (Lecture 6). Never commit passwords, keys or tokens (Lecture 2): history keeps them. *Dependabot* (Settings → Code security) can warn you about vulnerable libraries once your project has dependencies.

7 Homework 9

Homework 9: Issues, CI, and a release

Part A: practise with a "server" folder (no internet needed). The setup script creates `practice/hw9_server.git`, a repository that plays the role of GitHub, holding a tiny project whose test fails because of a typo. From the course folder:

```
$ bash codeHints/L09/setup_hw9.sh
$ cd practice
```

Do the tasks in order. To start over: `setup_hw9.sh --reset` from the course folder.

9.1 Clone

Clone the server into `hw9` and go in. Set your name and email (`git config user.name` ...) if they are not set globally.

9.2 See the failure

Run `bash test.sh`. It prints `FAIL`: this is what CI would show as a red cross.

9.3 Fix it
Correct the typo in `greet.sh` so that `bash test.sh` prints `PASS`.

9.4 Closing keyword
Commit the fix with a message that has the subject `Fix greeting typo` and a second paragraph `Closes #1`: `git commit -m "Fix greeting typo" -m "Closes #1"`. (Part B explains why this keyword matters, and a trap it sets.)

9.5 The workflow
Create `.github/workflows/ci.yml` (use the example of this lecture: it checks out the code and runs `bash test.sh`, on pushes to `main` and on pull requests). Spaces only, no tabs. Commit it as `Add CI workflow`. (Part A can only check the file's *words*; wrong indentation is caught by GitHub in Part B.)

9.6 Templates
Create `.github/ISSUE_TEMPLATE/bug_report.md` (front matter with `name:` and `about:`, then at least one `##` heading) and `.github/pull_request_template.md` (with a checklist line `- [ ] ...`). Commit them as `Add templates`.

9.7 Tags
Create the *lightweight* tag `v0.1.0` on the very first commit (`git rev-list --max-parents=0 HEAD` prints its ID) and the *annotated* tag `v1.0.0` (message `First release`) on your newest commit. Push everything: `git push origin main v0.1.0 v1.0.0`.

9.8 Questions
In `practice/hw9_answers.txt` (next to `hw9`; create it with `printf` or `echo`) write `next-bugfix=<version>` (the next version number after fixing another bug in `1.0.0`) and `issue-closes-when=<opened or merged>` (when does `Closes #12` close issue 12?).

Part B: the real thing on GitHub (optional, but strongly recommended: Part A never runs a real CI). You need your GitHub account and SSH key (Lecture 6).

9.9 Publish and watch CI
On GitHub create a new *Public* repository `ci-practice` with *nothing* ticked (no README, no `.gitignore`, no licence). **Do not create any issue yet.** In `practice/hw9` run `git remote add github git@github.com:YOURNAME/ci-practice.git` (the SSH address) and `git push github main v0.1.0 v1.0.0`. Open the **Actions** tab: your workflow ran. Add the line `repo=<you>/ci-practice` to `hw9_answers.txt`.

9.10 Issue to pull request to closed issue
Now (after the push) create Issue #1 (use the bug template; title: *Add a note to the README*). In `hw9` create a branch `readme-note`, add a line to `README.md`, commit, and `git push github readme-note`. Open a pull request into `main` with the description `Closes #1`; wait for the green check; merge it. Issue #1 should close by itself. Add `issue=1` to the answers file. Why the order matters: the commit from 9.4 already contains `Closes #1` and was pushed in 9.9. Had issue #1 existed at that moment, GitHub would have closed it immediately and your pull request would close nothing.

9.11 Release
On GitHub open **Releases** → **Draft a new release**, choose the tag `v1.0.0`, press *Generate release notes*, and publish.

9.12 Wait for green
After you merge, GitHub starts a new workflow run on `main`. Wait until the Actions tab shows it green *before* you run the checker.

9.13 Explore (not checked)
In Settings → Branches (or Rules) add a rule for `main` that requires a pull request and the

check `test`, then try to push to `main` directly and see GitHub refuse.

Check yourself: from the course folder run `bash codeHints/L09/check_hw9.sh`. Part A needs no network. Part B is checked if `hw9_answers.txt` contains `repo=`; the checker reads your public repository through GitHub's public interface (your issue, release and latest Actions run) and says so if it cannot reach GitHub. Then compare with the solutions at the end of this lecture.

8 Summary

- Issues track work; `Closes #12` in a pull request closes the issue when the change reaches `main`. Templates live in `.github/`.
- Actions run a YAML workflow from `.github/workflows/` on each push or pull request: `on`, `jobs`, `runs-on`, `steps`, `uses`, `run`. Green tick or red cross.
- Branch protection (pull request, approvals, passing checks, no force push) enforces the team's rules on `main`.
- Tags name fixed commits (annotated for releases; push them explicitly); releases are GitHub pages for tags; version as `MAJOR.MINOR.PATCH`. Pages publishes a free website. (Further reading: GitHub Docs, "About issues", "Understanding GitHub Actions"; *Pro Git*, Chapter 2.6.)

Solutions

Stop here if you have not tried the homework yet.
Attempt every task first, run the checker, and only then read on.

Solutions to Homework 9

Part A.

```
$ bash codeHints/L09/setup_hw9.sh
$ cd practice
$ git clone hw9_server.git hw9
$ cd hw9
$ bash test.sh
FAIL: got 'Helo, world'
$ sed -i.bak 's/Helo/Hello/' greet.sh && rm greet.sh.bak    # or edit by hand
$ bash test.sh
PASS
$ git commit -am "Fix greeting typo" -m "Closes #1"
$ mkdir -p .github/workflows .github/ISSUE_TEMPLATE
```

Create `.github/workflows/ci.yml` (spaces only):

```
name: CI
on:
  push:
    branches: [main]
  pull_request:
jobs:
  test:
    runs-on: ubuntu-latest
    steps:
      - uses: actions/checkout@v4
      - name: Run the tests
        run: bash test.sh
```

Create `.github/ISSUE_TEMPLATE/bug_report.md` and `.github/pull_request_template.md`:

```
---
name: Bug report
about: Something does not work
---

## What happened?

## What did you expect?
```

```
## What does this change?

## Checklist
- [ ] The tests pass
- [ ] I read my own diff
```

```
$ git add .github/workflows
$ git commit -m "Add CI workflow"
$ git add .github/ISSUE_TEMPLATE .github/pull_request_template.md
```

```
$ git commit -m "Add templates"
$ git tag v0.1.0 $(git rev-list --max-parents=0 HEAD)
$ git tag -a v1.0.0 -m "First release"
$ git push origin main v0.1.0 v1.0.0
$ printf 'next-bugfix=1.0.1\nissue-closes-when=merged\n' > ../hw9_answers.txt
```

(Part A checks only the workflow's words; GitHub reports wrong indentation in Part B.)

9.3–9.4. The checker runs your `test.sh` on a copy of the server's `main`, as the workflow does on GitHub. The second `-m` is a separate paragraph of the message; GitHub finds the keyword anywhere in it.

9.5. Without `uses: actions/checkout` the machine has no files, so `bash test.sh` fails. The folder is `.github/workflows` (with an *s*).

9.7. The annotated tag has its own object with your message (`git show v1.0.0` shows a *Tagger*). Tags are pushed only when you name them or use `--tags`.

9.8. Fixing a bug in `1.0.0` gives the patch version `1.0.1`. `Closes #12` closes the issue when the change is *merged* into the default branch, not when the pull request is opened.

Part B.

```
(GitHub) New repository: ci-practice, Public, no README
$ git remote add github git@github.com:YOURNAME/ci-practice.git      # the SSH address
$ git push github main v0.1.0 v1.0.0
(GitHub) Actions tab: the "CI" workflow ran: green tick
$ printf 'repo=YOURNAME/ci-practice\n' >> ../hw9_answers.txt
(GitHub) Issues > New issue "Add a note to the README"  -> number 1
$ git switch -c readme-note
$ echo "Notes coming soon." >> README.md
$ git commit -am "Add a note to the README"
$ git push github readme-note
(GitHub) Open the pull request, description "Closes #1"; wait for the green check;
    Merge
(GitHub) Issue #1 is now closed
$ printf 'issue=1\n' >> ../hw9_answers.txt
(GitHub) Releases > Draft a new release > tag v1.0.0 > Generate release notes > Publish
(GitHub) Actions: wait until the new run on main (after the merge) is green, then run
    the checker
```

Replace `YOURNAME` with your GitHub user name. The checker needs the answers file to contain `repo=`, `issue=`, and a remote of `practice/hw9` that points at that repository. It then asks GitHub's public interface whether the issue is closed, whether a release exists for `v1.0.0`, and whether the latest Actions run on `main` succeeded. If the last check is red, open the run's log in the Actions tab.

Common mistakes.

- A *tab* in the workflow, or a folder `.github/workflow` instead of `workflows`.
- Creating Issue #1 *before* the first push: the commit message `Closes #1` then closes it at once, and the pull request closes nothing. Push first, then create the issue.
- Forgetting to push the tags: `git push origin main` sends no tags.
- Creating the repository with a README: the first push is rejected. Create it empty.
- A private repository: the checker cannot see it and reports "cannot find".
- Running the checker while the workflow run on `main` is still in progress: the check "latest run is green" fails until it finishes. Wait and run it again.