

Ex No 9**Implement clustering techniques – Hierarchical and K-Means****AIM:**

To Implement clustering techniques – Hierarchical and K-Means using R.

PROCEDURE:

- Collect and load the dataset from sources like CSV files or databases.
- Clean and preprocess the data, including handling missing values and scaling features.
- Determine the number of clusters (K) for K-Means, or decide on the stopping criterion for Hierarchical Clustering.
- Choose the appropriate clustering algorithm: K-Means for partitioning, Hierarchical for nested clustering.
- Apply the K-Means algorithm using `fit_predict` to assign data points to clusters.
- Apply the Hierarchical Clustering algorithm using Agglomerative Clustering for hierarchical clusters.
- Visualize the clusters with scatter plots for K-Means, and dendrograms for Hierarchical Clustering.
- Evaluate clustering performance using metrics like silhouette score or inertia (for KMeans).
- Fine-tune the clustering by adjusting the number of clusters or linkage criteria.
- Interpret the results to understand the structure and relationships within the data.

CODE:**Hierarchical Clustering.R:**

```
# Load the iris dataset data(iris)
```

```
# Use only the numeric columns for clustering (exclude the Species column) iris_data
<- iris[, -5] # Standardize the data iris_scaled <- scale(iris_data)

# Compute the distance matrix distance_matrix <- dist(iris_scaled,
method = "euclidean")

# Perform hierarchical clustering using the "complete" linkage method hc_complete
<- hclust(distance_matrix, method = "complete")

# Plot the dendrogram plot(hc_complete, main = "Hierarchical Clustering Dendrogram",
xlab = "", sub = "", cex =
0.6)

# Cut the tree to form 3 clusters clusters
<- cutree(hc_complete, k = 3) # Print the
cluster memberships print(clusters)

# Add the clusters to the original dataset iris$Cluster
<- as.factor(clusters)

# Display the first few rows of the updated dataset head(iris)
```

K-Means Clustering.R:


```
# Load the iris dataset data(iris)

# Use only the numeric columns for clustering (exclude the Species column) iris_data
<- iris[, -5] # Standardize the data iris_scaled <- scale(iris_data) #
Set the number of clusters set.seed(123) # For reproducibility k <- 3 # Number
of clusters # Perform K-Means clustering kmeans_result <-
kmeans(iris_scaled, centers = k, nstart = 25)
```

```
# Print the K-Means result  
print(kmeans_result) # Print the  
cluster centers  
print(kmeans_result$centers) #  
Add the cluster assignments to  
the original dataset iris$Cluster  
<-  
as.factor(kmeans_result$cluster  
) # Display the first few rows  
of the updated dataset  
head(iris) # Plot the clusters  
library(ggplot2) ggplot(iris,  
aes(x = Sepal.Length, y =  
Sepal.Width, color = Cluster))  
+ geom_point(size  
= 3) + labs(title = "K-Means Clustering of Iris Dataset", x = "Sepal Length", y = "Sepal  
Width")
```

OUTPUT:

Hierarchical Clustering:



RESULT:

Thus, to implement clustering techniques – Hierarchical and K-Means using R has been successfully executed.