BSc (Hons) in **Information Technology Specialized in AI**

Faculty of Computing

IT3012 : Intelligent Agents

Year 3 · Semester 1 · 2026 Semester 2

Practical 04

> **Module Objective:** In previous weeks, your Drow Ranger agent used A* Search to find a physical path to the goal. However, it blindly assumed every non-wall tile was safe. Today, we implement a **Knowledge Base (KB)** and a **Forward Chaining Inference Engine**. Your agent must now mathematically prove a cell is logically *Feasible* before taking a step, using real-time rules about map vision and enemy threats.

Part 1: The Logic Engine Architecture

Step 1.1: Building the Knowledge Base (KB)

> Instead of hardcoding hundreds of nested `if-else` statements in our agent's movement logic, we will build a declarative Knowledge Base. You need to design a Python class that stores **Facts** (current percepts) and **Rules** (Horn Clauses).

1. Create a new file named `logic_engine.py` .
2. Implement a `KnowledgeBase` class based on the following structural requirements:

```
CLASS KnowledgeBase:
    // Attributes
    DECLARE facts AS Set                    // To store unique string fact
    DECLARE rules AS List                   // To store rules as Tuples: (

    // Methods
    FUNCTION tell_fact(fact_string):
        ADD fact_string TO facts

    FUNCTION tell_rule(premise_list, conclusion_string):
        APPEND Tuple(premise_list, conclusion_string) TO rules
```

```
FUNCTION clear_facts():
    EMPTY the facts Set
```

Part 2: Implementing Forward Chaining

Step 2.1: The Inference Algorithm

> The agent needs an Inference Engine to deduce new information from its raw sensors. Translate the following Data-Driven **Forward Chaining** algorithm into a Python method inside your `KnowledgeBase` class.

1. Write the `forward_chain()` method.
2. Ensure you use a `while` loop that continues to iterate over the rules until a full pass results in absolutely no new facts being deduced.

```
FUNCTION forward_chain():
   DECLARE new_facts_added = TRUE

   WHILE new_facts_added == TRUE:
       new_facts_added = FALSE

       FOR EACH (premises, conclusion) IN rules:
           IF conclusion IS NOT IN facts:

               // Modus Ponens Check
               IF ALL premises ARE IN facts:
                   ADD conclusion TO facts
                   new_facts_added = TRUE
```

Part 3: Hooking Logic into the Grid Game

Step 3.1: Defining the Game Constraints

> Now we translate the game's safety constraints into our logic engine using Propositional Logic.

1. In your main `agent.py`, instantiate the KB in the `__init__` method: `self.kb = KnowledgeBase()`.
2. Use your `tell_rule` method to define the following safety rules:
   Rule 1: `TargetVisible ∧ HasDust ⇒ SafeToEngage`
   Rule 2: `SafeToEngage ∧ BloodseekerMissing ⇒ Retreat`

Step 3.2: Validating Feasibility in A*

> Modify your existing A* pathfinding algorithm to consult the Knowledge Base before expanding a node.

1. Locate the neighbor-generation loop in your A* code (where you normally check for physical walls).
2. Before adding a neighbor to the `open_list`, clear the KB facts.
3. Feed the current percepts for that specific tile into the KB using `tell_fact()`.
4. Run `self.kb.forward_chain()`.
5. If `'Retreat'` is deduced and exists in `self.kb.facts`, mark the tile as **Infeasible**. Skip it (do not add it to the open list), even if it is physically reachable.

Part 4: Self-Evaluation Test Cases

4.1 Automated Validation

Create a file named `test_logic.py`. Copy and run the following Python assert statements to verify your Forward Chaining engine works correctly mathematically before you attempt to integrate it into the visual grid.

```
 from logic_engine import KnowledgeBase

def test_forward_chaining():
    kb = KnowledgeBase()

    # Add Domain Rules
    kb.tell_rule(['TargetVisible', 'HasDust'], 'SafeToEngage')
    kb.tell_rule(['SafeToEngage', 'BloodseekerMissing'], 'Retreat')

    # Test Case 1: Safe Engagement
    kb.clear_facts()
    kb.tell_fact('TargetVisible')
    kb.tell_fact('HasDust')
    kb.forward_chain()
    assert 'SafeToEngage' in kb.facts, "Test 1 Failed: Should deduce Sa
    assert 'Retreat' not in kb.facts, "Test 1 Failed: Should NOT deduce

    # Test Case 2: Unsafe Engagement (Bloodseeker Missing)
    kb.clear_facts()
    kb.tell_fact('TargetVisible')
    kb.tell_fact('HasDust')
    kb.tell_fact('BloodseekerMissing')
    kb.forward_chain()
    assert 'Retreat' in kb.facts, "Test 2 Failed: Should deduce Retreat

    print("✅ All Logic Engine Test Cases Passed!")

if __name__ == "__main__":
    test_forward_chaining()
```

Part 5: Theory-to-Implementation Mapping

> Based on the code you just wrote and the lecture on Logical Reasoning, complete the following analytical questions to explain *how* your code implements the theory.

1. Reachability vs. Feasibility (Apply)

In Step 3.2, you modified the A* algorithm's neighbor-generation loop. How does your

new code differentiate between checking if a node is "Reachable" (like a wall collision) versus checking if it is "Feasible"? Explain how the Knowledge Base enforces feasibility.

1. Reachability vs. Feasibility

Reachability checks whether a tile can physically be entered. The A* algorithm verifies that the tile is inside the grid and is not a wall.

Feasibility checks whether entering the tile is logically safe. Before adding a reachable neighbor to the open list, the agent clears the Knowledge Base, adds the tile's percepts as facts, and runs forward chaining. If the fact `Retreat` is deduced, the tile is considered infeasible and is skipped. Therefore, a tile can be physically reachable but logically infeasible.

2. Declarative vs. Procedural Paradigms (Analyze)

Why did we build a `KnowledgeBase` class with a `forward_chain()` loop instead of simply writing `if 'TargetVisible' in percepts and 'HasDust' in percepts:` directly inside the agent's movement code? What happens to the agent's code complexity if we add 50 new game rules?

2. Declarative vs. Procedural Paradigms

We use a `KnowledgeBase` because it stores facts and rules separately from the agent's movement code. The `forward_chain()` method applies the rules automatically to derive new facts.

If 50 new game rules are added, we only need to add those rules to the Knowledge Base. The movement code does not need 50 additional `if-else` statements, so the program remains easier to maintain and extend.

3. Modus Ponens & Horn Clauses (Understand)

The rule `['TargetVisible', 'HasDust'] ⇒ 'SafeToEngage'` is formally known as a Horn Clause. Briefly explain how your Python implementation of the `forward_chain()` `while` loop acts as a mathematical execution of the *Modus Ponens* inference rule.

3. Modus Ponens and Horn Clauses

The rule `TargetVisible ∧ HasDust ⇒ SafeToEngage` is a Horn Clause. The `forward_chain()` method checks whether all the premises of a rule are present in the Knowledge Base.

When `TargetVisible` and `HasDust` are facts, the method adds `SafeToEngage` as a new fact. This represents Modus Ponens: if the premises are true and they imply a conclusion, then the conclusion can be inferred. The loop continues until no new facts can be added.

Finalize and Lock Lab 05 Implementation

✅ **Lab 05 Theory-to-Implementation Mapping completed!**

FACULTY OF COMPUTING