BSc (Hons) in **Information Technology Specialized in AI**

Faculty of Computing

IT3012 : Intelligent Agents

Year 3 · Semester 1 · 2026 Semester 2

Practical 03

> **Objective & Lecture Mapping:** In previous labs, we built a Simple Reflex Agent that moved randomly or reacted only to immediate adjacent cells. Today, we transition to a **Goal-Based/Planning Agent**. You will expose the environment's state space to the agent, allowing it to use **Breadth-First Search (BFS)**, **Depth-First Search (DFS)**, and **Uniform-Cost Search (UCS)** to simulate and find paths to the food before taking a physical action.

Part 1: Practical Implementation — Building the Search Agent

Step 1.1: Exposing the World Model

> Classical search algorithms require an abstract model of the environment to simulate future states. Currently, your agent is "blind" to the overall map.

1. Create a new Branch called Week_03 in your Forked Github Repo and work on the below Questions.
2. Open `visual_grid_game.py` .
3. Locate the `get_percept(self)` method.
4. Add three new keys to the dictionary to pass the global state to the agent:

```
'grid_size': (self.width, self.height)
'walls': list(self.walls)
'all_food': list(self.food_positions)
```

Step 1.2: Implementing BFS, DFS, and UCS

> You will implement three distinct uninformed search strategies. The core node expansion structure is identical; only the data structure for the **Frontier** changes!

1. Open `agent.py` and create a new class called `SearchAgent`.
2. Import required structures: `from collections import deque` and `import heapq`.
3. **BFS:** Create `def bfs_search(...)`. Use a FIFO queue (`deque.popleft()`). This explores the shallowest nodes first.
4. **DFS:** Create `def dfs_search(...)`. Use a LIFO stack (`list.pop()`). This explores the deepest nodes first.
5. **UCS:** Create `def ucs_search(...)`. Use a Priority Queue (`heapq.heappop()`) ordered by the total path cost $g(n)$.
6. For all three algorithms, you must maintain a `reached` set (or visited array) to track explored states. This converts your algorithm from a *Tree Search* to a *Graph Search*, preventing infinite loops.

Step 1.3: Executing and Comparing Offline Plans

> The agent must now form a complete plan and execute it step-by-step.

1. In your `SearchAgent.__init__`, add an empty list: `self.plan = []` and a config string `self.active_algo = 'BFS'`.
2. In `sense_and_act(self, percept)`, check if `self.plan` is empty.
3. If empty, find the closest food pellet from `percept['all_food']`, execute the search method matching `self.active_algo`, and store the resulting sequence of actions in `self.plan`.
4. Return the first action from the plan using `return self.plan.pop(0)`.
5. **Observation Task:** Change `self.active_algo` between 'BFS', 'DFS', and 'UCS' and run the simulation. Watch how DFS takes erratic, winding paths, while BFS and UCS take direct, optimal paths!

Part 2: Theoretical Evaluation

> Based on your implementation and Lecture 04, complete the following analytical questions.

1. (Remember) You built your search logic based on the environment coordinates. What is the fundamental difference between the "State Space" and the "Search Tree"?

"State Space" is like the real map or all the possible places the agent can be in the game. Its like valid X and Y points of grid.

"Search Tree" is the paths agent build in it's memory while it is trying to find food. A single place on grid can show up many times in search tree ,if there are different paths to get to it.

2. (Understand) In Step 1.2, you were instructed to use a `reached` set. In graph search theory, what specific problem does this set solve, and what would happen to your DFS agent without it?

the "reached" set is list of places the agent already visited, so agent knows not to visit again same place again.

without the "reached" set , a DFS agent would easily get stuck in an infinite loop, as a example it might move left and then right ,then left forever. It would eventually crash the program and never find the food.

3. (Analyze) Compare the visual paths generated by BFS and DFS in your simulation. Why is BFS guaranteed to be optimal in this specific grid, whereas DFS produces winding, suboptimal routes?

"BFS" searches the grid step by step, spreading onwards in all directions. IT checks everything 1 step away ,then 2 step away. Because every move in our grid cost exactly 1 point ,BFS will always find the shortest path first.

"DFS" ,just picks the direction and keep going as deep as possible until it hits the wall, then it turns around. It stops as soon as it bumps into the food. the path it takes is usually very winding, long, and not the best one.

4. (Evaluate) If we scaled `visual_grid_game.py` up to a massive 1000x1000 grid, BFS and UCS might crash before finding food. According to the time and space complexity formulas from the lecture, contrast the memory bottlenecks of BFS versus DFS.

If the grid is huge ,"BFS" has to remember massive expanding circle of nodes all at once(exponential space complexity) .This takes up more memory and it will

likely to crash computer before it finds the food.

"DFS" only needs to remember single path it is currently walking down, plus a backup choice (linear space complexity) . This means DFS uses way less memory and won't crash on big grids as like BFS, even though the path it finds won't be optimal

Once Completed Get a PDF of the completed File and Push into the Week 03 brach in the Github Project

Finalize and Lock Lab 03 Documentation

Incomplete: 0/11 questions answered. Please provide detailed responses for all questions.

FACULTY OF COMPUTING