```
import java.util.Scanner;

public class IT26102666Lab3Q3 {
public static void main(String[] args) {
Scanner input = new Scanner(System.in);

System.out.print("Enter the Rupee amount: ");
int amount = input.nextInt();

int n5000 = amount / 5000;
amount = amount % 5000;

int n1000 = amount / 1000;
amount = amount % 1000;

int n500 = amount / 500;
amount = amount % 500;

int n200 = amount / 200;
amount = amount % 200;

int n100 = amount / 100;
amount = amount % 100;

int n50 = amount / 50;
amount = amount % 50;

int n20 = amount / 20;
amount = amount % 20;

int c10 = amount / 10;
amount = amount % 10;

int c5 = amount / 5;
amount = amount % 5;

int c2 = amount / 2;
amount = amount % 2;
```

```
int c1 = amount;

System.out.println();
System.out.println("5000 Notes - " + n5000);
System.out.println("1000 Notes - " + n1000);
System.out.println("500 Notes - " + n500);
System.out.println("200 Notes - " + n200);
System.out.println("100 Notes - " + n100);
System.out.println("50 Notes - " + n50);
System.out.println("20 Notes - " + n20);
System.out.println("10 Coins - " + c10);
System.out.println("05 Coins - " + c5);
System.out.println("02 Coins - " + c2);
System.out.println("01 Coins - " + c1);
}
}
```