Tosks

Testing / test cases


Dummy Frame work

get\_prediction function

update\_predictor function

Data structures / access functions

Choice predictor functions - Rob



get-prediction reads values in these arrays, and decides prediction update-predictor checks branch outcome, and sends result to the appropriate array

Local Prediction Access Functions

Int read\_local\_prediction (wint branch-addr)

// branch addr · branch instruction address (value of PC)

```
int read_local_prediction (uint branch-addr)
       //branch_addr: branch instruction address (value of PC)
      // returns counter value at index for branch
  void update_local_prediction (vint branch_addr, bool taken)
// branch_addr: branch instruction address (value of PC)
// taken: True if branch was actually taken
// increment/decrement/saturate counter
Global Prediction Access Functions
    int read_global_prediction()
  void update global prediction (uint path)
// path: path history bits
      1/ This function vill use Path History to determine how to update
Choice Prediction Access Functions
    int read_choice_prediction (wint branch_addr)
   Void update choice prediction (wint branch addr bool local)

// local: true if local predictor was right and global

// predictor was wrong
Path History Access Functions
    Void update_path_history (bool taken)

// taken: true if branch was actually taken

// Update value of Path History bits (shift in taken)

// Update choice prediction at this index by calling

// update_choice_prediction()
Top-level Functions
     get_prediction() would call read_xxxx_prediction() fris
```

get\_prediction() would call read\_xxxx\_prediction() fris // reeds to determine whether to use global or local // by calling read\_choice\_prediction() then interpret // prediction counter value and return prediction update\_predictor() would call update\_xxxx-prediction() fris // needs to update Path History 11 Then, needs to update local history