

# Tomasulo-Softcore Library

Yihao Liu & Stephen Longofono

November 7, 2018

## Introduction

This document outlines the Tomasulo-Softcore library, a Python library written to model a single-core software CPU based on Tomasulo's Algorithm. The source code is presented as an open-source library, and is available on Github.com under the MIT license. This library was developed as an academic exercise for the graduate-level computer architecture course at the University of Pittsburgh in Pennsylvania, U.S.A.

The library demonstrates all of the major facets of the algorithm, including register renaming, out-of-order execution, memory disambiguation, speculative execution.

Please reference the Github repository for the most up-to-date code, instructions, and test cases. The repository is hosted at:

<https://www.github.com/SLongofono/Tomasulo-Softcore.git/>

## 1 Building & Execution

### 1.1 System Requirements

The library was developed for Python 3.6+. No external libraries were used to develop the core library. The project was developed and tested in a Linux environment, in a directory with write and execute privileges. Note that the output files will be placed in the same directory as the input files passed in; in order to correctly generate an output file, the user must have write privileges to the directory with the input files.

Included in the repository is a shell script used to generate UML diagrams from the class hierarchy. If you choose to modify or extend the library, the script can be run again from the root directory of the repository to generate fresh images of the UML class diagrams. Running this script requires Pylint 2.2.1+, but is not otherwise necessary for the use of the core library.

### 1.2 Build Instructions

There are no build instructions for the library, as it is a standalone Python module. The entry point to execution is Tomasulo.py. To start the library and print usage instructions, simply invoke your Python interpreter with Tomasulo.py as an argument from the command line.

### 1.3 Running Test Inputs

All test inputs are passed as command line arguments. The test inputs all follow a rigid and ordered format, as demonstrated by the file "example\_input.txt" in the "testCases/" directory of the repository root. For convenience, all of our test cases are located in this "testCases/" directory. To execute the library on a test input file, type:

```
<Python3.6> Tomasulo.py <filepath>
```

where Python3.6 is the CLI invoker for your Python 3 interpreter, and filepath is the absolute filepath of the desired test input.

## 1.4 Defining System Inputs

The system inputs follow a rigid and specifically ordered format. All inputs should be UTF-8 compliant, printable text format files. The specifications are presented in order below:

- The first line of the file is ignored. In our sample inputs, the first line is used to label the table columns that the following 4 lines compose.
- The next four lines begin with a label, followed by a space, and then 4 entries of either a natural number or a space (only permissible in the third position). The labels are "Integer adder", "FP adder", "FP multiplier", and "Load/store unit".
- The next line begins with the label "ROB entries = ", followed by a natural number.
- The next line begins with "CDB buffer entries = ", followed by a natural number.
- The next line is optional. It consists of comma-delineated patterns of the form A=B. The pattern A is the letter "R" or the letter "F" concatenated with exactly one of the numbers 0-31. The pattern B is an integer value which can be represented in 32 bits.
- The next line is optional. It consists of comma-delineated patterns of the form Meme[A]=B. The pattern A is a single natural number between 0 and 255 inclusive. The pattern B is an integer or floating point value which can be represented in 64 bits.
- The next line is blank. This line is not optional.
- The remainder of the lines in the file are instructions. All instructions are represented as shown in the rubric. Replace immediate values and offsets by their integer equivalents. In the case of a branch instruction, express the offset in terms of instructions to move relative to PC-next.
- The last line of the file should be the last instruction.

## 1.5 System Outputs

The library will output execution information in two ways; during execution, progress and the contents of various system components are displayed to **stdout**. Upon completion, an output file will be written to the directory containing the input file. The output file will be the same name as the input file, with "\_output" appended just before the file extension.

## 2 Verification & Testing

In order to verify a proper and complete implementation of Tomasulo's algorithm, we developed a series of progressively more complex test inputs. All of the test cases used are provided in the repository under the "testCases/" directory. For convenience, they are repeated here along with a short description of which feature they verify.

### 2.1 simple1.txt

This test was designed to test a pair of independent integer ALU instructions, as a verification that our system could correctly process both types of Integer ALU instructions in isolation. It also serves as a verification of the general flow of the program, excluding the memory stage.

## Input

# of rs Cycles in EX Cycles in Mem # of FUs  
Integer adder 2 1 1  
FP adder 3 3 1  
FP multiplier 2 20 1  
Load/store unit 3 1 4 1  
ROB entries = 128  
CDB buffer entries = 1  
R1=10,R2=20,R3=30,F2=30.1  
Mem[4]=1,Mem[8]=2,Mem[12]=3.4

ADD R1,R2,R3  
SUB R4,R2,R3

## Output

=====Instruction Completion Table=====

ID	IS	EX	MEM	WB	COM
0	0	1	None	2	3
1	1	2	None	3	4

=====Integer ARF=====

R0 : 0	R1 : 50	R2 : 20	R3 : 30
R4 : -10	R5 : 0	R6 : 0	R7 : 0
R8 : 0	R9 : 0	R10: 0	R11: 0
R12: 0	R13: 0	R14: 0	R15: 0
R16: 0	R17: 0	R18: 0	R19: 0
R20: 0	R21: 0	R22: 0	R23: 0
R24: 0	R25: 0	R26: 0	R27: 0
R28: 0	R29: 0	R30: 0	R31: 0

=====Floating Point ARF=====

F0 : 0.000000	F1 : 0.000000
F2 : 30.100000	F3 : 0.000000
F4 : 0.000000	F5 : 0.000000
F6 : 0.000000	F7 : 0.000000
F8 : 0.000000	F9 : 0.000000
F10: 0.000000	F11: 0.000000
F12: 0.000000	F13: 0.000000
F14: 0.000000	F15: 0.000000
F16: 0.000000	F17: 0.000000
F18: 0.000000	F19: 0.000000
F20: 0.000000	F21: 0.000000
F22: 0.000000	F23: 0.000000
F24: 0.000000	F25: 0.000000
F26: 0.000000	F27: 0.000000
F28: 0.000000	F29: 0.000000
F30: 0.000000	F31: 0.000000

=====Memory Unit=====

Word 01: 1.000000	Word 02: 2.000000
Word 03: 3.400000	

## 2.2 simple2.txt

This test was designed to test a pair of independent floating point ALU instructions, as a verification that our system could correctly process both types of floating point ALU instructions in isolation. It also serves as a verification of the general flow of the program, excluding the memory stage.

### Input

```
# of rs Cycles in EX  Cycles in Mem # of FUs
Integer adder 2 1    1
FP adder 3 3    2
FP multiplier 2 20    1
Load/store unit 3 1 4 1
ROB entries = 128
CDB buffer entries = 1
F1=10.10,F2=20.20,F3=30.30,F4=30.1
```

```
ADD.D F1,F2,F3
SUB.D F4,F2,F3
```

### Output

=====Instruction Completion Table=====

ID	IS	EX	MEM	WB	COM
0	0	1	None	4	5
1	1	2	None	5	6

=====Integer ARF=====

R0 : 0	R1 : 0	R2 : 0	R3 : 0
R4 : 0	R5 : 0	R6 : 0	R7 : 0
R8 : 0	R9 : 0	R10: 0	R11: 0
R12: 0	R13: 0	R14: 0	R15: 0
R16: 0	R17: 0	R18: 0	R19: 0
R20: 0	R21: 0	R22: 0	R23: 0
R24: 0	R25: 0	R26: 0	R27: 0
R28: 0	R29: 0	R30: 0	R31: 0

=====Floating Point ARF=====

F0 : 0.000000	F1 : 50.500000
F2 : 20.200000	F3 : 30.300000
F4 : -10.100000	F5 : 0.000000
F6 : 0.000000	F7 : 0.000000
F8 : 0.000000	F9 : 0.000000
F10: 0.000000	F11: 0.000000
F12: 0.000000	F13: 0.000000
F14: 0.000000	F15: 0.000000
F16: 0.000000	F17: 0.000000
F18: 0.000000	F19: 0.000000
F20: 0.000000	F21: 0.000000
F22: 0.000000	F23: 0.000000
F24: 0.000000	F25: 0.000000
F26: 0.000000	F27: 0.000000
F28: 0.000000	F29: 0.000000
F30: 0.000000	F31: 0.000000

```

=====Memory Unit=====
Word 01: 1.000000          Word 02: 2.000000
Word 03: 3.400000

```

## 2.3 simple3.txt

This test was designed to test a pair of independent floating point multiplier instructions, as a verification that our system could correctly process floating point multiplier instructions in isolation.

### Input

```

# of rs Cycles in EX  Cycles in Mem # of FUs
Integer adder 2 1    1
FP adder  3 3    1
FP multiplier 2 20    2
Load/store unit 3 1 4 1
ROB entries = 128
CDB buffer entries = 1
F1=0.2345,F2=30.1,F3=3.14159,F4=-999.999,F5=2000

```

```

MULT.D F1,F2,F3
MULT.D F4,F2,F5

```

### Output

```

=====Instruction Completion Table=====
ID | IS  EX  MEM  WB  COM
0 | 0  1  None  2  3
1 | 1  2  None  3  4
2 | 3  4  None  5  6

```

```

=====Integer ARF=====
R0 : 0          R1 : 50          R2 : 20          R3 : 30
R4 : -10        R5 : 99          R6 : 0           R7 : 0
R8 : 0          R9 : 0           R10: 0           R11: 0
R12: 0          R13: 0           R14: 0           R15: 0
R16: 0          R17: 0           R18: 0           R19: 0
R20: 0          R21: 0           R22: 0           R23: 0
R24: 0          R25: 0           R26: 0           R27: 0
R28: 0          R29: 0           R30: 0           R31: 0

```

```

=====Floating Point ARF=====
F0 : 0.000000   F1 : 0.000000
F2 : 30.100000  F3 : 0.000000
F4 : 0.000000   F5 : 0.000000
F6 : 0.000000   F7 : 0.000000
F8 : 0.000000   F9 : 0.000000
F10: 0.000000  F11: 0.000000
F12: 0.000000  F13: 0.000000
F14: 0.000000  F15: 0.000000
F16: 0.000000  F17: 0.000000
F18: 0.000000  F19: 0.000000

```

F20: 0.000000	F21: 0.000000
F22: 0.000000	F23: 0.000000
F24: 0.000000	F25: 0.000000
F26: 0.000000	F27: 0.000000
F28: 0.000000	F29: 0.000000
F30: 0.000000	F31: 0.000000

=====Memory Unit=====

Word 04: 1.000000	Word 08: 2.000000
Word 12: 3.400000	

## 2.4 simple4.txt

This test case was designed to test the load and store instructions in isolation. It also serves as a verification of the general flow of the program, excluding the branch unit.

### Input

```
# of rs Cycles in EX Cycles in Mem # of FUs
Integer adder 2 1 1
FP adder 3 3 1
FP multiplier 2 20 1
Load/store unit 3 1 4 1
ROB entries = 128
CDB buffer entries = 1
R1=10,R2=20,R3=30,F2=30.1
Mem[4]=1,Mem[8]=2,Mem[12]=3.4
```

```
SD F2, 8(R0)
LD F1, 4(R0)
```

### Output

=====Instruction Completion Table=====

ID	IS	EX	MEM	WB	COM
0	0	1	2	6	7
1	1	2	6	10	11

=====Integer ARF=====

R0 : 0	R1 : 10	R2 : 20	R3 : 30
R4 : 0	R5 : 0	R6 : 0	R7 : 0
R8 : 0	R9 : 0	R10: 0	R11: 0
R12: 0	R13: 0	R14: 0	R15: 0
R16: 0	R17: 0	R18: 0	R19: 0
R20: 0	R21: 0	R22: 0	R23: 0
R24: 0	R25: 0	R26: 0	R27: 0
R28: 0	R29: 0	R30: 0	R31: 0

=====Floating Point ARF=====

F0 : 0.000000	F1 : 1.100000
F2 : 30.100000	F3 : 0.000000
F4 : 0.000000	F5 : 0.000000
F6 : 0.000000	F7 : 0.000000

F8 : 0.000000	F9 : 0.000000
F10: 0.000000	F11: 0.000000
F12: 0.000000	F13: 0.000000
F14: 0.000000	F15: 0.000000
F16: 0.000000	F17: 0.000000
F18: 0.000000	F19: 0.000000
F20: 0.000000	F21: 0.000000
F22: 0.000000	F23: 0.000000
F24: 0.000000	F25: 0.000000
F26: 0.000000	F27: 0.000000
F28: 0.000000	F29: 0.000000
F30: 0.000000	F31: 0.000000

=====Memory Unit=====

Word 01: 1.000000	Word 02: 30.10000
Word 03: 3.400000	

## 2.5 simple5.txt

This test case was designed to test the branch unit with a single branch instruction. It serves to test the simplest functions of the branch unit, including storing copies of the RAT and correct branch prediction.

### Input

```
# of rs Cycles in EX  Cycles in Mem # of FUs
Integer adder 2 1    1
FP adder  3 3    1
FP multiplier 2 20    1
Load/store unit 3 1 4 1
ROB entries = 16
CDB buffer entries = 1
R1=10,R2=20,R3=30,R4=20,F2=30.1
Mem[4]=1,Mem[8]=2,Mem[12]=3.4
```

```
SUB R4,R4,R2
BNE R4,R0,-2
```

### Output

=====Instruction Completion Table=====

ID	IS	EX	MEM	WB	COM
0	0	1	None	2	3
1	1	3	None	None	4
2	3	4	None	5	6
3	4	6	None	None	7

=====Integer ARF=====

R0 : 0	R1 : 10	R2 : 20	R3 : 30
R4 : 0	R5 : 0	R6 : 0	R7 : 0
R8 : 0	R9 : 0	R10: 0	R11: 0
R12: 0	R13: 0	R14: 0	R15: 0
R16: 0	R17: 0	R18: 0	R19: 0
R20: 0	R21: 0	R22: 0	R23: 0

R24: 0	R25: 0	R26: 0	R27: 0
R28: 0	R29: 0	R30: 0	R31: 0

=====Floating Point ARF=====

F0 : 0.000000	F1 : 0.000000
F2 : 30.100000	F3 : 0.000000
F4 : 0.000000	F5 : 0.000000
F6 : 0.000000	F7 : 0.000000
F8 : 0.000000	F9 : 0.000000
F10: 0.000000	F11: 0.000000
F12: 0.000000	F13: 0.000000
F14: 0.000000	F15: 0.000000
F16: 0.000000	F17: 0.000000
F18: 0.000000	F19: 0.000000
F20: 0.000000	F21: 0.000000
F22: 0.000000	F23: 0.000000
F24: 0.000000	F25: 0.000000
F26: 0.000000	F27: 0.000000
F28: 0.000000	F29: 0.000000
F30: 0.000000	F31: 0.000000

=====Memory Unit=====

Word 01: 1.000000	Word 02: 2.000000
Word 03: 3.400000	

## 2.6 simple6.txt

This test case was designed to test corner cases of the system configuration. This test will issue instructions to saturate the capacity of all functional units by filling the output buffers and the reservation stations. The goal is to prove that the library can make forward progress in the face of a demanding load.

### Input

```
# of rs Cycles in EX  Cycles in Mem # of FUs
Integer adder 1 1 1
FP adder 1 4 1
FP multiplier 1 4 1
Load/store unit 1 1 4 1
ROB entries = 128
CDB buffer entries = 2
R1=1,R2=2,R3=3,F1=1.1,F2=2.1
Mem[0]=0.0,Mem[4]=1.1,Mem[8]=2.2,Mem[12]=3.3
```

```
LD F3, 0(R0)
LD F4, 4(R0)
LD F5, 8(R0)
LD F6, 12(R0)
SD F1, 0(R0)
SD F2, 4(R0)
ADDD.D F7,F3,F4
ADDD.D F8,F3,F4
```



```

MULT.D F9,F3,F4
MULT.D F10,F3,F4
SUB R9,R3,R4
SUB R10,R3,R4

```

## Output

=====Instruction Completion Table=====

ID	IS	EX	MEM	WB	COM
0	0	1	2	6	7
1	7	8	9	13	14
2	14	15	16	20	21
3	21	22	23	27	28
4	28	29	30	34	35
5	35	35	37	41	42
6	36	37	None	42	43
7	43	43	None	48	49
8	44	45	None	49	50
9	50	51	None	55	56
10	51	52	None	53	57
11	54	55	None	56	58

=====Integer ARF=====

R0 : 0	R1 : 1	R2 : 2	R3 : 3
R4 : 0	R5 : 0	R6 : 0	R7 : 0
R8 : 0	R9 : 3	R10: 3	R11: 0
R12: 0	R13: 0	R14: 0	R15: 0
R16: 0	R17: 0	R18: 0	R19: 0
R20: 0	R21: 0	R22: 0	R23: 0
R24: 0	R25: 0	R26: 0	R27: 0
R28: 0	R29: 0	R30: 0	R31: 0

=====Floating Point ARF=====

F0 : 0.000000	F1 : 1.100000
F2 : 2.100000	F3 : 0.000000
F4 : 1.100000	F5 : 2.200000
F6 : 3.300000	F7 : 1.100000
F8 : 1.100000	F9 : 0.000000
F10: 0.000000	F11: 0.000000
F12: 0.000000	F13: 0.000000
F14: 0.000000	F15: 0.000000
F16: 0.000000	F17: 0.000000
F18: 0.000000	F19: 0.000000
F20: 0.000000	F21: 0.000000
F22: 0.000000	F23: 0.000000
F24: 0.000000	F25: 0.000000
F26: 0.000000	F27: 0.000000
F28: 0.000000	F29: 0.000000
F30: 0.000000	F31: 0.000000

=====Memory Unit=====

Word 00: 1.100000  
Word 02: 2.200000

Word 01: 2.200000  
Word 03: 3.300000

## 2.7 simple7.txt

This test case was designed to verify the absence of WAW hazards, a behavior that the algorithm was designed to remove.

### Input

# of rs Cycles in EX Cycles in Mem # of FUs  
Integer adder 2 1 1  
FP adder 3 3 1  
FP multiplier 2 20 1  
Load/store unit 3 1 4 1  
ROB entries = 128  
CDB buffer entries = 1  
R1=10,R2=20,R3=30,F2=30.1

ADD R1,R2,R3  
SUB R1,R2,R3

### Output

=====Instruction Completion Table=====

ID	IS	EX	MEM	WB	COM
0	0	1	None	2	3
1	1	2	None	3	4

=====Integer ARF=====

R0 : 0	R1 : -10	R2 : 20	R3 : 30
R4 : 0	R5 : 0	R6 : 0	R7 : 0
R8 : 0	R9 : 0	R10: 0	R11: 0
R12: 0	R13: 0	R14: 0	R15: 0
R16: 0	R17: 0	R18: 0	R19: 0
R20: 0	R21: 0	R22: 0	R23: 0
R24: 0	R25: 0	R26: 0	R27: 0
R28: 0	R29: 0	R30: 0	R31: 0

=====Floating Point ARF=====

F0 : 0.000000	F1 : 0.000000
F2 : 30.100000	F3 : 0.000000
F4 : 0.000000	F5 : 0.000000
F6 : 0.000000	F7 : 0.000000
F8 : 0.000000	F9 : 0.000000
F10: 0.000000	F11: 0.000000
F12: 0.000000	F13: 0.000000
F14: 0.000000	F15: 0.000000
F16: 0.000000	F17: 0.000000
F18: 0.000000	F19: 0.000000
F20: 0.000000	F21: 0.000000
F22: 0.000000	F23: 0.000000
F24: 0.000000	F25: 0.000000
F26: 0.000000	F27: 0.000000

```

F28: 0.000000          F29: 0.000000
F30: 0.000000          F31: 0.000000

```

```

=====Memory Unit=====
Word 01: 1.000000      Word 02: 2.000000
Word 03: 3.400000

```

## 2.8 simple8.txt

This test case was designed to verify the absence of WAR hazards, a behavior that the algorithm was designed to remove.

### Input

```

# of rs Cycles in EX  Cycles in Mem # of FUs
Integer adder 4 3    3
FP adder  3 3    1
FP multiplier 2 20    1
Load/store unit 3 1 4 1
ROB entries = 128
CDB buffer entries = 1
R1=1,R2=1,R3=1,R1=2,F2=30.1
Mem[4]=1,Mem[8]=2,Mem[12]=3.4

```

```

SUB R3,R3,R1
SUB R3,R4,R1
BNE R3,R0,-2

```

### Output

```

=====Instruction Completion Table=====
ID | IS  EX  MEM  WB  COM
0 | 0  1  None  4  5
1 | 1  2  None  5  6
2 | 2  6  None  None  9

```

```

=====Integer ARF=====
R0 : 0          R1 : 1          R2 : 1          R3 : 0
R4 : 1          R5 : 0          R6 : 0          R7 : 0
R8 : 0          R9 : 0          R10: 0          R11: 0
R12: 0          R13: 0          R14: 0          R15: 0
R16: 0          R17: 0          R18: 0          R19: 0
R20: 0          R21: 0          R22: 0          R23: 0
R24: 0          R25: 0          R26: 0          R27: 0
R28: 0          R29: 0          R30: 0          R31: 0

```

```

=====Floating Point ARF=====
F0 : 0.000000          F1 : 0.000000
F2 : 30.100000         F3 : 0.000000
F4 : 0.000000          F5 : 0.000000
F6 : 0.000000          F7 : 0.000000
F8 : 0.000000          F9 : 0.000000

```

F10: 0.000000	F11: 0.000000
F12: 0.000000	F13: 0.000000
F14: 0.000000	F15: 0.000000
F16: 0.000000	F17: 0.000000
F18: 0.000000	F19: 0.000000
F20: 0.000000	F21: 0.000000
F22: 0.000000	F23: 0.000000
F24: 0.000000	F25: 0.000000
F26: 0.000000	F27: 0.000000
F28: 0.000000	F29: 0.000000
F30: 0.000000	F31: 0.000000

=====Memory Unit=====

Word 01: 1.000000	Word 02: 2.000000
Word 03: 3.400000	

## 2.9 simple9.txt

This test case was designed to verify that the system is capable of handling RAW dependencies. Several truly dependent instructions are issued for each of the types of functional units, to test the ability to complete execution as prescribed by Tomasulo's algorithm.

### Input

```
# of rs Cycles in EX Cycles in Mem # of FUs
Integer adder 2 1 1
FP adder 3 3 1
FP multiplier 2 20 1
Load/store unit 3 1 4 1
ROB entries = 10
CDB buffer entries = 1
R1=10,R2=20,R3=30,F2=30.1
Mem[4]=1,Mem[8]=2,Mem[12]=3.4
```

```
ADD R1,R2,R3
SUB R4,R1,R3
```

### Output

=====Instruction Completion Table=====

ID	IS	EX	MEM	WB	COM
0	0	1	None	2	3
1	1	3	None	4	5

=====Integer ARF=====

R0 : 0	R1 : 50	R2 : 20	R3 : 30
R4 : 80	R5 : 0	R6 : 0	R7 : 0
R8 : 0	R9 : 0	R10: 0	R11: 0
R12: 0	R13: 0	R14: 0	R15: 0
R16: 0	R17: 0	R18: 0	R19: 0
R20: 0	R21: 0	R22: 0	R23: 0
R24: 0	R25: 0	R26: 0	R27: 0
R28: 0	R29: 0	R30: 0	R31: 0

=====Floating Point ARF=====

F0 : 0.000000	F1 : 0.000000
F2 : 30.100000	F3 : 0.000000
F4 : 0.000000	F5 : 0.000000
F6 : 0.000000	F7 : 0.000000
F8 : 0.000000	F9 : 0.000000
F10: 0.000000	F11: 0.000000
F12: 0.000000	F13: 0.000000
F14: 0.000000	F15: 0.000000
F16: 0.000000	F17: 0.000000
F18: 0.000000	F19: 0.000000
F20: 0.000000	F21: 0.000000
F22: 0.000000	F23: 0.000000
F24: 0.000000	F25: 0.000000
F26: 0.000000	F27: 0.000000
F28: 0.000000	F29: 0.000000
F30: 0.000000	F31: 0.000000

=====Memory Unit=====

Word 01: 1.000000	Word 02: 2.000000
Word 03: 3.400000	

## Output

### 2.10 complex6.txt

This test case was designed to test our model of system memory (RAM). Here, we write a series of patterns to memory to verify that loads and stores are executing in the correct order, and that data is written to the correct location.

## Input

```
# of rs Cycles in EX Cycles in Mem # of FUs
Integer adder 2 1 1
FP adder 3 3 1
FP multiplier 2 20 1
Load/store unit 3 1 4 1
ROB entries = 128
CDB buffer entries = 1
R1=10,R2=16,R3=30,F1=111.111,F2=222.222
Mem[4]=1,Mem[8]=2,Mem[12]=3.4
```

```
ADD R1,R0,R0
SD F1, 0(R1)
ADDI R1,R1,4
BNE R1,R2,-3
SD F2, 0(R1)
LD F3, 0(R1)
LD F4, -8(R1)
```

## Output

=====Instruction Completion Table=====

ID	IS	EX	MEM	WB	COM
0	0	1	None	2	3
1	1	3	4	8	9
2	2	3	None	4	10
3	3	5	None	None	11
4	4	5	6	10	12
5	5	6	None	7	13
6	6	8	None	None	14
7	7	8	9	13	15
8	8	9	None	11	16
9	9	12	None	None	17
10	10	12	13	17	18
11	12	13	None	14	19
12	13	15	None	None	20
13	17	18	19	23	24
14	18	19	23	27	28
15	19	20	27	31	32

=====Integer ARF=====

R0 : 0	R1 : 16	R2 : 16	R3 : 30
R4 : 0	R5 : 0	R6 : 0	R7 : 0
R8 : 0	R9 : 0	R10: 0	R11: 0
R12: 0	R13: 0	R14: 0	R15: 0
R16: 0	R17: 0	R18: 0	R19: 0
R20: 0	R21: 0	R22: 0	R23: 0
R24: 0	R25: 0	R26: 0	R27: 0
R28: 0	R29: 0	R30: 0	R31: 0

=====Floating Point ARF=====

F0 : 0.000000	F1 : 111.1100
F2 : 222.2220	F3 : 111.1110
F4 : 111.1110	F5 : 0.000000
F6 : 0.000000	F7 : 0.000000
F8 : 0.000000	F9 : 0.000000
F10: 0.000000	F11: 0.000000
F12: 0.000000	F13: 0.000000
F14: 0.000000	F15: 0.000000
F16: 0.000000	F17: 0.000000
F18: 0.000000	F19: 0.000000
F20: 0.000000	F21: 0.000000
F22: 0.000000	F23: 0.000000
F24: 0.000000	F25: 0.000000
F26: 0.000000	F27: 0.000000
F28: 0.000000	F29: 0.000000
F30: 0.000000	F31: 0.000000

=====Memory Unit=====

Word 01: 111.1110	Word 02: 111.1110
Word 03: 111.1110	Word 04: 111.1110

## 2.11 complex7.txt

This final test case was designed to show that our system can do real work. We execute a sum over some data in memory to induce a chain of dependencies and memory latencies.

### Input

```
# of rs Cycles in EX  Cycles in Mem # of FUs
Integer adder 2 1    1
FP adder    3 3    1
FP multiplier 2 20    1
Load/store unit 3 1 4 1
ROB entries = 128
CDB buffer entries = 1
R1=4,R2=20,R3=16,F2=30.1
Mem[0]=1.01,Mem[4]=2.01,Mem[8]=3.01,Mem[12]=4.01
```

```
ADD.D F2,F0,F0
ADD R2,R0,R0
LD F1,0(R2)
ADDI R2,R2,4
ADDI R1,R1,-1
ADD.D F2,F2,F1
BNE R0,R1,-5
SD F2,0(R3)
```

### Output

=====Instruction Completion Table=====

ID	IS	EX	MEM	WB	COM
0	0	1	None	4	5
1	1	2	None	3	6
2	2	3	4	8	9
3	3	4	None	5	10
4	4	5	None	6	11
5	5	9	None	12	13
6	6	7	None	None	14
7	7	8	9	13	15
8	8	9	None	10	16
9	9	10	None	11	17
10	10	14	None	17	18
11	11	12	None	None	19
12	12	13	14	18	20
13	13	14	None	15	21
14	14	15	None	16	22
15	15	19	None	22	23
16	16	17	None	None	24
17	17	18	19	22	25
18	18	19	None	20	26
19	19	20	None	21	27
20	20	24	None	27	28
21	21	22	None	None	29

=====Integer ARF=====			
R0 : 0	R1 : 0	R2 : 16	R3 : 16
R4 : 0	R5 : 0	R6 : 0	R7 : 0
R8 : 0	R9 : 0	R10: 0	R11: 0
R12: 0	R13: 0	R14: 0	R15: 0
R16: 0	R17: 0	R18: 0	R19: 0
R20: 0	R21: 0	R22: 0	R23: 0
R24: 0	R25: 0	R26: 0	R27: 0
R28: 0	R29: 0	R30: 0	R31: 0
=====Floating Point ARF=====			
F0 : 0.000000	F1 : 4.010000		
F2 : 10.40000	F3 : 0.000000		
F4 : 0.000000	F5 : 0.000000		
F6 : 0.000000	F7 : 0.000000		
F8 : 0.000000	F9 : 0.000000		
F10: 0.000000	F11: 0.000000		
F12: 0.000000	F13: 0.000000		
F14: 0.000000	F15: 0.000000		
F16: 0.000000	F17: 0.000000		
F18: 0.000000	F19: 0.000000		
F20: 0.000000	F21: 0.000000		
F22: 0.000000	F23: 0.000000		
F24: 0.000000	F25: 0.000000		
F26: 0.000000	F27: 0.000000		
F28: 0.000000	F29: 0.000000		
F30: 0.000000	F31: 0.000000		
=====Memory Unit=====			
Word 00: 1.010000	Word 01: 2.010000		
Word 02: 3.010000	Word 03: 4.010000		
Word 04: 10.40000			

### 3 Division of Labor

#### 3.1 Responsibilities

We developed our code and test cases together. Stephen was more experienced with Python, so for productivity’s sake he wrote much of the code. Yihao helped by developing the general flow of the program, writing effective test cases, identifying areas for improvement in the design, and general debugging.

#### 3.2 Code Contribution

Yihao developed the floating-point functional units and the memory unit. Stephen developed the other main components of the library. Stephen wrote the first pass of the five execution stages, and then worked with Yihao to debug them as each test case was visited. More specific details on the day-to-day code contributions are available in the commit history of the Github repository.



### **3.3 Test Contribution**

Stephen wrote the simpler test cases as a litmus test for the first pass of the data path. Stephen helped come up with the ideas for the more exhaustive tests. Yihao wrote the bulk of the test input files. Both team members completed all tests by hand to verify that our expected results were consistent.

### **3.4 Meetings & Participation**

Since there were only two members on our team, it was easy to work together and hold productive meetings. We spent several weekends coding side-by-side, and maintained effective communication throughout the project.