

Task No: 9
Date:

Write Pig Latin scripts sort, group, join, project, and filter the data
Tools: Pig, LINUX/WINDOWS

CO4
K3

AIM:

To Implement the Pig Latin scripts sort, group, join, project, and filter the data using Apache Pig in Windows Operating System.

PROCEDURE:

- 1) Install the prerequisite Stable software's Java Development Kit and Java Runtime Environment, Apache Hadoop.
- 2) Visit the Apache Pig download page: <https://pig.apache.org/downloads.html>
- 3) Download the latest stable release of Pig.
- 4) Extract the Pig Archive and Set Environment Variables for java, Apache Hadoop and Apache Pig

For Java:

JAVA_HOME=C:\Program Files\Java\jdk-1.8

Path = C:\Program Files\Java\jdk-1.8\bin

For Hadoop:

HADOOP_HOME=C:\ApacheHadoop2.9.2

Path = C:\ApacheHadoop2.9.2\bin

For Pig:

PIG_HOME = C:\Apachepig

Path = C:\Apachepig\bin

Path = C:\Apachepig\conf

- 5) Verify the Paths, Run following commands in a NEW Command Window
echo %PIG_HOME%
- 6) Open the pig. cmd file in edit mode, and change the value of the HADOOP_BIN_PATH
Old value:- %HADOOP_HOME%\bin
New Value:- %HADOOP_HOME%\libexec
- 7) Edit Pig Configuration, go to the conf directory within your Pig installation directory, rename the pig.properties.template file to pig.properties. and set the exectype property to "local"
exectype=local
- 8) Start Apache Pig, run the following command in a new Command Prompt as administrator
C:\Users\Lenovo>echo %PIG_HOME%
O/P: C:\ApachePig

```
C:\Users\Lenovo>pig -version
```

```
Apache Pig version 0.17.0 (r1797386)
```

```
compiled Jun 02 2017, 15:41:58
```

```
C:\Users\Lenovo>pig
```

```
Grunt Shell started:
```

```
grunt>
```

Output:

Pig Latin scripts:

Input.txt

```
Rajiv,42  
siddarth,45  
Rajesh,40  
Preethi,23  
Trupthi,34  
Archana,21  
Robin,22  
BOB,23  
Maya,23  
Sara,25  
David,23  
Maggy,22
```

Addressfile.txt

```
Rajiv,Chennai  
Rajesh,Delhi  
Trupthi,Hyderabad  
Robin,Pune  
Maya,Hyderabad  
Anderson,Chennai  
Antolina,Chennai
```

Load Data:

```
data = LOAD './input.txt' USING PigStorage(',') AS (name:chararray, age:int);
```

Sort Operator:

```
sortbyage = ORDER data BY age ASC|DESC;  
dump sortbyage;
```

Group Operator:

```
grouped_data = GROUP data BY age;  
dump grouped_data;
```

Filter Operator:

```
filterbyage = FILTER data BY (age>40);  
dump filterbyage;
```

Inner Join Operator:

```
table1 = LOAD './input.txt' USING PigStorage(',') AS (name:chararray, age:int);  
table2 = LOAD './addressfile.txt' USING PigStorage(',') AS (name:chararray, address:chararray);
```

```
joinbyname = JOIN table1 BY name, table2 BY name;
```

OuterJoin Operator:

```
LO = JOIN table1 BY name LEFT OUTER, table2 BY name;  
dump LO;
```

```
RO = JOIN table1 BY name RIGHT, table2 BY name;  
dump RO;
```

```
FO = JOIN table1 BY name FULL OUTER, table2 BY name;  
dump FO;
```

Store Operator:

```
grouped_data = GROUP data BY age;  
result = FOREACH grouped_data GENERATE group AS age, COUNT(data) AS count;  
STORE result INTO 'output';
```

Result:

Thus the Apache Pig Latin scripts sort, group, join, project, and filter the data are executed Successfully.