SL	Property | Syntax	Value	Default	Version	Description
1	Background-color - background-color: value - backgroundColor = ‘value’	- color (Name | HEX | RGB | HSL) - transparent (RGBA | HSLA) - initial | inherit	Transparent	CSS1	- it sets the background color of an element - background is total size of element - including (padding | border) not (margin) # can use (opacity) property also to transparent # (opacity) transparent all the content and child # (RGBA | HSLA) only transparent the element
2	Background-image - background-image: url() - backgroundImage = ‘url()’	- url(‘path/image’) - conic-gradient(red, blue, green) - linear-gradient(hex, rgb, name) - radial-gradient(hex 10%, hex) - repeating-conic-gradient(hex) - repeating-linear-gradient(rgb) - repeating-radial-gradient(hex) - none - initial | inherit	No	CSS1 / CSS3 – New Value	- sets the background image for an element - it can sets one / more images for an element - if image is smaller than container then repeat the image from top left corner both, horizontally and vertically # it can set (gradient color) instead of (image) # there basic three type of (gradient) and each of them can take two to three parameters # we can set (percentage) for each parameter # each parameter can take (color-name, hex, rgb)
3	Background-repeat - background-repeat: repeat - backgroundColor = ‘repeat’	- repeat - repeat-x - repeat-y - no-repeat - space - round - initial | inherit	Repeat	CSS1	- it works with (background-image) property to control image (repeating) system # space: repeat as possible without clipping first and last image is pinned either side and white space is distributed evenly # round: repeated and stretched to fill the space and no gaps between images
4	Background-position - background-position: x% y% - backgroundPosition = ‘x% y%’	- top let | top right - top center - center left | center right - center center - bottom left | bottom right - bottom center - x% y% - xpos ypos - initial | inherit	0% 0%	CSS1	- it works with (background-image) property - if image is smaller than container and no-repeat - then can set the image-position inside container # if we set only one value then # other one is set automatically # either (center | 50%)
5	Background-attachment - background-attachment: scroll - backgroundAttachment = ‘scroll’	- scroll - local - fixed - initial | inherit	Scroll	CSS1	- it works with (background-image) property - It sets whether a background-image scrolls with Rest of the page or fixed # scroll: image will scroll with the page # local: image will scroll with the element content # fixed: image will not scroll with the page

6	Background-size - background-size: - backgroundSize = ‘	- auto - cover - contain - percentage - length - initial | inherit	Auto	CSS3	- specify the size of the background image - there are four different value syntaxes - keyword (auto | cover | contain) - one value (set width | height will be auto) - two value (first width | second height) - multiple background (separated with comma) # cover: resize the image to cover the container image may stretch or cut a little bit at the edge # contain: resize the image to fully visible
7	Background-clip - background-clip: border-box - backgroundClip = ‘border-box’	- border-box - padding-box - content-box - initial | inherit	Border-box	CSS3	- defines how far the (color | image) should extend
8	Background-origin - background-origin: padding-box - backgroundOrigin = ‘padding-box’	- padding-box - border-box - content-box - initial | inherit	Padding-box	CSS3	- specify the origin position of an image (the background-positioning area) - this property has no effect if (attachment) is (fixed)
9	Background - background: property-value(s) - background = ‘property-value(s)’	- color - image | repeat - position | attachment - size	Default	CSS1 / CSS3	- it is also possible to specify all properties in one single property and is called shorthand property - it does not matter if one of the property value is Missing, as long as the other ones are in this order
0	Opacity - opacity: 1 - opacity = ‘1’	- number - initial | inherit	1	CSS3	- specifies the opacity / transparency of an element - all of it child element also inherit same opacity # take value from (0.0 – 1.0), lower value is more Transparent and 1 is no transparent
SL	Property | Syntax	Value	Default	Version	Description
1	Border-style - border-style: none - borderStyle: ‘none’;	- dotted | dashed - solid | double - groove | ridge - inset | outset - none | hidden - initial | inherit	None	CSS1	- specifies what kind of border to display - can have (1 – 4) values (top | right | bottom | left) - if specify 2 values then (top | bottom – left | right) - if specify 3 values then (top – left | right – bottom) - none of other border properties unless style will have any effect
2	Border-width - border-width: medium - borderWidth = ‘medium’;	- medium | thick | thin - length (pixel | in | em etc) - initial | inherit	Medium	CSS1	- specifies the width of the four borders - width can be specify by unit of pre-define value - can have (1 – 4) values like (border-style)
3	Border-color - border-color: inherit - borderColor = ‘inherit’;	- color (name | hex | rgb | hsl) - transparent (rgba | hsla) - initial | inherit	inherit	CSS1	- is used to set the color of the four borders - can have (1 – 4) values like (border-style) - must set the (style) before set the (color)
4	Border-radius	- length	0	CSS3	- is used to add rounded border to an element

	- border-radius: 0 - border-radius = ‘0’;	- percentage - initial | inherit			- can have (1 – 4) value - top-left | top-right | bottom-right | bottom-left
5	Border-image-source	- none - image - initial | inherit	None	CSS3	- it specify the path to the image to be used - if (none), then border style will be used
6	Border-image-width	- length - number - percentage - auto - initial | inherit	1	CSS3	- it specifies the width of the border image # it can take from one to four values (top, right, bottom, and left sides) # if the 4th is omitted, it is the same as 2nd, and so on
7	Border-image-slice	- number - percentage - fill - initial | inherit	100%	CSS3	- it specifies how to slice the image - image is always sliced into nine sections: four orners, for edges, and the middle - (middle) part is fully transparent, unless (fill) sets # it can take from one to four values, if 4th is omitted then is same as 2nd, and so on
8	Border-image-outset	- length - number - initial | inherit	0	CSS3	- it specifies the amount by which the amount by Which the border image are extends beyond the Border box # it can takes from one to four values (top, right, bottom, and left sides) # if the 4th is omitted, is same as 2nd, and so on
9	Border-image-repeat	- stretch - repeat - round - space - initial | inherit	Stretch	CSS3	- it specifies whether the border image should be repeated, rounded, spaced or stretched # it specifies how the images for sides and middle part of the border image are scaled and tiled # can sets two values, if 2nd is omitted, is same as 1st
	Border Border-image	Style | width | color Source | offset | width | slice | repeat	Default		
	Border sides Border radius sides Border image sides	Style | width | color Radius Source | offset | width | slice | repeat	Default		- top-left | top-right - bottom-right | bottom-left
1	Outline-style	- none | hidden - dotted | dashed - solid | double - groove | ridge - inset | outset	None	CSS2	- it specifies the style of an outline

		- initial | inherit			
2	Outline-color	- color - initial | inherit	Current	CSS2	- it specifies the color of an outline - always declare the (outline-style) before (color) - color can be (name | HEX | RGB | HSL | invert)
3	Outline-width	- medium - thin | thick | length - initial | inherit	Medium	CSS2	- it specifies the width of an outline - declare the (outline-style) before (width)
4	Outline-offset	- length - initial | inherit	0	CSS3	- it adds space between the outline and the edge or Border of an element - space between element and outline is transparent
5	Outline	Style | Color | Width	Default	CSS2	- an outline is a line that is drawn around elements, Outside the borders, to make element stand out - is drawn outside the element's border, and may overlap other content. Also the outline is not affected by the width of the outline - outline differ from borders in three ways -- an outline is a line drawn around elements, outside the border edge -- an outline does not take up space -- an outline may be non-rectangular - is shorthand property - it specified as (one, two or three) values from the List above. The order of the values does not matter

SL	Property | Syntax	Value	Default	Version	Description
1	Color	- color - initial | inherit	Not specified	CSS1	- it specifies the color of text - NB: use a background color combined with a text Color that makes the text easy to read - high contrast is very important for people with Vision problems, so always ensure that the Contrast between the text color and the background Color is good - color specified by (name | HEX | RGB)
2	Text-align	- left | right | center | justify - initial | inherit	ltr | rtl	CSS1	- is specifies the horizontal alignment of text in an element
3	Text-align-last	- auto - left | right | center | justify - start | end - initial | inherit	Auto	CSS3	- it specifies how to align the last line of a text - NB: in Edge prior 79, the (text-align-last) property Only works on text that has (text-align: justify)
4	Vertical-align	- baseline | middle - top | text-top - bottom | text-bottom - length | percentage - sub | super - initial | inherit	Baseline	CSS1	- it sets the vertical alignment of an element
5	Direction	- ltr | rtl - initial | inherit	Ltr	CSS2	- it specifies the text direction/writing direction within A block-level element - NB: use this property together with (Unicode-bidi) To set or return whether text should be overridden To support multiple languages in the same document
6	Unicode-bidi	- normal - embed | isolate | plaintext - bidi-override | isolate-override - initial | inherit	Normal	CSS2	- it is used together with the (direction) property to Set or return whether the text should be overridden To support multiple languages in the same document
7	Text-decoration-color	- color - initial | inherit	Current color	CSS3	- it specifies the color of the (text-decoration) (underlines, overlies, linethroughs)
8	Text-decoration-line	- none - underline | overline - line-through - initial	None	CSS3	- it sets the kind of text decoration to use - you ca also combine more than one value, like underline and overline to display lines both under and over the text
9	Text-decoration-style	- solid | double - dotted | dashed | wavy - initial | inherit	Solid	CSS3	- it sets the style of the text decoration

10	Text-decoration-thickness	- auto - from-font - length | percentage - initial | inherit	Auto	CSS3	- it specifies the thickness of the decoration line
11	Text-decoration	- line - color - style - thickness	Default	CSS1 CSS3	- it specifies the decoration added to text, and is a Shorthand property for (line | color | style | thickness) = here (text-decoration-line) is required
12	Text-transform	- none | capitalize - uppercase | lowercase - initial | inherit	None	CSS1	- it controls the capitalization of text or uppercase and Lowercase letters in a text or each word
5	Letter-spacing	- normal - length - initial | inherit	Normal	CSS1	- it increases or decreases the space between Characters in a text
	Word-spacing	- normal - length - initial | inherit	Normal	CSS1	- it increases or decreases the white space between words
	White-space	- normal - nowrap - pre | pre-line | pre-wrap - initial | inherit	Normal	CSS1	- it specifies how white-space inside an element is handled
	Line-height	- normal - number | length | percentage - initial | inherit	Normal	CSS1	- it specifies the height of a line - NB: negative values are not allowed
	Text-indent	- length | percentage - initial | inherit	0	CSS1	- it specifies the indentation of first line in a text-block - NB: negative values are allowed. - NB: first line will be indented to the left if negative
6	Text-shadow	- h-shadow | v-shadow - blur-radius | color - none - initial | inherit	None	CSS3	- it adds shadow to text - this property accepts a comma-separated list of shadows to be applied to the text
1	Font-family	- serif (small stroke | elegance) - sans-serif (clean, minimalistic) - monospace (mechanical) - cursive (handwriting) - fantasy (decorative | playful)		CSS1	- it specifies the font of a text - if the font name is more than one word, it must be in Quotation marks - it should hold several font names as (fallback) system To ensure maximum compatibility between browsers And operating system - start with the font you want, and end with a generic

					Family, font names should be separated with comma - NB: choosing the right font has a huge impact on how the readers experience a website - right font can create a strong identity for your brand - using a font that is easy to read is important the font Adds value to your text. It is also important to Choose the correct color and text size for the font
2	Web safe / web fonts				
3	Fallbacks				
4	Style				
5	Google				
6	Pairings				
7	Shorthand				

SL	Property | Syntax	Value	Default	Version	Description
1	Margin				
2	Padding				
3	Height				
4	Width				
5	Max-width				
6	Overflow				
	Align				

SL	Property | Syntax	Value	Default	Version	Description
1	Display				
2	Inline-block				
3	Position				
4	Float				
5	z-index				
	flexbox				

SL	Property | Syntax	Value	Default	Version	Description
1	Links				
2	Lists				
3	Tables				
4	Form				
	Box model				
	Website layout				
	User interface				
	Box sizing				
	Media queries				

SL	Property | Syntax	Value	Default	Version	Description
1	Navigation bar				
2	Dropdowns				
3	Image Gallery				
4	Image Sprites				
	Counters				
	Tooltips				
	Style images				
	Image reflection				
	Object fit				
	Object position				
	Masking				
	Buttons				
	Pagination				
	Multiple columns				

SL	Property | Syntax	Value	Default	Version	Description
	2D transforms				
	3D transforms				
	Transitions				
	Animations				

SL	Property | Syntax	Value	Default	Version	Description
	Colors				
	Gradients				
	Shadows				
	Text effects				

SL	Property | Syntax	Value	Default	Version	Description
1	Introduction				
2	Syntax				
3	Selectors				
4	How to				
	Comment				
	Colors				
	Gradients				
	Icons				
	Combinators				
	Pseudo-element				
	Attr selectors				
	Units				
	Specificity				
	Important				
	Math functions				
	Variables				

SL	Property | Syntax	Value	Default	Version	Description
	Responsive intro				
	Viewport				
	Grid view				

	Media queries				
	Images				
	Videos				
	Frameworks				
	Template				
	Grid intro				
	Container				
	Item				