



# GMWM Package - Part II

## Automatic and Computationally Efficient Method For Model Selection In Inertial Sensor Calibration

Roberto Molinari

Research Center for Statistics  
University of Geneva, Switzerland

joint work with  
James Balamuta (UIUC)  
Stéphane Guerrier (UIUC)  
Jan Skaloud (EPFL)  
Xinyu Zhang (CAS)

September 16, 2015

# The GMWM package in action

## Outline

### 1 Visualizing the signal(s):

- Is the signal disturbed (contaminated)?
- Which models could best describe the visualized WV?

### 2 Estimating the model(s)

- The `gmwm.imu()` function for parameter estimation
- The options for estimation

### 3 Inference

- Confidence intervals for the parameters
- Goodness-of-fit of the model to the signal

### 4 Model Selection

- The efficient computation of the WVIC
- Model selection from a set of user-specified models
- Automatic model selection from a set of all sub-models of a single user-specified model

# The GMWM package in action

## Getting to know the package

The package comes with an example dataset called `imu6`

- The data comes from the calibration of an XSens MTi-G sensor
- To use the data within the R session:
  - 1 Load the `gmwmdata` package (separate from the `gmwm` package)
  - 2 Make the dataset available in the session by typing `data(imu6)`
- Load external data (e.g. binary data) with `read.imu()`


```
install.packages("gmwmdata")  
library(gmwmdata)  
data(imu6)  
head(imu6)
```

	Gyro. X	Gyro. Y	Gyro. Z	Accel. X	Accel. Y	Accel. Z
1	-0.011138	-0.017646	-0.009531	1.083731	0.023897	9.638113
2	-0.006765	-0.013657	-0.021974	1.059858	0.042061	9.646901
3	...	...	...	...	...	...

# Visualizing the data

## The function `wvar.imu()`

Once the calibration data has been entered, it is possible to plot the observed WV vs  $\tau$  on a log-log scale



### R code:


```
imu.obj = imu(imu6,  
gyroscope = 1:3,  
accelerometer = 4:6)  
wv = wvar.imu(imu.obj)  
plot(wv)
```

(Run time: 3.70 [sec])

# Visualizing the data

## The function `wvar()`

It is obviously possible to plot the WV from the axis of an accelerometer or gyroscope individually



### R code:

```
WV.gx = wvar(imu6[,1])  
plot(WV.gx)
```

(Run time: 0.65 [sec])

The Allan variance can also be computed through the function `avar()`

## The `gmwm.imu()` function

The function tailor-made for IMU error modeling is `gmwm.imu()`

## Main arguments of the `gmwm.imu()` function

- `model`: The structure of the model is specified through this argument
- `data`: The signal to be modelled
- `compute.v`: The method for computing the weighting matrix  $\Omega$ 
  - `fast`: Estimated diagonal matrix
  - `diag`: Use a diagonal matrix with the asymptotic variance of  $\hat{\nu}$
  - `bootstrap`: Estimate  $\Omega$  through parametric bootstrap

## The model argument

The GMWM package can estimate each specific model or any latent model made by a combination of all or a subset of the following models

- `AR1()`: a first-order autoregressive process (reparametrization of Gauss-Markov process)
- `WN()`: white noise process
- `QN()`: quantization noise (rounding error)
- `RW()`: random walk process
- `DR()`: drift
- `AR()`:  $p$ -order autoregressive process
- `MA()`:  $q$ -order moving average process
- `ARMA()`: autoregressive-moving average processes

# GMWM estimation

## Latent model syntax

To specify a latent model we use the sign “+” between the available models while the `AR1()` model can be included more than once (say  $k$  times) and is can be specified as `k*AR1()`, for example

- `ARMA()+WN()+RW()`
- `3*AR1()+DR()`

## Convergence


If the `gmwm.imu()` function has problems of convergence, one can specify **starting values** for the parameters using the brackets in the syntax of each model (e.g. `WN(sigma2=0.5)`)



# GMWM estimation

## Visually assessing the fit

The function `plot()` applied to the object of a GMWM estimation allows to see how well the WV implied by the estimated model fits the observed WV



## R code:


```
mod = gmwm.imu(3*AR1(),  
imu6[,1]) plot(mod,  
process.decomp = T)
```

(Run time: 0.56 [sec] )

# Model Comparison

Suppose we want to compare three models...

AR1(), 2\*AR1() and 3\*AR1()



R code:

```
Xt = imu[,1]
m1 = gmwm.imu(AR1(),Xt)
m2 = gmwm.imu(2*AR1(),Xt)
m3 = gmwm.imu(3*AR1(),Xt)
compare.models(m1, m2, m3)
```

(Run time: 5.20 [sec])

# Inference

## Output of estimation

Aside from the value of the estimated parameters, the output of the function `gmwm.imu` provides other information for inference which include **confidence intervals** and **goodness of fit** test (GoF)

```
mod = gmwm.imu(2*AR1(), imu6[,1])  
summary(mod, inference = T)
```

Model Information:

	Estimates	CI Low	CI High	SE
AR1	9.998700e-01	9.998336e-01	9.999064e-01	2.211547e-05
SIGMA2	5.223319e-11	4.343878e-11	6.102759e-11	5.346620e-12
AR1	1.265324e-01	1.265324e-01	1.265324e-01	1.765050e-08
SIGMA2	5.031185e-05	5.021566e-05	5.040805e-05	5.848209e-08

\* The initial values of the parameters used in the minimization of the GMM objective function were generated by the program underneath seed: 1337.

Objective Function: 20.9297

Asymptotic Goodness of Fit:

Test Statistic: 903.8 on 15 degrees of freedom

The resulting p-value is: 0

# WIC model selection

## Two options for model selection

- **Manual:** the function `rank.models()` allows the user to specify the set of models from which to select
- **Automatic:** the function `auto.imu()` allows to specify one single model from which all sub-models are generated to create a set from which to select

### R code:

```
rank.models(3*AR1()+WN(),  
2*AR1()+QN(), imu6[,1], nested =  
F, bootstrap = F, model.type="imu",  
robust = F)
```

```
mod.res = auto.imu(imu6, model  
= 3*AR1()+WN()+RW()+QN()+DR(),  
bootstrap = F, robust = F)
```

# WIC model selection

## Automatic IMU model selection

Suppose we want to apply the `auto.imu()` function to the X-axis gyroscope in the `imu` dataset and consider all model combinations within the  $4*AR1() + WN() + RW()$  model

```
Xt = imu6[,1]
mod = 4*AR1()+WN()+RW()
mod.sel = auto.imu(Xt, model = mod)
summary(mod.sel)
```

The model ranking for data column 1:


				Obj Fun	Optimism	Criterion	GoF	P-Value
1.	AR1	AR1	AR1	17.2769	0.2974	17.5743		0
2.	AR1	AR1	AR1 RW	17.2679	0.3139	17.5818		0
3.	AR1	AR1	AR1 AR1	17.6022	0.4330	18.0351		0
4.	AR1	AR1	RW	20.1044	0.4871	20.5915		0
5.	AR1	AR1		20.9864	0.2070	21.1933		0
...								
19.	RW			28420.4972	0.0160	28420.5132		0

(Run time: 50.25 [sec]  $\approx$  14x faster than the bootstrap option 685.4 [sec])

# WIC Model Selection

## Visualizing the Automatic IMU Model Selection

We can observe the results of the `auto.imu()` function by requesting a plot. The plot will contain the empirical wavelet variance in addition to the best implied wavelet variance that we find. In this particular case, we used the defaults of the `auto.imu()` (63 models  $\times$  6 columns).



### R code:

```
imu.obj = imu(imu6, gyroscope = 1:3,  
accelerometer = 4:6, axis = c('X',  
'Y', 'Z'))  
auto.mod = auto.imu(imu.obj)  
plot(auto.mod)  
(Run time: 377.77 [sec])
```

# Upcoming features

Aside from **fine-tuning existing features** of the package (additional options, function optimization, support documentation, etc.), the GMWM package will be updated with the following features

- Sensor calibration under **dynamic conditions**

$$Y_t = \rho_t Y_{t-1} + \epsilon_t$$

- **Multivariate latent models**

$$Y_t^{(x)} = V_t + W_t^{(x)}$$

$$Y_t^{(y)} = V_t + W_t^{(y)}$$

$$Y_t^{(z)} = V_t + W_t^{(z)}$$

- Others (e.g. additional moments for the GMWM (AGMWM), other wavelet filters, unit-root and independence testing)

# Thank you very much for your attention!

A special thanks to

- Dr. Yannick Stebler (EPFL/u-blox)
- Prof. Maria-Pia Victoria-Feser (U. Geneva)
- Wenchao Yang (UIUC)

## Any questions?



More info...



[SMAC-group.com](http://SMAC-group.com)



[github.com/SMAC-Group](https://github.com/SMAC-Group)



[stephane@illinois.edu](mailto:stephane@illinois.edu)