

Mill housing with accessories, 4-high

Maintenance**7 Maintenance**

Target groups O, E, M, C



Definition of the target groups:

- Operating Instructions *General*,
Chapter *Introduction/target groups*.



Observe the following information:

- Operating Instructions *General*,
Chapter *Safety*,
Chapter *Maintenance*,
- *Subsuppliers'* Operating Instructions,
- Operating Instructions *Electrics*.

7.1 Maintenance schedule

Area	Inspection	Action	OC	TI
General	▪ Fastening	▪ Fasten	P	Y
	▪ Damage (condition)	▪ Replace ▪ Repair	P	M
	▪ Function	▪ Repair	N	S
	▪ Unusual noises	▪ Eliminate the cause	N	M
	▪ Wear	▪ Replace ▪ Repair	P	M
	▪ Contamination	▪ Clean	P	M
Limit switch	▪ Function	▪ Adjust ▪ Replace ▪ Repair	Z	M
Fluid line, fluid connection	▪ Leaks	▪ Replace ▪ Repair	P	M
	▪ Volumetric flow rate	▪ Set volumetric flow rate	N	M
Guide	▪ Function	▪ Adjust clearance ▪ Replace	R	Y

Maintenance

Area	Inspection	Action	OC	TI
	▪ Lubrication of sliding liners	▪ Clean slide liners ▪ Grease slide liners	P	M
Centralized lubrication	▪ Oil volume	▪ Adapt	P	B1
	▪ Oil quality	▪ replace	P	B1
	▪ Temperature	▪ Adjust ▪ Adapt	P	B1
Cylinder	▪ Function	▪ Replace ▪ Repair ▪ Set speed	N	S
	▪ Bearing assembly	▪ Fasten ▪ Replace ▪ Repair	P	Y
	▪ Seal	▪ Replace ▪ Repair	P	M

Operating condition (OC)

N	Normal operation (production)
P	Stop (maintenance, troubleshooting)
R	Repair
Z	Enabling mode

Time interval (TI)

S	every shift (8 hours)
**M	every month
**Y	every year
B1	According to supplier's specifications
**) Intervals together with numbers mean, for example: 3M= every three months	

NOTICE

In the first three months after commissioning, the pipework must be inspected every two weeks. This allows leaks to be detected at an early stage.