

SMPTE STANDARD - CD

Interoperable Master Format —  
Application #4 Cinema  
Mezzanine



| Table of Contents |  | Page |
|-------------------|--|------|
| 1                 | Scope .....  | 2    |
| 2                 | Conformance Notation .....                         | 3    |
| 3                 | Normative References .....                         | 3    |
| 4                 | Overall .....                                      | 4    |
| 5                 | Image Essence .....                                | 5    |
| 6                 | Track Files .....                                  | 8    |
| 7                 | Composition .....                                  | 15   |
| 8                 | DCDM Composition .....                             | 16   |
| 9                 | Pixel Color Schemes .....                          | 17   |
| Annex A           | SMPTE Label definitions (Normative) .....          | 18   |
| Annex B           | Active Area Rectangle Examples (Informative) ..... | 19   |
| Annex C           | Pixel Color Schemes Definition (Normative) .....   | 20   |
|                   | Bibliography (Informative) .....                   | 23   |

## Foreword

SMPTE (the Society of Motion Picture and Television Engineers) is an internationally-recognized standards developing organization. Headquartered and incorporated in the United States of America, SMPTE has members in over 80 countries on six continents. SMPTE's Engineering Documents, including Standards, Recommended Practices, and Engineering Guidelines, are prepared by SMPTE's Technology Committees. Participation in these Committees is open to all with a bona fide interest in their work. SMPTE cooperates closely with other standards-developing organizations, including ISO, IEC and ITU.

SMPTE Engineering Documents are drafted in accordance with the rules given in its Standards Operations Manual.

SMPTE ST 2067-40 was prepared by Technology Committee 35PM.

The following summarizes the substantive changes made from SMPTE ST 2067-40:2016, as amended by ST 2067-40:2016 Am1:2017, to this edition:

- support is added for image and timed text essence that conform to the D-Cinema Distribution Master as specified in the SMPTE ST 428 family of documents (sub-clause 5.2 and 6.3);
- the SMPTE labels identifying the image transfer characteristics supported by this document are modified (sub-clause 6.1.3.1.2);
- constraints on the Composition timeline and contents are relaxed (clause 7); and
- constraints on Display Mastering Metadata are clarified and relaxed (sub-clause 6.1.3.1.5)

## Intellectual Property

At the time of publication no notice had been received by SMPTE claiming patent rights essential to the implementation of this Engineering Document. However, attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. SMPTE shall not be held responsible for identifying any or all such patent rights.

## 1 Scope

This document specifies compositions for IMF Application #4. IMF Application #4 is a specialization of the IMF Framework. It is intended for the exchange and preservation of cinematographic content after digital postproduction, either sourced from film or from digital media. In particular, it supports Digital Cinema Distribution Master (DCDM) content as specified in the ST 428 family of specifications.

To simplify implementation, IMF Application #4 reuses constraints from IMF Application #2 whenever appropriate.

## 2 Conformance Notation

Normative text is text that describes elements of the design that are indispensable or contains the conformance language keywords: "shall", "should", or "may". Informative text is text that is potentially helpful to the user, but not indispensable, and can be removed, changed, or added editorially without affecting interoperability. Informative text does not contain any conformance keywords.

All text in this document is, by default, normative, except: the Introduction, any section explicitly labeled as "Informative" or individual paragraphs that start with "Note:"

The keywords "shall" and "shall not" indicate requirements strictly to be followed in order to conform to the document and from which no deviation is permitted.

The keywords, "should" and "should not" indicate that, among several possibilities, one is recommended as particularly suitable, without mentioning or excluding others; or that a certain course of action is preferred but not necessarily required; or that (in the negative form) a certain possibility or course of action is deprecated but not prohibited.

The keywords "may" and "need not" indicate courses of action permissible within the limits of the document.

The keyword "reserved" indicates a provision that is not defined at this time, shall not be used, and may be defined in the future. The keyword "forbidden" indicates "reserved" and in addition indicates that the provision will never be defined in the future.

A conformant implementation according to this document is one that includes all mandatory provisions ("shall") and, if implemented, all recommended provisions ("should") as described. A conformant implementation need not implement optional provisions ("may") and need not implement them as described.

Unless otherwise specified, the order of precedence of the types of normative information in this document shall be as follows: Normative prose shall be the authoritative definition; Tables shall be next; followed by formal languages; then figures; and then any other language forms.

## 3 Normative References

The following standards contain provisions which, through reference in this text, constitute provisions of this standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this standard are encouraged to investigate the possibility of applying the most recent edition of the standards indicated below.

SMPTE ST 400:2012, SMPTE Labels Structure

SMPTE ST 379-1:2009, Material Exchange Format (MXF) — MXF Generic Container

SMPTE ST 422:2019, Material Exchange Format — Mapping JPEG 2000 Codestreams into the MXF Generic Container

SMPTE ST 428-1:2019 - D-Cinema Distribution Master — Image Characteristics

SMPTE ST 428-7:2014 - Digital Cinema Distribution Master — Subtitle

SMPTE ST 428-10:2008 - D-Cinema Distribution Master — Closed Caption and Closed Subtitle

SMPTE ST 428-11:2013 - Additional Frame Rates for D-Cinema

SMPTE ST 428-21:2011 - Archive Frame Rates for D-Cinema

SMPTE ST 429-5:2017 - D-Cinema Packaging — Timed Text Track File

SMPTE ST 2067-2:2020, Interoperable Master Format — Core Constraints

SMPTE ST 2067-21:2020, Interoperable Master Format — Application 2E

SMPTE ST 2067-101:2018, Interoperable Master Format – Output Profile List – Common Image Definitions and Macros

SMPTE ST 2067-102:2017, Interoperable Master Format - Common Image Pixel Color Schemes

ISO 11664-3:2012 (CIE S014-3/E:2011), Colorimetry — Part 3: CIE Tristimulus Values

ISO/IEC 15444-1:2019, Information Technology — JPEG 2000 Image Coding System: Core Coding System

World Wide Web Consortium (W3C) (2004, October 28). XML Schema Part 1: Structures (Second Edition)

World Wide Web Consortium (W3C) (2004, October 28). XML Schema Part 2: Datatypes (Second Edition)

EDITOR'S NOTE: Highlighted UL and URI values defined herein are temporary and will be replaced by their final values prior to publication, at which point this note will be removed.

## 4 Overall

### 4.1 General

All provisions of SMPTE ST 2067-2 shall apply.

### 4.2 Format

Track Files shall conform to SMPTE ST 379-1.

### 4.3 XML Schema and Namespace

XML elements defined by this specification shall conform to the XML schema definitions (see W3C XML Schema Part 1: Structures) found in this specification. In the event of a conflict between schema definitions and the prose, the prose shall take precedence.

The XML schema root element shall be as defined in Table 1.

**Table 1 – XML Schema root element definition.**

```
<xs:schema targetNamespace="http://www.smp-te-ra.org/ns/2067-40/2020"
  xmlns:app4="http://www.smp-te-ra.org/ns/2067-40/2020"
  xmlns:xs="http://www.w3.org/2001/XMLSchema"
  elementFormDefault="qualified" attributeFormDefault="unqualified">
```

```
<!-- schema definitions found in this document -->  
</xs:schema>
```

## **5 Image Essence**

### **5.1 General**

Image essence shall consist of image frames, each a rectangular pixel array.

### **5.2 Constraints**

Image frames shall conform to the combinations of characteristics allowed in Table 2.

**Table 2 – Image Characteristics**

|                         | General characteristics  |         |         | DCDM characteristics |
|-------------------------|--|---------|---------|----------------------|
| Image Frame Width       | 1..2048  | 1..4096 | 1..8192 | See 5.3.1            |
| Image Frame Height      | 1..1556  | 1..3112 | 1..6224 |                      |
| Pixel Bit Depth         | 16   |         |         | 12                   |
| Frame Structure         | Progressive  |         |         |                      |
| Stereoscopy             | Monoscopic<br>Stereoscopic   |         |         |                      |
| Frame Rate              | 16<br>200/11<br>20<br>240/11<br>24<br>25<br>30<br>48<br>50<br>60<br>100<br>120 |         |         | See 5.3.2            |
| Sampling                | 4:4:4  |         |         |                      |
| Color Components §5.3.3 | $X_{TC}Y_{TC}Z_{TC}$   |         |         |                      |
| Colorimetry §5.3.4      | COLOR.APP4.1   |         |         | COLOR.APP4.2         |
| Quantization §5.3.5     | QE.APP4  |         |         |                      |

### 5.3 Characteristics

#### 5.3.1 DCDM characteristics size constraints

For the DCDM characteristics, combinations of image height and width shall be as specified at SMPTE ST 428-1.

#### 5.3.2 DCDM characteristics Frame Rate

For the DCDM characteristics, the frame rate values shall be as specified at SMPTE ST 428-1, SMPTE ST 428-11 and SMPTE ST 428-21.

#### 5.3.3 Color Components

The image shall be sampled using  $X_{TC}Y_{TC}Z_{TC}$  component triplets, as defined in 5.3.4.

### 5.3.4 Colorimetry

The  $X_{TC}Y_{TC}Z_{TC}$  components triplet shall be mapped to the XYZ tristimulus values specified in ISO 11664-3, as specified in Table 3.

**Table 3 – Colorimetry systems**

| System                                | Description  |
|---------------------------------------|--|
| COLOR.APP4.1                          | $X_{TC} = X \times 10^3 \div 65535, X \in [0, 52.37]$              |
|                                       | $Y_{TC} = Y \times 10^3 \div 65535, Y \in [0, 48]$                 |
|                                       | $Z_{TC} = Z \times 10^3 \div 65535, Z \in [0, 52.37]$              |
| COLOR.APP4.2                          | $X_{TC} = \left(\frac{X}{L_{vw}}\right)^{1/2.6}, X \in [0, 52.37]$ |
|                                       | $Y_{TC} = \left(\frac{Y}{L_{vw}}\right)^{1/2.6}, Y \in [0, 52.37]$ |
|                                       | $Z_{TC} = \left(\frac{Z}{L_{vw}}\right)^{1/2.6}, Z \in [0, 52.37]$ |
| where $L_{vw} = 52.37 \text{ cd/m}^2$ |  |

NOTE: The combination of the COLOR.APP4.2 colorimetry system and the QE.APP4 quantization system is mathematically equivalent to the color encoding specified at Section 4 of SMPTE ST 428-1:2019.

### 5.3.5 Quantization

The  $X_{TC}Y_{TC}Z_{TC}$  components triplet shall use the quantization equation as specified in Table 4.

**Table 4 – Quantization Systems**

| System  | Quantization equations                               |
|---------|--|
| QE.APP4 | $CV(X_{TC}) = \text{ROUND}[(2^n - 1) \times X_{TC}]$ |
|         | $CV(Y_{TC}) = \text{ROUND}[(2^n - 1) \times Y_{TC}]$ |
|         | $CV(Z_{TC}) = \text{ROUND}[(2^n - 1) \times Z_{TC}]$ |
|         | where $n$ is the pixel bit depth                     |

The ROUND(x) operator returns the largest integral value not greater than x if the fractional part of x is less than 0.5; or the smallest integral not less than x, if the fractional part of x is greater or equal to 0.5.

## 5.4 Encoding

### 5.4.1 Single Codestream

Each frame shall be a single codestream, as specified in ISO/IEC 15444-1.

### 5.4.2 Profile and Operating Levels

The JPEG 2000 profile and operating level for each image frame dimension shall conform to Table 5.

**Table 5 – JPEG 2000 Profiles**

|                            |  |  |   |
|----------------------------|--|--|---|
| Image Frame Width          | 1..2048  | 1..4096  | 1..8192   |
| Image Frame Height         | 1..1556  | 1..3112  | 1..6224   |
| JPEG 2000 Profile          | 2k IMF single/multi-tile reversible profile  | 4k IMF single/multi-tile reversible profile  | 8k IMF single/multi-tile reversible profile   |
| JPEG 2000 Operating Levels | Mainlevel 1 Sublevel 0<br>Mainlevel 2 Sublevel 0<br>Mainlevel 3 Sublevel 0<br>Mainlevel 4 Sublevel 0<br>Mainlevel 5 Sublevel 0<br>Mainlevel 6 Sublevel 0 | Mainlevel 1 Sublevel 0<br>Mainlevel 2 Sublevel 0<br>Mainlevel 3 Sublevel 0<br>Mainlevel 4 Sublevel 0<br>Mainlevel 5 Sublevel 0<br>Mainlevel 6 Sublevel 0<br>Mainlevel 7 Sublevel 0<br>Mainlevel 8 Sublevel 0 | Mainlevel 1 Sublevel 0<br>Mainlevel 2 Sublevel 0<br>Mainlevel 3 Sublevel 0<br>Mainlevel 4 Sublevel 0<br>Mainlevel 5 Sublevel 0<br>Mainlevel 6 Sublevel 0<br>Mainlevel 7 Sublevel 0<br>Mainlevel 8 Sublevel 0<br>Mainlevel 9 Sublevel 0<br>Mainlevel 10 Sublevel 0 |

The JPEG 2000 profile should be selected such that its maximum supported image frame dimensions (as specified in Table 5) are the smallest encompassing the image frame dimensions. Similarly, the JPEG 2000 operating level should be selected such that the image essence does not conform to any lower operating level.

### 5.4.3 Component Ordering

In a codestream, color components shall be ordered as specified in Table 6.

**Table 6 – JPEG 2000 Color Component Ordering**

| Component Index | $X_{TC}Y_{TC}Z_{TC}$ Component |
|-----------------|--------------------------------|
| 0               | $X_{TC}$                       |
| 1               | $Y_{TC}$                       |
| 2               | $Z_{TC}$                       |

## 6 Track Files

### 6.1 Image Track Files

#### 6.1.1 Essence

Image Track Files shall contain image essence conforming to Section 5.

#### 6.1.2 Shim Parameters

Track Files shall be associated with the shim parameter values specified in Table 7.



**Table 7 – Image track file Shim Parameter Values Definitions**

| <b>Shim Parameter</b> | <b>Value</b>  |
|-----------------------|---|
| shim_id               | <a href="http://www.smp-te-ra.org/ns/2067-40/2020/shims#image">http://www.smp-te-ra.org/ns/2067-40/2020/shims#image</a> |
| gc_type               | 379-1-gc  |
| picture_family        | JPEG2000  |
| picture_bitrate       | ST 2067-40  |
| picture_format        | ST 2067-40  |
| picture_custom_ANC    | false   |
| picture_render_ANC    | false   |

### 6.1.3 Wrapping

Image Track Files shall conform to SMPTE ST 422.

The image essence shall be wrapped according to mode P1 specified in SMPTE ST 422 ("Frame-wrapping").

The Top-Level File Package of Image Track Files shall reference an RGBA Picture Essence Descriptor.

#### 6.1.3.1 Generic Picture Essence Descriptor

##### 6.1.3.1.1 General

The Generic Picture Essence Descriptor items (including those specified in SMPTE ST 2067-2) shall be constrained as specified in Table 8.

**Table 8 – Generic Picture Essence Descriptor Items**

| <b>Generic Picture Essence<br/>Descriptor Item</b> | <b>Constraints</b>                                       |
|--|--|
| Sample Rate  | See Annex A of SMPTE ST 422.                             |
| Signal Standard                                    | Shall be ignored by the decoder.                         |
| Frame Layout                                       | 00h (FULL_FRAME)   |
| Stored Width                                       | Shall be equal to Image Frame Width. See Table 2.        |
| Stored Height                                      | Shall be equal to Image Frame Height. See Table 2.       |
| StoredF2Offset                                     | Shall not be present.                                    |
| Sampled Width                                      | Shall not be present or shall be equal to Stored Width.  |
| Sampled Height                                     | Shall not be present or shall be equal to Stored Height. |
| SampledXOffset                                     | Shall not be present or shall be 0.                      |

|  |   |
|--|---|
| SampledYOffset                             | Shall not be present or shall be 0.   |
| DisplayWidth                               | Shall not be present or shall be equal to Stored Width.   |
| DisplayHeight                              | Shall not be present or shall be equal to Stored Height.  |
| DisplayXOffset                             | Shall not be present or shall be 0.   |
| DisplayYOffset                             | Shall not be present or shall be 0.   |
| ActiveWidth                                | Annex B of this specification and Annex G in SMPTE ST 2067-2 provide examples.  |
| ActiveHeight                               |   |
| ActiveXOffset                              | Note: Unless explicitly set, the Active Area Rectangle is by default equal to the Display Rectangle, as specified in SMPTE ST 2067-2. |
| ActiveYOffset                              |   |
| DisplayF2Offset                            | Shall not be present.   |
| Aspect Ratio                               | Shall be present.<br>Annex B provides examples.   |
| Active Format Descriptor                   | Shall be ignored by the decoder   |
| Video Line Map                             | Shall be ignored by the decoder.  |
| Alpha Transparency                         | Shall not be present.   |
| Transfer Characteristic                    | Shall be present. See Section 6.1.3.1.2.  |
| Image Alignment Offset                     | Shall not be present.   |
| Image Start Offset                         | Shall not be present.   |
| Image End Offset                           | Shall not be present.   |
| FieldDominance                             | Shall not be present.   |
| Picture Essence Coding                     | Shall be present. See Section 6.1.3.1.4.  |
| Coding Equations                           | Shall not be present.   |
| Color Primaries                            | Shall be present. See Section 6.1.3.1.3.  |
| Alternative Center Cuts                    | Shall be ignored by the decoder.  |
| Mastering Display Primaries                | Should be present. See Section 6.1.3.1.5.   |
| Mastering Display White Point Chromaticity | Should be present. See Section 6.1.3.1.5.   |

### 6.1.3.1.2 Transfer Characteristic

The value of the Transfer Characteristic item shall be equal to one of the following:

- the label specified at Table A.2 if the COLOR.APP4.1 system is used.
- the label specified at Table A.3 if the COLOR.APP4.2 system is used.

#### 6.1.3.1.3 Color Primaries

The value of the Color Primaries item shall be equal to the label specified at Table A.1.

#### 6.1.3.1.4 Picture Essence Coding

The value of the Picture Essence Coding item shall indicate the JPEG 2000 profile and operating level of the image essence.

NOTE: The SMPTE Labels register defined by SMPTE ST 400 defines a UL for each of the JPEG 2000 profiles and operating levels listed in Section 5.4.2.

#### 6.1.3.1.5 Mastering Display Color Volume Metadata

Either none or both of the Mastering Display Primaries and Mastering Display White Point Chromaticity items as defined in SMPTE ST 2067-21 shall be present.

If the items are absent, no information on the mastering display is available.

Example 1: Table 9 lists example values of the Mastering Display Primaries item.

**Table 9 – Commonly used values of the Mastering Display Primaries item (Informative)**

| Value  | Notes   |
|--|---|
| {<br>{ 34000, 16000 },<br>{ 13250, 34500 },<br>{ 7500, 3000 }<br>} | Corresponds to the RGB color<br>primaries, in order, of the<br>reference projector defined in<br>SMPTE ST 2113 :<br>Red (0.6800, 0.3200),<br>Green (0.2650,0.6900),<br>Blue (0.1500,0.0600) |

Example 2: Table 10 lists example value of the Mastering Display White Point Chromaticity item.

**Table 10 – Commonly used values of the Mastering Display White Point Chromaticity item (Informative)**

| Value  |                  | Notes  |
|--------|------------------|--|
| {<br>} | { 15700, 17550 } | Corresponds to the white chromatic coordinates referenced as P3DCI in SMPTE ST 2113 : White (0.3140,0.3510).       |
| {<br>} | { 15635, 16450 } | Corresponds to the white chromatic coordinates referenced as P3D65 in SMPTE ST 2113 : White (0.3127, 0.3290).      |
| {<br>} | { 15990, 16800 } | Corresponds to the white chromatic coordinates as defined in SMPTE EG 432-1 : D61 White {0.3198, 0.3360}           |
| {<br>} | { 16085, 16890 } | Corresponds to the white chromatic coordinates referenced as P3D60 in SMPTE ST 2113 : D60 White (0.32168,0.33767). |
| {<br>} | { 16620, 17370 } | Corresponds to the white chromatic coordinates as defined in SMPTE EG 432-1 : D55 White (0.3324,0.3474)            |

### 6.1.3.2 RGBA Picture Essence Descriptor

#### 6.1.3.2.1 General

The RGBA Picture Essence Descriptor items shall be constrained as specified in Table 11.

**Table 11 – RGBA Essence Descriptor items**

| RGBA Picture Essence Descriptor Item | Constraints                                 |
|--------------------------------------|---|
| Component Max Ref                    | Shall be present. See Section 6.1.3.2.2.    |
| Component Min Ref                    | Shall be present. See Section 6.1.3.2.2.    |
| Alpha Max Ref                        | Shall not be present.                       |
| Alpha Min Ref                        | Shall not be present.                       |
| ScanningDirection                    | Shall be present and shall be equal to 00h. |
| PixellLayout                         | Shall be present. See Section 6.1.3.2.3.    |
| Palette                              | Shall not be present.                       |

|               |                       |
|---------------|-----------------------|
| PaletteLayout | Shall not be present. |
|---------------|-----------------------|

#### 6.1.3.2.2 Component Max Ref and Component Min Ref

The values of the Component Max Ref and Component Min Ref items shall be as specified in Table 12.

**Table 12 – Component Max Ref and Component Min Ref values**

|                          |       |      |
|--------------------------|-------|------|
| <b>Pixel Bit Depth</b>   | 16    | 12   |
| <b>Component Min Ref</b> | 0     | 0    |
| <b>Component Max Ref</b> | 65535 | 4095 |

#### 6.1.3.2.3 PixelLayout

The value of the PixelLayout item shall be equal to { D8h, n, D9h, n, DAh, n, 0, 0, 0, 0, 0, 0, 0, 0, 0 } where n is the pixel bit depth.

#### 6.1.3.3 JPEG 2000 Picture Sub Descriptor

##### 6.1.3.3.1 General

The Top-Level File Package of the Image Track File shall reference a JPEG 2000 Picture Sub Descriptor SMPTE ST 422 as constrained by Table 13.

**Table 13 – JPEG 2000 Picture Subdescriptor items**

| <b>JPEG 2000 Picture Subdescriptor Item</b> | <b>Constraints</b>                       |
|---|--|
| Coding Style Default                        | Shall be present.                        |
| J2CLayout                                   | Shall be present. See Section 6.1.3.3.2. |

##### 6.1.3.3.2 J2CLayout

The value of the J2CLayout item shall be equal to the PixelLayout item of the RGBA Descriptor (see Section 6.1.3.2.3).

#### 6.2 Audio Track Files

Each Audio Track File shall contain at least one audio channel.

#### 6.3 DCDM Timed Text Track Files

##### 6.3.1 General

A DCDM Timed Text Track File is a Track File that conforms to Section 6.3 of this document.

A Timed Text Track File primarily contains timed Text essence, e.g. subtitle and caption.

The DataEssenceCoding item shall not be present in a Timed Text Track File.

### 6.3.2 Shim Parameters

A DCDM Timed Text Track File is associated with the shim parameter values specified in Table 14

**Table 14 – DCDM Timed-text track file Shim Parameter Values Definitions**

| Shim Parameter        | Value   |
|-----------------------|---|
| shim_id               | http://www.smp-te-ra.org/ns/2067-40/2020/shims#timed-text |
| gc_type               | 379-1-gc  |
| data_family           | ST 428-7, ST 428-10                                       |
| data_file_arrangement | ST 429-5  |

### 6.3.3 Wrapping

DCDM Timed Text Track Files shall conform to SMPTE ST 429-5.

The Timed Text Resource shall contain a single Document Instance that conforms to SMPTE ST 428-7.

### 6.3.4 NamespaceURI

The NamespaceURI item of the Timed Text Descriptor shall be equal to the XML namespace name of the top-level XML element of the Document Instance.

### 6.3.5 RFC 5646 Language Tag List

The Timed Text Descriptor may contain the RFC 5646 Language Tag List property specified at SMPTE ST 2067-2. The value of the property shall indicate the languages associated with the data essence within the Data Essence Track File. Absence of the property shall indicate that no language is associated with the Data Essence Track File.

if the Language element of the SubtitleReel element of the Timed Text Resource is present, the RFC 5646 Language Tag List property shall be present and shall include one instance of the value of the Language element.

### 6.3.6 ResourceID

The ResourceID property of the Timed Text Descriptor shall be equal to the Id element of the SubtitleReel element of the Timed Text Resource.

### 6.3.7 Image Resources

For each Image element in the Timed Text Resource, an Ancillary Resource shall exist in the Track File such that the AncillaryResourceID of Ancillary Resource is equal to the value of the Image element. This Ancillary Resource contains the external image resource referenced by the Image element.

### 6.3.8 Font Resources

For each LoadFont element in the Timed Text Resource, an Ancillary Resource shall exist in the Track File such that the AncillaryResourceID of Ancillary Resource is equal to the ID attribute of the LoadFont element. This Ancillary Resource contains the font resource referenced by the LoadFont element.

## 7 Composition

### 7.1 Application Identification

The ApplicationIdentification element (as defined in SMPTE ST 2067-2) shall include exactly one instance of the value listed in Table 15.

**Table 15 – Application Identification**

|   |
|---|
| <a href="http://www.smpte-ra.org/ns/2067-40/2020">http://www.smpte-ra.org/ns/2067-40/2020</a> |
|---|

### 7.2 Homogeneous Essence

Within a given composition, the following shall remain constant:

- all image essence characteristics specified in Section 5.2 and 5.3.
- the codestream profile and level combination (see Section 5.4.2).

### 7.3 ContentKind

The ContentKind element shall be present in the Composition Playlist.

### 7.4 Creator

The Creator element shall be present in the Composition Playlist.

### 7.5 Issuer

The Issuer element shall be present in the Composition Playlist.

### 7.6 CompositionTimecode

If Composition edit rate is equal to one of the values listed in Table 16, the CompositionTimecode element of the Composition Playlist instance shall not be present.

**Table 16 – Edit rates not suitable for use with the CompositionTimecode element.**

| Frame Rate |
|------------|
| 16         |
| 200/11     |
| 20         |
| 240/11     |

NOTE: The frame rates listed in Table 16 cannot be represented by the CompositionTimecode element.

## 7.7 DCDM Timed Text Virtual Tracks

A Composition shall contain zero or more DCDM Timed Text Virtual Tracks.

Each DCDM Timed Text Virtual Track shall consist of one or more instances of one of the element specified in Table 17.

**Table 17 – DCDM Timed Text Sequence schema definition.**

```
<xs:element name="DCDMMainSubtitleSequence" type="cpl:SequenceType"/>
<xs:element name="DCDMMainCaptionSequence" type="cpl:SequenceType"/>
<xs:element name="DCDMClosedSubtitleSequence" type="cpl:SequenceType"/>
<xs:element name="DCDMClosedCaptionSequence" type="cpl:SequenceType"/>
```

Each Resource elements within a DCDM Timed Text Virtual Track:

- shall be of type TrackFileResourceType
- shall reference a DCDM Timed Text Track File that conforms to Section 6.3 and is constrained according to Table 18.
- shall have a native start point corresponding to time coordinate 0 in the timeline of the underlying Track File.
- shall have a native duration equal to or larger than the time coordinate after which no element will be active in the timeline of the underlying Track File.

**Table 18 – DCDM Timed Text Sequence essence constraints kind.**

| <i>Sequence Element</i>    | <i>Constraints</i> | <i>Description</i>   |
|----------------------------|--------------------|--|
| DCDMMainSubtitleSequence   | SMPTE ST 428-7     | Subtitle essence to be reproduced on the main screen in the auditorium.              |
| DCDMMainCaptionSequence    | SMPTE ST 428-10    | Open caption essence to be reproduced on the main screen of the auditorium.          |
| DCDMClosedSubtitleSequence | SMPTE ST 428-10    | Closed Subtitle essence to be reproduced on closed-style displays in the auditorium. |
| DCDMClosedCaptionSequence  | SMPTE ST 428-10    | Closed Caption essence to be reproduced on closed-style displays in the auditorium.  |

## 8 DCDM Composition

A DCDM Composition is intended to be transformed into a Composition specified in SMPTE ST 429-2.

A DCDM Composition shall conform to Section 7 and to the following constraints:

- the image essence shall conform to the DCDM characteristics specified in Table 2; and
- the ApplicationIdentification element of the Composition shall include exactly one instance of the value specified in Table 19.

**Table 19. DCDM Composition identification.**

```
http://www.smp-te-ra.org/ns/2067-40-DCDM/2020
```



## **9 Pixel Color Schemes**

Annex C defines Pixel Color Schemes, as specified in SMPTE ST 2067-101, for the use with IMF Application #4.

NOTE: Annex C is for the sole purpose of enabling Output Profile List (OPL) processing of Application #4 IMF packages.

## Annex A SMPTE Label definitions (Normative)

**Table A.1 – Cinema Mezzanine Color Primaries**

|                   |   |
|-------------------|---|
| <b>Name</b>       | Cinema Mezzanine Color Primaries  |
| <b>Symbol</b>     | ColorPrimaries_CinemaMezzanine  |
| <b>Namespace</b>  | http://www.smp-te-ra.org/reg/400/2012   |
| <b>Item UL</b>    | urn:smp-te:ul:060e2b34.0401010d.04010101.03080000   |
| <b>Definition</b> | Colors are sampled as the X, Y and Z tristimulus values specified in ISO 11664-3 (No color primaries are specified) |

**Table A.2 – Cinema Mezzanine Linear Transfer Characteristic**

|                   |   |
|-------------------|---|
| <b>Name</b>       | Cinema Mezzanine Linear Transfer Characteristic                                   |
| <b>Symbol</b>     | TransferCharacteristic_CinemaMezzanineLinear                                      |
| <b>Namespace</b>  | http://www.smp-te-ra.org/reg/400/2012   |
| <b>Item UL</b>    | urn:smp-te:ul:060e2b34.0401010d.04010101.01120000                                 |
| <b>Definition</b> | Identifies the COLOR.APP4.1 transfer characteristic specified in SMPTE ST 2067-40 |

**Table A.3 – Cinema Mezzanine DCDM Transfer Characteristic**

|                   |   |
|-------------------|---|
| <b>Name</b>       | Cinema Mezzanine DCDM Transfer Characteristic                                     |
| <b>Symbol</b>     | TransferCharacteristic_CinemaMezzanineDCDM  |
| <b>Namespace</b>  | http://www.smp-te-ra.org/reg/400/2012   |
| <b>Item UL</b>    | urn:smp-te:ul:060e2b34.0401010d.04010101.01130000                                 |
| <b>Definition</b> | Identifies the COLOR.APP4.2 transfer characteristic specified in SMPTE ST 2067-40 |

## Annex B     Active Area Rectangle Examples (Informative)

Table B.1 provides examples of the use of active area and aspect ratio for selected image frame sizes.

**Table B.1 – Example Image Frame Size**

|                  | 1.85 aspect<br>ratio image<br>within a 2K<br>container<br>(with black<br>bands) | 1.85 aspect<br>ratio image<br>within a 4K<br>container<br>(with black<br>bands) | 16/9 aspect<br>ratio image<br>within a 2K<br>container<br>(without black<br>bands) | 2.39 aspect<br>ratio image<br>within a 2K<br>container<br>(without<br>black bands) |
|------------------|---|---|--|--|
| Stored Width     | 2048  | 4096  | 1920   | 2048   |
| Stored Height    | 1556  | 3112  | 1080   | 858  |
| StoredF2FOffset  | 0   | 0   | 0  | 0  |
| Sampled Width    | 2048  | 4096  | 1920   | 2048   |
| Sampled Height   | 1556  | 3112  | 1080   | 858  |
| Sampled X Offset | 0   | 0   | 0  | 0  |
| Sampled Y Offset | 0   | 0   | 0  | 0  |
| Display Width    | 2048  | 4096  | 1920   | 2048   |
| Display Height   | 1556  | 3112  | 1080   | 858  |
| Display X Offset | 0   | 0   | 0  | 0  |
| Display Y Offset | 0   | 0   | 0  | 0  |
| Aspect Ratio     | 2048/1556   | 4096/3112   | 16/9   | 1024/429   |
| Active Width     | 2048  | 4096  | 1920   | 2048   |
| Active Height    | 1106  | 2212  | 1080   | 858  |
| Active X Offset  | 0   | 0   | 0  | 0  |
| Active Y Offset  | 215   | 430   | 0  | 0  |

## Annex C Pixel Color Schemes Definition (Normative)

### C.1 XML Schema Definition

XML elements defined by this Annex shall conform to the XML schema definitions (see W3C XML Schema Part 1: Structures and W3C XML Schema Part 2: Datatypes) found in this specification. In the event of a conflict between schema definitions and the prose, the prose shall take precedence.

The XML schema root element for Pixel Color Schemes shall be as defined in Table C.1.

**Table C.1. XML Schema root element definition**

```
<?xml version="1.0" encoding="UTF-8"?>
<xs:schema targetNamespace="http://www.smpte-ra.org/ns/2067-40/2020/opl-color-
  scheme"
  xmlns:oplcs="http://www.smpte-ra.org/ns/2067-101/2018/color-schemes"
  xmlns:oplc="http://www.smpte-ra.org/ns/2067-102/2017/"
  xmlns:app4cs="http://www.smpte-ra.org/ns/2067-40/2020/opl-color-
    scheme"
  xmlns:xs="http://www.w3.org/2001/XMLSchema"
  elementFormDefault="qualified" attributeFormDefault="unqualified">
  <xs:import namespace="http://www.smpte-ra.org/ns/2067-101/2018/color-schemes"/>
  <xs:import namespace="http://www.smpte-ra.org/ns/2067-102/2017"/>
  <!-- schema definitions found in this document excluding this one -->
</xs:schema>
```

### C.2 APP4-XYZ-12

The APP4-XYZ-12 color scheme shall be as specified in Table C.2. The mathematical functions "floor(x)" and "clamp(a, b, x)" in Table C.1 shall be as defined in SMPTE ST 2067-102. The XML datatype Integer4096TripletType shall be as defined in SMPTE ST 2067-102.

**Table C.2. APP4-XYZ-12 Color Scheme**

|                                    |   |
|------------------------------------|---|
| Name                               | APP4-XYZ-12   |
| URI                                | http://www.smpte-ra.org/ns/2067-40/2020/opl-color-scheme#APP4-XYZ-12  |
| Description                        | $X_{TC}$ , $Y_{TC}$ and $Z_{TC}$ components as specified in Section 5.3.4, using 12-bit bit depth, COLOR.APP4.2 colorimetry and QE.APP4 quantization system.  |
| Mapping from Reference Image Pixel | $X_{TC} = \text{floor}(4095 \cdot \text{clamp}(0, 1, P_1) + 0.5)$<br>$Y_{TC} = \text{floor}(4095 \cdot \text{clamp}(0, 1, P_2) + 0.5)$<br>$Z_{TC} = \text{floor}(4095 \cdot \text{clamp}(0, 1, P_3) + 0.5)$ |
| Mapping to Reference Image Pixel   | $P_1 = X_{TC} / 4095$<br>$P_2 = Y_{TC} / 4095$<br>$P_3 = Z_{TC} / 4095$<br>$P_4 = 1.0$  |
| Pixel Encoding Type                | <pre>&lt;xs:complexType name="APP4-XYZ-12-ColorEncodingType"&gt;   &lt;xs:simpleContent&gt;     &lt;xs:restriction base="oplcs:ColorEncodingType"&gt;       &lt;xs:simpleType&gt;</pre>                     |

```

    <xs:restriction base="oplc:Integer4096TripletType"/>
  </xs:simpleType>
</xs:restriction>
</xs:simpleContent>
</xs:complexType>

```

The three elements of the triplet shall correspond to the  $X_{TC}$ ,  $Y_{TC}$  and  $Z_{TC}$  components.

### C.3 APP4-XYZ-16

The APP4-XYZ-16 color scheme shall be as specified in Table C.3. The mathematical functions "floor(x)" and "clamp(a, b, x)" in Table C.1 shall be as defined in ST 2067-102. The XML datatype Integer65536TripletType shall be as defined in ST 2067-102.

**Table C.3. APP4-XYZ-16 Color Scheme**

|                                    |  |
|------------------------------------|--|
| Name                               | APP4-XYZ-16  |
| URI                                | <a href="http://www.smpte-ra.org/ns/2067-40/2020/opl-color-scheme#APP4-XYZ-16">http://www.smpte-ra.org/ns/2067-40/2020/opl-color-scheme#APP4-XYZ-16</a>  |
| Description                        | $X_{TC}$ , $Y_{TC}$ and $Z_{TC}$ components as specified in Section 5.3.4, using 16-bit bit depth, COLOR.APP4.1 colorimetry and QE.APP4 quantization system.   |
| Mapping from Reference Image Pixel | $X_{TC} = \text{floor}(65535 \cdot \text{clamp}(0, 1, P_1) + 0.5)$<br>$Y_{TC} = \text{floor}(65535 \cdot \text{clamp}(0, 1, P_2) + 0.5)$<br>$Z_{TC} = \text{floor}(65535 \cdot \text{clamp}(0, 1, P_3) + 0.5)$   |
| Mapping to Reference Image Pixel   | $P_1 = X_{TC} / 65535$<br>$P_2 = Y_{TC} / 65535$<br>$P_3 = Z_{TC} / 65535$<br>$P_4 = 1.0$  |
| Pixel Encoding Type                | <pre> &lt;xs:complexType name="APP4-XYZ-16-ColorEncodingType"&gt;   &lt;xs:simpleContent&gt;     &lt;xs:restriction base="oplcs:ColorEncodingType"&gt;       &lt;xs:simpleType&gt;         &lt;xs:restriction base="oplc:Integer65536TripletType"/&gt;       &lt;/xs:simpleType&gt;     &lt;/xs:restriction&gt;   &lt;/xs:simpleContent&gt; &lt;/xs:complexType&gt; </pre> |

The three elements of the triplet shall correspond to the  $X_{TC}$ ,  $Y_{TC}$  and  $Z_{TC}$  components.

### C.4 Consolidated Schema (Informative)

This specification is accompanied by the following element, which is an XML schema document as specified in W3C XML Schema Part 1: Structures.

st2067-40a-2020.xsd

This element collects the XML schema definitions defined in this specification. It is informative and, in case of conflict, this specification takes precedence.

## **Bibliography (Informative)**

SMPTE EG 432-1:2010, Digital Source Processing — Color Processing for D-Cinema

SMPTE RP 431-2:2011, D-Cinema Quality — Reference Projector and Environment

SMPTE ST 2113:2018, Colorimetry of P3 Color Spaces