



Quantum Coding Course

Ali Kookani
Yousef Mafi

Summer 2024



www.quantumatlas.ir



QuantumSTEM



About us

Quantum Atlas is an educational group which aims to educate people in various fields of quantum, from hardware to software and quantum machine learning.

www.quantumatlas.ir

[QuantumSTEM](#)

[Quantum Atlas](#)

به اطلس کوانتوم خوش آمدید.
اهتمامی جامع شما در قلمرو پیچیده فناوری‌های کوانتومی

The Evolution of Physics
کتاب تکنولوژی‌های کوانتومی
کتاب مقدمات ریاضی و فیزیک مکانیک کوانتوم

QuantumSTEM
QuantumTEQ@
QAdmission@
Q_STEM@
lme/QuantumSTEM
Notifications off
Media Saved Files Links Similar C



Syllabus



Section 1	Lecture 1	Quantum Computation and Information (Theoretical lecture) – By Y. Mafi
	Lecture 2	Quantum Circuits (Coding lecture) – By A. Kookani
Section 2	Lecture 3	Quantum Simulation (Coding lecture) – By A. Kookani
	Lecture 4	IBMQ and Error Correction (Implementation and Theoretical lecture) – By Y. Mafi
Section 3	Lecture 5	Quantum Algorithm (Theoretical lecture) – By Y. Mafi
	Lecture 6	Quantum Algorithm Simulation (Coding lecture) – By A. Kookani





Challenge 2

How can we implement the following circuit based on the coupling map? (only use CNOT gates)







Challenge 2

How can we implement the following circuit based on the coupling map? (only use CNOT gates)

Answer:







Challenge 2

How can we implement the following circuit based on the coupling map? (only use CNOT gates)

Answer:






Swap gate

❖ **Purpose:** The SWAP gate exchanges the states of two qubits.

❖ **Operation:**

- **Inputs:** Two qubits, Qubit q0 and Qubit q1.
- **Outputs:** The states of Qubit q0 and Qubit q1 are swapped.

$$\text{Swap} = \begin{bmatrix} 1 & 0 & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix}$$



$$\begin{aligned} |\psi\rangle = |q_0 q_1\rangle &= (\alpha_0|0\rangle + \alpha_1|1\rangle) \otimes (\beta_0|0\rangle + \beta_1|1\rangle) \\ &= \alpha_0\beta_0|00\rangle + \alpha_0\beta_1|01\rangle + \alpha_1\beta_0|10\rangle + \alpha_1\beta_1|11\rangle \end{aligned}$$



$$\begin{aligned} \text{Swap}|\psi\rangle = |\psi'\rangle &= \alpha_0\beta_0|00\rangle + \alpha_0\beta_1|10\rangle + \alpha_1\beta_0|01\rangle + \alpha_1\beta_1|11\rangle \\ &= (\beta_0|0\rangle + \beta_1|1\rangle) \otimes (\alpha_0|0\rangle + \alpha_1|1\rangle) \end{aligned}$$



Challenge 2

How can we implement the following circuit based on the coupling map? (only use CNOT gates)

Answer:







Challenge 2

How can we implement the following circuit based on the coupling map? (only use CNOT gates)

Answer:



Coupling map



Today

01

Quantum Properties

02

Deutsch-Jozsa Algorithm

(Quantum Phase Kick-Back)

03

Quantum Teleportation

(Quantum Entanglement)

04

Grover's Algorithm

(Quantum Superposition)

01

Quantum Properties



www.quantumatlas.ir



QuantumSTEM



Quantum Properties

❖ Superposition:

A quantum bit (qubit) can exist in multiple states simultaneously → parallel computations

❖ Entanglement:

The state of one qubit is directly related to the state of another, even when separated by large distances → process complex correlations between qubits

❖ Quantum Interference:

Quantum states can interfere with each other, leading to constructive or destructive interference → phase kickback effect

❖ Quantum Tunneling

Quantum particles can "tunnel" through barriers that would be insurmountable in classical physics → quantum annealing and optimization



02

Deutsch-Jozsa Algorithm



Deutsch Algorithm

- It solves the problem of determining whether a given function $f(x)$ is **constant** or **balanced**.
- Deutsch's Algorithm achieves this with only a single evaluation of the function by leveraging quantum superposition and interference.
- Time Complexity: Quantum $\mathcal{O}(1)$ Vs. Classic $\mathcal{O}(2^n)$



Deutsch Algorithm

1 $|\psi_0\rangle = |q_0 q_1\rangle = |00\rangle$

2 $|\psi_1\rangle = (H \otimes HX)|\psi_0\rangle = (H \otimes HX)|00\rangle$


$$|\psi_1\rangle = |+ -\rangle = \left(\frac{1}{\sqrt{2}}|0\rangle + \frac{1}{\sqrt{2}}|1\rangle \right) \otimes \left(\frac{1}{\sqrt{2}}|0\rangle - \frac{1}{\sqrt{2}}|1\rangle \right) |q_1\rangle$$

$$|\psi_1\rangle = \frac{1}{2}(|00\rangle - |01\rangle + |10\rangle - |11\rangle)$$

3 $|\psi_2\rangle = U_{oracle}|\psi_1\rangle \rightarrow$ Assume $f(x)$ is zero-constant function:

$$|\psi_2\rangle = \frac{1}{2}(U_{oracle}|\underbrace{00\rangle}_{|xy\rangle} - U_{oracle}|\overbrace{01\rangle} + U_{oracle}|\overbrace{10\rangle} - U_{oracle}|\overbrace{11\rangle})$$

$$|\psi_2\rangle = \frac{1}{2}(\underbrace{|0\rangle|0 \oplus 0\rangle}_{|x\rangle|y \oplus f(x)\rangle} - |0\rangle|1 \oplus 0\rangle + |1\rangle|0 \oplus 0\rangle - |1\rangle|1 \oplus 0\rangle)$$



x	f(x)
0	0
1	0

Zero-Constant



Deutsch Algorithm

1 $|\psi_0\rangle = |q_0 q_1\rangle = |00\rangle$

2 $|\psi_1\rangle = \frac{1}{2}(|00\rangle - |01\rangle + |10\rangle - |11\rangle)$


3 Assume $f(x)$ is zero-constant function:

$$|\psi_2\rangle = \frac{1}{2}(|0\rangle|0\rangle - |0\rangle|1\rangle + |1\rangle|0\rangle - |1\rangle|1\rangle)$$

$$|\psi_2\rangle = |+\ -\rangle$$

4 $|\psi_3\rangle = (H \otimes I)|\psi_2\rangle = (H \otimes I)|+\ -\rangle = |0-\rangle$

Ignore $|q_1\rangle$: $|\psi_3\rangle = |q_0\rangle = |0\rangle \rightarrow f(x)$ is constant if measurement of $|q_0\rangle$ become 0.





Deutsch Algorithm

1 $|\psi_0\rangle = |q_0 q_1\rangle = |00\rangle$

2 $|\psi_1\rangle = \frac{1}{2}(|00\rangle - |01\rangle + |10\rangle - |11\rangle)$


3 Assume $f(x)$ is balanced function:

$$|\psi_2\rangle = \frac{1}{2}(U_{oracle}|00\rangle - U_{oracle}|01\rangle + U_{oracle}|10\rangle - U_{oracle}|11\rangle)$$

$$|\psi_2\rangle = \frac{1}{2}(|0\rangle|0\oplus 1\rangle - |0\rangle|1\oplus 1\rangle + |1\rangle|0\oplus 0\rangle - |1\rangle|1\oplus 0\rangle)$$

$$|\psi_2\rangle = \frac{1}{2}(|0\rangle|1\rangle - |0\rangle|0\rangle + |1\rangle|0\rangle - |1\rangle|1\rangle) = |--\rangle$$

4 $|\psi_3\rangle = (H \otimes I)|\psi_2\rangle = (H \otimes I)|--\rangle = |1-\rangle$



Ignore $|q_1\rangle$: $|\psi_3\rangle = |q_0\rangle = |1\rangle \rightarrow f(x)$ is balanced if measurement of $|q_0\rangle$ become 1.



Deutsch-Jozsa Algorithm

1) $|\psi_0\rangle = |q_0 q_1 q_2\rangle = |000\rangle$


2) $|\psi_1\rangle = \frac{1}{2\sqrt{2}}(|000\rangle - |001\rangle + |010\rangle - |011\rangle + |100\rangle - |101\rangle + |110\rangle - |111\rangle)$

3) 1) Assume $f(x)$ is constant function:

$$|\psi_2\rangle = \frac{1}{2\sqrt{2}}(|001\rangle - |000\rangle + |011\rangle - |010\rangle + |101\rangle - |100\rangle + |111\rangle - |110\rangle)$$

2) Assume $f(x)$ is balanced function:

$$|\psi_2\rangle = \frac{1}{2\sqrt{2}}(|001\rangle - |000\rangle + |010\rangle - |011\rangle + |100\rangle - |101\rangle + |111\rangle - |110\rangle)$$



x_1	x_1	$f(x)$
0	0	1
0	1	1
1	0	1
1	1	1

One-constant

x_1	x_1	$f(x)$
0	0	1
0	1	0
1	0	0
1	1	1

Balanced



Deutsch-Jozsa Algorithm

1) $|\psi_0\rangle = |q_0 q_1 q_2\rangle = |000\rangle$


2) $|\psi_1\rangle = \frac{1}{2\sqrt{2}}(|000\rangle - |001\rangle + |010\rangle - |011\rangle + |100\rangle - |101\rangle + |110\rangle - |111\rangle)$

3) 1) Assume $f(x)$ is constant function:
 $|\psi_2\rangle = |+++-\rangle$

2) Assume $f(x)$ is balanced function:


$$|\psi_2\rangle = |---\rangle$$

- 4) 1) $|\psi_3\rangle = (H \otimes H \otimes I)|\psi_2\rangle = (H \otimes H \otimes I)|---\rangle = |00-\rangle \rightarrow$ Ignore $|q_2\rangle$: $|\psi_3\rangle = |q_0 q_1\rangle = |00\rangle$ Constant.
- 2) $|\psi_3\rangle = (H \otimes H \otimes I)|\psi_2\rangle = (H \otimes H \otimes I)|---\rangle = |11-\rangle \rightarrow$ Ignore $|q_2\rangle$: $|\psi_3\rangle = |q_0 q_1\rangle = |11\rangle$ Balanced.



Deutsch-Jozsa Algorithm

- An extension of Deutsch's Algorithm.
- Classical Algorithm: $2^{n-1} + 1$ queries $\rightarrow \mathcal{O}(2^n)$
- The Deutsch-Jozsa Algorithm: **just one query $\rightarrow \mathcal{O}(1)$**



03

Quantum Teleportation



www.quantumatlas.ir




QuantumSTEM



Quantum Entanglement

- Two or more qubits become intertwined such that the state of one qubit instantaneously influences the state of the other, no matter the distance separating them.
- It is a key resource for quantum computing, quantum communication, and quantum cryptography.
- When two qubits are entangled, their individual quantum states **cannot be described independently**; they must be considered as part of **a combined system**.




Bell-state

$$|AB\rangle = \frac{|00\rangle + |11\rangle}{\sqrt{2}}$$



Quantum Teleportation

- Quantum teleportation is a process by which the quantum state of a particle (such as a qubit) is transmitted from one location to another,
- without physically moving the particle itself.
- This process relies on quantum entanglement and classical communication.





Quantum Teleportation

1 $|\psi_0\rangle = |q_A q_a q_b\rangle = |000\rangle$

2 $|\psi_1\rangle = (\alpha|0\rangle + \beta|1\rangle) \otimes \left(\frac{|00\rangle + |11\rangle}{\sqrt{2}} \right)$


$$|\psi_1\rangle = \frac{1}{\sqrt{2}}(\alpha|000\rangle + \alpha|011\rangle + \beta|100\rangle + \beta|111\rangle)$$

3 $|\psi_2\rangle = \frac{1}{\sqrt{2}}(CNOT \otimes I)(\alpha|000\rangle + \alpha|011\rangle + \beta|100\rangle + \beta|111\rangle)$

$$|\psi_2\rangle = \frac{1}{\sqrt{2}}(H \otimes I \otimes I)(\alpha|000\rangle + \alpha|011\rangle + \beta|110\rangle + \beta|101\rangle)$$

$$|\psi_2\rangle = \frac{1}{\sqrt{2}}(\alpha|000\rangle + \alpha|011\rangle + \alpha|100\rangle + \alpha|111\rangle - \beta|110\rangle + \beta|001\rangle - \beta|110\rangle + \beta|001\rangle)$$

4 $|\psi_2\rangle = \frac{1}{\sqrt{2}}(\alpha|000\rangle + \alpha|011\rangle + \alpha|100\rangle + \alpha|111\rangle - \beta|110\rangle + \beta|001\rangle - \beta|110\rangle + \beta|001\rangle)$





Quantum Teleportation

1 $|\psi_0\rangle = |q_A q_a q_b\rangle = |000\rangle$


2 $|\psi_1\rangle = (\alpha|0\rangle + \beta|1\rangle) \otimes \left(\frac{|00\rangle + |11\rangle}{\sqrt{2}} \right)$

$$|\psi_1\rangle = \frac{1}{\sqrt{2}}(\alpha|000\rangle + \alpha|011\rangle + \beta|100\rangle + \beta|111\rangle)$$

3 $|\psi_2\rangle = \frac{1}{\sqrt{2}}(\alpha|000\rangle + \alpha|011\rangle + \alpha|100\rangle + \alpha|111\rangle - \beta|110\rangle + \beta|001\rangle - \beta|110\rangle + \beta|001\rangle)$

4 $|\psi_3\rangle = \frac{1}{4}(\alpha|0\rangle + \alpha|1\rangle + \alpha|0\rangle + \alpha|0\rangle + \beta|1\rangle + \beta|1\rangle + \beta|1\rangle + \beta|1\rangle)$

$|\psi_3\rangle = |q_b\rangle = \alpha|0\rangle + \beta|1\rangle$ Teleported state!!!




04

Grover's Algorithm



Grover's Algorithm



- A quadratic speedup for unstructured search problems (unsorted database).
- classical algorithms: N operations to search through N items $\rightarrow \mathcal{O}(N)$
- Grover's Algorithm: \sqrt{N} operations to search through N items $\rightarrow \mathcal{O}(\sqrt{N})$
- We need $\approx \sqrt{N}$ iteration





Grover's Algorithm

1 $|\psi_0\rangle = |q_0 q_1\rangle = |00\rangle$





Grover's Algorithm

1 $|\psi_0\rangle = |q_0 q_1\rangle = |00\rangle$

2 $|\psi_1\rangle = (H \otimes H)|00\rangle$

$$|\psi_1\rangle = \frac{1}{2}(|00\rangle + |01\rangle + |10\rangle + |11\rangle)$$



Grover's Algorithm

1 $|\psi_0\rangle = |q_0 q_1\rangle = |00\rangle$

2 $|\psi_1\rangle = \frac{1}{2}(|00\rangle + |01\rangle + |10\rangle + |11\rangle)$



3 $|\psi_2\rangle = \frac{1}{2}U_o(|00\rangle + |01\rangle + |10\rangle + |11\rangle)$

$$U_o = I - 2|s\rangle\langle s| \quad |s\rangle: \text{the desired state}$$

Assume $|s\rangle = |01\rangle$:

$$U_o = \begin{bmatrix} 1 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix} - 2 \begin{bmatrix} 0 \\ 1 \\ 0 \\ 0 \end{bmatrix} \begin{bmatrix} 0 & 1 & 0 & 0 \end{bmatrix}$$

$$U_o = \begin{bmatrix} 1 & 0 & 0 & 0 \\ 0 & -1 & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix}$$





Grover's Algorithm


1 $|\psi_0\rangle = |q_0 q_1\rangle = |00\rangle$

2 $|\psi_1\rangle = \frac{1}{2}(|00\rangle + |01\rangle + |10\rangle + |11\rangle)$

3 $|\psi_2\rangle = \frac{1}{2} U_o (|00\rangle + |01\rangle + |10\rangle + |11\rangle)$

$$|\psi_2\rangle = \begin{bmatrix} 1 & 0 & 0 & 0 \\ 0 & -1 & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix} \frac{1}{2} \begin{bmatrix} 1 \\ 1 \\ 1 \\ 1 \end{bmatrix}$$

$$|\psi_2\rangle = \frac{1}{2} \begin{bmatrix} 1 \\ -1 \\ 1 \\ 1 \end{bmatrix} = \frac{1}{2} (|00\rangle - |01\rangle + |10\rangle + |11\rangle)$$






Grover's Algorithm

- 1 $|\psi_0\rangle = |q_0 q_1\rangle = |00\rangle$
- 2 $|\psi_1\rangle = \frac{1}{2}(|00\rangle + |01\rangle + |10\rangle + |11\rangle) \rightarrow |\phi\rangle$
- 3 $|\psi_2\rangle = \frac{1}{2}(|00\rangle - |01\rangle + |10\rangle + |11\rangle)$
- 4 $|\psi_3\rangle = \frac{1}{2}U_D(|00\rangle - |01\rangle + |10\rangle + |11\rangle)$

$$U_D = 2|\phi\rangle\langle\phi| - I \quad |\phi\rangle: \text{the basic state}$$

$$U_D = 2 \begin{bmatrix} 0.5 \\ 0.5 \\ 0.5 \\ 0.5 \end{bmatrix} [0.5 \quad 0.5 \quad 0.5 \quad 0.5] - \begin{bmatrix} 1 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix}$$

$$U_D = \begin{bmatrix} -0.5 & +0.5 & +0.5 & +0.5 \\ +0.5 & -0.5 & +0.5 & +0.5 \\ +0.5 & +0.5 & -0.5 & +0.5 \\ +0.5 & +0.5 & +0.5 & -0.5 \end{bmatrix} \dots \dots \dots \dots$$




Grover's Algorithm

- 1 $|\psi_0\rangle = |q_0 q_1\rangle = |00\rangle$
- 2 $|\psi_1\rangle = \frac{1}{2}(|00\rangle + |01\rangle + |10\rangle + |11\rangle) \rightarrow |\phi\rangle$
- 3 $|\psi_2\rangle = \frac{1}{2}(|00\rangle - |01\rangle + |10\rangle + |11\rangle)$
- 4 $|\psi_3\rangle = \frac{1}{2}U_D(|00\rangle - |01\rangle + |10\rangle + |11\rangle)$

$$|\psi_3\rangle = \frac{1}{2} \begin{bmatrix} -0.5 & +0.5 & +0.5 & +0.5 \\ +0.5 & -0.5 & +0.5 & +0.5 \\ +0.5 & +0.5 & -0.5 & +0.5 \\ +0.5 & +0.5 & +0.5 & -0.5 \end{bmatrix} \begin{bmatrix} 1 \\ -1 \\ 1 \\ 1 \end{bmatrix}$$



$$|\psi_3\rangle = \begin{bmatrix} 0 \\ 1 \\ 0 \\ 0 \end{bmatrix} = |01\rangle \rightarrow |s\rangle$$





Grover's Algorithm

Step 0: Initialization







Grover's Algorithm

Step 1: Superposition

We need $\approx \sqrt{4} = 2$ iteration.







Grover's Algorithm

Step 2: Apply oracle (iteration 1)


Assume $|0010\rangle$ is $|s\rangle$





Grover's Algorithm


Step 3: Apply Diffuser (iteration 1)





Grover's Algorithm



Step 4: Apply Oracle (iteration 2)





Grover's Algorithm

Step 4: Apply Diffuser (iteration 2)





Coding time ;)
