

# Frame Analysis Report



Analyzed File:	MecanumFrame2.iam
Version:	2018 (Build 220112000, 112)
Creation Date:	5/12/2017, 1:22 PM
Simulation Author:	P136265
Summary:	

## Project Info (iProperties)

### Summary

Author Bryce Richards

### Project

Part Number	MecanumFrame2
Designer	Bryce Richards
Cost	\$0.00
Date Created	18/10/2017

### Status

Design Status WorkInProgress

### Physical

Mass	15.104 kg
Area	24299.036 mm <sup>2</sup>
Volume	1924.043 mm <sup>3</sup>
Center of Gravity	x=1.408 mm y=0.000 mm z=66.257 mm

## Simulation:1

### General objective and settings:

Simulation Type	Static Analysis
Last Modification Date	5/12/2017, 1:20 PM

### Material(s)

Name	Steel, Mild	
General	Mass Density	7.850 g/cm <sup>3</sup>
	Yield Strength	207.000 MPa
	Ultimate Tensile Strength	345.000 MPa
Stress	Young's Modulus	220.000 GPa
	Poisson's Ratio	0.275 ul
Part Name(s)	AS C350L0 35x35x1.6 SHS 00000033.ipt AS C350L0 35x35x1.6 SHS 00000037.ipt AS C350L0 35x35x1.6 SHS 00000036.ipt AS C350L0 35x35x1.6 SHS 00000038.ipt AS C350L0 35x35x1.6 SHS 00000023.ipt AS C350L0 35x35x1.6 SHS 00000026.ipt AS C350L0 35x35x1.6 SHS 00000027.ipt AS C350L0 35x35x1.6 SHS 00000028.ipt AS C350L0 35x35x1.6 SHS 00000031.ipt AS C350L0 35x35x1.6 SHS 00000032.ipt AS C350L0 35x35x1.6 SHS 00000029.ipt AS C350L0 35x35x1.6 SHS 00000030.ipt AS C350L0 35x35x1.6 SHS 00000024.ipt AS C350L0 35x35x1.6 SHS 00000025.ipt AS C350L0 35x35x1.6 SHS 00000039.ipt AS C350L0 35x35x1.6 SHS 00000040.ipt AS C350L0 35x35x1.6 SHS 00000041.ipt AS C350L0 35x35x1.6 SHS 00000042.ipt	

### Cross Section(s)

Geometry Properties	Section Area (A)	207.167 mm <sup>2</sup>
---------------------	------------------	-------------------------

	Section Width	35.000 mm
	Section Height	35.000 mm
	Section Centroid (x)	17.500 mm
	Section Centroid (y)	17.500 mm
Mechanical Properties	Moment of Inertia ( $I_x$ )	37886.231 mm <sup>4</sup>
	Moment of Inertia ( $I_y$ )	37886.231 mm <sup>4</sup>
	Torsional Rigidity Modulus (J)	56773.490 mm <sup>4</sup>
	Section Modulus ( $W_x$ )	2164.927 mm <sup>3</sup>
	Section Modulus ( $W_y$ )	2164.927 mm <sup>3</sup>
	Torsional Section Modulus ( $W_z$ )	3250.771 mm <sup>3</sup>
	Reduced Shear Area ( $A_x$ )	94.494 mm <sup>2</sup>
	Reduced Shear Area ( $A_y$ )	94.494 mm <sup>2</sup>
Part Name(s)	AS C350L0 35x35x1.6 SHS 00000033.ipt AS C350L0 35x35x1.6 SHS 00000037.ipt AS C350L0 35x35x1.6 SHS 00000036.ipt AS C350L0 35x35x1.6 SHS 00000038.ipt AS C350L0 35x35x1.6 SHS 00000023.ipt AS C350L0 35x35x1.6 SHS 00000026.ipt AS C350L0 35x35x1.6 SHS 00000027.ipt AS C350L0 35x35x1.6 SHS 00000028.ipt AS C350L0 35x35x1.6 SHS 00000031.ipt AS C350L0 35x35x1.6 SHS 00000032.ipt AS C350L0 35x35x1.6 SHS 00000029.ipt AS C350L0 35x35x1.6 SHS 00000030.ipt AS C350L0 35x35x1.6 SHS 00000024.ipt AS C350L0 35x35x1.6 SHS 00000025.ipt AS C350L0 35x35x1.6 SHS 00000039.ipt AS C350L0 35x35x1.6 SHS 00000040.ipt AS C350L0 35x35x1.6 SHS 00000041.ipt AS C350L0 35x35x1.6 SHS 00000042.ipt	

## ▣ Beam Model

Nodes	38
Beams	18
- Square/Rectangular Tubes	18

## ▣ Rigid Links

Name	Displacement			Rotation			Parent Node	Child Node(s)
	X - axis	Y - axis	Z - axis	X - axis	Y - axis	Z - axis		
Rigid Link:1	fixed	fixed	fixed	fixed	fixed	fixed	Node:1	Node:18, Node:8
Rigid Link:2	fixed	fixed	fixed	fixed	fixed	fixed	Node:2	Node:19, Node:3
Rigid Link:4	fixed	fixed	fixed	fixed	fixed	fixed	Node:6	Node:23, Node:7
Rigid Link:5	fixed	fixed	fixed	fixed	fixed	fixed	Node:9	Node:17, Node:16
Rigid Link:6	fixed	fixed	fixed	fixed	fixed	fixed	Node:10	Node:20, Node:13
Rigid Link:7	fixed	fixed	fixed	fixed	fixed	fixed	Node:11	Node:21, Node:14
Rigid Link:8	fixed	fixed	fixed	fixed	fixed	fixed	Node:12	Node:24, Node:15
Rigid Link:3	fixed	fixed	fixed	fixed	fixed	fixed	Node:4	Node:22, Node:5
Rigid Link:9	fixed	fixed	fixed	fixed	fixed	fixed	Node:29	Node:37
Rigid Link:10	fixed	fixed	fixed	fixed	fixed	fixed	Node:30	Node:38

## ▣ Operating conditions



### ▣ Gravity

Load Type	Gravity
Magnitude	9810.000 mm/s <sup>2</sup>
Direction	Z+

### ▣ Force:2

Load Type	Force
Magnitude	9810.000 N
Beam Coordinate System	No
Angle of Plane	0.00 deg
Angle in Plane	0.00 deg
Fx	0.000 N
Fy	0.000 N
Fz	9810.000 N
Offset	385.000 mm


### ▣ Selected Reference(s)




Fixed Constraint:1

Constraint Type	Fixed
Offset	50.000 mm

Selected Reference(s)







☐ **Fixed Constraint:2**

Constraint Type	Fixed
Offset	750.000 mm

☐ **Selected Reference(s)**







Fixed Constraint:3

Constraint Type	Fixed
Offset	50.000 mm

Selected Reference(s)







Fixed Constraint:4

Constraint Type	Fixed
Offset	750.000 mm

Selected Reference(s)







Fixed Constraint:5

Constraint Type	Fixed
Offset	50.000 mm

Selected Reference(s)







Fixed Constraint:6

Constraint Type	Fixed
Offset	750.000 mm

Selected Reference(s)







Fixed Constraint:7

Constraint Type	Fixed
Offset	750.000 mm

Selected Reference(s)









Fixed Constraint:8

Constraint Type	Fixed
Offset	50.000 mm

Selected Reference(s)



## Results

### Reaction Force and Moment on Constraints



Constraint Name	Reaction Force		Reaction Moment	
	Magnitude	Components (Fx,Fy,Fz)	Magnitude	Components (Mx,My,Mz)
Fixed Constraint:1	4139.730 N	-3334.022 N	144728.396 N mm	-14821.158 N mm
		624.374 N		-142981.217 N mm
		-2373.145 N		-16823.006 N mm
Fixed Constraint:2	4146.483 N	3333.050 N	144806.508 N mm	-14871.551 N mm
		628.683 N		143038.605 N mm
		-2385.132 N		16962.289 N mm
Fixed Constraint:3	490.325 N	294.247 N	25153.721 N mm	-7265.628 N mm
		376.478 N		23083.655 N mm
		-110.009 N		6860.407 N mm
Fixed Constraint:4	488.724 N	-293.275 N	25274.558 N mm	-7287.975 N mm
		374.578 N		-23224.587 N mm
		-111.947 N		-6804.947 N mm
Fixed Constraint:5	4146.483 N	3333.050 N	144806.508 N mm	14871.551 N mm
		-628.683 N		143038.605 N mm
		-2385.132 N		-16962.289 N mm
Fixed Constraint:6	490.325 N	294.247 N	25153.721 N mm	7265.628 N mm
		-376.478 N		23083.655 N mm
		-110.009 N		-6860.407 N mm
Fixed Constraint:7	4139.730 N	-3334.022 N	144728.396 N mm	14821.158 N mm
		-624.374 N		-142981.217 N mm
		-2373.145 N		16823.006 N mm
Fixed Constraint:8	488.724 N	-293.275 N	25274.558 N mm	7287.975 N mm
		-374.578 N		-23224.587 N mm
		-111.947 N		6804.947 N mm

### Static Result Summary

Name		Minimum	Maximum
Displacement		0.000 mm	2.234 mm
Forces	Fx	-3021.311 N	6791.643 N
	Fy	-3627.297 N	3627.297 N
	Fz	-3490.474 N	3334.022 N
Moments	Mx	-346668.069 N mm	395722.707 N mm
	My	-291178.347 N mm	563522.224 N mm
	Mz	-74304.091 N mm	74304.091 N mm
Normal Stresses	Smax	0.009 MPa	262.416 MPa
	Smin	-258.176 MPa	8.419 MPa
	Smax(Mx)	-0.000 MPa	182.788 MPa
	Smin(Mx)	-182.788 MPa	0.000 MPa
	Smax(My)	0.000 MPa	260.296 MPa
	Smin(My)	-260.296 MPa	-0.000 MPa
	Saxial	-16.093 MPa	16.849 MPa
Shear Stresses	Tx	-71.874 MPa	31.974 MPa
	Ty	-38.387 MPa	38.387 MPa
Torsional Stresses	T	-22.857 MPa	22.857 MPa


### Figures

#### Displacement








▣ Fx









▣ Fy





Fz






☐ Mx










My







▣ Mz



Smax











☐ Smin







**Smax(Mx)**






☐ Smin(Mx)










Smax(My)







☐ Smin(My)





Saxial









▣ Tx





Ty





⊞ T





C:\Users\P136265\Documents\mecanum-cad\MecanumFrame2.iam