Product Requirements Document (PRD)

Multidimensional Wheel of Life Assessment

Document status: Draft for review
Product type: Web-based self-assessment application
Primary platform: Responsive web application
Initial build environment: Google Antigravity
Target audience: Women participating in a personal development and leadership assessment

---

1. Product Overview

1.1 Product vision

Create a structured online assessment that helps women evaluate the quality and development of different areas of their lives through specific, carefully designed indicators rather than arbitrary self-ratings.

The application will guide users through a series of questions for each life domain, calculate domain-level scores automatically, and reveal a visual representation of their results after they complete the entire assessment.

The product aims to make personal reflection more systematic, actionable, and evidence-informed.

1.2 Problem statement

Traditional Wheel of Life exercises typically ask participants to assign a score to each area of life on a scale of 1–10.

This approach relies heavily on subjective judgement. Two people with similar circumstances may assign very different scores because they interpret the scale differently. Users may also struggle to determine an appropriate score without reflecting on the specific behaviours, experiences, and indicators that define each area.

Consequently, the resulting wheel may provide a useful starting point for reflection but insufficient detail to explain why an area received a particular rating or what requires attention.

1.3 Proposed solution

Replace direct domain-level ratings with a multidimensional assessment.

Each life domain will contain a set of statements or questions designed to measure relevant indicators. Users will respond to each item individually. The system will calculate a domain

score using a predefined scoring model, keeping that score hidden until the entire assessment is complete.

Upon completion, users will receive a results dashboard containing a radar chart, domain scores, interpretation bands, and personalised insights derived from their responses.

1.4 Product objectives

1. Improve the structure and consistency of self-assessment across life domains.
2. Reduce arbitrary scoring by grounding domain scores in individual responses.
3. Maintain a focused assessment experience that does not reveal interim domain scores.
4. Help users identify strengths, areas requiring attention, and opportunities for growth.
5. Provide a reusable assessment framework that supports updates to questions, domains, scoring rules, and interpretation bands.
6. Create a foundation for future administrative reporting and participant management, if required.

1.5 Non-goals

The initial product will not:

- Diagnose psychological, medical, or mental health conditions.
- Present assessment scores as objective proof of a person's worth, character, or life success.
- Generate a single overall score representing the quality of a user's life.
- Include social networking, community features, or coaching marketplaces.
- Require payment, subscriptions, or user accounts unless subsequently approved.
- Allow users to view calculated domain scores before completing the assessment.

---

2. Target Users

Primary user

Women completing a personal development and leadership assessment who want to understand their current position across multiple life domains.

User needs

- Understand what the assessment measures and how to complete it.
- Answer questions privately and without unnecessary distractions.
- Understand each question before responding.
- Complete the assessment without seeing scores that could influence later answers.
- Receive a clear visual summary of their results.
- Understand why particular areas may require attention.
- Identify meaningful next steps based on their responses.

Administrator or assessment owner

The person responsible for maintaining the assessment framework, reviewing its performance, and managing question content.

Administrative capabilities are a proposed future requirement and are not necessary for the first working prototype.

---

3. Assessment Framework

3.1 Life domains

The initial assessment concept specifies 12 paths on the Wheel of Life.

Spirituality is the first defined path. The remaining domain names and their final order must be supplied and approved before the complete assessment is implemented.

Each domain must have:

- A unique identifier.
- A name and short description.
- A defined set of assessment indicators.
- A set of questions or statements mapped to those indicators.
- A scoring configuration.
- An interpretation framework.

3.2 Spirituality example

The Spirituality domain will be the first fully implemented assessment section.

Potential indicators include:

- Spiritual growth.
- Personal responsibility.
- Stewardship.
- Fruitfulness.
- Consistency of practice.
- Alignment between beliefs and actions.

These are preliminary examples, not an approved measurement framework. The final indicators and questions must be reviewed before the assessment is used for meaningful evaluation.

3.3 Question requirements

Each domain will contain 10 questions in the proposed initial model.

Questions must:

- Measure a clearly defined indicator relevant to the domain.
- Use simple, unambiguous language.
- Ask about one idea at a time.
- Avoid leading, judgemental, or unnecessarily moralising language.
- Use a consistent response method unless an alternative is deliberately specified.
- Have a documented relationship to the domain's scoring model.
- Be reviewed for relevance, clarity, and potential cultural bias.

The application must distinguish between a question's displayed wording and its underlying scoring configuration.

3.4 Response scale

The current concept proposes a 1–10 response scale.

The precise meaning of the scale must be established before the final question bank is written. For example, the scale might represent how consistently a statement describes the respondent.

The interface must explain the scale and display its meaning consistently throughout the assessment.

Open methodology decision: The previous assessment framework used YES = 2, SOMETIMES = 1, and NO = 0 with nine statements per domain. The proposed redesign uses 10 questions with a 1–10 scale. The product owner must approve one model before implementation is finalised.

---

4. User Journey and Functional Requirements

4.1 Welcome page

The first page introduces the assessment and explains:

- Its purpose.
- What the user will be asked to do.
- The approximate time required, once established through testing.
- How to respond to questions.
- When results will become available.
- How responses and results will be handled.

Acceptance criteria

- The user can understand the assessment before starting.
- A clearly visible Start Assessment action is available.
- No assessment scores are displayed.
- Privacy information is accessible before the user begins.

4.2 Assessment instructions

Before the first question, the user receives concise instructions explaining the response scale and the importance of answering honestly based on their actual experiences.

Acceptance criteria

- The instructions define each response option or scale anchor.
- The user can proceed to the first domain.
- The instructions remain accessible when needed.

4.3 Domain assessment

The application presents one domain at a time, beginning with Spirituality.

Each domain contains 10 questions under the current proposed model.

The user interface must include:

- Domain name and short introduction.
- Question wording.
- Response controls.
- Question-level progress.
- Overall assessment progress.
- Back and Next controls.
- A clear indication of unanswered required questions.

The interface must not display the calculated score for the current domain or any previously completed domain.

Acceptance criteria

- The user can select and revise a response.
- The user cannot proceed past a required question without answering it.
- Previously submitted responses remain available when navigating backwards.
- Progress indicators communicate completion without revealing scores.
- Scores are not included in visible interface content, URLs, or client-side state before final release.

4.4 Domain transitions

After completing all questions in a domain, the user proceeds to the next domain.

The application may display a neutral completion message, such as “Spirituality section completed,” without revealing the result.

Acceptance criteria

- Domain completion is recorded.
- The next domain becomes accessible according to the defined sequence.
- Domain scores remain hidden.
- The system prevents incomplete domains from being treated as fully assessed.

4.5 Assessment completion

After the final domain, the application verifies that all required responses have been recorded.

The system calculates the final domain scores and makes the results dashboard available.

Acceptance criteria

- The results page cannot be accessed through normal application navigation before all required questions are answered.
- Incomplete assessments cannot produce a complete radar chart.
- Repeated submissions do not create inconsistent or duplicate results.
- The results reflect the user's latest valid responses.

5. Scoring and Interpretation

5.1 Domain score calculation

For the proposed 1–10 scale, the score for each domain is the arithmetic mean of its 10 question responses.

Formula:

Domain score = Sum of valid question scores ÷ Number of valid question scores

For a complete domain containing 10 responses:

Domain score = Sum of the 10 responses ÷ 10

The calculated result must remain on the 1–10 scale.

5.2 Calculation rules

- Every required question must have a valid response.
- No unanswered question may be silently treated as zero.
- The system must use full-precision values for internal calculations.
- Displayed domain scores should be rounded to one decimal place.
- Interpretation bands must use the unrounded score to avoid classification errors.
- Scoring logic must be reusable across all domains.
- Scoring rules must be independently testable.

5.3 Provisional interpretation bands

The current proposed model uses three levels:

Score range	Interpretation	Meaning
1.0–3.9	Needs Attention	Responses indicate an area that may benefit from deliberate attention and development.
4.0–6.9	Developing	Responses suggest existing foundations alongside opportunities for improvement.
7.0–10.0	Strong Foundation	Responses suggest relatively strong foundations in this area.

These are provisional interpretation bands. The product owner must approve them after the final scale is confirmed.

The application must not interpret a low score as a personal failure or a high score as proof of excellence. The language should encourage constructive reflection.

5.4 No overall life score

The system must not combine the domain scores into a single overall life score.

Each domain represents a distinct area of life and must retain its own score and interpretation.

---

6. Results Dashboard

6.1 Results overview

After successful completion, the user sees a results page containing:

1. A completion confirmation.
2. A radar chart representing all 12 domain scores.
3. A score summary for each domain.
4. The interpretation band for each domain.
5. Areas of relative strength.
6. Areas that may need attention.
7. Personalised insights based on individual responses.
8. Suggested reflection prompts or next steps.

6.2 Radar chart

The chart must:

- Contain 12 axes, one per domain.
- Use a consistent 1–10 radial scale.
- Plot the calculated score for each domain.
- Display domain names clearly.
- Include accessible labels or an equivalent text-based summary.
- Update correctly when valid assessment responses change.
- Avoid implying that a low score in one domain makes a person less valuable or successful.

6.3 Domain score breakdown

Each domain must have a corresponding result summary containing:

- Domain name.
- Calculated score out of 10.
- Interpretation band.
- A concise explanation of the result.
- Relevant responses or indicators that inform the interpretation.
- Suggested areas for reflection or action.

6.4 Personalised feedback

Personalised feedback must be based on the respondent's actual answers, not percentages or domain scores alone.

The system should identify meaningful patterns across individual responses, explain why they matter within the assessment framework, and suggest relevant reflection prompts.

Feedback must not invent personal circumstances, infer diagnoses, or make unsupported claims about the respondent.

If automated AI-generated feedback is introduced later, it must use the recorded responses and approved assessment rules as its source of truth. A deterministic, template-based approach is sufficient for the first prototype.

---

7. Data and Privacy Requirements

7.1 Data collection

The application should collect only the information necessary to complete the assessment and provide results.

The initial prototype should not require an account unless persistent storage or identity management is approved.

7.2 Response storage

The implementation must clearly define whether responses are:

- Held temporarily in the active session.
- Stored persistently for users to revisit.
- Stored for authorised administrative analysis.

The first prototype may calculate results for the active session, but the production implementation must use an explicitly approved data-retention model.

7.3 Score confidentiality

Hiding scores in the interface is not sufficient to make them confidential.

If scores must remain inaccessible until assessment completion, the scoring and result-release process must be enforced by a trusted backend or equivalent secure mechanism.

The system must not rely solely on CSS, hidden HTML elements, or client-side conditions to enforce score confidentiality.

7.4 Security

The production application must:

- Use HTTPS.
- Validate responses on the server.
- Restrict access to stored responses and results.
- Protect administrative functions with authentication and appropriate authorisation.
- Avoid exposing private results through predictable URLs.
- Define retention and deletion procedures.
- Provide clear privacy information to participants.

---

8. Technical Requirements

8.1 Architecture

Use a modern, maintainable web architecture with clearly separated responsibilities:

- **Presentation layer:** welcome page, questions, progress indicators, and results.
- **Assessment configuration:** domain definitions, questions, response scales, and interpretation bands.
- **Scoring engine:** validated scoring calculations and classification logic.
- **Application backend:** assessment completion, persistence, and controlled result release where required.
- **Data layer:** storage of assessment configurations and responses, when persistence is enabled.
- **Visualisation layer:** radar chart and accessible score summaries.

The specific technology stack should be selected and documented before implementation.

8.2 Maintainability

Domain definitions and question content must be stored separately from presentation components.

Adding or editing a question should not require rewriting the scoring engine.

Changes to scoring rules must be versioned so that historical results, if retained, can be interpreted using the rules that were active when the assessment was completed.

8.3 Performance and responsiveness

- The assessment must work on desktop, tablet, and mobile screens.
- Question navigation and response selection should feel immediate.
- The results chart must remain readable on small screens.
- The application must provide clear loading, error, and recovery states where applicable.

8.4 Accessibility

- Controls must be usable by keyboard.
- Text must have sufficient contrast.
- Form controls must have accessible labels.
- Errors must be clearly communicated.
- The radar chart must have a text-based alternative.
- The interface must not rely on colour alone to communicate interpretation bands.

---

9. Testing and Quality Assurance

9.1 Scoring tests

Test that:

- The average of valid responses is calculated correctly.
- Scores remain within the defined scale.
- Missing responses prevent domain completion.
- Display rounding does not alter classification.
- Interpretation band boundaries are handled correctly.
- Every domain is scored independently.
- No overall life score is generated.

9.2 User-flow tests

Test that:

- The user can start the assessment.
- Required questions cannot be skipped.
- Answers persist during navigation.
- Completed domains do not reveal scores.
- Incomplete assessments cannot access final results.
- The final results page displays all required domains.
- The radar chart matches the calculated domain scores.

9.3 Security tests

Test that:

- Domain scores are not exposed through the interface or client-side state before release.
- Unauthorised users cannot retrieve another participant's results.
- Backend validation rejects invalid responses.
- Direct navigation cannot bypass completion requirements.

9.4 Assessment quality testing

Before the assessment is used for meaningful evaluation:

- Review the questions with relevant subject-matter experts.
- Conduct usability testing with representative participants.
- Check whether participants interpret the response scale consistently.
- Examine whether questions are relevant to the indicators they are intended to measure.
- Evaluate the scoring model and interpretation bands using pilot data.
- Revise ambiguous or redundant questions.

---

10. Success Metrics

The product owner should establish baseline values during the pilot.

Recommended measures include:

- Assessment start-to-completion rate.

- Question-level abandonment rate.
- Frequency of validation errors.
- Successful completion rate across devices.
- Participant understanding of the results.
- Perceived relevance and clarity of feedback.
- Completion time.
- Evidence of consistent interpretation of the response scale.

These metrics should be used to improve the experience and assessment quality, not to imply that the scoring model is scientifically validated merely because users complete it successfully.

---

11. Delivery Phases

Phase 1: Assessment specification

- Confirm the final domain list.
- Approve the response scale.
- Define indicators for each domain.
- Draft and review the question bank.
- Confirm scoring rules and interpretation bands.

Phase 2: Functional prototype

- Build the welcome page.
- Implement the Spirituality domain.
- Implement question navigation and progress indicators.
- Build and test the scoring engine.
- Ensure scores remain hidden before completion.

Phase 3: Complete assessment

- Add the remaining approved domains.
- Implement completion validation.
- Build the radar chart.
- Build domain-level score summaries and feedback.
- Test the full end-to-end experience.

Phase 4: Production readiness

- Implement the approved data-storage model.
- Enforce backend access controls.
- Complete accessibility and security testing.
- Pilot the assessment with representative users.
- Refine the questions, scoring, and feedback.
- Deploy the production application.

---

12. Key Decisions Requiring Approval

The following decisions must be resolved before the full application is built:

1. **Number of domains:** The current redesign specifies 12 paths. The earlier assessment framework contains 10 domains. Confirm the final number and names.
2. **Response scale:** Confirm whether to use 10 questions per domain with a 1–10 scale, or retain the earlier nine-statement YES/SOMETIMES/NO model.
3. **Assessment content:** Approve the indicators and questions for each domain before treating the results as meaningful measurements.
4. **Interpretation bands:** Approve the final category names, thresholds, and explanatory language.
5. **Data storage:** Decide whether assessments are anonymous and session-based or whether results must be saved and retrieved later.
6. **Administrative access:** Decide whether an administrator needs to review individual responses or aggregate assessment data.
7. **Feedback method:** Confirm whether the first version uses predefined feedback rules or AI-generated personalised feedback.
8. **Result export:** Decide whether users need to download, print, or share their results.

---

13. Definition of Done

The initial release is complete when:

- The user can start and finish the approved assessment.
- Every approved domain has its required questions.
- Required responses are validated.
- Scores are calculated correctly and independently for each domain.
- Scores remain hidden until all required domains are completed.
- The final radar chart accurately represents the domain scores.
- Every domain has a score, interpretation band, and relevant feedback.
- No overall life score is produced.
- The application works on mobile and desktop.
- Automated scoring tests pass.
- Privacy and access requirements are implemented for the selected deployment model.
- The assessment has undergone usability testing before being used for consequential personal evaluation.

Final product principle: The Wheel of Life should help users understand the patterns within their lives through structured reflection. Its scores are indicators for personal development, not definitive judgements of a person's life.