

```

2
3  int main()
4  {
5      char x = 1;
6      char y = 2;
7      if(x&y){
8          printf("Result of the x&y is 1");
9      }
10     if(x&& y){
11         printf("Result of the x&&y is 1");
12     }
13     return 0;
14 }

```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS

```

PS D:\VS Code> .\bitwise_and_logical_and.exe
Result of the x&&y is 1
PS D:\VS Code>

```

```

1  #include<stdio.h>
2
3  int main()
4  {
5      char x = 3; // 0000 0011
6      printf("%d", x << 1); // 0000 0110
7      return 0;
8  }

```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS

```

PS D:\VS Code> .\leftShift.exe
6
PS D:\VS Code>

```

```
C program.c > main()
1  #include<stdio.h>
2
3  int main()
4  {
5      char x = 6; // 0000 0110
6      printf("%d", x >> 1); // 0000 0011
7      return 0;
8  }
```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS

```
PS D:\VS Code> .\rightShift.exe
3
PS D:\VS Code> 
```

```
C program.c > main()
1  #include<stdio.h>
2
3  int main()
4  {
5      char x = 2; // 0000 0010
6      char y = 1; // 0000 0001
7      printf("%d ^ %d = %d", x, y, x^y); // 0000 0011
8      return 0;
9  }
```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS

```
PS D:\VS Code> .\xor.exe
2 ^ 1 = 3
PS D:\VS Code> 
```

```
program.c > main()
1  #include<stdio.h>
2
3  int main()
4  {
5      int a = 4; // 0000 0100
6      int b = 3; // 0000 0011
7      a = a ^ b; // 0000 0111
8      b = a ^ b; // 0000 0100
9      a = a ^ b; // 0000 0011
10     printf("After xOR, a = %d, b = %d\n", a, b);
11     return 0;
12 }
```

PROBLEMS

OUTPUT

DEBUG CONSOLE

TERMINAL

PORTS

```
PS D:\VS Code> gcc .\program.c -o xor
```

```
PS D:\VS Code> .\xor.exe
```

```
After xOR, a = 3, b = 4
```

```
PS D:\VS Code> 
```