Qzicl v2 Glossary

Qzicl specific

API	Application Programming Interface — structured set of endpoints used to interact with PM services
CI/CD	Continuous Integration / Continuous Deployment — automated build
CRUD	Basic operations of a persistent storage application: Create, Read, Update, and Delete
JWT	JSON Web Token — cryptographic token used for secure user authentication
MSW	Mock Service Worker — API mocking layer for local development and automated testing
QA	Quality Assurance — testing phase ensuring PM features function as intended
Quiz ID	Unique identifier assigned to each Quiz in the system
REST	Representational State Transfer — architectural style used in PM's web API
SPA	Single-Page Application — client architecture used for the PM front end
UI	User Interface — visual layer of the PM web or mobile client
UX	User Experience — overall usability and design quality of the PM platform

Front-end and JavaScript ecosystem

CSR	Client-Side Rendering — page rendering performed by the user's browser
DOM	Document Object Model — structured representation of web page elements accessible via JavaScript
ENV	Environment Variables — configuration mechanism for storing runtime settings
ESM	ECMAScript Modules — JavaScript module system using `import` and `export` syntax
Express	Minimal Node.js web framework used to build PM's REST API
JSON	JavaScript Object Notation — lightweight data format for structured communication
JSX	JavaScript XML — syntax extension combining HTML-like markup with JavaScript logic
Node.js	JavaScript runtime that executes code outside the browser
NPM	Node Package Manager — registry and toolchain for managing dependencies
SNHU	Southern New Hampshire University — the academic community where *Qzicl* originated
SSR	Server-Side Rendering — page rendering performed on the server before delivery
Vite	A modern frontend build tool that provides fast development server and optimized bundling
Vitest	A Vite-native testing framework.