Qzicl_v2.1_OpenAPI_Spec

Version: 2.1.0 · **OpenAPI:** 3.0.0 · **Base URL:** `https://{host}:{port}/api/v21`

Table of Contents

1. Endpoint Summary
2. Endpoint Details
    - General
        - `GET /` — GET method to say hello and return a list of available topic areas
        - `GET /hello` — (alias) GET method to say hello and return a list of available topic areas
        - `GET /topic` — GET method to retrieve the list of available quizzes for a specified topic
        - `GET /quiz` — GET method to select which quiz to take and obtain a sessionID to use for that quiz
        - `GET /go` — GET method to request the first question of a quiz
        - `POST /continue` — POST method to submit an answer to the current question and receive the next question or a quiz complete message, discriminated by status property in the response (new with api/v21)
        - `DELETE /exit` — DELETE method to exit the quiz, delete the sessionID's data, and end the session
3. Data Models (Schemas)

Endpoint Summary

Method	URL	Summary	Success
GET	`/`	GET method to say hello and return a list of available topic areas	200
GET	`/hello`	(alias) GET method to say hello and return a list of available topic areas	200
GET	`/topic`	GET method to retrieve the list of available quizzes for a specified topic	200
GET	`/quiz`	GET method to select which quiz to take and obtain a sessionID to use for that quiz	200
GET	`/go`	GET method to request the first question of a quiz	200
POST	`/continue`	POST method to submit an answer to the current question and receive the next question or a quiz complete message, discriminated by status property in the response (new with api/v21)	200
DELETE	`/exit`	DELETE method to exit the quiz, delete the sessionID's data, and end the session	204

Endpoint Details

General

`GET /`

GET method to say hello and return a list of available topic areas

- **HTTP method:** `GET`
- **URL:** `https://{host}:{port}/api/v21/`
- **Authentication:** none

Parameters

Name	In	Type	Required	Description
`qname`	query	string	Yes	The name of the quiz application (e.g., qzicl)

Responses

Status	Meaning
200	OK response with a list of available topic areas
400	Unknown or unsupported qname

200 — OK response with a list of available topic areas

Content type: `application/json`

Field	Type	Required	Notes
`topics`	array of string	Yes	

Example:

```
{
  "topics": [
    "string"
  ]
}
```

400 — Unknown or unsupported qname

Content type: `application/json`

Field	Type	Required	Notes
`errorCode`	string	Yes	Machine-readable error code.
`message`	string	Yes	Human-readable explanation of the error.

Example:

```
{
  "errorCode": "UNKNOWN_QNAME",
  "message": "Unknown or unsupported qname"
}
```

Example

Request:

```
curl -X GET "https://{host}:{port}/api/v21/?qname=string"
```

Response 200:

```
{
  "topics": [
    "string"
  ]
}
```

↑ Back to contents

GET /hello

(alias) GET method to say hello and return a list of available topic areas

- **HTTP method:** GET
- **URL:** https://{host}:{port}/api/v21/hello
- **Authentication:** none

Parameters

Name	In	Type	Required	Description
qname	query	string	Yes	The name of the quiz application (e.g., qzicl)

Responses

Status	Meaning
200	OK response with a list of available topic areas
400	Unknown or unsupported qname

200 — OK response with a list of available topic areas

Content type: application/json

Field	Type	Required	Notes
topics	array of string	Yes	

Example:

```
{
  "topics": [
    "string"
  ]
}
```

400 — Unknown or unsupported qname

Content type: application/json

Field	Type	Required	Notes
errorCode	string	Yes	Machine-readable error code.
message	string	Yes	Human-readable explanation of the error.

Example:

```
{
  "errorCode": "UNKNOWN_QNAME",
  "message": "Unknown or unsupported qname"
}
```

Example

Request:

```
curl -X GET "https://{host}:{port}/api/v21/hello?qname=qzicl"
```

Response 200:

```
{
  "topics": [
    "string"
  ]
}
```

↑ Back to contents

GET /topic

GET method to retrieve the list of available quizzes for a specified topic

- **HTTP method:** GET
- **URL:** https://{host}:{port}/api/v21/topic
- **Authentication:** none

Parameters

Name	In	Type	Required	Description
topic_id	query	string	Yes	

Responses

Status	Meaning
200	OK response with a list of available quizzes for the specified topic
404	Unknown topic_id

200 — OK response with a list of available quizzes for the specified topic

Content type: `application/json`

Field	Type	Required	Notes
`quizzes`	array of string	No	

Example:

```
{
  "quizzes": [
    "string"
  ]
}
```

404 — Unknown topic_id

Content type: `application/json`

Field	Type	Required	Notes
`error`	string	No	

Example:

```
{
  "error": "Unknown topic_id"
}
```

Example

Request:

```
curl -X GET "https://{host}:{port}/api/v21/topic?topic_id=Mathematics"
```

Response 200:

```
{
  "quizzes": [
    "string"
  ]
}
```

↑ Back to contents

`GET` /quiz

GET method to select which quiz to take and obtain a sessionID to use for that quiz

- **HTTP method:** `GET`
- **URL:** `https://{host}:{port}/api/v21/quiz`
- **Authentication:** none

Parameters

Name	In	Type	Required	Description
`quiz_id`	query	string	Yes	

Responses

Status	Meaning
200	Quiz selected, return sessionID to use for that quiz
400	missing parameter, wrong type, inconsistent combination
404	Invalid quiz selection

200 — Quiz selected, return sessionID to use for that quiz

Content type: `application/json`

Field	Type	Required	Notes
`sessionID`	string	No	

Example:

```
{
  "sessionID": "20261015-00001"
}
```

400 — missing parameter, wrong type, inconsistent combination

Content type: `application/json`

Field	Type	Required	Notes
`error`	string	No	

Example:

```
{
  "error": "Missing or incorrect quiz type"
}
```

404 — Invalid quiz selection

Content type: `application/json`

Field	Type	Required	Notes
`errorCode`	string	Yes	Machine-readable error code.
`message`	string	Yes	Human-readable explanation of the error.

Example:

```
{
  "errorCode": "INVALID_QUIZ_SELECTION",
  "message": "Invalid quiz selection"
}
```

Example

Request:

```
curl -X GET "https://{host}:{port}/api/v21/quiz?quiz_id=Calculus"
```

Response 200:

```
{
  "sessionID": "20261015-00001"
}
```

↑ Back to contents

GET /go

GET method to request the first question of a quiz

Includes the assigned sessionID to request the first question

- **HTTP method:** `GET`
- **URL:** `https://{host}:{port}/api/v21/go`
- **Authentication:** none

Parameters

Name	In	Type	Required	Description
sessionID	query	string	Yes	

Responses

Status	Meaning
200	Successful response with first question and multiple-choice answers
400	Invalid or inconsistent session/question/answer information
404	Invalid session information

200 — Successful response with first question and multiple-choice answers

Content type: `application/json`

Field	Type	Required	Notes
question	string	No	
choiceIndices	array of integer	No	
choiceTexts	array of string	No	

Example:

```
{
  "question": "string",
  "choiceIndices": [
    1
  ],
  "choiceTexts": [
    "string"
  ]
}
```

400 — Invalid or inconsistent session/question/answer information

Content type: `application/json`

Field	Type	Required	Notes
errorCode	string	Yes	Machine-readable error code.
message	string	Yes	Human-readable explanation of the error.

Example:

```
{
  "errorCode": "NOEXIST_SESSION_ID",
  "message": "The specified sessionID does not exist."
}
```

404 — Invalid session information

Content type: `application/json`

Field	Type	Required	Notes
`errorCode`	string	Yes	Machine-readable error code.
`message`	string	Yes	Human-readable explanation of the error.

Example:

```
{
  "errorCode": "SESSION_TIMED_OUT",
  "message": "The session has timed out due to inactivity."
}
```

Example

Request:

```
curl -X GET "https://{host}:{port}/api/v21/go?sessionID=20261015-00001"
```

Response 200:

```
{
  "question": "string",
  "choiceIndices": [
    1
  ],
  "choiceTexts": [
    "string"
  ]
}
```

↑ Back to contents

POST /continue

POST method to submit an answer to the current question and receive the next question or a quiz complete message, discriminated by status property in the response (new with api/v21)

- **HTTP method:** `POST`
- **URL:** `https://{host}:{port}/api/v21/continue`
- **Authentication:** none

Parameters

None.

Request Body (optional)

Content type: `application/json`

Field	Type	Required	Notes
`sessionID`	string	Yes	The sessionID obtained from the quiz selection step
`questionID`	string	Yes	The ID of the current question being answered
`choiceIndex`	integer	Yes	The indices (range 1..n) of the choices being submitted for the current question

Example:

```
{
  "sessionID": "20261015-00001",
  "questionID": "Q1",
  "choiceIndex": 2
}
```

Responses

Status	Meaning
200	Answer accepted, return next question or quiz complete message
400	Missing session/question/answer information
404	session expired or does not exist

200 — Answer accepted, return next question or quiz complete message

Content type: `application/json`

Type: `one of: continue | exit`

Example:

```
[
  {
    "status": "in_progress",
    "question": "What is the airspeed velocity of an unladen swallow?",
    "choiceIndices": [
      1,
      2,
      3,
      4
    ],
    "choiceTexts": [
      "An African or European swallow?",
      "I don't know that!",
      "Winter or Summer?",
      "Morning or Evening?"
    ]
  }
]
```

400 — Missing session/question/answer information

Content type: `application/json`

Field	Type	Required	Notes
`errorCode`	string	Yes	Machine-readable error code.
`message`	string	Yes	Human-readable explanation of the error.

Example:

```
{
  "errorCode": "MISSING_INFORMATION",
  "message": "Missing session/question/Answer information"
}
```

404 — session expired or does not exist

Content type: `application/json`

Field	Type	Required	Notes
`errorCode`	string	Yes	Machine-readable error code.
`message`	string	Yes	Human-readable explanation of the error.

Example:

```
{
  "errorCode": "SESSION_TIMED_OUT",
  "message": "The session has timed out due to inactivity."
}
```

Example

Request:

```
curl -X POST "https://{host}:{port}/api/v21/continue" \
  -H "Content-Type: application/json" \
  -d '{"sessionID":"20261015-00001","questionID":"Q1","choiceIndex":2}'
```

Response 200:

```
[
  {
    "status": "in_progress",
    "question": "What is the airspeed velocity of an unladen swallow?",
    "choiceIndices": [
      1,
      2,
      3,
      4
    ],
    "choiceTexts": [
      "An African or European swallow?",
      "I don't know that!",
      "Winter or Summer?",
      "Morning or Evening?"
    ]
  }
]
```

↑ Back to contents

DELETE /exit

DELETE method to exit the quiz, delete the sessionID's data, and end the session

- **HTTP method:** DELETE
- **URL:** https://{host}:{port}/api/v21/exit
- **Authentication:** none

Parameters

Name	In	Type	Required	Description
sessionID	query	string	Yes	

Responses

Status	Meaning
204	Session successfully terminated, no content returned
400	Missing sessionID
404	Invalid sessionID

204 — Session successfully terminated, no content returned

No response body.

400 — Missing sessionID

Content type: application/json

Field	Type	Required	Notes
errorCode	string	Yes	Machine-readable error code.
message	string	Yes	Human-readable explanation of the error.

Example:

```
{
  "errorCode": "MISSING_SESSIONID",
  "message": "Missing sessionID information"
}
```

404 — Invalid sessionID

Content type: application/json

Field	Type	Required	Notes
errorCode	string	Yes	Machine-readable error code.
message	string	Yes	Human-readable explanation of the error.

Example:

```
{
  "errorCode": "INVALID_SESSION_ID",
  "message": "The specified sessionID does not exist."
}
```

Example

Request:

```
curl -X DELETE "https://{host}:{port}/api/v21/exit?sessionID=string"
```

Response 204:

(empty body)

↑ Back to contents

Data Models (Schemas)

exit

Field	Type	Required	Notes
status	string	No	

Example:

```
{
  "status": "complete"
}
```

continue

Field	Type	Required	Notes
`status`	string	Yes	
`question`	string	Yes	
`choiceIndices`	array of integer	Yes	
`choiceTexts`	array of string	Yes	

Example:

```
[
  {
    "status": "in_progress",
    "question": "What is the airspeed velocity of an unladen swallow?",
    "choiceIndices": [
      1,
      2,
      3,
      4
    ],
    "choiceTexts": [
      "An African or European swallow?",
      "I don't know that!",
      "Winter or Summer?",
      "Morning or Evening?"
    ]
  }
]
```

HelloResponse

Field	Type	Required	Notes
`topics`	array of string	Yes	

Example:

```
{
  "topics": [
    "string"
  ]
}
```

ErrorResponse

Field	Type	Required	Notes
`errorCode`	string	Yes	Machine-readable error code.
`message`	string	Yes	Human-readable explanation of the error.

Example:

```
{
  "errorCode": "INVALID_SESSION_ID",
  "message": "The specified sessionID does not exist."
}
```