

[illegible]

Signed by AMCO [Signature] Date 19-5-92

Signed by Client A. H. H. H. H. H. Date 20.5.92

	MATERIALS DELIVERED		A + B	(A + B) — C
	A	B		
	Since Contract Commenced (brought forward from previous sheet)	During Day		
CEMENT			Running Total	Stock on site at end of day.
SAND				
FLY/ASH				
CHEMICAL				

NO CLAIMS CAN BE ACCEPTED UNLESS REPORTED IN WRITING WITHIN 14 DAYS OF THE DATE OF THIS RETURN

**CLIENT'S COPY**

SK46SE/102-103



# RECORD OF BOREHOLE NO. H590A

Ground level : 378.6ft. above O.D. Newlyn (31.7.63)

Dia. of boring : 8in.

Type of boring : Post-hole Auger

Lining tubes : Not used

Daily Progress	Core Recovery or Samples		Change of Strata			Description of Strata	COAL MEASURES
	Depth	Percentage or Type	Legend	Depth	O.D. Level		
28.9.63	2'6" - 4'0"	U(4)		1'6"	377.2	TOPSOIL	
	4'0" - 5'0"	D		4'0"	374.6	Firm mottled gray and brown silty CLAY with fragments of brown sandstone	
				5'0"	373.6	Brown SANDSTONE	
<div>Key to type of sample : U (4) — 4 in. dia. undisturbed sample. U (1 1/2) — 1 1/2 in. dia. " " D — disturbed sample. BD — bulk disturbed sample. W — water sample. S { } — standard penetration test. C { } — dynamic cone penetration test. No. in brackets gives No. of blows/12 in. penetration.</div> <div>Remarks : (Observations on ground-water, etc.) Ground-water was first encountered at depth of 4ft. below ground level and rose to depth of 3ft.</div>							
MINISTRY OF TRANSPORT LONDON-YORKSHIRE MOTORWAY TROWELL TO BARLBOROUGH SECTION						Soils No : S/3547 FIG.213	

GEORGE WIMPEY & CO., LTD.

CENTRAL LABORATORY

HAYES



# RECORD OF BOREHOLE NO. 11550

Ground level : 378.1ft. above O.D. Newlyn (31.7.63)

Dia. of boring : 8in.

Type of boring : Post-hole Auger

Lining tubes : Not used

Daily Progress	Core Recovery or Samples		Change of Strata			Description of Strata	COAL MEASURES
	Depth	Percentage of Type	Legend	Depth	O.D. Level		
28.3.63	3'6" - 5'0"	U(4) D		3'6"	378.6	TOPSOIL	
	5'0" - 6'0"			5'0"	379.1	Soft gray very silty CLAY and fragments of silty SHALE	
				6'0"	372.1	Weathered grey-brown silty SHALE	
<div>Key to type of sample : U (4) — 4 in. dia. undisturbed sample. U (1½) — 1½ in. dia. " " D — disturbed sample. BD — bulk disturbed sample. W — water sample. S ( ) — standard penetration test. C ( ) — dynamic cone penetration test. No. in brackets gives No. of blows/12 in. penetration.</div> <div>Remarks : (Observations on ground-water, etc.) No ground-water was encountered during boring.</div>							
MINISTRY OF TRANSPORT LONDON-YORKSHIRE MOTORWAY TROWELL TO BARLBOROUGH SECTION						Soils No : S/3547 FIG.214	

GEORGE WIMPEY & CO., LTD.

CENTRAL LABORATORY

HAYES

## RECORD OF BÖREHOLE NO. 590C

Ground level: ..... 37.0ft. above O.B. Newlyn (24.63.)

Type of boring: ..... Shell and Auger and Rotary Core Drilling

Dis. of boring: ..... 8in. to 13ft., BX (13in. core) to 20ft.

Lining tubes: ..... 8in. to 9ft., BX (9in.) to 15ft.

[illegible]

GEORGE WIMPEY & CO., LTD.

CENTRAL LABORATORY

HAYES