



200 115
100
50
0
Bore
hole
depth
m
mpson

FORAKY LIMITED SK46SW/15

COLWICK, NOTTINGHAM. TEL: NOTTINGHAM 246331.

REPORT ON BOREHOLE No. W262

TYPE OF BORING: Rotary
DIAMETER: 6" 8"
INCLINATION AND BEARING: Vertical
LOCATION: 444,978.38; 361,774.1N
GROUND LEVEL: 530.23 SK46SW/43

Progress Date/Time	Core Recovery		Lining Tube	Water	Strike Log		Description Of Strata	
	Depth	Percentage of Type			Legend	Depth		
12.11.64	Open hole 5' 0"	-				5' 0" 525.2		
	6' 8"	100%		6' 6"		6' 9" 523.4	Sandstone	100%
	9' 4"	100%					Sandstone with clay bands	100%
	13' 10"	100%				13' 0" 517.2		
	17' 11"	100%						
	21' 6"	100%						
	25' 6"	100%					Grey mudstone with occasional ironstone bands	100%
	31' 6"	100%				30' 0" 500.2	Coal	100%
	36' 6"	100%				33' 9" 496.4	Seatearth	
	41' 0"	100%				34' 6" 495.7	Grey mudstone with occasional ironstone bands	100%
13.11.64	43' 9"	100%	15' 7"	31' 0"		41' 0" 489.2	Grey mudstone	
	48' 7"	100%				42' 0" 486.2	Grey sandstone	
	51' 0"	100%				43' 6" 484.2	Grey mudstone	100%
	55' 6"	89%				44' 2" 483.7	Black mudstone	
						46' 8" 483.4	Grey mudstone occasional ironstone bands	100%
						55' 6" 474.7		

KEY:

Symbols are in accordance with
GS 2001.

WATER STRIKE ———
WATER RISE LEVEL ———
WATER LOST ———

TESTS:

RII

REMARKS:

CONTRACT: LONDON - YORKSHIRE MOTORWAY

CONTRACT: LYM/WH-2, SEE INVESTIGATION - MINING
WINTON - BARLEBOROUGH SECTION

CLIENT: MINISTRY OF TRANSPORT. CONSULTING ENGINEERS: SIR OWEN WILLIAMS & PARTNERS.

JOB
NO
D240