
 British Geological Survey NATURAL ENVIRONMENT RESEARCH COUNCIL						Site Nottinghamshire/ Derbyshire COA NMCS2 Upgrade			Borehole Number M47	
Machine: Flush : Core Dia: mm Method :		Casing Diameter		Ground Level (mOD) 160.65		Client Highways Agency		Job Number F11451		
		Location 445011.23 E 361733.3 N		Dates 01/09/1999-02/09/1999		Engineer WSP Environmental Ltd		Sheet 1/2		
Depth (m)	TCR	SCR	RQD	FI	Field Records	Level (mOD)	Depth (m) (Thickness)	Description	Legend	Water
0.00-0.30					D01 0 blows		(0.30)	TOPSOIL.		
0.30-0.70	40	0	0	98	D02 0 blows	160.35	0.30	MADE GROUND: Dark grey and brown very sandy clay with much fine and medium angular and subangular gravel sized fragments of coal, slag, glass, sandstone, mudstone and quartz.		
0.70							(1.40)			
	0	0	0	97						
1.70-2.15					2,4/4,4,4,5 SPT N=17	158.95	1.70	No recovery. Grey silty weathered MUDSTONE. (Driller's description) (Coal Measures)		
2.15							(1.00)			
2.70-3.15	100	0	0	98	3,4/4,5,8,11 SPT N=28	157.95	2.70	Light grey slightly sandy CLAY with much fine to coarse angular and subangular mudstone lithorelicts. (Completely Weathered Mudstone) (Coal Measures)		
3.15							(1.52)			
	100	68	51	98						
					4,21/30,20,0,0 01/09/1999:0.00m					
3.97			0	3						
3.70-3.97					02/09/1999: SPT 50/121	156.43	4.22	Light grey thinly laminated subhorizontal thinly and thickly bedded subhorizontal slightly weathered fine grained SANDSTONE moderately weak to moderately strong locally strong with closely and medium spaced subhorizontal fractures open rough planar. (Coal Measures)		
4.11	95	87	77	0						
4.70			0	4						
5.05							(1.93)			
			0	14						
6.05										
6.20	100	75	26	0		154.50	6.15	Light grey thinly laminated subhorizontal very thinly and thinly bedded subhorizontal slightly weathered SILTSTONE, weak and moderately weak with very closely and closely spaced subhorizontal fractures open smooth undulose and planar. (Coal Measures) ---below 6.00m locally with strong interbeds of sandstone/sandy siltstone		
7.05			0	99			(2.18)			
7.55	91	32	0	8						
7.70			0	98						
8.33	57	6	0	0		152.32	8.33	Soft grey sandy CLAY with much fine to coarse angular and subangular gravel of mudstone. (Workings?) (Coal Measures)		
9.20							(2.00)			
			0	99						
Remarks 1. Inspection pit excavated to 0.70m. 2. Borehole complete at 15.00m. 3. Borehole installed with 50mm gas pipe at 15.00m. 4. Marker PostRef 223/0 S.								Scale (approx) 1:50	Logged By NBR	
								Figure No.		

 British Geological Survey NATURAL ENVIRONMENT RESEARCH COUNCIL						Site Nottinghamshire/ Derbyshire COA NMCS2 Upgrade		Borehole Number M47			
Machine: Flush : Core Dia: mm Method :			Casing Diameter			Ground Level (mOD) 160.65		Client Highways Agency		Job Number F11451	
			Location 445011.23 E 361733.3 N			Dates 01/09/1999-02/09/1999		Engineer WSP Environmental Ltd		Sheet 2/2	
Depth (m)	TCR	SCR	RQD	FI	Field Records	Level (mOD)	Depth (m) (Thickness)	Description	Legend	Water	
10.35			0	98		150.32	10.33				
10.40			0			150.25	10.40	Black highly weathered COAL, very weak with extremely closely spaced subhorizontal and subvertical fractures tight smooth planar. (Coal Measures)			
10.60	98	77	41	0							
10.70											
			0	98			(1.15)	Light grey thinly and medium bedded subhorizontal highly weathered fossiliferous SILTSTONE, weak with medium and closely spaced subhorizontal fractures open rough irregular. (Seatearth) (Coal Measures)			
11.35			0	7				---from 11.35m completely weathered			
11.55						149.10	11.55	Grey thinly cross laminated subhorizontal thinly and very thinly bedded subhorizontal slightly weathered fine and medium grained SANDSTONE, weak and moderately weak with very closely and closely spaced subhorizontal fractures open rough planar and medium spaced inclined fractures open rough planar iron stained. (Coal Measures)			
	85	58	35	0							
12.20			0	11							
12.50							(2.05)				
			0	25				---from 12.80m with medium spaced subhorizontal fractures open clay infilled			
13.60	100	18	0	0		147.05	13.60	Grey thinly laminated inclined highly weathered MUDSTONE, very weak and weak with extremely closely spaced random fractures open smooth irregular. (Coal Measures)			
13.70			0	3			(1.40)				
14.60			0	99				---from 14.60m fractures become very closely spaced open inclined rough irregular			
14.90								---from 14.90m non intact			
					02/09/1999: 8.35m	145.65	15.00	Complete at 15.00m			
					02/09/1999:						
Remarks											